

APP CRS	Rwy Idg	9003
280°	TDZE	413
	Apt Elev	421

RNAV (RNP) Y RWY 28

SYRACUSE HANCOCK INTL (SYR)

RNP AR APCH.

▼

For uncompensated Baro-VNAV systems, procedure NA below -18°C or above 54°C. For inop ALS, increase RNP 0.15 all Cats visibility to 1½. For inop ALS, increase RNP 0.30 all Cats visibility to 1%.

ALSF-2

ⓘ

MISSED APPROACH: Climb to 3000 on track 280° to MOYIK and on track 306° to WIFFY and hold.

ATIS	SYRACUSE APP CON	SYRACUSE TOWER	GND CON	CLNC DEL
124.225	126.125 269.125	120.3 239.0	121.7 348.6	125.05 257.775

MISSED APCH FIX

6 NM

281°

101°

WIFFY

ELEV 421

D

TDZE 413

TDZ/CL Rwy 28

HIRL Rwys 10-28 and 15-33

3000

MOYIK

tr 280°

306°

WIFFY

tr 306°

See planview for multiple IF locations.

ZIMBI

1600

RW28

280°

1600

GP 3.00°

TCH 60

3.6 NM

CATEGORY	A	B	C	D
RNP 0.15 DA		862/55	449 (500-1)	
RNP 0.30 DA		957-1½	544 (600-1½)	

AUTHORIZATION REQUIRED

SYRACUSE, NEW YORK

Orig-B 16JUL20

43°07'N-76°06'W

SYRACUSE HANCOCK INTL (SYR)

RNAV (RNP) Y RWY 28