hdg 265°

CATEGORY

S-ILS 27R

S-LOC 27R

SIDESTEP 27L

275° 5.2 NM

from FAF

R-165

2.5

.2 NM -4 NM

31.3

OSTRR

ATL 6.6

RADAR

2700

AL-26 (FAA)

Rwy 27R

MALS

 (A_4)

Rwy 27L

ALSF-2

(Å)

27R **11690**

985

1026

Rwy Idg

Apt Elev

Simultaneous approach authorized. Inop table does not apply to S-ILS 27R all Cats. For inop ALS, increase S-LOC 27R Cats

TDŹE

APP CRS

275°

RADAR required for procedure entry

A and B visibility to RVR 5500 ATLANTA

27L **8865**

999

1026

ATLANTA TOWER

ATLANTA, GEORGIA Amdt 7 12AUG21

60

FAF to MAP 5.2 NM 90 120 150 180

> 3:28 2:36 2:05

HIRL all Rwys TDZ/CL Rwys 8L, 9R 10, 26R, 27L and 28

Min:Sec 5:12

Knots

ATLANTA, GEORGIA

DME or RADAR required.

LOC I-AFA

111.3

27 JAN 2022

ō

24 FEB

3 2022

MAASN

MRCER.

ATL [11.6]

RADAR

2700

В

435 (400-34)

1420/55

1185/40

4000

-3.8 NM

421 (400-1)

ATL 15.3 RADAR

5000

200 (200-3/4)

1420/50

MMCAP RADAR ATL 18.8

275°-

435 (400-1)

1420-11/2

421 (400-11/2)

6000

7000

GS 3.00°

RADAR

3.5 NM - - 3.5 NM

1420/40

21224

ALL

RWYS

CPDLC

ILS or LOC RWY 27R

MISSED APPROACH: Climb to 1500

then climbing left turn to 4000 on heading 265° and RMG VORTAC

GND CON

R-165 to DUTIE/RMG 31.3

DME/RADAR and hold.

HARTSFIELD-JACKSON ATLANTA INTL (ATL)