NC-3, 27 JAN 2022 to 24 FEB 2022

ST. LOUIS, MISSO	DURI	AL-3	AL-360 (FAA)			21336
	P CRS Rwy ldg TDZE Apt Elev	7603 534 618	R		GPS) RW LAMBERT INTL	
For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -16°C (4°F) or above 54°C (130°F). Rwy 24 helicopter visibility reduction below ¾ SM NA. DME/DME RNP-0.3 NA. For inop ALS, increase LNAV/VNAV all Cats visibility to 1% and LNAV Cats C, D and E visibility to 1%. MISSED APPROACH: Clim to 3000 direct SORUE and on track 294° to AUGST and hold.						
D-ATIS 125.025 379.925	ST. LOUIS APP CO		GND CON 121.9 348.6 (Inbou 121.65 377.175 (118.925 227.125	und) Outbound)	CLNC DEL 119.5 363.1	CPDLC
MISSED APCH FIX 083° ► △ AUGST (230K)						
2949 1200 SORU	ennannannannannannannannannannannannanna	WITUN 793 A 2.4 NM t RW24 RW24 RW24 A 897 A 875 A 1017	A 787 Procee	dure NA for arr AC airway radi	3500 1/2,3/2 ival on TOY iols 189 CW 006.	(IAF) TROY TOY
		1649 Å Å16	549	ELEV 618	TDZE	534
*LNAV only *LNAV only CATEGORY LPV DA LNAV/ DA	WITUN 2.4 NM to RW24 RW24	2200 240* 2200 7 NM - 6.1 NM - C 734/40 200 (200-34) 931/50 397 (400-1)		658	Rwy 6-24 766 Rwy 11-29 900 Rwy 12L-30R 90 Rwy 12R-30L 110: 681 244° to RW24 A A A A A A A A A A A A A A A A A A A	00 X 150 13 X 150 20 X 200
LNAV MDA	1080/40 546 (50	D-¾) 1080-1¾	₃ 546 (500-1 ³ %)	HIRL all Rwys TDZ/CL Rwys	11, 12L, 12R, 29,	and 30R

ST. LOUIS, MISSOURI Amdt 1C 17AUG17

ST LOUIS LAMBERT INTL (STL)
RNAV (GPS) RWY 24