






APP CRS	Rwy Idg	10819
303°	TDZE	583
	Apt Elev	618

RNAV (RNP) Z RWY 30L

ST LOUIS LAMBERT INTL (STL)

RNP AR APCH.				MALSR		MISSED APPROACH: Climb to 3000 direct TUDNE and hold, continue climb-in-hold to 3000.	
▼ Use of FD or AP required during simultaneous operations. Simultaneous approach authorized with Rwy 29, except for arrivals at JYAAR and PEJAA. For uncompensated Baro-VNAV systems, procedure NA below -18°C or above 54°C. For inop ALS, increase RNP 0.15 all Cats visibility to RVR 5500 and RNP 0.30 all Cats visibility to RVR 6000.							
D-ATIS 125.025 379.925	ST. LOUIS APP CON 132.125 360.6	ST. LOUIS TOWER 118.5 257.7	GND CON 121.9 348.6 (Inbound) 121.65 377.175 (Outbound) 118.925 227.125 (Rwy 11/29)		CLNC DEL 119.5 363.1	CPDLC	



3000	TUDNE	See planview for multiple IF locations.			SAYIT
					2200
		303°		2200	
		4.9 NM		GP 3.00° TCH 58	
CATEGORY	A	B	C	D	
RNP 0.15 DA	947/35 364 (400-5%)				
RNP 0.30 DA	998/40 415 (400-3/4)				
AUTHORIZATION REQUIRED					

ELEV 618 TDZE 583

Rwy 6-24 7603 X 150
Rwy 11-29 9000 X 150
Rwy 12L-30R 9013 X 150
Rwy 12R-30L 11020 X 200

HIRL all Rwys
TDZ/CL Rwys 11, 12L, 12R, 29, and 30R