



WAAS CH 40007 W20A	APP CRS 197°	Rwy Idg 7001 TDZE -1 Apt Elev 4
--	------------------------	--

RNAV (GPS) Y RWY 20
LOUIS ARMSTRONG NEW ORLEANS INTL (MSY)

RNP APCH - GPS. ▼ Rwy 20 helicopter visibility reduction below RVR 4000 NA. Inop table does not apply to LPV all Cats. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -1°C or above 54°C. For inop ALS, increase LNAV Cat C/D visibility to 1½ SM.	MALS (A4)	MISSED APPROACH: Climb to 2000 direct POLIY and on track 109° to SAFES and hold.
--	--------------	---

D-ATIS 127.55	NEW ORLEANS APP CON WEST 125.5 350.35 EAST 133.15 290.3	NEW ORLEANS TOWER 119.5 254.3	GND CON 121.9 273.525	CLNC DEL 120.925	CPDLC
-------------------------	---	---	---------------------------------	----------------------------	-------



2000	POLIY	tr 109°	SAFES	RAYOP
1.3 NM to RWY 20	1.3 NM	4.8 NM	7 NM	GP 3.00° TCH 52
CATEGORY	A	B	C	D
LPV DA		249/40	250 (300-¾)	
LNAV/VNAV DA		325/40	326 (400-¾)	
LNAV MDA	460/40	461 (500-¾)	460/55	461 (500-1)
CIRCLING	520-1	516 (600-1)	580-1½ 576 (600-1½)	600-2 596 (600-2)

SC-4, 27 JAN 2022 to 24 FEB 2022

SC-4, 27 JAN 2022 to 24 FEB 2022