SC-2, 27 JAN 2022 to 24 FEB 2022

8310 Rwy Idg TDZE APP CRS 478 487 133° Apt Elev

RNAV (RNP) W RWY 13R DALLAS LOVE FLD (DAL)

7 (5) 2.57 401				D/ (LD (0 LO	VETED (DILL)	
For uncompensated Baro-VNAV systems, procedure NA below -5°C (23°F) or above 54°C (130°F). Simultaneous approach authorized. RF required. GPS required. Use of FD or AP providing RNAV track guidance required during simultaneous operations.			300	MISSED APPROACH: Climb to 3000 direct ENAVE and on track 151° to TACKE and hold.		
D-ATIS REGIONAL APP CON NORTH 124.3 282.275 SOUTH 125.2 343.65	LOVE TOWER 123.7 239.3	GND C		CLNC DEL 127.9	CPDLC	
2000 226° (0.6) HEXOV HEXOV A 1249 WUPAG 2100 (1.1) WUPAG 210K (IF) WUPAG 210K (IF) NOKME 4000 230K (RNP 0.30) A 1048 A 914						
RW13R [€] \$	11.11.	∧ 885				
***************************************				MISSED APCH FIX		
RADAR REQUIRED				TACKE A NM		
∧ 920	1368 ⚠	ENAVE 1049/	ELEV	487 D	TDZE 478	
<u>∧</u> 104			133 RW			
VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 52).	3000 ENAVE	tr 51° △	1 /	€\ \$\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\		
HEXOV	See planview for mul	tiolo IE locatio			*	
	JAPT 600 WUREM 1250	RW13R	100	TV B	VR VR 42 ¢	
GP 3.00° TCH 48 - 0.6 NM - 1.7 NM CATEGORY A B	133°	······································	_	A PARTY OF THE PAR	(3) M (4) (4) (4) (4) (4) (4) (4) (4) (4) (4)	
RNP 0.20 DA 781					<i>⊸</i>	
RNP 0.25 DA 833 RNP 0.30 DA 929						
AUTHORIZATION REQUIRED				CL Rwys 13L and Rwys 13L-31R, c		

DALLAS, TEXAS Orig-C 31MAR16