

WAAS
CH **65605**
W02A

APP CRS
022°

Rwy Idg
TDZE
Apt Elev
7100
683
683

RNP APCH.

⚠

Circling Rwy 15, 33 NA at night. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -16°C or above 54°C. For inop ALS, increase LNAV/VNAV all Cats visibility to 1½ SM. ** RVR 1800 authorized with use of FD or AP or HUD to DA.

MALSR

AS

MISSED APPROACH:
Climb to 3800 direct
HETIP and hold.

ATIS 119.85	CHATTANOOGA APP CON ★ 125.1 379.1	CHATTANOOGA TOWER ★ 118.3 (CTAF) 257.8	GND CON 121.7 348.6	CLNC DEL 120.95 348.6	UNICOM 122.95
-----------------------	---	--	-------------------------------	---------------------------------	-------------------------

CATEGORY	A	B	C	D
LPV DA**	883/24	200 (200-½)		
LNAV/VNAV DA	1197/60	514 (600-1¼)		
LNAV MDA	1200/24	517 (600-½)	1200/55 517 (600-1)	1200/60 517 (600-1¼)
CIRCLING	1300-1 617 (700-1)	1340-1 657 (700-1)	1480-2¼ 797 (800-2¼)	1580-3 897 (900-3)

CHATTANOOGA, TENNESSEE

Amdt 1A 03JAN19

35°02'N-85°12'W

LOVELL FLD (CHA)

RNAV (GPS) RWY 2