

DAYTON, OHIO

ILS or LOC RWY 23R

LOC I-FFO
109.7

APCH CRS
233°

Rwy Idg **12,600**
THRE **823**
Arpt Elev **823**

AL-108 [USAF]

WRIGHT-PATTERSON AFB (KFFO)

DME or RADAR required for Localizer.

ALSIF-1

† MISSED APPROACH: Climb via FFO R-233 to 2000, at 3 DME turn left direct CLACK to 3000 and hold.

ATIS
124.475 269.9

COLUMBUS APP CON
118.85 269.275

PATTERSON TOWER
126.9 281.45

GND CON
121.8 335.8

*** When Rwy 23R VGSI inop, circling to Rwy 23R NA at night.

† Missed approach requires use of RNAV or ATC radar monitoring.

EMERG SAFE ALT 100 NM 3700

2000 FFO R-233

AKATE FFO 3

3000

VGSI and ILS glidepath not coincident (VGSI Angle 3.00/TCH 53).

CLACK R-100

LOOMP R-052

ANNEE RADAR 5.7

GENIE 2.1

TACAN

ANNEE to RW23R GS 3.00° TCH 50

CATEGORY	A	B	C	D	E
S-ILS 23R *	1023/24		200	(200-½)	
S-LOC 23R **	1320/24 497 (500-½)		1320/50 497 (500-1)		
*** CIRCLING	1380-1	1440-1	1560-2	1620-2½	1620-2¾
	557 (600-1)	617 (600-1)	737 (800-2)	797 (800-2½)	797 (800-2¾)

DAYTON, OHIO
Amdt 7 09SEP21

39° 50'N-84° 03'W

WRIGHT-PATTERSON AFB (KFFO)

ELEV 823

THRE 823

EC-2, 27 JAN 2022 to 24 FEB 2022

EC-2, 27 JAN 2022 to 24 FEB 2022

ILS or LOC RWY 23R