

APP CRS	Rwy Idg	9500
191°	TDZE	995
	Apt Elev	1027

RNAV (RNP) Z RWY 19L

KANSAS CITY INTL (MCI)

RADAR required for procedure entry. RNP AR APCH-GPS.


▼

For uncompensated Baro-VNAV systems, procedure NA below -20°C or above 54°C. Simultaneous approach authorized with Rwy 19R, except for arrivals at NOAHS, FARMS, BUKKS, and SLABB. For inop ALS, increase RNP 0.20 all Cats visibility to RVR 4500 and RNP 0.30 all Cats visibility to RVR 5500.

MALSR

MISSED APPROACH: Climb to 1500 then climbing left turn to 4000 direct ANX VORTAC and hold.

D-ATIS	KANSAS CITY APP CON	INTERNATIONAL TOWER	GND CON	CLNC DEL	CPDLC
128.375	120.95 318.1	128.2 254.25	121.8	135.7	



1500 4000 ANX

RW19L

191°

2300

GP 3.00° TCH 59

See planview for multiple IF locations.

4 NM

CATEGORY	A	B	C	D
RNP 0.20 DA		1306/24	311 (300-½)	
RNP 0.30 DA		1361/35	366 (400-¾)	

AUTHORIZATION REQUIRED

