

WAAS CH 97322 W27A	APP CRS 268°	Rwy Idg TDZE Apt Elev	9912 10 36
--	------------------------	-----------------------------	---------------------------------------

RNAV (GPS) RWY 27L

PHILADELPHIA INTL (PHL)

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -12°C (11°F) or above 54°C (130°F). Simultaneous approach authorized. Use of FD or AP providing RNAV track guidance required during simultaneous operations. LNAV procedure NA during simultaneous operations. DME/DME RNP-0.3 NA. For inoperative ALS, increase LNAV/VNAV all Cats visibility to RVR 6000.

MALSR

MISSED APPROACH: Climb to 1500 then climbing left turn to 3000 direct OOD VORTAC and hold.

D-ATIS ARR 133.4 DEP 135.925	PHILADELPHIA APP CON 124.35 319.15	PHILADELPHIA TOWER 118.5 327.05 (Rwys 9L/27R, 8/26 and 17/35) 135.1 327.05 (Rwy 9R/27L)	GND CON 121.9 348.6	CLNC DEL 118.85 348.6
--	--	---	-------------------------------	---------------------------------

CATEGORY	A	B	C	D
LPV DA		260/24	250 (300-½)	
LNAV/ VNAV DA		423/45	413 (400-¾)	
LNAV MDA	560/24	550 (600-½)	560/60	550 (600-¼)
CIRCLING	560-1 524 (600-1)	600-1 564 (600-1)	620-1½ 584 (600-½)	720-2¼ 684 (700-2¼)

PHILADELPHIA, PENNSYLVANIA
Amdt 3B 24MAY18

39°52'N-75°14'W

PHILADELPHIA INTL (PHL)

RNAV (GPS) RWY 27L