


WAAS CH 77511 W23A	APP CRS 235°	Rwy Idg TDZE Apt Elev	7569 726 727
--	------------------------	-----------------------------	---

RNAV (GPS) Y RWY 23
BUFFALO NIAGARA INTL (BUF)

RNP APCH - GPS		ALSF-2		MISSED APPROACH: Climb to 3000 direct WABUS and hold.	
For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -17°C or above 54°C.					
D-ATIS 135.35	BUFFALO APP CON 126.15 263.125	BUFFALO TOWER 120.5 257.8	GND CON 133.2 257.8	CLNC DEL 124.7 257.8	CPDLC



3000	WABUS	*LNAV only.	BERKI	TRAVA	4 NM Holding Pattern
↑	✧		✧	✧	
		*1.1 NM to RW23	2300	055° → 3000	
			2300	← 235°	GP 3.00° TCH 51
		1.1 NM	3.7 NM	7 NM	
CATEGORY	A	B	C	D	
LPV DA		926/18	200 (200-½)		
LNAV/VNAV DA		1050/30	324 (400-¾)		
LNAV MDA	1140/24	414 (500-½)	1140/40	414 (500-¾)	
✪ CIRCLING	1200-1	473 (500-1)	1220-1½ 493 (500-1½)	1340-2 613 (700-2)	

