21168 BELLEVILLE, ILLINOIS AL-46 (FAA) TACAN SKE N/A TACAN-A APP CRS Rwy Idg Chan **59** TDŹE N/A 230° SCOTT AFB/MIDAMERICA ST LOUIS (BLV) 459 Apt Elev (112.2)V RADAR required. When local altimeter setting not recieved, use MISSED APPROACH: Climbing left turn to Δ St Louis Downtown altimeter setting; increase all MDA 60 feet; 3000 on heading 130° and SKE TACAN R-107 to DUTMY/SKE 14.1 DME and hold. increase Circling Cat C/D/E visibility 1/4 mile. ASR ST LOUIS APP CON SCOTT TOWER GND CON CLNC DEL ATIS \* 128.7 256.7 125.2 281.5 128.25 253.5 119.2 275.8 225.4 263.025 119.875 SKE 25 (IAF) ILSCA SKE 14.1 2700 2200 095 (IF) **BLVIF** SKE 14.1 R-010. ESA W/IN 100 NM 3500 3000 to V1098 WEPUX 050° (7) (IAF) WEPUX (IAF) SKE 7 SCAFB ZATUL ∧<sup>834</sup> SKE 14.1 SKE 3 R-090 SCOTT Chan 59 499± Λ<sub>871</sub> SKE ∷-R-107 (112.2)115.0 ENL DUTMY Chan 97 **ELEV** 459 3000 WEPUX DUTMY SKE SKE 7 **BLVI**F R-107 hdg Δ Remain SKE 14.1 130° 050° within 15 NM 3000 ZATUL 230 3000 SKE 3 2000 7.1 NM CATEGORY В REIL Rwy 14L 1240-21/4 1240-21/2 1240-23/4 C CIRCLING 1180-21/4 721 (800-21/4) HIRL Rwys 14R-32L and 14L-32R 781 (800-2¼)|781 (800-2½)|781 (800-2¾

BELLEVILLE, ILLINOIS Orig 26MAY16

27 JAN 2022

ō

24 FEB 2022

SCOTT AFB/MIDAMERICA ST LOUIS (BLV)