
NC-3, 27 JAN 2022 to 24 FEB 2022

RNAV (RNP) Z RWY 12L ST LOUIS LAMBERT INTL (STL)



ALSF-2

MISSED APPROACH: Climb to 3000

a ll Cats visi Rwy 11, ex	4°C (130°F). GPS requir ibility to 1¾ SM. Simulta cept for arrivals at RRIPP ultaneous operations.	neous approach autho	orized with	MISSED AI	PPROACH: Climb to 3000 23° to ODITY and on to TOY VORTAC and hold.
D-ATIS 125.025 379.925	ST. LOUIS APP CON 132.125 360.6	ST. LOUIS TOWER 120.05 284.6	GND COI 121.9 348.6 (Inbot 121.65 377.175 (118.925 227.125	und) Outbound)	CLNC DEL 119.5 363.1 CPDLC
	00 230K 2	10.3)	RADAR REQU	JIRED	3000 ©
RU	(IAF) DYON 0 250K (5, 6) (IF EUB 250	CORDI 250K 250K 24(12) 12.1 18.1 18.1 19.1 19.1 19.1 19.1 19.1 19	(FAF) OHROB	5000 301° (2.9) (IF) HRBEI 5000 2: (RF REG	50K
	OBA° (IF) RRP AARBY OK 250K	(6.9) FARIS 250K SAMM SSAMM 210K	210K (3)	∆ 793 RW12L	MISSED APCH FIX TROY TOY 263°.
123° to RW12L	Rwy 6-24 7603 X 150 Rwy 11-29 9000 X 150 Rwy 12L-30R 9013 X 150 Rwy 12R-30L 11020 X 200	5000 303° (2.	9) (IF) RRIPP 5000 250K (RF REQD)		(9.9)
658) (A) (A) (A) (A) (A) (A) (A) (A) (A) (A	2400 × 7	OHROB 1700	3000 tr 123° See planv	iew for multiple IF locations.
	<i>ॐ</i> ૹ	GP 3.00° TCH 54	1700 A B	l	RW12L
HIRL all Rwys TDZ/CL Rwys 11	, 12L, 12R, 29, and 30R	AUTHORIZATION REQUIRED			

ST. LOUIS, MISSOURI Orig-C 29MAR18

ST LOUIS LAMBERT INTL (STL) RNAV (RNP) Z RWY 12L