2022

FEB 2

241

2

27 JAN 2022

SC-2,

ILS or LOC RWY 4

RICK HUSBAND AMARILLO INTL (AMA)v For inop ALS, increase visibility ILS Cat E to 4000 RVR and LOC Cat E to RVR 6000. ***RVR 1800 authorized MALSR MISSED APPROACH: Climb to 4100, then climbing right turn to 5000 on PNH R-118 to CAUDE INT/13 DME Α Å with use of FD or AP or HUD to DA and hold. AMARILLO TOWER ★ CLNC DEL UNICOM ATIS AMARILLO APP CON★ GND CON 118.85 350.3 118.3(CTAF) 257.9 121.9 348.6 121.65 239.275 122.95 119.5 307.0 Λ 4932 **PANHANDLE** P-47 ADF or DME 116.6 PNH 3GD 108. **REQUIRED** Chan 113 23 ∧⁵⁰⁴⁹ 5300 to LOM (IAF) 217° (7.5) 4148 1 R-078 (IAF) 3726 R-261 3882 🔨 3754 3737 3745 Λ Tradewind R./18 LOCALIZER 110.3 5500 082 I-AMA 18.72b (14)SIDER CAUDE PNH 13 LOM/IAF PANDE 251 AM :-PNH 7.4 5₅₀₀ AM 25 DOGIN 3605 **TDZE** 3605 6100 5300 YOCAN 5000 4100 CAUDE *AM LOM PNH [7.4] Remain Δ within 10 NM PNH R-118 5272 *Procedure turn not authorized for Cat. E. 5300 038° GS 3.00° **5300** TCH 44 038° 5 NM 5 NM from FAF

AMARILLO, TEXAS Amdt 22F 10SFP20

CATEGORY

C CIRCLING

S-ILS 4 **

S-LOC 4

Α

4000/24

В

395 (400-1/2)

4080-1 475 (500-1)

3805/24

C

4000/35

395 (400-%)

4240-13/4

200 (200-1/2)

633 (700-134) 673 (700-214)

ILS or LOC RWY 4

60

Knots

Min:Sec

REIL Rwy 13 and 31

HIRL Rwys 4-22 and 13-31

FAF to MAP 5 NM

5:00 3:20 2:30 2:00

90 120 150 180

4000/40

395 (400-3/4)

4280-21/4

Е

4000/50

395 (400-1)

4460-3

855 (900-3)