

APP CRS	Rwy Idg	10300
078°	TDZE	1116
	Apt Elev	1135

RNAV (RNP) Z RWY 7L

PHOENIX SKY HARBOR INTL (PHX)

GPS required. Visibility reduction by helicopters NA. For uncompensated Baro-VNAV systems, procedure NA below 1°C (34°F) or above 46°C (116°F). For inoperative MALSR, increase RNP 0.30 all Cats visibility to 1½ mile. Simultaneous approach authorized with ILS or LOC Rwy 8. Use of FD or AP providing RNAV track guidance required during simultaneous operations.

MALSR

MISSED APPROACH:

Climb to 5000 via track 078° to UXCUN and via track 111° to IWA VORTAC and hold.

D-ATIS	PHOENIX APP CON	PHOENIX TOWER	GND CON	CLNC DEL	CPDLC
127.575	128.65 353.9	118.7 278.8 (Rwy 8-26) 120.9 254.3 (Rwy 7L-25R, 7R-25L)	119.75 269.2 (N) 132.55 269.2 (S)	118.1 269.2	

Procedure NA for arrivals at BXK VORTAC via V16 westbound.

Procedure Turn NA

GP 3.00° TCH 57

4000

078°

3000

6.1 NM

5.7 NM

YECCY

RW07L

5000

UXCUN

tr 078°

tr 111°

IWA

VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 73).

UPNIW

YECCY

RW07L

5000

UXCUN

tr 078°

tr 111°

IWA

CATEGORY	A	B	C	D
RNP 0.30 DA	1 523/50 407 (400-1)			

AUTHORIZATION REQUIRED

ELEV 1135 D TDZE 1116

078° to RW07L

HIRL Rwy 8-26, 7L-25R and 7R-25L  
REIL Rwy 26

PHOENIX, ARIZONA  
Orig-C 08MAR12

33°26'N-112°01'W

PHOENIX SKY HARBOR INTL (PHX)

RNAV (RNP) Z RWY 7L

SW-4, 27 JAN 2022 to 24 FEB 2022

SW-4, 27 JAN 2022 to 24 FEB 2022