

LOC/DME F-HZ	APP CRS	Rwy Idg	6L	6R
111.55	058°	TDZE	9000 773	8029 777
Chan 52 (Y)		Apt Elev	799	799

ILS or LOC RWY 6L

CLEVELAND-HOPKINS INTL (CLE)

From GROHL, HICKR, and KWENE: RNAV 1-DME/DME/IRU or GPS required for procedure entry. Aircraft not DME/DME/IRU or GPS equipped - RADAR required for procedure entry. RNAV 1.

DME required.



⚠ Circling Rwy 10 NA at night. Simultaneous approach authorized. Simultaneous operations require use of vertical guidance; maintain last assigned altitude until established on glideslope. Inop table does not apply to Sidestep 6R. For inop ALS, increase S-LOC 6L Cats C/D visibility to 1 $\frac{1}{2}$  SM.

Rwy 6L  
ALSF-2


Rwy 6R  
MALSR

MISSED APPROACH: Climb to 1800 then climbing left turn to 3000 on heading 350° and DJB VOR/DME R-054 to PASLE/DJB 20 DME and hold.

D-ATIS ARR 127.85 DEP 132.375	CLEVELAND APP CON 124.0 346.325	CLEVELAND TOWER 124.5 273.45	GND CON 121.7 273.45	CINC DEL 125.05 273.45	CPDLC
-------------------------------------	------------------------------------	---------------------------------	-------------------------	---------------------------	-------



ELEV 799	TDZE 6L 773	TDZE 6R 777
----------	-------------	-------------



CATEGORY	A	B	C	D
S-ILS 6L	973/18 200 (200- $\frac{1}{2}$ )			
S-LOC 6L	1260/24	487 (500- $\frac{1}{2}$ )	1260/50	487 (500-1)
SIDESTEP 6R	1260/55	483 (500-1)	1260-1 $\frac{1}{2}$ 483 (500-1 $\frac{1}{2}$ )	1260-2 483 (500-2)
Ⓢ CIRCLING	1420-1	621 (700-1)	1420-1 $\frac{3}{4}$ 621 (700-1 $\frac{3}{4}$ )	1420-2 621 (700-2)