



WAAS CH 65626 W29A	APP CRS 290°	Rwy Idg 7200 TDZE 56 Apt Elev 76
--	------------------------	---

RNAV (GPS) RWY 29
PORTLAND INTL JETPORT (PWM)

RNP APCH. ⚠ For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -18°C or above 54°C. For inop MALSR, increase LNAV/VNAV all Cts visibility to 1¾ mile, increase LNAV Cat C/D visibility to 1¾ mile. **RVR 1800 authorized with use of FD or AP or HUD to DA.			MALSR ⚠	MISSED APPROACH: Climb to 3000 direct BUXTO and hold, continue climb-in-hold to 3000.	
ATIS 119.05	PORTLAND APP CON ★ 119.75 269.35	PORTLAND TOWER ★ 120.9 0 (CTAF) 257.8	GND CON 121.9	CLNC DEL 121.9	UNICOM 122.95



3000	BUXTO	PEATT	SAPPE	4 NM Holding Pattern
*LNAV only	*1.5 NM to RW29	1700	1700	GP 3.00° TCH 50
1.5 NM	3.5 NM	5.8 NM		
CATEGORY	A	B	C	D
LPV DA	**256/24 200 (200-½)			
LNAV/VNAV DA	567-1¾ 511 (500-1¾)			
LNAV MDA	580/24	524 (600-½)	580/55	524 (600-1)
CIRCLING	620-1 544 (600-1)	640-1 564 (600-1)	740-1¾ 664 (700-1¾)	860-2½ 784 (800-2½)

NE-1, 27 JAN 2022 to 24 FEB 2022

NE-1, 27 JAN 2022 to 24 FEB 2022