



APP CRS	Rwy Idg	6502
288°	TDZE	10
	Apt Elev	18

RNAV (RNP) Y RWY 29

NEWARK LIBERTY INTL (EWR)

RNP AR APCH. RF required.			MISSED APPROACH: Climb to 2000 on track 288° to MUFIE and hold.		
Straight-in Rwy 29 at night, operational VGSI required, remain on or above VGSI glidepath until threshold. For uncompensated Baro-VNAV systems, procedure NA below -12°C or above 54°C. **Missed approach requires a minimum climb of 417 feet per NM to 800.					
D-ATIS	NEW YORK APP CON	NEWARK TOWER	GND CON	CLNC DEL	CPDLC
115.7 134.825	128.55 379.9	118.3 257.6	121.8	118.85	



ELEV 18		TDZE 10
2000		MUFIE
tr 288°		
RWY 29		JIMLO 2500
COPKO 2.4 NM to RWY 29		GIMEE 2500
TETER 3000		GP 3.00° TCH 60
2.4		5.2 NM
3.6 NM		3.4 NM
CATEGORY		D
RNP 0.16 DA		461-1½ 451 (500-1½)
RNP 0.30 DA		** 530-1¾ 520 (600-1¾)
RNP 0.30 DA		573-1⅞ 563 (600-1⅞)
AUTHORIZATION REQUIRED		