

LOC/DME I-CIZ 110.15 Chan 38 (Y)	APP CRS 184°	Rwy Idg 10000 TDZE 889 Apt Elev 896
--	------------------------	--

ILS or LOC RWY 18L

CINCINNATI/NORTHERN KENTUCKY INTL (CVG)


- T** Simultaneous approach authorized with Rwy 18C and 18R.
A DME or radar required. For inoperative MALS/R, increase S-LOC 18L Cat C and D visibility to RVR 6000.

MALSR

MISSED APPROACH: Climb to 1500 then climbing left turn to 3000 via CVG R-109 to CALIF INT/CVG 19 DME and hold.

D-ATIS		CINCINNATI APP CON		CINCINNATI TOWER		GND CON	CLNC DEL	CPDLC
ARR	DEP	119.7	363.15 (090°-265°)	118.975	360.85 (RWY 18L/36R)	121.7	127.175	
134.375	135.3	123.875	363.15 (270°-089°)	118.3	(RWY5 18C/36C 09/27)			

RADAR REQUIRED



HIRL all Rwys
TDZ/CL all Rwys except 27

FAF to MAP 4.5 NM					
Knots	60	90	120	150	180
Min:Sec	4:30	3:00	2:15	1:48	1:30

[illegible]