271° (10.6)

DMF or RADAR REQUIRED

800

LAWNN

I-MFA 6.3 RADAR

1500

COPRA

RADAR

1.500

560/50 552 (600-1)

450/50 442 (500-1)

I-MFA [15.1) I-MFA [11.1]

3000

4 NM

3000

hdg

270°

DHP

R-335

Localizer unusable

1.2 NM

560/60

552 (600-11/4)

Min:Sec

**HEMOP** 

I-MFA 3.1

1.2 NM from threshold

BRBRA

DHP 11.5

**ALTERNATE** 

VGSI and ILS glidepath not coincident

(VGSI Angle 3.00/TCH 77).

One Minute

Holding Pattern

3000

GS 3.00°

TCH 51

CATEGORY

S-ILS 8R

S-LOC 8R

MISSED APCH FIX

**KROME** 

RADAR

117.1 VKZ **=:=**. Chan 118 **ELEV** 9 D **TDZE** 8 092° 4.5 NM from FAF TDZ/CL Rwy 8R REIL Rwys 8L and 26R HIRL all Rwys FAF to MAP 3.3 NM 60 120 150 180 Knots

VIRGINIA KEY

MIAMI, FLORIDA Amdt 30D 11DEC14

MIAMI INTL (MIA) ILS or LOC RWY 8R

3:18 2:12 1:39 1:19

3.3 NM-