




LOC I-SDU 111.95	APP CRS 180°	Rwy Idg 11120 TDZE 290 Apt Elev 341
----------------------------	------------------------	--

ILS or LOC RWY 18C
MEMPHIS INTL (MEM)

Simultaneous approach authorized. DME or RADAR required. For inap ALS, increase S-ILS 18C all Cats visibility to 1¼ SM.	MALSR 	MISSED APPROACH: Climb to 900 then climbing left turn to 5000 on MEM VORTAC R-151 to KEEZE INT/MEM 10.4 DME and hold, continue climb-in-hold to 5000.
MEMPHIS APP CON 119.1 291.6 (176°-355°) 125.8 338.3 (356°-175°)	MEMPHIS TOWER (Rwy 9-27) 118.3 257.8 (Rwys 18C-36C, 18L-36R) 119.7 257.8 (Rwy 18R-36L) 128.425 257.8	GND CON (Rwy 9-27) 121.0 379.2 (Rwys 18C-36C, 18L-36R) 121.9 379.2 (Rwy 18R-36L) 121.65 379.2

D-ATIS 127.75	RADAR REQUIRED	CLNC DEL 125.2	CPDLC
--------------------------------	-----------------------	---------------------------------	--------------



SE-1, 27 JAN 2022 to 24 FEB 2022

SE-1, 27 JAN 2022 to 24 FEB 2022