




WAAS CH 78121 W12B	APP CRS 123°	Rwy Idg 10552 TDZE 540 Apt Elev 618
--	------------------------	--

RNAV (GPS) Y RWY 12R

ST LOUIS LAMBERT INTL (STL)

<p>▼ For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -16°C (4°F) or above 54°C (130° F). DME/DME RNP-0.3 NA. For inop ALS, increase LPV Cat E visibility to RVR 4000, LNAV Cats A/B visibility to RVR 5000, and LNAV Cat E visibility to 1½ SM. Inop table does not apply to LNAV/VNAV. Simultaneous approach authorized with Rwy 11. LNAV procedure NA during simultaneous operations. Use of FD or AP required during simultaneous operations.</p>			<p>MALSR</p> 		<p>MISSED APPROACH: Climb to 5000 direct FONTI and hold, continue climb-in-hold to 5000.</p>	
D-ATIS 125.025 379.925	ST. LOUIS APP CON 132.125 360.6	ST. LOUIS TOWER 118.5 257.7	GND CON 121.9 348.6 (Inbound) 121.65 377.175 (Outbound) 118.925 227.125 (Rwy 11/29)		CLNC DEL 119.5 363.1	CPDLC



PAULY		NAIRN		TUDNE		FONTI	
4500		3600		2400		5000	
123°		123°		123°		123°	
GP 3.00°		GP 3.00°		GP 3.00°		GP 3.00°	
TCH 54		TCH 54		TCH 54		TCH 54	
5.3 NM		4.9 NM		4.4 NM		1.3 NM	
CATEGORY	A	B	C	D	E		
LPV DA	740/18 200 (200-½)						
LNAV/VNAV DA	1103-2 563 (500-2)						
LNAV MDA	1000/40 460 (400-¾)			1000/50 460 (400-1)			