

APP CRS	Rwy Idg	8579
124°	TDZE	8
	Apt Elev	9

RNAV (RNP) Y RWY 12

MIAMI INTL (MIA)

<div><div><div>▼</div><div>▲</div><div>NA</div></div><div>GPS Required. For inoperative MALSR, increase 0.30 all Cats visibility to 1½. For uncompensated Baro-VNAV systems, procedure NA below 6°C (42°F) or above 49°C (120°F).</div></div>		<div><div>MALSR</div><div><div><div>AS</div><div><div></div><div></div><div></div></div></div></div></div>	<div><div>MISSED APPROACH:</div><div>Climb to 3000 direct VAYQO and via 109° track to VKZ VOR/DME and hold, continue climb-in-hold to 3000.</div></div>		
<div><div>D-ATIS</div><div>ARR 119.15</div><div>DEP 133.675</div></div>	<div><div>MIAMI APP CON</div><div>124.85</div><div>322.3</div></div>	<div><div>MIAMI TOWER</div><div>118.3</div><div>256.9</div></div>	<div><div>GND CON</div><div>121.8 (8L/8R/12/26L/26R)</div><div>127.5 (9/27/30)</div></div>	<div><div>CLNC DEL</div><div>348.6</div></div>	<div><div>CPDLC</div></div>

