

APP CRS

095°

Rwy Idg

9000

TDZE

1000

Apt Elev

1026

RNAV (RNP) Z RWY 10

HARTSFIELD-JACKSON ATLANTA INTL (ATL)

For uncompensated Baro-VNAV systems, procedure NA below -8°C (18°F) or above 54°C (130°F). GPS required. Simultaneous approach authorized; arrival from ROBNS NA. For inop ALS, increase RNP 0.11 DA all Cats visibility to RVR 4500.

ALSIF-2

MISSED APPROACH: Climb to 1500 then climbing right turn to 3000 direct SCARR and hold.

D-ATIS

ARR 119.65

DEP 125.55

ATLANTA

APP CON

127.9 379.9

ATLANTA TOWER

8L-26R 8R-26L 9L-27R 9R-27L 10-28 RWYS

119.1 125.325 123.85 119.3 119.5 254.4

ALL

8L-26R,8R-26L 9L-27R,9R-27L 10-28 RWYS

121.9 121.75 121.65 254.4

GND CON

ALL

2049 Δ

2049 Δ

CLNC DEL

118.1

CPDLC

MSA RW 10 25 NM

3100

MISSED APCH FIX

SCARR

ELEV 1026

TDZE 1000

CTEEE

4000

095°

2700

ZMANN

2700

RW10

GP 3.00° TCH 55

5 NM

5.2 NM

1500

3000

SCARR

18

0.6% DOWN - X 150

9000

0.4% DOWN

12390

0.3% DOWN - X 150

9000 X 150

0.5% DOWN

0.5% UP

271

27R

095° to RW10

HIRL all Rwy's

TDZ/CL Rwy's 8L, 9R, 10, 26R, 27L and 28

| | | | | |
|-------------|---|---------|---------------|---|
| CATEGORY | A | B | C | D |
| RNP 0.11 DA | | 1290/24 | 290 (300-1/2) | |
| RNP 0.30 DA | | 1456/50 | 456 (500-1) | |

AUTHORIZATION REQUIRED

ATLANTA, GEORGIA

Amdt 1 12OCT17

HARTSFIELD-JACKSON ATLANTA INTL (ATL)

33°38'N-84°26'W

RNAV (RNP) Z RWY 10