

WAAS	APP CRS	Rwy Idg	7015
CH 42829	212°	TDZE	887
W21A		Apt Elev	887

RNAV (GPS) RWY 21

DANE COUNTY RGNL/TRUAX FLD (MSN)

⚠

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -20°C (-4°F) or above 54°C (130°F). DME/DME RNP-0.3 NA. For inop MALSR, increase LNAV/VNAV all Cats visibility to 1¾ mile and LNAV Cat C/D visibility to 1⅓ mile.

MALSR

MISSED APPROACH:

Climb to 3600 direct WIROD and hold.

ATIS 124.65 278.3	MADISON APP CON ★ 135.45 343.7	MADISON TOWER ★ 119.3 (CTAF) 0 257.8	GND CON 121.9 348.6	CLNC DEL 121.625	UNICOM 122.95
----------------------	-----------------------------------	---	------------------------	---------------------	------------------

2248

ELEV 887

D

TDZE 887

REIL Rwy 14

HIRL all Rwy's

REIL Rwy's 3 and 32

3600	WIROD	* LNAV only	FONUV	4 NM Holding Pattern
	YARUT 1.9 NM to RW21	JAPRO 2500	HEVUS 2700	032° → 3600 ← 212°
	* 1.4 NM to RW21	* 1540		GP 3.00° TCH 53
	1.4 NM	0.5	3 NM	5 NM
CATEGORY	A	B	C	D
LPV DA	1087-½ 200 (200-½)			
LNAV/VNAV DA	1412-1⅓ 525 (600-1⅓)			
LNAV MDA	1380-½ 493 (500-½)		1380-1 493 (500-1)	
CIRCLING	1420-1 533 (600-1)	1460-1 573 (600-1)	1460-1½ 573 (600-½)	1700-2¾ 813 (900-2¾)

MADISON, WISCONSIN

DANE COUNTY RGNL/TRUAX FLD (MSN)

Amdt 2C 04FEB16

43°08'N-89°20'W

RNAV (GPS) RWY 21