

▼

DME or RADAR required. Simultaneous approach authorized.  
For inop ALS, increase S-ILS 17 Cat E visibility to RVR 4000,  
increase S-LOC 17 Cat C/D/E visibility to 1½ SM.

MALSR

MISSED APPROACH: Climb to 5800  
then climbing left turn to 10000 direct  
FFU VORTAC and hold.

|                |                        |                      |             |               |       |
|----------------|------------------------|----------------------|-------------|---------------|-------|
| D-ATIS         | SALT LAKE CITY APP CON | SALT LAKE CITY TOWER | GND CON     | CLNC DEL      | CPDLC |
| 124.75 125.625 | 125.7 284.6            | 118.3 257.8          | 121.9 348.6 | 127.3 379.975 |       |

Procedure NA for arrival on OGD VORTAC  
airway radials 068 CW 153.

|                      |           |
|----------------------|-----------|
| ELEV 4227            | TDZE 4219 |
| 169° 5.4 NM from FAF |           |
| 4463 ±               | 191       |
| 4254                 | 34R       |
| 34L                  | 35        |
| 34L                  | 35        |

|                          |                          |                          |                             |             |       |     |
|--------------------------|--------------------------|--------------------------|-----------------------------|-------------|-------|-----|
| UDUZU I-BNT [21.8] RADAR | IVOCY I-BNT [16.6] RADAR | PRYES I-BNT [11.9] RADAR | TIFUL INT I-BNT [7.2] RADAR | 5800        | 10000 | FFU |
| 11000                    | 9000                     | 7500                     | 6000                        | *LOC only   |       |     |
| GS 3.00° TCH 55          | 5.2 NM                   | 4.7 NM                   | 4.7 NM                      | 4.1 NM      | 1.3   |     |
| CATEGORY                 | A                        | B                        | C                           | D           | E     |     |
| S-ILS 17                 | 4419/18 200 (200-½)      |                          |                             |             |       |     |
| S-LOC 17                 | 4700/24                  | 481 (500-½)              | 4700/50                     | 481 (500-1) |       |     |

HIRL all Rwys

TDZ/CL Rwys 16L, 16R, 17, 35, 34L, and 34R

FAF to MAP 5.4 NM

|         |      |      |      |      |      |
|---------|------|------|------|------|------|
| Knots   | 60   | 90   | 120  | 150  | 180  |
| Min:Sec | 5:24 | 3:36 | 2:42 | 2:10 | 1:48 |

SALT LAKE CITY, UTAH

40°47'N-111°59'W

SALT LAKE CITY INTL (SLC)

ILS or LOC RWY 17

Amdt 14A 17AUG17