


WAAS CH 77937 W10D	APP CRS 090°	Rwy Idg TDZE Apt Elev	7500 680 680
--------------------------	-----------------	-----------------------------	--------------------

RNAV (GPS) Y RWY 10R
CHICAGO O'HARE INTL (ORD)

RNP APCH. Simultaneous approach authorized. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -19°C or above 54°C. LNAV procedure NA during simultaneous operations. Use of FD or AP providing RNAV track guidance required during simultaneous operations. For inop ALS, increase LNAV/VNAV all Cats visibility to 1 3/8 SM.				ALSIF-2 	MISSED APPROACH: Climb to 1200 then climbing right turn to 4000 direct DPA VOR/DME and hold.
D-ATIS 135.4 282.225	CHICAGO APP CON 119.0 292.125	O'HARE TOWERS 128.15 348.0 (Rwy 9L/27R) 133.0 348.0 (10R/28L) 120.75 121.15 126.9 132.7 348.0 (CENTER)			GND CON (TWR CENTER) 121.75 (OBND) 121.9 (IBND) 124.125 (TWR NORTH) 118.05 (TWR SOUTH) 226.675 (ALL TWRs)



ELEV 680 TDZE 680		DPA 1200 4000	
GP 3.00 TCH 55		*LNAV only.	
CATEGORY A		B	
LPV DA		930/24 250 (300-1/2)	
LNAV/VNAV DA		1157/50 477 (500-1)	
LNAV MDA		1120/24 440 (500-1/2) 1120/40 440 (500-3/4)	

EC-3, 27 JAN 2022 to 24 FEB 2022

EC-3, 27 JAN 2022 to 24 FEB 2022