

RNAV (GPS) Y RWY 18R  
CINCINNATI/NORTHERN KENTUCKY INTL (CVG)

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -16°C or above 54°C. Simultaneous approach authorized with Rwy 18L/C. LNAV procedure NA during simultaneous operations. Use of FD or AP providing RNAV track guidance required during simultaneous operations.



**MISSED APPROACH:** Climb to 3000 direct BEPEE and on 266° track to AVIEW and hold.


CINCINNATI TOWER  
**118.975 360.85** (RWY 18L/36R)  
**118.3** (RWYS 18C/36C, 09/27)  
**133.325** (RWY 18R/36L)

GND CO  
121 7

CLNC DEL  
127 175

CPDLC

## RADAR REQUIRED



Δ 1848

A1788


A 1372



A1256

A1114


MSA RW 10R 25 NM

3000



3000 ↑	BEPEE 	tr 266°	AVIEW 
-----------	--	------------	---


\* LNAV only.



CATEGORY		A	B	C	D
LPV	DA	1068/18 200 (200-½)			
LNAV/ VNAV	DA	1321/50 453 (500-1)			
LNAV	MDA	1320/24 452 (500-½)	1320/40 452 (500-¾)	1320/50 452 (500-1)	
CIRCLING		1460-1 564 (600-1)	1560-1¾ 664 (700-1¼)	1560-2 664 (700-2)	

ELEV 896	<b>D</b>	TDZE 868
----------	----------	----------

184° to  
RW18R



HIRL all Rwy's  
TDZ/CL all Rwy's except 27

Amdt 1D 12AUG21

39°03'N-84°40'W

RNAV (GPS) Y RWY 18R