

WAAS CH 61002 W28A	APP CRS 276°	Rwy Idg TDZE Apt Elev	8394 7 65
--	------------------------	-----------------------------	--------------------------------------

RNAV (GPS) Y RWY 28R

FORT LAUDERDALE/HOLLYWOOD INTL (FLL)

RNP APCH - GPS.

Simultaneous approach authorized. Use of FD or AP required during simultaneous operations. LNAV procedure NA during simultaneous operations. Inop table does not apply to LPV all Cats. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below 7°C or above 54°C. For inop ALS, increase LNAV Cats C and D visibility to 1½ SM.

MALSR

MISSED APPROACH:
Climb to 800 then climbing right turn to 4000 direct HUKUK and hold, continue climb-in-hold to 4000.

D-ATIS 135.0	MIAMI APP CON 133.775 285.6	FORT LAUDERDALE TOWER 119.3 257.8	GND CON 121.4	CLNC DEL 128.4	CPDLC
------------------------	---------------------------------------	---	-------------------------	--------------------------	-------

MISSED APCH FIX

ELEV 65 D TDZE 7

800 4000 HUKUK

VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 69°).

4 NM Holding Pattern

CATEGORY	A	B	C	D
LPV DA	257/40	250 (200-¾)		
LNAV/VNAV DA	529/55	522 (500-1)		
LNAV MDA	620/24	613 (600-½)	620-1¾	613 (600-1¾)
CIRCLING	680-1	615 (700-1)	800-2 735 (800-2)	800-2¼ 735 (800-2¼)

HIRL Rwy 10L-28R and 10R-28L

FORT LAUDERDALE, FLORIDA

Amdt 5 12AUG21

26°04'N-80°09'W

FORT LAUDERDALE/HOLLYWOOD INTL (FLL)

RNAV (GPS) Y RWY 28R

SE-3, 27 JAN 2022 to 24 FEB 2022

SE-3, 27 JAN 2022 to 24 FEB 2022