

ILS or LOC RWY 18R
CINCINNATI/NORTHERN KENTUCKY INTL (CVG)

MISSED APPROACH: Climb to 1300 then climbing right turn to 3000 via CVG R-244 to AVIEW INT/CVG 20 DME and hold.

CINCINNATI TOWER
118.975 360.85 (RWY 18L/36R)
118.3 (RWYS 18C/36C, 09/27)
133.325 (RWY 18R/36L)

Diagram of a roof section showing a gable end with a 134-degree angle. The roof is labeled R-294. The gable end is labeled JADRO FLM 43. The roof pitch is 117.3/100 for Chan 120 and 117.0/100 for Chan 117.

RADAR REQUIRED

△ 1848


A 1788

Δ 1372

△ 1256

A1114

LOCALIZER 110.75
I-CJN $\begin{smallmatrix} \cdot & \cdot \\ \text{---} & \text{---} \\ \cdot & \cdot \end{smallmatrix} = \cdot$
Chan 44 (Y)

CINCINNATI
117.3 CVG 
Chan 120

CATEGORY	A	B	C	D
S-ILS 18R	1068/18 200 (200-½)			
S-LOC 18R	1300/24 432 (500-½)		1300/40 432 (500-¾)	1300/50 432 (500-1)
CIRCLING	1460-1 564 (600-1)		1560-1¾ 664 (700-1¾)	1560-2 664 (700-2)

	Knots	60	90	120	150	180
Min:Sec	4:36	3:04	2:18	1:50	1:32	