APP CRS TDZE 301 Apt Elev 341

RNAV (RNP) X RWY 18L

MEMPHIS INTL (MEM)



MISSED APPROACH: Climb to 5000 on track 180° to DEEWY and on track 180° to FEYAM left turn on track 153° to KEEZE and hold, continue climb-in-hold to 5000.

GND CON

MEMPHIS APP CON 119.1 291.6 (176°-355°) 125.8 338.3 (356°-175°)

RADAR REQUIRED

all Cats visibility to RVR 6000.

MEMPHIS TOWER
(Rwy 9-27)
118.3 257.8
(Rwys 18C-36C, 18L-36R)
(Rwy 18R-36L)
128.425 257.8

720 Λ

1001

CATEGORY

RNP 0.11 DA

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -9°C (16°F)

or above 48°C (118 °F). Simultaneous approach authorized. GPS required.

Missed approach requires RNP less than 1.0. For inop ALS increase RNP 0.11

(Rwy 9-27) (Rwys 18C-36C, 18L-36R) (Rwy 18R-36L)

1450

121.0 379.2 121.9 379.2 121.65 379.2

RW18L 25 Ny

2500

D-ATIS 127.75


SE-1,


27 JAN 2022

ō

24 FEB 2022

(IF)
REISE 1





2000

AUTHORIZATION REQUIRED

5.2 NM

2000

647/40 346 (400-34)

7.7 NM

1337

(FAF)

RONEE

MEMPHIS, TENNESSEE Orig-D 29MAR18

36C 36R

MEMPHIS INTL (MEM) RNAV (RNP) X RWY 18L

GP 3.00°

TCH 60

RW18L