

APP CRS

197°

Rwy Idg

7001

TDZE

-1

Apt Elev

4

RNAV (RNP) Z RWY 20

LOUIS ARMSTRONG NEW ORLEANS INTL (MSY)

RNP AR APCH - GPS.

▼

For uncompensated Baro-VNAV systems, procedure NA below -1°C or above 54°C. For inop ALS, increase RNP 0.30 all Cats visibility to RVR 6000.

MALS

MISSED APPROACH: Climb to 2000 on track 197° to POLY and track 109° to SAFES and hold.

D-ATIS	NEW ORLEANS APP CON	NEW ORLEANS TOWER	GND CON	CLNC DEL	CPDLC
127.55	WEST 125.5 350.35 EAST 133.15 290.3	119.5 254.3	121.9 273.525	120.925	

ELEV 4

D

TDZE -1

197° to RWY 20

RLS Rwy 2

TDZ/CL Rwy 11

HIRL All Runways

MISSED APCH FIX

SAFES

2000

tr 197°

tr 109°

SAFES

RWY 20

JASPO

RAYOP

2000

2000

4000

GP 3.00°

TCH 52

6.1 NM

7 NM

CATEGORY	A	B	C	D
RNP 0.11 DA	363/40 364 (400-¾)			
RNP 0.30 DA	414/50 415 (500-1)			

AUTHORIZATION REQUIRED

NEW ORLEANS, LOUISIANA

Amdt 1A 07OCT21

LOUIS ARMSTRONG NEW ORLEANS INTL (MSY)

30°00'N-90°16'W

RNAV (RNP) Z RWY 20