EXACT ENUMERATION / DATA / VERIFICATION

Rank-3 fusion rings

A reproducible census through multiplicity 1000

Sébastien Palcoux

BIMSA

Computational companion, 26 October 2026

Abstract

We explain the exact enumeration of all based fusion rings of rank 3 through multiplicity 1000, comprising 460,353 isomorphism classes. The account separates the mathematical coverage argument, the completed search, and independent verification of the emitted tensors. All duality types are included, and no categorifiability filter is applied. Code, machine-readable counts, full multiplication tensors and provenance records accompany the text.

AI-generated research · independent verification pending. This manuscript, its code and data were developed with AI assistance. Independent human verification and Lean formalization are pending. Treat the results with caution: exact computational checks establish only their stated scope.

Scope. A census of based rings, not a classification of tensor categories. Only completed whole-rank results are released.

Contents

1 Objects, equivalence and the counting convention **3**

1.1 Why duality types can be searched separately 3

2 The certified release at rank 3 **3**

3 The classical rank-three Diophantine parameterization **4**

3.1 Every boundary and every arithmetic progression 4

3.2 The deliberate endpoint 4

4 What the independent verification establishes **4**

4.1 Provenance and reproducibility 5

4.2 Certified datasets and reproducibility 5

5 Reading and reusing the data **5**

6 Reproduction commands **6**

7 Correctness audit and companion classification **6**

1 Objects, equivalence and the counting convention

A *fusion ring* here is a free abelian group with a distinguished finite basis $B = \{b_0, b_1, \dots, b_{r-1}\}$, an associative multiplication with unit b_0, and an involution $i \mapsto i^*$ fixing 0. Its structure constants satisfy

$$b_i b_j = \sum_k N_{ij}^k b_k, \qquad N_{ij}^k \in \mathbb{Z}_{\geq 0},$$

$$N_{0j}^k = N_{j0}^k = \delta_{jk}, \qquad N_{ij}^0 = \delta_{i^*,j}, \tag{1}$$

$$N_{ij}^k = N_{i^*k}^j = N_{kj^*}^i. \tag{2}$$

These conventions agree with the usual based-ring definition; see [1, 2]. No assumption of categorifiability, commutativity or integrality of Frobenius–Perron dimensions is imposed unless proved in the relevant rank.

A based isomorphism is a bijection of the distinguished bases preserving the unit and multiplication. In tensor notation it is a permutation q fixing 0 such that

$$N_{ij}^k = N'^{q(k)}_{q(i)q(j)} \quad \text{for every } i, j, k.$$

The coefficient of the unit determines the involution, so such an isomorphism automatically intertwines duality. The *multiplicity* is the maximum entry of the *full* ordered multiplication tensor. It is at least one, including for group rings. Put

$$c_r(m) = \#\{\text{rank-}r \text{ fusion rings of multiplicity exactly } m\}/\cong, \qquad C_r(M) = \sum_{m=1}^{M} c_r(m).$$

A list through M contains all rings of multiplicity at most M, not only those of multiplicity equal to M. This distinction is essential when exporting OEIS b-files.

1.1 Why duality types can be searched separately

An involution on the $r-1$ nonunit elements consists of p disjoint transpositions and $r-1-2p$ fixed points, with $0 \leq p \leq \lfloor (r-1)/2 \rfloor$. Fix one representative d_p of each type. An isomorphism between two tensors with involution d_p commutes with d_p. Hence it is sufficient to quotient that stratum by the centralizer

$$Z_{S_{r-1}}(d_p), \qquad |Z_{S_{r-1}}(d_p)| = 2^p p!(r-1-2p)!.$$

Different p cannot be isomorphic. Therefore a whole-rank census is complete exactly when every required stratum has been searched exhaustively. Finishing only the non-self-dual strata does not certify a whole-rank counting term.

2 The certified release at rank 3

The released bound is $M = 1000$ and the cumulative number of classes is $C_3(1000) = 460,353$. Every duality type is included. The accompanying full tensor file has one record per based-isomorphism class.

The first sixteen terms are $4, 3, 4, 6, 5, 9, 6, 10, 12, 9, 10, 20, 9, 13, 16, 25$. The complete 1,000-term file is supplied as `oeis/b354471.txt`.

The data and their checksums are recorded in `results/census.json`. The corresponding completed-run evidence and independent audit are under `verification/rank3/`.

3 The classical rank-three Diophantine parameterization

This companion does not claim a new theoretical rank-three classification. It materializes the familiar parameterization through the requested bound. In the self-dual basis $(1, X, Y)$, reciprocity gives

$$X^2 = 1 + mX + kY, \qquad XY = kX + lY, \qquad Y^2 = 1 + lX + nY.$$

Comparing $(X^2)Y$ with $X(XY)$ proves that associativity is equivalent to

$$k^2 + l^2 = 1 + lm + kn. \tag{3}$$

Exchanging X, Y sends (k, l, m, n) to (l, k, n, m). Retain $k < l$, or $k = l$ with $m \le n$.

If $X^* = Y$, reciprocity instead gives

$$X^2 = aX + bY, \quad Y^2 = bX + aY, \quad XY = YX = 1 + aX + aY.$$

Associativity implies $b^2 - a^2 = 1$. Nonnegative integers force $a = 0$, $b = 1$, which is exactly $\mathbb{Z}[C_3]$.

3.1 Every boundary and every arithmetic progression

For the self-dual part take $k \le l$. If $k = 0$, equation (3) gives $l = 1$, $m = 0$, with n arbitrary in $[0, M]$. If $k = l$, it gives $k = l = 1$ and $m + n = 1$, leaving the representative $(1, 1, 0, 1)$. For $0 < k < l$, a common divisor of k, l would divide one, so $\gcd(k, l) = 1$. Set $C = k^2 + l^2 - 1$ and choose $0 \le m_0 < k$ with $lm_0 \equiv C \pmod{k}$. For $k = 1$ take $m_0 = 0$. Then every integral solution is

$$m = m_0 + kt, \qquad n = n_0 - lt, \qquad n_0 = (C - lm_0)/k,$$

where

$$\max\left(0, \left\lceil \frac{n_0 - M}{l} \right\rceil\right) \le t \le \min\left(\left\lfloor \frac{M - m_0}{k} \right\rfloor, \left\lfloor \frac{n_0}{l} \right\rfloor\right).$$

The Euclidean algorithm finds the inverse of l modulo k. This visits every bounded solution exactly once. The two boundary cases and $\mathbb{Z}[C_3]$ complete the census. Every emitted solution is checked again in (3); the independent tensor verifier does not use that equation.

3.2 The deliberate endpoint

The repository hard-caps the rank-three generator at $M = 1000$. It contains all exact-multiplicity counts and all multiplication tensors through that bound. There are no rank-three counts or searches beyond that endpoint in the released data. The b-file belongs to OEIS A354471.

4 What the independent verification establishes

The enumerator and verifier have separate mathematical tasks. Exhaustiveness uses the complete coordinate parameterization, the safe-pruning proof and the normal completion of every required branch. The verifier reads only the emitted *full tensors*; it neither reconstructs the parameterization nor trusts the generator's polynomial list.

For every tensor it checks nonnegative integral coefficients, both unit laws, uniqueness and involutivity of the dual, both reciprocity identities, and every integer associativity identity for all four indices. It then canonicalizes under *every* unit-fixing basis permutation. A matching hash is only a lookup aid: actual canonical tensors are compared. This detects both literal repetitions and different labellings of an isomorphic based ring.

Passing these checks proves soundness and uniqueness of the emitted data; by itself it would not prove that no ring was omitted. That is why normal completion logs and the mathematical coverage argument are retained separately. Comparison with the original ancillary file is an additional containment/regression test, not an input to enumeration and not a replacement for an exhaustiveness proof.

4.1 Provenance and reproducibility

The retained Vercleyen–Slingerland v4 ancillary file has SHA-256

`b587c3f683157369da7cc090f762bbff0e18dcf11acc3f5031d6bc0c643843f8`

Its 28,451 records contain 25,138 distinct classes. The 3,313 redundant records occur at rank five and exact multiplicities 9–12. Their original and corrected counts are respectively

$$(1463, 1794, 2283, 3049) \quad \longrightarrow \quad (863, 1082, 1383, 1948).$$

Every deletion has an explicit basis-permutation witness in the audit folder. This audit does not establish completeness of the source's partial-search cells.

The primary manifest `results/census.json` records every released count, bound, filename and checksum. Compressed tensors use the original line-per-ring, nested-curly-brace format. An entry is $N[i][j][k] = N_{ij}^k$: the output index has already been dualized where the internal parameter convention requires it. The raw tensor needs no additional index conversion.

4.2 Certified datasets and reproducibility

The primary manifest gives the complete bound, exact counts and data checksums for every rank. Each `verification/rankR/` directory records the independent audit and source identity for that dataset. For the laptop censuses it also retains the completed enumeration, commands, environment, phase timings and nonempty subprocess logs. Every required duality stratum completed normally; independent canonicalization found zero duplicate classes.

Independent checks use the supplied tensors; they do not rerun enumeration. The per-rank reports identify the verification environment and source revision, and certify agreement with the established exact-multiplicity count prefix. Hosted audits and local checks are identified separately in `verification/README.md`; see `docs/PROVENANCE.md` for attribution.

The local launcher has no clock limit, while the manual hosted workflow uses a finite shared deadline covering every computational phase. A timeout never certifies the unfinished bound. Only a complete, independently verified whole-rank candidate can enter the release; a later failed attempt cannot replace it. Reproduction commands and supported limits are in `docs/REPRODUCIBILITY.md`.

5 Reading and reusing the data

The result files count based rings, not monoidal categories or realizations of a ring. One tensor can admit several inequivalent categorifications, or none. No number here is a classification of fusion categories. The rank-specific count files use exact multiplicity; cumulative totals belong only in the summary column. Proposed OEIS additions must be regenerated from a complete manifest, not copied from an interrupted log.

The retained code was generated with AI assistance and is accompanied by explicit mathematical coverage arguments and independent integer checks. These checks are not a formal proof in a proof

assistant. The present text is an explanatory computational companion, not a claim of journal acceptance or external peer review.

6 Reproduction commands

From the repository root on a local computer, request a complete run with no clock limit. An interruption does not certify a smaller census.

```
python3 scripts/run_laptop.py --rank 3 --bound 1000
```

To verify the supplied release without recomputing it:

```
python3 scripts/check_release.py --full
```

For a shared-budget frontier search, use `scripts/extend_census.py`. For ranks five through eight it starts at the released bound plus one and restarts the unfinished bound without claiming checkpoint resumption. The local command above verifies all tensors and the old count prefix before packaging a result. The separate timed frontier wrapper bounds every phase. Rank three is instead capped at 1000.

7 Correctness audit and companion classification

The 25 October 2026 audit checked all 1,433,410 supplied rank-three through rank-eleven tensors by exact fusion axioms and exhaustive based-isomorphism tests, finding no duplicate classes. It did not rerun upstream enumeration. Census tensors and counting terms are unchanged. Separate proof and replay corrections repair model identifications and computational defects.

The 27 October continuation excludes R9_2_1607, R9_2_1975 and R9_2_1976 over the complex numbers. Seven cases remain unresolved: two at rank six, four at rank eight and one at rank nine. No new model is claimed. Independent human verification and formalization remain pending.

References

[1] P. Etingof, S. Gelaki, D. Nikshych and V. Ostrik, *Tensor Categories*, Mathematical Surveys and Monographs 205, American Mathematical Society, 2015.

[2] G. Vercleyen and J. Slingerland, *On Low Rank Fusion Rings*, Journal of Mathematical Physics 64 (2023), 091703; arXiv:2205.15637v4.

[3] V. Ostrik, *On formal codegrees of fusion categories*, Mathematical Research Letters 16 (2009), 895–901; arXiv:0810.3242.

[4] J. Dong and S. Palcoux, rank-four and rank-five census derivations, project manuscripts and computational supplements, September 2026. The relevant derivations are retained in the repository's `methods/` directory.

[5] OEIS Foundation Inc., *The On-Line Encyclopedia of Integer Sequences*, entries A348305, A354471, A354472, A354473, A354475, A354476 and A354477. Proposed updates in this repository are not submitted edits.