



GATED WYE LONG VALVE HANDLES

AYNJ-NF

2.5" F SWIVEL ROCKER X (2) 1.5" M

\$567.00 List Price

FEATURES

2.5" (65mm) female swivel inlet x two 1.5" (38mm) male outlets. Quarter-turn aluminum ball valves provide a positive shutoff. Full flow 1.5" (38mm) ball waterway. Rugged lightweight aluminum alloy casting with durable powder coat finish inside and out, hard coat anodized couplings, and super tough nylon folding handles. 2.5" NH female swivel rocker lug inlet coupling is standard.

SPECIFICATIONS

Coupling Size Side A	2.5" (65 mm)
Coupling Size Side B	1.5" (38 mm)
Coupling Swivel Side A	Non-Full Time Swivel
Coupling Swivel Side B	Rigid
Handle Type	Quarter Turn
L D H Inlet	No
L D H Outlet	No
Pressure Relief Valve	No
Type	Wyes
Valve Design	Ball Valve Aluminum
Weight	2.5

DOCUMENTS

Service Procedures

[GATED WYE SPECS & PARTS LIST \(PDF\)](#)

Technical Specifications and Drawings

[AYNJ-NF FINISHED GOOD PRINT \(PDF\)](#)

[AYNJ-NF FINISHED GOOD PRINT \(ZIP\)](#)

[AYNJ-NF FINISHED GOOD PRINT - STEP \(DXF\)](#)

[AYNJ-NF ITEM SPECIFICATION \(DOC\)](#)

Instructions For Installation, Safe Operation and Maintenance

[LDH GATED WYE MANUAL \(PDF\)](#)

[WYE: GATED & STANDPIPE WYE \(2.5INCH X 1.5INCH\) \(PDF\)](#)