

Randomization Basics

10 June 2025

Prof. Dr. Sebastian Wild

7 Randomization Basics

- 7.1 Motivation
- 7.2 Randomized Selection
- 7.3 Recap of Probability Theory
- 7.4 Probabilistic Turing Machines
- 7.5 Classification of Randomized Algorithms
- 7.6 Tail Inequalities and Concentration Bounds
- 7.7 Concentration in Action

7.1 Motivation

Computational Lottery?

- ▶ If we are faced with solving an **NP**-hard problem and known smart algorithms are too slow, we likely have to compromise on what “solving” means.
 - ▶ Classical algorithms are *always* and *exactly* correct.
- ↪ Here: Let's compromise on “always”, i. e., allow algorithms to occasionally **fail**!

Computational Lottery?

- ▶ If we are faced with solving an NP-hard problem and known smart algorithms are too slow, we likely have to compromise on what “solving” means.

- ▶ Classical algorithms are *always* and *exactly* correct.

↪ Here: Let's compromise on “always”, i. e., allow algorithms to occasionally **fail**!

- ⚡ A *deterministic* algorithm A that fails on input x will *always* fail for x .

↪ What if we require a solution for such an input x ? We get **nothing** from A !

- ▶ Must use a form of *nondeterminism*.

Computational Lottery?

- ▶ If we are faced with solving an NP-hard problem and known smart algorithms are too slow, we likely have to compromise on what “solving” means.

- ▶ Classical algorithms are *always* and *exactly* correct.

↪ Here: Let's compromise on “always”, i. e., allow algorithms to occasionally **fail**!

- ⚡ A *deterministic* algorithm A that fails on input x will *always* fail for x .

↪ What if we require a solution for such an input x ? We get **nothing** from A !

- ▶ Must use a form of *nondeterminism*.

- ▶ **Randomization:** Use *random bits* to guide computation.

↪ *Instead of always failing on some rare inputs, we rarely fail on any input.*

↑
can make this arbitrarily rare

Why Could Randomization Help?


- ▶ Main intuitive reason: (can be) much easier to be 99.999999% correct than 100%
How can this manifest itself?
 - ▶ **Faster and simpler algorithms**
Random choice can allow to sidestep tricky edge cases
 - ▶ We can use **fingerprinting** (a.k.a. checksums) *hashing*
Cheap surrogate question, mostly correct, but sometimes wrong.
 - ▶ Protect against **adversarial inputs**
We make our (algorithm's) behavior unpredictable, so it is harder to exploit us.

Why Could Randomization Help?

- ▶ Main intuitive reason: (can be) much easier to be 99.999999% correct than 100%
How can this manifest itself?
 - ▶ **Faster and simpler algorithms**
Random choice can allow to sidestep tricky edge cases
 - ▶ We can use **fingerprinting** (a.k.a. checksums)
Cheap surrogate question, mostly correct, but sometimes wrong.
 - ▶ Protect against **adversarial inputs**
We make our (algorithm's) behavior unpredictable, so it is harder to exploit us.
- ▶ Also: *probabilistic method* for proofs
 - ▶ Goal: Prove existence of discrete object with some property
 - ▶ Idea: Design randomized algorithm to find one
 - ↪ If algorithm succeeds with prob. > 0 , object must exist!

Ramsey theory

complete graph on n vertices



Claim:

\exists monochromatic clique
of size $\geq R(n)$

$$R(n) \approx \lg n$$

Average-Case Analysis vs. Randomized Algorithms

Average-Case Analysis

- ▶ algorithm is **deterministic**
same input, same computation

Randomized Algorithm (here)

- ▶ algorithm is **not** deterministic
same input, potentially different comp.

Average-Case Analysis vs. Randomized Algorithms

Average-Case Analysis

- ▶ algorithm is **deterministic**
same input, same computation
- ▶ input is chosen according to some
probability distribution

Randomized Algorithm (here)

- ▶ algorithm is **not** deterministic
same input, potentially different comp.
- ▶ input is chosen **adversarially** (worst-case
inputs)

(
oblivious adversary
(can't see random bits)

Average-Case Analysis vs. Randomized Algorithms

Average-Case Analysis

- ▶ algorithm is **deterministic**
same input, same computation
- ▶ input is chosen according to some **probability distribution**
- ▶ cost given as expectation over inputs

Randomized Algorithm (here)

- ▶ algorithm is **not** deterministic
same input, potentially different comp.
- ▶ input is chosen **adversarially** (worst-case inputs)
- ▶ cost given as expectation over random choices of algorithm

Average-Case Analysis vs. Randomized Algorithms

Average-Case Analysis

- ▶ algorithm is **deterministic**
same input, same computation
- ▶ input is chosen according to some **probability distribution**
- ▶ cost given as expectation over inputs

Randomized Algorithm (here)

- ▶ algorithm is **not** deterministic
same input, potentially different comp.
- ▶ input is chosen **adversarially** (worst-case inputs)
- ▶ cost given as expectation over random choices of algorithm

example: sorting by first shuffle

Confusingly enough, the analysis (technique) is often the same!

But: Implications are quite different; randomization is much more versatile and robust.

7.2 Randomized Selection

Separation Example

- ▶ Before we introduce randomization more formally, let's see a successful example
- ▶ Here, not a “hard” problem, but a showcase where randomization makes something possible that is *provably*


Introductory Example – Quickselect

Selection by Rank


- ▶ **Given:** array $A[0..n)$ of numbers and number $k \in [0..n)$.
 - ▶ **Goal:** find element that would be in position k if A was sorted (k th smallest element).
- but 0-based & counting dups* (pointing to k)
- ▶ $k = \lfloor n/2 \rfloor \rightsquigarrow$ median; $k = \lfloor n/4 \rfloor \rightsquigarrow$ lower quartile
 $k = 0 \rightsquigarrow$ minimum; $k = n - \ell \rightsquigarrow \ell$ th largest


Introductory Example – Quickselect

Selection by Rank

- ▶ **Given:** array $A[0..n)$ of numbers and number $k \in [0..n)$.

- ▶ **Goal:** find element that would be in position k if A was sorted (k th smallest element).
- ▶ $k = \lfloor n/2 \rfloor \rightsquigarrow$ median; $k = \lfloor n/4 \rfloor \rightsquigarrow$ lower quartile
 $k = 0 \rightsquigarrow$ minimum; $k = n - \ell \rightsquigarrow$ ℓ th largest

```
1 procedure quickselect( $A[0..n)$ ,  $k$ ):  
2    $l := 0$ ;  $r := n$   
3   while  $r - l > 1$   
4      $b :=$  random pivot from  $A[l..r)$   
5      $j :=$  partition( $A[l..r)$ ,  $b$ )  
6     if  $j \geq k$  then  $r := j - 1$   
7     if  $j \leq k$  then  $l := j + 1$   
8   return  $A[k]$ 
```

- ▶ simple algorithm:
determine rank of random element,
recurse

 $\rightsquigarrow O(n)$ time **in expectation**
- ▶ worst case: $\Theta(n^2)$
- ▶ $O(n)$ also possible deterministically,
but algorithm is more involved


median of medians

A closer look at Selection

While all within $\Theta(n)$, we do get a strict separation for selecting the median.

Theorem 7.1 (Bent & John (1985))

Any **deterministic** comparison-based algorithm for finding the median of n elements uses at least $2n - o(n)$ comparisons in the worst case. ◀

Proof omitted.

A closer look at Selection

While all within $\Theta(n)$, we do get a strict separation for selecting the median.

Theorem 7.1 (Bent & John (1985))

Any **deterministic** comparison-based algorithm for finding the median of n elements uses at least $2n - o(n)$ comparisons in the worst case. ◀

Proof omitted.

The following weaker result is easier to see:


Theorem 7.2 (Blum et al. (1973))

Any deterministic comparison-based algorithm for finding the median of n elements uses at least $\underbrace{n-1}_{\checkmark} + \underbrace{(n-1)/2}_{\checkmark} \sim 1.5n$ comparisons in the worst case. ◀

Proof: Two types of comparisons

(1) certificate
comparisons


$n-1$



$n=11$

always necessary for correct algorithm

sorting



n elements
 $n-1$ comps

A Median Adversary

(2) "nonessential" comparisons

Proof (Theorem 7.2):

(most part of certificate)

in particular, comparisons between L and S

$m = \text{true median}$

$L = \{x : x > m\}$

$S = \{x : x < m\}$

$(|S| = |L|)$

Given a deterministic algorithm A ,
we (the adversary) try to answer
comparison queries by A in the
least useful way (for A)

Here: maintain elements in 3 sets, S , L and U (undecided)

initially all in U

query " $x \leq y$ " if x and y not in same set, answer $S < U < L$

$\left. \begin{array}{l} x, y \in S \\ x, y \in L \end{array} \right\}$ arbitrary answer

$x, y \in U$ $x < y$, put x to S , y into L

\Rightarrow created one non-essential comp for A
remove 2 elements from U

$\Rightarrow \geq \frac{n-1}{2}$ non-essential comparisons



Randomized Selection


- ▶ Can prove: Randomized Quickselect uses in expectation $\sim (2 \ln 2 + 2)n \approx 3.39n$ comparisons to find the median
- ▶ But we can do better!

Randomized Selection

- ▶ Can prove: Randomized Quickselect uses in expectation $\sim (2 \ln 2 + 2)n \approx 3.39n$ comparisons to find the median
- ▶ But we can do better!

```
1 procedure floydRivest( $A[\ell..r]$ ,  $k$ ):  
2    $n := r - \ell$   
3   if  $n < n_0$  return quickselect( $A$ ,  $k$ )  
4    $s := \frac{1}{2}n^{2/3}$  // all numbers to be rounded  
5    $sd := \frac{1}{2}\sqrt{\ln(n)s(n-s)/n}$   
6    $S[0..s] :=$  random sample from  $A$   
7    $\hat{k} := s \frac{k}{n}$   
8    $p :=$  floydRivest( $S$ ,  $\hat{k} - sd$ )  
9    $q :=$  floydRivest( $S$ ,  $\hat{k} + sd$ )  
10   $(i, j) :=$  partition  $A$  around  $p_0$  and  $p_1$   
11  if  $i == k$  return  $A[i]$   
12  if  $j == k$  return  $A[j]$   
13  if  $k < i$  return floydRivest( $A[\ell..i]$ ,  $k$ )  
14  if  $k > j$  return floydRivest( $A[j..r]$ ,  $k$ )  
15  return floydRivest( $A[i..j]$ ,  $k$ )
```

- ▶ Variant of Quickselect with huge sample
- ▶ Analysis sketch:
 - ▶ partition costs $1.5n$ comparisons



Randomized Selection

- ▶ Can prove: Randomized Quickselect uses in expectation $\sim (2 \ln 2 + 2)n \approx 3.39n$ comparisons to find the median
- ▶ But we can do better!

```
1 procedure floydRivest( $A[\ell..r]$ ,  $k$ ):  
2    $n := r - \ell$   
3   if  $n < n_0$  return quickselect( $A$ ,  $k$ )  
4    $s := \frac{1}{2}n^{2/3}$  // all numbers to be rounded  
5    $sd := \frac{1}{2}\sqrt{\ln(n)s(n-s)/n}$   
6    $S[0..s] :=$  random sample from  $A$   
7    $\hat{k} := s \frac{k}{n}$   
8    $p :=$  floydRivest( $S$ ,  $\hat{k} - sd$ )  
9    $q :=$  floydRivest( $S$ ,  $\hat{k} + sd$ )  
10   $(i, j) :=$  partition  $A$  around  $p_0$  and  $p_1$   
11  if  $i == k$  return  $A[i]$   
12  if  $j == k$  return  $A[j]$   
13  if  $k < i$  return floydRivest( $A[\ell..i]$ ,  $k$ )  
14  if  $k > j$  return floydRivest( $A[j..r]$ ,  $k$ )  
15  return floydRivest( $A[i..j]$ ,  $k$ )
```

- ▶ Variant of Quickselect with huge sample
 - ▶ Analysis sketch:
 - ▶ partition costs $1.5n$ comparisons
 - ▶ Everything on sample has cost $o(n)$
 - ▶ by the choice of parameters, with prob $1 - o(1)$:
 - (a) $i < k < j$ after partition
 - (b) $j - i = o(n)$
- \rightsquigarrow all recursive calls expected $o(n)$ cost

Randomized Selection

- ▶ Can prove: Randomized Quickselect uses in expectation $\sim (2 \ln 2 + 2)n \approx 3.39n$ comparisons to find the median
- ▶ But we can do better!

```
1 procedure floydRivest( $A[\ell..r]$ ,  $k$ ):  
2    $n := r - \ell$   
3   if  $n < n_0$  return quickselect( $A$ ,  $k$ )  
4    $s := \frac{1}{2}n^{2/3}$  // all numbers to be rounded  
5    $sd := \frac{1}{2}\sqrt{\ln(n)s(n-s)/n}$   
6    $S[0..s] :=$  random sample from  $A$   
7    $\hat{k} := s \frac{k}{n}$   
8    $p :=$  floydRivest( $S$ ,  $\hat{k} - sd$ )  
9    $q :=$  floydRivest( $S$ ,  $\hat{k} + sd$ )  
10   $(i, j) :=$  partition  $A$  around  $p_0$  and  $p_1$   
11  if  $i == k$  return  $A[i]$   
12  if  $j == k$  return  $A[j]$   
13  if  $k < i$  return floydRivest( $A[\ell..i]$ ,  $k$ )  
14  if  $k > j$  return floydRivest( $A[j..r]$ ,  $k$ )  
15  return floydRivest( $A[i..j]$ ,  $k$ )
```

▶ Variant of Quickselect with huge sample

▶ Analysis sketch:

- ▶ partition costs $1.5n$ comparisons
- ▶ Everything on sample has cost $o(n)$
- ▶ by the choice of parameters, with prob $1 - o(1)$:
 - (a) $i < k < j$ after partition
 - (b) $j - i = o(n)$

\rightsquigarrow all recursive calls expected $o(n)$ cost

\rightsquigarrow Randomized median selection with $1.5n + o(n)$ comparisons

\rightsquigarrow Separation from deterministic case!

Power of Randomness

- ▶ Selection by Rank shows two aspects of randomization:
 - ▶ A simpler algorithm by avoiding edge cases (like an initial order giving bad pivots)
 - ▶ Protection against adversarial inputs
(inputs constructed with knowledge about the algorithm)

Here randomization provably more powerful than any thinkable deterministic algorithm!

constant factor for #cmps

Power of Randomness

- ▶ Selection by Rank shows two aspects of randomization:
 - ▶ A simpler algorithm by avoiding edge cases (like an initial order giving bad pivots)
 - ▶ Protection against adversarial inputs
(inputs constructed with knowledge about the algorithm)
- Here randomization provably more powerful than any thinkable deterministic algorithm!

constant factor for #cmps

- ▶ What can we gain for (NP-)hard problems?
- ▶ But first, let's define things properly.

7.3 Recap of Probability Theory

Probability Theory

- ▶ We will quickly revisit some key terms from probability theory
 - ▶ Single place to look up notation etc.
- ▶ Much will focus on discrete probability, but some continuous tools useful, too

Probability Spaces

Discrete probability space (Ω, \mathbb{P}) :

- ▶ $\Omega = \{\omega_1, \omega_2, \dots\}$ a (finite or) *countable* set
- ▶ $\mathbb{P} : 2^\Omega \rightarrow [0, 1]$ a discrete probability measure, i. e.,
 - ▶ $\mathbb{P}[\Omega] = 1$
 - ▶ $\mathbb{P}[A] = \sum_{\omega \in A} \mathbb{P}[\omega] \rightsquigarrow \mathbb{P}$ determined by $w_i = \mathbb{P}[\omega_i]$.

fair die

$$\Omega = \left\{ \begin{array}{|c|} \hline 1 \\ \hline \end{array}, \begin{array}{|c|} \hline 2 \\ \hline \end{array}, \begin{array}{|c|} \hline 3 \\ \hline \end{array}, \begin{array}{|c|} \hline 4 \\ \hline \end{array}, \begin{array}{|c|} \hline 5 \\ \hline \end{array}, \begin{array}{|c|} \hline 6 \\ \hline \end{array} \right\}$$

$$\mathbb{P}\left[\begin{array}{|c|} \hline 1 \\ \hline \end{array}\right] = \frac{1}{6}$$

Probability Spaces

Discrete probability space (Ω, \mathbb{P}) :

- ▶ $\Omega = \{\omega_1, \omega_2, \dots\}$ a (finite or) *countable* set
- ▶ $\mathbb{P} : 2^\Omega \rightarrow [0, 1]$ a discrete probability measure, i. e.,
 - ▶ $\mathbb{P}[\Omega] = 1$
 - ▶ $\mathbb{P}[A] = \sum_{\omega \in A} \mathbb{P}[\omega] \rightsquigarrow \mathbb{P}$ determined by $w_i = \mathbb{P}[\omega_i]$.

General probability space $(\Omega, \mathcal{F}, \mathbb{P})$:

- ▶ Ω is a set of points (the universe)
- ▶ $\mathcal{F} \subseteq 2^\Omega$ is a σ -algebra, i. e., (discrete case: $\mathcal{F} = 2^\Omega$; $\Omega = \mathbb{R}$: Borel σ -algebra \mathcal{B} generated by (a, b))
 - ▶ $\emptyset \in \mathcal{F}$
 - ▶ closed under complementation: $A \in \mathcal{F} \implies \overline{A} = \Omega \setminus A \in \mathcal{F}$
 - ▶ closed under *countable* union: $A_1, A_2, \dots \in \mathcal{F} \implies \bigcup_{i=1}^{\infty} A_i \in \mathcal{F}$
- ▶ $\mathbb{P} : \mathcal{F} \rightarrow [0, 1]$ is a probability measure, i. e., ($\Omega = \mathbb{R} \rightsquigarrow$ Lebesgue measure $\lambda((a, b)) = b - a$)
 - ▶ $\mathbb{P}[\Omega] = 1$
 - ▶ If $A_1, A_2, \dots \in \mathcal{F}$ are pairwise *disjoint* then $\mathbb{P}[\bigcup_{i=1}^{\infty} A_i] = \sum_{i=1}^{\infty} \mathbb{P}[A_i]$

Events

something we can assign a probability to



$A \in \mathcal{F}$ is called an *event* of $(\Omega, \mathcal{F}, \mathbb{P})$; also a *measurable set*.

Events

something we can assign a probability to



$A \in \mathcal{F}$ is called an *event* of $(\Omega, \mathcal{F}, \mathbb{P})$; also a *measurable set*.

Basic properties

- ▶ $\mathbb{P}[\bar{A}] = 1 - \mathbb{P}[A]$ counter-probability ($\bar{A} = \Omega \setminus A$)
- ▶ $\mathbb{P}[\bigcup A_i] \leq \sum_i \mathbb{P}[A_i]$ the union bound (a.k.a. Boole's inequality a.k.a. σ -subadditivity)

Events

something we can assign a probability to



$A \in \mathcal{F}$ is called an *event* of $(\Omega, \mathcal{F}, \mathbb{P})$; also a *measurable set*.

Basic properties

- ▶ $\mathbb{P}[\bar{A}] = 1 - \mathbb{P}[A]$ counter-probability ($\bar{A} = \Omega \setminus A$)
- ▶ $\mathbb{P}[\bigcup A_i] \leq \sum_i \mathbb{P}[A_i]$ the *union bound* (a.k.a. Boole's inequality a.k.a. σ -subadditivity)
- ▶ $\{A_1, \dots, A_k\}$ (*mutually independent*) $\iff \mathbb{P}[\bigcap_i A_i] = \prod_i \mathbb{P}[A_i]$


An infinite set of events is mutually independent if every finite subset is so.

k-wise independence means that only all size- k subsets are independent.

pairwise indep. $\exists i, j \in [k] \quad \mathbb{P}[A_i \cap A_j] = \mathbb{P}[A_i] \cdot \mathbb{P}[A_j]$

\nRightarrow mutual independence

$\{A_1, A_2, A_3\}$ 2-wise indep.
but not mut. indep.



$A_i =$ edge has
2-coloring
at endpoints

Events

something we can assign a probability to

$A \in \mathcal{F}$ is called an *event* of $(\Omega, \mathcal{F}, \mathbb{P})$; also a *measurable set*.

Basic properties

- ▶ $\mathbb{P}[\bar{A}] = 1 - \mathbb{P}[A]$ counter-probability ($\bar{A} = \Omega \setminus A$)
- ▶ $\mathbb{P}[\bigcup A_i] \leq \sum_i \mathbb{P}[A_i]$ the *union bound* (a.k.a. Boole's inequality a.k.a. σ -subadditivity)

- ▶ $\{A_1, \dots, A_k\}$ (*mutually independent*) $\iff \mathbb{P}[\bigcap_i A_i] = \prod_i \mathbb{P}[A_i]$


An infinite set of events is mutually independent if every finite subset is so.

k-wise independence means that only all size- k subsets are independent.

- ▶ *conditional probability* for A given B : $\mathbb{P}[A | B] = \frac{\mathbb{P}[A \cap B]}{\mathbb{P}[B]}$
generally undefined if $\mathbb{P}[B] = 0$

- ▶ *law of total probability*: If $\Omega = B_1 \dot{\cup} B_2 \dot{\cup} \dots$ is a partition of Ω , we have

$$\mathbb{P}[A] = \sum_{\substack{i \\ \mathbb{P}[B_i] \neq 0}} \mathbb{P}[A | B_i] \cdot \mathbb{P}[B_i].$$



Random Variables

Random variables (r.v.) $X : \Omega \rightarrow \mathcal{X}$; often $\mathcal{X} = \mathbb{R}$ (in general spaces: only *measurable* functions)

für die

$$\Omega = \left\{ \begin{array}{|c|} \hline \bullet \\ \hline \end{array}, \begin{array}{|c|} \hline \bullet \bullet \\ \hline \end{array}, \begin{array}{|c|} \hline \bullet \bullet \bullet \\ \hline \end{array}, \begin{array}{|c|} \hline \bullet \bullet \bullet \bullet \\ \hline \end{array}, \begin{array}{|c|} \hline \bullet \bullet \bullet \bullet \bullet \\ \hline \end{array}, \begin{array}{|c|} \hline \bullet \bullet \bullet \bullet \bullet \bullet \\ \hline \end{array} \right\}$$

$$\mathbb{P} \left[\begin{array}{|c|} \hline \bullet \\ \hline \end{array} \right] = \frac{1}{6}$$

$$X : \Omega \rightarrow \{1, \dots, 6\}$$

$$Y : \Omega \rightarrow \{\text{even}, \text{odd}\}$$

Random Variables

Random variables (r.v.) $X : \Omega \rightarrow \mathcal{X}$; often $\mathcal{X} = \mathbb{R}$ (in general spaces: only *measurable* functions)

Basic properties and conventions:

- ▶ event $\{X = x\}$ is defined as $\{\omega \in \Omega : X(\omega) = x\}$.
- ▶ For event A define the indicator r.v. $\mathbb{1}_A$ via $\mathbb{1}_A(\omega) = [\omega \in A] = \begin{cases} 1 & \omega \in A \\ 0 & \text{else} \end{cases}$

Random Variables

Random variables (r.v.) $X : \Omega \rightarrow \mathcal{X}$; often $\mathcal{X} = \mathbb{R}$ (in general spaces: only *measurable* functions)

Basic properties and conventions:

- ▶ event $\{X = x\}$ is defined as $\{\omega \in \Omega : X(\omega) = x\}$.
- ▶ For event A define the indicator r.v. $\mathbb{1}_A$ via $\mathbb{1}_A(\omega) = [\omega \in A]$
- ▶ $F_X(x) = \mathbb{P}[X \leq x]$ is the *cumulative distribution function (CDF)*.
- ▶ X is *discrete* if $X(\Omega) = \{X(\omega) : \omega \in \Omega\}$ is countable. $\mathcal{X} = \mathbb{N}$
- ▶ for discrete r.v. X define $f_X(n) = \mathbb{P}[X = n]$ the *probability mass function (PMF)*.
- ▶ If F_X is everywhere differentiable, X is *continuous*.
Then $f_X = F'_X$ is its *probability density function*.

Random Variables

Random variables (r.v.) $X : \Omega \rightarrow \mathcal{X}$; often $\mathcal{X} = \mathbb{R}$ (in general spaces: only *measurable* functions)

Basic properties and conventions:

- ▶ event $\{X = x\}$ is defined as $\{\omega \in \Omega : X(\omega) = x\}$.
- ▶ For event A define the indicator r.v. $\mathbb{1}_A$ via $\mathbb{1}_A(\omega) = [\omega \in A]$
- ▶ $F_X(x) = \mathbb{P}[X \leq x]$ is the *cumulative distribution function (CDF)*.
- ▶ X is *discrete* if $X(\Omega) = \{X(\omega) : \omega \in \Omega\}$ is countable.
- ▶ for discrete r.v. X define $f_X(n) = \mathbb{P}[X = n]$ the *probability mass function (PMF)*.
- ▶ If F_X is everywhere differentiable, X is *continuous*.
Then $f_X = F'_X$ is its *probability density function*.

Equality in distribution:

$$X \stackrel{\mathcal{D}}{=} Y + Z$$

- ▶ We write $X \stackrel{\mathcal{D}}{=} Y$ if $F_X = F_Y$

Independent Random Variables

Independence:

- ▶ Consider *vector* $X = (X_1, \dots, X_k)$ as single function from Ω to \mathbb{R}^k .
CDF/PMF/PDF of X is called *joint CDF/PMF/PDF* of X_1, \dots, X_k .
- ▶ r.v.s *independent* \iff joint PMF/PDF *factors*:
 X and Y independent $\iff \mathbb{P}[X = x \wedge Y = y] = \mathbb{P}[X = x] \cdot \mathbb{P}[Y = y]$ for all x, y .
(Naturally follows from independent events)

Independent Random Variables

Independence:

- ▶ Consider *vector* $X = (X_1, \dots, X_k)$ as single function from Ω to \mathbb{R}^k .
CDF/PMF/PDF of X is called *joint CDF/PMF/PDF* of X_1, \dots, X_k .
- ▶ r.v.s *independent* \iff joint PMF/PDF *factors*:
 X and Y independent $\iff \mathbb{P}[X = x \wedge Y = y] = \mathbb{P}[X = x] \cdot \mathbb{P}[Y = y]$ for all x, y .
(Naturally follows from independent events)

i.i.d. sequences

- ▶ We often talk about sequences of random variables X_1, X_2, \dots
- ▶ a sequence of *i.i.d.* r.v. X_1, X_2, \dots (^{mutually}independent and identically distributed)
has $X_i \stackrel{\mathcal{D}}{=} X_1$ and $\{X_i\}_{i \geq 1}$ are mutually independent
 - ▶ typical example: sequence of coin tosses (with same coin)

Expected Values

Expectation of an \mathcal{X} -valued r.v. X , written $\mathbb{E}[X]$, is given by

► $\mathbb{E}[X] = \sum_{x \in \mathcal{X}} x \cdot f_X(x)$ for *discrete* X with PMF f_X ,

► $\mathbb{E}[X] = \int_{x \in \mathcal{X}} x \cdot f_X(x) dx$ for *continuous* X with PDF f_X .

► undefined if sum does not converge / integral does not exist.

Expected Values

Expectation of an \mathcal{X} -valued r.v. X , written $\mathbb{E}[X]$, is given by

► $\mathbb{E}[X] = \sum_{x \in \mathcal{X}} x \cdot f_X(x)$ for *discrete* X with PMF f_X ,

► $\mathbb{E}[X] = \int_{x \in \mathcal{X}} x \cdot f_X(x) dx$ for *continuous* X with PDF f_X .

► undefined if sum does not converge / integral does not exist.

Properties:

► *linearity*: $\mathbb{E}[aX + bY] = a\mathbb{E}[X] + b\mathbb{E}[Y]$ (X, Y r.v. and a, b constants)

even if X and Y are not independent

only for *finite* sums / linear combinations!

► X and Y *independent* $\implies \mathbb{E}[X \cdot Y] = \mathbb{E}[X] \cdot \mathbb{E}[Y]$.

Conditional Expectation

Similar to conditional *probability*, we can define conditional *expectations*.

- ▶ *conditional expectation* on event $\mathbb{E}[X \mid A] = \sum_x^{\mathcal{X}} \mathbb{P}[X = x \mid A]$ for *discrete* X .
for general A , continuous definition problematic
- ▶ *conditional expectation* on $\{Y = y\}$, written $\mathbb{E}[X \mid Y = y]$.
 - ▶ for *discrete* X and Y

$$\mathbb{E}[X \mid Y = y] = \sum_{x \in \mathcal{X}} x \cdot \mathbb{P}[X = x \mid \{Y = y\}]$$

Conditional Expectation

Similar to conditional *probability*, we can define conditional *expectations*.

- ▶ *conditional expectation* on event $\mathbb{E}[X \mid A] = \sum_x \mathbb{P}[X = x \mid A]$ for *discrete* X .
for general A , continuous definition problematic

- ▶ *conditional expectation* on $\{Y = y\}$, written $\mathbb{E}[X \mid Y = y]$.

- ▶ for *discrete* X and Y

$$\mathbb{E}[X \mid Y = y] = \sum_{x \in \mathcal{X}} x \cdot \mathbb{P}[X = x \mid \{Y = y\}]$$

- ▶ for *continuous* X and Y , use the joint density $f_{(X,Y)}$ and define the *marginal density* of Y as $f_Y(y) = \int_{x \in \mathcal{X}} f(x, y) dx$. Then

$$\mathbb{E}[X \mid Y = y] = \int_{\mathcal{X}} x \cdot f_{X|Y}(x, y) dx \quad \text{with} \quad f_{X|Y}(x, y) = \frac{f_{(X,Y)}(x, y)}{f_Y(y)}$$

Conditional Expectation

Similar to conditional *probability*, we can define conditional *expectations*.

- ▶ *conditional expectation* on event $\mathbb{E}[X \mid A] = \sum_x \mathbb{P}[X = x \mid A]$ for *discrete* X .
for general A , continuous definition problematic

- ▶ *conditional expectation* on $\{Y = y\}$, written $\mathbb{E}[X \mid Y = y]$.

- ▶ for *discrete* X and Y

$$\mathbb{E}[X \mid Y = y] = \sum_{x \in \mathcal{X}} x \cdot \mathbb{P}[X = x \mid \{Y = y\}]$$

- ▶ for *continuous* X and Y , use the joint density $f_{(X,Y)}$ and define the *marginal density* of Y as $f_Y(y) = \int_{x \in \mathcal{X}} f(x, y) dx$. Then

$$\mathbb{E}[X \mid Y = y] = \int_{\mathcal{X}} x \cdot f_{X|Y}(x, y) dx \quad \text{with} \quad f_{X|Y}(x, y) = \frac{f_{(X,Y)}(x, y)}{f_Y(y)}$$

- ▶ With $g(y) := \mathbb{E}[X \mid Y = y]$ we obtain a *new r.v.* $\underline{\mathbb{E}[X \mid Y]} = g(Y)$.
- ▶ *law of total expectation*: $\mathbb{E}[X] = \mathbb{E}_Y[\mathbb{E}_X[X \mid Y]]$.

Famous Distributions

discrete

- ▶ *Bernoulli r.v.* $X \stackrel{\mathcal{D}}{=} \text{B}(p) \rightsquigarrow \mathbb{P}[X = 1] = p, \mathbb{P}[X = 0] = 1 - p$
- ▶ *Binomial r.v.* $Y \stackrel{\mathcal{D}}{=} \text{Bin}(n, p) \rightsquigarrow Y = X_1 + \dots + X_n$ for X_1, \dots, X_n i.i.d. $X_i \stackrel{\mathcal{D}}{=} \text{B}(p)$
- ▶ *discrete uniform r.v.* $X \stackrel{\mathcal{D}}{=} \mathcal{U}([0..n)) \rightsquigarrow \mathbb{P}[X = i] = \frac{1}{n}$ for $i \in [0..n)$ (else 0) $\mathcal{U} \stackrel{\mathcal{D}}{=} \mathcal{U}(\{1..n\})$
- ▶ *Geometric r.v.* $X \stackrel{\mathcal{D}}{=} \text{Geo}(p) \rightsquigarrow \mathbb{P}[X = k] = (1 - p)^{k-1}p$ for $k \in \mathbb{N}_{\geq 1}$

continuous

- ▶ *continuous uniform* $X \stackrel{\mathcal{D}}{=} \mathcal{U}([0, 1)) \rightsquigarrow f_X(x) = 1$ for $x \in [0, 1)$ (else 0)

(of course there are many more)

7.4 Probabilistic Turing Machines

Model of Computation

Definition 7.3 (Probabilistic Turing Machine)


A *probabilistic Turing Machine* (PTM) $M = (Q, \Sigma, \Gamma, \delta, q_0, \square, q_{\text{halt}})$ is a deterministic TM with an additional read-only tape, filled with random bits.

The *transition function* δ takes as input

- ▶ the current state q
- ▶ the current tape symbol a
- ▶ the current *random-tape symbol* $r \in \{0, 1\}$

and outputs

- ▶ the next state q'
- ▶ the new tape symbol b
- ▶ the tape-head movement $d \in \{L, R, N\}$
- ▶ the *random-tape head movement* $d_r \in \{L, R, N\}$



Model of Computation

Definition 7.3 (Probabilistic Turing Machine)

A *probabilistic Turing Machine* (PTM) $M = (Q, \Sigma, \Gamma, \delta, q_0, \square, q_{\text{halt}})$ is a deterministic TM with an additional read-only tape, filled with random bits.

The *transition function* δ takes as input

- ▶ the current state q
- ▶ the current tape symbol a
- ▶ the current *random-tape symbol* $r \in \{0, 1\}$

and outputs

- ▶ the next state q'
- ▶ the new tape symbol b
- ▶ the tape-head movement $d \in \{L, R, N\}$
- ▶ the *random-tape head movement* $d_r \in \{L, R, N\}$

Intended semantics: random tape filled with i.i.d. $B(\frac{1}{2})$ r.v.

Randomized Computation

- ▶ *Configuration* of PTM: $(\alpha q \beta, \rho q \sigma)$
 $\alpha q \beta$ normal TM config
 $\rho \sigma$ content of random tape, with head on first bit of σ
- ▶ *computation relation* \vdash similar to TM
content of random tape unchanged, heads can move independently
- ▶ *function computed* by PTM M :
for input x and **fixed random bits** ρ , computation is deterministic:
 $M(x, \rho) = y$ if $(q_0 x, q_0 \rho) \vdash^* (q_{\text{halt}} y, \rho' q_{\text{halt}} \rho'')$

Randomized Computation

- ▶ *Configuration* of PTM: $(\alpha q \beta, \rho q \sigma)$
 $\alpha q \beta$ normal TM config
 $\rho \sigma$ content of random tape, with head on first bit of σ
- ▶ *computation relation* \vdash similar to TM
content of random tape unchanged, heads can move independently
- ▶ *function computed* by PTM M :
for input x and **fixed random bits** ρ , computation is deterministic:
 $M(x, \rho) = y$ if $(q_0 x, q_0 \rho) \vdash^* (q_{\text{halt}} y, \rho' q_{\text{halt}} \rho'')$

\rightsquigarrow *Randomized computation of PTM:*

random variable $M(x, B_0 B_1 B_2 \dots)$ where B_0, B_1, B_2, \dots are i.i.d. $B(\frac{1}{2})$ distributed

\rightsquigarrow Write $\mathbb{P}[M(x) = y] = \sum_b \mathbb{P}[B_0 B_1 \dots = b] \cdot [M(x, b) = y]$

- ▶ Hope: PTM M so that correct output computed with high probability

Warmup: Rejection Sampling

We assume only random *bits*. How to simulate, say, a fair (6-sided) die?

Warmup: Rejection Sampling

We assume only random *bits*. How to simulate, say, a fair (6-sided) die?

```
1 procedure rollDie():
2   do
3     Draw 3 random bits  $b_2, b_1, b_0$ 
4     // Interpret as binary representation of a number in  $[0..7]$ 
5      $n = \sum_{i=0}^2 2^i b_i$ 
6   while ( $n = 0 \vee n = 7$ )
7   return  $n$ 
```

Warmup: Rejection Sampling

We assume only random *bits*. How to simulate, say, a fair (6-sided) die?

```
1 procedure rollDie():
2   do
3     Draw 3 random bits  $b_2, b_1, b_0$ 
4     // Interpret as binary representation of a number in  $[0..7]$ 
5      $n = \sum_{i=0}^2 2^i b_i$ 
6     while ( $n = 0 \vee n = 7$ )
7     return  $n$ 
```

Correctness: Every output $1, \dots, 6$ equally likely by construction.

Warmup: Rejection Sampling

We assume only random *bits*. How to simulate, say, a fair (6-sided) die?

```
1 procedure rollDie():
2   do
3     Draw 3 random bits  $b_2, b_1, b_0$ 
4     // Interpret as binary representation of a number in  $[0..7]$ 
5      $n = \sum_{i=0}^2 2^i b_i$ 
6     while  $(n = 0 \vee n = 7)$ 
7     return  $n$ 
```

Correctness: Every output $1, \dots, 6$ equally likely by construction.

$$\# \text{ iterations} \stackrel{D}{=} \text{Geo}\left(\frac{3}{4}\right)$$

Termination: *Infinite* runs possible!

$$/ \quad \mathbb{E}[\text{Geo}(p)] = \frac{1}{p}$$

Expected Running Time: Leave loop with probability $\frac{6}{8} = \frac{3}{4}$ in each iteration

\rightsquigarrow in expectation, only $\frac{4}{3} = \sum_{i \geq 1} i \cdot \left(\frac{1}{4}\right)^{i-1} \frac{3}{4}$ repetitions.

rollDie is a correct and practically efficient algorithm.

What can go wrong?

What can go wrong in a randomized computation?

- ▶ Computation could run into a deterministic infinite loop (as for deterministic TM)
 - ⚡ don't ever terminate, no output
 - ↪ Clearly don't want that (just as before)
(annoyingly undecidable to check . . . also just as before)

What can go wrong?

What can go wrong in a randomized computation?

- ▶ Computation could run into a deterministic infinite loop (as for deterministic TM)

- ⚡ don't ever terminate, no output

- ↪ Clearly don't want that (just as before)

- (annoyingly undecidable to check ... also just as before)

- ▶ Computation could repeatedly have branches that keep looping (as for rollDie)

- ↪ For every t , there is a probability $p > 0$ to run for more than t time steps

- ▶ This is a new option that deterministic TMs didn't have
... but nondeterministic TMs did, and we just defined running time to be ∞ there!

So, is that a problem? Or is it not??

Random Termination

Key question: What is the probability space for the running time of the PTM simulating rollDie?

► Note: this could indeed be a problem.

► $\{0, 1\}^*$ (the set of **finite** bitstrings) is countably infinite (=discrete)


► But the set of *infinite strings* (ω -language) is not!

$\{0, 1\}^\omega = \{b_0 b_1 \dots : b_i \in \{0, 1\}\} = \{b : b : \mathbb{N}_0 \rightarrow \{0, 1\}\}$ surjectively maps to $[0, 1) \subset \mathbb{R}$

$b \mapsto 0.b_0 b_1 b_2 \dots$

Random Termination

Key question: What is the probability space for the running time of the PTM simulating rollDie?

- ▶ Note: this could indeed be a problem.
 - ▶ $\{0, 1\}^*$ (the set of **finite** bitstrings) is countably infinite (=discrete)
 - ▶ But the set of *infinite strings* (ω -language) is not!
 $\{0, 1\}^\omega = \{b_0 b_1 \dots : b_i \in \{0, 1\}\} = \{b : b : \mathbb{N}_0 \rightarrow \{0, 1\}\}$ surjectively maps to $[0, 1) \subset \mathbb{R}$

 $b \mapsto 0.b_0 b_1 b_2 \dots$
- ▶ Config $(\alpha q \beta, \rho q \sigma)$ for PTM needs $\sigma \in \{0, 1\}^\omega$ in general

Random Termination

Key question: What is the probability space for the running time of the PTM simulating rollDie?

- ▶ Note: this could indeed be a problem.
 - ▶ $\{0, 1\}^*$ (the set of **finite** bitstrings) is countably infinite (=discrete)
 - ▶ But the set of **infinite strings** (ω -language) is not!
 $\{0, 1\}^\omega = \{b_0 b_1 \dots : b_i \in \{0, 1\}\} = \{b : b : \mathbb{N}_0 \rightarrow \{0, 1\}\}$ surjectively maps to $[0, 1) \subset \mathbb{R}$
 $b \mapsto 0.b_0 b_1 b_2 \dots$
- ▶ Config $(\alpha q \beta, \rho q \sigma)$ for PTM needs $\sigma \in \{0, 1\}^\omega$ in general
- ▶ Define the random variable $Time_M(x) \in \mathbb{N}_0 \cup \{\infty\}$ on the *Bernoulli probability space*
 - ▶ generators: $\{\pi_x : x \in \{0, 1\}^*\}$ where $\pi_x = \{xw : w \in \{0, 1\}^\omega\} \subseteq \{0, 1\}^\omega$
 - ▶ Bernoulli σ -algebra: smallest \mathcal{F} containing all $\{\pi_x\}_x$ that is closed under countable union and complement
 - ▶ $\mathbb{P}[\pi_x] = 2^{-|x|}$

rollDie terminates iff $\rho \in T \subseteq \{0, 1\}^\omega$ $\mathbb{P}[T]$

Random Termination

Key question: What is the probability space for the running time of the PTM simulating rollDie?

- ▶ Note: this could indeed be a problem.
 - ▶ $\{0, 1\}^*$ (the set of **finite** bitstrings) is countably infinite (=discrete)
 - ▶ But the set of *infinite strings* (ω -language) is not!
 $\{0, 1\}^\omega = \{b_0 b_1 \dots : b_i \in \{0, 1\}\} = \{b : b : \mathbb{N}_0 \rightarrow \{0, 1\}\}$ surjectively maps to $[0, 1) \subset \mathbb{R}$
 $b \mapsto 0.b_0 b_1 b_2 \dots$
- ▶ Config $(\alpha q \beta, \rho q \sigma)$ for PTM needs $\sigma \in \{0, 1\}^\omega$ in general
- ▶ Define the random variable $Time_M(x) \in \mathbb{N}_0 \cup \{\infty\}$ on the *Bernoulli probability space*
 - ▶ generators: $\{\pi_x : x \in \{0, 1\}^*\}$ where $\pi_x = \{xw : w \in \{0, 1\}^\omega\} \subseteq \{0, 1\}^\omega$
 - ▶ Bernoulli σ -algebra: smallest \mathcal{F} containing all $\{\pi_x\}_x$ that is closed under countable union and complement
 - ▶ $\mathbb{P}[\pi_x] = 2^{-|x|}$

\rightsquigarrow expectations over $\rho \in \{0, 1\}^\omega$, the infinite initial random-bit tape input are well-defined

(Expected) Time

Definition 7.4 (PTM running time)

For a PTM M , we define $time_M(x)$ as for nondeterministic TMs as the supremum of time steps over all computations. worst case

Moreover, we define the *expected time* as

$$time_{nondet}() = \infty$$

$$\mathbb{E}\text{-}time_M(x) = \mathbb{E}[time_M(x)] = \mathbb{E}_{\rho}[\inf\{t \in \mathbb{N}_0 : (q_0x, q_0\rho) \vdash^t (q_{halt}y, \rho'q_{halt}\rho'')\}]$$

\uparrow
random

Similarly

$$\mathbb{E}\text{-}Time_M(n) = \sup\{\mathbb{E}\text{-}time_M(x) : x \in \Sigma^n\}$$



(Expected) Time

Definition 7.4 (PTM running time)

For a PTM M , we define $time_M(x)$ as for nondeterministic TMs as the supremum of time steps over all computations.

Moreover, we define the *expected time* as

$$\mathbb{E}\text{-}time_M(x) = \mathbb{E}[time_M(x)] = \mathbb{E}_\rho \left[\inf \{ t \in \mathbb{N}_0 : (q_0 x, q_0 \rho) \vdash^t (q_{\text{halt}} y, \rho' q_{\text{halt}} \rho'') \} \right]$$

Similarly

$$\mathbb{E}\text{-}Time_M(n) = \sup \{ \mathbb{E}\text{-}time_M(x) : x \in \Sigma^n \}$$

- ▶ We can of course also study full distribution of $time_M(x)$
- ▶ Useful property of expected time:
 $\mathbb{E}\text{-}time_M(x) < \infty \quad \text{iff} \quad \mathbb{P}[time_M(x) = \infty] = 0$

A New Complexity Measure: Random Bits

Definition 7.5 (Random-bit complexity)

For a PTM M computing with input alphabet Σ , the *random-bit cost* for an input $x \in \Sigma^*$ is denote by

$$random_M(x) = \sup\{|\rho'| : (xq_0, q_0\rho) \vdash^* (\alpha q\beta, \rho'q\rho'') \vdash^* (q_{\text{halt}}y, \rho'q_{\text{halt}}\rho'')\}$$

and similarly

$$Random_M(n) = \sup\{random_M(x) : x \in \Sigma^n\}.$$

Further, the *expected random-bit cost* are defined as

$\mathbb{E}\text{-}random_M(x) = \mathbb{E}_\rho[random_M(x)]$ and

$\mathbb{E}\text{-}Random_M(n) = \sup\{\mathbb{E}\text{-}random_M(x) : x \in \Sigma^n\}$



Randomization vs. Nondeterminism

- ▶ Superficially similar concepts
- ▶ Key difference: meaning of number of computations of TM
 - ▶ nondeterministic TM: accept if **some (single)** accepting computation is possible
 - ▶ randomized TM: accept if **most** possible computations are accepting
- ↪ nondeterminism = purely theoretical construction (overly powerful yardstick)
- ▶ randomization = widely applied efficient design technique

7.5 Classification of Randomized Algorithms

Las Vegas

Consider here the general problem to compute some *function* $f : \Sigma^* \rightarrow \Gamma^*$.

\leadsto Covers *decision problems* $L \subseteq \Sigma^*$ by setting $\Gamma = \{0, 1\}$ and $f(w) = \begin{cases} 1 & w \in L \\ 0 & w \notin L \end{cases}$

Las Vegas

Consider here the general problem to compute some *function* $f : \Sigma^* \rightarrow \Gamma^*$.

\leadsto Covers *decision problems* $L \subseteq \Sigma^*$ by setting $\Gamma = \{0, 1\}$ and $f(w) = \begin{cases} 1 & w \in L \\ 0 & w \notin L \end{cases}$

Definition 7.6 (Las Vegas Algorithm)

A randomized algorithm A is a *Las-Vegas (LV) algorithm* for a problem $f : \Sigma^* \rightarrow \Gamma^*$ if for all $x \in \Sigma^*$ holds

- (a) $\mathbb{P}[time_A(x) < \infty] = 1$ (*terminate almost surely*)
- (b) $A(x) \in \{f(x), \boxed{?}\}$ (answer always *correct* or “*don't know*”)
- (c) $\mathbb{P}[A(x) = f(x)] \geq \frac{1}{2}$ (*correct half the time*)



Don't Know vs. Won't Terminate

Theorem 7.7 (Don't know don't needed)

Every Las Vegas algorithm A for $f : \Sigma^* \rightarrow \Gamma^*$ can be transformed into a randomized algorithm B for f so that for all $x \in \Sigma^*$ holds

(a) $\mathbb{P}[B(x) = f(x)] = 1$ (always correct)

(b) $\mathbb{E}\text{-time}_B(x) \leq 2 \cdot \text{time}_A(x)$

(can never output $\boxed{?}$, not "just"
almost surely)



Don't Know vs. Won't Terminate

Theorem 7.7 (Don't know don't needed)

Every Las Vegas algorithm A for $f : \Sigma^* \rightarrow \Gamma^*$ can be transformed into a randomized algorithm B for f so that for all $x \in \Sigma^*$ holds

(a) $\mathbb{P}[B(x) = f(x)] = 1$ (always correct)

(b) $\mathbb{E}\text{-time}_B(x) \leq 2 \cdot \text{time}_A(x)$

Proof:

See exercises.



Don't Know vs. Won't Terminate

Theorem 7.7 (Don't know don't needed)

Every Las Vegas algorithm A for $f : \Sigma^* \rightarrow \Gamma^*$ can be transformed into a randomized algorithm B for f so that for all $x \in \Sigma^*$ holds

(a) $\mathbb{P}[B(x) = f(x)] = 1$ (always correct)

(b) $\mathbb{E}\text{-time}_B(x) \leq 2 \cdot \text{time}_A(x)$

Proof:

See exercises.

Theorem 7.8 (Termination Enforcible)

Every randomized algorithm B for $f : \Sigma^* \rightarrow \Gamma^*$ with $\mathbb{P}[B(x) = f(x)] = 1$ can be transformed into a Las Vegas algorithm A for f so that for all $x \in \Sigma^*$ holds

(a) $\mathbb{P}[A(x) = f(x)] \geq \frac{1}{2}$

(b) $\text{time}_A(x) \leq 2 \cdot \mathbb{E}\text{-time}_B(x)$ (always terminates).

Don't Know vs. Won't Terminate

Theorem 7.7 (Don't know don't needed)

Every Las Vegas algorithm A for $f : \Sigma^* \rightarrow \Gamma^*$ can be transformed into a randomized algorithm B for f so that for all $x \in \Sigma^*$ holds

(a) $\mathbb{P}[B(x) = f(x)] = 1$ (always correct)

(b) $\mathbb{E}\text{-time}_B(x) \leq 2 \cdot \text{time}_A(x)$

Proof:

See exercises.

Theorem 7.8 (Termination Enforcible)

Every randomized algorithm B for $f : \Sigma^* \rightarrow \Gamma^*$ with $\mathbb{P}[B(x) = f(x)] = 1$ can be transformed into a Las Vegas algorithm A for f so that for all $x \in \Sigma^*$ holds

(a) $\mathbb{P}[A(x) = f(x)] \geq \frac{1}{2}$

(b) $\text{time}_A(x) \leq 2 \cdot \mathbb{E}\text{-time}_B(x)$ (always terminates).

Proof:

See exercises.

Las Vegas Variants

↪ Can trade *expected* time bound for *worst-case* bound by *allowing “don’t know”* and *vice versa!*

Both types are called commonly LV algorithms; where helpful, we distinguish:

(A) *Always-Decisive Las Vegas algorithms* (output of Theorem 7.7)

(B) *Always-Terminating Las Vegas algorithms* (output of Theorem 7.8)

Las Vegas Examples

rollDie by rejection sampling is Las Vegas of unbounded worst-case type.

Easy to transform into Las Vegas according to Definition 7.6:

```
1 procedure rollDieLasVegas:
2   Draw 3 random bits  $b_2, b_1, b_0$ 
3    $n = \sum_{i=0}^2 2^i b_i$  // Interpret as binary representation of a number in  $[0 : 7]$ 
4   if ( $n = 0 \vee n = 7$ )
5     return ?
6   else
7     return  $n$ 
```

Other famous examples: (randomized) *Quicksort* and *Quickselect*

- ▶ always correct *and*
- ▶ $\text{time}(n) = O(n^2) < \infty$
- ▶ much better average:
 - ▶ $\mathbb{E}\text{-time}_{\text{QSort}}(n) = \Theta(n \log n)$
 - ▶ $\mathbb{E}\text{-time}_{\text{QSelect}}(n) = \Theta(n)$

To Err is Algorithmic

Sometimes sensible to allow *wrong / imprecise* answers . . .
but random should not mean *arbitrary*!

To Err is Algorithmic

Sometimes sensible to allow *wrong / imprecise* answers ...
but random should not mean *arbitrary*!

Definition 7.9 (Monte Carlo Algorithm)

A randomized algorithm A is a *Monte Carlo algorithm* for $f : \Sigma^* \rightarrow \Gamma^*$

- ▶ with *bounded error* if $\exists \varepsilon > 0 \forall x \in \Sigma^* : \mathbb{P}[A(x) = f(x)] \geq \frac{1}{2} + \varepsilon$.
- ▶ with *unbounded error* if $\forall x \in \Sigma^* : \mathbb{P}[A(x) = f(x)] > \frac{1}{2}$.



To Err is Algorithmic

Sometimes sensible to allow *wrong / imprecise* answers ...
but random should not mean *arbitrary*!

Definition 7.9 (Monte Carlo Algorithm)

A randomized algorithm A is a *Monte Carlo algorithm* for $f : \Sigma^* \rightarrow \Gamma^*$

- ▶ with bounded error if $\exists \varepsilon > 0 \forall x \in \Sigma^* : \mathbb{P}[A(x) = f(x)] \geq \frac{1}{2} + \varepsilon$.
- ▶ with unbounded error if $\forall x \in \Sigma^* : \mathbb{P}[A(x) = f(x)] > \frac{1}{2}$.

Seems like a minuscule difference? We will see it is vital!

7.6 Tail Inequalities and Concentration Bounds

How To Summarize A Random Variable?


- ▶ running time of randomized algorithm is a **random variable**
 - ▶ For two randomized algorithms A and B , we'd like to decide which is better
Whether A is faster than B is also random.
- ↪ need a way to **compare** random variables!

How To Summarize A Random Variable?

- ▶ running time of randomized algorithm is a **random variable**
 - ▶ For two randomized algorithms A and B , we'd like to decide which is better
Whether A is faster than B is also random.
- ⇒ need a way to **compare** random variables!

- ▶ One option: *stochastic dominance*

- ▶ If $\forall t : \mathbb{P}[time_A(x) \geq t] \geq \mathbb{P}[time_B(x) \geq t]$,
we say $time_A(x)$ (weakly) stochastically dominates $time_B(x)$ (on input x)
- ▶ Would rather use B then!



How To Summarize A Random Variable?

- ▶ running time of randomized algorithm is a **random variable**
- ▶ For two randomized algorithms A and B , we'd like to decide which is better
Whether A is faster than B is also random.

↪ need a way to **compare** random variables!

- ▶ One option: *stochastic dominance*
 - ▶ If $\forall t : \mathbb{P}[\text{time}_A(x) \geq t] \geq \mathbb{P}[\text{time}_B(x) \geq t]$,
we say $\text{time}_A(x)$ (weakly) stochastically dominates $\text{time}_B(x)$ (on input x)
 - ▶ Would rather use B then!
- 👎 dominance rarely true for real algorithms
- 👎 no prediction of running time / comparison with explicit bound

How To Summarize A Random Variable?


- ▶ running time of randomized algorithm is a **random variable**
- ▶ For two randomized algorithms A and B , we'd like to decide which is better
Whether A is faster than B is also random.


↪ need a way to **compare** random variables!

- ▶ One option: *stochastic dominance*


- ▶ If $\forall t : \mathbb{P}[\text{time}_A(x) \geq t] \geq \mathbb{P}[\text{time}_B(x) \geq t]$,
we say $\text{time}_A(x)$ (weakly) stochastically dominates $\text{time}_B(x)$ (on input x)


- ▶ Would rather use B then!

-  dominance rarely true for real algorithms

-  no prediction of running time / comparison with explicit bound

↪ look at **expected value** $\mathbb{E}\text{-time}(x)$ (randomized version of average case)

-  simple (one number); reflects typical case

-  not always reliable / representative

When Expectation Isn't Enough

- ▶ Two hypothetical algorithms:
 - ▶ A takes 1 step in half the cases and 3 steps otherwise
 - ▶ B takes 1 step in 99% of cases and **101** steps otherwise
- ↪ both have $\mathbb{E}\text{-time}(x) = 2$
- ▶ probably want $A \dots$ certainly would want to be able to distinguish them!

When Expectation Isn't Enough

- ▶ Two hypothetical algorithms:
 - ▶ A takes 1 step in half the cases and 3 steps otherwise
 - ▶ B takes 1 step in 99% of cases and **101** steps otherwise
 - ↪ both have $\mathbb{E}\text{-time}(x) = 2$
 - ▶ probably want $A \dots$ certainly would want to be able to distinguish them!
- ▶ **Goal:** Strengthen algorithms so $\text{time}(x)$ rarely far from $\mathbb{E}\text{-time}(x)$
 - ▶ formally: bound probability that X (far) exceeds $\mathbb{E}[X]$
 - ↪ *concentration bounds* a.k.a. *tail inequalities*
 - 👍 can then compare these typical times again
 - 👍 also obtain more reliable algorithms
 - ↪ Let's establish some tools for that!

With High Probability

⚠ not always the same definition

Definition 7.10 (With high probability)

We say

- ▶ an event $X = X(n)$ happens *with high probability (w.h.p.)* when $\forall c : \mathbb{P}[X(n)] = 1 \pm O(n^{-c})$ as $n \rightarrow \infty$.
- ▶ a random variable $X = X(n)$ is in $O(f(n))$ with high probability (w.h.p.) when $\forall c \exists d : \mathbb{P}[X \leq df(n)] = 1 \pm O(n^{-c})$ as $n \rightarrow \infty$.
(This means, the constant in $O(f(n))$ may depend on c .)

With High Probability

Definition 7.10 (With high probability)

We say

- ▶ an event $X = X(n)$ happens *with high probability (w.h.p.)* when
 $\forall c : \mathbb{P}[X(n)] = 1 \pm O(n^{-c})$ as $n \rightarrow \infty$.
- ▶ a random variable $X = X(n)$ is *in* $O(f(n))$ *with high probability (w.h.p.)* when
 $\forall c \exists d : \mathbb{P}[X \leq df(n)] = 1 \pm O(n^{-c})$ as $n \rightarrow \infty$.
(This means, the constant in $O(f(n))$ may depend on c .)

- ▶ Very strong notion: failure probability smaller than any polynomial

\rightsquigarrow If A succeeds w.h.p. then also polynomially many repetitions of A succeed w.h.p.

Lemma 7.11 (Repetitions w.h.p.)

Suppose A is an algorithm that w.h.p. does not fail.

In n^d independent repetitions of A on inputs of size n , w.h.p. no repetition fails.

With High Probability [2]

- an event $X = X(n)$ happens *with high probability (w.h.p.)* when $\forall c : \mathbb{P}[X(n)] = 1 \pm O(n^{-c})$ as $n \rightarrow \infty$.

Proof (Lemma 7.11):

Let c from the definition of w.h.p. be given.

$$\mathcal{F}_i \equiv \text{if } A \text{ fails} \quad B = \bigcup_{i=1}^n A_i \quad \text{claim: } \overline{B} \text{ w.h.p.}$$

\rightsquigarrow events that happen with high probability can be combined

With High Probability [2]

Proof (Lemma 7.11):

Let c from the definition of w.h.p. be given.

The event F_i that the i th run of A fails happens with probability $O(n^{-(c+d)})$ by definition.

▪
▪
▪
▪
▪
▪
▪
▪
▪
▪

\rightsquigarrow events that happen with high probability can be combined

With High Probability [2]


Proof (Lemma 7.11):

Let c from the definition of w.h.p. be given.

The event F_i that the i th run of A fails happens with probability $O(n^{-(c+d)})$ by definition.

Then $\mathbb{P}[\cup_{i=1}^{n^d} F_i]$

\rightsquigarrow events that happen with high probability can be combined



With High Probability [2]

Proof (Lemma 7.11):

Let c from the definition of w.h.p. be given.

The event F_i that the i th run of A fails happens with probability $O(n^{-(c+d)})$ by definition.

$$\text{Then } \mathbb{P}[\cup_{i=1}^{n^d} F_i] \leq \sum_{i=1}^{n^d} \mathbb{P}[F_i]$$

union bound

\rightsquigarrow events that happen with high probability can be combined



With High Probability [2]

Proof (Lemma 7.11):

Let c from the definition of w.h.p. be given.

The event F_i that the i th run of A fails happens with probability $O(n^{-(c+d)})$ by definition.

$$\text{Then } \mathbb{P}[\cup_{i=1}^{n^d} F_i] \leq \sum_{i=1}^{n^d} \mathbb{P}[F_i] = n^d \cdot O(n^{-(c+d)})$$

\rightsquigarrow events that happen with high probability can be combined



With High Probability [2]

Proof (Lemma 7.11):

Let c from the definition of w.h.p. be given.

The event F_i that the i th run of A fails happens with probability $O(n^{-(c+d)})$ by definition.

$$\text{Then } \mathbb{P}[\cup_{i=1}^{n^d} F_i] \leq \sum_{i=1}^{n^d} \mathbb{P}[F_i] = n^d \cdot O(n^{-(c+d)}) = O(n^{-c}).$$

\rightsquigarrow events that happen with high probability can be combined

Concentration I – Markov's Inequality

Theorem 7.12 (Markov's Inequality)

Let $X \in \mathbb{R}_{\geq 0}$ be a r.v. that assumes only weakly positive values. Then holds

$$\forall a > 0 : \mathbb{P}[X \geq a] \leq \frac{\mathbb{E}[X]}{a}$$

Proof: Let $a > 0$ given, define $I := \mathbb{1}_{\{X \geq a\}} = [X \geq a] = \begin{cases} 1 & X \geq a \\ 0 & X < a \end{cases}$

$$I \leq \frac{X}{a} \quad \begin{array}{l} \text{if } X \geq a \leadsto I=1 \text{ and } \frac{X}{a} \geq 1 \quad \checkmark \\ \text{if } X < a \leadsto I=0 \text{ and } X \geq 0 \leadsto \frac{X}{a} \geq 0 \quad \checkmark \end{array}$$

take \mathbb{E} \nearrow

$$\frac{\mathbb{E}[X]}{a} \geq \mathbb{E}[I] = \mathbb{P}[X \geq a]$$



Since $X \geq 0$ implies $\mathbb{E}[X] \geq 0$, nicer equivalent form: $\forall a > 0 : \mathbb{P}[X \geq a\mathbb{E}[X]] \leq \frac{1}{a}$

Mnemonic: With probability at least $\frac{1}{a}$, won't exceed expectation by a factor a .

Markov's Inequality Visually

If $X \in \mathbb{N}_0$, we can visualize Markov's Inequality nicely.

Recall: $X \in \mathbb{N}_0$ implies $\mathbb{E}[X] = \sum_{n=0}^{\infty} n \cdot \mathbb{P}[X = n] = \sum_{n=0}^{\infty} \mathbb{P}[X \geq n]$.



Moments

- ▶ Markov's Inequality is tight (for some r.v.), but not usually a strong concentration result.
- ▶ but we can apply it to $f(X)$ for any (positive) *function* of X !

Moments

- ▶ Markov's Inequality is tight (for some r.v.), but not usually a strong concentration result.
- ▶ but we can apply it to $f(X)$ for any (positive) *function* of X !

Towards this, we consider moments of r.v.:

Definition 7.13 (Moments, variance, standard deviation)

For a random variable $X \in \mathbb{R}$,

- ▶ $\mathbb{E}[X^k]$ is the *kth moment* of X . $\mathbb{E}[X]$ 1st moment
- ▶ $\mathbb{E}[|X - \mathbb{E}[X]|^k]$ is the *kth centered moment* of X .
- ▶ The *variance* of X is the second centered moment: $\text{Var}[X] = \mathbb{E}[(X - \mathbb{E}[X])^2]$
- ▶ The *standard deviation* of X is $\sigma[X] = \sqrt{\text{Var}[X]}$. ◀

Note: None of the moments is guaranteed to exist!

Concentration II – Chebychev's Inequality

Using second moments, we obtain a stronger concentration inequality.

Theorem 7.14 (Chebychev's Inequality)

Let X be a random variable. We have

$$\forall a > 0 : \mathbb{P}[|X - \mathbb{E}[X]| \geq a] \leq \frac{\text{Var}[X]}{a^2}.$$

Proof: Apply Markov to $Y = (X - \mathbb{E}[X])^2$

$$\mathbb{P}[Y \geq b] \leq \frac{\mathbb{E}[Y]}{b}$$
$$\mathbb{P}[Y \geq b] = \mathbb{P}[(X - \mathbb{E}[X])^2 \geq b] = \mathbb{P}[|X - \mathbb{E}[X]| \geq \sqrt{b}] \leq \frac{\mathbb{E}[Y]}{b} = \frac{\text{Var}[X]}{a^2}$$

↑
take $\sqrt{}$ on
both sides

Convergence in Probability

Corollary 7.15 (Chebychev Concentration)

Let X_1, X_2, \dots be a sequence of random variables and assume

► $\mathbb{E}[X_n]$ and $\text{Var}[X_n]$ exist for all n and

► $\sigma[X_n] = o(\mathbb{E}[X_n])$ as $n \rightarrow \infty$.

Then holds

$$\forall \varepsilon > 0 : \mathbb{P} \left[\left| \frac{X_n}{\mathbb{E}[X_n]} - 1 \right| \geq \varepsilon \right] \rightarrow 0 \quad (n \rightarrow \infty).$$

This means $\frac{X_n}{\mathbb{E}[X_n]}$ *converges in probability* to 1.

Convergence in Probability

Corollary 7.15 (Chebychev Concentration)

Let X_1, X_2, \dots be a sequence of random variables and assume

- ▶ $\mathbb{E}[X_n]$ and $\text{Var}[X_n]$ exist for all n and
- ▶ $\sigma[X_n] = o(\mathbb{E}[X_n])$ as $n \rightarrow \infty$.

Then holds

$$\forall \varepsilon > 0 : \mathbb{P} \left[\left| \frac{X_n}{\mathbb{E}[X_n]} - 1 \right| \geq \varepsilon \right] \rightarrow 0 \quad (n \rightarrow \infty).$$

This means $\frac{X_n}{\mathbb{E}[X_n]}$ *converges in probability* to 1.

We're getting there, but this is still a far cry from our "with high probability"!
(superpolynomial convergence rate in above limit)

Concentration III – Chernoff Bounds

Stronger concentration inequalities require more assumptions on distribution of X .
A classical one is that X consists of many **small and independent** parts.

Concentration III – Chernoff Bounds

Stronger concentration inequalities require more assumptions on distribution of X .

A classical one is that X consists of many **small and independent** parts.

Theorem 7.16 (Chernoff Bound for Bernoulli trials)

Let $X_1, \dots, X_n \in \{0, 1\}$ be *(mutually) independent* with $X_i \stackrel{\mathcal{D}}{=} B(p_i)$.

Define $\underline{X} = X_1 + \dots + X_n$ and $\mu = \mathbb{E}[X_1] + \dots + \mathbb{E}[X_n] = p_1 + \dots + p_n$. Then holds

$$(1) \quad \forall \delta > 0 : \mathbb{P}[X \geq (1 + \delta)\mu] < \left(\frac{e^\delta}{(1 + \delta)^{1 + \delta}} \right)^\mu$$

$$(2) \quad \forall \delta \in (0, 1] : \mathbb{P}[X \geq (1 + \delta)\mu] \leq \exp(-\mu\delta^2/3)$$

$$\delta = 1 \quad \frac{e}{2^2} = \frac{e}{4} < \frac{1}{2}$$

Proof: Again Markov... Let $t > 0$
 $e^{t \cdot}$ on both sides
 $(1) \Rightarrow (2)$
 $Y = e^{t \cdot X} \geq 0$

$$Y_i = e^{t X_i}$$

X_1, \dots, X_n unabh. indep.

$$\mathbb{P}[X \geq (1 + \delta)\mu] \stackrel{e^{t \cdot} \text{ on both sides}}{\leq} \mathbb{P}[Y \geq e^{t(1 + \delta)\mu}] \stackrel{\text{Markov}}{\leq} \frac{\mathbb{E}[Y]}{e^{t(1 + \delta)\mu}}$$

$$\mathbb{E}[Y] = \mathbb{E}[e^{t \cdot X}] = \mathbb{E}[e^{t \sum_{i=1}^n X_i}] = \mathbb{E}\left[\prod_{i=1}^n e^{t \cdot X_i}\right] = \prod_{i=1}^n \mathbb{E}[e^{t X_i}]$$


Concentration III – Chernoff Bounds [2]

Proof (cont.):

$$\begin{aligned}\mathbb{E}[e^{tX_i}] &= 1 \cdot \mathbb{P}\{X_i=0\} + e^t \mathbb{P}\{X_i=1\} \\ &= (1-p_i) + e^t p_i\end{aligned}$$

$$\begin{aligned}\mathbb{E}[Y] &= \prod_{i=1}^n \left(\underbrace{1 + p_i (e^t - 1)}_{\leq e^{p_i(e^t - 1)}} \right) \\ &\leq \exp\left(\sum_{i=1}^n p_i (e^t - 1)\right) \\ &= \exp\left((e^t - 1) \underbrace{\sum p_i}_{= \mu}\right) \quad (*)\end{aligned}$$

$$\begin{aligned}\mathbb{E}[X \geq (1+\delta)\mu] &\leq \frac{\mathbb{E}[Y]}{e^{t(1+\delta)\mu}} \quad (t > 0) \\ &\leq \frac{e^{\mu(e^t - 1)}}{e^{\mu t(1+\delta)}} = \frac{(e^{e^t - 1})^\mu}{(e^{t(1+\delta)})^\mu}\end{aligned}$$



$$\text{with } t = \ln(1+s) > 0$$

$$= \frac{e^{\mu(1+s)-1}}{(1+s)^{\mu(1+s)}} = \left(\frac{e^s}{(1+s)^{1+s}} \right)^{\mu}$$

□

Chernoff Bound for Binomial Distribution

The algorithmically most widely used special case has identical coin flips.

Corollary 7.17 (Chernoff Bound for Binomial Distribution)

Let $X \stackrel{\mathcal{D}}{=} \text{Bin}(n, p)$. Then

$$\forall \delta \geq 0 \quad : \quad \mathbb{P} \left[\left| \frac{X}{n} - p \right| \geq \delta \right] \leq 2 \exp(-2\delta^2 n)$$

\rightsquigarrow $\boxed{\text{Bin}(n, p) \in np \pm n^{0.501} \text{ w.h.p.}}$