



5

Parameterized Hardness

27 May 2025

Prof. Dr. Sebastian Wild

5 Parameterized Hardness

- 5.1 Parameterized Reductions
- 5.2 Nondeterministic FPT: Para-NP
- 5.3 Bounded Nondeterminism: $W[P]$
- 5.4 Tail-nondeterministic NRAM

How to prove \notin FPT?

- For some problems, no algorithm seems to achieve fpt running time

How to prove \notin FPT?

- ▶ For some problems, no algorithm seems to achieve fpt running time
 - ▶ example: p -CLIQUE
- \rightsquigarrow maybe no fpt algorithm can exist for p -CLIQUE!

How to prove \notin FPT?

► For some problems, no algorithm seems to achieve fpt running time

► example: p -CLIQUE

\rightsquigarrow maybe no fpt algorithm can exist for p -CLIQUE!

► **Problem:** Certainly exists in case $P = NP$

\rightsquigarrow strongest lower bound we can hope for will have to be conditional on $P \neq NP$

How to prove \notin FPT?

► For some problems, no algorithm seems to achieve fpt running time

► example: p -CLIQUE

\rightsquigarrow maybe no fpt algorithm can exist for p -CLIQUE!

► **Problem:** Certainly exists in case $P = NP$

\rightsquigarrow strongest lower bound we can hope for will have to be conditional on $P \neq NP$

► Typical complexity-theory results:

No algorithm has property X unless (more or less widely believed) complexity hypothesis Y fails.

5.1 Parameterized Reductions

FPT Reductions

Goal: Compare relative hardness of *parameterized* problems

⇒ Need a notion of reductions on parameterized problems

► to preserve (non)existence of fpt algorithms, need to keep small k

FPT Reductions

Goal: Compare relative hardness of *parameterized* problems

↪ Need a notion of reductions on parameterized problems

► to preserve (non)existence of fpt algorithms, need to keep small k

Definition 5.1 (Parameterized Reduction)

Let (L_1, κ_1) and (L_2, κ_2) be two parameterized problems (over alphabets Σ_1 resp. Σ_2).

An *fpt-reduction* (*fpt many-one reduction*) from (L_1, κ_1) to (L_2, κ_2) is a mapping $A : \Sigma_1^* \rightarrow \Sigma_2^*$ so that for all $x \in \Sigma_1^*$

1. (equivalence) $x \in L_1 \iff A(x) \in L_2$,
2. (fpt) A is computable by an fpt-algorithm (w.r.t. to κ_1), and
3. (parameter-preserving) $\kappa_2(A(x)) \leq g(\kappa_1(x))$ for a computable function $g : \mathbb{N} \rightarrow \mathbb{N}$.

(
does not depend $|x|$)

We then write $(L_1, \kappa_1) \leq_{\text{fpt}} (L_2, \kappa_2)$.

$$L_1 \leq_p L_2$$

Not all reductions are fpt


Many reductions from classical complexity theory are **not** parameter preserving.

Recall:

VERTEXCOVER

Given: graph $G = (V, E)$ and $k \in \mathbb{N}$


Question: $\exists V' \subset V : |V'| \leq k \wedge \forall \{u, v\} \in E : (u \in V' \vee v \in V')$



INDEPENDENTSET

Given: graph $G = (V, E)$ and $k \in \mathbb{N}$

Question: $\exists V' \subset V : |V'| \geq k \wedge \forall u, v \in V' : \{u, v\} \notin E$



Not all reductions are fpt

Many reductions from classical complexity theory are **not** parameter preserving.

Recall:

VERTEXCOVER

Given: graph $G = (V, E)$ and $k \in \mathbb{N}$

Question: $\exists V' \subset V : |V'| \leq k \wedge \forall \{u, v\} \in E : (u \in V' \vee v \in V')$

INDEPENDENTSET

Given: graph $G = (V, E)$ and $k \in \mathbb{N}$


Question: $\exists V' \subset V : |V'| \geq k \wedge \forall u, v \in V' : \{u, v\} \notin E$

► We know: $\text{INDEPENDENTSET} \leq_p \text{VERTEXCOVER}$:

► Set $G' = G$ and $k' = |V(G)| - k$ (Complement of an indep. set must be a vertex cover, and vice versa!)

$$k = 5$$

$$k' = 9 - 5 = 4$$



not parameter
preserving

Not all reductions are fpt

Many reductions from classical complexity theory are **not** parameter preserving.

Recall:

VERTEXCOVER

Given: graph $G = (V, E)$ and $k \in \mathbb{N}$

Question: $\exists V' \subset V : |V'| \leq k \wedge \forall \{u, v\} \in E : (u \in V' \vee v \in V')$

INDEPENDENTSET

Given: graph $G = (V, E)$ and $k \in \mathbb{N}$

Question: $\exists V' \subset V : |V'| \geq k \wedge \forall u, v \in V' : \{u, v\} \notin E$

► We know: $\text{INDEPENDENTSET} \leq_p \text{VERTEXCOVER}$:

► Set $G' = G$ and $k' = |V(G)| - k$ (Complement of an indep. set must be a vertex cover, and vice versa!)

► $\nRightarrow p\text{-INDEPENDENTSET} \leq_{\text{fpt}} p\text{-VERTEXCOVER}$

► Indeed, we know $\text{VERTEXCOVER} \in \text{FPT}$, but INDEPENDENTSET probably isn't.

Not all reductions are fpt

Many reductions from classical complexity theory are **not** parameter preserving.

Recall:

VERTEXCOVER

Given: graph $G = (V, E)$ and $k \in \mathbb{N}$

Question: $\exists V' \subset V : |V'| \leq k \wedge \forall \{u, v\} \in E : (u \in V' \vee v \in V')$

INDEPENDENTSET

Given: graph $G = (V, E)$ and $k \in \mathbb{N}$

Question: $\exists V' \subset V : |V'| \geq k \wedge \forall u, v \in V' : \{u, v\} \notin E$

► We know: $\text{INDEPENDENTSET} \leq_p \text{VERTEXCOVER}$:

► Set $G' = G$ and $k' = |V(G)| - k$ (Complement of an indep. set must be a vertex cover, and vice versa!)


► $\nRightarrow p\text{-INDEPENDENTSET} \leq_{\text{fpt}} p\text{-VERTEXCOVER}$

► Indeed, we know $\text{VERTEXCOVER} \in \text{FPT}$, but INDEPENDENTSET probably isn't.


► But: $p\text{-INDEPENDENTSET} \leq_{\text{fpt}} p\text{-CLIQUE}$ (and $p\text{-CLIQUE} \leq_{\text{fpt}} p\text{-INDEPENDENTSET}$)

► Set $G' = (V, \binom{V}{2} \setminus E)$ and $k' = k$ (Independent set iff clique in complement graph)

$k=2$



$k'=2$



5.2 Nondeterministic FPT: Para-NP

Parameterized NP: Non-deterministic NP

Good, so we have reductions.

If P corresponds to FPT . . . but what is the analogue for NP?

Parameterized NP: Non-deterministic NP

Good, so we have reductions.

If P corresponds to FPT ... but what is the analogue for NP?

Definition 5.2 (para-NP)

The class para-NP consists of all parameterized decision problems that are solved by a *non-deterministic* fpt-algorithm.

$$f(k) \cdot n^{O(k)}$$

Parameterized NP: Non-deterministic NP

Good, so we have reductions.

If P corresponds to FPT ... but what is the analogue for NP?

Definition 5.2 (para-NP)

The class para-NP consists of all parameterized decision problems that are solved by a *non-deterministic* fpt-algorithm. ◀

Some nice properties:

1. para-NP is closed under fpt-reductions.

$$A \in \text{para-NP} \quad , \quad B \leq_{\text{fpt}} A \quad \Rightarrow \quad B \in \text{para-NP}$$

2. $\text{FPT} = \text{para-NP} \iff P = \text{NP}$

3. an analogue for *kernalization* in FPT holds for para-NP

Parameterized NP: Non-deterministic NP

Good, so we have reductions.

If P corresponds to FPT ... but what is the analogue for NP?

Definition 5.2 (para-NP)

The class para-NP consists of all parameterized decision problems that are solved by a *non-deterministic* fpt-algorithm.

Some nice properties:

1. para-NP is closed under fpt-reductions.
2. $\text{FPT} = \text{para-NP} \iff \text{P} = \text{NP}$
3. an analogue for *kernalization* in FPT holds for para-NP

Can define para-NP-hard and para-NP-complete similarly as for NP:

Definition 5.3 (para-NP-hard)

(L, κ) is para-NP-hard if $(L', \kappa') \leq_{\text{fpt}} (L, \kappa)$ for all $(L', \kappa') \in \text{para-NP}$.

Hello hardness, my old friend

Theorem 5.4 (para-NP-complete \rightarrow NP-complete for finite parameter)

Let (L, κ) be a nontrivial ($\emptyset \neq L \neq \Sigma^*$) parameterized problem that is para-NP-complete. Then $L_{\leq d} = \{x \in L : \kappa(x) \leq d\}$ is NP-hard.

$\exists \Delta$
The converse is essentially also true (using a generalization of kernelizations).

Proof: Let (L, κ) para-NP-complete

Let L' NP-complete $\Rightarrow (L', \kappa_{one}) \in \text{para-NP}$
 $\kappa_{one}(x) = 1$

/
non-det. algorithm for L' is also non-det.
fpt algorithm for (L', κ_{one})

para-NP-complete

$\Rightarrow (L', \kappa_{one}) \leq_{\text{fpt}} (L, \kappa)$ i.e. \exists algo. A $x \in L' \Leftrightarrow A(x) \in L$

running time of A $f(\underbrace{\kappa_{one}(x)}_1) \cdot |x|^c$

$d = f(1) = O(1)$

running time of A is
polynomial $|x|$

A maps L' to $L_{\leq d} = \{x \in L : \kappa(x) \leq d\}$

in poly time

$\Rightarrow L' \leq_p L_{\leq d} \quad \Rightarrow L_{\leq d} \text{ NP-hard}$

para-NP-complete is too strict

Above Theorem means that many problems cannot be para-NP-complete!

For each of the following

- ▶ p -CLIQUE,
- ▶ p -INDEPENDENTSET
- ▶ p -DOMINATINGSET

bounding k by a **constant** d makes *polytime* algorithm possible.

FPT $f(k) n^c$

XP $n^{O(k)}$ for constant k
is *polynomial*

para-NP-complete is too strict

Above Theorem means that many problems cannot be para-NP-complete!

For each of the following

- ▶ p -CLIQUE,
- ▶ p -INDEPENDENTSET
- ▶ p -DOMINATINGSET

bounding k by a **constant** d makes *polytime* algorithm possible.

↪ $L_{\leq d}$ cannot be NP-complete for each of these

- ▶ but we rather expect them \notin FPT

↪ para-NP theory does not settle complexity status