ALGORITHMICS\$APPLIED

APPLIEDALGORITHMICS\$

CS\$APPLIEDALGORITHMI

DALGORITHMICS\$APPLIE

EDALGORITHMICS\$APPLIE

GORITHMICS\$APPLIEDAL

HMICS\$APPLIEDALGORIT

ICS\$APPLIEDALGORITHM

8

Error-Correcting Codes


28 April 2021

Sebastian Wild

Outline

8 Error-Correcting Codes

- 8.1 Introduction
- 8.2 Lower Bounds
- 8.3 Hamming Codes



- ▶ most forms of communication are "noisy"
 - ▶ humans: acoustic noise, unclear pronunciation, misunderstanding, foreign languages

- ▶ most forms of communication are "noisy"
 - humans: acoustic noise, unclear pronunciation, misunderstanding, foreign languages
- ► How do humans cope with that?
 - ▶ slow down and/or speak up
 - ask to repeat if necessary



- ▶ most forms of communication are "noisy"
 - humans: acoustic noise, unclear pronunciation, misunderstanding, foreign languages
- ► How do humans cope with that?
 - ▶ slow down and/or speak up
 - ask to repeat if necessary



▶ But how is it possible (for us) to decode a message in the presence of noise & errors?

Bcaesue it semes taht ntaurul lanaguge has a lots fo redundancy bilt itno it!


- ▶ most forms of communication are "noisy"
 - humans: acoustic noise, unclear pronunciation, misunderstanding, foreign languages
- ► How do humans cope with that?
 - ▶ slow down and/or speak up
 - ask to repeat if necessary



► But how is it possible (for us) to decode a message in the presence of noise & errors?

Because it semes taht ntaurul lanaguge has a lots fo redundancy bilt itno it!

- → We can
- 1. **detect errors** "This sentence has aao pi dgsdho gioasghds."
- correct (some) errors "Tiny errs ar corrrected automaticly." (sometimes too eagerly as in the Chinese Whispers / Telephone)



Noisy Channels

- ► computers: copper cables & electromagnetic interference
- transmit a binary string
- ▶ but occasionally bits can "flip"
- → want a robust code



Noisy Channels

- ► computers: copper cables & electromagnetic interference
- transmit a binary string
- ▶ but occasionally bits can "flip"
- → want a robust code



- ▶ We can aim at
 - 1. error detection
- → can request a re-transmit
- 2. error correction
- → avoid re-transmit for common types of errors

Noisy Channels

- computers: copper cables & electromagnetic interference
- ► transmit a binary string wessege
- but occasionally bits can "flip"
- → want a robust code



- ▶ We can aim at
 - **1. error detection** → can request a re-transmit
 - **2. error correction** \rightarrow avoid re-transmit for common types of errors
- ▶ This will require *redundancy*: sending *more* bits than plain message
 - → **goal:** robust code with lowest redundancy that's the opposite of compression!

Clicker Question



What do you think, how many extra bits do we need to **detect** a **single bit error** in a message of 100 bits?

sli.do/comp526

Click on "Polls" tab

Clicker Question



What do you think, how many extra bits do we need to **correct** a **single bit error** in a message of 100 bits?

sli.do/comp526

Click on "Polls" tab

8.2 Lower Bounds

Block codes

▶ model:

- ▶ want to send message $S \in \{0, 1\}^*$ (bitstream) across a (*communication*) *channel*
- any bit transmitted through the channel might *flip* (0 → 1 resp. 1 → 0) no other errors occur (no bits lost, duplicated, inserted, etc.)
- ▶ instead of *S*, we send *encoded bitstream* $C \in \{0, 1\}^*$ sender *encodes S* to *C*, receiver *decodes C* to *S* (hopefully)
- → what errors can be detected and/or corrected?

Block codes

- ▶ model:
 - ▶ want to send message $S \in \{0, 1\}^*$ (bitstream) across a (communication) channel
 - any bit transmitted through the channel might *flip* (0 → 1 resp. 1 → 0) no other errors occur (no bits lost, duplicated, inserted, etc.)
 - ▶ instead of *S*, we send *encoded bitstream* $C \in \{0, 1\}^*$ sender *encodes S* to *C*, receiver *decodes C* to *S* (hopefully)
 - → what errors can be detected and/or corrected?
- ▶ all codes discussed here are *block codes*
 - ▶ divide *S* into messages $m \in \{0, 1\}^k$ of *k* bits each $(k = message \ length)$
 - encode each message (separately) as $C(m) \in \{0, 1\}^n$ $(n = block \ length, \ n \ge k)$
 - → can analyze everything block-wise

Block codes

- ▶ model:
 - ▶ want to send message $S \in \{0, 1\}^*$ (bitstream) across a (communication) channel
 - any bit transmitted through the channel might *flip* (0 → 1 resp. 1 → 0) no other errors occur (no bits lost, duplicated, inserted, etc.)
 - ▶ instead of *S*, we send *encoded bitstream* $C \in \{0, 1\}^*$ sender *encodes S* to *C*, receiver *decodes C* to *S* (hopefully)
 - → what errors can be detected and/or corrected?
- ▶ all codes discussed here are *block codes*
 - ▶ divide *S* into messages $m \in \{0, 1\}^k$ of *k* bits each $(k = message \ length)$
 - encode each message (separately) as $C(m) \in \{0, 1\}^n$ $(n = block \ length, \ n \ge k)$
 - → can analyze everything block-wise
- **b** between 0 and n bits might be flipped invalid code
 - ▶ how many flipped bits can we definitely **detect**?
 - ▶ how many flipped bits can we **correct** without retransmit?

i.e. decoding m still possible

$$m \neq m' \implies C(m) \neq C(m')$$

$$m \neq m' \implies C(m) \neq C(m')$$

- each block code is an *injective* function $C: \{0,1\}^k \to \{0,1\}^n$
- ▶ define $\mathcal{C} = \text{set of all codewords} = C(\{0,1\}^k) = \{ b \in \{0,1\}^k : b = C(m) \}$
- Arr $\mathcal{C} \subseteq \{0, 1\}^n$ $|\mathcal{C}| = 2^k \text{ out of } 2^n \text{ } n\text{-bit strings are valid codewords}$
- ▶ <u>decoding</u> = finding closest valid codeword

$$m \neq m' \implies C(m) \neq C(m')$$

- each block code is an *injective* function $C: \{0,1\}^k \to \{0,1\}^n$
- ▶ define $C = \text{set of all codewords} = C(\{0, 1\}^k)$
- \sim $\mathcal{C} \subseteq \{0,1\}^n$ $|\mathcal{C}| = 2^k$ out of 2^n n-bit strings are valid codewords
- ▶ decoding = finding closest valid codeword
- ► distance of code:

 $d = \text{minimal Hamming distance of any two codewords} = \min_{x,y \in \mathbb{C}} d_H(x,y)$

$$m \neq m' \implies C(m) \neq C(m')$$

- each block code is an *injective* function $C : \{0, 1\}^k \to \{0, 1\}^n$
- ▶ define $C = \text{set of all codewords} = C(\{0, 1\}^k)$
- $\leadsto \mathcal{C} \subseteq \{0,1\}^n$

 $|\mathcal{C}| = 2^k$ out of 2^n *n*-bit strings are valid codewords

- decoding = finding closest valid codeword
- ► distance of code:

 $d = \text{minimal Hamming distance of any two codewords} = \min_{x,y \in \mathbb{C}} d_H(x,y)$

Implications for codes

- **1.** Need distance d to <u>detect</u> all errors flipping up to d-1 bits.
- **2.** Need distance *d* to **correct** all errors flipping up to $\lfloor \frac{d-1}{2} \rfloor$ bits.



Lower Bounds

► Main advantage of concept of code distance: can *prove* lower bounds on block length

Lower Bounds

► Main advantage of concept of code distance: can *prove* lower bounds on block length

- ► Singleton bound: $2^k \le 2^{n-(d-1)} \Leftrightarrow n \ge k+d-1$
 - ▶ *proof sketch:* We have 2^k codeswords with distance d after deleting the first d-1 bits, all are still distinct but there are only $2^{n-(d-1)}$ such shorter bitstrings.



4

Lower Bounds

- ► Main advantage of concept of code distance: can *prove* lower bounds on block length
- ► Singleton bound: $2^k \le 2^{n-(d-1)} \longrightarrow n \ge k+d-1$
 - ▶ *proof sketch:* We have 2^k codeswords with distance d after deleting the first d-1 bits, all are still distinct but there are only $2^{n-(d-1)}$ such shorter bitstrings.



► Hamming bound: $2^k \le \frac{2^n}{\sum_{f=0}^{\lfloor (d-1)/2 \rfloor} \binom{n}{f}}$






- ▶ proof idea: consider "balls" of bitstrings around codewords count bitstrings with Hamming-distance $\leq t = \lfloor (d-1)/2 \rfloor$ correcting t errors means all these balls are disjoint so $2^k \cdot$ ball size $\leq 2^n$
- → We will come back to these.

8.3 Hamming Codes


Parity Bit

▶ simplest possible error-detecting code: add a parity bit



Parity Bit


▶ simplest possible error-detecting code: add a parity bit



- ► can detect any single-bit error (actually, any odd number of flipped bits)
- ▶ used in many hardware (communication) protocols
 - ► PCI buses, serial buses
 - caches
 - early forms of main memory

Parity Bit

▶ simplest possible error-detecting code: add a parity bit



- ► can detect any single-bit error (actually, any odd number of flipped bits)
- ▶ used in many hardware (communication) protocols
 - ► PCI buses, serial buses
 - caches
 - ▶ early forms of main memory
- very simple and cheap
- cannot correct any errors

Clicker Question



What do you think, how many extra bits do we need to **detect** a **single bit error** in a message of 100 bits?

sli.do/comp526

Click on "Polls" tab

, any downtime is expensive!

- ▶ typical application: heavy-duty server RAM
 - bits can randomly flip (e.g., by cosmic rays)
 - individually very unlikely, but in always-on server with lots of RAM, it happens!

https://blogs.oracle.com/linux/attack-of-the-cosmic-rays-v2



,any downtime is expensive!

- ▶ typical application: heavy-duty server RAM
 - bits can randomly flip (e.g., by cosmic rays)
 - individually very unlikely, but in always-on server with lots of RAM, it happens!

https://blogs.oracle.com/linux/attack-of-the-cosmic-rays-v2





Can we **correct** a bit error without knowing where it occurred? How?

, any downtime is expensive!

- typical application: heavy-duty server RAM
 - bits can randomly flip (e.g., by cosmic rays)
 - individually very unlikely, but in always-on server with lots of RAM, it happens!

https://blogs.oracle.com/linux/attack-of-the-cosmic-rays-v2





Can we correct a bit error without knowing where it occurred? How?

- ► Yes! store every bit *three times!*
 - ▶ upon read, do majority vote
 - ▶ if only one bit flipped, the other two (correct) will still win

, any downtime is expensive!

- ▶ typical application: heavy-duty server RAM
 - bits can randomly flip (e.g., by cosmic rays)
 - individually very unlikely, but in always-on server with lots of RAM, it happens!

https://blogs.oracle.com/linux/attack-of-the-cosmic-rays-v2





Can we **correct** a bit error without knowing where it occurred? How?

- ► Yes! store every bit *three times!*
 - ▶ upon read, do majority vote
 - ▶ if only one bit flipped, the other two (correct) will still win
 - triples the cost!



You want WHAT!?!

, any downtime is expensive!

- ▶ typical application: heavy-duty server RAM
 - bits can randomly flip (e.g., by cosmic rays)
 - individually very unlikely, but in always-on server with lots of RAM, it happens!

https://blogs.oracle.com/linux/attack-of-the-cosmic-rays-v2





Can we correct a bit error without knowing where it occurred? How?

- ► Yes! store every bit *three times!*
 - upon read, do majority vote
 - ▶ if only one bit flipped, the other two (correct) will still win
 - triples the cost!



You want WHAT!?!



instead of 200% (!)

Can do it with 11% extra memory!