

Compression

16 March 2020

Sebastian Wild

Outline

7 Compression

- 7.1 Context
- 7.2 Character Encodings
- 7.3 Huffman Codes
- 7.4 Run-Length Encoding
- 7.5 Lempel-Ziv-Welch
- 7.6 Move-to-Front Transformation
- 7.7 Burrows-Wheeler Transform

7.1 Context

Overview

- ► Unit 4–6: How to *work* with strings
 - finding substrings
 - finding approximate matches
 - ► finding repeated parts
 - ▶ ...
- ▶ Unit 7–8: How to *store* strings
 - ► computer memory: must be binary
 - ▶ how to compress strings (save space)
 - ▶ how to robustly transmit over noisy channels → Unit 8

Terminology

- ▶ **source text:** string $S \in \Sigma_S^*$ to be stored / transmitted Σ_S is some alphabet
- ▶ coded text: encoded data $C \in \Sigma_C^*$ that is actually stored / transmitted usually use $\Sigma_C = \{0, 1\}$
- encoding: algorithm mapping source texts to coded texts $S \rightarrow C$
- **decoding:** algorithm mapping coded texts back to original source text $C \rightarrow S$

What is a good encoding scheme?

- ▶ Depending on the application, goals can be
 - efficiency of encoding/decoding
 - ► resilience to errors/noise in transmission
 - ► security (encryption)

 In integrity (detect modifications made by third parties)
 - ► size
- ► Focus in this unit: <u>size</u> of coded text | C |
 Encoding schemes that (try to) minimize the size of coded texts perform *data compression*.
- ► We will measure the *compression ratio*: $\frac{|C| \cdot \lg |\Sigma_C|}{|S| \cdot \lg |\Sigma_S|} \stackrel{\Sigma_C = \{0,1\}}{=} \frac{|C|}{|S| \cdot \lg |\Sigma_S|}$
 - < 1 means successful compression
 - = 1 means no compression
 - > 1 means "compression" made it bigger!? (yes, that happens ...)

Types of Data Compression

- ► Logical vs. Physical
 - Logical Compression uses meaning of data
 only applies to a certain domain, e.g., sound recordings
 - Physical Compression only knows the (physical) bits in the data, not the meaning behind them
- Lossy vs. Lossless
 - ▶ **lossy compression** can only decode **approximately**; the exact source text *S* is lost
 - ▶ **lossless compression** always decodes *S* exactly
- ► For media files, lossy, logical compression is useful (e.g. JPEG, MPEG)
- ► We will concentrate on *physical*, *lossless* compression algorithms. These techniques can be used for any application.

What makes data compressible?

- <u>Physical, lossless</u> compression methods mainly exploit two types of redundancies in source texts:
 - uneven character frequencies some characters occur more often than others → Part I
 - 2. repetitive texts
 different parts in the text are (almost) identical → Part II

What makes data compressible?

- Physical, lossless compression methods mainly exploit two types of redundancies in source texts:
 - uneven character frequencies some characters occur more often than others → Part I
 - 2. repetitive texts different parts in the text are (almost) identical \rightarrow Part II



There is no such thing as a free lunch!

Not *everything* is compressible (\rightarrow tutorials)

→ focus on versatile methods that often work

Part I

Exploiting character frequencies

7.2 Character Encodings

Character encodings

- ► Simplest form of encoding: Encode each source character individually
- \rightsquigarrow encoding function $\underline{E}: \Sigma_S \to \Sigma_C^*$
 - typically, $|\Sigma_S| \gg |\Sigma_C|$, so need several bits per character
 - for $c \in \Sigma_S$, we call E(c) the *codeword* of c
- ▶ fixed-length code: |E(c)| is the same for all $c \in \Sigma$
- ▶ variable-length code: not all codewords of same length

Fixed-length codes

- fixed-length codes are the simplest type of character encodings
- Example: ASCII (American Standard Code for Information Interchange, 1963)

```
0000000 NUL
               0010000 DLE
                              0100000
                                            0110000 0
                                                          1000000 a
                                                                       1010000 P
                                                                                     1100000 '
                                                                                                  1110000 p
0000001 SOH
               0010001 DC1
                              0100001 !
                                            0110001 1
                                                          1000001 A
                                                                       1010001 0
                                                                                     1100001 a
                                                                                                  1110001 a
0000010 STX
               0010010 DC2
                              0100010 "
                                            0110010 2
                                                          1000010 B
                                                                       1010010 R
                                                                                     1100010 b
                                                                                                  1110010 r
0000011 ETX
               0010011 DC3
                              0100011 #
                                            0110011 3
                                                         1000011 C
                                                                       1010011 S
                                                                                    1100011 c
                                                                                                  1110011 s
0000100 FOT
               0010100 DC4
                              0100100 $
                                            0110100 4
                                                          1000100 D
                                                                       1010100 T
                                                                                     1100100 d
                                                                                                  1110100 t
0000101 ENO
               0010101 NAK
                              0100101 %
                                            0110101 5
                                                          1000101 E)
                                                                       1010101 U
                                                                                     1100101 e
                                                                                                  1110101 u
0000110 (ACK)
               0010110 SYN
                              0100110 &
                                            0110110 6
                                                          1000110 F
                                                                       1010110 V
                                                                                     1100110 f
                                                                                                  1110110 v
0000111 BEL
               0010111 ETB
                              0100111 '
                                            0110111 7
                                                          1000111 G
                                                                       1010111 W
                                                                                     1100111 q
                                                                                                  1110111 w
0001000 BS
                                            0111000 8
                                                          1001000 H
                                                                       1011000 X
                                                                                     1101000 h
                                                                                                  1111000 x
               0011000 CAN
                              0101000 (
0001001 HT
               0011001 EM
                              0101001 )
                                            0111001 9
                                                         1001001 I
                                                                       1011001 Y
                                                                                    1101001 i
                                                                                                  1111001 v
0001010 LF
               0011010 SUB
                                            0111010 :
                                                          1001010 J
                                                                       1011010 Z
                                                                                     1101010 i
                                                                                                  1111010 z
                              0101010 *
0001011 VT
               0011011 ESC
                              0101011 +
                                            0111011 :
                                                          1001011 K
                                                                       1011011 [
                                                                                     1101011 k
                                                                                                  1111011 {
0001100 FF
               0011100 FS
                              0101100 .
                                            0111100 <
                                                         1001100 L
                                                                       1011100 \
                                                                                    1101100 l
                                                                                                  1111100
0001101 CR
               0011101 GS
                              0101101 -
                                            0111101 =
                                                          1001101 M
                                                                       1011101 1
                                                                                    1101101 m
                                                                                                  1111101 }
0001110 SO
                                                                       1011110 ^
               0011110 RS
                              0101110 .
                                            0111110 >
                                                          1001110 N
                                                                                     1101110 n
                                                                                                  1111110 ~
0001111 SI
               0011111 US
                              0101111 /
                                            0111111 ?
                                                          1001111 0
                                                                       1011111
                                                                                     1101111 o
                                                                                                  1111111 DEL
```

- ▶ 7 bit per character
- ▶ just enough for English letters and a few symbols (plus control characters)

Fixed-length codes – Discussion


Encoding & Decoding as fast as it gets

Unless all characters equally likely, it wastes a lot of space

inflexible (how to support adding a new character?)

Variable-length codes

▶ to gain more flexibility, have to allow different lengths for codewords



Variable-length codes – UTF-8

► Modern example: UTF-8 encoding of Unicode:

default encoding for text-files, XML, HTML since 2009

- ► Encodes any Unicode character (137 994 as of May 2019, and counting)
- ▶ uses 1–4 bytes (codeword lengths: 8, 16, 24, or 32 bits)
- ▶ Every ASCII character is encoded in 1 byte with leading bit 0, followed by the 7 bits for ASCII
- Non-ASCII charactters start with 1–4 1s indicating the total number of bytes, followed by a 0 and 3–5 bits.

The remaining bytes each start with 10 followed by 6 bits.

Char. number range	UTF-8 octet sequence				
(hexadecimal)	(binary)				
0000 0000-0000 007F	(1)				
0000 0080-0000 07FF	110xxxxx 10xxxxxx				
0000 0800-0000 FFFF	1110xxxx 10xxxxxx 10xxxxxx				
0001 0000-0010 FFFF	11110xxx 10xxxxxx 10xxxxxx 10xxxxxx				



For English text, most characters use only 8 bit, but we can include any Unicode character, as well.

Pitfall in variable-length codes

- ► Happily encode text $S = \underline{\text{banana}}$ with the coded text $C = \underline{1100} \underline{100} \underline{0100}$

Pitfall in variable-length codes

- $7 C = 1100100100 \text{ decodes both to banana and to bass: } \frac{1100100100}{\text{b a s s}} \frac{1000100}{\text{s}}$
- but how should we have known?

Pitfall in variable-length codes

- ► Happily encode text S = banana with the coded text $C = \underbrace{1100}_{\text{b}} \underbrace{0100}_{\text{a n a n a}} \underbrace{0100}_{\text{a n n a n a}}$
- $rac{1}{7}$ C = 1100100100 decodes **both** to banana and to bass: $\frac{110}{b} \frac{0100100}{a} \frac{100}{s} \frac{100}{s}$
- → not a valid code . . . (cannot tolerate ambiguity)
 but how should we have known?
- E(n) = 10 is a (proper) **prefix** of E(s) = 100
 - Leaves decoding wondering whether to stop after reading 10 or continue
 - Require a *prefix-free* code: No codeword is a prefix of another.

 prefix-free \implies instantaneously decodable


Code tries

► From now on only consider <u>prefix-free</u> codes E: E(c) is not a prefix of E(c') for any $c, c' \in \Sigma_S$.

standard trie

Any prefix-free code corresponds to a *(code) trie* (trie of codewords) with characters of Σ_S at **leaves**.

no need for end-of-string symbols \$ here (already prefix-free!)




- ► Encode AN, ANT 01001000...
- ▶ Decode 111000001010111 TO

Code tries

- ► From now on only consider prefix-free codes E: E(c) is not a prefix of E(c') for any $c, c' \in \Sigma_S$.

Any prefix-free code corresponds to a *(code) trie* (trie of codewords) with characters of Σ_S at **leaves**.

no need for end-of-string symbols \$ here (already prefix-free!)



- ► Encode AN_ANT → 010010000100111
- ► Decode 111000001010111 → T0_EAT

Who decodes the decoder?

- ▶ Depending on the application, we have to **store/transmit** the **used code**!
- ▶ We distinguish:
 - ▶ fixed coding: code agreed upon in advance, not transmitted (e.g., Morse, UTF-8)
- static coding: code depends on message, but stays same for entire message; it must be transmitted (e. g., Huffman codes → next)
 - adaptive coding: code depends on message and changes during encoding; implicitly stored withing the message (e. g., LZW → below)

7.3 Huffman Codes

Character frequencies

- ▶ Goal: Find character encoding that produces short coded text
- ► Convention here: fix $\Sigma_C = \{0, 1\}$ (binary codes), abbreviate $\Sigma = \Sigma_S$,
- ▶ **Observation:** Some letters occur more often than others.

Typical English prose:

e	12.70%		d	4.25%	p	1.93%	
t	9.06%		1	4.03%	b	1.49%	-
a	8.17%		c	2.78%	\mathbf{v}	0.98%	
О	7.51%		u	2.76%	\mathbf{k}	0.77%	
i	6.97%		m	2.41%	j	0.15%	1
n	6.75%		w	2.36%	x	0.15%	1
s	6.33%		f	2.23%	q	0.10%	1
h	6.09%		g	2.02%	\mathbf{z}	0.07%	1
r	5.99%	_	y	1.97%			
$\overline{}$							$-\!-\!-$

→ Want shorter codes for more frequent characters!

Huffman coding

e.g. frequencies / probabilities

- ▶ **Given:** Σ and weights $w : \Sigma \to \mathbb{R}_{\geq 0}$
- ▶ **Goal:** prefix-free code E (= code trie) for Σ that minimizes coded text length

i. e., a code trie minimizing
$$\sum_{c \in \Sigma} w(c) \cdot |E(c)|$$

Huffman coding

e.g. frequencies / probabilities

- ▶ **Given:** Σ and weights $w: \Sigma \to \mathbb{R}_{\geq 0}$
- ▶ **Goal:** prefix-free code E (= code trie) for Σ that minimizes coded text length

i. e., a code trie minimizing
$$\sum_{c \in \Sigma} w(c) \cdot |E(c)|$$

- ▶ If we use w(c) = #occurrences of c in S, this is the character encoding with smallest possible |C|
 - → best possible character-wise encoding

▶ Quite ambitious! *Is this efficiently possible?*

Huffman's algorithm

► Actually, yes! A greedy/myopic approach succeeds here.

Huffman's algorithm:


- 1. Find two characters a, b with lowest weights.
 - ▶ We will encode them with the same prefix, plus one distinguishing bit, i. e., E(a) = u0 and E(b) = u1 for a bitstring $u \in \{0, 1\}^*$ (u to be determined)
- 2. (Conceptually) replace a and b by a single character "ab" \Rightarrow 5 degrees by 1 with w(ab) = w(a) + w(b).
- 3. Recursively apply Huffman's algorithm on the smaller alphabet. This in particular determines $u = E(\Box b)$.

Huffman's algorithm


► Actually, yes! A greedy/myopic approach succeeds here.

Huffman's algorithm:

- 1. Find two characters a, b with lowest weights.
 - We will encode them with the same prefix, plus one distinguishing bit, (i. e., E(a) = u0 and E(b) = u1 for a bitstring $u \in \{0, 1\}^*$ (u to be determined)
- **2.** (Conceptually) replace a and b by a single character "ab" with $w(\mathbf{ab}) = w(\mathbf{a}) + w(\mathbf{b})$.
- 3. Recursively apply Huffman's algorithm on the smaller alphabet. This in particular determines u = E(ab).
- efficient implementation using a (min-oriented) priority queue
 - start by inserting all characters with their weight as key
 - ▶ step 1 uses two deleteMin calls
 - ▶ step 2 inserts a new character with the sum of old weights as key



- ► Example text: S = LOSSLESS $\longrightarrow \Sigma_S = \{E, L, 0, S\}$
- ightharpoonup Character frequencies: E:1, L:2, 0:1, S:4




2

L


4

S


- ► Example text: S = LOSSLESS \leadsto $\Sigma_S = \{E, L, 0, S\}$
- ightharpoonup Character frequencies: E:1, L:2, 0:1, S:4



- ► Example text: S = LOSSLESS $\longrightarrow \Sigma_S = \{E, L, 0, S\}$
- ightharpoonup Character frequencies: E:1, L:2, 0:1, S:4




- ► Example text: S = LOSSLESS \leadsto $\Sigma_S = \{E, L, 0, S\}$
- ightharpoonup Character frequencies: E:1, L:2, 0:1, S:4



→ *Huffman tree* (code trie for Huffman code)

- ► Example text: S = LOSSLESS \longrightarrow $\Sigma_S = \{E, L, 0, S\}$
- ightharpoonup Character frequencies: E:1, L:2, 0:1, S:4



→ *Huffman tree* (code trie for Huffman code)

 $\text{LOSSLESS} \rightarrow \underbrace{\textbf{01001110100011}} \qquad \qquad \text{compression ratio: } \quad \frac{14}{8 \cdot \log 4} = \frac{14}{16} \approx 88\%$

Huffman tree – tie breaking

- ► The above procedure is ambiguous:
 - ▶ which characters to choose when weights are equal?
 - ▶ which subtree goes left, which goes right?
- ► For COMP 526: always use the following rule:
 - To break ties when selecting the two characters, first use the smallest letter according to the alphabetical order, or the tree containing the smallest alphabetical letter.
 - 2. When combining two trees of different values, place the lower-valued tree on the left (corresponding to a 0-bit).
 - When combining trees of equal value, place the one containing the smallest letter to the left.

Huffman code – Optimality

Theorem 7.1 (Optimality of Huffman's Algorithm)

Given Σ and $w: \Sigma \to \mathbb{R}_{\geq 0}$, Huffman's Algorithm computes codewords $E: \Sigma \to \{0,1\}^*$ with minimal expected codeword length $\ell(E) = \sum_{c \in \Sigma} w(c) \cdot |E(c)|$, among all prefix-free codes for Σ .

Huffman code – Optimality

Theorem 7.1 (Optimality of Huffman's Algorithm)

Given Σ and $w: \Sigma \to \mathbb{R}_{\geq 0}$, Huffman's Algorithm computes codewords $E: \Sigma \to \{0,1\}^*$ with minimal expected codeword length $\ell(E) = \sum_{c \in \Sigma} w(c) \cdot |E(c)|$, among all prefix-free codes for Σ .

Proof sketch: by induction over $\sigma = |\Sigma|$

- ▶ Given any optimal prefix-free code E^* (as its code trie).
- ▶ code trie \rightarrow ∃ two sibling leaves x, y at largest depth D
- ▶ swap characters in leaves to have two lowest-weight characters a, b in x, y (that can only make ℓ smaller, so still optimal)
- ▶ any optimal code for $\Sigma' = \Sigma \setminus \{a, b\} \cup \{ab\}$ yields optimal code for Σ by replacing leaf ab by internal node with children a and b.
- \leadsto recursive call yields optimal code for Σ' by inductive hypothesis, so Huffman's algorithm finds optimal code for Σ .

