

Learning Outcomes

1. Understand the context of *error-prone communication*.
2. Understand concepts of *error-detecting codes* and *error-correcting codes*.
3. Know and understand the *terminology of block codes*.
4. Know and understand *Hamming codes*, in particular (7,4) Hamming code.
5. Reason about the *suitability of a code* for an application.

Unit 6: Error-Correcting Codes



Outline

6 Error-Correcting Codes

- 6.1 Introduction
- 6.2 Lower Bounds
- 6.3 Hamming Codes

6.1 Introduction

Noisy Communication

- ▶ most forms of communication are “noisy”
 - ▶ humans: acoustic noise, unclear pronunciation, misunderstanding, foreign languages

Noisy Communication

- ▶ most forms of communication are “noisy”
 - ▶ humans: acoustic noise, unclear pronunciation, misunderstanding, foreign languages
- ▶ How do humans cope with that?
 - ▶ slow down and/or speak up
 - ▶ ask to repeat if necessary



Noisy Communication

- ▶ most forms of communication are “noisy”
 - ▶ humans: acoustic noise, unclear pronunciation, misunderstanding, foreign languages
- ▶ How do humans cope with that?
 - ▶ slow down and/or speak up
 - ▶ ask to repeat if necessary
- ▶ But how is it possible (for us) to decode a message in the presence of noise & errors?



*Bcaesue it semes taht ntaurul lanaguge has a lots fo **redundancy** bilt itno it!*

Noisy Communication

- ▶ most forms of communication are “noisy”
 - ▶ humans: acoustic noise, unclear pronunciation, misunderstanding, foreign languages

- ▶ How do humans cope with that?

- ▶ slow down and/or speak up
 - ▶ ask to repeat if necessary



- ▶ But how is it possible (for us) to decode a message in the presence of noise & errors?

*Because it seems that natural language has a lot of **redundancy** built into it!*

→ We can

1. **detect errors** “This sentence has aao pi dgsdho gioasghds.”
2. **correct (some) errors** “Tiny errs ar corrected automaticly.”
(sometimes too eagerly as in the Chinese Whispers / Telephone)



Noisy Channels

- ▶ computers: copper cables & electromagnetic interference
 - ▶ transmit a binary string
 - ▶ but occasionally bits can “flip”
- ⇒ want a robust code



Noisy Channels

- ▶ computers: copper cables & electromagnetic interference
- ▶ transmit a binary string
- ▶ but occasionally bits can “flip”
- ↪ want a robust code



- ▶ We can aim at
 1. **error detection** ↪ can request a re-transmit
 2. **error correction** ↪ avoid re-transmit for common types of errors

Noisy Channels

- ▶ computers: copper cables & electromagnetic interference
- ▶ transmit a binary string
- ▶ but occasionally bits can “flip”
- ~> want a robust code



- ▶ We can aim at
 1. **error detection** ~> can request a re-transmit
 2. **error correction** ~> avoid re-transmit for common types of errors
- ▶ This will require *redundancy*: sending *more* bits than plain message
 - ~> **goal**: robust code with lowest redundancy

that's the opposite of compression!

Clicker Question



What do you think, how many extra bits do we need to **detect** a **single bit error** in a message of 100 bits?



→ *sli.do/comp526*

Clicker Question



What do you think, how many extra bits do we need to correct a **single bit error** in a message of 100 bits?



→ *sli.do/comp526*