



Random Tricks

25 June 2025

Prof. Dr. Sebastian Wild

9 Random Tricks

- 9.1 Hashing – Balls Into Bins
- 9.2 Universal Hashing
- 9.3 Perfect Hashing
- 9.4 Primality Testing
- 9.5 Schöning's Satisfiability
- 9.6 Karger's Cuts

Uses of Randomness

- ▶ Since it is likely that $BPP = P$, we focus on the more fine-grained benefits of randomization:
 - ▶ simpler algorithms (with same performance)
 - ▶ improving performance (but not jumping from exponential to polytime)
 - ▶ improved robustness
- ▶ Here: Collection of examples illustrating different techniques
 - ▶ fingerprinting / hashing
 - ▶ exploiting abundance of witnesses
 - ▶ random sampling

9.1 Hashing – Balls Into Bins

Fingerprinting / Hashing

- ▶ Often have elements from huge universe $U = [0..u)$ of possible values, but only deal with few actual items x_1, \dots, x_n at one time.

Think: $n \ll u$

$\in \mathcal{U}$

- ▶ Fingerprinting can help to be more efficient in this case

- ▶ fingerprints from $[0..m)$

- ▶ $m \ll u$

- ▶ *Hash Function* $h : U \rightarrow [0..m)$

h will have collisions

$(x, y \in \mathcal{U} \text{ , } h(x) = h(y))$

Fingerprinting / Hashing

- ▶ Often have elements from huge universe $U = [0..u)$ of possible values, but only deal with few actual items x_1, \dots, x_n at one time.

Think: $n \ll u$

- ▶ Fingerprinting can help to be more efficient in this case

- ▶ fingerprints from $[0..m)$


- ▶ $m \ll u$

- ▶ *Hash Function* $h : U \rightarrow [0..m)$

- ▶ Classic Example: hash tables and Bloom filters

Hash Tables

indirect chaining




Performance :

How big are buckets?

$$X_j = \# \text{ keys } x \text{ with } h(x) = j \\ \text{in our HT}$$

worst case $X_i = n$

Bloom Filters



insert(x) : $H[h(x)] := 1$

query(x) : $H[h(x)]$


└ output 1 (Yes) can be
a false positive!

output 0 (No) correct

(reduce false positive rate using
independent $h_1, h_2, h_3, h_4, \dots$)

application : segmented database

"cheap first checks"



Uniform – Universal – Perfect

Randomness is essential for hashing to make any sense! Three very different uses

1. *uniform hashing assumption*: (optimistic, often roughly right in practice!)
How good is hashing if input is “as nicely random” as possible?

Uniform hashing assumption:

All m^n possible hash seq. $h(x_1), h(x_2), h(x_3), \dots, h(x_n)$ are
equally likely.

Uniform – Universal – Perfect

Randomness is essential for hashing to make any sense! Three very different uses

1. *uniform hashing assumption*: (optimistic, often roughly right in practice!)
How good is hashing if input is “as nicely random” as possible?
2. Since fixed h is prone to “algorithmic complexity attacks” (worst case inputs)
 \rightsquigarrow *universal hashing*: pick h at random from class H of suitable functions

universal class of hash functions



Uniform – Universal – Perfect

Randomness is essential for hashing to make any sense! Three very different uses

1. *uniform hashing assumption*: (optimistic, often roughly right in practice!)
How good is hashing if input is “as nicely random” as possible?
2. Since fixed h is prone to “algorithmic complexity attacks” (worst case inputs)
 \rightsquigarrow *universal hashing*: pick h at random from class H of suitable functions

\nearrow
universal class of hash functions
3. For given keys, can construct collision-free hash function
 \rightsquigarrow *perfect hashing*

Uniform Hashing – Balls into Bins

Uniform Hashing Assumption:

When n elements x_1, \dots, x_n are inserted, for their *hash sequence* $h(x_1), \dots, h(x_n)$, all m^n possible values are **equally likely**.



behavior of data structure completely **independent** of x_1, \dots, x_n !

Uniform Hashing – Balls into Bins


Uniform Hashing Assumption:

When n elements x_1, \dots, x_n are inserted, for their *hash sequence* $h(x_1), \dots, h(x_n)$, all m^n possible values are **equally likely**.

~> behavior of data structure completely **independent** of x_1, \dots, x_n !

~> might as well forget data!

Balls into bins model (a.k.a. balanced allocations)

► throw n balls into m bins  Literature usually swaps n and m !

► each ball picks bin *i.i.d. uniformly* at random $B_i = \text{bin of } i\text{th ball} \stackrel{\mathcal{D}}{=} \mathcal{U}([0..m])$

► classic abstract model to study randomized algorithms

- For hashing, effectively the best imaginable case tends to be a bit optimistic!
- but: data in applications often not far from this

A Paradox?

► X_j : Number of balls in bin j :

$$\rightsquigarrow X_1 \stackrel{\mathcal{D}}{=} \dots \stackrel{\mathcal{D}}{=} X_m \stackrel{\mathcal{D}}{=} \text{Bin}(n, \frac{1}{m})$$

\rightsquigarrow All X_j concentrated around expectation $\frac{n}{m}$ (Chernoff!)

A Paradox?

► X_i : Number of balls in bin i :

$$\rightsquigarrow X_1 \stackrel{\mathcal{D}}{=} \dots \stackrel{\mathcal{D}}{=} X_m \stackrel{\mathcal{D}}{=} \text{Bin}(n, \frac{1}{m})$$

\rightsquigarrow All X_i concentrated around expectation $\frac{n}{m}$ (Chernoff!)

Consider $\boxed{m = n}$ $\rightsquigarrow \mathbb{E}[X_i] = 1$

A Paradox?

► X_i : Number of balls in bin i :

$$\rightsquigarrow X_1 \stackrel{\mathcal{D}}{=} \dots \stackrel{\mathcal{D}}{=} X_m \stackrel{\mathcal{D}}{=} \text{Bin}(n, \frac{1}{m})$$

\rightsquigarrow All X_i concentrated around expectation $\frac{n}{m}$ (Chernoff!)

Consider $\boxed{m = n}$ $\rightsquigarrow \mathbb{E}[X_i] = 1$

► But also: expected number of *empty* bins:

$$\mathbb{E}[\#i \text{ with } X_i = 0] = \sum_{i=1}^m \mathbb{P}[X_i = 0]$$

A Paradox?

► X_i : Number of balls in bin i :

$$\rightsquigarrow X_1 \stackrel{\mathcal{D}}{=} \dots \stackrel{\mathcal{D}}{=} X_m \stackrel{\mathcal{D}}{=} \text{Bin}(n, \frac{1}{m})$$

\rightsquigarrow All X_i concentrated around expectation $\frac{n}{m}$ (Chernoff!)

Consider $\boxed{m = n}$ $\rightsquigarrow \mathbb{E}[X_i] = 1$

► But also: expected number of *empty* bins:

$$\begin{aligned}\mathbb{E}[\#i \text{ with } X_i = 0] &= \sum_{i=1}^m \mathbb{P}[X_i = 0] \\ &= m \cdot \left(1 - \frac{1}{m}\right)^n \quad (m = n, \underbrace{(1 + 1/n)^n \approx e})\end{aligned}$$

A Paradox?

► X_i : Number of balls in bin i :

$$\rightsquigarrow X_1 \stackrel{\mathcal{D}}{=} \dots \stackrel{\mathcal{D}}{=} X_m \stackrel{\mathcal{D}}{=} \text{Bin}(n, \frac{1}{m})$$

\rightsquigarrow All X_i concentrated around expectation $\frac{n}{m}$ (Chernoff!)

Consider $\boxed{m = n}$ $\rightsquigarrow \mathbb{E}[X_i] = 1$

► But also: expected number of *empty* bins:

$$\begin{aligned}\mathbb{E}[\#i \text{ with } X_i = 0] &= \sum_{i=1}^m \mathbb{P}[X_i = 0] \\ &= m \cdot \left(1 - \frac{1}{m}\right)^n \quad (m = n, (1 + 1/n)^n \approx e) \\ &= n \cdot e(1 \pm O(n^{-1}))\end{aligned}$$

A Paradox?

► X_i : Number of balls in bin i :

$$\rightsquigarrow X_1 \stackrel{\mathcal{D}}{=} \dots \stackrel{\mathcal{D}}{=} X_m \stackrel{\mathcal{D}}{=} \text{Bin}(n, \frac{1}{m})$$

\rightsquigarrow All X_i concentrated around expectation $\frac{n}{m}$ (Chernoff!)

Consider $\boxed{m = n}$ $\rightsquigarrow \mathbb{E}[X_i] = 1$

► But also: expected number of *empty* bins:

$$\begin{aligned}\mathbb{E}[\#i \text{ with } X_i = 0] &= \sum_{i=1}^m \mathbb{P}[X_i = 0] \\ &= m \cdot \left(1 - \frac{1}{m}\right)^n \quad (m = n, (1 + 1/n)^n \approx e) \\ &= n \cdot \frac{1}{e}(1 \pm O(n^{-1}))\end{aligned}$$

\rightsquigarrow In expectation, $\frac{1}{e}$ fraction (37%) of bins empty!

How does that fit together with $\mathbb{E}[X_i] = 1$? Which expectation should we expect?

A Paradox?

► X_i : Number of balls in bin i :

$$\rightsquigarrow X_1 \stackrel{\mathcal{D}}{=} \dots \stackrel{\mathcal{D}}{=} X_m \stackrel{\mathcal{D}}{=} \text{Bin}(n, \frac{1}{m})$$

\rightsquigarrow All X_i concentrated around expectation $\frac{n}{m}$ (Chernoff!)

actually, just shows $X_i = n/m \pm n^{0.501}$

Consider $m = n$ $\rightsquigarrow \mathbb{E}[X_i] = 1$

► But also: expected number of *empty* bins:

$$\begin{aligned}\mathbb{E}[\#i \text{ with } X_i = 0] &= \sum_{i=1}^m \mathbb{P}[X_i = 0] \\ &= m \cdot \left(1 - \frac{1}{m}\right)^n \quad (m = n, (1 + 1/n)^n \approx e) \\ &= n \cdot e(1 \pm O(n^{-1}))\end{aligned}$$

\rightsquigarrow In expectation, $\frac{1}{e}$ fraction (37%) of bins empty!

How does that fit together with $\mathbb{E}[X_i] = 1$? Which expectation should we expect?

Birthday Paradox

► Let's consider a different question to approach this . . .

► *Birthday 'Paradox':*

How many people does it take to likely have two people with the same birthday?

Birthday Paradox

- ▶ Let's consider a different question to approach this . . .
- ▶ *Birthday 'Paradox':*
How many people does it take to likely have two people with the same birthday?
- ▶ In balls-into-bins language: What n makes it likely that $\exists j \in [m] : X_j \geq 2$?

Birthday Paradox

► Let's consider a different question to approach this . . .

► ***Birthday 'Paradox':***

How many people does it take to likely have two people with the same birthday?

► In balls-into-bins language: What n makes it likely that $\exists j \in [m] : X_j \geq 2$?

Compute counter-probability: $\mathbb{P}[\max X_j \leq 1]$

$$\underbrace{1}_{\text{ball 1}} \cdot \underbrace{\left(1 - \frac{1}{m}\right)}_{\text{ball 2}} \cdot \left(1 - \frac{2}{m}\right) \cdots \left(1 - \frac{n-1}{m}\right)$$

Birthday Paradox

► Let's consider a different question to approach this ...

► ***Birthday 'Paradox':***

How many people does it take to likely have two people with the same birthday?

► In balls-into-bins language: What n makes it likely that $\exists j \in [m] : X_j \geq 2$?

Compute counter-probability: $\mathbb{P}[\max X_j \leq 1]$

Taylor series $e^x = \underbrace{1 + x}_{\pm O(x^2)} \pm O(x^2)$ as $x \rightarrow 0$

$$1 \cdot \left(1 - \frac{1}{m}\right) \cdot \left(1 - \frac{2}{m}\right) \cdots \left(1 - \frac{n-1}{m}\right) = e^{-\frac{1}{m}} \cdot e^{-\frac{2}{m}} \cdots e^{-\frac{n-1}{m}} \cdot \left(1 \pm O\left(\left(\frac{n}{m}\right)^2\right)\right)$$

Birthday Paradox

► Let's consider a different question to approach this . . .

► ***Birthday 'Paradox':***

How many people does it take to likely have two people with the same birthday?

► In balls-into-bins language: What n makes it likely that $\exists j \in [m] : X_j \geq 2$?

Compute counter-probability: $\mathbb{P}[\max X_j \leq 1]$

Taylor series $e^x = 1 + x \pm O(x^2)$ as $x \rightarrow 0$

$$\begin{aligned} 1 \cdot \left(1 - \frac{1}{m}\right) \cdot \left(1 - \frac{2}{m}\right) \cdots \left(1 - \frac{n-1}{m}\right) &= e^{-\frac{1}{m}} \cdot e^{-\frac{2}{m}} \cdots e^{-\frac{n-1}{m}} \cdot \left(1 \pm O\left(\left(\frac{n}{m}\right)^2\right)\right) \\ &= e^{-\frac{n^2}{2m}} \pm O\left(\frac{n}{m}\right) \quad \left(\frac{n}{m} \rightarrow 0\right) \end{aligned}$$

Birthday Paradox

- ▶ Let's consider a different question to approach this . . .

- ▶ ***Birthday 'Paradox':***

How many people does it take to likely have two people with the same birthday?

- ▶ In balls-into-bins language: What n makes it likely that $\exists j \in [m] : X_j \geq 2$?

Compute counter-probability: $\mathbb{P}[\max X_j \leq 1]$

Taylor series $e^x = 1 + x \pm O(x^2)$ as $x \rightarrow 0$

$$\begin{aligned} 1 \cdot \left(1 - \frac{1}{m}\right) \cdot \left(1 - \frac{2}{m}\right) \cdots \left(1 - \frac{n-1}{m}\right) &= e^{-\frac{1}{m}} \cdot e^{-\frac{2}{m}} \cdots e^{-\frac{n-1}{m}} \cdot \left(1 \pm O\left(\left(\frac{n}{m}\right)^2\right)\right) \\ &= e^{-\frac{n^2}{2m}} \pm O\left(\frac{n}{m}\right) \quad \left(\frac{n}{m} \rightarrow 0\right) \end{aligned}$$

\rightsquigarrow Only for $n = \Theta(\sqrt{m})$ nontrivial probability

- ▶ $\mathbb{P}[\max X_j \leq 1] = \frac{1}{2}$ for $n \approx \sqrt{2m \ln(2)}$, so for $m = 365$ days, need $n \approx 22.49$ people

Birthday Paradox

- ▶ Let's consider a different question to approach this . . .

- ▶ ***Birthday 'Paradox':***

How many people does it take to likely have two people with the same birthday?

- ▶ In balls-into-bins language: What n makes it likely that $\exists j \in [m] : X_j \geq 2$?

Compute counter-probability: $\mathbb{P}[\max X_j \leq 1]$

Taylor series $e^x = 1 + x \pm O(x^2)$ as $x \rightarrow 0$

$$\begin{aligned} 1 \cdot \left(1 - \frac{1}{m}\right) \cdot \left(1 - \frac{2}{m}\right) \cdots \left(1 - \frac{n-1}{m}\right) &= e^{-\frac{1}{m}} \cdot e^{-\frac{2}{m}} \cdots e^{-\frac{n-1}{m}} \cdot \left(1 \pm O\left(\left(\frac{n}{m}\right)^2\right)\right) \\ &= e^{-\frac{n^2}{2m}} \pm O\left(\frac{n}{m}\right) \quad \left(\frac{n}{m} \rightarrow 0\right) \end{aligned}$$

\rightsquigarrow Only for $n = \Theta(\sqrt{m})$ nontrivial probability

- ▶ $\mathbb{P}[\max X_j \leq 1] = \frac{1}{2}$ for $n \approx \sqrt{2m \ln(2)}$, so for $m = 365$ days, need $n \approx 22.49$ people

\rightsquigarrow Can't expect to see **all** bins close to **expected** occupancy.

Fullest Bin

$$\hat{X} = \max_{j \in [m]} X_j$$

Theorem 9.1

If we throw n balls into n bins, then w.h.p., the *fullest bin* has $O\left(\frac{\log n}{\log \log n}\right)$ balls.

Proof:

$$\mathbb{P}[\max X_j \geq M] \leq m \cdot \mathbb{P}[X_1 \geq M]$$

union bound

$$\mathbb{P}[X_1 \geq M] = \mathbb{P}\left[\bigcup_{\substack{I \subseteq [n] \\ |I|=M}} \text{balls } i \in I \text{ land in bin 1}\right]$$

$$\leq \binom{n}{M} \mathbb{P}(|I| \text{ balls land in bin 1})$$

$$\leq \binom{n}{M} \left(\frac{1}{m}\right)^M$$

$\boxed{n=m}$

$$= \binom{n}{M} \left(\frac{1}{n}\right)^M = \frac{n!}{M! (n-M)! n^M} \leq \frac{n^M}{n^M} = 1$$

Fulllest Bin [2]

Proof (cont.):

$$\leq \frac{1}{M!} \quad \text{Stirling, } M! \geq \left(\frac{M}{e}\right)^M \sqrt{2\pi M}$$

$$\leq \left(\frac{e}{M}\right)^M \cdot \left(\frac{1}{\sqrt{2\pi M}}\right) \leq 1$$

$$\leq \left(\frac{e}{M}\right)^M \quad \text{need this} \leq \frac{1}{n}$$

$$\left(\frac{e}{M}\right)^M \approx \frac{1}{n} \quad M = c \frac{\ln n}{\ln \ln n}$$

$$\exp(\ln((\frac{e}{M})^M)) = \exp(M(\ln e - \ln M)) = \exp(-\ln n - \ln \ln n - \ln \ln n) \approx \frac{1}{n}$$

to show w.h.p. $\mathbb{P}[\hat{X} \geq M] = O(n^{-d})$

$$n \cdot \left(\frac{e}{M}\right)^M = n \cdot \left(\frac{e}{c} \cdot \frac{\ln \ln n}{\ln n}\right)^{c \frac{\ln n}{\ln \ln n}} \quad c > e$$

$$= \exp\left(\ln n + c \cdot \frac{\ln n}{\ln \ln n} \ln\left(\frac{\ln \ln n}{\ln n}\right)\right)$$

$$= \exp \left(\ln n + \ln n \cdot \frac{c \ln \ln \ln n}{\ln \ln n} - c \ln n \cdot \frac{\ln \ln n}{\ln \ln n} \right)$$

$$= \exp \left((1-c) \ln n + \ln n \cdot \frac{c \ln \ln \ln n}{\ln \ln n} \right)$$

$$= n^{2-c} \cdot \exp \left(\ln n \left(\frac{c \ln \ln \ln n}{\ln \ln n} - 1 \right) \right)$$

$$o(1) \leq 1 \text{ for large } n$$

$$\leq 1 \text{ for large } n$$

$$\leq n^{2-c} = O(n^{-d}) \quad \text{for } c > d+2$$

Fullest Bin – Consequences

- Closer analysis shows for $n = \alpha m$, constant α (“load factor”),

$$\max X_j = \frac{\ln n}{\ln(\ln(n)/\alpha)} \cdot (1 + o(1)) \text{ w.h.p.}$$

Fulllest Bin – Consequences

- Closer analysis shows for $n = \alpha m$, constant α (“load factor”),

$$\max X_j = \frac{\ln n}{\ln(\ln(n)/\alpha)} \cdot (1 + o(1)) \text{ w.h.p.}$$

What can we learn from this?

1. Under *uniform hashing assumption*, even **worst case** of chaining hashing cost beats BST.
2. ... but not by much.
3. Expected costs aren't fully informative for hashing;
(big difference between expected average case and expected worst case)

Fulllest Bin – Consequences

- Closer analysis shows for $n = \alpha m$, constant α (“load factor”),

$$\max X_j = \frac{\ln n}{\ln(\ln(n)/\alpha)} \cdot (1 + o(1)) \text{ w.h.p.}$$

What can we learn from this?

1. Under *uniform hashing assumption*, even **worst case** of chaining hashing cost beats BST.
2. ... but not by much.
3. Expected costs aren't fully informative for hashing;
(big difference between expected average case and expected worst case)

Biggest caveat: uniform hashing assumption!

↪ ... we'll come back to that

Fulllest Bin – Consequences

- Closer analysis shows for $n = \alpha m$, constant α (“load factor”),

$$\max X_j = \frac{\ln n}{\ln(\ln(n)/\alpha)} \cdot (1 + o(1)) \text{ w.h.p.}$$

What can we learn from this?

1. Under *uniform hashing assumption*, even **worst case** of chaining hashing cost beats BST.
2. ... but not by much.
3. Expected costs aren't fully informative for hashing;
(big difference between expected average case and expected worst case)

Biggest caveat: uniform hashing assumption!

↪ ... we'll come back to that

- Cool trick: *Power of 2 choices*

Assume *two* candidate bins per ball (hash functions), take less loaded bin

↪ $\max X_j = \ln \ln n / \ln 2 \pm O(1)$ (!)

analysis more technical; details in *Mitzenmacher & Upfal*

Coupon Collector

- ▶ Balls into bins nicely models other situations worth memorizing
- ▶ ***Coupon Collector Problem:***
How many (wrapped) packs do I need to buy to get all collectibles?

Coupon Collector

- ▶ Balls into bins nicely models other situations worth memorizing
 - ▶ **Coupon Collector Problem:**
How many (wrapped) packs do I need to buy to get all collectibles?
 - ▶ Balls-into-bins: What n makes it likely that $\forall j : X_j \geq 1$?
 - ▶ Define S_i as the number of balls to get from i empty bins to $i - 1$ empty bins.
- $\leadsto S = S_m + S_{m-1} + \cdots + S_1$ is the total number of balls for coupon collector

Coupon Collector

- ▶ Balls into bins nicely models other situations worth memorizing
- ▶ **Coupon Collector Problem:**
How many (wrapped) packs do I need to buy to get all collectibles?
- ▶ Balls-into-bins: What n makes it likely that $\forall j : X_j \geq 1$?
 - ▶ Define S_i as the number of balls to get from i empty bins to $i - 1$ empty bins.
 - $\leadsto S = S_m + S_{m-1} + \cdots + S_1$ is the total number of balls for coupon collector
 - ▶ $S_i \stackrel{\mathcal{D}}{=} \text{Geo}(p_i)$ where $p_i = \frac{i}{m}$

Coupon Collector

- ▶ Balls into bins nicely models other situations worth memorizing

- ▶ **Coupon Collector Problem:**

How many (wrapped) packs do I need to buy to get all collectibles?

- ▶ Balls-into-bins: What n makes it likely that $\forall j : X_j \geq 1$?

- ▶ Define S_i as the number of balls to get from i empty bins to $i - 1$ empty bins.

$\rightsquigarrow S = S_m + S_{m-1} + \dots + S_1$ is the total number of balls for coupon collector

- ▶ $S_i \stackrel{\mathcal{D}}{=} \text{Geo}(p_i)$ where $p_i = \frac{i}{m} \rightsquigarrow \mathbb{E}[S_i] = \frac{1}{p_i} = \frac{m}{i}$

Coupon Collector

- ▶ Balls into bins nicely models other situations worth memorizing

- ▶ **Coupon Collector Problem:**

How many (wrapped) packs do I need to buy to get all collectibles?

- ▶ Balls-into-bins: What n makes it likely that $\forall j : X_j \geq 1$?

- ▶ Define S_i as the number of balls to get from i empty bins to $i - 1$ empty bins.

$\rightsquigarrow S = S_m + S_{m-1} + \dots + S_1$ is the total number of balls for coupon collector

- ▶ $S_i \stackrel{\mathcal{D}}{=} \text{Geo}(p_i)$ where $p_i = \frac{i}{m} \rightsquigarrow \mathbb{E}[S_i] = \frac{1}{p_i} = \frac{m}{i}$

- ▶
$$\mathbb{E}[S] = \sum_{i=1}^m \mathbb{E}[S_i] = m \sum_{i=1}^m \frac{1}{i} = mH_m = m \ln m \pm O(m)$$

Coupon Collector

- ▶ Balls into bins nicely models other situations worth memorizing

- ▶ **Coupon Collector Problem:**

How many (wrapped) packs do I need to buy to get all collectibles?

- ▶ Balls-into-bins: What n makes it likely that $\forall j : X_j \geq 1$?

- ▶ Define S_i as the number of balls to get from i empty bins to $i - 1$ empty bins.

$\rightsquigarrow S = S_m + S_{m-1} + \dots + S_1$ is the total number of balls for coupon collector

- ▶ $S_i \stackrel{\mathcal{D}}{=} \text{Geo}(p_i)$ where $p_i = \frac{i}{m}$ $\rightsquigarrow \mathbb{E}[S_i] = \frac{1}{p_i} = \frac{m}{i}$

- ▶
$$\mathbb{E}[S] = \sum_{i=1}^m \mathbb{E}[S_i] = m \sum_{i=1}^m \frac{1}{i} = mH_m = m \ln m \pm O(m)$$

- ▶ Can similarly show $\text{Var}[S] = \Theta(m^2)$

(since S_i are independent, stdev is linear + using $\text{Var}[S_i] = \frac{1 - p_i}{p_i^2}$)

$\rightsquigarrow \sigma[S] = \Theta(m) = o(\mathbb{E}[S])$, so S converges in probability to $\mathbb{E}[S]$ (Chebyshev)

9.2 Universal Hashing

Randomized Hashing

- ▶ Balls-into-bins model is worryingly optimistic.
 - ▶ Assumes that chosen bins $B_1, \dots, B_n \in [m]$ are *mutually independent*.
 - ↪ Assumes both that input is not adversarial **and** that hash functions work well.

Randomized Hashing

- ▶ Balls-into-bins model is worryingly optimistic.
 - ▶ Assumes that chosen bins $B_1, \dots, B_n \in [m]$ are *mutually independent*.
 - ↪ Assumes both that input is not adversarial **and** that hash functions work well.
- ↪ To replace the assumption about the input by explicit randomization, would need a *fully random hash function* $h : [n] \rightarrow [m]$
 - ▶ if we were to uniformly choose from m^n possibilities we'd need to store $\lg(m^n) = n \lg m$ bits just for h
 - ▶ (even if we did so, how to efficiently *evaluate* h then is unclear)
 - ⚡ too expensive

Randomized Hashing

- ▶ Balls-into-bins model is worryingly optimistic.
 - ▶ Assumes that chosen bins $B_1, \dots, B_n \in [m]$ are *mutually independent*.
 - ↪ Assumes both that input is not adversarial **and** that hash functions work well.
- ↪ To replace the assumption about the input by explicit randomization, would need a *fully random hash function* $h : [n] \rightarrow [m]$
 - ▶ if we were to uniformly choose from m^n possibilities we'd need to store $\lg(m^n) = n \lg m$ bits just for h
 - ▶ (even if we did so, how to efficiently *evaluate* h then is unclear)
 - ⚡ too expensive
- ↪ Pick h at random, but from a smaller class \mathcal{H} of “convenient” functions

Universal Hashing

What's a convenient class?

Definition 9.2 (Universal Family)

Let \mathcal{H} be a set of hash functions from U to $[m]$ and $|U| \geq m$.

Assume $h \in \mathcal{H}$ is chosen uniformly at random.

(a) Then \mathcal{H} is called a *universal* if

$$\forall x_1, x_2 \in U : x_1 \neq x_2 \implies \mathbb{P}_h[h(x_1) = h(x_2)] \leq \frac{1}{m}.$$

(b) \mathcal{H} is called *strongly universal* or *pairwise independent* if

$$\forall x_1, x_2 \in U, y_1, y_2 \in R : x_1 \neq x_2 \implies \mathbb{P}_h[h(x_1) = y_1 \wedge h(x_2) = y_2] \leq \frac{1}{m^2}.$$



Universal Hashing

What's a convenient class?

Definition 9.2 (Universal Family)

Let \mathcal{H} be a set of hash functions from U to $[m]$ and $|U| \geq m$.

Assume $h \in \mathcal{H}$ is chosen uniformly at random.

(a) Then \mathcal{H} is called a *universal* if

$$\forall x_1, x_2 \in U : x_1 \neq x_2 \implies \mathbb{P}[h(x_1) = h(x_2)] \leq \frac{1}{m}.$$

(b) \mathcal{H} is called *strongly universal* or *pairwise independent* if

$$\forall x_1, x_2 \in U, y_1, y_2 \in R : x_1 \neq x_2 \implies \mathbb{P}[h(x_1) = y_1 \wedge h(x_2) = y_2] \leq \frac{1}{m^2}.$$

- ▶ strong universal implies universal
- ▶ In the following, always assume (uniformly) **random** $h \in \mathcal{H}$.
- ▶ by contrast, x_1, \dots, x_n may be chosen adversarially (but all distinct) from $[u]$

Examples of universal families

$$h_{ab}(x) = (a \cdot x + b \bmod p) \bmod m \quad p \text{ prime}, p \geq m$$

$$h_a(x) = (a \cdot x \bmod 2^k) \operatorname{div} 2^{k-\ell} \quad u = 2^k, m = 2^\ell$$

- ▶ $\mathcal{H}_1 = \{h_{ab} : a \in [1..p), b \in [0..p)\}$ is universal
- ▶ $\mathcal{H}_0 = \{h_{ab} : a \in [\underline{0}..p), b \in [0..p)\}$ is strongly universal
- ▶ $\mathcal{H}_2 = \{h_a : a \in [1..2^k), a \text{ odd}\}$ is universal



How good is universal hashing?

$$\hat{X} \approx \frac{\text{balls into bins}}{n} \approx \frac{2n}{2n}$$

Theorem 9.3

Assign $x_1, \dots, x_n \in [u]$ to bins $h(x_i) \in [m]$ using hash function h , uniformly chosen from a universal family of hash functions \mathcal{H} .

Let X_j be the load of bin $j \in [m]$.

$$n = m \sqrt{2n}$$

$$\text{Then } \mathbb{P} \left[\max_j X_j \geq \sqrt{2} \cdot \frac{n}{\sqrt{m}} \right] \leq \frac{1}{2}.$$

$$X_j \stackrel{D}{=} \text{Bin}(n, p)$$

Proof:

$$C_{ij} = 'x_i \text{ and } x_j \text{ collide}' = [h(x_i) = h(x_j)]$$

$$\Rightarrow \mathbb{P}[C_{ij}] \leq \frac{1}{m}$$

$$C = \sum_{1 \leq i < j \leq n} C_{ij}$$

$$\mathbb{E}[C] = \sum \mathbb{E}[C_{ij}] \leq \binom{n}{2} \cdot \frac{1}{m} < \frac{n^2}{2m}$$

$$\hat{X} \text{ itself implies } \binom{\hat{X}}{2} \text{ collisions}$$

$$\Rightarrow C \geq \binom{\hat{X}}{2} = \frac{\hat{X}(\hat{X}-1)}{2} \geq \frac{(\hat{X}-1)^2}{2}$$

How good is universal hashing [2]

Proof:

$$\mathbb{P}\left[\hat{X} \geq n\sqrt{\frac{2}{m}}\right] \leq \mathbb{P}\left[C \geq \frac{n^2}{m}\right] = \mathbb{P}\left[C \geq 2 \cdot \mathbb{E}[C]\right] \leq \frac{1}{2}$$

then $\hat{X}^2 \geq n\sqrt{\frac{2}{m}} + 1$ implies

$$\frac{(\hat{X}-1)^2}{2} \geq \frac{n^2}{m} \text{ which implies}$$

$$C \geq \frac{n^2}{m}$$

□

So, how good is universal hashing?

- ▶ For $n = m$, fullest bin $\leq \sqrt{2n}$
- ▶ Much worse than $\Theta(\log n / \log \log n)$!

So, how good is universal hashing?

- ▶ For $n = m$, fullest bin $\leq \sqrt{2n}$
- ▶ Much worse than $\Theta(\log n / \log \log n)$!
- ▶ Note that we only proved an upper bound, however
 - ▶ bound is tight in the worst case
(if all we know is pairwise independence of hash values)
 \rightsquigarrow exercises
 - ▶ for practical choices like $\mathcal{H}_0, \mathcal{H}_1, \mathcal{H}_2$ better bounds are proven
(close to $O(n^{1/3})$ instead of $O(n^{1/2})$)
but still far worse than uniform hashing

9.3 Perfect Hashing

Perfect Hashing: Random Sampling

A hash function $h : [u] \rightarrow [m]$ is called

- ▶ *perfect* for a set $\mathcal{X} = \{x_1, \dots, x_n\} \subset [u]$ if $i \neq j$ implies $h(x_i) \neq h(x_j)$
- ▶ *minimal* for set $\mathcal{X} = \{x_1, \dots, x_n\} \subset [u]$ if $m = n$

Perfect Hashing


- ▶ only possible for $n \leq m$
- ▶ stringent requirement \rightsquigarrow here focus on static \mathcal{X}
 - ▶ carefully chosen variants with partial rebuilding allow insertion and deletion in $O(1)$ amortized expected time

Perfect Hashing: Random Sampling

A hash function $h : [u] \rightarrow [m]$ is called

- ▶ *perfect* for a set $\mathcal{X} = \{x_1, \dots, x_n\} \subset [u]$ if $i \neq j$ implies $h(x_i) \neq h(x_j)$
- ▶ *minimal* for set $\mathcal{X} = \{x_1, \dots, x_n\} \subset [u]$ if $m = n$

Perfect Hashing

- ▶ only possible for $n \leq m$
 - ▶ stringent requirement \rightsquigarrow here focus on static \mathcal{X}
 - ▶ carefully chosen variants with partial rebuilding allow insertion and deletion in $O(1)$ amortized expected time
 - ▶ further requirements
 1. Hash function must be fast to evaluate (ideally $O(1)$ time)
 2. Hash function must be small to store (ideally $O(n)$ space)
 3. should be fast to compute given \mathcal{X} (ideally $O(n)$ time)
 4. Have small m (ideally $m = \Theta(n)$)
- 

Perfect Hashing: Simple, but space inefficient

Start simple: pick $h \in \mathcal{H}$ from universal class

what can we guarantee? n fixed

\Rightarrow increase m until likely that h perfect

birthday paradox: $n \approx \sqrt{m}$

So let's try $m \geq n^2$

$\hat{X} \geq 2$ implies $C \geq 1$

which implies $C \geq \frac{n^2}{m}$

$$\mathbb{P}[\hat{X} \geq 2] \leq \mathbb{P}\left[C \geq \frac{n^2}{m}\right] = \mathbb{P}\left[C \geq 2\mathbb{E}[C]\right] \leq \frac{1}{2}$$


as for universal hashing above

$$\Rightarrow \mathbb{P}\{\text{no collisions}\} \geq \frac{1}{2}$$

good prob. to get a perfect hash function!

\hookrightarrow HT has n^2 space

Perfect Hashing: Two-tier solution



$O(n)$ tier 1 buckets

for each tier 1 bucket i

choose $h_2^{(i)}$ as above

using $m_i = X_i^2$ $X_i = \# \text{ elements in bucket } i$

↳ after expected linear time

over hash function is perfect

$$x \mapsto h_2^{(h_1(x))}(x)$$

To show: overall space (for all secondary hash tables) small

Perfect Hashing.

① Choose h , uniformly from \mathcal{H} (universal)
with $m = n$ bins until C (#collisions) $\leq n$

② For each bucket $i = 1, \dots, n$

If $X_i \geq 2$ draw random hash function $h_2^{(i)}$ from \mathcal{H}' (universal)

with X_i^2 bins

repeat until $h_2^{(i)}$ perfect

$$X_i \text{ in bin} \Rightarrow \binom{X_i}{2} \text{ collisions}$$

$$\frac{X_i^2}{2} - \frac{X_i}{2}$$

③ Output $h_2^{(h_1(x))}$

Claim: (a) #repetitions small

(b) space usage small

(a) ① $\mathbb{E}[C] = \binom{n}{2} \cdot \frac{1}{n} = \frac{n-1}{2} \xrightarrow{\text{Markov}} \mathbb{P}[C \leq n] \geq \frac{1}{2}$

② see above: $\mathbb{E} \# \text{ rep.} = 2$

$$\Rightarrow \mathbb{E} \text{ time} = O(n)$$

(b) space = $\underbrace{\Theta(n)}_{\substack{\text{top level HT} \\ \text{and all } h_2^{(i)} h_1}} + \sum_{i=1}^n X_i^2 = \Theta(n) + \underbrace{\sum \binom{X_i}{2}}_{= C \leq n} + \underbrace{\sum \frac{X_i}{2}}_{\leq n}$

$$= \Theta(n)$$

9.4 Primality Testing

Abundance of Witnesses

- ▶ Suppose $L \in \text{NP}$ and all of the following are true:
 - ▶ alleged certificate must be easy to check trivially in polytime; often very fast
 - ▶ for $x \in L$, there are **many** certificates that show $x \in L$ not generally true, but sometimes!

↪ Conceivable that a randomized algorithm succeeds:

- ▶ Guess a random certificate string
- ▶ Check if it decides the problem

Primality Testing

Testing if a given number n is *prime* is one of the oldest algorithmic questions.

Trivial approach: test for all (primes) $p \leq \sqrt{n}$ whether $p \mid n$

```
1 procedure sieveOfEratosthenes( $n$ ):
2    $isPrime[2..n] := true$ 
3   for  $i := 2, 3, \dots, \lfloor \sqrt{n} \rfloor$ 
4     if  $isPrime[i]$ 
5       for  $j = i, i + 1, i + 2, \dots, \lfloor n/i \rfloor$ 
6          $isPrime[i \cdot j] := false$ 
7   return  $\{p \in [2..n] : isPrime[p]\}$ 
8
9 procedure isPrimeTrivial( $n$ ):
10   $P := sieveOfEratosthenes(\lfloor \sqrt{n} \rfloor)$ 
11  return  $\forall p \in P : p \nmid n$ 
```

Primality Testing

Testing if a given number n is *prime* is one of the oldest algorithmic questions.

Trivial approach: test for all (primes) $p \leq \sqrt{n}$ whether $p \mid n$

```
1 procedure sieveOfEratosthenes( $n$ ):
2    $isPrime[2..n] := true$ 
3   for  $i := 2, 3, \dots, \lfloor \sqrt{n} \rfloor$ 
4     if  $isPrime[i]$ 
5       for  $j = i, i + 1, i + 2, \dots, \lfloor n/i \rfloor$ 
6          $isPrime[i \cdot j] := false$ 
7   return  $\{p \in [2..n] : isPrime[p]\}$ 
8
9 procedure isPrimeTrivial( $n$ ):
10   $P := sieveOfEratosthenes(\lfloor \sqrt{n} \rfloor)$ 
11  return  $\forall p \in P : p \nmid n$ 
```

Running time:

► dominated by sieving primes up to $m = \lfloor \sqrt{n} \rfloor$

$$\text{► } T(m) \leq m + \sum_{\substack{p \leq m \\ p \text{ prime}}} \frac{m}{p} \leq m + m \sum_{p=1}^m \frac{1}{p}$$

$$\rightsquigarrow T(m) = O(m \log m)$$

Primality Testing

Testing if a given number n is *prime* is one of the oldest algorithmic questions.

Trivial approach: test for all (primes) $p \leq \sqrt{n}$ whether $p \mid n$

```
1 procedure sieveOfEratosthenes( $n$ ):
2    $isPrime[2..n] := true$ 
3   for  $i := 2, 3, \dots, \lfloor \sqrt{n} \rfloor$ 
4     if  $isPrime[i]$ 
5       for  $j = i, i + 1, i + 2, \dots, \lfloor n/i \rfloor$ 
6          $isPrime[i \cdot j] := false$ 
7   return  $\{p \in [2..n] : isPrime[p]\}$ 
8
9 procedure isPrimeTrivial( $n$ ):
10   $P := sieveOfEratosthenes(\lfloor \sqrt{n} \rfloor)$ 
11  return  $\forall p \in P : p \nmid n$ 
```

Running time:

► dominated by sieving primes up to $m = \lfloor \sqrt{n} \rfloor$

$$\text{► } T(m) \leq m + \sum_{\substack{p \leq m \\ p \text{ prime}}} \frac{m}{p} \leq m + m \sum_{p=1}^m \frac{1}{p}$$

$$\rightsquigarrow T(m) = O(m \log m)$$

► closer analysis: actually $T(m) = O(m \log \log m)$

Space: \sqrt{n} bits

Complexity of Primality Testing and Factorization

- ▶ PRIMES:

- ▶ **Given:** Integer n in binary encoding
- ▶ **Goal:** Check if n is a prime number

- ▶ INTEGERFACTORIZATION:

- ▶ **Given:** Integer n in binary encoding
- ▶ **Goal:** Find nontrivial factors $n = m_1 \cdot m_2, 2 \leq m_1, m_2 < n$ or determine “ n prime”

Complexity of Primality Testing and Factorization

- ▶ PRIMES:
 - ▶ **Given:** Integer n in binary encoding
 - ▶ **Goal:** Check if n is a prime number
- ▶ INTEGERFACTORIZATION:
 - ▶ **Given:** Integer n in binary encoding
 - ▶ **Goal:** Find nontrivial factors $n = m_1 \cdot m_2, 2 \leq m_1, m_2 < n$ or determine “ n prime”
- ▶ If n is composite, a factorization is a certificate for *non-primality* \rightsquigarrow PRIMES \in CO-NP
 - ▶ n encoded in binary \rightsquigarrow Sieve of Eratosthenes is pseudopolynomial \in NP ?

Complexity of Primality Testing and Factorization

- ▶ PRIMES:
 - ▶ **Given:** Integer n in binary encoding
 - ▶ **Goal:** Check if n is a prime number
- ▶ INTEGERFACTORIZATION:
 - ▶ **Given:** Integer n in binary encoding
 - ▶ **Goal:** Find nontrivial factors $n = m_1 \cdot m_2, 2 \leq m_1, m_2 < n$ or determine “ n prime”
- ▶ If n is composite, a factorization is a certificate for *non-primality* \rightsquigarrow PRIMES \in co-NP
 - ▶ n encoded in binary \rightsquigarrow Sieve of Eratosthenes is pseudopolynomial
- ▶ we will show PRIMES \in co-RP \subset BPP

Complexity of Primality Testing and Factorization

- ▶ PRIMES:
 - ▶ **Given:** Integer n in binary encoding
 - ▶ **Goal:** Check if n is a prime number
- ▶ INTEGERFACTORIZATION:
 - ▶ **Given:** Integer n in binary encoding
 - ▶ **Goal:** Find nontrivial factors $n = m_1 \cdot m_2, 2 \leq m_1, m_2 < n$ or determine “ n prime”
- ▶ If n is composite, a factorization is a certificate for *non-primality* \rightsquigarrow PRIMES \in CO-NP
 - ▶ n encoded in binary \rightsquigarrow Sieve of Eratosthenes is pseudopolynomial
- ▶ we will show PRIMES \in CO-RP \subset BPP
- ▶ Major theoretical breakthrough: PRIMES \in P Agrawal, Kayal, and Saxena (2004)
- ▶ This is not known for INTEGERFACTORIZATION
 - ▶ Indeed much of classic cryptography (RSA) builds on factoring being intractable
 - ▶ *Shor's algorithm* can factor integers on a (theoretical) quantum computer in polytime! (not clear whether or when this is a practical concern)

Does PRIMES have abundance of witnesses?

try the obvious: NOTPRIME

factors? composite numbers w/ 2 large prime factors $\{$

hardly promising approach

since it solves FACTORIZATION

Primality Testing: Fermat's Little Theorem

Theorem 9.4 (Fermat's Little Theorem)

For p a prime and $a \in [1..p-1]$ holds

$$a^{p-1} \equiv 1 \pmod{p} \quad (*)$$

Pick a random $a \in [1..p-1]$, compute $a^{p-1} \bmod p$ If $\neq 1$

$\Rightarrow p$ not prime.

only \Rightarrow , not \Leftarrow

indeed Carmichael numbers are not prime, but fulfill $(*)$

Primality Testing: Second Attempt

Theorem 9.5 (Euler's Criterion)

Let $p > 2$ an odd number.

field \mathbb{Z} modulo p

$$p \text{ prime} \iff \forall a \in \mathbb{Z}_p \setminus \{0\} : a^{\frac{p-1}{2}} \bmod p \in \{1, -1\}$$



Primality Testing: Second Attempt

Theorem 9.5 (Euler's Criterion)

Let $p > 2$ an odd number.

$$p \text{ prime} \iff \forall a \in \mathbb{Z}_p \setminus \{0\} : a^{\frac{p-1}{2}} \bmod p \in \{1, -1\}$$

Theorem 9.6 (Number of Witnesses)

For every odd $n \in \mathbb{N}$, $(n-1)/2$ odd, we have:

1. If n is prime then $a^{(n-1)/2} \bmod n \in \{1, n-1\}$, for all $a \in \{1, \dots, n-1\}$.
2. If n is not prime then $a^{(n-1)/2} \bmod n \notin \{1, n-1\}$ for at least half of the elements in $\{1, \dots, n-1\}$.

Simple Solovay-Strassen Primality Test

Input: an odd number n with $(n - 1)/2$ odd.

1. Choose a random $a \in \{1, 2, \dots, n - 1\}$.
2. Compute $A := a^{(n-1)/2} \bmod n$.
3. If $A \in \{1, n - 1\}$ then output “ n probably prime” (reject);
4. otherwise output “ n not prime” (accept).

Simple Solovay-Strassen Primality Test

Input: an odd number n with $(n - 1)/2$ odd.

1. Choose a random $a \in \{1, 2, \dots, n - 1\}$.
2. Compute $A := a^{(n-1)/2} \bmod n$.
3. If $A \in \{1, n - 1\}$ then output “ n probably prime” (reject);
4. otherwise output “ n not prime” (accept).

Theorem 9.7 (Correctness)

The simple Solovay-Strassen algorithm is a polynomial **OSE-MC** algorithm to detect composite numbers n with $n \bmod 4 = 3$.



Simple Solovay-Strassen Primality Test

Input: an odd number n with $(n - 1)/2$ odd.

1. Choose a random $a \in \{1, 2, \dots, n - 1\}$.
2. Compute $A := a^{(n-1)/2} \bmod n$.
3. If $A \in \{1, n - 1\}$ then output “ n probably prime” (reject);
4. otherwise output “ n not prime” (accept).

Theorem 9.7 (Correctness)

The simple Solovay-Strassen algorithm is a polynomial **OSE-MC** algorithm to detect composite numbers n with $n \bmod 4 = 3$.

Corollary 9.8

For positive integers n with $n \bmod 4 = 3$ the simple Solovay-Strassen algorithm provides a polynomial **TSE-MC** algorithm to detect prime numbers.

Sampling Primes

RANDOMPRIME(ℓ, k) Input: $\ell, k \in \mathbb{N}, \ell \geq 3$.

1. Set $X :=$ "not found yet"; $I := 0$;
2. while $X =$ "not found yet" and $I < 2\ell^2$ do
 - ▶ generate random bit string $a_1, a_2, \dots, a_{\ell-2}$ and
 - ▶ compute $n := 2^{\ell-1} + \sum_{i=1}^{\ell-2} a_i \cdot 2^i + 1$
// This way n becomes a random, odd number of length ℓ
 - ▶ Realize k independent runs of Solovay-Strassen-algorithm on n ;
 - ▶ if at least one output says " $n \notin PRIMES$ " then $I := I + 1$
else $X :=$ "PN found"; output n ;
3. if $I = 2 \cdot \ell^2$ then output "no PN found".

Thm: RandomPrime(ℓ, ℓ) is TSE-MC, $O(\ell^5)$ poly-time for generating primes of length ℓ .

It shows (a) output prime w/ prob $(\frac{1}{2})^k$
(b) does not fail w/ prob $\frac{1}{2\ell}$

key ingredient : prob to hit a prime number

when choosing odd n uniformly $\in [2^{e-1}, 2^e)$

Prime Number Theorem : $\pi(x) = \#\text{primes} \leq x$

$$= \frac{x}{\ln(x)} (1 + o(1))$$

\leadsto # repetitions to sample prime $\approx \ell$

9.5 Schönning's Satisfiability

Random Sampling

If a solution is tricky to construct in a target fashion,
but many solutions are known to exist, random sampling can help.

Generate random object according to simple procedure until solution found.

We've seen ideas of random sampling in perfect hashing.

Now: Use more aggressive sampling to find rare objects.

Warmup: 2SAT

Famously, 3SAT is NP-complete.

2SAT: Given CNF formula φ with ≤ 2 literals per clause; is φ satisfiable?

Warmup: 2SAT

Famously, 3SAT is NP-complete.

2SAT: Given CNF formula φ with ≤ 2 literals per clause; is φ satisfiable?

By contrast, 2SAT $\in P$

Warmup: 2SAT

Famously, 3SAT is NP-complete.

2SAT: Given CNF formula φ with ≤ 2 literals per clause; is φ satisfiable?

By contrast, 2SAT $\in P$

$$a \rightarrow b \equiv \neg a \vee b$$

Idea: Any clause $(\ell_1 \vee \ell_2)$ is equivalent to the *implications* $\neg \ell_1 \rightarrow \ell_2$ and $\neg \ell_2 \rightarrow \ell_1$

\rightsquigarrow Represent formula as *implication graph*:

- ▶ vertices = literals in φ
- ▶ edges = all implications equivalent to some clause

Warmup: 2SAT

Famously, 3SAT is NP-complete.

2SAT: Given CNF formula φ with ≤ 2 literals per clause; is φ satisfiable?

By contrast, 2SAT $\in P$

Idea: Any clause $(\ell_1 \vee \ell_2)$ is equivalent to the *implications* $\neg\ell_1 \rightarrow \ell_2$ and $\neg\ell_2 \rightarrow \ell_1$

\rightsquigarrow Represent formula as *implication graph*:

- ▶ vertices = literals in φ
- ▶ edges = all implications equivalent to some clause

\rightsquigarrow Can show: φ satisfiable \iff no SCC contains both x_i and $\neg x_i$

- ▶ SCCs computable in linear time
- ▶ indeed, if no strong component contains contradiction, topological sort of components allows to read off satisfying assignment

strongly connected component

Warmup: 2SAT

Famously, 3SAT is NP-complete.

2SAT: Given CNF formula φ with ≤ 2 literals per clause; is φ satisfiable?

By contrast, 2SAT $\in P$

Idea: Any clause $(\ell_1 \vee \ell_2)$ is equivalent to the *implications* $\neg\ell_1 \rightarrow \ell_2$ and $\neg\ell_2 \rightarrow \ell_1$

\rightsquigarrow Represent formula as *implication graph*:

- ▶ vertices = literals in φ
- ▶ edges = all implications equivalent to some clause

\rightsquigarrow Can show: φ satisfiable \iff no SCC contains both x_i and $\neg x_i$

- ▶ SCCs computable in linear time
- ▶ indeed, if no strong component contains contradiction, topological sort of components allows to read off satisfying assignment

\rightsquigarrow Basically, a solved problem . . . we will use it for demonstration purposes only

Warmup: A randomized 2SAT algorithm

```
1 procedure localSearch2SAT( $\varphi$ , confidence):  
2    $k :=$  number of variables in  $\phi$   
3   Choose assignment  $\alpha \in \{0, 1\}^k$  uniformly at random.  
4   for  $j = 1, \dots, \text{confidence} \cdot 2k^2$   
5     if  $\alpha$  fulfills  $\varphi$  return  $\alpha$  // satisfiable!  
6     Arbitrarily choose clause  $C = \ell_1 \vee \ell_2$  not satisfied under  $\alpha$ .  
7     Choose  $\ell$  from  $\{\ell_1, \ell_2\}$  uniformly at random.  
8      $\alpha =$  assignment obtained by negating  $\ell$ .  
9   return PROBABLY_NOT_SATISFIABLE
```

Warmup: A randomized 2SAT algorithm


```
1 procedure localSearch2SAT( $\varphi$ , confidence):  
2    $k :=$  number of variables in  $\phi$   
3   Choose assignment  $\alpha \in \{0, 1\}^k$  uniformly at random.  
4   for  $j = 1, \dots, \text{confidence} \cdot 2k^2$   
5     if  $\alpha$  fulfills  $\varphi$  return  $\alpha$  // satisfiable!  
6     Arbitrarily choose clause  $C = \ell_1 \vee \ell_2$  not satisfied under  $\alpha$ .  
7     Choose  $\ell$  from  $\{\ell_1, \ell_2\}$  uniformly at random.  
8      $\alpha =$  assignment obtained by negating  $\ell$ .  
9   return PROBABLY_NOT_SATISFIABLE
```

Theorem 9.10 (localSearch2SAT is OSE-MC for 2SAT)

Let φ be a 2SAT formula.

1. If φ is unsatisfiable, localSearch2SAT always returns PROBABLY_NOT_SATISFIABLE.
2. If φ is satisfiable, localSearch2SAT returns satisfying assignment with probability at least $1 - 2^{-\text{confidence}}$.
3. localSearch2SAT runs in $O(\text{confidence} \cdot k^2 n)$ time.





X_t

$y_i =$ starting in i expected # step until k

Randomized 2SAT – Analysis

Proof:

Claims 1. and 3. are trivial. It remains to prove Claim 2.



Randomized 2SAT – Analysis

Proof:

Claims 1. and 3. are trivial. It remains to prove Claim 2.

localSearch2SAT starts with random $\alpha = \alpha_0$.

In iteration t , flip one variable in α_t to obtain α_{t+1} .



Randomized 2SAT – Analysis

Proof:

Claims 1. and 3. are trivial. It remains to prove Claim 2.

localSearch2SAT starts with random $\alpha = \alpha_0$.

In iteration t , flip one variable in α_t to obtain α_{t+1} .

We will analyze a *simplified* random process W that never behaves worse than localSearch2SAT

~> obtain an upper bound on error probability.

Randomized 2SAT – Analysis

Proof:

Claims 1. and 3. are trivial. It remains to prove Claim 2.

localSearch2SAT starts with random $\alpha = \alpha_0$.

In iteration t , flip one variable in α_t to obtain α_{t+1} .

We will analyze a *simplified* random process W that never behaves worse than localSearch2SAT

\rightsquigarrow obtain an upper bound on error probability.

φ satisfiable $\rightsquigarrow \exists \alpha^*$ that satisfies φ .

W will stop iff $\alpha = \alpha^*$ (localSearch2SAT might stop sooner)

Randomized 2SAT – Analysis

Proof:

Claims 1. and 3. are trivial. It remains to prove Claim 2.

localSearch2SAT starts with random $\alpha = \alpha_0$.

In iteration t , flip one variable in α_t to obtain α_{t+1} .

We will analyze a *simplified* random process W that never behaves worse than localSearch2SAT

\rightsquigarrow obtain an upper bound on error probability.

φ satisfiable $\rightsquigarrow \exists \alpha^*$ that satisfies φ .

W will stop iff $\alpha = \alpha^*$ (localSearch2SAT might stop sooner)

We measure W 's progress via $X_t = k - d_H(\alpha_t, \alpha^*)$.

While localSearch2SAT starts at a random α , we let W start at $\alpha_0 = \neg\alpha^*$. So $X_0 = 0$.

Randomized 2SAT – Analysis

Proof:

Claims 1. and 3. are trivial. It remains to prove Claim 2.

localSearch2SAT starts with random $\alpha = \alpha_0$.

In iteration t , flip one variable in α_t to obtain α_{t+1} .

We will analyze a *simplified* random process W that never behaves worse than localSearch2SAT

\rightsquigarrow obtain an upper bound on error probability.

φ satisfiable $\rightsquigarrow \exists \alpha^*$ that satisfies φ .

W will stop iff $\alpha = \alpha^*$ (localSearch2SAT might stop sooner)

We measure W 's progress via $X_t = k - d_H(\alpha_t, \alpha^*)$.

While localSearch2SAT starts at a random α , we let W start at $\alpha_0 = \neg\alpha^*$. So $X_0 = 0$.

$C = \ell_1 \vee \ell_2$ not satisfied $\rightsquigarrow \alpha^*$ and α_t differ in one or both

in either case, flipping random one gets closer to α^* with prob. $\geq \frac{1}{2}$

Randomized 2SAT – Analysis

Proof:

Claims 1. and 3. are trivial. It remains to prove Claim 2.

localSearch2SAT starts with random $\alpha = \alpha_0$.

In iteration t , flip one variable in α_t to obtain α_{t+1} .

We will analyze a *simplified* random process W that never behaves worse than localSearch2SAT

\rightsquigarrow obtain an upper bound on error probability.

φ satisfiable $\rightsquigarrow \exists \alpha^*$ that satisfies φ .

W will stop iff $\alpha = \alpha^*$ (localSearch2SAT might stop sooner)

We measure W 's progress via $X_t = k - d_H(\alpha_t, \alpha^*)$.

While localSearch2SAT starts at a random α , we let W start at $\alpha_0 = \neg\alpha^*$. So $X_0 = 0$.

$C = \ell_1 \vee \ell_2$ not satisfied $\rightsquigarrow \alpha^*$ and α_t differ in one or both

in either case, flipping random one gets closer to α^* with prob. $\geq \frac{1}{2}$


Assume W makes correct flip with prob $= \frac{1}{2}$.

$\rightsquigarrow \mathbb{P}[X_{t+1} = X_t + \mathbf{1} \mid X_t] = \frac{1}{2}$ and $\mathbb{P}[X_{t+1} = X_t - \mathbf{1} \mid X_t] = \frac{1}{2}$

(except $X_t = 0$, then always +1 and $X_t = k$, then terminate)

$(X_t)_{t \geq 0}$ is thus a *Markov process*.

Randomized 2SAT – Analysis [2]



Proof (cont.):

Let now y_i be the expected number of steps to reach state k from $X = i$.

$$y_k = 0$$

$$y_0 = 1 + y_1$$

$$y_i = 1 + p_i \cdot y_{i+1} + q_i \cdot y_{i-1} \quad q_i = 1 - p_i \quad \text{for us } p_i = \frac{1}{2} \quad 1 \leq i \leq k-1$$

Randomized 2SAT – Analysis [2]

Proof (cont.):

Let now y_i be the expected number of steps to reach state k from $X = i$.

$$y_k = 0$$

$$y_0 = 1 + y_1$$

$$y_i = 1 + p_i \cdot y_{i+1} + q_i \cdot y_{i-1} \quad q_i = 1 - p_i \quad \text{for us } p_i = \frac{1}{2}$$

Can solve this recurrence for general p_i by writing for $i \in [1..k)$:

$$\underline{p_i y_i} + \underline{q_i y_i} = y_i = \underline{1} + \underline{p_i y_{i+1}} + \underline{q_i y_{i-1}}$$

rearrange to $p_i(y_{i+1} - y_i) = \underline{q_i(y_i - y_{i-1})} - \underline{1}$. Now divide by p_i .

$$\rightsquigarrow \text{Recurrence of differences:} \quad \dot{y}_i = \frac{q_i}{p_i} \dot{y}_{i-1} - \frac{1}{p_i}$$

Write $\boxed{\dot{y}_i = y_{i+1} - y_i}$ and abbreviate $a_i = q_i/p_i$ and $b_i = -1/p_i$:

Randomized 2SAT – Analysis [2]

Proof (cont.):

Let now y_i be the expected number of steps to reach state k from $X = i$.

$$y_k = 0$$

$$y_0 = 1 + y_1$$

$$y_i = 1 + p_i \cdot y_{i+1} + q_i \cdot y_{i-1} \quad q_i = 1 - p_i \quad \text{for us } p_i = \frac{1}{2}$$

Can solve this recurrence for general p_i by writing for $i \in [1..k)$:

$$p_i y_i + q_i y_i = y_i = 1 + p_i y_{i+1} + q_i y_{i-1}$$

rearrange to $p_i(y_{i+1} - y_i) = q_i(y_i - y_{i-1}) - 1$. Now divide by p_i .

$$\rightsquigarrow \text{Recurrence of differences:} \quad \dot{y}_i = \frac{q_i}{p_i} \dot{y}_{i-1} - \frac{1}{p_i}$$

Write $\dot{y} = y_{i+1} - y_i$ and abbreviate $a_i = q_i/p_i$ and $b_i = -1/p_i$:

$$\dot{y}_i = a_i \dot{y}_{i-1} + b_i \quad (1 \leq i \leq k-1)$$

$$\dot{y}_0 = y_1 - y_0 = -1$$

Randomized 2SAT – Analysis [3]

Proof (cont.):

Recurrences 101: Telescoping recurrence! Can solve this in full generality:

$$\rightsquigarrow \dot{y}_i = \left(\prod_{j=1}^i a_j \right) \cdot \dot{y}_0 + \sum_{j=1}^i \left(\prod_{k=j+1}^i a_k \right) b_j$$



Randomized 2SAT – Analysis [3]

Proof (cont.):

Recurrences 101: Telescoping recurrence! Can solve this in full generality:

$$\rightsquigarrow \dot{y}_i = \left(\prod_{j=1}^i a_j \right) \cdot \dot{y}_0 + \sum_{j=1}^i \left(\prod_{k=j+1}^i a_k \right) b_j$$

Moreover: Telescoping sum $\sum_{j=0}^{i-1} \dot{y}_j = y_i - y_0 \rightsquigarrow y_0 = y_k - \sum_{j=0}^{k-1} \dot{y}_j$

Randomized 2SAT – Analysis [3]

Proof (cont.):

Recurrences 101: Telescoping recurrence! Can solve this in full generality:


$$\rightsquigarrow \dot{y}_i = \left(\prod_{j=1}^i a_j \right) \cdot \dot{y}_0 + \sum_{j=1}^i \left(\prod_{k=j+1}^i a_k \right) b_j$$

Moreover: Telescoping sum $\sum_{j=0}^{i-1} \dot{y}_j = y_i - y_0 \rightsquigarrow y_0 = y_k - \sum_{j=0}^{k-1} \dot{y}_j$

We have $p = q = \frac{1}{2}$, so $a_i = 1$ and $b_i = -2 \rightsquigarrow \dot{y}_i = \dot{y}_0 + -2i = -2i - 1$

$$\rightsquigarrow y_0 = \sum_{j=0}^{k-1} (2j + 1) = k^2$$

(

expected shpr from a to 



Randomized 2SAT – Analysis [3]

Proof (cont.):

Recurrences 101: Telescoping recurrence! Can solve this in full generality:

$$\rightsquigarrow \dot{y}_i = \left(\prod_{j=1}^i a_j \right) \cdot \dot{y}_0 + \sum_{j=1}^i \left(\prod_{k=j+1}^i a_k \right) b_j$$

Moreover: Telescoping sum $\sum_{j=0}^{i-1} \dot{y}_j = y_i - y_0 \rightsquigarrow y_0 = y_k - \sum_{j=0}^{k-1} \dot{y}_j$

We have $p = q = \frac{1}{2}$, so $a_i = 1$ and $b_i = -2 \rightsquigarrow \dot{y}_i = \dot{y}_0 + -2i = -2i - 1$

$$\rightsquigarrow y_0 = \sum_{j=0}^{k-1} (2j + 1) = k^2$$

\rightsquigarrow W reaches α^* after $y_0 = k^2$ expected iterations

\rightsquigarrow Expected #iterations for localSearch2SAT to reach α^* is $\leq k^2$

Randomized 2SAT – Analysis [3]

Proof (cont.):

Recurrences 101: Telescoping recurrence! Can solve this in full generality:

$$\rightsquigarrow \dot{y}_i = \left(\prod_{j=1}^i a_j \right) \cdot \dot{y}_0 + \sum_{j=1}^i \left(\prod_{k=j+1}^i a_k \right) b_j$$

Moreover: Telescoping sum $\sum_{j=0}^{i-1} \dot{y}_j = y_i - y_0 \rightsquigarrow y_0 = y_k - \sum_{j=0}^{k-1} \dot{y}_j$

We have $p = q = \frac{1}{2}$, so $a_i = 1$ and $b_i = -2 \rightsquigarrow \dot{y}_i = \dot{y}_0 + -2i = -2i - 1$

$$\rightsquigarrow y_0 = \sum_{j=0}^{k-1} (2j + 1) = k^2$$

\rightsquigarrow W reaches α^* after $y_0 = k^2$ expected iterations

\rightsquigarrow Expected #iterations for localSearch2SAT to reach α^* is $\leq k^2$

$\mathbb{P}[\text{localSearch2SAT unsuccessful after } 2k^2 \text{ iterations}] \leq \frac{1}{2}$ (Markov)

Randomized 2SAT – Analysis [3]

Proof (cont.):

Recurrences 101: Telescoping recurrence! Can solve this in full generality:

$$\rightsquigarrow \dot{y}_i = \left(\prod_{j=1}^i a_j \right) \cdot \dot{y}_0 + \sum_{j=1}^i \left(\prod_{k=j+1}^i a_k \right) b_j$$

Moreover: Telescoping sum $\sum_{j=0}^{i-1} \dot{y}_j = y_i - y_0 \rightsquigarrow y_0 = y_k - \sum_{j=0}^{k-1} \dot{y}_j$

We have $p = q = \frac{1}{2}$, so $a_i = 1$ and $b_i = -2 \rightsquigarrow \dot{y}_i = \dot{y}_0 + -2i = -2i - 1$

$$\rightsquigarrow y_0 = \sum_{j=0}^{k-1} (2j + 1) = k^2$$

\rightsquigarrow W reaches α^* after $y_0 = k^2$ expected iterations

\rightsquigarrow Expected #iterations for localSearch2SAT to reach α^* is $\leq k^2$

$\mathbb{P}[\text{localSearch2SAT unsuccessful after } 2k^2 \text{ iterations}] \leq \frac{1}{2}$ (Markov)

Treat $\text{confidence} \cdot 2k^2$ iterations as *confidence* repetitions of independent attempts of $2k^2$ each.

Probability that none successful $\leq 2^{-\text{confidence}}$. ■

From 2SAT to 3SAT

- ▶ Let's try the same on 3SAT. What changes?

From 2SAT to 3SAT

- ▶ Let's try the same on 3SAT. What changes?
- ▶ Key argument in 2SAT
 - ▶ fixing one clause had probability $\geq \frac{1}{2}$ to move closer to α^*
 - ▶ for 3SAT, this is only $\geq \frac{1}{3}$ (worst case: 2 out of 3 literals already correct)

From 2SAT to 3SAT

- ▶ Let's try the same on 3SAT. What changes?
- ▶ Key argument in 2SAT
 - ▶ fixing one clause had probability $\geq \frac{1}{2}$ to move closer to α^*
 - ▶ for 3SAT, this is only $\geq \frac{1}{3}$ (worst case: 2 out of 3 literals already correct)

\rightsquigarrow same analysis gives expected iterations to reach y_0

$$y_0 = y_k - \sum_{j=0}^{k-1} \dot{y}_j \quad \text{with} \quad \dot{y}_i = \left(\prod_{j=1}^i a_j \right) \cdot \dot{y}_0 + \sum_{j=1}^i \left(\prod_{k=j+1}^i a_k \right) b_j$$

but with $p = \frac{1}{3}$, $q = \frac{2}{3}$, so $a_i = 2$ and $b_i = -3$

$$\rightsquigarrow \dot{y}_i = 2^i \cdot (-1) + \sum_{j=1}^i 2^{i-j} \cdot (-3)$$

From 2SAT to 3SAT

- ▶ Let's try the same on 3SAT. What changes?
- ▶ Key argument in 2SAT
 - ▶ fixing one clause had probability $\geq \frac{1}{2}$ to move closer to α^*
 - ▶ for 3SAT, this is only $\geq \frac{1}{3}$ (worst case: 2 out of 3 literals already correct)

\rightsquigarrow same analysis gives expected iterations to reach y_0

$$y_0 = y_k - \sum_{j=0}^{k-1} \dot{y}_j \quad \text{with} \quad \dot{y}_i = \left(\prod_{j=1}^i a_j \right) \cdot \dot{y}_0 + \sum_{j=1}^i \left(\prod_{k=j+1}^i a_k \right) b_j$$

but with $p = \frac{1}{3}$, $q = \frac{2}{3}$, so $a_i = 2$ and $b = -3$

$$\rightsquigarrow \dot{y}_i = 2^i \cdot (-1) + \sum_{j=1}^i 2^{i-j} \cdot (-3) = -2^i - 3 \sum_{k=0}^{i-1} 2^k$$

From 2SAT to 3SAT

- ▶ Let's try the same on 3SAT. What changes?
- ▶ Key argument in 2SAT
 - ▶ fixing one clause had probability $\geq \frac{1}{2}$ to move closer to α^*
 - ▶ for 3SAT, this is only $\geq \frac{1}{3}$ (worst case: 2 out of 3 literals already correct)

\rightsquigarrow same analysis gives expected iterations to reach y_0

$$y_0 = y_k - \sum_{j=0}^{k-1} \dot{y}_j \quad \text{with} \quad \dot{y}_i = \left(\prod_{j=1}^i a_j \right) \cdot \dot{y}_0 + \sum_{j=1}^i \left(\prod_{k=j+1}^i a_k \right) b_j$$

but with $p = \frac{1}{3}$, $q = \frac{2}{3}$, so $a_i = 2$ and $b = -3$

$$\rightsquigarrow \dot{y}_i = 2^i \cdot (-1) + \sum_{j=1}^i 2^{i-j} \cdot (-3) = -2^i - 3 \sum_{k=0}^{i-1} 2^k = -2^i - 3(2^i - 1) = -4 \cdot 2^i + 3$$

From 2SAT to 3SAT

- ▶ Let's try the same on 3SAT. What changes?
- ▶ Key argument in 2SAT
 - ▶ fixing one clause had probability $\geq \frac{1}{2}$ to move closer to α^*
 - ▶ for 3SAT, this is only $\geq \frac{1}{3}$ (worst case: 2 out of 3 literals already correct)

\rightsquigarrow same analysis gives expected iterations to reach y_0

$$y_0 = y_k - \sum_{j=0}^{k-1} \dot{y}_j \quad \text{with} \quad \dot{y}_i = \left(\prod_{j=1}^i a_j \right) \cdot \dot{y}_0 + \sum_{j=1}^i \left(\prod_{k=j+1}^i a_k \right) b_j$$

but with $p = \frac{1}{3}$, $q = \frac{2}{3}$, so $a_i = 2$ and $b = -3$

$$\rightsquigarrow \dot{y}_i = 2^i \cdot (-1) + \sum_{j=1}^i 2^{i-j} \cdot (-3) = -2^i - 3 \sum_{k=0}^{i-1} 2^k = -2^i - 3(2^i - 1) = -4 \cdot 2^i + 3$$

$$\rightsquigarrow y_0 = - \sum_{j=0}^{k-1} (-4 \cdot 2^j + 3) \geq 4 \cdot (2^k - 1)$$

From 2SAT to 3SAT

- ▶ Let's try the same on 3SAT. What changes?
- ▶ Key argument in 2SAT
 - ▶ fixing one clause had probability $\geq \frac{1}{2}$ to move closer to α^*
 - ▶ for 3SAT, this is only $\geq \frac{1}{3}$ (worst case: 2 out of 3 literals already correct)

↪ same analysis gives expected iterations to reach y_0

$$y_0 = y_k - \sum_{j=0}^{k-1} \dot{y}_j \quad \text{with} \quad \dot{y}_i = \left(\prod_{j=1}^i a_j \right) \cdot \dot{y}_0 + \sum_{j=1}^i \left(\prod_{k=j+1}^i a_k \right) b_j$$

but with $p = \frac{1}{3}$, $q = \frac{2}{3}$, so $a_i = 2$ and $b = -3$

$$\rightsquigarrow \dot{y}_i = 2^i \cdot (-1) + \sum_{j=1}^i 2^{i-j} \cdot (-3) = -2^i - 3 \sum_{k=0}^{i-1} 2^k = -2^i - 3(2^i - 1) = -4 \cdot 2^i + 3$$

$$\rightsquigarrow y_0 = - \sum_{j=0}^{k-1} (-4 \cdot 2^j + 3) \geq 4 \cdot (2^k - 1)$$

↪ Worse than deterministic brute force!

Local Search with Restarts

- ▶ Problem first attempt: Over time, more likely to move *away* from α^*
 - ▶ Need $\approx 2^k$ expected time to move k steps closer to α^*
 - ▶ Won't cut it for large k

Local Search with Restarts

- ▶ Problem first attempt: Over time, more likely to move *away* from α^*
 - ▶ Need $\approx 2^k$ expected time to move k steps closer to α^*
 - ▶ Won't cut it for large k
 - ▶ But we assume here that we start with $\neg\alpha^*$
whereas actual random α might be (much) closer!
- ↪ Keep local search for small improvements,
but restart overall method many times, to hopefully start close to α^* some time

Schöning's Randomized 3SAT Algorithm

```
1 procedure Schöning3SAT( $\varphi$ , assignment):  
2    $k$  = number of variables in  $\varphi$   
3   for  $i = 1, \dots, 24 \left\lceil \sqrt{k} \left(\frac{4}{3}\right)^k \right\rceil$  do  
4     Choose assignment  $\alpha \in \{0, 1\}^k$  uniformly at random.  
5     for  $j = 1, \dots, 3k$  do  
6       if  $\alpha$  fulfills  $\varphi$  return  $\alpha$   
7       Arbitrarily choose clause  $C = \ell_1 \vee \ell_2 \vee \ell_3$  not satisfied under  $\alpha$ .  
8       Choose  $\ell$  from  $\{\ell_1, \ell_2, \ell_3\}$  uniformly at random.  
9        $\alpha :=$  assignment obtained by negating  $\ell$ .  
10  return PROBABLY_NOT_SATISFIABLE
```

Schöning's Randomized 3SAT Algorithm

```
1 procedure Schöning3SAT( $\varphi$ , confidence):  
2    $k$  = number of variables in  $\varphi$   
3   for  $i = 1, \dots, 24 \left\lceil \sqrt{k} \left(\frac{4}{3}\right)^k \right\rceil$  do  
4     Choose assignment  $\alpha \in \{0, 1\}^k$  uniformly at random.  
5     for  $j = 1, \dots, 3k$  do  
6       if  $\alpha$  fulfills  $\varphi$  return  $\alpha$   
7       Arbitrarily choose clause  $C = \ell_1 \vee \ell_2 \vee \ell_3$  not satisfied under  $\alpha$ .  
8       Choose  $\ell$  from  $\{\ell_1, \ell_2, \ell_3\}$  uniformly at random.  
9        $\alpha :=$  assignment obtained by negating  $\ell$ .  
10  return PROBABLY_NOT_SATISFIABLE
```

local
search

Theorem 9.11 (Schöning3SAT is OSE-MC for 3SAT)

Let φ be a 3SAT formula with n clauses over k variables.

1. Schöning3SAT is a OSE-MC for 3SAT.

2. To be correct with probability $\geq 1 - \frac{1}{2}$, it runs in time $O(\frac{1}{2} \cdot \left(\frac{4}{3}\right)^k k^{3/2} n)$

Schöning3SAT is OSE-MC for 3SAT

Proof: $1 - 2^{-\text{confidence prob.}}$

2. follows immediately from standard OSE-MC probability amplification.

Also obvious: φ unsatisfiable \rightsquigarrow Schöning3SAT returns PROBABLY_NOT_SATISFIABLE.

Schöning3SAT is OSE-MC for 3SAT

Proof:

2. follows immediately from standard OSE-MC probability amplification.

Also obvious: φ unsatisfiable \rightsquigarrow Schöning3SAT returns PROBABLY_NOT_SATISFIABLE.

It remains to show: $\exists \alpha^*$ that satisfies $\varphi \rightsquigarrow \mathbb{P}[\text{Schöning3SAT returns } \alpha^*] \geq \frac{1}{2}$

Schöning3SAT is OSE-MC for 3SAT

Proof:

2. follows immediately from standard OSE-MC probability amplification.

Also obvious: φ unsatisfiable \rightsquigarrow Schöning3SAT returns PROBABLY_NOT_SATISFIABLE.

It remains to show: $\exists \alpha^*$ that satisfies $\varphi \rightsquigarrow \mathbb{P}[\text{Schöning3SAT returns } \alpha^*] \geq \frac{1}{2}$

Claim: $q := \mathbb{P}[\overset{\text{one run of outer loop}}{\text{local search finds } \alpha^*}] \geq \frac{1}{12\sqrt{k}} \left(\frac{3}{4}\right)^k$

Proof:

$X = k - d_G(\alpha^*, \alpha)$ #variables correctly assigned in random α

Schöning3SAT is OSE-MC for 3SAT

Proof:

2. follows immediately from standard OSE-MC probability amplification.

Also obvious: φ unsatisfiable \rightsquigarrow Schöning3SAT returns PROBABLY_NOT_SATISFIABLE.

It remains to show: $\exists \alpha^*$ that satisfies $\varphi \rightsquigarrow \mathbb{P}[\text{Schöning3SAT returns } \alpha^*] \geq \frac{1}{2}$

Claim: $q := \mathbb{P}[\overset{\text{one run of outer loop}}{\text{local search finds } \alpha^*}] \geq \frac{1}{12\sqrt{k}} \left(\frac{3}{4}\right)^k$

Proof:

$X = k - d_G(\alpha^*, \alpha)$ #variables correctly assigned in random $\alpha \rightsquigarrow X_0 \stackrel{\mathcal{D}}{=} \text{Bin}(k, \frac{1}{2})$

Schöning3SAT is OSE-MC for 3SAT

Proof:

2. follows immediately from standard OSE-MC probability amplification.

Also obvious: φ unsatisfiable \rightsquigarrow Schöning3SAT returns PROBABLY_NOT_SATISFIABLE.

It remains to show: $\exists \alpha^*$ that satisfies $\varphi \rightsquigarrow \mathbb{P}[\text{Schöning3SAT returns } \alpha^*] \geq \frac{1}{2}$


Claim: $q := \mathbb{P}[\text{local search finds } \alpha^*] \geq \frac{1}{12\sqrt{k}} \left(\frac{3}{4}\right)^k$

one run of outer loop

Proof:

$X = k - d_G(\alpha^*, \alpha)$ #variables correctly assigned in random $\alpha \rightsquigarrow X \stackrel{\mathcal{D}}{=} \text{Bin}(k, \frac{1}{2})$

Conditional on X , need local search to climb $u = k - X$ steps up to succeed.



Schöning3SAT is OSE-MC for 3SAT

Proof:

2. follows immediately from standard OSE-MC probability amplification.

Also obvious: φ unsatisfiable \rightsquigarrow Schöning3SAT returns PROBABLY_NOT_SATISFIABLE.

It remains to show: $\exists \alpha^*$ that satisfies $\varphi \rightsquigarrow \mathbb{P}[\text{Schöning3SAT returns } \alpha^*] \geq \frac{1}{2}$

Claim: $q := \mathbb{P}[\overset{\text{one run of outer loop}}{\text{local search finds } \alpha^*}] \geq \frac{1}{12\sqrt{k}} \left(\frac{3}{4}\right)^k$

Proof:

$X = k - d_G(\alpha^*, \alpha)$ #variables correctly assigned in random $\alpha \rightsquigarrow X_0 \stackrel{\mathcal{D}}{=} \text{Bin}(k, \frac{1}{2})$

Conditional on X , need local search to climb $u = k - X$ steps up to succeed.

We keep trying for $3k$ steps, but will only consider first $3u$ of them.

If at least $2u$ of these are up-steps, we succeed no matter which ones are up steps.

Schöning3SAT is OSE-MC for 3SAT

Proof:


2. follows immediately from standard OSE-MC probability amplification.

Also obvious: φ unsatisfiable \rightsquigarrow Schöning3SAT returns PROBABLY_NOT_SATISFIABLE.

It remains to show: $\exists \alpha^*$ that satisfies $\varphi \rightsquigarrow \mathbb{P}[\text{Schöning3SAT returns } \alpha^*] \geq \frac{1}{2}$

Claim: $q := \mathbb{P}[\text{local search finds } \alpha^*] \geq \frac{1}{12\sqrt{k}} \left(\frac{3}{4}\right)^k$

one run of outer loop



Proof:

$X = k - d_G(\alpha^*, \alpha)$ #variables correctly assigned in random $\alpha \rightsquigarrow X_0 \stackrel{\mathcal{D}}{=} \text{Bin}(k, \frac{1}{2})$

Conditional on X , need local search to climb $u = k - X$ steps up to succeed.

We keep trying for $3k$ steps, but will only consider first $3u$ of them.

If at least $2u$ of these are up-steps, we succeed no matter which ones are up steps.

Pessimistically, assume up-step with prob $= \frac{1}{3}$.

$$q_u = \mathbb{P}[\geq 2u \text{ up in } 3u \text{ steps}] \geq \mathbb{P}[= 2u \text{ up in } 3u \text{ steps}] = \binom{3u}{u} \left(\frac{1}{3}\right)^{2u} \left(\frac{2}{3}\right)^u$$

Schöning3SAT is OSE-MC for 3SAT

Proof:

2. follows immediately from standard OSE-MC probability amplification.

Also obvious: φ unsatisfiable \rightsquigarrow Schöning3SAT returns PROBABLY_NOT_SATISFIABLE.

It remains to show: $\exists \alpha^*$ that satisfies $\varphi \rightsquigarrow \mathbb{P}[\text{Schöning3SAT returns } \alpha^*] \geq \frac{1}{2}$

Claim: $q := \mathbb{P}[\text{local search finds } \alpha^*] \geq \frac{1}{12\sqrt{k}} \left(\frac{3}{4}\right)^k$

one run of outer loop

Proof:

$X = k - d_G(\alpha^*, \alpha)$ #variables correctly assigned in random $\alpha \rightsquigarrow X_0 \stackrel{\mathcal{D}}{=} \text{Bin}(k, \frac{1}{2})$

Conditional on X , need local search to climb $u = k - X$ steps up to succeed.

We keep trying for $3k$ steps, but will only consider first $3u$ of them.

If at least $2u$ of these are up-steps, we succeed no matter which ones are up steps.

Pessimistically, assume up-step with prob $= \frac{1}{3}$.

$$q_u = \mathbb{P}[\geq 2u \text{ up in } 3u \text{ steps}] \geq \mathbb{P}[= 2u \text{ up in } 3u \text{ steps}] = \binom{3u}{u} \left(\frac{1}{3}\right)^{2u} \left(\frac{2}{3}\right)^u$$

Stirling-Robbins Inequality: $n! = e^{r_n} \cdot \sqrt{2\pi n} \left(\frac{n}{e}\right)^n$ with $\frac{1}{12n+1} < r_n < \frac{1}{12n} \rightsquigarrow \underline{1 \leq e^{r_n} \leq 2}$

/

$\in \{1, 2\}$

Schöning3SAT is OSE-MC for 3SAT

Proof:

2. follows immediately from standard OSE-MC probability amplification.

Also obvious: φ unsatisfiable \rightsquigarrow Schöning3SAT returns PROBABLY_NOT_SATISFIABLE.

It remains to show: $\exists \alpha^*$ that satisfies $\varphi \rightsquigarrow \mathbb{P}[\text{Schöning3SAT returns } \alpha^*] \geq \frac{1}{2}$

Claim: $q := \mathbb{P}[\overset{\text{one run of outer loop}}{\text{local search finds } \alpha^*}] \geq \frac{1}{12\sqrt{k}} \left(\frac{3}{4}\right)^k$

Proof:

$X = k - d_G(\alpha^*, \alpha)$ #variables correctly assigned in random $\alpha \rightsquigarrow X_0 \stackrel{\mathcal{D}}{=} \text{Bin}(k, \frac{1}{2})$

Conditional on X , need local search to climb $u = k - X$ steps up to succeed.

We keep trying for $3k$ steps, but will only consider first $3u$ of them.

If at least $2u$ of these are up-steps, we succeed no matter which ones are up steps.

Pessimistically, assume up-step with prob $= \frac{1}{3}$.

$$q_u = \mathbb{P}[\geq 2u \text{ up in } 3u \text{ steps}] \geq \mathbb{P}[= 2u \text{ up in } 3u \text{ steps}] = \binom{3u}{u} \left(\frac{1}{3}\right)^{2u} \left(\frac{2}{3}\right)^u$$

Stirling-Robbins Inequality: $n! = e_n^r \cdot \sqrt{2\pi n} \left(\frac{n}{e}\right)^n$ with $\frac{1}{12n+1} < r_n < \frac{1}{12n} \rightsquigarrow 1 \leq e^{r_n} \leq 2$

$$\rightsquigarrow \binom{3u}{u} = \frac{(3u)!}{u!(2u)!} \geq \frac{c}{\sqrt{u}} \cdot \frac{3^{3u}}{2^{2u}} \quad \text{with} \quad c = \frac{\sqrt{3}}{8\sqrt{2\pi}} \approx 0.086 > \frac{1}{12}$$

Schöning3SAT is OSE-MC for 3SAT

Proof:

2. follows immediately from standard OSE-MC probability amplification.

Also obvious: φ unsatisfiable \rightsquigarrow Schöning3SAT returns PROBABLY_NOT_SATISFIABLE.

It remains to show: $\exists \alpha^*$ that satisfies $\varphi \rightsquigarrow \mathbb{P}[\text{Schöning3SAT returns } \alpha^*] \geq \frac{1}{2}$

Claim: $q := \mathbb{P}[\overset{\text{one run of outer loop}}{\text{local search finds } \alpha^*}] \geq \frac{1}{12\sqrt{k}} \left(\frac{3}{4}\right)^k$

Proof:

$X = k - d_G(\alpha^*, \alpha)$ #variables correctly assigned in random $\alpha \rightsquigarrow X_0 \stackrel{\mathcal{D}}{=} \text{Bin}(k, \frac{1}{2})$

Conditional on X , need local search to climb $u = k - X$ steps up to succeed.

We keep trying for $3k$ steps, but will only consider first $3u$ of them.

If at least $2u$ of these are up-steps, we succeed no matter which ones are up steps.

Pessimistically, assume up-step with prob $= \frac{1}{3}$.

$$q_u = \mathbb{P}[\geq 2u \text{ up in } 3u \text{ steps}] \geq \mathbb{P}[= 2u \text{ up in } 3u \text{ steps}] = \binom{3u}{u} \left(\frac{1}{3}\right)^{2u} \left(\frac{2}{3}\right)^u \geq \frac{c}{\sqrt{u}} 2^{-u}$$

Stirling-Robbins Inequality : $n! = e_n^r \cdot \sqrt{2\pi n} \left(\frac{n}{e}\right)^n$ with $\frac{1}{12n+1} < r_n < \frac{1}{12n} \rightsquigarrow 1 \leq e^{r_n} \leq 2$

$$\rightsquigarrow \binom{3u}{u} = \frac{(3u)!}{u!(2u)!} \geq \frac{c}{\sqrt{u}} \cdot \frac{3^{3u}}{2^{2u}} \quad \text{with} \quad c = \frac{\sqrt{3}}{8\sqrt{2\pi}} \approx 0.086 > \frac{1}{12}$$

Schöning3SAT is OSE-MC for 3SAT [2]

Proof (Theorem 9.11 cont.):

Proof (Claim cont.):

$$q = \sum_{x=0}^k \mathbb{P}[X = x] \cdot q_{k-x}$$



Schöning3SAT is OSE-MC for 3SAT [2]

Proof (Theorem 9.11 cont.):

Proof (Claim cont.):

$$q = \sum_{x=0}^k \mathbb{P}[X = x] \cdot q_{k-x} = \sum_{u=0}^k \mathbb{P}[X = k - u] \cdot q_u$$



Schöning3SAT is OSE-MC for 3SAT [2]

Proof (Theorem 9.11 cont.):

Proof (Claim cont.):

$$q = \sum_{x=0}^k \mathbb{P}[X = x] \cdot q_{k-x} = \sum_{u=0}^k \mathbb{P}[X = k - u] \cdot q_u \geq \frac{1}{2^k} + \sum_{u=1}^k \binom{k}{k-u} \left(\frac{1}{2}\right)^k \cdot q_u$$



Schöning3SAT is OSE-MC for 3SAT [2]

Proof (Theorem 9.11 cont.):

Proof (Claim cont.):

$$\begin{aligned} q &= \sum_{x=0}^k \mathbb{P}[X = x] \cdot q_{k-x} = \sum_{u=0}^k \mathbb{P}[X = k - u] \cdot q_u \geq \frac{1}{2^k} + \sum_{u=1}^k \binom{k}{k-u} \left(\frac{1}{2}\right)^k \cdot q_u \\ &\geq \frac{1}{2^k} + \sum_{u=1}^k \binom{k}{u} \left(\frac{1}{2}\right)^k \underbrace{\frac{c}{\sqrt{u}}}_{\geq \frac{1}{2}} 2^{-u} \end{aligned}$$



Schöning3SAT is OSE-MC for 3SAT [2]

Proof (Theorem 9.11 cont.):

Proof (Claim cont.):

$$\begin{aligned} q &= \sum_{x=0}^k \mathbb{P}[X = x] \cdot q_{k-x} = \sum_{u=0}^k \mathbb{P}[X = k-u] \cdot q_u \geq \frac{1}{2^k} + \sum_{u=1}^k \binom{k}{k-u} \left(\frac{1}{2}\right)^k \cdot q_u \\ &\geq \frac{1}{2^k} + \sum_{u=1}^k \binom{k}{u} \left(\frac{1}{2}\right)^k \underbrace{\frac{c}{\sqrt{u}}}_{\geq \frac{c}{\sqrt{k}}} 2^{-u} \geq \frac{1}{2^k} + \frac{c}{\sqrt{k}} \left(\frac{1}{2}\right)^k \left[\underbrace{\sum_{u=0}^k \binom{k}{u} \left(\frac{1}{2}\right)^u}_{A} \mathbf{1}^{k-u} - \binom{k}{0} \cdot 1 \right] \end{aligned}$$



Schöning3SAT is OSE-MC for 3SAT [2]

Proof (Theorem 9.11 cont.):

Proof (Claim cont.):

$$\begin{aligned} q &= \sum_{x=0}^k \mathbb{P}[X = x] \cdot q_{k-x} = \sum_{u=0}^k \mathbb{P}[X = k - u] \cdot q_u \geq \frac{1}{2^k} + \sum_{u=1}^k \binom{k}{k-u} \left(\frac{1}{2}\right)^k \cdot q_u \\ &\geq \frac{1}{2^k} + \sum_{u=1}^k \binom{k}{u} \left(\frac{1}{2}\right)^k \frac{c}{\sqrt{u}} 2^{-u} \geq \frac{1}{2^k} + \frac{c}{\sqrt{k}} \left(\frac{1}{2}\right)^k \underbrace{\left[\sum_{u=0}^k \binom{k}{u} \left(\frac{1}{2}\right)^u \mathbf{1}^{k-u} - \binom{k}{0} \cdot 1 \right]}_A \end{aligned}$$

A is an instance of binomial theorem $\sum_{k=0}^n \binom{n}{k} a^k b^{n-k} = (a + b)^n$

Schöning3SAT is OSE-MC for 3SAT [2]

Proof (Theorem 9.11 cont.):

Proof (Claim cont.):

$$\begin{aligned} q &= \sum_{x=0}^k \mathbb{P}[X = x] \cdot q_{k-x} = \sum_{u=0}^k \mathbb{P}[X = k - u] \cdot q_u \geq \frac{1}{2^k} + \sum_{u=1}^k \binom{k}{k-u} \left(\frac{1}{2}\right)^k \cdot q_u \\ &\geq \frac{1}{2^k} + \sum_{u=1}^k \binom{k}{u} \left(\frac{1}{2}\right)^k \frac{c}{\sqrt{u}} 2^{-u} \geq \frac{1}{2^k} + \frac{c}{\sqrt{k}} \left(\frac{1}{2}\right)^k \underbrace{\left[\sum_{u=\mathbf{0}}^k \binom{k}{u} \left(\frac{1}{2}\right)^u \mathbf{1}^{k-u} - \binom{k}{0} \cdot 1 \right]}_A \end{aligned}$$

A is an instance of binomial theorem $\sum_{k=0}^n \binom{n}{k} a^k b^{n-k} = (a + b)^n$

$$q \geq \frac{1}{2^k} + \frac{c}{\sqrt{k}} \left(\frac{1}{2}\right)^k \left[\left(\frac{1}{2} + 1\right)^k - 1 \right]$$



Schöning3SAT is OSE-MC for 3SAT [2]

Proof (Theorem 9.11 cont.):

Proof (Claim cont.):

$$\begin{aligned} q &= \sum_{x=0}^k \mathbb{P}[X = x] \cdot q_{k-x} = \sum_{u=0}^k \mathbb{P}[X = k-u] \cdot q_u \geq \frac{1}{2^k} + \sum_{u=1}^k \binom{k}{k-u} \left(\frac{1}{2}\right)^k \cdot q_u \\ &\geq \frac{1}{2^k} + \sum_{u=1}^k \binom{k}{u} \left(\frac{1}{2}\right)^k \frac{c}{\sqrt{u}} 2^{-u} \geq \frac{1}{2^k} + \frac{c}{\sqrt{k}} \left(\frac{1}{2}\right)^k \underbrace{\left[\sum_{u=\mathbf{0}}^k \binom{k}{u} \left(\frac{1}{2}\right)^u \mathbf{1}^{k-u} - \binom{k}{0} \cdot 1 \right]}_A \end{aligned}$$

A is an instance of binomial theorem $\sum_{k=0}^n \binom{n}{k} a^k b^{n-k} = (a+b)^n$

$$q \geq \frac{1}{2^k} + \frac{c}{\sqrt{k}} \left(\frac{1}{2}\right)^k \left[\left(\frac{1}{2} + 1\right)^k - 1 \right] \geq \frac{c}{\sqrt{k}} \left(\frac{3}{4}\right)^k \geq \frac{1}{12\sqrt{k}} \left(\frac{3}{4}\right)^k$$



Schöning3SAT is OSE-MC for 3SAT [2]

Proof (Theorem 9.11 cont.):

Proof (Claim cont.):

$$\begin{aligned}
 q &= \sum_{x=0}^k \mathbb{P}[X = x] \cdot q_{k-x} = \sum_{u=0}^k \mathbb{P}[X = k-u] \cdot q_u \geq \frac{1}{2^k} + \sum_{u=1}^k \binom{k}{k-u} \left(\frac{1}{2}\right)^k \cdot q_u \\
 &\geq \frac{1}{2^k} + \sum_{u=1}^k \binom{k}{u} \left(\frac{1}{2}\right)^k \frac{c}{\sqrt{u}} 2^{-u} \geq \frac{1}{2^k} + \frac{c}{\sqrt{k}} \left(\frac{1}{2}\right)^k \underbrace{\left[\sum_{u=0}^k \binom{k}{u} \left(\frac{1}{2}\right)^u \mathbf{1}^{k-u} - \binom{k}{0} \cdot 1 \right]}_A
 \end{aligned}$$

A is an instance of binomial theorem $\sum_{k=0}^n \binom{n}{k} a^k b^{n-k} = (a+b)^n$

$$q \geq \frac{1}{2^k} + \frac{c}{\sqrt{k}} \left(\frac{1}{2}\right)^k \left[\left(\frac{1}{2} + 1\right)^k - 1 \right] \geq \frac{c}{\sqrt{k}} \left(\frac{3}{4}\right)^k \geq \frac{1}{12\sqrt{k}} \left(\frac{3}{4}\right)^k$$

Expected number of independent repetitions before success: $\frac{1}{q}$.

Schöning3SAT is OSE-MC for 3SAT [2]

Proof (Theorem 9.11 cont.):

Proof (Claim cont.):

$$\begin{aligned}
 q &= \sum_{x=0}^k \mathbb{P}[X = x] \cdot q_{k-x} = \sum_{u=0}^k \mathbb{P}[X = k - u] \cdot q_u \geq \frac{1}{2^k} + \sum_{u=1}^k \binom{k}{k-u} \left(\frac{1}{2}\right)^k \cdot q_u \\
 &\geq \frac{1}{2^k} + \sum_{u=1}^k \binom{k}{u} \left(\frac{1}{2}\right)^k \frac{c}{\sqrt{u}} 2^{-u} \geq \frac{1}{2^k} + \frac{c}{\sqrt{k}} \left(\frac{1}{2}\right)^k \underbrace{\left[\sum_{u=0}^k \binom{k}{u} \left(\frac{1}{2}\right)^u \mathbf{1}^{k-u} - \binom{k}{0} \cdot 1 \right]}_A
 \end{aligned}$$

A is an instance of binomial theorem $\sum_{k=0}^n \binom{n}{k} a^k b^{n-k} = (a + b)^n$

$$q \geq \frac{1}{2^k} + \frac{c}{\sqrt{k}} \left(\frac{1}{2}\right)^k \left[\left(\frac{1}{2} + 1\right)^k - 1 \right] \geq \frac{c}{\sqrt{k}} \left(\frac{3}{4}\right)^k \geq \frac{1}{12\sqrt{k}} \left(\frac{3}{4}\right)^k$$

Expected number of independent repetitions before success: $\frac{1}{q}$.

Schöning3SAT runs $2 \cdot \frac{1}{q} = 24\sqrt{k} \left(\frac{4}{3}\right)^k$ repetitions. \rightsquigarrow Success prob $\geq \frac{1}{2}$.

9.6 Karger's Cuts

THIS SECTION WILL BE SKIPPED AND IS NOT PART OF THE EXAM MATERIAL.

Smart probability amplification: Karger's Min-Cut

Definition 9.12 (Min-Cut)

Given: A (multi)graph $G = (V, E, c)$, where $c : E \rightarrow \mathbb{N}$ is the multiplicity of an edge

Feasible Solutions: cuts of G , i. e., $M(G) = \{(V_1, V_2) : V_1 \cup V_2 = V \wedge V_1 \cap V_2 = \emptyset\}$,

Goal: Minimize

Costs: $\sum_{e \in C(V_1, V_2)} c(e)$, where $C(V_1, V_2) = \{\{u, v\} \in E : u \in V_1 \wedge v \in V_2\}$.



Random Contraction

```
1 procedure contractionMinCut( $G = (V, E, c)$ )
2   Set  $label(v) := \{v\}$  for every vertex  $v \in V$ .
3   while  $G$  has more than 2 vertices
4     Choose random edge  $e = \{x, y\} \in E$ .
5      $G := \text{Contract}(G, e)$ .
6     Set  $label(z) := label(x) \cup label(y)$  for  $z$  the vertex resulting from  $x$  and  $y$ .
7   Let  $G = (\{u, v\}, E', c')$ ; return  $(label(u), label(v))$  with cost  $c'(\{u, v\})$ .
```

Theorem 9.13 (contractionMinCut correct with some probability)

contractionMinCut is a polytime randomized algorithm that finds a minimal cut for a given multigraph G with n vertices with probability $\geq 2/(n(n-1))$. ◀

Lemma 9.14 (Threshold for contractionMinCut)

Let $l : \mathbb{N} \rightarrow \mathbb{N}$ a monotonic, increasing function with $1 \leq l(n) \leq n$. If we stop contractionMinCut whenever G only has $l(n)$ vertices and determine for the resulting graph G/F deterministically a minimal cut, then we need time in

$$O(n^2 + l(n)^3)$$

and we find a minimal cut for G with probability at least

$$\frac{\binom{l(n)}{2}}{\binom{n}{2}}$$



Karger's Min-Cut Improved

```
1 procedure KargerSteinMinCut( $G(V, E, c)$ )
2    $n = |V|$ 
3   if  $n \geq 6$ 
4     compute minimal cut deterministically
5   else
6      $h = \lceil 1 + \frac{n}{\sqrt{2}} \rceil$ 
7      $G/F_1 = \text{Contract random edges in } G \text{ until } h \text{ nodes left}$ 
8      $(C_1, cost_1) = \text{KargerSteinMinCut}(G/F_1)$ 
9      $G/F_2 = \text{Contract random edges in } G \text{ until } h \text{ nodes left}$ 
10     $(C_2, cost_2) = \text{KargerSteinMinCut}(G/F_2)$ 
11    if  $cost_1 < cost_2$  return  $(C_1, cost_1)$  else  $C_2, cost_2$ 
```

Theorem 9.15 (KargerSteinMinCut beats deterministic min-cut)

KargerSteinMinCut runs in time $O(n^2 \cdot \log(n))$ and finds a minimal cut with probability $\Omega(\frac{1}{\log(n)})$. 