

ALGORITHMS OF BIOINFORMATICS

5

String Matching

4 December 2025

Prof. Dr. Sebastian Wild

5 String Matching

- 5.1 Read Mapping
- 5.2 String Matching with Finite Automata
- 5.3 Constructing String Matching Automata
- 5.4 The Knuth-Morris-Pratt algorithm
- 5.5 The Aho-Corasick Algorithm

5.1 Read Mapping

Shotgun Sequencing

Recall:

- *Shotgun sequencing* approach to determine a (human) genome:



Compeau & Pevzner, *Bioinformatics Algorithms*, Fig 3.1
<https://cogniterra.org/lesson/29884/step/2?unit=21982>

- For a single human genome need 300M reads of 200bp (30x coverage)
 - 60 GB of raw data
 - genome assembly from those is expensive and error prone

Shotgun Sequencing

Recall:

- ▶ *Shotgun sequencing* approach to determine a (human) genome:



Compeau & Pevzner, *Bioinformatics Algorithms*, Fig 3.1
<https://cogniterra.org/lesson/29884/step/2?unit=21982>

- ▶ For a single human genome need 300M reads of 200bp (30x coverage)
 - ~ 60 GB of raw data
 - ~ genome assembly from those is expensive and error prone

We now have carefully assembled *reference genomes* to compare with!

Shotgun Sequencing in Medicine

Predominant medical use of whole genome sequencing:
detecting known markers (mutations / gene combinations) for diseases

Shotgun Sequencing in Medicine

Predominant medical use of whole genome sequencing:
detecting known markers (mutations / gene combinations) for diseases

Example: (more details in Compeau & Pevzner 2015)

- ▶ *Ohdo syndrome* (form of mental retardation, “mask-like” face)
- ▶ known to be indicated by single protein-truncating mutation

Often even a **single base replacement** w.r.t. a human reference genome,
a *SNP (single nucleotide polymorphism)*

Shotgun Sequencing in Medicine


Predominant medical use of whole genome sequencing:
detecting known markers (mutations / gene combinations) for diseases

Example: (more details in Compeau & Pevzner 2015)

- ▶ *Ohdo syndrome* (form of mental retardation, “mask-like” face)
- ▶ known to be indicated by single protein-truncating mutation

Often even a **single base replacement** w.r.t. a human reference genome,
a **SNP** (*single nucleotide polymorphism*)

~> *To find SNPs, we don't need a new patient's genome fully assembled!*



Read Mapping

- ▶ We thus work towards solving the *read mapping problem*
 - ▶ **Given:** genome/text $T[0..n)$, reads/patterns $P[0..p)$, $P[r] = P_r[0..m_r)$
 - ▶ **Goal:** locations i_r of “best match” for P_r in T for $r \in [0..p)$.
- ▶ “best match” can be interpreted in several ways, leading to different problems:
 - (a) best **semilocal alignment** of P_r to T (gold standard, usually too expensive)
 - (b) match with **fewest mismatches**
 - (c) match with $\leq d$ **mismatches** or **NO_MATCH** if no such exists
for SNPs can even set $d = 1$
 - (d) **exact match** or **NO_MATCH** if no such exists

Read Mapping

- ▶ We thus work towards solving the *read mapping problem*
 - ▶ **Given:** genome/text $T[0..n)$, reads/patterns $P[0..p)$, $P[r] = P_r[0..m_r)$
 - ▶ **Goal:** locations i_r of “best match” for P_r in T for $r \in [0..p)$.
- ▶ “best match” can be interpreted in several ways, leading to different problems:
 - (a) best **semilocal alignment** of P_r to T (gold standard, usually too expensive)
 - (b) match with **fewest mismatches**
 - (c) match with $\leq d$ **mismatches** or **NO_MATCH** if no such exists
for SNPs can even set $d = 1$
 - (d) **exact match** or **NO_MATCH** if no such exists

We will first focus on exact matches.

- ▶ simplifies the problem (to get started)
- ▶ the SNPs variants can be reduced to it (using postprocessing)

Part I

Exact matches

Notation

$$\Sigma = \{0..5\}$$

► *alphabet* Σ : finite set of allowed **characters**; $\sigma = |\Sigma|$ “a string over alphabet Σ ”


► focus on nucleotides $\{A, C, G, T\}$ and amino acids

► but try to keep methods generic

► letters (Latin, Greek, Arabic, Cyrillic, Asian scripts, ...) Unicode characters

↖ comprehensive standard character set
including emoji and all known symbols

Notation

- ▶ *alphabet* Σ : finite set of allowed **characters**; $\sigma = |\Sigma|$ “a string over alphabet Σ ”
 - ▶ focus on nucleotides $\{A, C, G, T\}$ and amino acids
 - ▶ but try to keep methods generic
 - ▶ letters (Latin, Greek, Arabic, Cyrillic, Asian scripts, ...) **Unicode characters**
 comprehensive standard character set including emoji and all known symbols
- ▶ $\Sigma^n = \Sigma \times \cdots \times \Sigma$: strings of **length** $n \in \mathbb{N}_0$ (n -tuples)
 - ▶ $\Sigma^* = \bigcup_{n \geq 0} \Sigma^n$: set of **all** (finite) strings over Σ , $\Sigma^+ = \bigcup_{n \geq 1} \Sigma^n$
 - ▶ $\varepsilon \in \Sigma^0$: the *empty* string (same for all alphabets)

Notation

- ▶ *alphabet* Σ : finite set of allowed **characters**; $\sigma = |\Sigma|$ “a string over alphabet Σ ”
 - ▶ focus on nucleotides $\{A, C, G, T\}$ and amino acids
 - ▶ but try to keep methods generic
 - ▶ letters (Latin, Greek, Arabic, Cyrillic, Asian scripts, ...) **Unicode characters**
 - comprehensive standard character set including emoji and all known symbols
- ▶ $\Sigma^n = \Sigma \times \cdots \times \Sigma$: strings of **length** $n \in \mathbb{N}_0$ (n -tuples)
 - ▶ $\Sigma^\star = \bigcup_{n \geq 0} \Sigma^n$: set of **all** (finite) strings over Σ , $\Sigma^+ = \bigcup_{n \geq 1} \Sigma^n$
 - ▶ $\varepsilon \in \Sigma^0$: the *empty* string (same for all alphabets)
- ▶ for $S \in \Sigma^n$, write $S = S[0..n)$, so $S[i]$ (other sources: S_i) for ***i*th** character ($0 \leq i < n$)
 - zero-based (like arrays)!
- ▶ for $S, T \in \Sigma^\star$, write $ST = S \cdot T$ for **concatenation** of S and T
- ▶ for $S \in \Sigma^n$, write $S[i..j)$ for the **substring** $S[i] \cdot S[i+1] \cdots S[j-1]$ ($0 \leq i \leq j \leq n$)
 - ▶ $S[i..i) = \varepsilon$
 - ▶ $S[0..j)$ is a **prefix** of S ; $S[i..n)$ is a **suffix** of S

String matching – Definition

Search for a string (pattern) in a large body of text

► Input:

- $T \in \Sigma^n$: The text being searched within
- $P \in \Sigma^m$: The pattern being searched for; typically $n \gg m$

► Output:

- the *first occurrence (match)* of P in T : $\min\{i \in [0..n - m) : T[i..i + m) = P\}$
- or NO_MATCH if there is no such i (“ P does not occur in T ”)
- sometimes also: find **all** occurrences of P in T .

String matching – Definition

Search for a string (pattern) in a large body of text

► Input:

- $T \in \Sigma^n$: The text being searched within
- $P \in \Sigma^m$: The pattern being searched for; typically $n \gg m$

► Output:

- the *first occurrence (match)* of P in T : $\min\{i \in [0..n - m) : T[i..i + m) = P\}$
- or NO_MATCH if there is no such i (“ P does not occur in T ”)
- sometimes also: find **all** occurrences of P in T .

- trivially solvable with $(n - m + 1) \cdot \overset{\text{try all starting positions}}{m} \sim nm$ character comparisons

↪ too slow for read mapping!

- string matching available, e. g., Java in `String.indexOf`, Python in `str.find`
 - not always robust enough for bioinformatics data (small alphabet, long repetitions)

5.2 String Matching with Finite Automata

Theoretical Computer Science to the rescue!

► string matching = deciding whether $T \in \Sigma^* \cdot P \cdot \Sigma^*$

► $\Sigma^* \cdot P \cdot \Sigma^*$ is *regular* formal language

$\rightsquigarrow \exists$ *deterministic finite automaton* (DFA) to recognize $\Sigma^* \cdot P \cdot \Sigma^*$

\rightsquigarrow can check for occurrence of P in $|T| = n$ steps!

Theoretical Computer Science to the rescue!

► string matching = deciding whether $T \in \Sigma^* \cdot P \cdot \Sigma^*$

► $\Sigma^* \cdot P \cdot \Sigma^*$ is *regular* formal language

$\rightsquigarrow \exists$ *deterministic finite automaton* (DFA) to recognize $\Sigma^* \cdot P \cdot \Sigma^*$

\rightsquigarrow can check for occurrence of P in $|T| = n$ steps!



Job done!

Theoretical Computer Science to the rescue!

► string matching = deciding whether $T \in \Sigma^* \cdot P \cdot \Sigma^*$

► $\Sigma^* \cdot P \cdot \Sigma^*$ is *regular* formal language

$\rightsquigarrow \exists$ *deterministic finite automaton* (DFA) to recognize $\Sigma^* \cdot P \cdot \Sigma^*$

\rightsquigarrow can check for occurrence of P in $|T| = n$ steps!



Job done!



WTF!?

Theoretical Computer Science to the rescue!

► string matching = deciding whether $T \in \Sigma^* \cdot P \cdot \Sigma^*$

► $\Sigma^* \cdot P \cdot \Sigma^*$ is *regular* formal language

$\rightsquigarrow \exists$ *deterministic finite automaton* (DFA) to recognize $\Sigma^* \cdot P \cdot \Sigma^*$

\rightsquigarrow can check for occurrence of P in $|T| = n$ steps!



Job done!



WTF!?

We are not quite done yet.

► (Problem 0: programmer might not know automata and formal languages . . .)

► Problem 1: existence alone does not give an algorithm!

► Problem 2: automaton could be very big!


String matching with DFA

- Assume first, we already have a deterministic automaton
- How does string matching work?

Example:

$T = \text{aabacaababacaa}$

$P = \text{ababaca}$



text:		a	a	b	a	c	a	a	b	a	b	a	c	a	a
state:	0	1	1	2	3	0									


String matching with DFA

- Assume first, we already have a deterministic automaton
- How does string matching work?

Example:

$T = \text{aabacaababacaa}$

$P = \text{ababaca}$



text:		a	a	b	a	c	a	a	b	a	b	a	c	a	a
state:	0	1	1	2	3	0	1	1	2	3	4	5	6	7	7


String matching DFA – Intuition

Why does this work?

► Main insight:

State q means:
*“we have seen $P[0..q)$ until here
 (but not any longer prefix of P)”*


$T = \text{aabacaababacaa}$
 $P = \text{ababaca}$



text:		a	a	b	a	c	a	a	b	a	b	a	c	a	a
state:	0	1	1	2	3	0	1	1	2	3	4	5	6	7	7

► If the next text character c does not match, we know:

- (i) text seen so far ends with $P[0..q) \cdot c$
- (ii) $P[0..q) \cdot c$ is not a prefix of P
- (iii) without reading c , $P[0..q)$ was the *longest* prefix of P that ends here.




String matching DFA – Intuition

Why does this work?

► Main insight:

State q means:
*“we have seen $P[0..q)$ until here
 (but not any longer prefix of P)”*


$T = \text{aabacaababacaa}$
 $P = \text{ababaca}$



text:		a	a	b	a	c	a	a	b	a	b	a	c	a	a
state:	0	1	1	2	3	0	1	1	2	3	4	5	6	7	7

► If the next text character c does not match, we know:

- (i) text seen so far ends with $P[0...q) \cdot c$
- (ii) $P[0...q) \cdot c$ is not a prefix of P
- (iii) without reading c , $P[0..q)$ was the *longest* prefix of P that ends here.




↪ New longest matched prefix will be (weakly) shorter than q

↪ All information about the text needed to determine it is contained in $P[0...q) \cdot c$!

5.3 Constructing String Matching Automata


NFA instead of DFA?

It remains to *construct* the DFA.



NFA instead of DFA?

It remains to *construct* the DFA.



↪ We *could* use the NFA directly for string matching:

- at any point in time, we are in a **set of states**
- accept when one of them is final state


Example:

text:		a	a	b	a	c	a	a	b	a	b	a	c	a	a
state:	0	0, 1	0, 1	0, 2	0, 1, 3										

But maintaining a whole set makes this slow ...

NFA instead of DFA?

It remains to *construct* the DFA.



↪ We *could* use the NFA directly for string matching:

- at any point in time, we are in a **set of states**
- accept when one of them is final state

Example:

text:		a	a	b	a	c	a	a	b	a	b	a	c	a	a
state:	0	0,1	0,1	0,2	0,1,3	0	0,1	0,1	0,2	0,1,3	0,2,4	0,1,3,5	0,6	0,1,7	0,1,7

But maintaining a whole set makes this slow ...

Computing DFA directly



You have an NFA and want a DFA?
Simply apply the power-set construction
(and maybe DFA minimization)!

The powerset method has exponential state blow up!
I guess I might as well use brute force string matching ...



Computing DFA directly





You have an NFA and want a DFA?
Simply apply the power-set construction
(and maybe DFA minimization)!

The powerset method has exponential state blow up!
I guess I might as well use brute force string matching ...



Ingenious algorithm by Knuth, Morris, and Pratt: construct DFA *inductively*:

Suppose we add character $P[j]$ to automaton A_j for $P[0..j)$ to construct A_{j+1}

- ▶ add new state and matching transition \rightsquigarrow easy 
- ▶ for each $c \neq P[j]$, we need $\delta(j, c)$ (transition from  when reading c)

Computing DFA directly



You have an NFA and want a DFA?
Simply apply the power-set construction
(and maybe DFA minimization)!

The powerset method has exponential state blow up!
I guess I might as well use brute force string matching ...



Ingenious algorithm by Knuth, Morris, and Pratt: construct DFA *inductively*:

Suppose we add character $P[j]$ to automaton A_j for $P[0..j)$ to construct A_{j+1}

- ▶ add new state and matching transition \rightsquigarrow easy $\xrightarrow{P[j+1]} \textcircled{j+1}$
- ▶ for each $c \neq P[j]$, we need $\delta(j, c)$ (transition from \textcircled{j} when reading c)
- ▶ $\delta(j, c) =$ length of the longest prefix of $P[0..j)c$ that is a suffix of $P[1..j)c$
= state of automaton after reading $P[1..j)c$
 $\leq j \rightsquigarrow$ can use known automaton A_j for that!

State q means:
“we have seen $P[0..q)$ until here
(but not any longer prefix of P)”

Computing DFA directly



You have an NFA and want a DFA?
Simply apply the power-set construction
(and maybe DFA minimization)!

The powerset method has exponential state blow up!
I guess I might as well use brute force string matching ...



Ingenious algorithm by Knuth, Morris, and Pratt: construct DFA *inductively*:

Suppose we add character $P[j]$ to automaton A_j for $P[0..j)$ to construct A_{j+1}

- ▶ add new state and matching transition \rightsquigarrow easy $\xrightarrow{P[j+1]} \textcircled{j+1}$
- ▶ for each $c \neq P[j]$, we need $\delta(j, c)$ (transition from \textcircled{j} when reading c)
- ▶ $\delta(j, c) =$ length of the longest prefix of $P[0..j)c$ that is a suffix of $P[1..j)c$
= state of automaton after reading $P[1..j)c$
 $\leq j \rightsquigarrow$ can use known automaton A_j for that!

\rightsquigarrow can directly compute A_{j+1} from A_j !



seems to require simulating automata $m \cdot \sigma$ times

State q means:
"we have seen $P[0..q)$ until here
(but not any longer prefix of P)"

Computing DFA efficiently

- ▶ **KMP's second insight:** simulations in one step differ only in last symbol

↪ simply maintain state x , the state after reading $P[1..j]$.

- ▶ copy its transitions
- ▶ update x by following transitions for $P[j]$


$$P[1..j] \prec$$

Computing DFA efficiently

- **KMP's second insight:** simulations in one step differ only in last symbol

↪ simply maintain state x , the state after reading $P[1..j]$.

- copy its transitions
- update x by following transitions for $P[j]$



Example: $P[0..7] = ababaca$

```

1  procedure constructDFA( $P[0..m]$ ):
2      //  $\delta[q][c]$  = target state when reading  $c$  in state  $q$ 
3      for  $c \in \Sigma$  do
4           $\delta[0][c] := 0$ 
5       $\delta[0][P[0]] := 1$ 
6       $x := 0$ 
7      for  $j = 1, \dots, m - 1$  do
8          for  $c \in \Sigma$  do // copy transitions
9               $\delta[j][c] := \delta[x][c]$ 
10              $\delta[j][P[j]] := j + 1$  // match edge
11              $x := \delta[x][P[j]]$  // update  $x$ 

```

$\delta(c, q)$	0	1	2	3	4	5	6
a							
b	1	1	3	1			
c	0	2	0	4			
	0	0	0	0			

Computing DFA efficiently

- ▶ **KMP's second insight:** simulations in one step differ only in last symbol

↪ simply maintain state x , the state after reading $P[1..j]$.

- ▶ copy its transitions
- ▶ update x by following transitions for $P[j]$

```
1 procedure constructDFA( $P[0..m]$ ):  
2   //  $\delta[q][c]$  = target state when reading  $c$  in state  $q$   
3   for  $c \in \Sigma$  do  
4      $\delta[0][c] := 0$   
5    $\delta[0][P[0]] := 1$   
6    $x := 0$   
7   for  $j = 1, \dots, m - 1$  do  
8     for  $c \in \Sigma$  do // copy transitions  
9        $\delta[j][c] := \delta[x][c]$   
10     $\delta[j][P[j]] := j + 1$  // match edge  
11     $x := \delta[x][P[j]]$  // update  $x$ 
```

Example: $P[0..7] = \text{ababaca}$

$\delta(c, q)$	0	1	2	3	4	5	6
a	1	1	3	1	5	1	7
b	0	2	0	4	0	4	0
c	0	0	0	0	0	6	0

String matching with DFA – Discussion

► Time:

- Matching: n table lookups for DFA transitions
 - building DFA: $\Theta(m\sigma)$ time (constant time per transition edge).
- $\rightsquigarrow \Theta(m\sigma + n)$ time for string matching.

► Space:

- $\Theta(m\sigma)$ space for transition matrix.



fast matching time actually: hard to beat!



total time asymptotically optimal for small alphabet (for $\sigma = O(n/m)$)



substantial **space overhead**, in particular for large alphabets


5.4 The Knuth-Morris-Pratt algorithm

Failure Links

- ▶ Recall: String matching with DFA is fast,
but needs table of $m \times \sigma$ transitions.
- ▶ in fast DFA construction, we used that all simulations differ only by *last* symbol
- ↪ **KMP's third insight:** do this last step of simulation from state x during *matching!*
... but how?

Failure Links


- ▶ Recall: String matching with DFA is fast, but needs table of $m \times \sigma$ transitions.
- ▶ in fast DFA construction, we used that all simulations differ only by *last* symbol
- ↪ **KMP's third insight:** do this last step of simulation from state x during *matching*! ... but how?
- ▶ **Answer:** Use a new type of transition: \times , the *failure links*
 - ▶ Use this transition (only) if no other one fits.
 - ▶ \times does not consume a character. ↪ might follow several failure links



↪ Computations are deterministic (but automaton is not a classic DFA.)

Failure link automaton – Example


Example: $T = \text{abababaaaca}$, $P = \text{ababaca}$



T : a b a b a b a a b a b

Failure link automaton – Example

Example: $T = \text{abababaaaca}$, $P = \text{ababaca}$



T : a b a b a b a a b a b

P :

a	b	a	b	a	x						
		(a)	(b)	(a)	b	a	x				
							a	b	a	b	

to state 3

to state 1

q :

1	2	3	4	5	3,4	5	3,1,0,1	2	3	4
---	---	---	---	---	-----	---	---------	---	---	---

(after reading this character)

The Knuth-Morris-Pratt Algorithm

```
1 procedure KMP( $T[0..n]$ ,  $P[0..m]$ ):  
2    $fail[0..m] := failureLinks(P)$   
3    $i := 0$  // current position in  $T$   
4    $q := 0$  // current state of KMP automaton  
5   while  $i < n$  do  
6     if  $T[i] == P[q]$  then  
7        $i := i + 1$ ;  $q := q + 1$   
8       if  $q == m$  then  
9         return  $i - q$  // occurrence found  
10      else // i.e.  $T[i] \neq P[q]$   
11        if  $q \geq 1$  then  
12           $q := fail[q]$  // follow one  $\times$   
13        else  
14           $i := i + 1$   
15      end while  
16      return NO_MATCH
```

- ▶ only need single array *fail* for failure links
- ▶ (failureLinks on next slide)

The Knuth-Morris-Pratt Algorithm

```
1 procedure KMP( $T[0..n]$ ,  $P[0..m]$ ):  
2    $fail[0..m] := \text{failureLinks}(P)$   
3    $i := 0$  // current position in  $T$   
4    $q := 0$  // current state of KMP automaton  
5   while  $i < n$  do  
6     if  $T[i] == P[q]$  then  
7        $i := i + 1$ ;  $q := q + 1$   
8       if  $q == m$  then  
9         return  $i - q$  // occurrence found  
10      else // i.e.  $T[i] \neq P[q]$   
11        if  $q \geq 1$  then  
12           $q := fail[q]$  // follow one  $\times$   
13        else  
14           $i := i + 1$   
15      end while  
16      return NO_MATCH
```

► only need single array *fail* for failure links

► (failureLinks on next slide)

Analysis: (matching part)

► always have $fail[j] < j$ for $j \geq 1$

\rightsquigarrow in each iteration

► either advance position in text ($i := i + 1$)

► or shift pattern forward (guess $i - q$)

► each can happen at most n times


$\rightsquigarrow \leq 2n$ symbol comparisons!

Computing failure links

► failure links point to error state x (from DFA construction)

↪ run same algorithm, but store $fail[j] := x$ instead of copying all transitions

```
1 procedure failureLinks( $P[0..m]$ ):  
2    $fail[0] := 0$   
3    $x := 0$   
4   for  $j := 1, \dots, m-1$  do  
5      $fail[j] := x$   
6     // update failure state using failure links:  
7     while  $P[x] \neq P[j]$   
8       if  $x == 0$  then  
9          $x := -1$ ; break  
10      else  
11         $x := fail[x]$   
12      end while  
13       $x := x + 1$   
14   end for
```



Computing failure links

► failure links point to error state x (from DFA construction)

\rightsquigarrow run same algorithm, but store $fail[j] := x$ instead of copying all transitions

```
1 procedure failureLinks( $P[0..m]$ ):  
2    $fail[0] := 0$   
3    $x := 0$   
4   for  $j := 1, \dots, m - 1$  do  
5      $fail[j] := x$   
6     // update failure state using failure links:  
7     while  $P[x] \neq P[j]$   
8       if  $x == 0$  then  
9          $x := -1$ ; break  
10      else  
11         $x := fail[x]$   
12      end while  
13       $x := x + 1$   
14 end for
```

Analysis:

► m iterations of for loop

► while loop always decrements x

► x is incremented only once per iteration of for loop

$\rightsquigarrow \leq m$ iterations of while loop *in total*

$\rightsquigarrow \leq 2m$ symbol comparisons

Knuth-Morris-Pratt – Discussion

► Time:

- $\leq 2n + 2m = O(n + m)$ character comparisons
 - clearly must at least *read* both T and P in the worst case
- ~> KMP has optimal worst-case complexity

► Space:

- $\Theta(m)$ space for failure links



total time asymptotically optimal (for any alphabet size)



reasonable extra space

The KMP prefix function

- ▶ It turns out that the failure links are useful beyond KMP
- ▶ a slight variation is (more?) widely used: (for historic reasons)
the (KMP) prefix function $F : [1..m - 1] \rightarrow [0..m - 1]$:

$F[j]$ *is the length of the longest prefix of $P[0..j]$
that is a suffix of $P[1..j]$.*

- ▶ Can show: $fail[j] = F[j - 1]$ for $j \geq 1$, and hence

$fail[q] =$ *length of the
longest prefix of $P[0..q]$
that is a suffix of $P[1..q]$.*

← memorize this!

- ▶ EAA Buch: String indices are 1-based, but definition of failure links matches!

$$\Pi_P(q) = fail[q]$$

$\Pi_P : [1..m] \rightarrow [0..m - 1]$ with $\Pi_P(q) = \max\{k \in \mathbb{N}_0 : k < q \wedge P[0..k] \sqsupseteq P[0..q]\} = fail[q]$

5.5 The Aho-Corasick Algorithm

Multiple-Pattern Matching

► So far: process a single pattern P in one pass over T .

↪ Cannot beat time $\Omega(p \cdot n)$

Multiple-Pattern Matching

► So far: process a single pattern P in one pass over T .

↪ Cannot beat time $\Omega(p \cdot n)$

► The essence of KMP can be generalized to deal with several patterns!

↪ The *Aho-Corasick Algorithm*

Multiple-Pattern Matching

- ▶ So far: process a single pattern P in one pass over T .

↪ Cannot beat time $\Omega(p \cdot n)$

- ▶ The essence of KMP can be generalized to deal with several patterns!

↪ The *Aho-Corasick Algorithm*

The Multiple-Pattern Matching Problem

- ▶ **Given:** text $T[0..n)$, patterns $P[0..p)$, $P[r] = P_r[0..m_r)$
 - ▶ all over $\Sigma = [0..\sigma)$ for **constant** σ
 - ▶ total length of patterns: $m := \sum_{0 \leq r < p} m_r$
- ▶ **Goal:** all matches, i. e., all pairs (i, r) such that $P_r = T[i..i + m_r)$

Multiple-Pattern Matching

- ▶ So far: process a single pattern P in one pass over T .

↪ Cannot beat time $\Omega(p \cdot n)$

- ▶ The essence of KMP can be generalized to deal with several patterns!

↪ The *Aho-Corasick Algorithm*

The Multiple-Pattern Matching Problem

- ▶ **Given:** text $T[0..n)$, patterns $P[0..p)$, $P[r] = P_r[0..m_r)$

- ▶ all over $\Sigma = [0..\sigma)$ for **constant** σ

- ▶ total length of patterns: $m := \sum_{0 \leq r < p} m_r$

- ▶ **Goal:** all matches, i.e., all pairs (i, r) such that $P_r = T[i..i + m_r)$

single pass!


Aho-Corasick can do this with $O(m)$ preprocessing and $O(n + \text{output})$ matching time!

Here *output* is the number of match pairs (i, r) .

Aho-Corasick Automaton – Overview

Aho-Corasick Automaton

1. Build trie A from patterns $P[0..p)$.
2. Add *failure links* to A .
3. Add *output links* to A . NEW




Recap: Tries

- ▶ efficient dictionary data structure for strings
- ▶ name from **re**trieval, but pronounced “try”
- ▶ tree based on symbol comparisons

▶ **Example:**

{aa\$, aaab\$, abaab\$, abb\$,
abbab\$, bba\$, bbab\$, bbb\$}




Recap: Tries

- ▶ efficient dictionary data structure for strings
- ▶ name from **re**trieval, but pronounced “try”
- ▶ tree based on symbol comparisons


▶ **Example:**

{aa\$, aaab\$, abaab\$, abb\$,
abbab\$, bba\$, bbab\$, bbb\$}



When stored string is a strict prefix of another, internal nodes can correspond to strings.


{aa\$, aaab\$, abaab\$, abb\$,
 abbab\$, bba\$, bbab\$, bbb\$}



Aho-Corasick Automaton – Adding Failure Links

Trie for P_r corresponds to match-edges-only NFA.

\rightsquigarrow Interpreting the trie as automaton, add ε -edges back to the root.




Aho-Corasick Automaton – Adding Failure Links

Trie for P_r corresponds to match-edges-only NFA.

↪ Interpreting the trie as automaton, add ε -edges back to the root.

► as in KMP, instead of determinizing the automation classically, we again use failure links

↪ construction as for KMP using failure state x , repeated for each word.



Aho-Corasick Automaton – Output Links

An automaton state might contain other patterns as suffix \rightsquigarrow must output match(es)! But we are not in an accepting state, so direct use of automaton so far would miss occurrence!

- ▶ **output links:** each state points to longest suffix pattern (if any).
 - ▶ During matching, traverse linked list of matches and output each $\rightsquigarrow O(\text{output})$ cost overall
 - ▶ Computation of output links similar to failure links! (handle patterns by length)

in
ting

