

ALGORITHMS \$ EFFICIENT
CIENTALGORITHMS \$ EFFI
EFFICIENTALGORITHMS \$
FFICIENTALGORITHMS \$
FICIENTALGORITHMS \$
GORITHMS \$ EFFICIENTAL
HMS \$ EFFICIENTALGORIT
ICIENTALGORITHMS \$ EFF
ITMS \$ EFFICIENTALGOR
LGORITHMS \$ EFFICIENTAL
MS \$ EFFICIENTALGORIT
NTALGORITHMS \$ EFFIC
ORITHMS \$ EFFICIENTALG
RITHMS \$ EFFICIENTALGO
S \$ EFFICIENTALGORITHM
TALGORITHMS \$ EFFICIENT
THMS \$ EFFICIENTALGORI

5

Parallel Algorithms

2 November 2022

Sebastian Wild

Learning Outcomes

1. Know and apply *parallelization strategies* for embarrassingly parallel problems.
2. Identify *limits of parallel speedups*.
3. Understand and use the *parallel random-access-machine* model in its different variants.
4. Be able to *analyze* and compare simple shared-memory parallel algorithms by determining *parallel time and work*.
5. Understand efficient parallel *prefix sum* algorithms.
6. Be able to devise high-level description of *parallel quicksort and mergesort* methods.

Unit 5: *Parallel Algorithms*



Outline

5 Parallel Algorithms

- 5.1 Parallel computation
- 5.2 Parallel String Matching
- 5.3 Parallel primitives
- 5.4 Parallel sorting

5.1 Parallel computation

Clicker Question



Have you ever written a concurrent program (explicit threads, job pools library, or using a framework for distributed computing)?

- ☐ **A** Yes
- ☐ **B** No
- ☐ **C** Concur... what?



→ *sli.do/comp526*

Types of parallel computation

£££ can't buy you more time . . . but more computers!

⇒ Challenge: Algorithms for *parallel* computation.

Types of parallel computation

£££ can't buy you more time . . . but more computers!

↪ Challenge: Algorithms for *parallel* computation.

There are two main forms of parallelism:

1. shared-memory parallel computer ← *focus of today*

- ▶ *p processing elements* (PEs, processors) working in parallel
- ▶ **single** big memory, **accessible from every PE**
- ▶ communication via shared memory
- ▶ think: a big server, 128 CPU cores, terabyte of main memory

2. distributed computing

- ▶ *p* PEs working in parallel
- ▶ each PE has **private** memory
- ▶ communication by sending **messages** via a network
- ▶ think: a cluster of individual machines

PRAM – Parallel RAM

- ▶ extension of the RAM model (recall Unit 1)
- ▶ the p PEs are identified by ids $0, \dots, p-1$
 - ▶ like w (the word size), p is a parameter of the model that can grow with n
 - ▶ $p = \Theta(n)$ is not unusual maaany processors!
- ▶ the PEs all ^{the same} **independently** run a RAM-style program
(they can use their id there)
- ▶ each PE has its own registers, but **MEM** is shared among all PEs
- ▶ computation runs in **synchronous** steps:
in each time step, every PE executes one instruction

PRAM – Conflict management



Problem: What if several PEs simultaneously overwrite a memory cell?

- ▶ **EREW-PRAM** (exclusive read, exclusive write)
any **parallel access** to same memory cell is **forbidden** (crash if happens)

- ▶ **CREW-PRAM** (concurrent read, exclusive write)
parallel **write** access to same memory cell is *forbidden*, but reading is fine



- ▶ **CRCW-PRAM** (concurrent read, concurrent write)
concurrent access is allowed,
need a rule for write conflicts:
 - ▶ common CRCW-PRAM:
all concurrent writes to same cell must write *same* value
 - ▶ arbitrary CRCW-PRAM:
some unspecified concurrent write wins
 - ▶ (more exist . . .)



- ▶ no single model is always adequate, but our default is CREW

PRAM – Execution costs

Cost metrics in PRAMs

- ▶ **space:** total amount of accessed memory
- ▶ **time:** number of steps till all PEs finish assuming sufficiently many PEs!
sometimes called *depth* or *span*
- ▶ **work:** total #instructions executed on **all** PEs

PRAM – Execution costs

Cost metrics in PRAMs

- ▶ **space:** total amount of accessed memory
- ▶ **time:** number of steps till all PEs finish assuming sufficiently many PEs!
sometimes called *depth* or *span*
- ▶ **work:** total #instructions executed on **all** PEs

Holy grail of PRAM algorithms:

- ▶ minimal time
- ▶ work (asymptotically) no worse than running time of best sequential algorithm
 \rightsquigarrow “*work-efficient*” algorithm: work in same Θ -class as best sequential

Clicker Question



Does every computational problem allow a work-efficient algorithm?

A Yes

B No



→ *sli.do/comp526*

Clicker Question



Does every computational problem allow a work-efficient algorithm?

A Yes ✓

B ~~No~~



→ *sli.do/comp526*



The number of processors

Hold on, my computer does not have $\Theta(n)$ processors! Why should I care for span and work!?

Theorem 5.1 (Brent's Theorem)

If an algorithm has span T and work W (for an arbitrarily large number of processors), it can be run on a PRAM with p PEs in time $O(T + \frac{W}{p})$ (and using $O(W)$ work). ◀

Proof: schedule parallel steps in round-robin fashion on the p PEs.



⇒ span and work give guideline for *any* number of processors

5.2 Parallel String Matching

Embarrassingly Parallel

- ▶ A problem is called “*embarrassingly parallel*” if it can immediately be split into *many, small subtasks* that can be solved completely *independently* of each other
- ▶ Typical example: sum of two large matrices (all entries independent)
- ↪ best case for parallel computation (simply assign each processor one subtask)
- ▶ Sorting is not embarrassingly parallel
 - ▶ no obvious way to define many small (= efficiently solvable) subproblems
 - ▶ but: some subtasks of our algorithms are (stay tuned . . .)

Clicker Question



Is the string-matching problem “embarrassingly parallel”?

- ☐ **A** Yes
- ☐ **B** No
- ☐ **C** Only for $n \gg m$
- ☐ **D** Only for $n \approx m$



→ sli.do/comp526


Parallel string matching – Easy?

► We have seen a plethora of string matching methods in Unit 4

► But all efficient methods seem inherently sequential

Indeed, they became efficient only after building on knowledge from previous steps!

Sounds like the *opposite* of parallel!




~> How well can we parallelize string matching?

Here: string matching = find *all* occurrences of P in T (more natural problem for parallel)
always assume $m \leq n$

Parallel string matching – Easy?

- ▶ We have seen a plethora of string matching methods in Unit 4
- ▶ But all efficient methods seem inherently sequential
Indeed, they became efficient only after building on knowledge from previous steps!

Sounds like the *opposite* of parallel!



~> How well can we parallelize string matching?

Here: string matching = find *all* occurrences of P in T (more natural problem for parallel)
always assume $m \leq n$

Subproblems in string matching:

- ▶ string matching = check all guesses $i = 0, \dots, n - m - 1$
- ▶ checking one guess is a subtask!

Parallel string matching – Brute force

- ▶ Check all guesses in parallel

```
1 procedure parallelBruteForce( $T[0..n)$ ,  $P[0..m)$ )
2   for  $i := 0, \dots, n - m - 1$  do in parallel ← only difference to normal brute force!
3     for  $j := 0, \dots, m - 1$  do
4       if  $T[i + j] \neq P[j]$  then break inner loop
5     if  $j == m$  then report match at  $i$ 
6   end parallel for
```

- ▶ PE k is executing the loop iteration where $i = k$.
 - ↪ requires that all iterations can be done **independently!**
 - ▶ Different PEs work **in lockstep** (synchronized after each instruction)
 - ▶ similar to OpenMP `#pragma omp parallel for`
- ▶ checking whether *no* match was found by *any* PE more effort ↪ ... stay tuned

Parallel string matching – Brute force

- ▶ Check all guesses in parallel

```
1 procedure parallelBruteForce( $T[0..n]$ ,  $P[0..m]$ )
2   for  $i := 0, \dots, n - m - 1$  do in parallel ← only difference to normal brute force!
3     for  $j := 0, \dots, m - 1$  do
4       if  $T[i + j] \neq P[j]$  then break inner loop
5     if  $j == m$  then report match at  $i$ 
6   end parallel for
```

- ▶ PE k is executing the loop iteration where $i = k$.
 - ↪ requires that all iterations can be done **independently!**
 - ▶ Different PEs work **in lockstep** (synchronized after each instruction)
 - ▶ similar to OpenMP `#pragma omp parallel for`
 - ▶ checking whether *no* match was found by *any* PE more effort ↪ ... stay tuned
- ↪ **Time:** $\Theta(m)$ using sequential checks **Work:** $\Theta((n - m)m)$ ↪ not great
 $\Theta(\log m)$ on CREW-PRAM (↪ tutorials) ... much more than best sequential
 $\Theta(1)$ on CRCW-PRAM (↪ tutorials)

Parallel string matching – Blocking



Divide T into **overlapping** blocks of $2m - 1$ characters:
 $T[0..2m - 1)$, $T[m..3m - 1)$, $T[2m..4m - 1)$, $T[3m..5m - 1)$...

- Find matches inside blocks in parallel, using efficient sequential method

```
1 procedure blockingStringMatching( $T[0..n)$ ,  $P[0..m)$ )  
2   for  $b := 0, \dots, \lceil n/m \rceil$  do in parallel  
3      $result := \text{KMP}(T[bm .. (b+1)m - 1), P)$   
4     if  $result \neq \text{NO\_MATCH}$  then report match at  $result$   
5   end parallel for
```



$$m = 3$$

$$2m - 1 = 5$$

Parallel string matching – Blocking



Divide T into **overlapping** blocks of $2m - 1$ characters:

$T[0..2m - 1), T[m..3m - 1), T[2m..4m - 1), T[3m..5m - 1) \dots$

- Find matches inside blocks in parallel, using efficient sequential method

```
1 procedure blockingStringMatching( $T[0..n), P[0..m)$ )
2   for  $b := 0, \dots, \lceil n/m \rceil$  do in parallel
3      $result := \text{KMP}(T[bm .. (b+1)m - 1), P)$ 
4     if  $result \neq \text{NO\_MATCH}$  then report match at  $result$ 
5   end parallel for
```

↪ **Time:**

- loop body has text of length $n' = 2m - 1$ and pattern of length m

↪ KPM runtime $\Theta(n' + m) = \Theta(m)$

↪ **Work:** $\Theta(\frac{n}{m} \cdot m) = \Theta(n)$ ↪ work efficient!

Clicker Question



Is the string-matching problem “embarrassingly parallel”?

- ☐ **A** Yes
- ☐ **B** No
- ☐ **C** Only for $n \gg m$
- ☐ **D** Only for $n \approx m$



→ sli.do/comp526

Clicker Question



Is the string-matching problem “embarrassingly parallel”?

- ☐ A ~~Yes~~
- ☐ B ~~No~~
- ☒ C Only for $n \gg m$ ✓
- ☐ D ~~Only for $n \approx m$~~



→ sli.do/comp526

Parallel string matching – Discussion

- 👍 very simple methods
- 👍 could even run distributed with access to part of T
- 👎 parallel speedup only for $m \ll n$

Parallel string matching – Discussion



very simple methods



could even run distributed with access to part of T



parallel speedup only for $m \ll n$

► work-efficient methods with better parallel time possible?

↪ must genuinely parallelize the matching process! (and the preprocessing of the pattern)

↪ needs new ideas (much more complicated, but possible!)

Parallel string matching – Discussion



very simple methods



could even run distributed with access to part of T



parallel speedup only for $m \ll n$

► work-efficient methods with better parallel time possible?

↪ must genuinely parallelize the matching process! (and the preprocessing of the pattern)

↪ needs new ideas (much more complicated, but possible!)

► **Parallel string matching – State of the art:**

► $O(\log m)$ time & work-efficient parallel string matching (very complicated)

► this is optimal for CREW-PRAM

► on CRCW-PRAM: matching part even in $O(1)$ time (easy)

but preprocessing requires $\Theta(\log \log m)$ time (very complicated)

5.3 Parallel primitives

Building blocks



- ▶ Most nontrivial problems need tricks to be parallelized
 - ▶ Some versatile building blocks are known that help in many problems
- ~→ We study some of them now, before we apply them to *parallel sorting*


Prefix sums

Prefix-sum problem (also: cumulative sums, running totals)

- ▶ Given: array $A[0..n)$ of numbers
- ▶ Goal: compute all prefix sums $A[0] + \dots + A[i]$ for $i = 0, \dots, n - 1$
may be done “in-place”, i. e., by overwriting A

Example:

input:



3	0	0	5	7	0	0	2	0	0	0	4	0	8	0	1
---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---

output:

3	3	3	8	15	15	15	17	17	17	17	21	21	29	29	30
---	---	---	---	----	----	----	----	----	----	----	----	----	----	----	----

Clicker Question



What is the *sequential* running time achievable for prefix sums?

A $O(n^3)$

D $O(n)$

B $O(n^2)$

E $O(\sqrt{n})$

C $O(n \log n)$

F $O(\log n)$



→ sli.do/comp526

Clicker Question



What is the *sequential* running time achievable for prefix sums?

A ~~$O(n^3)$~~

B ~~$O(n^2)$~~

C ~~$O(n \log n)$~~

D $O(n)$ ✓

E ~~$O(\sqrt{n})$~~

F ~~$O(\log n)$~~



→ sli.do/comp526

Prefix sums – Sequential

- ▶ sequential solution does $n - 1$ additions
- ▶ but: cannot parallelize them!
⚡ data dependencies!

~> need a different approach

```
1 procedure prefixSum( $A[0..n]$ )  
2   for  $i := 1, \dots, n - 1$  do  
3      $A[i] := A[i - 1] + A[i]$ 
```

Prefix sums – Sequential

- ▶ sequential solution does $n - 1$ additions
- ▶ but: cannot parallelize them!
⚡ data dependencies!

~> need a different approach

Let's try a simpler problem first.

Excursion: Sum

- ▶ Given: array $A[0..n)$ of numbers
- ▶ Goal: compute $A[0] + A[1] + \dots + A[n - 1]$
(solved by prefix sums)

```
1 procedure prefixSum( $A[0..n)$ )  
2   for  $i := 1, \dots, n - 1$  do  
3      $A[i] := A[i - 1] + A[i]$ 
```

Prefix sums – Sequential

- ▶ sequential solution does $n - 1$ additions
- ▶ but: cannot parallelize them!
⚡ data dependencies!

↪ need a different approach

Let's try a simpler problem first.


Excursion: Sum

- ▶ Given: array $A[0..n)$ of numbers
- ▶ Goal: compute $A[0] + A[1] + \dots + A[n - 1]$
(solved by prefix sums)

Any algorithm *must* do $n - 1$ binary additions

↪ Height of tree = parallel time!

```
1 procedure prefixSum( $A[0..n)$ )
2   for  $i := 1, \dots, n - 1$  do
3      $A[i] := A[i - 1] + A[i]$ 
```



Parallel prefix sums


- Idea: Compute all prefix sums with balanced trees in parallel
Remember partial results for reuse

input:

3	0	0	5	7	0	0	2	0	0	0	4	0	8	0	1
---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---


Parallel prefix sums

- Idea: Compute all prefix sums with balanced trees in parallel
Remember partial results for reuse




Parallel prefix sums

- Idea: Compute all prefix sums with balanced trees in parallel
Remember partial results for reuse




Parallel prefix sums

- Idea: Compute all prefix sums with balanced trees in parallel
Remember partial results for reuse




Parallel prefix sums

- Idea: Compute all prefix sums with balanced trees in parallel
Remember partial results for reuse



Parallel prefix sums

- Idea: Compute all prefix sums with balanced trees in parallel
Remember partial results for reuse



Parallel prefix sums – Code

- ▶ can be realized in-place (overwriting A)
- ▶ assumption: in each parallel step, all reads precede all writes

```
1 procedure parallelPrefixSums( $A[0..n]$ )
2   for  $r := 1, \dots, \lceil \lg n \rceil$  do
3      $O(1)$   $step := 2^{r-1}$ 
4      $O(\log n)$  for  $i := step, \dots, n-1$  do in parallel
5        $O(1)$   $x := A[i] + A[i - step]$ 
6        $O(1)$   $A[i] := x$ 
7     end parallel for
8   end for
```

$O(n)$ $O(n \log n)$

Parallel prefix sums – Analysis

► Time:

- all additions of one round run in parallel

- $\lceil \lg n \rceil$ rounds

$\rightsquigarrow \Theta(\log n)$ time best possible! (from sum)

► Work:

- $\geq \frac{n}{2}$ additions in all rounds (except maybe last round)

$\rightsquigarrow \Theta(n \log n)$ work

- more than the $\Theta(n)$ sequential algorithm!

Parallel prefix sums – Analysis

► Time:

- all additions of one round run in parallel

- $\lceil \lg n \rceil$ rounds

$\rightsquigarrow \Theta(\log n)$ time best possible!

► Work:

- $\geq \frac{n}{2}$ additions in all rounds (except maybe last round)

$\rightsquigarrow \Theta(n \log n)$ work

- more than the $\Theta(n)$ sequential algorithm!

- Typical trade-off: greater parallelism at the expense of more overall work

Parallel prefix sums – Analysis

► Time:

- all additions of one round run in parallel

- $\lceil \lg n \rceil$ rounds

↪ $\Theta(\log n)$ time best possible!

► Work:

- $\geq \frac{n}{2}$ additions in all rounds (except maybe last round)

↪ $\Theta(n \log n)$ work

- more than the $\Theta(n)$ sequential algorithm!

- Typical trade-off: greater parallelism at the expense of more overall work

- For prefix sums:

- can actually get $\Theta(n)$ work in *twice* that time!

↪ algorithm is slightly more complicated

- instead here: linear work in *thrice* the time using “blocking trick”

Work-efficient parallel prefix sums

← recall string matching!

standard trick to improve work: compute small blocks sequentially

1. Set $b := \lceil \lg n \rceil$
2. For blocks of b consecutive indices, i. e., $A[0..b), A[b..2b), \dots$ **do in parallel:**
 - ▶ compute local prefix sums with fast **sequential** algorithm
3. Use previous work-inefficient parallel algorithm only on **rightmost elements** of block, i. e., to compute prefix sums of $A[b-1], A[2b-1], A[3b-1], \dots$
4. For blocks $A[0..b), A[b..2b), \dots$ **do in parallel:**
 - Add block-prefix sums to local prefix sums

Analysis:

- ▶ **Time:**
 - ▶ 2. & 4.: $\Theta(b) = \Theta(\log n)$ time
 - ▶ 3. $\Theta(\log(n/b)) = \Theta(\log n)$ time
- ▶ **Work:**
 - ▶ 2. & 4.: $\Theta(b)$ per block $\times \lceil \frac{n}{b} \rceil$ blocks $\rightsquigarrow \Theta(n)$
 - ▶ 3. $\Theta(\frac{n}{b} \log(\frac{n}{b})) = \Theta(n)$

$$n = 12$$

$$b = 4$$

0	4	8
1 1 1 1	1 1 1 1	1 1 1 1

1 2 3 4	1 2 3 4	1 2 3 4
---------	---------	---------

$$n' = \left\lceil \frac{n}{b} \right\rceil = \Theta\left(\frac{n}{b}\right) = \Theta\left(\frac{n}{\log n}\right)$$

4	4	4
---	---	---

4	8	12
---	---	----

1 2 3 4	1 2 3 4	1 2 3 4
---------	---------	---------

1 2 3 4	5 6 7 8	9 10 11 12
---------	---------	------------

time

work

$$\Theta(b) = \Theta(\log n) \quad \Theta(b) \text{ per block} \\ \times \frac{n}{b} \text{ blocks} \\ = \Theta(n)$$

$$\Theta(\log n') \\ = \Theta(\log n) \quad \Theta(n' \log n')$$

$$= \Theta\left(\frac{n}{\log n} \log n\right) \\ = \Theta(n)$$


$$\Theta(b)$$

$$\Theta\left(\frac{n}{b} \cdot b\right) = \Theta(n)$$

Compacting subsequence

How do prefix sums help with sorting? one more step to go ...


Goal: *Compact* a subsequence of an array



Compacting subsequences

How do prefix sums help with sorting? one more step to go ...

Goal: *Compact* a subsequence of an array



Use prefix sums on bitvector B

↪ offset of selected cells in S

```
1 C := B // deep copy of B
2 parallelPrefixSums(C)
3 for j := 0, ..., n - 1 do in parallel
4     if B[j] == 1 then S[C[j] - 1] := A[j]
5 end parallel for
```

Clicker Question



What is the parallel time and work achievable for *compacting* a subsequence of an array of size n ?

- ☐ A $O(1)$ time, $O(n)$ work
- ☐ B $O(\log n)$ time, $O(n)$ work
- ☐ C $O(\log n)$ time, $O(n \log n)$ work
- ☐ D $O(\log^2 n)$ time, $O(n^2)$ work
- ☐ E $O(n)$ time, $O(n)$ work



→ sli.do/comp526

Clicker Question



What is the parallel time and work achievable for *compacting* a subsequence of an array of size n ?

- ☐ A ~~$O(1)$ time, $O(n)$ work~~
- ☒ B $O(\log n)$ time, $O(n)$ work ✓
- ☐ C ~~$O(\log n)$ time, $O(n \log n)$ work~~
- ☐ D ~~$O(\log^2 n)$ time, $O(n^2)$ work~~
- ☐ E ~~$O(n)$ time, $O(n)$ work~~



→ sli.do/comp526