



Date	SYM	REVISION RECORD	AUTH	DR.	CK.
10/12/07	E	UPDATED PCB LAYOUT	T.B.	B.S.	
11/21/07	F	DIM. 5.30 WAS 5.00	T.B.	B.S.	
6/06/08	G	Temperature range was -40°C to +315°C	T.B.	B.S.	
2/26/10	H	Dim. 29.30 was 31.80	T.B.	B.S.	
3/05/10	J	Updated PCB Layout	T.B.	B.S.	
4/25/14	K	Updated to ROHS 2 Compliant	T.B.	B.S.	



SPECIFICATIONS:

- * Holder material- 30% glass reinforced Liquid Crystal Polymer resin, UL File No. E123598 UL94V-0
- * Color: White
- * Contacts : 0.020" thick PHOS-BRONZE, GOLD FLASH
- * Temperature range: -40°C to +280°C
- * Vibration Test: 10-50-10 Hz swept in 60 seconds
X,Y,Z direction: 1 hour each direction
- * Result: No dislodgement of the cell or damage
No discontinuity over 10 micro-seconds
- * Shock Test: Half sine wave acceleration 150G. 6 ms
3 shock pulses each direction per axis, total of 18 pulses
- * Result: No evidence of physical damage
- * ROHS 2 COMPLIANT

Tolerance (Except as noted)	 <div>Memory Protection Devices, Inc 200 Broad Hollow Road, Farmingdale, New York 11735</div>		
decimal $\pm .5$ (.020)		Scale	Drawn By B.S. Approved By T.B.
Fractional $\pm .8$ (.030)	Title SURFACE MOUNT BATTERY HOLDER FOR CR2032		
Angular $\pm 3^{\circ}$	Date 4/25/14	Drawing Number BU2032SM-HD-G	