

Raw Security Data Profile

```
{
  "ssh": {
    "version": "OpenSSH 9.6p1",
    "banner": "OpenSSH_9.6p1",
    "port": 22,
    "network": {
      "address_family": {
        "value": "any",
        "risk": "low"
      },
      "listen_address": "0.0.0.0:22"
    },
    "authentication": {
      "usepam": true,
      "max_auth_tries": 6,
      "permit_root_login": "without-password",
      "ignorerhosts": true,
      "hostbasedauthentication": false,
      "pubkey_authentication": true,
      "gssapiauthentication": false,
      "password_authentication": {
        "value": true,
        "risk": "high"
      },
      "permit_empty_passwords": false,
      "authentication_methods": {
        "value": "any",
        "risk": "high"
      }
    },
    "session": {
      "login_grace_time": 120,
      "max_sessions": 10,
      "client_alive_interval": {
        "value": 0,
        "risk": "medium"
      },
      "client_alive_count_max": 3,
      "maxstartups": "10:30:100"
    },
    "forwarding": {
      "gateway_ports": false,
      "allow_tcp_forwarding": {
        "value": true,
        "risk": "medium"
      },
      "allow_agent_forwarding": {
        "value": true,
        "risk": "medium"
      }
    }
  }
}
```

```

    },
    "allow_streamlocal_forwarding": {
        "value": true,
        "risk": "medium"
    },
    "permit_open": {
        "value": "any",
        "risk": "medium"
    },
    "permit_listen": {
        "value": "any",
        "risk": "medium"
    }
},
"features": {
    "x11_forwarding": {
        "value": true,
        "risk": "medium"
    },
    "strict_modes": true,
    "compression": true,
    "use_dns": {
        "value": false,
        "risk": "low"
    },
    "banner": "none",
    "permit_user_environment": false,
    "log_level": "INFO",
    "syslog_facility": "AUTH"
},
"compression": "enabled (zlib@openssh.com)",
"all_ciphers": [
    "chacha20-poly1305@openssh.com",
    "aes128-ctr",
    "aes192-ctr",
    "aes256-ctr",
    "aes128-gcm@openssh.com",
    "aes256-gcm@openssh.com"
],
"sshd_config_permissions": "644 root root /etc/ssh/sshd_config",
"ssh_privkey_permissions": "600 root root /etc/ssh/ssh_host_ecdsa_k
"ssh_pubkey_permissions": "644 root root /etc/ssh/ssh_host_ecdsa_ke
},
"crypto": {
    "weak_macs": [
        {
            "algorithm": "umac-64-etm@openssh.com",
            "severity": "medium",
            "reason": "UMAC-64 in EtM; 64-bit birthday bound too small for
        },
        {
            "algorithm": "hmac-shal-etm@openssh.com",
            "severity": "high",

```

```

    "reason": "SHA-1 in EtM mode; enables Terrapin attack (CVE-2023
  },
  {
    "algorithm": "umac-64@openssh.com",
    "severity": "medium",
    "reason": "UMAC with 64-bit tag; birthday attack risk at ~2^32
  },
  {
    "algorithm": "umac-128@openssh.com",
    "severity": "medium",
    "reason": "Algorithm is deprecated or has known cryptographic w
  },
  {
    "algorithm": "hmac-sha2-256",
    "severity": "medium",
    "reason": "Algorithm is deprecated or has known cryptographic w
  },
  {
    "algorithm": "hmac-sha2-512",
    "severity": "medium",
    "reason": "Algorithm is deprecated or has known cryptographic w
  },
  {
    "algorithm": "hmac-sha1",
    "severity": "high",
    "reason": "SHA-1 hash; collision attacks demonstrated; deprecate
  }
],
"weak_kex": [
  {
    "algorithm": "ecdh-sha2-nistp256",
    "severity": "high",
    "reason": "NIST P-256 curve has suspected NIST/NSA backdoor per
  },
  {
    "algorithm": "ecdh-sha2-nistp384",
    "severity": "high",
    "reason": "NIST P-384 curve; same NSA-standardized curve trust
  },
  {
    "algorithm": "ecdh-sha2-nistp521",
    "severity": "high",
    "reason": "NIST P-521 curve; same NSA-standardized curve trust
  },
  {
    "algorithm": "diffie-hellman-group14-sha256",
    "severity": "medium",
    "reason": "Algorithm is deprecated or has known cryptographic w
  }
],
"weak_host_keys": [
  {
    "algorithm": "ecdsa-sha2-nistp256",

```

```

        "severity": "high",
        "reason": "Algorithm is deprecated or has known cryptographic w
    }
]
},
"vulnerabilities": [
    {
        "cve": "CVE-2023-48795",
        "name": "Terrapin Attack",
        "risk": "high",
        "description": "Prefix truncation attack on SSH handshake via Cha
        "affected_algorithms": [
            "hmac-sha1-etm@openssh.com"
        ],
        "notes": "Mitigated by removing CBC-EtM MACs and ensuring strict
    },
    {
        "cve": "CVE-2002-20001",
        "name": "DROWN (Diffie-Hellman Key Reuse)",
        "risk": "high",
        "description": "Use of weak Diffie-Hellman groups allows a man-in
        "affected_algorithms": [
            "ecdh-sha2-nistp256",
            "ecdh-sha2-nistp384",
            "ecdh-sha2-nistp521"
        ],
        "notes": "Remove DH group sizes below 3072 bits."
    }
]
}

```