```
┌──(kali㉿kali)-[~]
└─$ ./CFC0324.s8.zx305.sh

═══════════════════════════════════════════
   Domain Mapper - Environment Setup
═══════════════════════════════════════════

[?] Enter network range (e.g. 192.168.1.0/24): 127.0.0.1/32
[?] Enter domain name: test.local
[?] Do you want to provide AD credentials? (y/n): n
[*] Skipping AD credentials
[?] Password list path (press Enter for default rockyou):
[?] Enter name for results folder (press Enter for auto):

[+] Environment initialized successfully
[+] Results directory: results_2026-01-28_14-15

═══════════════════════════════════════════
        Scan Level Selection
═══════════════════════════════════════════
1) Basic Scan
2) Intermediate Scan
3) Advanced Scan

[?] Choose scan level (1-3): 1
```

```
[?] Choose scan level (1-3): 1

[+] Selected scan level: basic

═══════════════════════════════════════════
         Network Scanning
═══════════════════════════════════════════

[*] Running Basic scan (-Pn)
Starting Nmap 7.95 ( https://nmap.org ) at 2026-01-28 14:15 EST
Nmap scan report for localhost (127.0.0.1)
Host is up (0.0000020s latency).
Not shown: 999 closed tcp ports (reset)
PORT   STATE SERVICE
22/tcp open  ssh

Nmap done: 1 IP address (1 host up) scanned in 0.08 seconds

[+] Scan completed
[+] Results saved to: results_2026-01-28_14-15/scan_results.txt

═══════════════════════════════════════════
         Enumeration Phase
═══════════════════════════════════════════
```





DOMAIN MAPPER – Project Explanation (ZX305)

This project demonstrates an automated **network security assessment workflow** implemented in Bash and executed in a Kali Linux environment.

The goal of the project is to simulate the typical phases of a network security assessment while maintaining a structured, safe, and educational approach.
The script follows a clear execution flow and does not perform uncontrolled exploitation.

Project Workflow

1. **Environment Setup**
   The script collects user input such as network range, domain name, optional Active

Directory credentials, and output directory configuration.

2. **Network Scanning**
   Based on the selected scan level (Basic / Intermediate / Advanced), the script performs network discovery using Nmap and saves the results to a dedicated output file.

3. **Enumeration Phase**
   The enumeration phase analyzes the scan results to identify open services and relevant information about the target hosts.

4. **Attack Simulation Phase**
   Attack techniques are simulated in a controlled and educational manner.
   No real exploitation is performed. This phase is intended to demonstrate awareness of common attack vectors rather than execute them.

5. **PDF Wrap / Reporting**
   All collected results are merged into a single report file.
   The final output demonstrates how security findings can be documented and prepared for reporting purposes.

Conclusion

This project highlights the importance of automation, structured workflows, and clear documentation in network security assessments.
All stages were executed successfully, and the results are stored in an organized results directory.