RoHS



VIEW A
SCALE 4/1



VIEW C
SCALE 4/1



VIEW D
SCALE 2/1





VIEW B
SCALE 4/1



Recommend PCB Layout(TOP VIEW)
Layout Tolerance:±0.05

NOTE
1.Material
Plunger: Brass
Barrel: Brass
Spring: SUS
Housing: PA46
2.Plating
Plunger: Au over NI
Barrel: Au over NI
3.Electrical
Rated current & voltage: DC 12V; 2.0A Max.
4.Mechanical
Spring force: 60g±20% at normal working height
Durability: 10,000 cycles(minimum)
5.To ensure the best usage,please operateit based on the working height Based on the engineering drawings,shall not exceed the maximum allowed compression
6.To avoid arcing issue, The adaptor startto power supply after connector mated fully.

ITEM NO.	DESCRIPTION	DRAWN	DATE

东莞市溪榜电子有限公司
DONG GUAN XI BANG ELECTRONI CS CO., LTD.

TOLERANCE UNLESS OTHERWISE STATED :		3RD. ANGEL'S	UNITS	MM
	Up to 5 ±0.2 Above 5 ~ 15 ±0.3 Above 15 ~ 30 ±0.4 Above 30 ~ 50 ±0.5 Angle ±0.3°			

DRAWN BY:	DATE	MAT'L	
Long. Liu. Ting	23. 4. 8		
CHECKED BY:	DATE	FINISH	
Lai. Hai. Jie	23. 4. 8		
APPROVED BY:	DATE	SCALE	1 : 1
He. Long. Fei	23. 4. 8	SHEET NO.	1 of 1

TITLE	CONNECTOR		
MODLE	POGO PIN		
DWG NO.	XB-PGC-CT-300G-4P-X	SIZE	A4
PART NO.	Magnetic PoGo Pin	VER	R