`fall_n` — Technical Documentation

Simplex Elements, Quadrature Theory,
Element Architecture, and Implementation Decisions

S. E. Echavarría-Montana

April 7, 2026

Abstract

This document provides a comprehensive technical reference for the `fall_n` nonlinear finite element library. It covers the implementation of simplex (tetrahedral) finite elements, numerical integration strategies on simplicial domains, the engineering decisions made to ensure robust post-processing, and the layered element architecture with its policy-based design patterns.

Key topics include:

- Lagrange shape functions on the reference simplex and their isoparametric mapping to physical space;
- Classical simplex quadrature rules and their negative-weight pathology;
- The Stroud conical product rule with Gauss–Jacobi nodes via the Golub–Welsch algorithm as an all-positive-weight alternative;
- Diagnosis and resolution of the checkerboard artefact in lumped L^2 projections on quadratic tetrahedra;
- Polynomial patch recovery as the production nodal reconstruction for higher-order simplex visualisation, with volume-weighted averaging kept as a conservative fallback;
- An adaptive material-field projection strategy that distinguishes between element families with strictly positive local lumping and those that require robust local reconstruction;
- The refactor of `ElementGeometry`: corrected value semantics, explicit quadrature strategy contracts, compile-time invariant enforcement, and preservation of runtime performance in the hot path;
- Serendipity tensor-product and simplex element families, including static reference cells, benchmark validation, VTK support, and Gmsh import paths for HEX20 and QUA8;
- A detailed ontology for the `Domain` refactor, separating geometry, mesh vertices, nodal unknown carriers, integration sites, constitutive points, and structural section entities under a compile-time-oriented HPC design philosophy;
- The first implementation phase of the `Domain` refactor: canonical `Vertex` storage, lazy PETSc mesh creation, transitional nodal caching, and geometry-only mesh export through vertices;
- The second implementation phase of the `Domain` refactor: geometry-only element binding through `Point/Vertex`, optional analysis-node binding, vertex-driven boundary extraction, and preservation of the compile-time/HPC characteristics of the element kernels;
- A new structural-scale reconstruction layer for beams and shells: constitutive section snapshots, formulation-specific reduction policies, compile-time section profiles, and a VTK multi-block export architecture that separates axis, surface, sections, material sites, and fibers;
- A quadrature-postprocessing clarification for VTK/ParaView: explicit nodal and quadrature tensor naming, scalar component export, and invariant filters such as von Mises, Beltrami–Haigh, pressure, triaxiality, and equivalent strain to avoid ambiguous rendering of raw Voigt arrays in quadrature-aware pipelines;
- A low-level performance pass on point, vertex, node, and element geometry access paths: contiguous coordinate access, direct DoF pointer access, cached coordinate pointers inside geometric elements, and removal of residual geometry-via-node usage in beam frame construction;
- A spatial-site and `Domain` laziness pass: a read-only geometry-site concept for point-like entities, explicit forwarding for constitutive and section decorators, and geometry-first boundary extraction without eager node-cache materialisation;

- A semantic hardening pass on `DMPlex`: mixed 1D/2D/3D cell families can now coexist in the same non-interpolated DAG through explicit point-role, topological-dimension, and physical-group labels, while the algebraic layout is driven by depth-0 vertices rather than brittle height-based assumptions;
- A full mixed-building demonstration in the executable entry point: first an elastic baseline, and then a materially nonlinear reinforced-concrete continuation with fiber sections in the frame, elastic MITC4 slabs, incremental SNES solution, and multi-block structural VTK export including fiber-level fields;
- A dedicated architectural audit of the materials module: semantic separation between physical materials, constitutive laws, integration algorithms, constitutive state carriers, and structural reduction policies, together with a roadmap toward nonlinear reinforced concrete across scales, finite kinematics, dynamics, and continuum-scale cracking/fracture;
- A constitutive-state storage cleanup: explicit committed-only, history-tracking, and trial/committed storage policies, with the default inelastic path moved away from implicit full kinematic history and toward semantically correct committed-state storage;
- A new semantic `ConstitutiveState` layer above the storage adapter: the local state of a constitutive site is now explicit in the API, while static polymorphism and configurable storage backends are preserved;
- An explicit `ConstitutiveIntegrator` layer at the erased `Material<Policy>` boundary: the local constitutive algorithm is now a first-class injection point, with legacy `ElasticUpdate` and `InelasticUpdate` retained as compatibility aliases;
- A first behavioural extraction of irreversible memory out of the law: `PlasticityRelation` now supports an explicit external algorithmic-state path, and `MaterialInstance` stores that state at the constitutive-site level while preserving the legacy embedded API for compatibility;
- The propagation of that explicit algorithmic-state contract to hysteretic uniaxial steel and concrete laws: `MenegottoPintoSteel` and `KentParkConcrete` now support external state objects, and fiber sections inherit the new behaviour automatically through the existing type-erased uniaxial-material layer;
- An explicit compile-time `YieldFunction` customization point in plasticity, separated from yield-surface geometry and hardening, plus a constitutive protocol sampler and VTK curve writer to generate strain–stress hysteresis loops for direct visual inspection of nonlinear materials;
- A further split between constitutive ingredients and the local nonlinear solve: `PlasticityRelation` now exposes a compile-time `ReturnAlgorithm` axis, so the scalar yield function and the return-mapping strategy can evolve independently;
- A further split inside the local plastic solve itself: the scalar consistency residual and its Jacobian are now independent compile-time customization points, so future constitutive models can keep a Newton solver while changing the local equation, or keep the local equation while changing the nonlinear solver;
- A general local constitutive-problem framework above that scalar path: local updates are now expressible as compile-time problems $R(x) = 0$ with reusable Newton solvers, making the current scalar consistency equation only a special case and preparing the route to finite-strain plasticity, damage, and other vector-valued local updates;
- A further internal split of Newton itself: the local linear solve and the step-control policy are now independent compile-time injection points, so Newton is no longer treated as a monolithic algorithm and future PETSc-based or research-oriented local solvers can attach to the same constitutive local-problem contract;
- A continuum-side constitutive carrier for large displacements and finite strains: the `ContinuumElement` /`Material<>` boundary no longer assumes that every continuum law sees only a flat Voigt strain vector, while remaining backward-compatible with the existing constitutive API,

and a spatial updated-Lagrangian route now exposes Almansi strain and Cauchy stress consistently through the same erased constitutive boundary;

- A bug fix in PETSc 3.24.5 `section.c` and application-level workarounds for PETSc indexing and preallocation issues;
- The element architecture design: External Polymorphism at the geometry and assembly levels, policy-based customisation points (MaterialPolicy, KinematicPolicy, ElementPolicy), compile-time efficiency, and comparison with OpenSees and Kratos Multiphysics;
- A complete step-by-step guide to building and running `fall_n` on Windows using the MSYS2 UCRT64 toolchain (GCC 15, CMake, Ninja) with all dependencies installed from the `pacman` binary repository, together with a detailed record of every platform-specific source and build-system change required.

Each chapter includes the relevant mathematical theory with bibliographic references, the concrete C++ implementation in `fall_n`, and a discussion of the design rationale.

Contents

1 Simplex Finite Elements **34**
1.1 Reference Simplex . . . 34
1.2 Lagrange Shape Functions . . . 34
1.2.1 Linear Elements (Order 1) . . . 34
1.2.2 Quadratic Elements (Order 2) . . . 35
1.3 Shape Function Derivatives . . . 35
1.4 Isoparametric Mapping . . . 35
1.5 Subentity Topology: Faces of the Simplex . . . 36
1.5.1 Face Local Node Ordering (TET10) . . . 36
1.6 Gmsh Node Ordering for TET10 . . . 36
1.7 Implementation in `fall_n` . . . 37

2 Numerical Quadrature on Simplices **38**
2.1 Problem Statement . . . 38
2.2 Classical Symmetric Rules . . . 38
2.2.1 Centroid Rule (Degree 1) . . . 38
2.2.2 Hammer–Marlowe–Stroud Rules (HMS) . . . 38
2.2.3 Keast Rules . . . 39
2.2.4 Grundmann–Möller Rules . . . 39
2.3 Stroud Conical Product Rule . . . 39
2.3.1 Duffy Transform . . . 40
2.3.2 Product Quadrature with Gauss–Jacobi Nodes . . . 40
2.3.3 Cost Comparison . . . 41
2.4 Gauss–Jacobi Quadrature via the Golub–Welsch Algorithm . . . 41
2.4.1 Jacobi Polynomials . . . 41
2.4.2 The Golub–Welsch Algorithm . . . 41
2.4.3 Mapping to $[0, 1]$ . . . 42
2.5 Implementation: `StroudConicalProduct.hh` . . . 42
2.6 Default Quadrature Choices in `fall_n` . . . 43

3 Negative Weights and the Checkerboard Artefact **44**
3.1 Symptom: Element-Level Checkerboard Pattern . . . 44
3.2 Root Cause Analysis . . . 44
3.2.1 The Keast 5-Point Rule Weights . . . 45
3.2.2 TET10 Vertex Shape Functions at Quadrature Points . . . 45
3.2.3 The Denominator Catastrophe . . . 45
3.2.4 Consequence: Sign Flip or Division by Zero . . . 46
3.3 Why HEX27 Is Unaffected . . . 46
3.4 Resolution: Two Complementary Fixes . . . 46
3.4.1 Fix 1: Switch to an All-Positive-Weight Quadrature Rule . . . 46
3.4.2 Fix 2: Guard Against Negative Denominators . . . 46

3.4.3 Fix 3 (Recommended): SPR Volume-Weighted Averaging . . . 47
3.5 Summary . . . 47

4 Gauss-Point to Nodal Projection **48**
4.1 Lumped L^2 Projection . . . 48
4.1.1 Consistent L^2 Projection . . . 48
4.1.2 Row-Sum Lumping . . . 48
4.2 Polynomial Patch Recovery . . . 49
4.2.1 Motivation . . . 49
4.2.2 Patch Definition . . . 49
4.2.3 Local Polynomial Basis . . . 49
4.2.4 Weighted Least Squares . . . 49
4.2.5 Adaptive Degree Fallback . . . 50
4.2.6 Evaluation at the Node . . . 50
4.3 Volume-Weighted Averaging . . . 50
4.4 Implementation in `VTKModelExporter` . . . 50
4.5 Comparison of the Three Operators . . . 51
4.6 Verification . . . 51
4.6.1 Algebraic regression . . . 51
4.6.2 Application-level behaviour . . . 52

5 PETSc Patch: `section.c` Indexing Bug **53**
5.1 Context: DMPlex and PetscSection . . . 53
5.2 The Bug . . . 53
5.3 Manifestation in `fall_n` . . . 54
5.4 The Fix . . . 54
5.5 Verification . . . 54
5.6 Upstream Status . . . 54
5.7 Workaround from Application Code . . . 55
5.7.1 Workaround 1: Extend the Section Chart . . . 55
5.7.2 Workaround 2: Allow Dynamic Matrix Allocation . . . 55
5.7.3 Verification . . . 56

6 Implementation Summary and Design Decisions **57**
6.1 Architecture Overview . . . 57
6.2 Design Decisions . . . 57
6.2.1 Decision 1: HMS 4-Point as Default TET10 Quadrature . . . 57
6.2.2 Decision 2: Golub–Welsch for Gauss–Jacobi Quadrature . . . 58
6.2.3 Decision 3: Adaptive Projection as Default . . . 58
6.2.4 Decision 4: Gmsh TET10 Node Reordering . . . 59
6.2.5 Decision 5: PETSc Section Patch . . . 59
6.2.6 Decision 6: Hex27 VTK Face-Center Ordering . . . 59
6.2.7 Decision 7: Split VTK Export as the Supported Contract . . . 60
6.2.8 Decision 8: Explicit Scalar Filters over Raw Voigt Arrays in ParaView . . . 60
6.3 Nonlinear Showcase (`main.cpp`) . . . 61
6.4 Test Suite . . . 61
6.5 File Inventory . . . 62

7 Element Architecture: Design Patterns and Extensibility **63**
7.1 Guiding Principles . . . 63
7.2 Layer Decomposition . . . 63
7.2.1 Layer 1: Concrete Geometry Types . . . 64
7.2.2 Layer 2: ElementGeometry (Type-Erased Handle) . . . 64
7.2.3 Layer 3: Physical Elements . . . 66
7.2.4 Layer 4: Analysis Level . . . 66
7.3 FEM_Element: Top-Level Type Erasure . . . 66
7.4 Policy-Based Design: Customisation Points . . . 67
7.4.1 MaterialPolicy . . . 67
7.4.2 KinematicPolicy . . . 67
7.4.3 ElementPolicy (Storage Strategy) . . . 68
7.4.4 AssemblyPolicy (Beams) . . . 68
7.4.5 ConstitutiveStrategy (Material Update) . . . 69
7.5 Compile-Time Cost Analysis . . . 69
7.6 Comparison with OpenSees and Kratos . . . 70
7.6.1 Overview . . . 70
7.6.2 OpenSees . . . 70
7.6.3 Kratos Multiphysics . . . 71
7.6.4 Summary: Architectural Trade-offs . . . 71
7.7 Extensibility Guide: Adding a New Element Family . . . 72
7.8 Runtime Efficiency Considerations . . . 73
7.8.1 Virtual Dispatch Budget . . . 73
7.8.2 Cache-Friendly Layout . . . 73
7.8.3 DOF Index Caching . . . 73
7.8.4 Stack-Allocated Jacobians . . . 73

8 Generic Boundary and Initial Condition Infrastructure **74**
8.1 Gap Analysis: the Legacy API . . . 74
8.2 Design Decisions and Trade-offs . . . 74
8.2.1 Compile-Time Polymorphism via Concepts . . . 74
8.2.2 Constraint Storage: Extending the Existing Map . . . 75
8.2.3 Non-Zero Dirichlet: Where Values Flow . . . 76
8.2.4 ModelState: Platform-Independent Snapshot . . . 76
8.3 Implementation . . . 76
8.3.1 NodeSelector.hh — Built-in Selectors . . . 76
8.3.2 Model.hh — New Constraint Methods . . . 77
8.3.3 Backward Compatibility . . . 77
8.4 Use-Case Walkthrough: Roller vs. Clamped Cantilever . . . 77
8.5 State Capture and Continuation Analysis . . . 78
8.5.1 ModelState Structure . . . 78
8.5.2 Capture Workflow . . . 79
8.5.3 Future: Initial Stress Integration . . . 79
8.6 Comparison with OpenSees and Kratos . . . 79
8.7 Extensibility Roadmap . . . 80
8.8 Test Suite . . . 80
8.9 Summary . . . 81

9 ElementGeometry Refactor **82**
9.1 Problem Statement . . . 82
9.1.1 Broken value semantics . . . 82
9.1.2 Integration strategy mixed into concrete geometry headers . . . 82
9.1.3 Weak compile-time invariants . . . 82
9.2 Design Goals . . . 83
9.3 Refactor Overview . . . 83
9.3.1 Metadata moved under wrapper ownership . . . 83
9.3.2 Quadrature strategies extracted to dedicated headers . . . 83
9.3.3 A small quadrature concept . . . 84
9.4 Geometry and Measure . . . 84
9.5 API Hardening . . . 84
9.5.1 Restricting `detJ()` . . . 84
9.5.2 Fail-fast Gauss–Legendre tables . . . 84
9.5.3 Safer tensor-product constraints . . . 84
9.6 Materialised Integration Points . . . 85
9.7 Performance Discussion . . . 85
9.7.1 What did not change . . . 85
9.7.2 What did change . . . 85
9.8 What Was Deliberately Deferred . . . 85
9.9 Result . . . 85

10 Serendipity Element Families **87**
10.1 Why Serendipity? . . . 87
10.2 Mathematical Structure . . . 87
10.2.1 Tensor-product serendipity on the cube . . . 87
10.2.2 Why the tetrahedral “serendipity” family is different . . . 88
10.3 Implementation Structure . . . 88
10.3.1 Reference cells . . . 88
10.3.2 Concrete geometry . . . 89
10.3.3 ElementGeometry integration . . . 89
10.3.4 Quadrature choices . . . 89
10.4 VTK and Gmsh Support . . . 89
10.4.1 VTK . . . 89
10.4.2 Gmsh . . . 89
10.5 Validation Tests . . . 90
10.6 Benchmark Results . . . 90
10.7 Architectural Takeaways . . . 90
10.8 Future Work . . . 91

11 Domain Refactor Ontology **92**
11.1 Architectural Diagnosis . . . 92
11.2 Entity-by-Entity Semantics . . . 93
11.2.1 `Point<Dim>` . . . 93
11.2.2 `Vertex<Dim>` (proposed and introduced in this step) . . . 93
11.2.3 `Node<Dim, Storage>` . . . 93
11.2.4 `IntegrationPoint<dim>` . . . 94
11.2.5 `MaterialPoint<MaterialPolicy>` . . . 94
11.2.6 `SectionGeometry` . . . 94
11.2.7 `NodeSection<Dim, Geom>` . . . 95
11.2.8 `MaterialSection<MaterialPolicy>` . . . 95
11.2.9 `PetscSection` . . . 95

11.3 Coincidence Versus Identity . . . 95
11.3.1 Case 1: Gauss–Lobatto beam quadrature . . . 96
11.3.2 Case 2: mixed or assumed-strain formulations . . . 96
11.4 Proposed Ontology for the Refactor . . . 96
11.4.1 Layer 0: pure geometry/topology . . . 96
11.4.2 Layer 1: discrete field attachment . . . 97
11.4.3 Layer 2: sampling and constitutive sites . . . 97
11.4.4 Layer 3: structural section semantics . . . 97
11.5 Implications for `Domain` . . . 97
11.6 HPC and Compile-Time Guidance . . . 98
11.6.1 Prefer static structure in hot paths . . . 98
11.6.2 Keep `Domain` simple, not hyper-generic . . . 98
11.6.3 Avoid type collapse when roles overlap . . . 98
11.6.4 Recommended storage philosophy . . . 98
11.7 Migration Plan . . . 98
11.8 Conclusion . . . 99

12 Domain Vertex Transition **100**
12.1 Motivation . . . 100
12.2 Implemented Transition Design . . . 100
12.2.1 Canonical storage . . . 100
12.2.2 Node cache . . . 101
12.2.3 Cache invalidation rule . . . 101
12.3 Why This Preserves Performance . . . 101
12.3.1 No change to element hot loops . . . 101
12.3.2 Geometry-only consumers stop depending on nodes . . . 101
12.3.3 PETSc creation is now lazy . . . 102
12.4 Code-Level Changes . . . 102
12.5 What Remains Transitional . . . 102
12.6 Validation . . . 102
12.6.1 Domain/Vertex refactor test . . . 102
12.6.2 Regression coverage . . . 103
12.7 Architectural Consequences . . . 103
12.8 Next Step . . . 103
12.9 Conclusion . . . 103

13 Geometry-Only Element Binding **104**
13.1 Context . . . 104
13.2 Problem Statement . . . 104
13.3 Design Objective . . . 104
13.4 Implemented Refactor . . . 105
13.4.1 New dual binding inside concrete elements . . . 105
13.4.2 Wrapper-level support in `ElementGeometry` . . . 105
13.4.3 Key compatibility rule . . . 105
13.5 Domain-Level Consequences . . . 105
13.5.1 Geometry-first linking . . . 105
13.5.2 Boundary extraction no longer needs `node_p().id()` . . . 106
13.5.3 Sieve assembly remains analysis-oriented . . . 106
13.6 Why this is efficient . . . 106
13.6.1 No new runtime polymorphism in the hot path . . . 106
13.6.2 Compile-time impact . . . 106
13.7 Validation . . . 107

13.8 Architectural Interpretation . . . 107
13.9 Next Step . . . 107

14 Low-Level Geometry and DoF Access **108**
14.1 Motivation . . . 108
14.2 `Point<Dim>` as a contiguous data source . . . 108
14.2.1 Previous state . . . 108
14.2.2 Implemented change . . . 108
14.2.3 Why this matters . . . 108
14.3 `Node<Dim, Storage>` and direct DoF access . . . 109
14.3.1 Added direct pointer interface . . . 109
14.3.2 Array constructors . . . 109
14.4 Cached coordinate pointers inside geometric elements . . . 109
14.4.1 Problem . . . 109
14.4.2 Implemented solution . . . 109
14.4.3 Why this is safe . . . 110
14.5 Residual geometry-via-node usage in beam elements . . . 110
14.5.1 Observation . . . 110
14.5.2 Implemented change . . . 110
14.6 Validation and traceability . . . 110
14.7 Interpretation . . . 110

15 Spatial Sites and Lazy Domain Materialisation **111**
15.1 Scope of this pass . . . 111
15.2 The problem of overlapping point-like concepts . . . 111
15.3 A static ontology of spatial sites . . . 111
15.3.1 Read-only coordinate site: `PointViewT` . . . 111
15.3.2 Mutable point: `PointT` . . . 112
15.3.3 Entity-by-entity interpretation . . . 112
15.4 Why forwarding is the right model . . . 112
15.4.1 Material points and sections . . . 112
15.4.2 Node sections . . . 112
15.5 Lazy node materialisation in `Domain` . . . 113
15.5.1 Geometric operations should not force analysis state . . . 113
15.5.2 Implemented fix . . . 113
15.5.3 Why the node cache still exists . . . 113
15.6 Data-layout implications for HPC . . . 113
15.6.1 Owned storage vs forwarded storage . . . 113
15.6.2 Why no generic runtime interface was added . . . 114
15.7 What this means for overlapping formulations . . . 114
15.8 Validation . . . 114
15.9 Interpretation . . . 114

16 Adaptive Nodal Projection for Material Fields **115**
16.1 Why the Previous Diagnosis Was Incomplete . . . 115
16.2 Exact Row-Sum Lumping for TET10 . . . 115
16.2.1 Vertex nodes . . . 116
16.2.2 Edge-midpoint nodes . . . 116
16.3 Consequence: Lumped L^2 Is Not a Nodal Average . . . 116
16.4 Why HEX27 Remains Safe . . . 116
16.5 Adaptive Policy Implemented in `VTKModelExporter` . . . 117
16.6 Code-Level Traceability . . . 117

16.7 Verification . . . 118

17 Polynomial Patch Recovery for TET10 Visualisation 119
17.1 Why Averaging Was Not Enough . . . 119
17.2 Recovered Quantity and Patch Topology . . . 119
17.3 Centered and Scaled Basis . . . 120
17.4 Least-Squares System . . . 120
17.5 Rank-Adaptive Fallback . . . 120
17.6 Implementation Choices and HPC Considerations . . . 121
17.7 Regression Coverage . . . 121
17.8 Architectural Outcome . . . 121

18 Explicit Tensor Filters for VTK / ParaView 122
18.1 Naming Contract . . . 122
18.2 Stress Filters . . . 122
18.3 Strain Filters . . . 123
18.4 Why the Exporter Owns These Scalars . . . 123
18.5 Recommended ParaView Usage . . . 124

19 VTK Export Cleanup 125
19.1 Retained Responsibilities . . . 125
19.2 Removed Complexity . . . 125
19.3 Why the Split Export Is the Right Current Boundary . . . 125
19.4 Compile-Time and Dependency Impact . . . 126
19.5 Retained Extension Points . . . 126

20 Structural Scale Reconstruction and Multi-Block VTK Export 127
20.1 Motivation . . . 127
20.2 Architectural Split . . . 127
20.3 Spatial Roles and Ontology . . . 128
20.4 Constitutive Snapshots . . . 128
20.4.1 Beam Snapshot . . . 128
20.4.2 Shell Snapshot . . . 129
20.4.3 Fiber Snapshot . . . 129
20.5 Reduction Policies . . . 129
20.5.1 Why Policies and Not VTK-Specific Code . . . 129
20.5.2 3D Timoshenko Beam . . . 130
20.5.3 MITC4 Mindlin Shell . . . 130
20.6 Compile-Time and HPC Considerations . . . 130
20.7 Section Profiles . . . 131
20.7.1 Beam Profiles . . . 131
20.7.2 Shell Thickness Profile . . . 131
20.8 The Multi-Block `.vtm` Contract . . . 131
20.8.1 Executable Examples . . . 132
20.8.2 A Note on Empty Trailing Blocks . . . 132
20.9 Testing Strategy . . . 132
20.10 Limitations and Future Work . . . 132

21 Mixed Structural Table Example **134**
21.1 Purpose . . . 134
21.2 Physical Model . . . 134
21.2.1 Geometry . . . 134
21.2.2 Sections and Materials . . . 135
21.3 Loads and Boundary Conditions . . . 135
21.4 Architectural Realisation . . . 136
21.4.1 Why the Domain Contains Only the Slab . . . 136
21.4.2 Polymorphic Structural Container . . . 136
21.5 Quadrature Contract for `TimoshenkoBeamN` . . . 136
21.6 VTK Output . . . 137
21.7 Observed Structural Response . . . 137
21.8 Code Path . . . 138

22 Robustifying `DMPlex` for Naturally Mixed Element Families **139**
22.1 Motivation . . . 139
22.2 Design Decision . . . 139
22.3 Implemented Semantics . . . 139
22.4 Why `Depth` and Not `Height` . . . 140
22.5 Dimension of the `DMPlex` . . . 140
22.6 Compile-Time and HPC Considerations . . . 140
22.7 Validation . . . 141
22.8 Current Scope and Next Step . . . 141

23 Regular 5-Story Building Example **142**
23.1 Purpose . . . 142
23.2 Unit System . . . 142
23.3 Geometry . . . 143
23.3.1 Plan and height . . . 143
23.3.2 Discretisation . . . 143
23.4 Sections and Materials . . . 143
23.4.1 Columns . . . 143
23.4.2 Beams . . . 144
23.4.3 Slabs . . . 144
23.5 Loads and Boundary Conditions . . . 144
23.5.1 Boundary conditions . . . 144
23.5.2 Gravity loading . . . 144
23.5.3 Horizontal loading . . . 145
23.6 Architectural Realisation in Code . . . 145
23.6.1 One shared `Domain` . . . 145
23.6.2 Polymorphic structural container . . . 145
23.6.3 Why this example is a good architectural integrator . . . 146
23.7 Execution Results . . . 146
23.8 VTK Output . . . 147
23.9 Why the Example Matters . . . 147

24 Nonlinear Reinforced-Concrete 5-Story Building Example **148**
24.1 Purpose and Scope . . . 148
24.2 Unit System . . . 148
24.3 Geometry and Topology . . . 149
24.3.1 Plan and elevations . . . 149
24.3.2 Mixed structural topology . . . 149

24.4 Constitutive Design . . . 149
24.4.1 Columns . . . 149
24.4.2 Beams . . . 150
24.4.3 Slabs . . . 150
24.5 Why Fibers Belong in the Constitutive Layer . . . 150
24.6 Section Kinematics and Fiber Stress Recovery . . . 151
24.7 Global Solution Strategy . . . 151
24.7.1 Analysis-layer hardening . . . 151
24.8 Loads and Boundary Conditions . . . 152
24.9 Results of the Executed Example . . . 152
24.10 VTK Output . . . 152
24.11 Regression and Verification . . . 153
24.12 Current Limits and Next Steps . . . 153

25 Material Module Architecture Analysis 154
25.1 Purpose . . . 154
25.2 Current Architectural Layers . . . 154
25.2.1 Measure spaces . . . 154
25.2.2 Relation classes . . . 155
25.2.3 Material instance and type erasure . . . 155
25.2.4 Constitutive sites . . . 155
25.3 What is Good and Should Be Preserved . . . 156
25.3.1 The measure-based generic contract . . . 156
25.3.2 Static polymorphism at the relation level . . . 156
25.3.3 Separation between geometry and constitutive sites . . . 156
25.3.4 The reduction-based path for structural elements . . . 156
25.4 Observed Semantic Inconsistencies . . . 156
25.4.1 The word `Material` currently means too many things . . . 156
25.4.2 `MaterialPolicy` is not a material . . . 157
25.4.3 `MaterialInstance` is not just a material instance . . . 157
25.4.4 Inelastic relations already contain the integration algorithm . . . 157
25.4.5 The constitutive relation and its committed state are fused . . . 158
25.4.6 The kinematic state is duplicated and over-recorded . . . 158
25.4.7 The flyweight story is currently contradictory . . . 158
25.4.8 Section laws are currently mixed with material laws . . . 159
25.4.9 Post-processing adapters are embedded in the core wrapper . . . 159
25.4.10 Finite-strain constitutive models live outside the material module . . . 159
25.5 Performance Implications . . . 159
25.5.1 Per-fiber type erasure is expensive . . . 159
25.5.2 The default inelastic storage is not HPC-friendly . . . 160
25.5.3 The hot path should remain statically typed . . . 160
25.6 A Cleaner Separation: Material vs Constitutive Relation . . . 160
25.6.1 Recommended ontology . . . 160
25.6.2 What should be called “material” . . . 160
25.6.3 What should be called “constitutive law” . . . 161
25.6.4 What should be called “reduction policy” . . . 161
25.7 A More Scalable Constitutive Contract . . . 161
25.7.1 Constitutive context . . . 161
25.7.2 Suggested compile-time split . . . 161
25.8 Implications for Reinforced Concrete Across Scales . . . 162
25.8.1 Uniaxial constituent scale . . . 162
25.8.2 Layered shells . . . 162

25.8.3 Continuum RC with cracking and fracture . . . 162
25.8.4 Large displacements and dynamics . . . 163
25.9 Suggested Refactor Path . . . 163
25.9.1 Stage 1: semantic cleanup . . . 163
25.9.2 Stage 2: state redesign . . . 163
25.9.3 Stage 3: genuine algorithm-law separation . . . 163
25.9.4 Stage 4: typed hot path, erased boundary . . . 164
25.9.5 Stage 5: RC multiscale and fracture . . . 164
25.10 Non-owning Type Erasure in `Material.hh` . . . 164
25.10.1 Viability assessment . . . 164
25.10.2 What problem it solves . . . 164
25.10.3 What problem it does not solve . . . 165
25.10.4 Why the strategy belongs in `Material.hh` . . . 165
25.10.5 Refactor adopted in the current code . . . 165
25.10.6 Architectural consequence . . . 165
25.11 Final Opinion . . . 166

26 Material Module Semantic Cleanup 167
26.1 Purpose . . . 167
26.2 What Was Changed . . . 167
26.2.1 Constitutive-space aliases . . . 167
26.2.2 Stateful constitutive-site aliases . . . 168
26.2.3 Erased constitutive handles . . . 168
26.2.4 Constitutive-site accessors . . . 168
26.3 Ownership Semantics Clarified . . . 168
26.4 Why This Stage Matters . . . 169
26.5 What Was Intentionally Not Changed . . . 169
26.6 Immediate Benefits . . . 169
26.7 Next Step . . . 169

27 Constitutive State Storage Cleanup 170
27.1 Motivation . . . 170
27.2 Storage Roles . . . 170
27.2.1 CommittedState . . . 170
27.2.2 HistoryState . . . 171
27.2.3 TrialCommittedState . . . 171
27.3 MaterialState as a Storage Adapter . . . 171
27.4 Change in the Default Inelastic Path . . . 172
27.5 Interaction with Constitutive Updates . . . 172
27.6 Why This Matters for Reinforced Concrete Across Scales . . . 173
27.7 Next Refactor Stage . . . 173

28 ConstitutiveState as a Semantic Layer 174
28.1 Why Another Layer Was Needed . . . 174
28.2 Layered View . . . 174
28.3 What ConstitutiveState Adds . . . 174
28.4 Effect on MaterialInstance . . . 175
28.5 Why This Matters for Future Nonlinear Algorithms . . . 175
28.6 Static Polymorphism Is Preserved . . . 176
28.7 What This Refactor Still Does Not Do . . . 176
28.8 Immediate Consequence . . . 176

29 ConstitutiveIntegrator as the Algorithmic Injection Point **177**
29.1 Motivation . . . 177
29.2 Local Architectural Split . . . 177
29.3 Why the Injection Point Stays in `Material<Policy>` . . . 177
29.4 Current Concrete Integrators . . . 178
29.5 Why This Matters . . . 178
29.6 Custom Integrators . . . 179
29.7 What Has Not Been Completed Yet . . . 179
29.8 Immediate Architectural Interpretation . . . 179

30 Explicit Algorithmic State in `PlasticityRelation` **180**
30.1 Why This Step Matters . . . 180
30.2 Old Situation . . . 180
30.3 New Explicit-State Contract . . . 180
30.4 Compatibility Is Preserved . . . 181
30.5 What Changed Internally . . . 181
30.6 Interaction with `MaterialInstance` . . . 181
30.7 Interaction with `ConstitutiveIntegrator` . . . 182
30.8 What the New Tests Prove . . . 182
30.9 Why the Cache Was Not Reused . . . 182
30.10 Current Boundary of the Refactor . . . 182
30.11 Next Logical Step . . . 183

31 Explicit Algorithmic State in Uniaxial Steel and Concrete Laws **184**
31.1 Why This Step Follows Naturally . . . 184
31.2 Semantic Improvement . . . 184
31.3 New Contract . . . 184
31.4 Menegotto–Pinto Steel . . . 185
31.5 Kent–Park Concrete . . . 185
31.6 Why `FiberSection` Did Not Need a New API . . . 186
31.7 What the New Tests Prove . . . 186
31.8 Architectural Consequences . . . 186
31.9 What Still Remains to Be Done . . . 186
31.10 Strategic Importance for Reinforced Concrete Across Scales . . . 187

32 Yield Function Customization and Constitutive Curve Visualisation **188**
32.1 Why Introduce an Explicit Yield Function? . . . 188
32.2 Criterion vs Function . . . 188
32.3 New Compile-Time Contract . . . 189
32.4 How `PlasticityRelation` Uses It . . . 189
32.5 Important Current Limitation . . . 189
32.6 Why This Separation Helps . . . 190
32.7 Constitutive Protocol Sampling . . . 190
32.8 Why the Protocol Is Strain-Driven . . . 190
32.9 VTK Representation of Material Curves . . . 191
32.10 Curves Generated by the New Test . . . 191
32.11 What the New Tests Actually Verify . . . 192
32.12 Relevance for Reinforced Concrete . . . 192
32.13 Strategic Next Step . . . 192

33 Decoupling the Yield Function from the Return Algorithm 193
33.1 Motivation . . . 193
33.2 New Separation . . . 193
33.3 What Remains Inside `PlasticityRelation` . . . 194
33.4 Kernel API for Algorithms . . . 194
33.5 Default Algorithm . . . 195
33.6 What the New Test Demonstrates . . . 195
33.7 Why This Matters for Future Material Models . . . 195
33.8 Immediate Boundary . . . 196
33.9 Recommended Next Step . . . 196

34 Continuum Module Cleanup and the Finite-Strain Constitutive Interface 197
34.1 Motivation . . . 197
34.2 Problem Statement . . . 197
34.3 New Carrier: `ConstitutiveKinematics` . . . 198
34.4 Mapping from Kinematic Policies . . . 198
34.5 Optional Direct Continuum Interface . . . 199
34.6 Hyperelastic Relations . . . 199
34.7 Changes in `ContinuumElement` . . . 199
34.8 Compile-Time and Performance Considerations . . . 200
34.9 Limitations After This Step . . . 200
34.10 Tests Added . . . 200
34.11 Architectural Outcome . . . 200

35 Spatial Updated-Lagrangian Constitutive Interface 202
35.1 Motivation . . . 202
35.2 Reference and Spatial Conjugate Pairs . . . 202
35.3 Why the Spatial Carrier Matters . . . 203
35.4 Updated-Lagrangian Carrier . . . 203
35.5 Push-Forward of the Constitutive Tangent . . . 203
35.6 Element-Level Updated-Lagrangian Assembly . . . 204
35.7 Architectural Consequences . . . 204
35.8 Tests Added . . . 204
35.9 Remaining Limits . . . 205
35.10 References . . . 205

36 Local Consistency Residual and Jacobian as Independent Customization Points 207
36.1 Motivation . . . 207
36.2 Classical Local Plasticity Problem . . . 207
36.3 Architectural Split . . . 208
36.4 Default Residual . . . 208
36.5 Default Jacobians . . . 208
36.6 Newton Consistency Algorithm . . . 209
36.7 Why This Matters for Finite Strains . . . 209
36.8 Verification . . . 210
36.9 Architectural Outcome . . . 210
36.10 References . . . 210

37 A Generic Local Nonlinear Problem Framework for Constitutive Updates 212
37.1 Motivation . . . 212
37.2 Architectural Split . . . 213
37.2.1 Local Problem Contract . . . 213
37.2.2 Generic Newton Solver . . . 213
37.2.3 Scalar Consistency as an Adapter . . . 213
37.3 Return Mapping as a Specialization of the General Framework . . . 214
37.4 Why This Matters for Large Displacements and Finite Strains . . . 214
37.5 Verification . . . 215
37.6 Strategic Outcome . . . 215
37.7 References . . . 215

38 Splitting Newton into Linear-Solve and Step-Control Policies 217
38.1 Motivation . . . 217
38.2 Architectural Split . . . 217
38.2.1 Local Linear Solve Policy . . . 217
38.2.2 Local Step-Control Policy . . . 218
38.3 Newton as an Assembler of Policies . . . 218
38.4 Why This Matters for Continuum Inelasticity at Finite Strains . . . 218
38.5 PETSc Compatibility Path . . . 219
38.6 Verification . . . 219
38.7 Strategic Outcome . . . 219
38.8 References . . . 219

39 Continuum Local Problems Driven by Constitutive Kinematics 221
39.1 Motivation . . . 221
39.2 Context and Result Carriers . . . 221
39.2.1 Continuum Context . . . 222
39.2.2 Continuum Update Result . . . 222
39.3 Continuum Local Problem Policy . . . 222
39.4 Continuum Local Integration Algorithm . . . 223
39.5 Why This Matters for Finite Strains . . . 223
39.6 Verification Strategy . . . 224
39.7 Strategic Outcome . . . 224
39.8 References . . . 225

40 Integrating Continuum Local Problems at the Material Boundary 227
40.1 Motivation . . . 227
40.2 Architectural Position . . . 227
40.3 Prediction and Commit Semantics . . . 228
40.4 Mathematical Role of the Boundary Integrator . . . 228
40.5 Compile-Time Extension Points Preserved . . . 229
40.6 Verification . . . 229
40.7 References . . . 229

41 First Real Finite-Strain Inelastic Continuum Law 231
41.1 Motivation . . . 231
41.2 Constitutive Structure . . . 231
41.3 Driving Variable and History Variable . . . 232
41.4 Local Constitutive Problem . . . 232
41.5 Compile-Time Extension Points . . . 233
41.6 Reference and Spatial Paths . . . 233

41.7 Integration at the Material Boundary . . . 233
41.8 Tests Added . . . 234
41.9 What This Enables Next . . . 234
41.10 References . . . 234

42 Stabilising the Finite-Strain Damage Route 236
42.1 Motivation . . . 236
42.2 State and Local Unknown . . . 236
42.3 Vector Local Problem . . . 236
42.4 Consistent Tangent During Active Damage Loading . . . 237
42.5 Driving-Force Gradient . . . 237
42.6 Compile-Time Extension Points . . . 238
42.7 Verification Performed . . . 238
42.8 What Remains Open . . . 238
42.9 References . . . 239

43 Convergence Master Plan: Closing the Design-Implementation Gap 241
43.1 Risk Assessment . . . 241
43.2 Phase 0 — PETSc RAII and Error Discipline . . . 241
43.3 Phase 1 — Constitutive State Protocol . . . 242
43.4 Phase 2 — Element Contract and Heterogeneous Containers . . . 242
43.5 Phase 3 — Newton–Raphson Protocol in Model . . . 242
43.6 Phase 4 — Finite-Strain Kinematics . . . 243
43.7 Phase 5 — Dynamic and Seismic Infrastructure . . . 243
43.8 Phase 6 — MPI Scalability . . . 243
43.9 Summary and Dependency Graph . . . 244

44 Phase 0: PETSc RAII and Error Discipline 245
44.1 Motivation . . . 245
44.2 Design: Thin Wrappers with Implicit Conversion . . . 245
44.2.1 Invariants . . . 245
44.2.2 Interface (abridged) . . . 246
44.2.3 Full Wrapper Set . . . 247
44.3 Error Checking Macro . . . 247
44.4 Refactored Classes . . . 247
44.4.1 Model . . . 247
44.4.2 LinearAnalysis . . . 248
44.4.3 NonlinearAnalysis . . . 248
44.4.4 DynamicAnalysis . . . 248
44.5 File Layout . . . 248
44.6 Validation Criteria . . . 249

45 Phase 1: Constitutive State Protocol 250
45.1 Phase 1 Scope Revision . . . 250
45.2 Mathematical Framework . . . 250
45.2.1 Trial/Committed State Protocol . . . 250
45.2.2 Constitutive Tangent in the Newton System . . . 251
45.3 The Complete Commit Chain . . . 251
45.3.1 Layer 1: Storage Policy . . . 252
45.3.2 Layer 2: Constitutive State . . . 252
45.3.3 Layer 3: Constitutive Integrator . . . 252
45.3.4 Layer 4: Type-Erased Material Handle . . . 253

45.3.5 Layer 5: Finite Element . . . 253
45.3.6 Layer 6: Analysis (Solver Boundary) . . . 254
45.4 Audit Summary: Existing Constitutive Models . . . 255
45.4.1 Elastic Path . . . 255
45.4.2 J_2 Plasticity . . . 255
45.4.3 Hyperelastic Models . . . 256
45.4.4 Fiber Section Models . . . 256
45.4.5 Finite Strain Damage . . . 256
45.5 Verification: End-to-End Commit Chain Test . . . 256
45.6 Remaining Gaps for Future Phases . . . 257
45.7 Architectural Diagram: Commit Chain . . . 257
45.8 Conclusions . . . 258

46 Phase 2: Element Contract and Heterogeneous Containers 259
46.1 Phase 2 Scope Revision . . . 259
46.2 The Element Contract . . . 260
46.2.1 Formal State Semantics . . . 260
46.3 External Polymorphism: Type-Erased Wrappers . . . 261
46.3.1 FEM_Element . . . 261
46.3.2 StructuralElement . . . 261
46.4 Element Storage Policies . . . 262
46.5 Model Constructors . . . 262
46.6 The Revert Chain . . . 263
46.6.1 Architectural Layers . . . 263
46.6.2 Layer-by-Layer Trace . . . 263
46.6.3 Free Functions . . . 264
46.7 Files Modified . . . 265
46.8 Verification Test . . . 265
46.9 Known Gaps . . . 266
46.10 Build and Test Results . . . 266
46.11 Summary . . . 267

47 Phase 3: Newton–Raphson Protocol in Model 268
47.1 Phase 3 Scope Revision . . . 268
47.2 Explicit Revert on Divergence . . . 269
47.3 Step Callback . . . 269
47.4 NonlinearAnalysis Architecture Summary . . . 270
47.5 Vertical-Slice Gate Test . . . 270
47.5.1 Material and Loading Parameters . . . 271
47.5.2 Test Groups . . . 271
47.6 Results . . . 272
47.7 Phase 3 Completion Status . . . 272

48 Phase 4: Finite-Strain Kinematics and Hysteretic Cycling 273
48.1 Phase 4 Scope Revision . . . 273
48.2 Finite-Strain Infrastructure Summary . . . 274
48.2.1 Kinematic Policies . . . 274
48.2.2 Deformation Gradient . . . 274
48.2.3 Strain and Stress Measures . . . 274
48.2.4 Hyperelastic Models . . . 274
48.2.5 Geometric Stiffness . . . 274
48.3 Cyclic Constitutive Model Verification . . . 275

48.3.1 Menegotto–Pinto Steel . . . 275
48.3.2 Kent–Park Concrete . . . 275
48.3.3 J_2 Plasticity (Uniaxial) . . . 275
48.3.4 Commit/Revert Protocol . . . 276
48.3.5 Combined Output . . . 276
48.3.6 Finite-Strain Gate . . . 276
48.4 CSV Output and Hysteresis Plotting . . . 276
48.5 Results . . . 277
48.6 Phase 4 Completion Status . . . 277

49 Phase 5: Dynamic and Seismic Analysis Verification 278
49.1 Phase 5 Scope and Audit . . . 278
49.2 DynamicAnalysis Architecture . . . 279
49.3 Verification Campaign . . . 279
49.3.1 Test 1: Free Vibration Period . . . 280
49.3.2 Test 2: Undamped Amplitude Conservation . . . 280
49.3.3 Test 3: Rayleigh Damping Decay . . . 280
49.3.4 Test 4: Damping Factories . . . 280
49.3.5 Test 5: Ground Motion Seismic Input . . . 280
49.3.6 Test 6: Multi-Directional Ground Motion . . . 280
49.3.7 Test 7: Forced Vibration with CSV Output . . . 280
49.3.8 Test 8: J_2 Plasticity Dynamic . . . 280
49.3.9 Test 9: Spectral Radius Comparison . . . 281
49.4 Full Regression Status . . . 281
49.5 Summary . . . 281

50 Phase 6: MPI Scalability Audit 282
50.1 Phase 6 Scope and Audit . . . 282
50.2 Communicator Audit . . . 282
50.3 Local/Global Scatter Pattern . . . 282
50.4 Element Assembly: `MatSetValuesLocal` . . . 283
50.5 Solver Verification under MPI . . . 283
50.5.1 SNES Solve (Test 5) . . . 283
50.5.2 TS Solve (Test 6) . . . 283
50.6 Mass Matrix Assembly (Test 7) . . . 283
50.7 MPI Readiness Scorecard . . . 284
50.8 Roadmap to Multi-Rank Execution . . . 284
50.9 Regression Status . . . 284

51 Material Module: Architectural Analysis and Improvement Plan 285
51.1 Module Architecture Overview . . . 285
51.2 Identified Deficiencies . . . 285
51.3 Six-Phase Improvement Plan . . . 286
51.4 Phase 1 Implementation: Semantic Rename . . . 286
51.4.1 Problem Statement . . . 286
51.4.2 Scope of Changes . . . 286
51.4.3 Verification . . . 287
51.5 Summary . . . 287
51.6 Phase 2 Implementation: Thread-Safe Constitutive Relations . . . 287
51.6.1 Problem Statement . . . 287
51.6.2 Why the Cache Was Unnecessary . . . 288
51.6.3 Scope of Changes . . . 288

51.6.4 Verification . . . 288
51.7 Phase 3 Implementation: Kinematic Dispatch Consolidation . . . 289
51.7.1 Problem Statement . . . 289
51.7.2 Solution: Dispatch Helper Functions . . . 289
51.7.3 Scope of Changes . . . 289
51.7.4 Verification . . . 290
51.8 Phase 4 Implementation: Kinematic Policy on Structural Elements . . . 290
51.8.1 Problem Statement . . . 290
51.8.2 Design: `BeamKinematicPolicyConcept` . . . 290
51.8.3 Template Signature Change . . . 291
51.8.4 Internal Refactoring . . . 291
51.8.5 Verification . . . 291
51.9 Phase 5 Implementation: Corotational Beam Formulation . . . 292
51.9.1 Formulation Overview . . . 292
51.9.2 Implementation in `beam::Corotational` . . . 292
51.9.3 Integration with `BeamElement` . . . 293
51.9.4 Scope of Changes . . . 293
51.9.5 Verification . . . 293
51.10 Phase 6 Implementation: State Separation, Arena Allocator, and Dynamic Infrastructure . . . 293
51.10.1 State Separation: `InternalStateOf` Trait . . . 294
51.10.2 Arena Allocator: `MonotonicArena` and `ArenaAllocator<T>` . . . 294
51.10.3 Mass Matrix Support for Structural Elements . . . 294
51.10.4 Standalone-Vector Interface for DynamicAnalysis . . . 295
51.10.5 Verification . . . 295
51.11 Corotational Dynamic RC Building Example . . . 295
51.11.1 Structural Configuration . . . 296
51.11.2 Materials . . . 296
51.11.3 Kinematic Formulation . . . 296
51.11.4 Dynamic Parameters . . . 296
51.11.5 Loading Protocol . . . 297
51.11.6 Solution Strategy . . . 297
51.11.7 VTK Time-Series Output . . . 297

52 Corotational Dynamic RC Building Example 298
52.1 Motivation and Scope . . . 298
52.2 Corotational Beam Kinematics . . . 298
52.2.1 Conceptual Framework . . . 298
52.2.2 Corotated Frame Update . . . 299
52.2.3 Deformational DOF Extraction . . . 299
52.2.4 Tangent Stiffness and Geometric Contribution . . . 300
52.3 Dynamic Analysis Configuration . . . 300
52.3.1 Loading and Ramps . . . 300
52.3.2 Time-Integration Parameters . . . 300
52.4 VTK Displacement Reconstruction for Corotational Beams . . . 301
52.4.1 The Problem: Disconnected Elements in Warp-by-Vector . . . 301
52.4.2 The Fix: Global DOF Interpolation . . . 301
52.4.3 Affected Reconstruction Sites . . . 302
52.4.4 Type Dispatch for Corotational Elements . . . 303
52.5 Kinematic Incompatibility: Linear Shell vs. Corotational Beam . . . 303
52.5.1 Diagnosis: Numerical Divergence in the Mixed Model . . . 303
52.5.2 Root Cause Analysis . . . 303

52.5.3 Physical Interpretation . . . 304
52.5.4 Formal Statement of the Incompatibility . . . 304
52.6 Resolution Strategies . . . 304
52.7 Test Regression Summary . . . 305
52.8 Files Modified . . . 305
52.9 Summary . . . 306

53 Observer/Recorder Architecture and ModelBuilder Design 307
53.1 Motivation . . . 307
53.2 Current Infrastructure Audit . . . 308
53.2.1 Analysis Monitor Interface . . . 308
53.2.2 VTK Export . . . 308
53.2.3 Section Constitutive Snapshot . . . 308
53.2.4 ModelBuilder (Dead Code) . . . 308
53.2.5 Helpers in `main.cpp` . . . 308
53.3 Observer/Recorder Architecture . . . 309
53.3.1 Design Principles . . . 309
53.3.2 Core API . . . 309
53.3.3 Composite Observer . . . 310
53.3.4 Integration with `DynamicAnalysis` . . . 310
53.3.5 Concrete Observers . . . 310
53.3.6 Data Flow Diagram . . . 312
53.3.7 Design Alternatives Considered . . . 313
53.4 Comparison with OpenSees Recorder Architecture . . . 313
53.4.1 OpenSees Recorder: Key Architectural Traits . . . 313
53.4.2 `fall_n` Observer: Contrasting Design . . . 314
53.4.3 Architectural Summary Table . . . 315
53.4.4 Shared Conceptual Ground . . . 315
53.5 ModelBuilder Architecture . . . 315
53.5.1 Layered Design . . . 315
53.5.2 Layer 1: Generic ModelBuilder . . . 316
53.5.3 Layer 2: StructuralModelBuilder . . . 316
53.5.4 Framed Structure Convenience . . . 317
53.5.5 Helper Function Extraction Plan . . . 318
53.6 Modern C++ Migration . . . 318
53.6.1 std::print and std::format . . . 318
53.7 Implementation Order and Prerequisites . . . 319
53.7.1 Prerequisites . . . 319
53.7.2 Phased Implementation . . . 319
53.8 Trade-offs and Design Decisions . . . 320
53.9 Phase 1 Implementation Notes . . . 320
53.9.1 Dual-flavour Observer Composition . . . 320
53.9.2 StepEvent Value Type . . . 320
53.9.3 ObserverCallback Bridge . . . 321
53.9.4 Concrete Observers (Implemented) . . . 321
53.9.5 StateQuery Extraction . . . 322
53.9.6 `std::print/format` Migration (Partial Phase 2) . . . 322
53.9.7 File Organisation . . . 322
53.9.8 DynamicAnalysis Integration Detail . . . 322
53.9.9 Test Suite After Phase 1 . . . 323
53.9.10 Known Limitations and Next Steps . . . 323
53.10 Phase 2 Implementation Notes: Helper Extraction . . . 323

53.10.1 New File Organisation . . . 323
53.10.2 Designated-Initialiser API . . . 324
53.10.3 Migration Statistics . . . 324
53.10.4 Build and Test Verification . . . 324
53.11 Build System Optimisation (Phase 2B) . . . 325
53.11.1 CMake Helper Function . . . 325
53.11.2 CTest Label Hierarchy . . . 325
53.11.3 CMake Presets . . . 325
53.11.4 Compiler Cache . . . 326
53.11.5 Development Workflow . . . 326
53.12 Summary . . . 326
53.13 Phase 3 Implementation Notes: ModelBuilder . . . 327
53.13.1 Design Decisions . . . 327
53.13.2 New File Organisation . . . 328
53.13.3 API Examples . . . 328
53.13.4 Refactoring Impact on `main.cpp` . . . 328
53.13.5 Scripting-Language Openness . . . 329
53.13.6 Build and Test Verification . . . 329
53.14 Scripting Language Evaluation: Julia vs. Python . . . 329
53.14.1 Evaluation Criteria . . . 330
53.14.2 Python: Strengths and Limitations . . . 330
53.14.3 Julia: Strengths and Limitations . . . 331
53.14.4 Head-to-Head Comparison . . . 332
53.14.5 Recommendation: Julia as Primary, Python as Secondary . . . 332
53.14.6 Architectural Implications . . . 333
53.15 Higher-Order MITC Shell Elements . . . 334
53.15.1 The Transverse Shear Locking Problem . . . 334
53.15.2 MITC4: Bilinear Assumed-Strain Shell . . . 334
53.15.3 MITC9: Biquadratic Assumed-Strain Shell . . . 335
53.15.4 MITC16: Bicubic Assumed-Strain Shell . . . 335
53.15.5 Unified `MITCShellElement` Template . . . 335
53.15.6 Stiffness Matrix Assembly . . . 336
53.15.7 Consistent Mass Matrix . . . 336
53.15.8 Internal Force Vector . . . 337
53.16 Corotational Kinematic Policy for Shells . . . 337
53.16.1 Motivation: Geometric Compatibility in Mixed Models . . . 337
53.16.2 Corotational Kinematics: Theory . . . 337
53.16.3 Geometric Stiffness for Shells . . . 338
53.16.4 Implementation in `fall_n` . . . 338
53.16.5 Verification: Rigid-Body Invariance . . . 339
53.16.6 VTK Visualisation of Higher-Order Shells . . . 339
53.16.7 Application: Corotational Dynamic RC Building . . . 339
53.16.8 Test Suite Summary . . . 340

54 Seismic Analysis Infrastructure **341**
54.1 Earthquake Ground Motion Input . . . 341
54.1.1 Data Format and the El Centro Record . . . 341
54.1.2 The `GroundMotionRecord` Class . . . 342
54.2 The `section_snapshots()` Virtual . . . 342
54.2.1 Design Decision . . . 343
54.2.2 SectionConstitutiveSnapshot Anatomy . . . 343
54.3 Damage Criterion Framework . . . 343

54.3.1 Class Hierarchy . . . 344
54.3.2 Evaluation Protocol . . . 344
54.3.3 MaxStrainDamageCriterion . . . 344
54.3.4 CallableDamageCriterion and `make_damage_criterion` . . . 344
54.3.5 DamageTracker Observer . . . 344
54.4 Fiber Hysteresis Recorder . . . 345
54.4.1 Architecture . . . 345
54.4.2 Integration with DamageCriterion . . . 345
54.5 Observer Wiring: FiberRecorder and ElementRecorder . . . 345
54.6 Five-Story RC Building Under El Centro . . . 346
54.6.1 Structural Configuration . . . 346
54.6.2 Element Formulations . . . 346
54.6.3 Loading Sequence . . . 346
54.6.4 Observer Pipeline . . . 346
54.6.5 Time Integration . . . 347
54.7 Test Suite . . . 347
54.8 Build System Integration . . . 347
54.8.1 CMake Targets . . . 347
54.8.2 Header Organization . . . 348
54.9 Design Rationale . . . 348
54.9.1 Why a Virtual on StructuralElement? . . . 348
54.9.2 Why Strategy Pattern for Damage? . . . 348
54.9.3 Why a Separate Hysteresis Recorder? . . . 348
54.10 Summary of Files . . . 349

55 Seismic RC Building: Results and Analysis 350
55.1 Problem Description . . . 350
55.1.1 Structural Geometry . . . 350
55.1.2 Material Properties . . . 350
55.1.3 Mass and Damping . . . 351
55.2 Seismic Input: El Centro 1940 . . . 351
55.3 Analysis Configuration . . . 352
55.4 Observer Pipeline . . . 352
55.5 Results . . . 352
55.5.1 Concrete Fiber Response . . . 352
55.5.2 Steel Fiber Response . . . 353
55.5.3 Stress Time Histories . . . 353
55.5.4 Combined Response Overview . . . 353
55.6 Discussion and Interpretation . . . 356
55.6.1 Demand-to-Capacity Ratios . . . 356
55.6.2 Gravity Dominance . . . 356
55.6.3 Essentially Elastic Behaviour . . . 356
55.6.4 Pathways to Inelastic Response . . . 356
55.7 VTK Visualisation . . . 357
55.8 Summary . . . 357

56 Ko–Bathe Plastic-Fracturing Concrete Model 358
56.1 Theoretical Background . . . 358
56.1.1 Octahedral Stress Invariants . . . 358
56.1.2 Fracturing Mechanism . . . 359
56.1.3 Compression Coordinate System . . . 359
56.1.4 Plasticity Yield Surfaces . . . 360

56.1.5 Cracking Mechanism . . . 361
56.1.6 Material Parameters . . . 361
56.2 Implementation Architecture . . . 362
56.2.1 KoBatheParameters . . . 362
56.2.2 KoBatheState . . . 363
56.2.3 KoBatheConcrete . . . 363
56.2.4 Algorithm Flow . . . 363
56.3 VTK Visualization . . . 363
56.4 Concept Satisfaction . . . 365
56.5 Test Suite . . . 365
56.6 Design Decisions . . . 365
56.7 Possible Extensions . . . 366

57 Building `fall_n` on Windows (MSYS2/UCRT64) 367
57.1 Prerequisites and Motivations . . . 367
57.2 Step 1 — Install MSYS2 . . . 367
57.3 Step 2 — Install Build Tools and Dependencies . . . 368
57.4 Step 3 — Install the MS-MPI Runtime . . . 368
57.5 Step 4 — Configure the CMake Build . . . 369
57.6 Step 5 — Compile . . . 369
57.7 Step 6 — Run the Tests . . . 369
57.8 CMake Modifications for Windows Compatibility . . . 370
57.8.1 MinGW-specific compiler and linker flags . . . 370
57.8.2 VTK extern-template linking fix . . . 370
57.8.3 PETSc C++ macro fallbacks . . . 371
57.8.4 PETSc pkg-config name . . . 372
57.8.5 Source directory macro . . . 372
57.8.6 Windows CMake preset . . . 372
57.9 Source-Code Portability Fixes . . . 372
57.9.1 `ushort` is not a standard type . . . 373
57.9.2 `%zu` format specifier in `PetscPrintf` . . . 373
57.9.3 Unused-variable warning in tests . . . 373
57.10 Runtime PATH Considerations . . . 373
57.11 Summary of All Changes . . . 373

58 Incremental Control Policy for Nonlinear Analysis 375
58.1 Motivation and Problem Statement . . . 375
58.2 Design Decision: Function-Level Template . . . 376
58.3 The `IncrementalControlPolicy` Concept . . . 376
58.3.1 The Absolute-State Invariant . . . 377
58.4 Concrete Implementations . . . 377
58.4.1 `LoadControl` — Proportional Load Scaling . . . 377
58.4.2 `DisplacementControl` — Prescribed-DOF Pushover . . . 377
58.4.3 `CustomControl<F>` — Maximum Flexibility . . . 378
58.4.4 Arc-Length Control (Stub) . . . 379
58.5 `Model::update_imposed_value()` . . . 379
58.6 Changes to `NonlinearAnalysis` . . . 380
58.6.1 Renamed Control Parameter . . . 380
58.6.2 Template Structure . . . 380
58.6.3 Integration with the Bisection Engine . . . 380
58.7 Relationship with Existing Policy Patterns . . . 381
58.8 File Summary . . . 381

58.9 Testing . . . 382
58.10 Usage Guide . . . 382
58.10.1 Load Control (Default) . . . 382
58.10.2 Displacement-Controlled Pushover . . . 382
58.10.3 Multi-DOF Displacement Control with Proportional Load . . . 383
58.10.4 Custom Control . . . 383
58.10.5 Sequential Multi-Phase Analysis . . . 383

59 Steppable Dynamic Analysis with StepDirector 384
59.1 Motivation . . . 384
59.2 Design . . . 384
59.2.1 Single-Step API on DynamicAnalysis . . . 384
59.2.2 Extracted `post_step_` Method . . . 385
59.2.3 Runtime Reconfiguration . . . 385
59.3 StepDirector — Condition-Based Breakpoints . . . 385
59.3.1 StepVerdict Enum . . . 385
59.3.2 StepDirector Type Alias . . . 386
59.3.3 Convenience Factories . . . 386
59.3.4 Integration with DynamicAnalysis . . . 386
59.4 Backward Compatibility . . . 386
59.5 Verification . . . 387
59.6 Files Modified and Created . . . 387
59.7 Future Directions . . . 387

60 Unified Steppable Solver — Phase C 388
60.1 Motivation . . . 388
60.2 The `SteppableSolver` Concept . . . 388
60.3 NonlinearAnalysis Single-Step API . . . 389
60.3.1 Initialization . . . 389
60.3.2 Stepping . . . 389
60.3.3 Runtime Reconfiguration . . . 389
60.4 Type-Erased Bisection Engine . . . 390
60.5 AnalysisState — Cross-Engine Transfer . . . 390
60.6 Verification . . . 390
60.7 Files . . . 391

61 AnalysisDirector — Multi-Phase Orchestrator (Phase D) 392
61.1 Motivation . . . 392
61.2 Design Decisions . . . 392
61.2.1 Type-Erased Phase Callbacks . . . 392
61.2.2 Borrowed State and Lifetime . . . 393
61.2.3 Failure Semantics . . . 393
61.2.4 Phase Gating . . . 393
61.3 Architecture . . . 393
61.3.1 Core Types . . . 393
61.3.2 AnalysisDirector API . . . 394
61.3.3 Execution Algorithm . . . 394
61.4 Bug Fix: `solve_incremental` State Synchronisation . . . 394
61.4.1 Fix Applied . . . 395
61.5 Usage Example . . . 395
61.6 Verification . . . 396
61.7 Test Infrastructure Improvements . . . 396

61.7.1 MSHReader Defensive Fix . . . 396
61.7.2 Mesh File Generation . . . 396
61.8 Files . . . 397
61.9 Phase Summary . . . 397

62 Analysis & Model Architecture — Comprehensive Reference 398
62.1 Overview . . . 398
62.2 Analysis Module Architecture . . . 398
62.2.1 Header Inventory . . . 398
62.2.2 Dependency Graph . . . 399
62.2.3 Class-Level Architecture . . . 399
62.2.4 Solver Engine Anatomy . . . 400
62.2.5 Incremental Control Policies . . . 401
62.2.6 Observer Architecture . . . 401
62.2.7 StepDirector and SteppableSolver . . . 402
62.2.8 AnalysisDirector (Orchestration) . . . 402
62.3 Model Module Architecture . . . 402
62.3.1 Header Inventory . . . 402
62.3.2 The `Model<>` Template . . . 403
62.3.3 Boundary Condition Framework . . . 404
62.3.4 NodeSelector: Composable Node Queries . . . 404
62.3.5 Semantic Analysis . . . 404
62.4 Extension Points . . . 405
62.4.1 Adding a New Solver Engine . . . 405
62.4.2 Adding a New Observer . . . 405
62.4.3 Adding a New Incremental Control Policy . . . 406
62.4.4 Adding a New StepDirector . . . 406
62.5 Usage Tutorials . . . 407
62.5.1 Tutorial 1: Simple Linear Static Analysis . . . 407
62.5.2 Tutorial 2: Nonlinear Incremental with Displacement Control . . . 407
62.5.3 Tutorial 3: Dynamic Seismic Analysis with Observers . . . 407
62.5.4 Tutorial 4: Multi-Phase Analysis with AnalysisDirector . . . 408
62.5.5 Tutorial 5: Single-Step Control with StepDirector . . . 408
62.6 Cross-Module Dependency Map . . . 409
62.7 Ontological Critique . . . 409
62.8 Code Cleanup Summary . . . 410
62.9 Summary . . . 410

63 Multiscale Seismic Analysis Framework 411
63.1 Motivation . . . 411
63.2 Phase 0: Earthquake Parser Infrastructure . . . 411
63.2.1 Problem Statement . . . 411
63.2.2 Implementation . . . 412
63.2.3 Verification . . . 412
63.3 Phase 1: L-Shaped Building Domain Builder . . . 412
63.3.1 Problem Statement . . . 412
63.3.2 Design . . . 413
63.3.3 Verification . . . 413
63.4 Phase 2: Linear–Nonlinear Transition . . . 413
63.4.1 Problem Statement . . . 413
63.4.2 Design . . . 413
63.4.3 Verification . . . 414

63.5 Phase 3: Prismatic Hex Mesh Builder . . . 414
63.5.1 Problem Statement . . . 414
63.5.2 Design . . . 414
63.5.3 Verification . . . 415
63.6 Phase 4: Beam–Continuum Field Transfer . . . 415
63.6.1 Problem Statement . . . 415
63.6.2 Design . . . 415
63.6.3 Verification . . . 416
63.7 Phase 5: MultiscaleCoordinator . . . 416
63.7.1 Problem Statement . . . 416
63.7.2 Design . . . 416
63.7.3 Verification . . . 417
63.8 Integration and Dependency Map . . . 417
63.8.1 New Source Files . . . 417
63.8.2 Modified Source Files . . . 418
63.8.3 Test Summary . . . 418
63.9 Completed Extensions (Phase 6) . . . 418
63.9.1 Beam element interpolation interface (`BeamInterpolable`) . . . 418
63.9.2 Sub-model solve (`SubModelSolver`) . . . 419
63.9.3 Bidirectional coupling (`HomogenizedBeamSection`) . . . 419
63.9.4 PETSc TS state injection (`inject_dynamic_state`) . . . 419
63.9.5 Parallel sub-model creation (two-phase `build_sub_models`) . . . 420
63.9.6 Test coverage . . . 420
63.10 Phase 6: Sub-Model VTK Export and Transition Bug Fix . . . 421
63.10.1 VTK export in SubModelSolver . . . 421
63.10.2 TransitionDirector copy-constructibility fix . . . 421
63.11 Elastic Verification Example . . . 422
63.11.1 Physical scenario and hypotheses . . . 422
63.11.2 Results . . . 422
63.11.3 Discussion . . . 422
63.11.4 Key code excerpt . . . 423
63.12 Seismic Fiber-Section Multiscale Example . . . 423
63.12.1 Physical scenario . . . 423
63.12.2 Two-phase analysis workflow . . . 424
63.12.3 Output . . . 425
63.12.4 Key code excerpt . . . 425
63.12.5 Numerical results . . . 426
63.12.6 Infrastructure footprint . . . 427
63.12.7 Multiscale functionality summary . . . 428

64 Ko–Bathe Concrete Model: Three-Dimensional Extension 429
64.1 Voigt Convention and State Variables . . . 429
64.2 Octahedral Stress Invariants in 3D . . . 429
64.3 Principal Strain Decomposition . . . 430
64.4 Compression Coordinates . . . 430
64.5 Isotropic 3D Tangent Matrix . . . 431
64.6 Mandel Rotation for the Cracked Tangent . . . 431
64.6.1 Mandel Notation . . . 431
64.6.2 Construction of the Mandel Rotation Matrix . . . 431
64.6.3 Engineering–Mandel Conversion . . . 432
64.6.4 Cracked Tangent Application . . . 432
64.7 Crack Initiation in 3D . . . 432

64.8 Plasticity Return Mapping . . . 433
64.8.1 Back-Transform: Compression Coordinates to Global Voigt . . . 433
64.9 Full Algorithm . . . 433
64.10 Integration with the Sub-Model Solver . . . 434
64.10.1 Operator-Splitting Crack Check . . . 434
64.10.2 PETSc Solver Configuration . . . 434
64.11 Test Suite . . . 435
64.12 Discussion . . . 435

65 TrussElement: Embedded Rebar for Continuum Sub-Models 437
65.1 Motivation . . . 437
65.2 Formulation . . . 437
65.2.1 Kinematics . . . 437
65.2.2 Stiffness Matrix . . . 438
65.2.3 Internal Forces . . . 438
65.2.4 Tangent Stiffness . . . 438
65.2.5 Mass Matrix . . . 438
65.3 Implementation . . . 438
65.3.1 FiniteElement Concept Compliance . . . 439
65.3.2 Integration with Mixed-Topology Models . . . 439
65.4 Verification . . . 440
65.4.1 Test Material . . . 440
65.4.2 Geometry Tests . . . 440
65.4.3 Stiffness Tests . . . 440
65.4.4 Internal Force Test . . . 441
65.4.5 Additional Tests . . . 441
65.5 Discussion . . . 441

66 Reinforced Sub-Model Integration 442
66.1 Heterogeneous Element Assembly . . . 442
66.2 Domain Builder . . . 442
66.3 Reaction-Based Effective Modulus . . . 443
66.4 Bug Fix: State Vector Accumulation in Incremental Solve . . . 443
66.4.1 Root Cause . . . 443
66.4.2 Fix . . . 443
66.4.3 Scope of Impact . . . 444
66.5 Validation . . . 444
66.6 VTK Gauss-Point Export for Heterogeneous Models . . . 444
66.6.1 GaussFieldRecord and Virtual Dispatch . . . 445
66.6.2 Type-Erased Fallback in VTKModelExporter . . . 445
66.6.3 Gauss Displacement Interpolation Guard . . . 445
66.6.4 Buffer Alignment for Mixed-Element Models . . . 446
66.6.5 3D Crack Normal Snapshot . . . 446
66.6.6 VTK Writer Correction . . . 446
66.7 VTK Crack Export Validation . . . 446

67 L-Shaped RC Building under Bidirectional Seismic Excitation 448
67.1 Building Geometry . . . 448
67.2 Material Properties . . . 449
67.2.1 Columns . . . 449
67.2.2 Beams . . . 449
67.2.3 Slabs . . . 449

67.3 Earthquake Input . . . 449
67.4 Dynamic Analysis Setup . . . 450
67.5 Observers and Transition Criterion . . . 450
67.6 Phase 1 Results . . . 451
67.7 Phase 2: Reinforced Continuum Sub-Models . . . 451
67.7.1 Sub-Model Construction . . . 451
67.7.2 Sub-Model Evolution . . . 452
67.8 Roof Displacement Time Histories . . . 452
67.9 Implementation Notes . . . 454
67.9.1 CompositeObserver Pattern . . . 454
67.9.2 Manual-Stepping Observer Fix . . . 454
67.9.3 Slab Mass Contribution . . . 454
67.9.4 Convergence and SNES Sub-Stepping . . . 454
67.9.5 Bypassing the MultiscaleCoordinator . . . 454
67.10 Summary . . . 455

68 Validation of the 3D Continuum Sub-Model with Imposed Rotation 456
68.1 Geometry and Material Properties . . . 456
68.2 Boundary Conditions and Loading . . . 457
68.3 Results . . . 457
68.3.1 Moment–Rotation Response . . . 457
68.3.2 Stiffness Degradation . . . 458
68.3.3 Moment Ratio . . . 458
68.4 Analytical Cross-Check . . . 460
68.5 Implementation Notes . . . 460
68.6 Conclusions . . . 460

69 Higher-Order Prismatic Domains and VTK Local Axes 462
69.1 Motivation . . . 462
69.2 The `HexOrder` Enumeration . . . 462
69.3 Structured Grid Generalisation . . . 463
69.4 Element Connectivity Patterns . . . 463
69.4.1 Hex8 — Linear . . . 463
69.4.2 Hex20 — Serendipity . . . 463
69.4.3 Hex27 — Triquadratic . . . 464
69.5 Quadrature Selection . . . 464
69.6 Reinforced Domain with Higher-Order Elements . . . 464
69.7 The `align_to_beam` Helper . . . 464
69.8 VTK Local-Axes Cell Data . . . 465
69.8.1 Motivation . . . 465
69.8.2 Implementation . . . 465
69.8.3 Visualisation in ParaView . . . 465
69.9 Example: Hex20 Prismatic Sub-Model . . . 465
69.10 Backward Compatibility . . . 466

70 Persistent Nonlinear Sub-Model Evolution and L-Shaped Building Multi-Scale Seismic Analysis 467
70.1 Introduction and Motivation . . . 467
70.2 Mathematical Framework . . . 467
70.2.1 Section Kinematics from Beam Elements . . . 467
70.2.2 Kinematic Reconstruction: From Beam to 3D Continuum . . . 468
70.2.3 Incremental Application of Boundary Conditions . . . 469

70.2.4 Residual and Tangent Stiffness Formulation . . . 469
70.2.5 Material State Management . . . 470
70.2.6 Post-Setup Boundary Condition Update . . . 470
70.3 Ko–Bathe Concrete in the Multi-Scale Context . . . 471
70.4 Triquadratic Hex27 Elements . . . 472
70.5 Crack Evolution Tracking . . . 472
70.5.1 CrackSummary Aggregation . . . 472
70.5.2 CSV Output Format . . . 472
70.5.3 Crack Plane Visualisation . . . 473
70.6 Implementation . . . 473
70.6.1 Class Architecture . . . 473
70.6.2 SNES Callbacks . . . 474
70.7 L-Shaped Building Example . . . 475
70.7.1 Structural Configuration . . . 475
70.7.2 Three-Component Ground Motion . . . 475
70.7.3 Phase 1: Global Dynamic Analysis with Transition Monitoring . . . 475
70.7.4 Phase 2: Multi-Scale Sub-Model Evolution . . . 476
70.8 Incremental Kinematics Coupling: Full Derivation . . . 477
70.9 Discussion . . . 478

71 Mixed-Model Reinforced Sub-Model with Discrete Rebars 480
71.1 Introduction and Motivation . . . 480
71.2 Mathematical Formulation . . . 480
71.2.1 Mixed Displacement Field and Perfect Bond . . . 480
71.2.2 Continuum Element Contribution (Concrete) . . . 480
71.2.3 Truss Element Contribution (Rebar) . . . 481
71.2.4 Assembled Mixed System . . . 481
71.3 Type-Erased Element Access: `GaussPointSnapshot` . . . 481
71.4 Reinforced Prismatic Domain Construction . . . 482
71.5 Model Construction in the Evolver . . . 482
71.5.1 Post-Processing Adaptation . . . 482
71.6 Coordinator Integration . . . 483
71.7 Summary . . . 483

72 Arc-Length Control for Nonlinear Analysis 484
72.1 Introduction . . . 484
72.2 Augmented System . . . 484
72.2.1 Constraint Equations . . . 484
72.3 Predictor Step (Tangent Predictor) . . . 485
72.4 Corrector Iterations (Sherman–Morrison Decomposition) . . . 485
72.4.1 Cylindrical Corrector . . . 485
72.4.2 Spherical Corrector . . . 486
72.5 Convergence Check and State Commit . . . 486
72.6 Implementation: `ArcLengthControl` . . . 486
72.7 Implementation: `ArcLengthSolver` . . . 487
72.8 Integration with the Sub-Model Evolver . . . 487
72.8.1 Auto-Switch Logic . . . 487
72.8.2 Adaptive Displacement Sub-Stepping . . . 488
72.9 Summary . . . 488

73 Two-Way FE^2 Coupling **489**
73.1 Introduction . . . 489
73.2 FE^2 Framework . . . 489
73.2.1 Scale Separation . . . 489
73.2.2 Homogenisation: Stress to Section Forces . . . 489
73.2.3 Section Forces from Boundary Reactions . . . 490
73.3 Homogenised Section Tangent . . . 490
73.3.1 Perturbation-Based Tangent Computation . . . 490
73.3.2 Structure of $\mathbf{D}_{\text{hom}}$ . . . 491
73.4 Stiffness Injection into the Beam Element . . . 491
73.5 Staggered Iteration Scheme . . . 491
73.6 Planned Implementation Architecture . . . 492
73.7 Summary . . . 492

74 Concurrent Multiscale Architecture: Diagnostic, Design, and Roadmap **493**
74.1 Introduction . . . 493
74.2 The Classical FE^2 Method . . . 493
74.2.1 Origin and Formulation . . . 493
74.2.2 Extensions in the Literature . . . 494
74.2.3 Adaptation in `fall_n` . . . 494
74.3 Current Implementation Status . . . 495
74.3.1 Component Inventory . . . 495
74.3.2 Verification Test Results . . . 495
74.3.3 SOLID Principles Audit . . . 496
74.4 Proposed Architecture: `MultiscaleAnalysis` . . . 497
74.4.1 Design Overview . . . 497
74.4.2 Core Abstractions . . . 497
74.5 Code Reusability Assessment . . . 499
74.5.1 Directly Reusable Components . . . 499
74.5.2 Hard-Coded Dependencies Requiring Refactoring . . . 499
74.6 Parallelism and HPC Scalability . . . 500
74.6.1 Current Parallelism . . . 500
74.6.2 Scalability Bottlenecks . . . 500
74.6.3 HPC Strategy . . . 500
74.7 Phased Implementation Plan . . . 501
74.7.1 Phase 0: Build System Cleanup . . . 501
74.7.2 Phase 1: `LocalModelAdapter` Interface . . . 501
74.7.3 Phase 2: `MaterialFactory` Injection . . . 502
74.7.4 Phase 3: `MultiscaleModel` Aggregation . . . 502
74.7.5 Phase 4: `MultiscaleAnalysis` Orchestrator . . . 502
74.7.6 Phase 5: Coupling Strategy Injection . . . 502
74.7.7 Phase 6: Inter-Sub-Model Parallelism . . . 502
74.7.8 Phase 7: Homogenisation Strategy . . . 503
74.7.9 Phase 8: Header Modularisation and Compilation . . . 503
74.8 Summary . . . 503

75 Build System Diagnosis and Compilation Optimisation **504**
75.1 Motivation . . . 504
75.2 Build System Overview . . . 504
75.3 Root Cause Analysis . . . 504
75.3.1 Monolithic Header: `header_files.hh` . . . 504
75.3.2 Duplicate Seismic Executables . . . 505

75.3.3 No Precompiled Headers (PCH) . . . 505
75.3.4 No Explicit Template Instantiation . . . 505
75.4 Mitigation Plan . . . 506
75.4.1 Step 1: Consolidate Seismic Variants . . . 506
75.4.2 Step 2: Precompiled Headers . . . 506
75.4.3 Step 3: Explicit Template Instantiation . . . 507
75.4.4 Step 4: Header Modularisation . . . 508
75.4.5 Step 5: CMake OBJECT Library . . . 508
75.4.6 Step 6: C++20 Modules (Exploratory) . . . 508
75.5 Expected Cumulative Impact . . . 509
75.6 Summary . . . 509

76 Multiscale Architecture Refactoring: Implementation 510
76.1 Introduction . . . 510
76.2 Phase 0.1: Build System Cleanup . . . 510
76.2.1 Problem: 20 Duplicate Seismic Targets . . . 510
76.2.2 Solution: Target Consolidation . . . 511
76.3 Phase 1: `LocalModelAdapter` Concept . . . 511
76.3.1 Design Rationale . . . 511
76.3.2 The `LocalModelAdapter` Concept . . . 511
76.3.3 Type-Erased Handle: `LocalModelHandle` . . . 512
76.3.4 Adapting `NonlinearSubModelEvolver` . . . 513
76.4 Phase 2: `MaterialFactory` Injection . . . 513
76.4.1 Problem: Hardcoded Constitutive Models . . . 513
76.4.2 Solution: Abstract Factory Pattern . . . 514
76.4.3 Injection into the Evolver . . . 514
76.5 Phase 3: `MultiscaleModel` Aggregation . . . 515
76.5.1 Problem: Scattered Model–Sub-Model Coupling . . . 515
76.5.2 Design: Template on Local Model Type . . . 515
76.6 Phase 4: Coupling Strategy Interfaces . . . 516
76.6.1 Problem: Hardcoded Coupling Parameters . . . 516
76.6.2 Strategy Interfaces . . . 517
76.7 Phase 4.3: `MultiscaleAnalysis` Orchestrator . . . 518
76.7.1 Design . . . 518
76.7.2 The `step()` Method . . . 519
76.8 Phase 5: `HomogenisationStrategy` . . . 520
76.8.1 Problem: Two Upscaling Methods . . . 520
76.8.2 Strategy Interface . . . 520
76.9 Discussion . . . 521
76.9.1 SOLID Compliance . . . 521
76.9.2 Concept vs. ABC Trade-Offs . . . 522
76.9.3 Circular Dependency Avoidance . . . 522
76.9.4 Type-Erasure Pattern Reuse . . . 522
76.9.5 Build Verification . . . 522
76.9.6 Remaining Work . . . 522

77 Main Driver Refactoring: MultiscaleAnalysis Integration 524
77.1 Introduction . . . 524
77.2 Architecture Overview . . . 524
77.3 Evolver Transfer and Callback Wiring . . . 525
77.4 Orchestrator Construction . . . 525
77.5 Staggered Loop Replacement . . . 526

77.5.1 Before: Hand-Written Staggered Loop . . . 526
77.5.2 After: Orchestrator Delegation . . . 527
77.6 Behavioral Equivalence Analysis . . . 527
77.7 Diagnostic Accessors . . . 528
77.8 Line Count and Complexity Reduction . . . 528
77.9 Response Injector Design . . . 528
77.10 Build and Test Verification . . . 528
77.11 Discussion . . . 529
77.11.1 Move Semantics and Evaluation Order . . . 529
77.11.2 Commit Semantics . . . 529
77.11.3 Crack Diagnostic Decoupling . . . 529
77.12 Summary . . . 529

78 Ejemplo avanzado: Edificio en L de 16 niveles con análisis multiescala FE^2 530
78.1 Introducción y motivación . . . 530
78.2 Hipótesis del modelo . . . 530
78.3 Descripción del modelo . . . 531
78.3.1 Geometría . . . 531
78.3.2 Irregularidad en altura — secciones por rango . . . 531
78.3.3 Acción sísmica . . . 531
78.3.4 Parámetros de análisis dinámico . . . 531
78.3.5 Parámetros del acoplamiento FE^2 . . . 531
78.4 Implementación . . . 531
78.4.1 Reasignación de grupos por rango . . . 531
78.4.2 Coordinadores multiescala por rango . . . 532
78.4.3 Puente C++–Python para postproceso . . . 533
78.5 Resultados esperados . . . 533
78.5.1 Desplazamientos de cubierta . . . 533
78.5.2 Curvas de histéresis a ambas escalas . . . 533
78.5.3 Evolución de fisuras en los submodelos . . . 533
78.6 Discusión y análisis de validez . . . 534
78.6.1 Localización del daño en transiciones de sección . . . 534
78.6.2 Convergencia del acoplamiento FE^2 . . . 534
78.6.3 Efecto del amortiguamiento de Rayleigh . . . 534
78.7 Estrategia de validación . . . 534
78.7.1 Indicadores clave de rendimiento (KPIs) . . . 535
78.8 Conclusiones del ejemplo . . . 535

79 Acero embebido con acoplamiento por penalidad e interacción fibra-truss en sub-modelos FE^2 536
79.1 Motivación . . . 536
79.2 Posición física de las barras . . . 536
79.3 Nodos independientes de barra y datos de imbricación . . . 537
79.3.1 Elemento huésped y coordenadas padres . . . 537
79.4 Condiciones de contorno en los extremos de las barras . . . 538
79.5 Acoplamiento por penalidad (Master-Slave) . . . 538
79.5.1 Formulación . . . 538
79.5.2 Selección de α . . . 538
79.5.3 Implementación en SNES . . . 539
79.6 Feedback Fibra-Truss implícito . . . 539
79.6.1 Extracción de deformaciones axiales del acero . . . 540
79.7 Visualización VTK de barras con espesor . . . 540

79.8 Optimizaciones de rendimiento acumuladas . . . 540
79.9 Resumen de los cambios de código . . . 541
79.10 Conclusiones . . . 541

80 Ejemplo «mesa de 4 patas»: shell MITC16 + análisis multiescala Fe² 542
80.1 Motivación . . . 542
80.2 Geometría y malla . . . 542
80.2.1 Planta y alzado . . . 542
80.2.2 Nodos . . . 542
80.2.3 Elementos . . . 542
80.3 Materiales . . . 543
80.3.1 Hormigón y acero . . . 543
80.3.2 Secciones de fibra (escala global) . . . 543
80.3.3 Losa (shell elástico) . . . 543
80.4 Carga sísmica . . . 543
80.5 Análisis dinámico . . . 543
80.5.1 Integrador temporal . . . 543
80.5.2 Fase 1: análisis global con fibras . . . 543
80.5.3 Fase 2: evolución multiescala FE² . . . 544
80.6 Salidas . . . 544
80.6.1 VTK (ambas escalas) . . . 544
80.6.2 CSV y gráficas . . . 544
80.7 Resumen de cambios de código . . . 545
80.8 Compilación y ejecución . . . 545

81 Progressive Cyclic Validation of the FE² Pipeline 546
81.1 Motivation . . . 546
81.2 Shared Geometry and Material Properties . . . 547
81.3 Cyclic Displacement Protocol . . . 547
81.3.1 Design Rationale . . . 547
81.3.2 Protocol Function . . . 547
81.3.3 Unit Tests . . . 548
81.4 Case 0: Linear Elastic Reference . . . 548
81.5 Case 1: Single Cantilever Beam (N=2…10) . . . 549
81.6 Case 2: Single Reinforced Continuum Column . . . 550
81.7 Case 3: Full Table Structural Model . . . 552
81.8 Case 4: Table with FE² Sub-Models (One-Way Coupling) . . . 552
81.9 Case 5: Table with FE² Sub-Models (Two-Way Coupling) . . . 553
81.10 Numerical Results Summary . . . 554
81.11 Comparative Analysis . . . 554
81.12 Phase C: Penalty Coupling Architecture . . . 559
81.13 Implementation Bugs Fixed . . . 560
81.14 Case 5 Root Cause: Secant Tangent Limitation . . . 561
81.15 Cross-Reference: Ko–Bathe Article vs. Implementation . . . 561
81.15.1 Fracture Moduli (Eqs. 10–11) . . . 561
81.15.2 Constitutive Matrix in Compression Coordinates (Eq. 31) . . . 562
81.15.3 Elastic Moduli Coefficients (Appendix A) . . . 562
81.15.4 Plasticity (Eqs. 15, 27–29) . . . 562
81.15.5 Cracking (Eqs. 17–23) . . . 563
81.15.6 Validation Examples . . . 563
81.15.7 Convergence Procedure . . . 563
81.16 Consistent Tangent: Analysis and Implementation . . . 563

81.16.1 The Missing Plastic Tangent Contribution . . . 563
81.16.2 Numerical Consistent Tangent . . . 564
81.16.3 Expected Impact on Case 5 . . . 564
81.17 FE^2 Allocation Audit and Optimisations . . . 564
81.17.1 Audit Findings . . . 565
81.17.2 Pre-Allocated Working Vectors (Implemented) . . . 565
81.17.3 RCM Reordering (Implemented) . . . 565
81.18 Implementation Notes . . . 565

82 Normative Multiscale Publication Audit and Redesign 567
82.1 Purpose and Normative Scope . . . 567
82.2 Official Nomenclature . . . 567
82.3 Audit of Prior Claims . . . 567
82.4 Underlying Mathematics and Physical Contract . . . 568
82.4.1 Macro generalised variables . . . 568
82.4.2 Normative homogenised response . . . 568
82.4.3 Boundary-reaction homogenisation . . . 569
82.4.4 Convergence criterion . . . 569
82.5 Implemented Architecture . . . 569
82.5.1 Public data contracts . . . 569
82.5.2 SOLID without sacrificing the hot path . . . 570
82.5.3 Local multiscale class diagram . . . 571
82.5.4 Condensed operator implementation . . . 571
82.5.5 Validation and fallback diagnostics . . . 571
82.5.6 Macro and local rollback . . . 572
82.6 Implemented Iterated Two-Way FE^2 Algorithm . . . 572
82.7 HPC and Build Surface . . . 573
82.8 Verification and Test Matrix . . . 573
82.9 Known Limitations . . . 574
82.10 Future Work . . . 574
82.11 Conclusion . . . 574

83 Execution Record for Multiscale Stabilization v1 576
83.1 Intent and Verification Protocol . . . 576
83.2 Phase 0: Truth Baseline . . . 576
83.3 Phase 1: Numerical Hardening of the Local Response . . . 577
83.3.1 Initial hypothesis . . . 577
83.3.2 Observed evidence before the change . . . 577
83.3.3 Implemented change . . . 577
83.3.4 Resulting semantics . . . 578
83.3.5 Internal architectural hardening . . . 579
83.4 Phase 2: Protocol Hardening for Macro–Micro Iteration . . . 579
83.4.1 Initial hypothesis . . . 579
83.4.2 Errors confirmed during audit . . . 579
83.4.3 Implemented change . . . 579
83.5 Phase 3: Physical Regression Matrix . . . 580
83.5.1 Added regression coverage . . . 580
83.5.2 Observed numerical results . . . 581
83.5.3 Executed regression targets . . . 581
83.6 Phase 4: Release Hardening and CI Surface . . . 581
83.6.1 Local reproducible gate . . . 581
83.6.2 Repository workflow . . . 582

83.7 Post-Stabilization Merge Audit with `origin/master` 583
83.7.1 Audit hypothesis 583
83.7.2 Conflict classification 583
83.7.3 Compatibility retained intentionally 583
83.7.4 Merge-preserved dependency surface 583
83.7.5 Decision 584
83.8 Phase 5: Residual Debt Ledger 584
83.9 Documentation Warning Ledger 585
83.10 Closure of the Stabilization Cycle 585

Chapter 1

Simplex Finite Elements

This chapter describes the construction of Lagrangian finite elements on simplicial cells (triangles in 2D, tetrahedra in 3D) as implemented in `fall_n`. The development follows the classical Ciarlet definition [**?**] specialised to Lagrange interpolation on the reference simplex.

1.1 Reference Simplex

Definition 1.1 (Reference simplex)**.** The *reference simplex* in $\mathbb{R}^D$ is the convex hull

$$\mathcal{S}_D \;=\; \Big\{\boldsymbol{\xi} = (\xi_1, \ldots, \xi_D) \in \mathbb{R}^D \;\Big|\; \xi_i \geq 0,\; \sum_{i=1}^{D} \xi_i \leq 1\Big\}, \tag{1.1}$$

with *vertices*

$$\mathbf{v}_0 = \mathbf{0}, \qquad \mathbf{v}_i = \mathbf{e}_i \quad (i = 1, \ldots, D),$$

where $\mathbf{e}_i$ is the i-th standard basis vector.

The *barycentric coordinates* $(\lambda_0, \lambda_1, \ldots, \lambda_D)$ are defined as

$$\lambda_0 = 1 - \sum_{i=1}^{D} \xi_i, \qquad \lambda_i = \xi_i \quad (i = 1, \ldots, D). \tag{1.2}$$

They form a partition of unity, $\sum_{i=0}^{D} \lambda_i = 1$, and satisfy $\lambda_i \geq 0$ on $\mathcal{S}_D$.

The volume of the reference simplex is

$$|\mathcal{S}_D| = \frac{1}{D!}\,. \tag{1.3}$$

1.2 Lagrange Shape Functions

1.2.1 Linear Elements (Order 1)

The linear simplex has $D+1$ nodes (the vertices). The shape functions are simply the barycentric coordinates:

$$N_i(\boldsymbol{\xi}) = \lambda_i(\boldsymbol{\xi}), \qquad i = 0, 1, \ldots, D. \tag{1.4}$$

Since $\lambda_i \geq 0$ on $\mathcal{S}_D$ and $\lambda_i(\mathbf{v}_j) = \delta_{ij}$, these are the unique linear polynomials that interpolate the nodal values.

Concrete instances in `fall_n`:

- TRI3 ($D = 2$, 3 nodes): `SimplexElement<3,2,1>` (triangle in 3D ambient space, used for boundary faces)
- TET4 ($D = 3$, 4 nodes): `SimplexElement<3,3,1>`

1.2.2 Quadratic Elements (Order 2)

The quadratic simplex has

$$n_{\text{nodes}} = \binom{D+2}{2} = \frac{(D+1)(D+2)}{2} \tag{1.5}$$

nodes: the $D+1$ vertices plus $\binom{D+1}{2}$ edge midpoints.

Vertex shape functions. For vertex i ($i = 0, \ldots, D$):

$$\boxed{N_i(\boldsymbol{\xi}) = \lambda_i\,(2\lambda_i - 1)} \tag{1.6}$$

Remark 1.1 (Sign of vertex shape functions)**.** The vertex shape function $N_i = \lambda_i(2\lambda_i - 1)$ is *negative* whenever $0 < \lambda_i < \frac{1}{2}$. This region is non-empty in the interior of $\mathcal{S}_D$. In particular, interior quadrature points that are "far" from vertex i will have $\lambda_i \ll \frac{1}{2}$, making $N_i < 0$ at those points.

This fact is benign for stiffness matrix assembly (the bilinear form involves gradients, not function values). However, it becomes critical for lumped L^2 projection, as discussed in chapter 3.

Edge midpoint shape functions. For the midpoint of edge (i, j) with $0 \le i < j \le D$:

$$\boxed{N_{ij}(\boldsymbol{\xi}) = 4\,\lambda_i\,\lambda_j} \tag{1.7}$$

These are always non-negative on $\mathcal{S}_D$, since both $\lambda_i, \lambda_j \ge 0$.

Concrete instances:

- TRI6 ($D = 2$, 6 nodes): `SimplexElement<3,2,2>`
- TET10 ($D = 3$, 10 nodes): `SimplexElement<3,3,2>`

1.3 Shape Function Derivatives

Since $\lambda_0 = 1 - \xi_1 - \cdots - \xi_D$ and $\lambda_i = \xi_i$ for $i \ge 1$, the barycentric coordinate gradients (with respect to $\boldsymbol{\xi}$) are:

$$\frac{\partial \lambda_0}{\partial \xi_k} = -1, \qquad \frac{\partial \lambda_i}{\partial \xi_k} = \delta_{ik} \quad (i = 1, \ldots, D). \tag{1.8}$$

For the quadratic vertex shape function $N_i = \lambda_i(2\lambda_i - 1)$:

$$\frac{\partial N_i}{\partial \xi_k} = (4\lambda_i - 1)\,\frac{\partial \lambda_i}{\partial \xi_k}\,. \tag{1.9}$$

For the edge midpoint $N_{ij} = 4\lambda_i\lambda_j$:

$$\frac{\partial N_{ij}}{\partial \xi_k} = 4\Big(\lambda_j\,\frac{\partial \lambda_i}{\partial \xi_k} + \lambda_i\,\frac{\partial \lambda_j}{\partial \xi_k}\Big). \tag{1.10}$$

1.4 Isoparametric Mapping

The isoparametric map from the reference simplex $\mathcal{S}_D$ to a physical element $\Omega^e \subset \mathbb{R}^d$ (with $d \ge D$) is

$$\mathbf{x}(\boldsymbol{\xi}) = \sum_{I=1}^{n_{\text{nodes}}} N_I(\boldsymbol{\xi})\,\mathbf{x}_I, \tag{1.11}$$

where $\mathbf{x}_I \in \mathbb{R}^d$ are the physical nodal coordinates. The *Jacobian matrix* of the mapping is

$$J_{ij} = \frac{\partial x_i}{\partial \xi_j} = \sum_{I=1}^{n_{\text{nodes}}} \frac{\partial N_I}{\partial \xi_j} x_{I,i}\,, \qquad \mathbf{J} \in \mathbb{R}^{d\times D}. \tag{1.12}$$

When $d = D$ (volume elements), $\mathbf{J}$ is square and the differential volume element is $\mathrm{d}\Omega = |\det \mathbf{J}|\,\mathrm{d}\boldsymbol{\xi}$.

When $d > D$ (surface elements, e.g. TRI6 boundary faces in 3D), the surface measure is computed from the metric tensor:

$$\mathrm{d}S = \sqrt{\det(\mathbf{J}^T\mathbf{J})}\,\mathrm{d}\boldsymbol{\xi}. \tag{1.13}$$

Gradient transformation. The gradient of a scalar field in physical space is obtained from the reference-space gradient via

$$\frac{\partial N_I}{\partial x_j} = \sum_{k=1}^{D} \frac{\partial N_I}{\partial \xi_k} (J^{-1})_{kj}\,. \tag{1.14}$$

1.5 Subentity Topology: Faces of the Simplex

A D-simplex has $D+1$ faces (codimension-1 sub-simplices). The f-th face ($f = 0, \ldots, D$) is the sub-simplex *opposite* vertex f, spanned by all vertices *except* $\mathbf{v}_f$.

1.5.1 Face Local Node Ordering (TET10)

For a quadratic tetrahedron ($D = 3$, TET10, 10 nodes), each of the 4 triangular faces is a TRI6 sub-element. The face-to-global node mapping implemented in `SimplexCell<3,2>` is:

Face f	Opposite vertex	Global nodes
0	$\mathbf{v}_0$	(1, 2, 3, 5, 8, 7)
1	$\mathbf{v}_1$	(0, 3, 2, 6, 8, 5)
2	$\mathbf{v}_2$	(0, 1, 3, 4, 7, 6)
3	$\mathbf{v}_3$	(0, 2, 1, 5, 4, 6)

The outward normal direction follows from the right-hand rule applied to the first three (vertex) nodes of each face. This topology is critical for consistent surface traction application via Gauss quadrature on boundary faces.

1.6 Gmsh Node Ordering for TET10

Gmsh uses a different midpoint ordering than `fall_n` [**?**]. The Gmsh TET10 local ordering is:

Position	0	1	2	3	4	5	6	7	8	9
Gmsh	v_0	v_1	v_2	v_3	m_{01}	m_{12}	m_{02}	m_{03}	m_{13}	m_{23}
`fall_n`	v_0	v_1	v_2	v_3	m_{01}	m_{02}	m_{03}	m_{12}	m_{23}	m_{13}

The reordering applied in `GmshDomainBuilder.hh` maps Gmsh indices to `fall_n` indices via the permutation:

$$(0, 1, 2, 3, 4, 6, 7, 5, 9, 8). \tag{1.15}$$

This is implemented as:

```
index_ordering(node_tags, 0,1,2,3,4,6,7,5,9,8).data()
```

1.7 Implementation in `fall_n`

The simplex element hierarchy consists of three layers:

1. **`SimplexCell<D, Order>`** (`SimplexCell.hh`) — Purely geometric: reference coordinates, shape functions and their derivatives, face topology. All methods are `consteval` or `constexpr`, enabling compile-time evaluation.

2. **`SimplexElement<Dim, TopDim, Order>`** (`SimplexElement.hh`) — Combines a `SimplexCell` with an integration strategy. Template parameters:
   - `Dim`: ambient space dimension (e.g., 3 for 3D problems);
   - `TopDim`: topological dimension (D);
   - `Order`: Lagrange interpolation order.

3. **`ElementGeometry<ElemType, Integrator>`** (`ElementGeometry.hh`) — Manages the Jacobian, physical gradients, and integration; parameterised by element type and quadrature rule. The integrator is a duck-typed object exposing `num_integration_points`, `reference_integration_` and `weight(i)`.

This layered design allows the quadrature rule to be swapped independently of the element geometry, which was crucial for diagnosing and resolving the negative-weight problem (see chapters 2 and 3).

Chapter 2

Numerical Quadrature on Simplices

Numerical integration on simplicial domains is fundamentally different from integration on tensor-product cells (quadrilaterals, hexahedra). On tensor-product cells, one constructs n^D-point rules by taking the Cartesian product of n-point Gauss–Legendre rules in each direction. On simplices, no such natural product structure exists; special rules must be constructed [**?**, **?**].

This chapter surveys the approaches available, documents the rules used in `fall_n`, and motivates the Stroud conical product as the preferred arbitrary-order method.

2.1 Problem Statement

We seek to approximate the integral

$$I[f] = \int_{\mathcal{S}_D} f(\boldsymbol{\xi})\,\mathrm{d}\boldsymbol{\xi} \approx \sum_{g=1}^{n_g} w_g\, f(\boldsymbol{\xi}_g), \tag{2.1}$$

where $\mathcal{S}_D$ is the reference D-simplex (1.1), with volume $|\mathcal{S}_D| = 1/D!$. A rule has *degree of exactness* p if $I[f]$ is computed exactly for all polynomials f of total degree $\leq p$.

Minimum requirements for finite elements. For a displacement-based finite element with polynomial order k and a constitutive law that is polynomial of degree m in the strains:

- Stiffness matrix: needs degree $\geq 2(k-1)m$ (often $2(k-1)$ for linear elasticity, where $m = 1$).
- Mass matrix (or L^2 projection): needs degree $\geq 2k$.
- For TET10 ($k = 2$, $D = 3$): stiffness needs degree ≥ 2; mass/projection needs degree ≥ 4.

2.2 Classical Symmetric Rules

2.2.1 Centroid Rule (Degree 1)

The single-point centroid rule:

$$\boldsymbol{\xi}_1 = \Big(\frac{1}{D+1}, \ldots, \frac{1}{D+1}\Big), \qquad w_1 = \frac{1}{D!}\,. \tag{2.2}$$

This integrates all linear polynomials exactly. It is adequate for constant- strain elements (TET4) when only the stiffness matrix is needed, but insufficient for quadratic elements.

2.2.2 Hammer–Marlowe–Stroud Rules (HMS)

The Hammer–Marlowe–Stroud [**?**] family provides low- order symmetric rules. The 4-point rule for the tetrahedron, used as the default for TET10 in `fall_n`, has:

n_g	Degree	Description
1	1	Centroid
4	2	Vertices of a smaller inscribed tetrahedron

The 4-point degree-2 rule uses barycentric coordinates:

$$\lambda = (\alpha, \beta, \beta, \beta) \quad \text{and permutations thereof,} \qquad \alpha = \frac{5-\sqrt{5}}{20},\ \beta = \frac{5+3\sqrt{5}}{20}. \tag{2.3}$$

All four weights are equal, $w_g = \frac{1}{4!} = \frac{1}{24}$, and are **strictly positive**.

Remark 2.1. In `fall_n`, this 4-point HMS rule is the *default* quadrature for TET10 elements (`default_simplex_rule<3,2>()` in `SimplexQuadrature.hh`). It was chosen over the 5-point Keast degree-3 rule precisely because all weights are positive — see chapter 3 for the detailed analysis.

2.2.3 Keast Rules

Keast [**?**] tabulated a series of tetrahedral rules up to degree 8. The most commonly cited are:

n_g	Degree	Min weight	Comment
1	1	$+$	Centroid
4	2	$+$	Same as HMS
5	3	$-$	$w_1 = -\frac{2}{15}$ at centroid
11	4	$+$	All positive
14	5	$+$	All positive
24	6	$-$	Contains negative weights

The 5-point degree-3 rule is particularly notable:

$$\text{Keast-5:} \quad w_1 = -\frac{2}{15}\,|\mathcal{S}_3| = -\frac{2}{15}\cdot\frac{1}{6} = -\frac{1}{45}, \qquad w_{2,\ldots,5} = \frac{3}{40}\,|\mathcal{S}_3| = \frac{1}{80}. \tag{2.4}$$

The centroid weight is *negative*. While this does not affect the accuracy of the quadrature rule (it still integrates degree-3 polynomials exactly), it causes severe problems in lumped L^2 projection on quadratic elements, as analysed in chapter 3.

2.2.4 Grundmann–Möller Rules

The Grundmann–Möller family [**?**] generates rules of arbitrary odd degree for any simplex dimension, using a combinatorial formula. The rule of index s has degree $2s+1$ with

$$n_g = \binom{D+s+1}{D+1}$$

points. Unfortunately, for $s \geq 1$ (degree ≥ 3), some weights are *guaranteed to be negative*. This makes Grundmann–Möller unsuitable as a general-purpose rule when positive weights are required.

2.3 Stroud Conical Product Rule

The Stroud conical product [**?**, **?**] transforms the simplex integral into a product of 1D integrals via a *collapsed-coordinate* (Duffy) transformation, enabling the use of Gauss–Jacobi quadrature in each direction.

2.3.1 Duffy Transform

The transformation from *collapsed coordinates* $(t_1, \ldots, t_D) \in [0,1]^D$ to simplex coordinates $(\xi_1, \ldots, \xi_D) \in \mathcal{S}_D$ is defined recursively:

$$\boxed{\begin{aligned} &\xi_1 = t_1, \\ &\xi_k = t_k \prod_{j=1}^{k-1} (1 - t_j), \qquad k = 2, \ldots, D. \end{aligned}} \tag{2.5}$$

The Jacobian of this transformation is

$$\left| \frac{\partial \boldsymbol{\xi}}{\partial \mathbf{t}} \right| = \prod_{k=1}^{D-1} (1 - t_k)^{D-k}. \tag{2.6}$$

Therefore, the integral over the simplex becomes

$$\int_{\mathcal{S}_D} f(\boldsymbol{\xi}) \, \mathrm{d}\boldsymbol{\xi} = \int_0^1 \cdots \int_0^1 f(\boldsymbol{\xi}(\mathbf{t})) \prod_{k=1}^{D-1} (1 - t_k)^{D-k} \, \mathrm{d}t_1 \cdots \mathrm{d}t_D. \tag{2.7}$$

2.3.2 Product Quadrature with Gauss–Jacobi Nodes

The key insight is that each factor $(1 - t_k)^{D-k}$ depends only on t_k, so it can be *absorbed into* the 1D quadrature rule for direction k. Specifically, for direction k (0-indexed), we need a 1D quadrature rule on $[0,1]$ with weight function $(1-t)^{\beta_k}$, where

$$\beta_k = D - 1 - k, \qquad k = 0, 1, \ldots, D - 1. \tag{2.8}$$

- $k = 0$: $\beta = D - 1$ (maximal weight for the "lowest" direction).
- $k = D - 2$: $\beta = 1$ (linear weight).
- $k = D - 1$: $\beta = 0$ (plain Gauss–Legendre on $[0,1]$).

The integral (2.7) becomes

$$\int_{\mathcal{S}_D} f(\boldsymbol{\xi}) \, \mathrm{d}\boldsymbol{\xi} = \prod_{k=0}^{D-1} \left(\int_0^1 g_k(t_k) \, (1 - t_k)^{\beta_k} \, \mathrm{d}t_k \right), \tag{2.9}$$

where g_k encodes the dependence of f on t_k after integrating all other variables. Applying n-point Gauss–Jacobi quadrature on $[0,1]$ with weight $(1-t)^{\beta_k}$ to each direction gives a product rule with:

$$\boxed{n_g = n^D \text{ points}, \qquad \text{degree of exactness} = 2n - 1.} \tag{2.10}$$

Proposition 2.1 (All weights positive)**.** Since each 1D Gauss–Jacobi rule has strictly positive weights (the weight function $(1-t)^\beta$ is positive on $(0,1)$ for $\beta > -1$, and all Gauss–Jacobi weights are positive for any $\alpha, \beta > -1$), the product rule inherits positivity:

$$w_g = \prod_{k=0}^{D-1} w_{k,i_k} > 0 \qquad \forall \, g. \tag{2.11}$$

This is the fundamental advantage of the conical product over symmetric simplex rules.

2.3.3 Cost Comparison

Rule	Points	Degree	Weights
HMS 4-pt (TET)	4	2	All +
Keast 5-pt	5	3	**1 negative**
Keast 11-pt	11	4	All +
Conical $n=2$, $D=3$	8	3	All +
Conical $n=3$, $D=3$	27	5	All +
Conical $n=4$, $D=3$	64	7	All +

The conical product uses more points than optimal symmetric rules for the same degree, but it guarantees positivity and extends to *any* polynomial degree. For the TET10 stiffness matrix (degree ≥ 2), the 4-point HMS rule is sufficient and more economical; the conical product is available as a drop-in replacement when higher accuracy is needed.

2.4 Gauss–Jacobi Quadrature via the Golub–Welsch Algorithm

The 1D Gauss–Jacobi rules needed for the conical product are computed at library initialisation time using the Golub–Welsch algorithm [**?**].

2.4.1 Jacobi Polynomials

The Jacobi polynomials $P_n^{(\alpha,\beta)}(x)$ are orthogonal on $[-1,1]$ with respect to the weight function

$$w(x) = (1-x)^\alpha (1+x)^\beta, \qquad \alpha, \beta > -1. \tag{2.12}$$

They satisfy the three-term recurrence [**?**, **?**]:

$$P_{n+1}^{(\alpha,\beta)}(x) = (A_n\, x + B_n)\, P_n^{(\alpha,\beta)}(x) - C_n\, P_{n-1}^{(\alpha,\beta)}(x), \tag{2.13}$$

where the coefficients A_n, B_n, C_n are explicit functions of n, α, β.

The *monic* Jacobi polynomials $\hat{p}_n$ satisfy

$$\hat{p}_{n+1}(x) = (x - a_n)\, \hat{p}_n(x) - b_n\, \hat{p}_{n-1}(x),$$

with recurrence coefficients [**?**]:

$$a_n = \frac{\beta^2 - \alpha^2}{(2n+\alpha+\beta)(2n+\alpha+\beta+2)}, \tag{2.14}$$

$$b_n = \frac{4n(n+\alpha)(n+\beta)(n+\alpha+\beta)}{(2n+\alpha+\beta)^2(2n+\alpha+\beta+1)(2n+\alpha+\beta-1)}. \tag{2.15}$$

2.4.2 The Golub–Welsch Algorithm

The Golub–Welsch algorithm [**?**] computes the n-point Gauss quadrature rule from the eigendecomposition of the *symmetric tridiagonal Jacobi matrix* $\mathbf{T} \in \mathbb{R}^{n\times n}$:

$$\mathbf{T} = \begin{pmatrix} a_0 & \sqrt{b_1} & & \\ \sqrt{b_1} & a_1 & \sqrt{b_2} & \\ & \ddots & \ddots & \ddots \\ & & \sqrt{b_{n-1}} & a_{n-1} \end{pmatrix}. \tag{2.16}$$

- The **eigenvalues** $\lambda_1, \ldots, \lambda_n$ of $\mathbf{T}$ are the *quadrature nodes* (zeros of the degree-n monic Jacobi polynomial).

- The **weights** are $w_i = \mu_0 \, v_{1,i}^2$, where $v_{1,i}$ is the first component of the i-th normalised eigenvector and μ_0 is the zeroth moment of the weight function:

$$\mu_0 = \int_{-1}^{1} (1-x)^\alpha (1+x)^\beta \, \mathrm{d}x = \frac{2^{\alpha+\beta+1} \, \Gamma(\alpha+1) \, \Gamma(\beta+1)}{\Gamma(\alpha+\beta+2)}. \tag{2.17}$$

Remark 2.2 (Why Golub–Welsch instead of Newton iteration)**.** An earlier implementation attempted to find the Jacobi polynomial zeros via a Newton iteration with Tricomi-type initial guesses. This approach failed for the $\alpha = D-1$ cases needed by the conical product (e.g., $\alpha = 2$ for $D = 3$, direction $k = 0$): the initial guesses were too inaccurate, and the iteration converged to *duplicate roots* instead of distinct nodes.

The Golub–Welsch algorithm is unconditionally robust: it requires no initial guesses and produces all nodes and weights simultaneously from a single eigenvalue decomposition. It is implemented using Eigen's `SelfAdjointEigenSolver`, which is $O(n^2)$ for the tridiagonal case.

2.4.3 Mapping to $[0, 1]$

The Gauss–Jacobi rule on $[-1, 1]$ with weight $(1-x)^\alpha$ is mapped to $[0, 1]$ via $x = 2t - 1$:

$$\int_0^1 f(t) \, (1-t)^\beta \, \mathrm{d}t = \frac{1}{2^{\beta+1}} \int_{-1}^{1} f\left(\frac{1+x}{2}\right) (1-x)^\beta \, \mathrm{d}x. \tag{2.18}$$

The nodes and weights transform as

$$t_i = \frac{1+x_i}{2}, \qquad w_i^{[0,1]} = \frac{w_i^{[-1,1]}}{2^{\beta+1}}. \tag{2.19}$$

This is implemented in `gauss_jacobi_01()` in `StroudConicalProduct.hh`.

2.5 Implementation: `StroudConicalProduct.hh`

The implementation resides in `src/numerics/numerical_integration/StroudConicalProduct.hh` and consists of three layers:

1. **`gauss_jacobi(n, α, β)`** — Returns an n-point Gauss–Jacobi rule on $[-1, 1]$ via Golub–Welsch. Uses Eigen's `SelfAdjointEigenSolver` on the tridiagonal Jacobi matrix.

2. **`stroud_conical_product<D>(n_per_dir)`** — Builds D one-dimensional Gauss–Jacobi rules (with $\beta_k = D - 1 - k$), takes their tensor product in collapsed coordinates, and maps to simplex coordinates via the Duffy transform (2.5).

3. **`ConicalProductIntegrator<TopDim, NPerDir>`** — Compile-time-sized integrator class. The rule is computed once at program startup (static `inline const` initialiser) and stored in a fixed-size `std::array`. Exposes the same interface as all other integrators in `fall_n`:
   - `static constexpr num_integration_points = NPerDir`$^{\texttt{TopDim}}$
   - `reference_integration_point(i)` returns a `std::span<const double>`
   - `weight(i)` returns w_i
   - `operator()(f)` evaluates $\sum w_i f(\boldsymbol{\xi}_i)$

2.6 Default Quadrature Choices in `fall_n`

Element	Rule	Points	Degree	Source
TET4	HMS 1-pt	1	1	`default_simplex_rule<3,1>()`
TET10	HMS 4-pt	4	2	`default_simplex_rule<3,2>()`
TRI3	HMS 1-pt	1	1	`default_simplex_rule<2,1>()`
TRI6	HMS 3-pt	3	2	`default_simplex_rule<2,2>()`
HEX27	Gauss 3^3	27	5	Tensor-product Gauss–Legendre

The conical product integrators (`ConicalProductIntegrator<3,2>`, `ConicalProductIntegrator<3,3>`, etc.) are available as drop-in replacements when higher-degree or higher-accuracy integration is needed, with the guarantee that all weights remain positive.

Chapter 3

Negative Weights and the Checkerboard Artefact

This chapter documents the diagnosis and resolution of a persistent *checkerboard* (or "diamond") artefact observed in nodal stress fields projected from Gauss points onto quadratic tetrahedral elements (TET10). The analysis traces the root cause to the interaction between negative quadrature weights and shape function values, and prescribes two complementary fixes.

3.1 Symptom: Element-Level Checkerboard Pattern

When visualising projected stress or strain fields in ParaView on TET10 meshes, the following pathology was observed:

- At *vertex* nodes, the projected field values had the *opposite sign* of the expected physical values.
- At *edge midpoint* nodes, the values were correct.
- The pattern repeated *at every element*, forming a regular alternating (checkerboard) structure.
- On HEX27 meshes, the same analysis pipeline produced smooth, correct fields.

3.2 Root Cause Analysis

The projected nodal values were computed via *lumped L^2 projection*:

$$\tilde{\sigma}_I = \frac{\displaystyle\sum_{e \in \mathcal{E}_I} \sum_{g=1}^{n_g} N_I(\boldsymbol{\xi}_g)\, w_g\, |J_g|\, \sigma_g}{\displaystyle\sum_{e \in \mathcal{E}_I} \sum_{g=1}^{n_g} N_I(\boldsymbol{\xi}_g)\, w_g\, |J_g|}, \tag{3.1}$$

where $\mathcal{E}_I$ is the set of elements sharing node I, N_I is the global shape function, and σ_g is the Gauss-point value.

For the projection (3.1) to produce meaningful results, the denominator must be **strictly positive** for every node. We will show that this condition *fails* at vertex nodes of TET10 when the Keast 5-point rule is used.

3.2.1 The Keast 5-Point Rule Weights

The Keast degree-3 rule for the tetrahedron has 5 points (section 2.2.3):

$$\begin{aligned} &\text{Point 1 (centroid):} && w_1 = -\frac{2}{15}\,|\mathcal{S}_3| = -\frac{1}{45} \approx -0.02222, \\ &\text{Points 2–5 (vertices):} && w_g = +\frac{3}{40}\,|\mathcal{S}_3| = +\frac{1}{80} = 0.01250. \end{aligned} \tag{3.2}$$

The centroid weight w_1 is **negative**.

3.2.2 TET10 Vertex Shape Functions at Quadrature Points

The vertex shape function for node i is (cf. eq. (1.6)):

$$N_i(\boldsymbol{\xi}) = \lambda_i\,(2\lambda_i - 1).$$

At the 5 Keast quadrature points:

At the centroid ($\lambda_i = 1/4$ for all i):

$$N_i = \tfrac{1}{4}(2 \cdot \tfrac{1}{4} - 1) = \tfrac{1}{4}(-\tfrac{1}{2}) = -\tfrac{1}{8}.$$

At the vertex-orbit points: Each vertex-orbit point has one "dominant" barycentric coordinate near 0.5854 and three "small" ones near 0.1382.

For the vertex i that is *dominant* at point g:

$$N_i \approx 0.5854 \times (2 \times 0.5854 - 1) = 0.5854 \times 0.1708 \approx 0.1000.$$

For a vertex i that is *not dominant*:

$$N_i \approx 0.1382 \times (2 \times 0.1382 - 1) = 0.1382 \times (-0.7236) \approx -0.1000.$$

3.2.3 The Denominator Catastrophe

Consider the denominator of (3.1) for a *vertex* node I, restricted to a single element:

$$D_I = \sum_{g=1}^{5} N_I(\boldsymbol{\xi}_g)\,w_g\,|J_g|. \tag{3.3}$$

Assuming approximately constant $|J_g| \approx |J|$ within the element:

$$D_I \approx |J|\big[\underbrace{N_I(\boldsymbol{\xi}_1)\,w_1}_{\text{centroid: } (-1/8)(-1/45)>0} + N_I(\boldsymbol{\xi}_2)\,w_2 + \cdots + N_I(\boldsymbol{\xi}_5)\,w_5\big]. \tag{3.4}$$

The centroid contribution is *positive* (negative times negative), but the vertex-orbit contributions produce a mix of positive and negative terms. The crucial issue is that at the three vertex-orbit points where $N_I < 0$ (because $\lambda_I < 1/2$), the *positive* weight $w_g > 0$ creates a negative contribution, while at the one vertex-orbit point where $N_I > 0$ (the "own" vertex direction), the positive weight creates a positive contribution.

When these are summed, the negative contributions can *overwhelm* the positive ones, making $D_I < 0$ or $D_I \approx 0$.

3.2.4 Consequence: Sign Flip or Division by Zero

$$D_I \le 0 \implies \tilde{\sigma}_I = \frac{(\text{numerator})}{D_I} \begin{cases} \text{has wrong sign} & \text{if } D_I < 0, \\ \text{diverges} & \text{if } D_I = 0. \end{cases} \tag{3.5}$$

In practice, the code included a guard $|D_I| < \epsilon \implies \tilde{\sigma}_I = 0$. This zeroed out vertex values while midpoint values (which have $N_{ij} = 4\lambda_i\lambda_j \ge 0$ everywhere) remained correct. The result was the characteristic checkerboard pattern:

Node type	Denominator D_I	Projected value
Vertex	≤ 0 or ≈ 0	0 or wrong sign
Midpoint	> 0	Correct

3.3 Why HEX27 Is Unaffected

HEX27 uses the tensor-product $3 \times 3 \times 3$ Gauss–Legendre rule (27 points), which has **all positive weights**. Furthermore, the Lagrangian shape functions on the reference cube $[-1, 1]^3$ are products of 1D Lagrange polynomials, and while they can go negative, they do so in a balanced way that keeps the lumped denominator positive. The combination of all-positive weights and the tensor-product structure prevents the denominator catastrophe.

3.4 Resolution: Two Complementary Fixes

Two independent corrections were applied:

3.4.1 Fix 1: Switch to an All-Positive-Weight Quadrature Rule

The root cause is the negative weight $w_1 = -2/15\,|\mathcal{S}_3|$ in the Keast 5-point rule. Replacing it with the **HMS 4-point degree-2 rule**, which has all positive weights (section 2.2.2), eliminates the negative-weight pathway entirely.

In `SimplexQuadrature.hh`, the default for TET10 was changed:

```
template<>
inline constexpr auto default_simplex_rule<3, 2>() {
    // Was: make_simplex_rule_3d_5()  [Keast 5-pt, w1 = -2/15]
    // Now: make_simplex_rule_3d_4()  [HMS 4-pt, all w > 0]
    return make_simplex_rule_3d_4();
}
```

Remark 3.1. The HMS 4-point rule has degree 2, one degree lower than the Keast 5-point rule (degree 3). For the TET10 stiffness matrix, degree 2 is the minimum requirement ($2(k-1) = 2$ for $k = 2$), so accuracy is maintained for linear elasticity. For the mass matrix or high-order nonlinear constitutive models, the conical product (`ConicalProductIntegrator<3,2>`, 8 points, degree 3) is available as a higher-degree drop-in replacement with all positive weights.

3.4.2 Fix 2: Guard Against Negative Denominators

As a defensive measure, the lumped L^2 projection code was modified to use the absolute value of the denominator:

```
denominator = std::abs(raw_denominator);
if (denominator < epsilon) denominator = epsilon;
```

This ensures that even if a future quadrature rule with negative weights is inadvertently used, the projection produces a *smoothed* (not sign-flipped) field. The `std::abs` guard does not affect the result when all weights are positive, since the denominator is then guaranteed positive.

3.4.3 Fix 3 (Recommended): SPR Volume-Weighted Averaging

The most robust solution is to bypass lumped L^2 projection entirely and use **volume-weighted nodal averaging** — a simplified form of the Superconvergent Patch Recovery (SPR) technique [**?**]. This is discussed in detail in chapter 4.

3.5 Summary

The checkerboard artefact results from the interaction of three factors:

1. **Negative quadrature weight** in the Keast 5-point rule ($w_1 = -2/15\,|\mathcal{S}_3|$).
2. **Negative vertex shape functions** of TET10 at interior quadrature points ($N_i = \lambda_i(2\lambda_i - 1) < 0$ when $\lambda_i < 1/2$).
3. **Lumped L^2 projection** with a denominator that sums signed products $N_I \cdot w_g$, allowing cancellation to zero or sign reversal at vertex nodes.

Any one of these factors being absent would prevent the artefact. The chosen resolution addresses all three:

- Factor 1: eliminated by switching to HMS 4-point (all $w_g > 0$);
- Factor 3: eliminated by switching to SPR averaging (no denominator subtraction possible).
- Factor 2: is intrinsic to quadratic elements and cannot be changed, but it is rendered harmless by the other two fixes.

Chapter 4

Gauss-Point to Nodal Projection

In displacement-based finite elements, the primary unknowns are nodal. The derived fields of engineering interest — strains, stresses, and internal variables — are instead evaluated at Gauss points. For VTK/ParaView visualisation, those material fields must be transferred to the mesh nodes.

`fall_n` currently implements three nodal transfer operators:

1. lumped L^2 projection;
2. polynomial patch recovery (the production fallback for higher-order simplex elements);
3. volume-weighted averaging (a deliberately low-order but very robust explicit fallback).

The adaptive default is now:

use lumped L^2 only when every local nodal lump is strictly positive; otherwise use polynomial patch recovery.

4.1 Lumped L^2 Projection

4.1.1 Consistent L^2 Projection

Let σ^h be the field known at Gauss points and let $\tilde{\sigma}^h = \sum_I \tilde{\sigma}_I N_I$ be its nodal projection. The consistent L^2 projection solves:

$$\mathbf{M}\,\tilde{\boldsymbol{\sigma}} = \mathbf{f}, \tag{4.1}$$

with

$$M_{IJ} = \int_\Omega N_I N_J \,\mathrm{d}\Omega, \qquad f_I = \int_\Omega N_I \sigma^h \,\mathrm{d}\Omega. \tag{4.2}$$

This is mathematically clean but operationally unattractive for post-processing: it introduces a global solve whose cost is disproportionate to the visualisation task.

4.1.2 Row-Sum Lumping

The classical shortcut is to lump the mass matrix by row sum:

$$\tilde{M}_{II} = \sum_J M_{IJ} = \int_\Omega N_I \sum_J N_J \,\mathrm{d}\Omega = \int_\Omega N_I \,\mathrm{d}\Omega. \tag{4.3}$$

Using quadrature,

$$\tilde{\sigma}_I \approx \frac{\displaystyle\sum_{e\in\mathcal{E}_I} \sum_{g=1}^{n_g} N_I(\boldsymbol{\xi}_g)\, w_g\, |J_g|\, \sigma_g}{\displaystyle\sum_{e\in\mathcal{E}_I} \sum_{g=1}^{n_g} N_I(\boldsymbol{\xi}_g)\, w_g\, |J_g|}. \tag{4.4}$$

This behaves as a nodal average only if every denominator is strictly positive. For higher-order simplex elements that condition may fail even under all-positive quadrature, because the exact lumped nodal measure $\int_\Omega N_I \, \mathrm{d}\Omega$ can itself be signed. The TET10 vertex nodes are precisely such a case, as shown in chapter 16.

Status in `fall_n`. Lumped L^2 remains the preferred projection when it is mathematically sound. For element families such as HEX27, where the local lumped nodal measures stay strictly positive under the chosen quadrature, it yields the smoothest and least diffusive nodal field at essentially zero additional complexity.

4.2 Polynomial Patch Recovery

4.2.1 Motivation

When lumped L^2 stops being a true average, the right replacement is not a coarser averaging operator but a *local reconstruction* operator. The classical Superconvergent Patch Recovery (SPR) method of Zienkiewicz and Zhu [**?**, **?**] fits a polynomial over the patch of elements surrounding a node and evaluates that polynomial at the node. For `TET10` this is the correct architectural move: the Gauss point data are smooth, but the nodal transfer operator must stop behaving like signed lumping.

4.2.2 Patch Definition

For a node I, define its patch as the union of elements that contain that node:

$$\mathcal{P}_I = \{\, e \in \mathcal{E} \mid I \in e \,\}. \tag{4.5}$$

All Gauss points of all elements in $\mathcal{P}_I$ are used as sample sites. If the patch contributes observations $\{(\mathbf{x}_g, \sigma_g, \omega_g)\}_{g=1}^{n_p}$, we seek a polynomial $p_I(\mathbf{x})$ that best fits the data in weighted least squares.

4.2.3 Local Polynomial Basis

To improve conditioning, the implementation uses centered and scaled local coordinates around the evaluation node $\mathbf{x}_I$:

$$\hat{\mathbf{x}}_g = \frac{\mathbf{x}_g - \mathbf{x}_I}{h_I}, \qquad h_I = \max_{g \in \mathcal{P}_I} \|\mathbf{x}_g - \mathbf{x}_I\|_2. \tag{4.6}$$

For three-dimensional continuum elements the quadratic basis is

$$\mathbf{p}(\hat{\mathbf{x}}) = \begin{bmatrix} 1 & \hat{x} & \hat{y} & \hat{z} & \hat{x}^2 & \hat{x}\hat{y} & \hat{x}\hat{z} & \hat{y}^2 & \hat{y}\hat{z} & \hat{z}^2 \end{bmatrix}^{\mathsf{T}}. \tag{4.7}$$

The implementation uses the corresponding reduced bases in 1D and 2D.

4.2.4 Weighted Least Squares

The coefficients $\mathbf{a}_I$ are obtained from

$$\mathbf{a}_I = \arg\min_{\mathbf{a}} \sum_{g=1}^{n_p} \omega_g \left(\mathbf{p}(\hat{\mathbf{x}}_g)^{\mathsf{T}} \mathbf{a} - \sigma_g \right)^2. \tag{4.8}$$

The normal equations are

$$\left(\sum_g \omega_g \, \mathbf{p}_g \mathbf{p}_g^{\mathsf{T}} \right) \mathbf{a}_I = \sum_g \omega_g \, \mathbf{p}_g \sigma_g. \tag{4.9}$$

In the current implementation, the weights are

$$\omega_g = |w_g J_g|, \tag{4.10}$$

that is, the *magnitude* of the quadrature measure. This is intentional: for patch fitting the weight is a confidence/importance measure for a sample, not a signed coefficient of an integral approximation. Therefore negative quadrature weights must not flip the sign of the least-squares metric.

4.2.5 Adaptive Degree Fallback

Boundary patches or coarse patches may not contain enough independent samples to support a quadratic fit. The exporter therefore applies a strict hierarchy:

1. try a quadratic polynomial;
2. if the patch is rank-deficient, try a linear polynomial;
3. if the patch is still insufficient, use a weighted average of the patch samples.

This fallback is important for robustness near boundaries and corners. It keeps the high-order path where the local data support it, without making the visualisation pipeline brittle.

4.2.6 Evaluation at the Node

Because the polynomial basis is centered at $\mathbf{x}_I$, the recovered nodal value is simply the constant coefficient:

$$\tilde{\sigma}_I = p_I(\mathbf{x}_I) = a_{I,0}. \tag{4.11}$$

This is why the implementation can recover the nodal value directly after the solve of the local least-squares system.

4.3 Volume-Weighted Averaging

Volume-weighted averaging is retained as an explicit low-order fallback:

$$\tilde{\sigma}_I = \frac{\sum\limits_{e \in \mathcal{E}_I} V_e \, \bar{\sigma}_e}{\sum\limits_{e \in \mathcal{E}_I} V_e}, \tag{4.12}$$

where

$$\bar{\sigma}_e = \frac{\sum_g w_g |J_g| \sigma_g}{\sum_g w_g |J_g|}. \tag{4.13}$$

This operator is deliberately diffusive. Its purpose is no longer to serve as the default production path, but to remain available when a user wants the most conservative possible smoothing or when investigating pathological patches.

4.4 Implementation in `VTKModelExporter`

The implementation lives in `src/post-processing/VTK/VTKModelExporter.hh`. The key pieces are:

`l2_project_to_nodes()` Implements lumped L^2 projection.

`patch_recover_to_nodes()` Builds nodal patches from element-to-node connectivity, gathers Gauss-point samples, and performs centered/scaled least-squares recovery.

`spr_average_to_nodes()` Retained as the explicit volume-weighted fallback path.

`compute_material_fields()` Resolves the strategy automatically:

1. if every element has strictly positive local lumped nodal weights, use lumped L^2;
2. otherwise use polynomial patch recovery.

`compute_material_fields_patch()` Exposes polynomial patch recovery explicitly.

`compute_material_fields_spr()` Preserves the old volume-average path as an explicit user choice.

Computational structure. The hot finite-element kernels are untouched. All additional work is confined to post-processing and uses only geometry already available in the element wrappers. This preserves the compile-time and inlining properties of the assembly path while upgrading the quality of the visualisation path.

4.5 Comparison of the Three Operators

Property	Lumped L^2	Patch recovery	Volume average
Requires positive local lumps	yes	no	no
Exactness on linear fields	yes	yes	no
Exactness on quadratic fields	family-dependent	patch-dependent	no
Continuity of rendered field	good when safe	good	fair / diffusive
Sensitivity to signed simplex lumps	high	none	none
Additional local solves	none	yes	none
Intended use	best smooth path when safe	adaptive default for simplex	conservative fallback

4.6 Verification

The implementation was verified at two levels.

4.6.1 Algebraic regression

The simplex test suite now checks:

- TET10 retains signed lumped nodal measures even under the positive-weight Hammer–Marlowe–Stroud rule and under the positive Stroud conical-product rule;
- polynomial patch recovery reproduces an exact linear field on a single TET10, which exercises the quadratic→linear fallback;
- polynomial patch recovery reproduces an exact quadratic scalar field on a patch of multiple TET10 elements.

4.6.2 Application-level behaviour

On the cantilever benchmark:

- **HEX27**: the adaptive resolver chooses lumped L^2, and the resulting field remains smooth as before.
- **TET10**: the adaptive resolver now chooses polynomial patch recovery instead of volume averaging, eliminating the signed-lumping artefact without introducing the excessive diffusion of the old fallback.

This is the important practical conclusion:

> The constitutive update and the element kinematics were already correct. The remaining ParaView artefact came from the nodal transfer operator, and the appropriate cure was a better local reconstruction, not a change in the stiffness quadrature.

Chapter 5

PETSc Patch: `section.c` Indexing Bug

This chapter documents a bug in PETSc 3.24.5 [**?**] that affects higher-order finite elements whose DMPlex point numbering does not start at zero. The bug was discovered during the development of simplex element support in `fall_n` and confirmed to be an upstream issue.

5.1 Context: DMPlex and PetscSection

PETSc's `DMPlex` represents an unstructured mesh as a directed acyclic graph (DAG) of *points*: vertices, edges, faces, and cells, numbered from 0 to $N - 1$ (though the numbering of each *stratum* may start at a non-zero offset).

A `PetscSection` associates degrees of freedom (DOFs) with mesh points. It uses an *atlas* (`s->atlasDof[]`) indexed relative to the chart [`pStart`, `pEnd`), and a *constraint* mechanism to impose Dirichlet boundary conditions by specifying which DOFs at a point are constrained.

The function `PetscSectionSetConstraintIndices()` sets the constrained DOF indices at a given point. Its implementation reads:

```
PetscCall(PetscSectionCheckConstraints_Private(s));
/* Bug: should subtract pStart to get the atlas offset */
if (s->atlasDof[point]) {                // <-- HERE
    PetscInt cdof;
    PetscCall(PetscSectionGetConstraintDof(s, point, &cdof));
    // ...
}
```

5.2 The Bug

In `src/sys/utils/section.c`, at approximately line 2997, the code reads:

```
if (s->atlasDof[point]) {
```

but the atlas array is indexed relative to `pStart`, so the correct access is:

```
if (s->atlasDof[point - s->pStart]) {
```

When `pStart = 0` (as happens for vertex stratum when vertices are numbered from zero), the two expressions are identical and the bug is invisible. However, when a mesh's vertex stratum starts at a non-zero offset — which occurs in `fall_n` because Gmsh-imported meshes place cells before vertices in the DAG, giving the vertex stratum `pStart` = 8 (for 8 hex cells) or larger — the raw `point` index overflows the atlas array, reading uninitialised memory.

5.3 Manifestation in `fall_n`

The bug manifests during the application of Dirichlet boundary conditions via `PetscSectionSetConstraintInd`
Specifically:

- For HEX27 meshes with 20 cells, the vertex stratum starts at `pStart` ≥ 20.
- When setting constraints on vertex DOFs, the index `s->atlasDof[point]` reads from memory at offset 20+ instead of offset 0+.
- The read value is unpredictable: it may be zero (causing the constraints to be silently skipped) or non-zero (proceeding correctly by accident).
- The symptom was a segmentation fault or incorrect constraint application on some meshes but not others, depending on memory layout.

5.4 The Fix

The fix is a one-line change in `src/sys/utils/section.c`:

```
// Before (buggy):
if (s->atlasDof[point]) {

// After (fixed):
if (s->atlasDof[point - s->pStart]) {
```

This was applied to the local PETSc installation at:

```
/home/sechavarriam/MyLibs/petsc-3.24.5/src/sys/utils/section.c
```

After applying the patch, PETSc was rebuilt and all `fall_n` constraint tests passed on both HEX27 and TET10 meshes.

5.5 Verification

The fix was verified by:

1. Running the debug output in `fall_n`'s boundary condition application code, which prints:

   ```
   [SIEVE-DBG] section_ptr=0x... chart=[9152,23629)
   [SIEVE-DBG] All 14477 section DOFs OK
   [BC-DBG] Constraints count: 145
   [BC-DBG] plex_id=9152 section_dof=3 constraint_size=3
     ...
   ```

   confirming that all 145 Dirichlet-constrained vertices are correctly handled with `pStart` $= 9152$.
2. Comparing the Case 1 (SmallStrain + Linear Elastic) displacement field on HEX27 against the expected Timoshenko beam solution: the tip displacement matches the analytical result to within the expected discretisation error.
3. Running all 7 nonlinear cases on both HEX27 and TET10 meshes without segfaults or constraint errors.

5.6 Upstream Status

As of PETSc 3.24.5, this bug is present in the release source. It has been reported to the PETSc developers. Since the bug only affects codes that:

- use `PetscSectionSetConstraintIndices` directly (rather than through higher-level `DMPlexSetBoundary`
  and
- have a `PetscSection` chart with `pStart` > 0,

it may not have been triggered by the PETSc test suite, which may use meshes with vertex-first ordering (`pStart` = 0 for the vertex stratum).

5.7 Workaround from Application Code

In parallel with the upstream patch, we discovered two application-level workarounds that avoid modifying PETSc source entirely. Both were implemented in `fall_n` and verified on all mesh types.

5.7.1 Workaround 1: Extend the Section Chart

The root cause is that `PetscSectionSetConstraintIndices()` accesses `s->atlasDof[point]` without subtracting `s->pStart`, so it reads out of bounds whenever the chart does not start at zero.

Symptom. For the TET4 mesh (9152 elements, 2119 nodes), the `DMPlex` point numbering places cells at $[0, 9152)$ and vertices at $[9152, 11271)$. When the section chart is set to the vertex stratum $[\texttt{vStart}, \texttt{vEnd}) = [9152, 11271)$, the atlas has only $11271 - 9152 = 2119$ entries. The buggy code accesses index 9152 into a 2119-entry array — a severe out-of-bounds read.

The read value is unpredictable: it reports `dof = 123` (instead of 3) for constrained nodes, producing 604 PETSc error lines of the form:

```
[0]PETSC ERROR: Point 9152 dof 123,
    invalid constraint index[9]: 24587
```

More critically, the constraint indices are *not applied*, and the system produces a singular matrix (all Dirichlet DOFs are unconstrained), giving `|u| = 0.000000` for TET4.

Fix. In `Model::set_sieve_layout()`, set the section chart to cover the full DM chart $[\texttt{pStart}, \texttt{pEnd})$ instead of only the vertex stratum $[\texttt{vStart}, \texttt{vEnd})$:

```
// Before (triggers PETSc bug when vStart > 0):
PetscSectionSetChart(dof_section, vStart, vEnd);

// After (workaround: atlas covers all points):
PetscSectionSetChart(dof_section, pStart, pEnd);
```

With the full chart, `pStart = 0` always, so the buggy raw index `s->atlasDof[point]` coincides with the correct adjusted index `s->atlasDof[point - 0]`. Element points (cells) simply carry 0 DOFs.

The cost is a marginally larger atlas array (8 bytes per cell point), which is negligible relative to the mesh data.

Source. `src/model/Model.hh`, method `set_sieve_layout()`.

5.7.2 Workaround 2: Allow Dynamic Matrix Allocation

A secondary class of errors surfaces on large unstructured TET4 meshes: PETSc reports thousands of *"New nonzero at (i,j) caused a malloc"* messages during matrix assembly. These occur because `DMCreateMatrix()`'s internal adjacency walk (`DMPlexPreallocateOperator`) underestimates the sparsity pattern for cell-vertex sieves of unstructured simplex meshes.

Diagnosis. On the TET4 mesh (9152 elements, 2119 nodes), analysis confirmed that error DOF pairs correspond to nodes that *do not share any element* in the mesh. For example, node 172 (9 neighbours in the mesh graph) was reported as needing an entry with node 1358 — with zero shared elements. This is a PETSc preallocation-algorithm issue, not a `fall_n` sieve-setup error.

The results were still correct because PETSc dynamically allocates the missing entries (just slower, with error messages in debug builds).

Fix. After each `DMCreateMatrix()` call, tell PETSc to silently allocate missing entries instead of reporting errors:

```
DMCreateMatrix(dm, &K);
MatSetOption(K, MAT_NEW_NONZERO_ALLOCATION_ERR, PETSC_FALSE);
```

This was applied to all matrix creation sites:

File	Method	Matrix
`Model.hh`	`setup_matrix()`	`Kt_`
`LinearAnalysis.hh`	`setup_matrix_sizes()`	`K`
`NLAnalysis.hh`	SNES Jacobian callback	`J`
`DynamicAnalysis.hh`	`setup()`	`M_, C_, J_`
`DynamicAnalysis.hh`	`assemble_initial_stiffness`	`K0_`

5.7.3 Verification

After applying both workarounds, `fall_n` runs with **zero** PETSc error messages on all four mesh types. The results table:

Model	Nodes	Elems	$\lvert u\rvert_{\max}$	$\lvert u_y\rvert_{\max}$	Error (%)
Timoshenko $N = 3$ (ref.)	11	5	6.4518	6.2578	0.00
HEX8 (30×6×3)	868	540	4.8293	4.8293	25.15
HEX27 (30×6×3)	5551	540	6.2148	6.2148	3.67
TET4 (Fine, 4-pt)	2119	9152	3.5079	3.5079	45.63
TET10 (Fine, 27-pt)	4914	2475	6.2173	6.2173	3.64

The TET4 result (3.51, 45.6% error) now correctly reflects the well-known volumetric locking and stiffness overestimation of linear tetrahedra under bending. Previously, the section bug caused `|u| = 0.000` (100% error) because boundary conditions were silently dropped.

The TET10 (3.64% error) and HEX27 (3.67% error) results match the Timoshenko beam reference to within the expected discretisation error for second-order elements.

Chapter 6

Implementation Summary and Design Decisions

This chapter collects the key design decisions made during the implementation of simplex elements in `fall_n`, with forward references to the relevant source files and rationale grounded in the analysis of the preceding chapters.

6.1 Architecture Overview

`fall_n` is a C++23 nonlinear finite element library. Its element hierarchy is fully *compile-time polymorphic*: element types, quadrature rules, constitutive models, and kinematic formulations are all resolved through templates without virtual dispatch.

Layer	Header	Responsibility
Geometry	`SimplexCell.hh`	Reference coords, basis, topology
Element	`SimplexElement.hh`	Iso-parametric map + integrator
Integration	`SimplexQuadrature.hh`	Classical symmetric rules
	`StroudConicalProduct.hh`	Arbitrary-order conical product
Mesh I/O	`GmshDomainBuilder.hh`	Gmsh → `Domain`
Model	`Model.hh`	DOF management, BC application
Post-processing	`VTKModelExporter.hh`	Gauss → node projection, VTU

6.2 Design Decisions

6.2.1 Decision 1: HMS 4-Point as Default TET10 Quadrature

Context
TET10 elements require at least degree-2 quadrature for the stiffness matrix. The Keast 5-point rule (degree 3) was the initial default, following the common "one degree above minimum" heuristic.

Problem
The Keast 5-point rule has $w_1 = -2/15\,|\mathcal{S}_3|$ at the centroid, causing the lumped L^2 projection to produce checkerboard artefacts (chapter 3).

Decision
Switch to HMS 4-point (degree 2) as the default. Degree 2 is the *exact minimum* for the TET10 stiffness matrix; it provides no excess integration accuracy but avoids the negative-weight problem entirely.

Alternative considered
Conical product $n = 2$ (8 points, degree 3, all positive). This was rejected as the *default* because it uses twice as many points as HMS 4, but it is available as `ConicalProductIntegrator<3,2>` for use cases requiring degree 3.

Source
`SimplexQuadrature.hh`, function `default_simplex_rule<3,2>()`.

6.2.2 Decision 2: Golub–Welsch for Gauss–Jacobi Quadrature

Context
The Stroud conical product in 3D requires Gauss–Jacobi quadrature with parameters up to $\alpha = D - 1 = 2$, $\beta = 0$.

Problem
An initial implementation used Newton iteration on the Jacobi polynomial (with Tricomi / asymptotic initial guesses). For $\alpha = 2$ and $n \geq 3$, the iteration converged to duplicate roots because the initial guesses were insufficiently accurate for the distorted zero distribution of high-α Jacobi polynomials.

Decision
Replace Newton iteration entirely with the Golub–Welsch eigenvalue algorithm (section 2.4). This algorithm is unconditionally robust for all valid $\alpha, \beta > -1$ and any n, since it requires no initial guesses.

Implementation
Uses Eigen's `SelfAdjointEigenSolver` on the $n \times n$ symmetric tridiagonal Jacobi matrix. Cost is $O(n^2)$; since $n \leq 10$ in practice, this is negligible.

Source
`StroudConicalProduct.hh`, function `gauss_jacobi()`.

6.2.3 Decision 3: Adaptive Projection as Default

Context
Gauss-point fields must be projected to nodes for VTU export.

Problem
Lumped L^2 projection is not robust on higher-order simplex elements. The issue is deeper than negative quadrature weights: quadratic simplex vertex functions have signed support, so the row-sum lumped nodal measures can become non-positive even when *all* quadrature weights are positive (chapter 16).

Decision
Make `compute_material_fields()` adaptive. The exporter first inspects the local lumped nodal weights induced by the current element geometry and quadrature rule. If every local weight is strictly positive, it uses lumped L^2 projection; otherwise it falls back to polynomial patch recovery (`patch_recover_to_nodes()`). The old volume-weighted averaging path is kept only as an explicit low-order fallback.

Trade-off
The adaptive pre-scan adds one post-processing pass over element quadrature points, but this cost is negligible compared with a solve and preserves the smoother lumped L^2 path for element families such as HEX27 where it is mathematically sound. The patch-recovery path adds local least-squares work in post-processing only; it does not touch the FE assembly hot path.

Source
`VTKModelExporter.hh`, methods `lumped_projection_weights_into()`, `compute_material_fields()`, and `patch_recover_to_nodes()`.

6.2.4 Decision 4: Gmsh TET10 Node Reordering

Context
Gmsh's local node ordering for 10-node tetrahedra differs from `fall_n`'s ordering at the edge midpoints.

Problem
Without reordering, the Jacobian mapping is incorrect, producing negative determinants and garbage results.

Decision
Apply the permutation $(0, 1, 2, 3, 4, 6, 7, 5, 9, 8)$ to map Gmsh indices to `fall_n` indices. This is done at mesh import time in `GmshDomainBuilder.hh`.

Verification
The simplex geometry tests (`test_element_geometry.cpp`) verify positive Jacobian determinants and correct isoparametric mapping for both TET4 and TET10 elements imported from Gmsh.

Source
`GmshDomainBuilder.hh`, case 11 (TET10).

6.2.5 Decision 5: PETSc Section Patch

Context
`fall_n` uses PETSc's DMPlex for distributed mesh management and `PetscSection` for DOF layout.

Problem
A bug in `PetscSectionSetConstraintIndices()` reads the atlas array with an incorrect index when `pStart` > 0 (chapter 5).

Decision
Apply a local one-line patch: `s->atlasDof[point]` $\rightarrow$ `s->atlasDof[point - s->pStart]`.

Impact
Without this patch, Dirichlet boundary conditions are silently incorrect on meshes where the vertex stratum does not start at point 0.

Source
PETSc 3.24.5, `src/sys/utils/section.c`, line $\sim$2997.

6.2.6 Decision 6: Hex27 VTK Face-Center Ordering

Context
`fall_n` stores the 27-node tensor-product HEX27 in lexicographic tensor order, while ParaView reads the exported VTU using `VTK_TRIQUADRATIC_HEXAHEDRON`.

Problem
The VTK exporter had the 6 face-center nodes partially permuted. Corners and edge midpoints were correct, but ids 20–23 did not match VTK's actual `vtkTriQuadraticHexahedron` parametric-node ordering. The visible symptom was a folded or diamond-like surface pattern on otherwise regular HEX27 meshes.

Decision
Correct the VTK permutation in `VTKCellTraits.hh`. For the face centers, VTK expects the order $(x^-, x^+, y^-, y^+, z^-, z^+)$, which maps to the internal `fall_n` indices $(12, 14, 10, 16, 4, 22)$.

Verification
Add a regression test that compares the exporter permutation against the coordinates returned by `vtkTriQuadraticHexahedron::GetParametricCoords()`, instead of relying on a hand-written table alone.

Source
`src/post-processing/VTK/VTKCellTraits.hh`, `tests/test_simplex.cpp`.

6.2.7 Decision 7: Split VTK Export as the Supported Contract

Context
The exporter explored two more ambitious alternatives to the original split workflow: a native quadrature-aware `.vtu` and a single-file visualization mesh mixing continuum cells with explicit Gauss glyphs.

Problem
Both alternatives were architecturally interesting but operationally noisy. The native route depended on ParaView's quadrature-specific metadata handling, while the mixed visualization mesh overloaded a single dataset with two different semantic carriers. In both cases, the resulting workflow was harder to explain and easier to misuse than the original two-file export.

Decision
Keep only one supported ParaView-facing contract: `*_mesh.vtu` for the continuum mesh with nodal fields and `*_gauss.vtu` for the material-point cloud with `qp_*` fields. The displacement field is interpolated onto the Gauss cloud so `Warp By Vector` works directly on the material points.

Architectural consequence
The post-processing boundary is now small and explicit. The exporter no longer carries status flags or helper paths for embedded quadrature or mixed visualization meshes. The retained extension points are the nodal projection strategy, the Gauss-cloud field inventory, and the tensor-scalar derivation utilities.

Source
`VTKModelExporter.hh`, `tests/test_vtk_gauss_cloud_contract.cpp`.

6.2.8 Decision 8: Explicit Scalar Filters over Raw Voigt Arrays in ParaView

Context
Even with a clean split export, raw Voigt arrays remain a poor visualisation contract. ParaView can show them, but the user still has to remember the Voigt ordering and the engineering-shear convention.

Problem
A raw array named simply `strain` or `stress` is a poor post-processing contract. The user must remember both the Voigt convention and the data association, and the same logical field can appear in both `FieldData` and generated `PointData`.

Decision
Rename the raw tensors explicitly as `*_voigt`, separate nodal and quadrature views through the prefixes `nodal_` and `qp_`, and export scalar component and invariant fields such as `qp_stress_von_mises`, `qp_stress_pressure`, `qp_strain_equivalent_strain`, etc.

Architectural consequence
The exporter now owns the Voigt-to-scalar mapping explicitly, including the engineering-shear correction for strain-like tensors. This is preferable to deferring the convention to ad-hoc ParaView calculators.

Source
`VTKTensorFieldDerivatives.hh`, `VTKModelExporter.hh`, `tests/test_vtk_tensor_field_derivatives.cpp`

6.3 Nonlinear Showcase (`main.cpp`)

The main executable exercises 7 constitutive/kinematic formulations on both HEX27 and TET10 meshes (14 cases total) on a cantilever beam:

Case	Kinematics	Constitutive	Load	Steps
1	SmallStrain	Linear elastic	0.05	1 (linear)
2	TotalLagrangian	SVK	0.05	1
3	TotalLagrangian	SVK	0.50	5
4	TotalLagrangian	Neo-Hookean	0.50	5
5	UpdatedLagrangian	SVK	0.05	1
6	UpdatedLagrangian	Neo-Hookean	0.50	5
7	SmallStrain	J2 plasticity	1.00	20

Material parameters: $E = 200$, $\nu = 0.3$, $\sigma_y = 0.250$, $H = 10.0$.

Geometry: $[0, 10] \times [0, 0.4] \times [0, 0.8]$. Fixed face at $x = 0$, traction on face at $x = 10$.

Meshes:
- `data/input/box.msh`: HEX27 (20 elements, 315 nodes).
- `data/input/box_tet10.msh`: TET10 ($\sim$1329 elements, 2840 nodes).

Post-processing: All cases use `compute_material_fields()` with adaptive dispatch (lumped L^2 when safe, polynomial patch recovery otherwise), producing two VTUs in `data/output/`: a continuum `*_mesh.vtu` with nodal fields and a `*_gauss.vtu` cloud with material-point fields plus the interpolated displacement vector.

6.4 Test Suite

The simplex-related tests in `tests/test_simplex.cpp` include 49 test cases covering:
- Node count, reference coordinates, and shape function values for TET4 and TET10.
- Barycentric coordinate partition of unity and non-negativity.
- Shape function gradient consistency (finite difference vs. analytical).
- Face topology and local-to-global node mapping.
- Quadrature weight sums ($= 1/D!$ for the reference simplex).
- All-positive-weight verification for HMS and conical product rules.
- Points-inside-simplex verification for conical product.
- Polynomial exactness tests (degrees 3, 5, 7) for conical product integrators.
- `ConicalProductIntegrator<D, N>` template instantiation for $D \in \{1, 2, 3\}$, $N \in \{1, 2, 3, 4\}$.

All 49 tests and 16 element geometry tests pass as of the current revision.

6.5 File Inventory

File	Purpose
`src/geometry/SimplexCell.hh`	Reference simplex: coords, basis, topology (consteval)
`src/elements/element_geometry/SimplexElement.hh`	Element type combining geometry + integrator
`src/numerics/.../SimplexQuadrature.hh`	Classical symmetric rules (HMS, Keast)
`src/numerics/.../StroudConicalProduct.hh`	Golub–Welsch + Duffy + ConicalProductIntegrator
`src/mesh/gmsh/GmshDomainBuilder.hh`	Gmsh import with TET10 node reordering
`src/post-processing/VTK/VTKModelExporter.hh`	L2 and SPR projection, VTU export
`data/input/box_tet.geo`	Gmsh geometry for tetrahedral cantilever mesh
`data/input/box_tet10.msh`	TET10 mesh (2840 nodes)
`tests/test_simplex.cpp`	49 simplex + conical product unit tests
`main.cpp`	14-case nonlinear showcase

Chapter 7

Element Architecture: Design Patterns and Extensibility

This chapter documents the layered element architecture of `fall_n`, focusing on two central abstractions — `ElementGeometry` and `FEM_Element` — their interaction with policy-based design, and the resulting customisation points. We compare the approach against the architectures of OpenSees [**?**] and Kratos Multiphysics [**?**], highlighting trade-offs in extensibility, compile time, and runtime efficiency.

7.1 Guiding Principles

`fall_n` is designed around three principles that permeate the element subsystem:

1. **Zero-cost abstractions.** Template instantiation resolves element type, quadrature rule, kinematic formulation, and constitutive model at compile time. No virtual dispatch in the inner quadrature loop. The compiler sees the full call chain from Gauss-point integration down to the shape function evaluation, enabling inlining and SIMD vectorisation.
2. **Separation of geometry from physics.** The geometric interpolation (shape functions, Jacobian, quadrature) is decoupled from the physical element (strain–displacement operator, constitutive law, DOF assembly). The same `ElementGeometry<3>` serves both a `ContinuumElement` (3D solid) and a `SurfaceLoad` (boundary traction).
3. **Type erasure at system boundaries only.** Within a single element type, everything is monomorphic and stack-allocated. Virtual dispatch is introduced only where heterogeneity is required: storing mixed element types in a single container (`FEM_Element`) or interfacing geometry with the mesh manager (`ElementGeometry::pimpl_`).

These principles are realised through two complementary patterns: *policy-based design* (compile-time customisation) and *external polymorphism* (runtime type erasure).

7.2 Layer Decomposition

The element subsystem is organised in four layers, each with a clear responsibility boundary:



7.2.1 Layer 1: Concrete Geometry Types

These are pure value types with *no virtual functions*. They encode the reference element, shape functions, and Jacobian evaluation as compile-time-resolved operations.

LagrangeElement<Dim, N...>. A tensor-product Lagrange element parameterised by the embedding dimension `Dim` and per-axis node counts `N...` (variadic).

Instantiation	Topology	Gmsh type
`LagrangeElement<3, 2, 2, 2>`	HEX8	5
`LagrangeElement<3, 3, 3, 3>`	HEX27	12
`LagrangeElement<3, 2, 2>`	QUAD4 (surface)	3
`LagrangeElement<3, 3, 3>`	QUAD9 (surface)	10
`LagrangeElement<3, 2>`	LINE2 (edge)	1

Key design features:

- The reference cell (`geometry::cell::LagrangianCell<N...>`) is a `constexpr` object holding the nodal coordinates, the tensor-product basis, and the subentity topology — all computed at compile time.
- The topological dimension is deduced from the parameter pack: `sizeof...(N)`. Thus a surface element is simply a `LagrangeElement<3, 3, 3>` — same code path, fewer template parameters.
- Shape functions are products of 1D Lagrange polynomials, evaluated by index decomposition. No lookup table; the compiler folds constant expressions.
- The `local_index_[]` array enables node reordering (e.g., Gmsh to internal convention) without modifying the connectivity array.

SimplexElement<Dim, TopDim, Order>. A simplex element parameterised by embedding dimension, topological dimension, and polynomial order. It mirrors the `LagrangeElement` public interface but derives its reference cell from `geometry::simplex::SimplexCell<TopDim, Order>`, which stores the barycentric-based Lagrange shape functions for simplicial geometry.

Both families share a structurally identical interface (node access, `H()`, `dH_dx()`, `evaluate_jacobian()`, `map_local_point()`) but they are *unrelated types* — there is no inheritance hierarchy linking them. Uniformity is achieved through duck-typing in the next layer.

7.2.2 Layer 2: ElementGeometry (Type-Erased Handle)

`ElementGeometry<dim>` is a type-erased value-semantic wrapper that stores *any* concrete geometry type together with its quadrature rule behind a single, uniform interface. It is the pivot of the entire element subsystem.

Pattern: External Polymorphism. The design follows the *External Polymorphism* pattern (Cleary et al. 1997, popularised by Sean Parent's "Inheritance Is the Base Class of Evil" talk):

1. **Concept** (`impl::ElementGeometryConcept<dim>`) — abstract base with pure virtual methods: `H()`, `dH_dx()`, `evaluate_jacobian()`, `differential_measure()`, `num_integration_points()` quadrature accessors, and subentity topology.
2. **Model** (`impl::OwningModel_ElementGeometry<ElementType, IntegrationStrategy>`) — template class deriving from the concept, *owning* a concrete `ElementType` and `IntegrationStrategy` by value. Each virtual override delegates to the stored objects.
3. **Handle** (`ElementGeometry<dim>`) — holds a `std::unique_ptr<ElementGeometryConcept<dim>>` (`pimpl_`). Provides value semantics via `clone()`, move defaulted.



Why External Polymorphism and not classical inheritance?

- `LagrangeElement` and `SimplexElement` remain pure value types — no vtable pointer, no heap allocation, fully `constexpr`-eligible. They can be used independently of the type-erasure layer (e.g., in constexpr unit tests).
- The virtual dispatch lives in the *wrapper*, not in the element itself. Concrete element code retains full optimisation potential.
- New element families (e.g., NURBS, serendipity, spectral) are added by writing a new value type with the required interface — no base class to inherit from, no code changes in existing elements.

Differential measure dispatch. The `differential_measure()` method in `OwningModel` uses `if constexpr` on the compile-time-known topological dimension:

```
if constexpr (topological_dim == dim)
    return std::abs(J.determinant());          // volume
else if constexpr (topological_dim == 1)
    return J.col(0).norm();                    // arc length
else if constexpr (topological_dim == 2 && dim == 3)
    return J.col(0).cross(J.col(1)).norm();    // surface area
```

Despite crossing the virtual boundary, the Jacobian matrix itself is stack-allocated (Eigen fixed-size `Matrix<double, dim, Dynamic, ..., dim, dim>`), so no heap allocation occurs inside the hot loop.

Integration via template callback. `ElementGeometry` exposes a non-virtual template method `integrate(f)` that accepts any callable `f(LocalCoordView)` and loops over quadrature points:

```
template<std::invocable<LocalCoordView> F>
auto integrate(F&& f) const {
    // ... sum w_i * |J(xi_i)| * f(xi_i) ...
}
```

Because `f` is a template parameter (not `std::function`), the compiler inlines the integrand. Only the quadrature point data (coordinates, weights) and the Jacobian evaluation pass through the virtual boundary; the user's element-level computation stays in the monomorphic world.

7.2.3 Layer 3: Physical Elements

Physical elements combine an `ElementGeometry` with material data and DOF assembly logic. Each physical element type is a class template parameterised by a *MaterialPolicy* and a *KinematicPolicy*.

ContinuumElement<MaterialPolicy, ndof, KinematicPolicy>. The workhorse for 1D/2D/3D solid mechanics:

- Holds a non-owning pointer to an `ElementGeometry<dim>` (owned by the `Domain`).
- Owns the `MaterialPoint` array (one per Gauss point), each holding a `Material<MaterialPolicy>` with its constitutive strategy.
- Provides `inject_K()`, `compute_internal_forces()`, `inject_tangent_stiffness()`, `commit_material` — the full `FiniteElement` concept interface.
- The strain–displacement operator $\mathbf{B}$ is delegated to the `KinematicPolicy` (e.g., `SmallStrain` or `TotalLagrangian`), resolved at compile time.

BeamElement<BeamPolicy, Dim, AsmPolicy>. Timoshenko beam with section integration:

- Two-node, local-frame kinematics with a rotation matrix $\mathbf{R}$.
- Integration along the beam axis uses `MaterialSection<BeamPolicy>` objects instead of `MaterialPoint`.
- The `AsmPolicy` template parameter selects between direct assembly (`DirectAssembly`) and static condensation (`CondensedAssembly`) — a compile-time strategy switch.

SurfaceLoad. Not a "physical element" in the structural sense, but uses the `ElementGeometry` quadrature machinery to compute consistent nodal forces from a distributed traction on a boundary face.

7.2.4 Layer 4: Analysis Level

`Model<MaterialPolicy, KinematicPolicy, ndofs, ElemPolicy>` owns the element container, the `Domain`, and the PETSc objects (`PetscSection`, matrices, vectors).

The `ElemPolicy` template parameter controls element storage (section 7.4.3). For homogeneous meshes, the container is a raw `std::vector<ContinuumElement<...>>` with zero overhead. For mixed meshes, it is `std::vector<FEM_Element>` with one virtual dispatch per element call.

7.3 FEM_Element: Top-Level Type Erasure

`FEM_Element` applies the same External Polymorphism pattern as `ElementGeometry`, but at the assembly level:



Key design decisions:

- **Value semantics.** Copy via `clone()`, move defaulted. No shared ownership, no reference counting.
- **Self-wrap guard.** A `requires` clause prevents wrapping a `FEM_Element` inside another `FEM_Element` (double indirection).
- **Recursive concept satisfaction.** `FEM_Element` itself satisfies the `FiniteElement` concept, verified by a `static_assert` at the bottom of the header. This means it can be nested inside other type-erased wrappers without losing the concept constraint.
- **Optional interface methods.** Mass matrix operations (`density()`, `inject_mass()`) use `if constexpr` inside `Model<T>` to detect whether the concrete element supports them, defaulting to a no-op otherwise. This avoids bloating the concept with operations not all elements provide.

There is also a `StructuralElement` wrapper, identical in pattern, that provides type safety for structural-only models (beams, shells). Both derive from *no common base class* — they are independent type-erasure handles, unified only by the `FiniteElement` concept.

7.4 Policy-Based Design: Customisation Points

`fall_n` uses policies — template parameters that select compile-time strategies — at multiple levels. Each policy is a *customisation point*: a seam where the user can inject different behaviour without modifying existing code.

7.4.1 MaterialPolicy

A *trait bag* that binds kinematic and conjugate types:

Policy	StrainT	StressT	dim
ThreeDimensionalMaterial	Strain<6>	Stress<6>	3
PlaneMaterial	Strain<3>	Stress<3>	2
UniaxialMaterial	Strain<1>	Stress<1>	1
TimoshenkoBeam3D	BeamStrain<6,3>	BeamForces<6>	3
TimoshenkoBeam2D	BeamStrain<3,2>	BeamForces<3>	2

All generic code (`Material<P>`, `MaterialPoint<P>`, `MaterialState<P>`, `ElasticRelation<P>`) is parameterised on a single `MaterialPolicy` and extracts its types via `P::StrainT`, `P::StressT`, etc.

Extensibility. Adding a shell element requires only:

1. Define `ShellMaterial<N, 3>` with appropriate `ShellGeneralizedStrain<N,3>` and `ShellResultants<N`
2. Write a constitutive model conforming to `ConstitutiveRelation<ShellMaterial<N,3»`.
3. Write the element class (`ShellElement`) satisfying `FiniteElement`.

No existing code changes; the policy mechanism propagates types automatically.

7.4.2 KinematicPolicy

Selects the strain–displacement relationship at compile time:

Policy	Description	Linear?	K_σ?
SmallStrain	$\varepsilon = \nabla^s \mathbf{u}$	yes	no
TotalLagrangian	$\mathbf{E} = \frac{1}{2}(\mathbf{F}^T\mathbf{F} - \mathbf{I})$	no	yes
UpdatedLagrangian	Cauchy strain in current config.	no	yes
Corotational	Large rotation, small strain	no	yes

Each policy is a struct with static methods:

```
struct SmallStrain {
    static constexpr bool is_geometrically_linear    = true;
    static constexpr bool needs_geometric_stiffness  = false;

    template <std::size_t dim>
    static GPKinematics<dim> evaluate(
        ElementGeometry<dim>* geo, std::size_t num_nodes,
        std::size_t ndof, const Array& Xi,
        const Eigen::VectorXd& u_e);

    template <std::size_t dim>
    static auto compute_B(ElementGeometry<dim>* geo, ...);
};
```

`ContinuumElement` calls `KinematicPolicy::evaluate<dim>()` at each quadrature point. The boolean traits steer `if constexpr` branches inside the element (e.g., add K_σ only when `needs_geometric_stiffness == true`).

Extensibility. A new formulation (e.g., logarithmic strain) is added by defining a new struct satisfying `KinematicPolicyConcept` with the required static methods and boolean traits. No changes to `ContinuumElement` or any analysis class.

7.4.3 ElementPolicy (Storage Strategy)

Controls how `Model` stores its element collection:

Policy	Container	Homogeneous	Overhead
`SingleElementPolicy<E>`	`std::vector<E>`	yes	none
`MultiElementPolicy`	`std::vector<FEM_Element>`	no	1 vtable + 1 ptr chase

The concept `ElementPolicyLike` enforces the policy interface:

```
template <typename P>
concept ElementPolicyLike = requires {
    typename P::element_type;
    typename P::container_type;
    { P::is_homogeneous } -> std::convertible_to<bool>;
} && FiniteElement<typename P::element_type>;
```

Default path. `Model<ThreeDimensionalMaterial>` defaults to: `SingleElementPolicy<ContinuumElement<ThreeDimensionalMaterial, 3, SmallStrain»`, yielding a contiguous `std::vector` of monomorphic elements — optimal for cache locality and auto-vectorisation.

7.4.4 AssemblyPolicy (Beams)

Beam elements accept an `AsmPolicy` parameter:

- `DirectAssembly` — full stiffness matrix, no condensation.
- `CondensedAssembly` — static condensation of internal DOFs before injection into PETSc.

Both are stateless tag types; the choice is resolved at compile time via `if constexpr` inside `BeamElement::inject_K()`.

7.4.5 ConstitutiveStrategy (Material Update)

The material update mechanism (`Material<P>`) delegates to a type-erased strategy object (`IntegrationStrategy<P>`), enabling runtime polymorphism over the constitutive response:

- `ElasticRelation<P>` — linear elastic.
- `HyperelasticRelation<P>` — Neo-Hookean, SVK, etc.
- `J2Plasticity<P>` — return mapping with isotropic hardening.

This is the *only* place in the element quadrature loop where runtime polymorphism is used, because the constitutive model is genuinely a runtime choice (same mesh, different materials per physical group).

7.5 Compile-Time Cost Analysis

Policy-based design with heavy template usage has a well-known compile-time cost. `fall_n` mitigates this through several strategies:

1. **Header-only by necessity, not by choice.** The library is header-only because C++ templates must be visible at the point of instantiation. However, explicit template instantiation could be added in `.cpp` files for the most common configurations to reduce redundant codegen across translation units.
2. **Type erasure as a firewall.** `ElementGeometry<dim>` and `FEM_Element` act as *template firewalls*: code that consumes an `ElementGeometry<3>` does not need to see the headers of `LagrangeElement` or `SimplexElement`. This significantly reduces transitive include graphs.
3. **Consteval reference cells.** The `LagrangianCell<N...>` and `SimplexCell<TopDim, Order>` objects with their basis functions and topological tables are `constexpr`/`consteval`, evaluated by the compiler once. They produce no runtime code unless actually called; the compiler may fold constant subexpressions entirely.
4. **Concept constraints as documentation.** The `FiniteElement`, `KinematicPolicyConcept`, `ElementPolicyLike` concepts serve as lightweight checks that produce clear error messages at instantiation time, avoiding the traditional deep-template-error-message problem.

Measured impact. A full rebuild of `fall_n` (main + 12 test targets) takes approximately 105 seconds on a single core with GCC 11 and debug optimisation (`-g`). The dominant cost is Eigen's template instantiation inside `ContinuumElement` and `BeamElement`; the element geometry layer adds minimal overhead because the type-erasure boundary limits template propagation.

7.6 Comparison with OpenSees and Kratos

7.6.1 Overview

Aspect	**OpenSees**	**Kratos**	**fall_n**
Language	C++ (C++11/14)	C++ (C++17) + Python	C++ (C++20/23)
Polymorphism model	Classical inheritance	Classical inheritance + Python bridge	Policies + External Polymorphism
Element base	`Element` (virtual)	`Element` (virtual)	`FiniteElement` (concept)
Geometry base	`CrdTransf` (virtual)	`Geometry<TPoint>` (virtual)	`ElementGeometry<dim>` (type-erased)
Material base	`UniaxialMaterial` / `NDMaterial` (virtual)	`ConstitutiveLaw` (virtual)	`Material<Policy>` (policy + type-erased strategy)
Dispatch cost	1–3 vtable calls per GP	1–2 vtable calls per GP	0 (homogeneous) or 1 (heterogeneous)

7.6.2 OpenSees

OpenSees [**?**] uses a deep inheritance hierarchy: `DomainComponent` → `Element` → concrete types. Materials form an even deeper tree: `Material` → `UniaxialMaterial` → specific laws.

Strengths.

- Extremely mature (20+ years), battle-tested in earthquake engineering.
- Simple runtime scripting via Tcl (later Python) — users define models without recompiling.
- Large element library (200+ elements).

Weaknesses (from an architecture perspective).

- **Monolithic virtual hierarchy.** All elements inherit from `Element`, which carries 30+ virtual methods including `getResistingForce()`, `getTangentStiff()`, etc. Adding a new element requires implementing all of them (or relying on default no-ops that may silently produce incorrect results).
- **No separation of geometry and physics.** A `Brick20N` element hard-codes its shape functions, Jacobian, AND constitutive integration in a single class. Changing the quadrature rule requires modifying the element source.
- **Dynamic dispatch in the inner loop.** Every call to `material->getStress()` and `material->getTangent()` at each Gauss point goes through virtual dispatch. While the cost is small relative to the linear algebra, it inhibits inlining and auto-vectorisation across the material boundary.
- **No concept or constraint checking.** Adding a new element with a typo in a virtual override signature compiles silently and produces incorrect results at runtime.

Contrast with fall_n. `fall_n` eliminates the monolithic base class by defining `FiniteElement` as a C++20 concept that enforces the interface at compile time. The element is free to organise its internals however it pleases; the concept checks only what the assembler needs. Geometry is factored out into `ElementGeometry`, so the same mesh can serve continuum, surface-load, and post-processing operations.

7.6.3 Kratos Multiphysics

Kratos [?] uses a more modular architecture than OpenSees, with explicit separation of geometry (`Geometry<TPoint>`), element (`Element`), condition (`Condition`), constitutive law (`ConstitutiveLaw`), and process (`Process`).

Strengths.

- **Multi-physics by design.** The `ModelPart` / `ProcessInfo` / `Variable` registry enables coupling of disparate physics (structural, fluid, thermal) sharing the same mesh.
- **Python-driven workflow.** Element selection, boundary conditions, solver parameters, and post-processing are all scriptable in Python without recompilation.
- **Geometry separated from element.** `Geometry<TPoint>` handles shape functions and Jacobian; `Element` handles physics. This is conceptually analogous to `fall_n`'s two-layer split.

Weaknesses (from an architecture perspective).

- **Runtime overhead of the variable system.** Each nodal value is stored in a hash-map-like container (`Variable<T>` keys), requiring a lookup per node per variable access. This sacrifices cache locality and prevents compile-time resolution of DOF layouts.
- **Virtual geometry hierarchy.** `Geometry<TPoint>` is an inheritance tree: `Geometry` → `Triangle2D3`, etc. Shape functions are declared `virtual`, adding dispatch cost at each Gauss point. There is no mechanism to "inline" the geometry into the element at compile time.
- **Heavyweight element interface.** `Element` carries methods for `CalculateLocalSystem`, `CalculateMassMatrix`, `CalculateDampingMatrix`, `GetDofList`, etc. Many elements implement subsets, leaving the rest as no-ops or throwing exceptions — a code-smell of interface bloat.
- **No compile-time guarantees.** Registering a new element involves adding entries to a factory map at runtime. Errors in the element's interface (wrong return type, missing method) are caught only at link time or, worse, at runtime.

Contrast with fall_n. `fall_n`'s policy-based design replaces the Kratos variable registry with compile-time type parameters: the `MaterialPolicy` selects the strain/stress types, the `KinematicPolicy` selects the B-operator, and the `ElementPolicy` selects the storage strategy — all resolved by the compiler. The trade-off is that `fall_n` requires recompilation to change element types, whereas Kratos allows runtime scripting.

7.6.4 Summary: Architectural Trade-offs

Trade-off	OpenSees	Kratos	fall_n
Runtime scripting	✓✓	✓✓✓	—
Compile-time safety	—	—	✓✓✓
Zero-cost inner loop	—	—	✓✓
Geometry–physics split	—	✓✓	✓✓✓
Heterogeneous elements	✓✓✓	✓✓✓	✓✓
Multi-physics coupling	✓	✓✓✓	—
Maturity / element count	✓✓✓	✓✓✓	✓

`fall_n` occupies a different niche: it is *not* a general-purpose production FE framework, but a research library where the primary concern is **architectural clarity and compile-time correctness** over runtime flexibility. The policy-based approach is intentionally opinionated:

it makes the "easy things trivial" (adding a new constitutive model, kinematic formulation, or element family within the existing type system) at the cost of making the "hard things hard" (mixing unrelated physics, runtime element selection from user input).

7.7 Extensibility Guide: Adding a New Element Family

This section walks through the concrete steps to add a hypothetical "Serendipity element" family, illustrating each customisation point.

1. **Layer 1: Concrete geometry type.** Create `SerendipityElement<Dim, Order>`:
   - Store node coordinates, define `H()`, `dH_dx()`, `evaluate_jacobian()`, `map_local_point()` with the serendipity basis functions.
   - No base class needed. The type must be movable and copyable.

2. **Layer 1: Integration strategy.** Create or reuse a quadrature class (`GaussLegendre2D<p>`, `ReducedIntegration<...>`, etc.) exposing `reference_integration_point(i)` and `weight(i)`.

3. **Layer 2: Instantiate through ElementGeometry.** No code changes. The constructor template:

```
ElementGeometry<3> geo(
    SerendipityElement<3, 2>{tag, node_ids},
    GaussLegendre2D<3>{});
```

   automatically instantiates an `OwningModel<Serendipity..., GL...>` and stores it behind the type-erased handle.

4. **Layer 3: Use with ContinuumElement.** No code changes. `ContinuumElement` receives a pointer to the geometry and calls `H()`, `dH_dx()`, `differential_measure()` through the virtual interface. The **B** matrix and assembly are generic.

5. **Layer 4: Mesh import.** Add a case in `GmshDomainBuilder.hh` for the Gmsh element type code, constructing `ElementGeometry` with the serendipity concrete type and the desired integrator.

6. **Optional: Type-safe model.** If the serendipity element will be used in its own model (no mixing), define:

```
using SerendipitySolid =
    ContinuumElement<ThreeDimensionalMaterial, 3,
                     SmallStrain>;
using SerendipityModel =
    Model<ThreeDimensionalMaterial, SmallStrain, 3,
          SingleElementPolicy<SerendipitySolid>>;
```

   This compiles to a contiguous vector with zero virtual dispatch.

What does NOT need to change:

- `ElementGeometry.hh` (new type is auto-detected by the templated constructor).
- `ContinuumElement.hh` (works through geometry pointer).
- `FEM_Element.hh` (type erasure is generic).
- `Model.hh` (policy-parameterised).
- Any analysis class (`LinearAnalysis`, `NLAnalysis`, etc.).
- Any material or constitutive model.

This is the central extensibility promise: **new element families are additive** — they require only new files, not modifications to existing ones — conforming to the Open/Closed Principle.

7.8 Runtime Efficiency Considerations

7.8.1 Virtual Dispatch Budget

In the homogeneous path (`SingleElementPolicy`), the element assembly loop has **zero** virtual calls for the physics: all `inject_K()`, `B()`, `H()`, `dH_dx()` calls are monomorphic and inlineable.

The only virtual calls per Gauss point are:

- `ElementGeometry::evaluate_jacobian()` — 1 vcall for the Jacobian (through pimpl).
- `ElementGeometry::H()`, `dH_dx()` — $n_{\text{nodes}} \times (1 + \text{dim})$ vcalls for shape functions and derivatives.
- `Material::compute_response()` — 1 vcall for the constitutive model (through the strategy pointer).

This is *identical per-element overhead* to OpenSees or Kratos, but `fall_n` avoids the additional vtable dispatch that those frameworks incur at the element container level.

7.8.2 Cache-Friendly Layout

`SingleElementPolicy<E>` stores all elements contiguously in a single `std::vector<E>`. Each element's `MaterialPoint` array is heap-allocated (as a `std::vector<MaterialPointT>`), but its entries are contiguous for that element.

`MultiElementPolicy` stores `FEM_Element` objects contiguously (the `unique_ptr<Concept>` wrappers are packed), but the pointed-to `Model<T>` objects are heap-allocated with potentially scattered addresses. This adds one pointer chase per element — acceptable for heterogeneous cases where the element count is moderate.

7.8.3 DOF Index Caching

`ContinuumElement` caches its flat `dof_indices_[]` array (one entry per element DOF, combining all nodes). The cache is populated lazily on first use and reused across `inject_K()`, `compute_internal_forces()`, and `inject_tangent_stiffness()`. This avoids the per-call overhead of traversing the node pointers to collect DOF indices at every assembly step.

```
void ensure_dof_cache() noexcept {
    if (dofs_cached_) return;
    collect_dof_indices();
}
```

7.8.4 Stack-Allocated Jacobians

The Jacobian matrix crossing the virtual boundary is declared as:

```
using JacobianMatrix = Eigen::Matrix<double, dim,
    Eigen::Dynamic, Eigen::ColMajor, dim, dim>;
```

The `MaxRows = dim`, `MaxCols = dim` template parameters tell Eigen to use a fixed-size stack buffer (up to $3 \times 3 = 72$ bytes) with a dynamic column count. Since `dim` ≤ 3, no heap allocation occurs, even though the column count is "dynamic" (it varies between volume and surface elements).

This ensures that the virtual call to `evaluate_jacobian()` returns by value without any `new`/`delete`, making the hot path allocation-free.

Chapter 8

Generic Boundary and Initial Condition Infrastructure

This chapter documents the design and implementation of the generic boundary condition (BC) and initial condition (IC) infrastructure for `fall_n`. The goals are:

1. **Per-DOF granularity:** constrain individual degrees of freedom (roller supports, symmetry BCs) rather than all DOFs simultaneously.
2. **Imposed (non-zero) Dirichlet:** prescribe non-zero displacement, temperature, or any nodal field value.
3. **Compile-time node selectors:** apply constraints via geometric predicates (plane, box, sphere, custom lambda) that resolve at compile time with zero runtime overhead.
4. **State transfer:** capture the complete post-solve state (`ModelState`) and use it as the initial condition for a subsequent analysis—enabling staged construction, restart, and multi-physics chaining.
5. **Extensibility:** the design should accommodate future field types (temperature, initial stress, pore pressure) without modifying the selector or constraint machinery.

8.1 Gap Analysis: the Legacy API

The original Model API exposed these methods for boundary conditions:

```
void fix_node(size_t node_idx);                          // ALL DOFs = 0
void fix_x(double val, double tol = 1e-6);               // all DOFs at x=val
void apply_node_force(size_t node_idx, auto... f);        // nodal Neumann
void apply_surface_traction(string group, auto... t);     // consistent traction
```

8.2 Design Decisions and Trade-offs

8.2.1 Compile-Time Polymorphism via Concepts

Consistent with `fall_n`'s policy-based architecture (Chapter 7), the node selector system uses C++20 concepts rather than virtual dispatch:

```
namespace fn {
template <typename S, typename NodeT>
concept NodeSelector = requires(const S& s, const NodeT& n) {
    { s(n) } -> std::convertible_to<bool>;
};
```

Table 8.1: Limitations of the legacy BC interface.

Limitation	Impact
`fix_node` constrains *all* DOFs	Cannot model roller supports, symmetry planes, or mixed BCs.
`fix_x/y/z` misnamed	These fix all three displacement components, not just the named one. Misleading to users.
No non-zero Dirichlet via Model API	`global_imposed_solution_` was created and zeroed but never populated through the Model interface. Only `DynamicAnalysis::PrescribedBC` filled it.
`ElementInitialStress` unused	The struct existed in `BoundaryCondition.hh` and was storable in `BoundaryConditionSet`, but no evaluator integrated it into the assembly pipeline.
Procedural selection	Every `fix_*` method hard-coded a coordinate loop. No reusable geometric predicate.
`VecAssemblyBegin/End` per call	`apply_node_force` triggered PETSc assembly for each node.

```
}
```

Any callable `f(const Node<dim>&)-> bool` satisfies `NodeSelector`: lambdas, function objects, and the built-in selectors all qualify. The compiler resolves the predicate at compile time, and after inlining a `PlaneSelector` collapses to a single `fabs` + comparison—zero overhead compared to a hand-written loop.

Why not `std::function`? A `std::function<bool(const Node&)>` would erase the type and force heap allocation for lambdas that exceed the small-buffer size (typically 16–32 bytes). For selectors applied to every node in the mesh, this per-call overhead is measurable. The concept-based approach pays nothing at runtime.

Why not virtual? A virtual `AbstractSelector::operator()` would add one indirect call per node per constraint pass. With 10 000 nodes this is $\sim$10 μs (branch-predictor penalty), acceptable but unnecessary when the concrete type is known at compile time.

8.2.2 Constraint Storage: Extending the Existing Map

The existing `ConstraintDofInfo` type already maps sieve point IDs to (DOF index list, prescribed value list):

```
using ConstraintDofInfo =
  std::map<PetscInt,
           std::pair<std::vector<PetscInt>,
                     std::vector<PetscScalar>>>;
```

The new API *extends* this map rather than replacing it. The key operations are:

1. **Insert in sorted order.** PETSc's `PetscSectionSetConstraintIndices` requires increasing DOF indices. The `constrain_dof` method uses `std::lower_bound` to maintain this invariant.
2. **Merge, not overwrite.** If DOF 0 of a node is already constrained and the user constrains DOF 2, both are stored. An update to DOF 0 changes the prescribed value without duplicating the index.

8.2.3 Non-Zero Dirichlet: Where Values Flow

Non-zero prescribed values are stored in `constraints_` alongside the DOF indices. During `setup()`, a new `fill_imposed_solution()` step extracts these values from the constraint map into the PETSc local vector `global_imposed_solution_`:

```
void setup() {
    setup_boundary_conditions();   // PETSc section
    setup_vectors();               // create Vecs
    fill_imposed_solution();       // NEW: u_D -> imposed
    setup_matrix();                // create Mat
}
```

Remark 8.1. Non-zero Dirichlet requires that the analysis accounts for the coupling $\mathbf{K}_{fc}\,\mathbf{u}_c$ in the right-hand side. `NonlinearAnalysis` handles this naturally: the internal forces $\mathbf{f}_{\text{int}}(\mathbf{u}_{\text{free}} + \mathbf{u}_D)$ include the prescribed part. `LinearAnalysis` currently does *not* apply this correction—for non-zero Dirichlet, users should solve with `NonlinearAnalysis` (which converges in one Newton step for linear problems).

8.2.4 ModelState: Platform-Independent Snapshot

For state transfer between models, we need a data structure that:

- Does *not* depend on PETSc (no `Vec`, `Mat`).
- Does *not* depend on the `MaterialPolicy` template parameter (so an elastic model's state can seed a plastic model).
- Is copyable, movable, and (future) serialisable.

`ModelState<dim>` satisfies all three. It stores:

- Per-node: ID, displacement, velocity.
- Per-element, per-Gauss-point: stress and strain in Voigt notation (`std::array<double, nvoigt>`).

The PETSc-to-array extraction in `capture_state()` uses `VecGetArrayRead` (zero-copy read) and the element's `material_points()` accessor which recomputes stress from the committed strain via the constitutive relation.

8.3 Implementation

8.3.1 NodeSelector.hh — Built-in Selectors

Table 8.2: Built-in node selectors.

Selector	Predicate	Parameters
`PlaneSelector<dim>`	$\lvert x_i - v\rvert < \varepsilon$	axis i, value v, tolerance ε
`BoxSelector<dim>`	$x \in [\text{lo}, \text{hi}]$	corners, tolerance
`SphereSelector<dim>`	$\lVert x - c\rVert \le r$	centre c, radius r, tolerance
`NodeIdSelector`	$\text{id} \in S$	set of node IDs

Combinators turn simple selectors into compound predicates:

```
auto corner = fn::select_and(
    fn::PlaneSelector<3>{0, 0.0},    // x = 0
    fn::PlaneSelector<3>{1, 0.0}     // y = 0
);
auto not_x0 = fn::select_not(fn::PlaneSelector<3>{0, 0.0});
auto union_ = fn::select_or(selectorA, selectorB);
```

Convenience factories (`fn::on_plane`, `fn::in_box`, `fn::in_sphere`, `fn::node_ids`) provide a terser syntax.

8.3.2 Model.hh — New Constraint Methods

Table 8.3: New Model constraint API.

Method	Description
`constrain_dof(n, d, v)`	Constrain DOF d of node n to value v. Sorted insertion.
`constrain_node(n, vals)`	Constrain all DOFs of node n to the given array of values.
`constrain_dof_where(sel, d, v)`	Constrain DOF d at every node matching selector `sel`.
`constrain_where(sel)`	Constrain all DOFs (homogeneous) at every matching node.
`constrain_where(sel, vals)`	Constrain all DOFs with prescribed values at every matching node.
`is_constrained(n)`	Query: is any DOF of node n constrained?
`is_dof_constrained(n, d)`	Query: is DOF d of node n constrained?
`prescribed_value(n, d)`	Get the prescribed displacement at DOF d (0 if free).
`num_constraints()`	Total number of constrained DOFs across all nodes.
`capture_state()`	Extract current solution into a `ModelState<dim>`.
`apply_initial_displacement(s)`	Populate imposed solution from a `ModelState<dim>`.

8.3.3 Backward Compatibility

The legacy methods `fix_node`, `fix_x`, `fix_y`, `fix_z`, and `fix_orthogonal_plane` remain unchanged in semantics—they continue to constrain *all* DOFs of every matching node. Internally, `fix_orthogonal_plane` now delegates to:

```
void fix_orthogonal_plane(int i, double val, double tol) {
    constrain_where(fn::PlaneSelector<dim>{i, val, tol});
}
```

The code path is identical; only the implementation reuses the selector infrastructure.

8.4 Use-Case Walkthrough: Roller vs. Clamped Cantilever

Consider a cantilever beam $[0, L]\times[0, b]\times[0, h]$ loaded at $x = L$ by a surface traction $\mathbf{t} = (0, t_y, t_z)$.

Clamped support (legacy):

```
M.fix_x(0.0);    // constrains u_x, u_y, u_z at x=0
```

Equivalent new API:

```
M.constrain_where(fn::PlaneSelector<3>{0, 0.0});
```

Roller support (new API): Only $u_x = 0$ at $x = 0$. Rigid body prevention requires additionally constraining u_y and u_z at isolated points:

```
// u_x = 0 on entire face
M.constrain_dof_where(fn::PlaneSelector<3>{0, 0.0}, 0, 0.0);

// Prevent rigid translation + rotation about x:
auto origin = fn::select_and(fn::PlaneSelector<3>{0, 0.0},
    fn::select_and(fn::PlaneSelector<3>{1, 0.0},
                   fn::PlaneSelector<3>{2, 0.0}));
M.constrain_dof_where(origin, 1, 0.0);  // u_y at origin
M.constrain_dof_where(origin, 2, 0.0);  // u_z at origin

auto top_z = fn::select_and(fn::PlaneSelector<3>{0, 0.0},
    fn::select_and(fn::PlaneSelector<3>{1, 0.0},
                   fn::PlaneSelector<3>{2, h}));
M.constrain_dof_where(top_z, 1, 0.0);   // prevents Rx
```

The roller case has 30 constrained DOFs (28 nodes $\times$ 1 + 2 extra) versus 84 (28 $\times$ 3) for the clamped case. With fewer constraints, the beam is more flexible:

Table 8.4: Roller vs. clamped comparison (HEX8 beam, $E = 200$, $\nu = 0.3$).

BC type	**Constrained DOFs**	$\max\lvert u\rvert$	**Ratio**
Clamped	84	0.594	1.00
Roller (u_x only)	30	2.762	4.64×

This confirms: the per-DOF mechanism works correctly and produces a physically meaningful stiffer/more-flexible response.

8.5 State Capture and Continuation Analysis

8.5.1 ModelState Structure

```
template <size_t dim>
struct ModelState {
    static constexpr size_t nvoigt = dim * (dim + 1) / 2;

    struct NodalData {
        size_t node_id;
        array<double, dim> displacement;
        array<double, dim> velocity;        // zero for static
    };

    struct GaussPointData {
        array<double, nvoigt> stress;
        array<double, nvoigt> strain;
    };

    struct ElementData {
        size_t element_index;
        vector<GaussPointData> gauss_points;
    };

    vector<NodalData>   nodes;
    vector<ElementData> elements;
```

```
};
```

8.5.2 Capture Workflow

`Model::capture_state()` extracts:

1. **Nodal displacements:** from the PETSc local vector `current_state_` via `VecGetArrayRead` (zero-copy). Each node's DOF offsets from `node.dof_index()` are used to index into the raw array.
2. **Element stress/strain:** from each `MaterialPoint`'s committed strain (`current_state()`) and recomputed stress (`compute_response()`). The Voigt vectors are copied component-by-component into `std::array<double, nvoigt>`, guarded by the compile-time `num_components` constant.

8.5.3 Future: Initial Stress Integration

The existing `ElementInitialStress<dim>` struct in `BoundaryCondition.hh` can be populated from `ModelState::ElementData`:

```
for (const auto& ed : state.elements) {
    ElementInitialStress<dim> eis;
    eis.element_index = ed.element_index;
    for (const auto& gp : ed.gauss_points) {
        eis.gauss_point_stresses.push_back(gp.stress);
    }
    bcs.add_initial_stress(std::move(eis));
}
```

For this to take effect, the element assembly must incorporate $\boldsymbol{\sigma}_0$ into the internal force:

$$\mathbf{f}_{\text{int}}(\mathbf{u}) = \int_{\Omega_e} \mathbf{B}^T \left(\boldsymbol{\sigma}(\boldsymbol{\varepsilon}(\mathbf{u})) + \boldsymbol{\sigma}_0\right) \mathrm{d}V$$

This requires modifications to `ContinuumElement::compute_internal_force_vector`, specifically adding a σ`_initial` term at each Gauss point. This integration is deferred to a future phase.

8.6 Comparison with OpenSees and Kratos

Table 8.5: BC/IC handling comparison across frameworks.

Feature	OpenSees	Kratos	fall_n
Single-DOF fix	`fix nodeTag dof`	`DISPLACEMENT_X: 0.0`	`constrain_dof(n,d,v)`
Geometric selection	Tcl loops	Python `FindNodalH`	`PlaneSelector`, lambda
Non-zero Dirichlet	`imposedMotion` pattern	`ApplyDirichletProcess`	`constrain_dof_where(s,d,v)`
State transfer	`-database` serialise	`ModelPartIO`	`ModelState` capture/apply
Initial stress	Per-element update	`INITIAL_STRESS_TENSOR`	Defined, not yet integrated
Dispatch cost	Virtual (runtime)	Virtual + Python (runtime)	Compile-time (zero)

Key differences:

- **OpenSees** uses a tag-based Tcl scripting layer for BC specification. Geometric loops require user scripting. State transfer uses a persistence layer (`FE_Datastore`).
- **Kratos** uses Python processes (`ApplyDirichletProcess`, `ApplyNeumannProcess`) that iterate over model parts. Highly flexible but with Python → C++ boundary overhead.
- **fall_n** resolves all selector logic at compile time. The constraint map lives in pure C++ with PETSc-section-based enforcement. No scripting layer, no virtual dispatch per node.

8.7 Extensibility Roadmap

The current infrastructure is designed for forward extension. Table 8.6 outlines planned capabilities and their implementation path.

Table 8.6: Extensibility roadmap.

Capability	Implementation path	Status
Per-DOF constraints	`constrain_dof`, `constrain_dof_where`	**Implemented**
Non-zero Dirichlet	`fill_imposed_solution()` + NL correction	**Implemented** (NL only)
Node selectors	`NodeSelector` concept + built-in selectors	**Implemented**
State capture/transfer	`ModelState` + `capture_state`	**Implemented**
Initial stress	Extend `ContinuumElement::compute_internal_force` to add $\boldsymbol{\sigma}_0$ at each GP	Designed, deferred
Body forces	Consistent nodal load via $\int N^T \mathbf{b}\,\mathrm{d}V$	Planned
Temperature field	Additional `ModelState` field + thermal strain $\boldsymbol{\varepsilon}_\theta = \alpha\,\Delta T\,\mathbf{1}$	Planned
Multi-step builder	Fluent builder with chained `.constrain().material().build()`	Planned
State serialisation	HDF5/JSON export of `ModelState`	Planned
Linear non-zero BC	RHS correction $\mathbf{f}_{\text{eff}} = \mathbf{f}_{\text{ext}} - \mathbf{K}_{fc}\,\mathbf{u}_D$ in `LinearAnalysis`	Planned

8.8 Test Suite

The implementation is validated by 81 tests in `tests/test_boundary_conditions.cpp`, organized as follows:

Table 8.7: Test suite structure (81 tests).

Category	Count	Coverage
Node selectors (pure geometry)	38	PlaneSelector, BoxSelector, SphereSelector, NodeIdSelector, combinators, la
ModelState data structure	9	Default state, add/query, copy semantics
Per-DOF constraints	11	Single DOF, multiple DOFs, non-zero value, value update
Selector-based constraints	10	PlaneSelector on DOF, all DOFs, values, lambda, composite
Full solve: roller vs. clamped	3	Clamped > 0, Roller > 0, Roller > Clamped
State capture after solve	7	Non-empty, node count, element count, non-zero displacement, non-zero str
Backward compatibility	3	`fix_x` gives positive deflection, reasonable magnitude

8.9 Summary

The generic BC/IC infrastructure extends `fall_n` from an all-or-nothing clamped-support tool to a framework capable of:

- **Arbitrary Dirichlet BCs:** per-DOF, per-node, per-selector, with prescribed values (zero or non-zero).
- **Zero-cost selectors:** compile-time geometric predicates with no runtime overhead versus hand-written loops.
- **State snapshots:** PETSc-independent `ModelState` for continuation, restart, and future serialisation.
- **Full backward compatibility:** `fix_x`, `fix_y`, `fix_z` continue to work exactly as before.

The design follows the same policy-based, compile-time polymorphic philosophy established in the element architecture (Chapter 7) and validated by an 81-test suite.

Chapter 9

ElementGeometry Refactor

This chapter documents the refactor of the `ElementGeometry` subsystem. The goal of the change was not to redesign the whole geometry layer from scratch, but to fix the most important semantic and architectural weaknesses without degrading the hot path of element integration.

The guiding constraint was explicit: *prefer compile-time cost over runtime cost whenever the trade-off is reasonable.* In other words, stronger type constraints, cleaner ownership, and slightly more template work at compile time are acceptable, whereas extra runtime indirection inside the Gauss loop is not.

9.1 Problem Statement

Before the refactor, `ElementGeometry<dim>` already had a good high-level idea: concrete geometry and quadrature strategy were stored behind a type-erased, value-semantic wrapper. However, three problems were architecturally significant.

9.1.1 Broken value semantics

The wrapper cloned only its internal `pimpl_`, while metadata such as `integration_point_`, `sieve_id`, and `physical_group_` lived outside the cloned state. As a consequence, copy construction and copy assignment were semantically incomplete: two `ElementGeometry` objects could share the same geometric map while disagreeing on already-materialised Gauss-point data or mesh metadata.

This violated a core expectation of value types:

$$\texttt{b = a} \quad \Longrightarrow \quad \texttt{b} \text{ must represent the same logical value as } \texttt{a}.$$

9.1.2 Integration strategy mixed into concrete geometry headers

The concrete geometry headers contained both the element type and the quadrature strategy implementation. This worked, but it blurred the boundary between two distinct concepts:

- a geometric interpolation on a reference cell, and
- a numerical integration policy on that reference cell.

Architecturally this was undesirable because the element family and the quadrature family evolve for different reasons.

9.1.3 Weak compile-time invariants

Some invalid states were still representable:

- unsupported Gauss–Legendre orders silently produced zero-filled arrays;
- `detJ()` was visible even for embedded geometries with non-square Jacobians;

- tensor-product geometries did not consistently enforce `topological_dim` $\leq$ `dim`.

These were not merely cosmetic issues. They weakened the library contract and made failures harder to interpret.

9.2 Design Goals

The refactor was driven by the following goals:

1. Preserve the existing *external polymorphism* structure.
2. Keep quadrature evaluation monomorphic and inlineable inside the concrete model.
3. Repair value semantics of the wrapper.
4. Make invalid geometric or quadrature configurations fail early.
5. Reduce conceptual coupling between geometry and integration.

Equally important is what was *not* attempted in this refactor: the geometry layer still depends on `Node<dim>`, which means it is not yet a purely geometric vertex layer. That larger ontological cleanup remains a future step because it cuts across `Model`, DOF storage, and multiple element families.

9.3 Refactor Overview

9.3.1 Metadata moved under wrapper ownership

`ElementGeometry` now owns an internal metadata aggregate containing:

- the materialised integration points,
- the optional DMPlex sieve identifier, and
- the physical-group label imported from Gmsh.

This has two consequences.

First, copy construction and copy assignment now copy both the cloned geometry implementation and the metadata, restoring proper value semantics.

Second, the metadata is no longer a public bag of fields. It is accessed through a narrow API: `sieve_id()`, `has_sieve_id()`, `physical_group()`, `integration_points()`, etc.

This is a direct SRP improvement: the wrapper remains responsible for its own logical state, and downstream code no longer reaches into its internals.

9.3.2 Quadrature strategies extracted to dedicated headers

Two strategy types were extracted:

- `GaussLegendreCellIntegrator.hh`
- `SimplexIntegrator.hh`

The concrete geometry classes remain pure descriptions of interpolation and mapping. The numerical integration policy is still attached at compile time, but it is no longer embedded in the same header for incidental reasons.

This separation is conceptually important. In isoparametric finite elements, geometry defines the map

$$\mathbf{x}(\boldsymbol{\xi}) = \sum_{a=1}^{n_n} N_a(\boldsymbol{\xi})\, \mathbf{x}_a,$$

while quadrature defines an approximation of

$$\int_{\hat{\Omega}} f(\boldsymbol{\xi})\, \mathrm{d}\hat{\Omega} \;\approx\; \sum_{g=1}^{n_g} w_g\, f(\boldsymbol{\xi}_g).$$

They are related in use, but they are not the same abstraction.

9.3.3 A small quadrature concept

The new `QuadratureStrategy` concept formalises the contract expected by `ElementGeometry`'s internal model:

- `num_integration_points`
- `reference_integration_point(i)`
- `weight(i)`

The benefit is not runtime polymorphism. The benefit is that failures move to compile time, where the error is cheaper and more local.

9.4 Geometry and Measure

The refactor keeps the existing zero-cost logic for the differential measure. Given the Jacobian $J = \partial \mathbf{x}/\partial \boldsymbol{\xi}$, the integration measure depends on the relationship between topological and embedding dimensions:

$$\text{full-dimensional cell:} \quad \mathrm{d}\Omega = |\det J|\,\mathrm{d}\hat{\Omega}, \tag{9.1}$$

$$\text{embedded curve:} \quad \mathrm{d}s = \|J\|\,\mathrm{d}\hat{s}, \tag{9.2}$$

$$\text{embedded surface in } \mathbb{R}^3: \quad \mathrm{d}S = \|J_1 \times J_2\|\,\mathrm{d}\hat{S}. \tag{9.3}$$

This dispatch still happens inside `OwningModel_ElementGeometry<ElementType, IntegrationStrategy>` using `if constexpr`. Therefore the compiler sees the concrete element type, the concrete topological dimension, and the concrete matrix shape. No extra runtime branch was introduced inside the integration loop.

9.5 API Hardening

9.5.1 Restricting `detJ()`

`detJ()` now exists only when the Jacobian is square, namely when the element is full-dimensional:

$$\texttt{topological_dim} = \texttt{dim}.$$

This is important because a determinant is not defined for the Jacobian of an embedded beam or surface. Exposing the member unconditionally was misleading: it suggested a mathematically meaningful operation where none exists.

9.5.2 Fail-fast Gauss–Legendre tables

Unsupported Gauss–Legendre orders no longer fall back to zero arrays. Instead, they trigger a compile-time error. This is the right contract for a template-based numerical kernel: if the requested order is unsupported, the program should fail where the invalid instantiation occurs.

9.5.3 Safer tensor-product constraints

`LagrangeElement<Dim, N...>` now enforces that the number of natural coordinates does not exceed the embedding dimension. This prevents invalid type combinations from entering the system.

9.6 Materialised Integration Points

The wrapper continues to precompute physical Gauss-point coordinates when the domain requests them. The refactor extends this step so that the integration weight is also stored in each materialised point.

This is useful for post-processing and point-wise objects attached to Gauss points because the point now carries a coherent local state:

- physical coordinates,
- global identifier for VTK export,
- quadrature weight.

The operation remains amortised and explicit. It does not change the quadrature path used in stiffness or residual evaluation.

9.7 Performance Discussion

The refactor was intentionally biased toward preserving runtime behaviour.

9.7.1 What did not change

- Concrete geometry evaluation is still template-based.
- The Jacobian and shape-function evaluation remain statically resolved.
- The quadrature loop still uses direct calls on the concrete strategy stored inside the model.
- No new virtual call was inserted inside `integrate()`.

9.7.2 What did change

- More errors are now diagnosed at compile time.
- Integration strategies live in dedicated headers, reducing conceptual coupling and making future dependency management easier.
- Copying `ElementGeometry` is slightly more expensive if integration points have already been materialised, because the copy now correctly copies them. This is not a regression; it is the real cost of correct value semantics.

This is the intended trade-off. Copying a fully materialised geometric entity is not a hot-path operation in FEM assembly, whereas incorrect copies are architecturally dangerous.

9.8 What Was Deliberately Deferred

The refactor does *not* yet solve the deeper issue that the geometry layer depends on `Node<dim>`, and `Node<dim>` already contains DOF state. From a strict modelling standpoint, a geometric layer should ideally depend on a lighter vertex concept carrying only:

- identifier,
- coordinates,
- optional mesh-backend handle.

That separation would improve the ontology of the codebase and further align the design with SRP and DIP. However, it affects much more than `ElementGeometry`; it is therefore better handled as a dedicated follow-up refactor instead of being folded into the present change.

9.9 Result

Architecturally, the refactor moves `ElementGeometry` from “good idea with leaky semantics” toward “stable boundary abstraction”.

The most important outcomes are:

1. wrapper copies are now semantically correct;
2. geometry and quadrature are more cleanly separated;
3. invalid numerical configurations fail early;
4. the hot numerical path remains compile-time resolved.

This is a meaningful improvement even though the subsystem is not yet the final form of the geometry layer. It removes a real correctness bug, strengthens the public contract, and prepares the code for a later, larger cleanup around geometric vertices versus analysis nodes.

Chapter 10

Serendipity Element Families

This chapter documents the implementation of the new serendipity element families added to `fall_n`, their integration into `ElementGeometry`, the associated tests, and the benchmark results.

The implementation goal was architectural, not merely additive: to introduce a new family without changing the overall layering of the codebase. In particular:

- the concrete element remains a pure value type;
- `ElementGeometry` continues to provide the type-erased boundary;
- quadrature remains a separate compile-time policy;
- no new virtual dispatch is introduced in the hot integration path.

10.1 Why Serendipity?

For tensor-product cells, the quadratic Lagrange family and the quadratic serendipity family differ substantially in node count:

Reference cell	Quadratic Lagrange	Quadratic serendipity
Quadrilateral	9 nodes	8 nodes
Hexahedron	27 nodes	20 nodes

The serendipity family removes face-center and volume-center nodes while retaining vertex and edge nodes. This makes the element attractive when the primary objective is to reduce geometry, interpolation, and assembly cost without dropping to first order.

Architecturally, serendipity is also a good stress test of the current design. It requires:

- a new reference cell type;
- a new concrete geometry type;
- VTK support for new node counts;
- optional Gmsh import support;
- no changes in the physical element layer.

That is precisely the extensibility story claimed in section 7.7; this chapter documents the claim becoming real code.

10.2 Mathematical Structure

10.2.1 Tensor-product serendipity on the cube

For the quadratic serendipity family on the reference hypercube $\hat{\Omega} = [-1, 1]^d$, nodes are located at:

- the 2^d vertices;

- the $d\,2^{d-1}$ edge midpoints.

Thus, for $d = 3$, the quadratic hexahedron has

$$2^3 + 3 \cdot 2^2 = 8 + 12 = 20$$

nodes.

Corner shape functions. Let $\mathbf{r} = (r_1, \ldots, r_d)$ be a corner node with $r_j \in \{-1, 1\}$. The quadratic serendipity shape function is

$$N_{\mathbf{r}}(\mathbf{x}) = 2^{-d}\left(\prod_{j=1}^{d}(1 + r_j x_j)\right)\left(1 + \sum_{j=1}^{d} r_j x_j - d\right).$$

Edge-midpoint shape functions. Let $\mathbf{r}$ be an edge node, so exactly one component $r_k = 0$ and all others are ± 1. Then

$$N_{\mathbf{r}}(\mathbf{x}) = 2^{1-d}(1 - x_k^2) \prod_{j \neq k}(1 + r_j x_j).$$

These expressions unify the 1D, 2D, and 3D quadratic serendipity family. The implementation therefore uses a single generic formula for `TopDim` $= 1, 2, 3$, with compile-time node descriptors and `consteval` reference-node tables.

10.2.2 Why the tetrahedral "serendipity" family is different

The simplex case requires more care. For tetrahedra at order $p = 2$, the standard quadratic Lagrange simplex already uses only:

- 4 vertices;
- 6 edge midpoints;
- no face-interior nodes;
- no volume-interior nodes.

Therefore the practical quadratic tetrahedral family is already "serendipity-like" in the sense relevant to this codebase: there are no face-center or body-center DOFs to remove.

For this reason, the new `SerendipitySimplexElement` is represented as an explicit family alias over the existing simplex implementation for orders 1 and 2. This is mathematically honest and avoids inventing an ad hoc reduced tetrahedron with unclear approximation properties.

10.3 Implementation Structure

10.3.1 Reference cells

The tensor-product family is implemented in `SerendipityCell.hh`. The file introduces:

- `serendipity_num_nodes(top_dim, order)`;
- `serendipity_reference_nodes<TopDim, Order>()`;
- `SerendipityBasis<TopDim, Order>`;
- `SerendipityCell<TopDim, Order>`.

Reference nodes are computed with `consteval`, so the full node layout is available at compile time and can participate in static assertions and compile-time topology generation.

10.3.2 Concrete geometry

The concrete tensor-product family is implemented in `SerendipityElement.hh` as

```
SerendipityElement<Dim, TopDim, Order>,
```

mirroring the shape of the existing `SimplexElement` and `LagrangeElement` abstractions:

- it stores node IDs and bound node pointers;
- it exposes `H()`, `dH_dx()`, `map_local_point()`, and `evaluate_jacobian()`;
- it carries a `ReferenceCell` type with compile-time topology.

The new family is therefore a first-class Layer 1 geometry type.

10.3.3 ElementGeometry integration

`ElementGeometry.hh` was extended in only one place: its face-topology and face-factory logic now recognises the serendipity family. No changes were required in the outer wrapper API.

This confirms the architectural objective: the extension point is the concrete geometry type, not the type-erasure layer.

10.3.4 Quadrature choices

The following quadratures were selected from the rules already present in the library:

Element	Quadrature	Rationale
HEX20	`GaussLegendreCellIntegrator<3,3,3>`	full quadratic tensor-product integration
QUAD8 face	`GaussLegendreCellIntegrator<3,3>`	compatible face integration
EDGE3 face	`GaussLegendreCellIntegrator<3>`	compatible edge integration
TET10 serendipity	`SimplexIntegrator<3,2>`	same requirements as quadratic simplex

The choice is intentionally conservative. The goal of this first integration is correctness and compatibility, not aggressive reduced integration.

10.4 VTK and Gmsh Support

10.4.1 VTK

`VTKCellTraits.hh` now recognises:

- 8-node quadratic serendipity quadrilaterals (`VTK_QUADRATIC_QUAD`);
- 20-node quadratic serendipity hexahedra (`VTK_QUADRATIC_HEXAHEDRON`).

The test executable writes four validation files:

- `data/output/serendipity_hex20_sample_mesh.vtu`
- `data/output/serendipity_hex20_sample_gauss.vtu`
- `data/output/serendipity_tet10_sample_mesh.vtu`
- `data/output/serendipity_tet10_sample_gauss.vtu`

These contain both the cell geometry and the materialised Gauss cloud, together with a simple scalar field for visual inspection in ParaView.

10.4.2 Gmsh

`GmshDomainBuilder.hh` was extended with support for:

- `HEX_20` (element type 17);
- `QUA_8` (element type 16) for boundary faces.

The chosen internal node ordering matches the standard corner-plus-edge layout, so no non-trivial permutation was required for these two element types.

10.5 Validation Tests

The new test executable `test_serendipity.cpp` validates:

1. static node counts for the family;
2. reference-node coordinates for HEX20;
3. partition of unity of the HEX20 basis;
4. Kronecker interpolation property at all 20 reference nodes;
5. exact reproduction of a representative quadratic polynomial;
6. unit-cube volume and mixed-monomial integration through `ElementGeometry`;
7. creation and integration of quadratic serendipity face geometry;
8. partition of unity and volume for the tetrahedral serendipity family;
9. VTK cell-type dispatch and actual file generation.

This test set is deliberately front-loaded toward interpolation quality. Before benchmarking or embedding the element into larger analyses, the basis itself must satisfy the core finite element identities.

10.6 Benchmark Results

The microbenchmark measures repeated geometric integration of a constant field through `ElementGeometry`. It was executed locally after the full test suite passed.

Case	Wall time [s]	Observation
HEX20 serendipity	6.04	baseline for 4000 integrations
HEX27 triquadratic	19.14	about 3.2× slower than HEX20
TET10 serendipity(simplex)	0.334	practically same as quadratic simplex
TET10 quadratic simplex	0.364	expected baseline

Interpretation. The HEX20 result is the important one. The node reduction from 27 to 20 lowers the cost of geometry interpolation and Jacobian assembly enough to be visible even though both elements use the same $3 \times 3 \times 3$ Gauss rule.

The tetrahedral result confirms the modelling claim made earlier: at quadratic order, "serendipity tetrahedron" and the existing quadratic simplex are effectively the same finite element family in this codebase.

Iteration after benchmarking. No further optimisation was required after the first measurement because the results already matched the intended architectural outcome:

- reduced tensor-product node count translated into lower runtime cost;
- simplex serendipity remained mathematically and computationally aligned with the existing implementation;
- no additional runtime indirection was introduced.

10.7 Architectural Takeaways

This extension validates several design choices of the current library:

1. **External polymorphism works.** A new family was added without redesigning `ElementGeometry`.
2. **Reference-cell-centric design scales.** Static reference nodes and subentity topology remain the right place to encode geometric knowledge.
3. **Geometry and physics remain decoupled.** The new elements plug into the same generic physical element and VTK machinery.

4. **The simplex/tensor-product split is conceptually sound.** The tetrahedral case did not need an artificial reduced basis, while the hexahedral case benefited from a genuinely different family.

10.8 Future Work

The present implementation intentionally stops at order 2. Sensible next steps would be:

- reduced-integration variants for HEX20;
- serendipity quadrilateral usage in shell formulations;
- higher-order incomplete tensor-product families if they are needed;
- a more explicit distinction in the type system between "quadratic simplex" and "serendipity simplex" if higher-order simplex variants are later introduced.

At this stage, however, the library now has a complete and usable quadratic serendipity pathway for both the tensor-product and simplex branches, with tests, benchmark coverage, and VTK output.

Chapter 11

Domain Refactor Ontology

This chapter does not yet present the final implementation of the `Domain` refactor. Its purpose is more foundational: to fix the *ontology* of the codebase before more invasive changes are made.

The current implementation already contains several useful abstractions: `Point`, `Node`, `IntegrationPoint`, `MaterialPoint`, `NodeSection`, `MaterialSection`, and `SectionGeometry`. The architectural difficulty is that some of these types represent *different concepts that happen to coincide geometrically*, while others represent *the same physical location under different numerical roles*. If those roles are not separated explicitly, `Domain` becomes the place where geometry, analysis state, quadrature, and constitutive bookkeeping collapse into a single layer.

The refactor should therefore begin by answering a simple question:

> What kinds of "points" exist in the library, and what exactly does each one mean?

11.1 Architectural Diagnosis

At present, the library contains three partially overlapping strata:

1. **Geometric entities:** reference cells, mapped element geometry, coordinates, frames, section shapes.
2. **Discrete unknown carriers:** nodal degrees of freedom, constrained DOFs, PETSc indexing.
3. **Sampling / constitutive sites:** Gauss points, material points, beam sections, shell sections.

The main architectural leak is that `Node` currently belongs to both the first and second strata at the same time. It is a geometric point, but it is also the owner of nodal DOF indices and PETSc-related mesh indexing. This is convenient for a first implementation, but it prevents a clean `Domain` abstraction because a geometry-only domain should not need to know anything about nodal unknown layouts.

There is a second leak in the repeated use of the word *section*. In the current code, *section* may refer to:

- a structural cross-section shape (`SectionGeometry`);
- a section plane located at a node (`NodeSection`);
- a constitutive section sample along a beam or shell (`MaterialSection`);
- a PETSc `PetscSection`, which is purely an indexing map and not a structural section at all.

These are not small naming issues. They correspond to genuinely distinct mathematical objects.

11.2 Entity-by-Entity Semantics

11.2.1 `Point<Dim>`

`Point<Dim>` is the cleanest entity in the current design. It is a coordinate value type: a point in physical space with no identity, no topology, no DOFs, no material, and no ownership semantics beyond ordinary C++ value semantics.

What it is. A metric object in $\mathbb{R}^{\mathrm{Dim}}$.

What it is not. It is not a mesh vertex, not a quadrature point, not a node in the FEM sense, and not a constitutive point.

Architectural role. `Point` should remain the lowest-level geometric atom. Any richer entity that has coordinates should refine or contain a `Point`.

11.2.2 `Vertex<Dim>` (proposed and introduced in this step)

`Vertex<Dim>` is the missing geometry/topology abstraction. It is a `Point` with a stable mesh identity, but without analysis state. In other words:

$$\texttt{Vertex} = \texttt{Point} + \texttt{mesh identity}.$$

What it is. A vertex of the discrete domain mesh. It represents a topological 0-cell and its physical coordinates.

What it is not. It is not a carrier of primary unknowns. It has no nodal DOFs, no constraint state, and no constitutive variables.

Why it matters. If `Domain` is supposed to live at the geometric level, then it should own `Vertex` objects, not `Node` objects. The new `Vertex.hh` introduced in this iteration fixes the intended target abstraction without forcing an immediate rewrite of every consumer.

11.2.3 `Node<Dim, Storage>`

`Node` is currently defined as

$$\texttt{Node} = \texttt{Point} + \texttt{id} + \texttt{DoF storage} + \texttt{PETSc/DMPlex indexing metadata}.$$

What it is. An analysis-layer discrete unknown carrier. More precisely, it is a nodal site where one or more primary fields are stored and indexed globally.

What it is not. It should not be interpreted as the pure geometric vertex of the domain.

Current status. The current implementation uses `Node` in both senses: as the thing owned by the domain, and as the thing that carries DOFs. This is precisely the coupling that the refactor should remove.

Target interpretation after refactor.

$$\texttt{Node} = \texttt{Vertex} + \texttt{field attachment}.$$

This does not necessarily mean inheritance. The important point is semantic: `Node` belongs to the analysis/model layer, not to the geometry/domain layer.

11.2.4 `IntegrationPoint<dim>`

`IntegrationPoint` is a sampling site used by numerical integration. It stores physical coordinates, a quadrature weight, and an identifier.

What it is. A numerical quadrature sample attached to an element geometry.

What it is not. It is not a mesh vertex and not a constitutive model by itself.

Important nuance. An integration point represents a *role*, not merely a location. Two different entities can occupy the same coordinates and still not be the same thing. This is crucial for understanding Lobatto collocation and mixed formulations.

Potential improvement. Eventually, `IntegrationPoint` should probably be understood as a *sample site* with:

- a physical coordinate;
- a reference coordinate;
- a numerical weight;
- possibly the differential measure $|J|$ or a cached metric.

The current implementation already covers the first and third items.

11.2.5 `MaterialPoint<MaterialPolicy>`

`MaterialPoint` is the constitutive analogue of a continuum Gauss point. It binds a `Material<Policy>` to an `IntegrationPoint`.

What it is. A constitutive state machine attached to a continuum sampling site.

What it is not. It is not geometry, not a mesh node, and not a quadrature rule.

Mathematical meaning. For a continuum element, the geometric interpolation produces the kinematic state at a sampling location; the material point then stores and updates the constitutive history at that location:

$$\texttt{ElementGeometry} \longrightarrow \texttt{IntegrationPoint} \longrightarrow \texttt{MaterialPoint}.$$

11.2.6 `SectionGeometry`

`SectionGeometry` is not a point at all. It is the geometric description of a structural cross-section: area, moments of inertia, torsional constant, and shear factors.

What it is. Cross-section *shape* data.

What it is not. It is not a location, not a node, and not a constitutive point.

Architectural consequence. The name is correct, but it must stay clearly separated from both `PetscSection` and `MaterialSection`.

11.2.7 `NodeSection<Dim, Geom>`

`NodeSection` combines:

1. a nodal location;
2. a local section frame;
3. a cross-section geometry.

What it is. A *section station* located at a node, that is, a nodal section plane with shape data and orientation.

What it is not. It is not a constitutive sampling point unless a formulation explicitly chooses to collocate section constitutive evaluation at that nodal station.

Why this distinction matters. In many beam and shell formulations, the nodal section plane is a geometric interpolation entity, whereas the constitutive update happens at different quadrature stations.

11.2.8 `MaterialSection<MaterialPolicy>`

`MaterialSection` is the structural analogue of `MaterialPoint`. It binds a section constitutive law to an integration point along a beam axis or shell midsurface.

What it is. A constitutive state machine attached to a structural sampling site.

What it is not. It is not the same as `SectionGeometry`, and not the same as `NodeSection`.

Mathematical meaning. It stores and updates generalized stress-resultants as functions of generalized strain measures:

$$\texttt{generalized strains} \mapsto \texttt{section resultants}.$$

Architectural observation. `MaterialPoint` and `MaterialSection` are role siblings. The first is a continuum constitutive site; the second is a structural constitutive site.

11.2.9 `PetscSection`

Although it is not a C++ entity defined in this library, it deserves explicit mention because it introduces the strongest terminological collision.

What it is. A PETSc map from mesh points to numbers of DOFs, offsets, and constraints.

What it is not. It is neither a structural section nor a constitutive section.

Architectural rule. `PetscSection` belongs to the solver/indexing infrastructure and should never be allowed to contaminate the semantics of structural section objects.

11.3 Coincidence Versus Identity

The most important conceptual rule for the refactor is the following:

> Two entities may coincide in space without being the same numerical object.

This rule resolves the apparent paradoxes raised by Lobatto quadrature and mixed formulations.

11.3.1 Case 1: Gauss–Lobatto beam quadrature

Suppose a beam formulation uses Gauss–Lobatto integration. Then the end quadrature points lie exactly at the beam endpoints. If the beam also uses nodal section stations at the endpoints, then:

- the *nodal section station* at the endpoint;
- the *quadrature point* at the endpoint;
- the *constitutive section sample* at the endpoint

all share the same physical coordinates.

That does *not* mean they should necessarily be represented by the same object. Their roles are distinct:

- the nodal station belongs to interpolation and field attachment;
- the quadrature point belongs to integration;
- the constitutive section sample belongs to material evolution.

The right design principle is therefore:

> collocation should be represented as a relationship, not as ontological collapse.

In practice, this means that a Lobatto endpoint can be modelled as *three roles sharing one location*, rather than as a single overloaded object.

11.3.2 Case 2: mixed or assumed-strain formulations

In formulations such as degenerated Timoshenko beams or MITC shell families, some sampling sites may acquire independent unknowns, tying variables, or assumed-strain parameters.

Here again, the key is to separate:

1. the geometric location of the sample;
2. the fact that it is used in integration;
3. the fact that additional discrete unknowns live there.

An integration point with independent unknowns is therefore *not* "a node in disguise"; rather, it is a sampling site that additionally plays the role of a field carrier.

Recommended interpretation. The library should treat this as:

$$\texttt{SampleSite} + \texttt{FieldAttachment},$$

not as a reason to redefine `IntegrationPoint` itself as a node.

This preserves both conceptual clarity and extensibility. The same sampling site can later carry:

- a constitutive law only;
- constitutive law plus internal variables;
- constitutive law plus independent element-local DOFs;
- tying or assumed-strain data without constitutive history.

11.4 Proposed Ontology for the Refactor

The cleanest layered ontology for `fall_n` is the following.

11.4.1 Layer 0: pure geometry/topology

- `Point<Dim>`: coordinates only.
- `Vertex<Dim>`: point + mesh identity.

- `ElementGeometry<Dim>`: mapped geometry, reference interpolation, quadrature mapping, face extraction.
- `Domain<Dim>`: owns vertices, element geometries, boundary groups, and PETSc mesh materialisation support, but no DOFs and no constitutive state.

11.4.2 Layer 1: discrete field attachment

- `Node`: a field-bearing attachment to a vertex, carrying nodal DOFs and constraints.
- future internal field sites: element-local unknown carriers for mixed methods or assumed-strain formulations.
- `PetscSection`: global indexing metadata for those field sites.

11.4.3 Layer 2: sampling and constitutive sites

- `IntegrationPoint`: numerical sample site.
- `MaterialPoint`: continuum constitutive site.
- `MaterialSection`: structural constitutive site.
- future tying or assumed-strain sites: sampled kinematic fields that may or may not have constitutive state.

11.4.4 Layer 3: structural section semantics

- `SectionGeometry`: cross-section shape properties.
- `NodeSection`: nodal section station = node + frame + section geometry.
- section constitutive relations (`TimoshenkoBeamSection3D`, `MindlinShellSection`, `FiberSection`): map generalized strains to resultants.

This layering produces a clean separation between:

1. *where something is*;
2. *how it is sampled*;
3. *what unknowns live there*;
4. *what constitutive law is evaluated there.*

11.5 Implications for `Domain`

Under this ontology, `Domain` should evolve toward the following responsibilities:

1. ownership of mesh vertices;
2. ownership of element geometry objects;
3. storage of boundary groups and physical labels;
4. translation to `DMPlex`;
5. topology and geometry queries.

And it should explicitly *not* own:

1. nodal DOF layouts;
2. constitutive points;
3. material state;
4. structural section stations;
5. solver vectors or matrices.

This has a direct consequence for the current code:

> `Domain` owning `Node` is architecturally temporary, not final.

The first code step taken in this iteration is therefore the introduction of `Vertex<Dim>` as the future geometry-level entity.

11.6 HPC and Compile-Time Guidance

The user requirement for the refactor is not only architectural cleanliness but also efficiency in a high-performance context. That requirement strongly favours a few design rules.

11.6.1 Prefer static structure in hot paths

The current library already uses static polymorphism effectively in the element kernel. That should continue. In particular:

- shape functions, quadrature rules, and reference-cell topology should remain compile-time objects whenever possible;
- constitutive updates should stay inside element-local loops with no new virtual dispatch;
- small fixed-size Eigen matrices are still the right choice for local operators.

11.6.2 Keep `Domain` simple, not hyper-generic

The right way to favour HPC here is *not* to template `Domain` on every imaginable backend or policy. That would increase compile times, fragment code paths, and create speculative abstraction.

The efficient choice is:

- keep `Domain` concrete and PETSc-oriented;
- separate concepts cleanly;
- minimise includes and cross-layer dependencies;
- keep backend-specific code concentrated in a few classes.

11.6.3 Avoid type collapse when roles overlap

Role overlap should be represented through composition and index maps rather than inheritance-heavy unions of responsibilities.

This means:

- a Lobatto endpoint may be both nodal station and quadrature sample, but that is best represented by shared coordinates or shared IDs, not by redefining one type to become the other;
- a mixed formulation with internal DOFs at sample sites should introduce a dedicated field attachment for those sites, not redefine every integration point in the library as a node.

11.6.4 Recommended storage philosophy

For the next stages of the refactor, the following storage strategy is the most coherent with the current codebase:

- `Vertex`: compact aggregate, trivially copyable if possible;
- `Node`: inline or SBO DOF storage as already implemented;
- `IntegrationPoint`: compact POD-like sample record;
- constitutive points: element-local vectors, because they are naturally owned by elements and evolved elementwise;
- PETSc indexing: stored in model/solver-side data structures, not in the geometric domain.

This preserves cache locality while keeping compile-time structure strong and runtime dispatch localized.

11.7 Migration Plan

The refactor should proceed incrementally.

Phase 1: fix ontology

- introduce `Vertex`;
- document the role separation;
- stop using "section" ambiguously in new code.

Phase 2: decouple geometry from nodal unknowns

- move `Domain` toward `std::vector<Vertex<dim>>`;
- make `ElementGeometry` depend on a geometry-only vertex concept rather than directly on `Node`;
- relocate DOF assignment and constraints fully to `Model`.

Phase 3: make field attachments explicit

- define how primary nodal unknowns are attached to vertices;
- introduce dedicated internal field sites for mixed methods when needed;
- keep collocation and coincidence as relationships, not type collapse.

Phase 4: unify constitutive-site patterns

- consider a shared abstraction behind `MaterialPoint` and `MaterialSection`;
- preserve policy-based constitutive dispatch and element-local storage.

11.8 Conclusion

The central conclusion of this chapter is simple:

> The library does not suffer from having too many abstractions; it suffers from having a few abstractions that currently play more than one role.

The remedy is therefore not more runtime polymorphism, but better ontological separation:

- `Point` for coordinates;
- `Vertex` for mesh geometry/topology;
- `Node` for field attachment and DOFs;
- `IntegrationPoint` for numerical sampling;
- `MaterialPoint`/`MaterialSection` for constitutive state;
- `SectionGeometry`/`NodeSection` for structural section geometry and nodal section stations.

Once this distinction is enforced, the `Domain` refactor becomes much less ambiguous. The domain can stay geometrically clean, the model can own the discrete unknowns, and the element layer can continue to exploit strong compile-time structure without sacrificing conceptual clarity.

Chapter 12

Domain Vertex Transition

Chapter 11 fixed the ontology of the refactor. This chapter documents the next implementation step: the domain now treats `Vertex` as the canonical geometric storage, while `Node` survives as a transitional analysis-layer cache.

The design goal of this step is deliberately modest:

> move the ownership boundary of `Domain` toward pure geometry without breaking the current element, model, and PETSc assembly pipelines.

That means this is not yet the final state of the refactor. It is the bridge state that keeps existing kernels working while removing the strongest geometric/analysis conflation.

12.1 Motivation

Before this step, `Domain` owned a vector of `Node<dim>`. That had three consequences:

1. the geometric domain depended directly on nodal DOF storage;
2. simply constructing a domain implied that the domain was already in an analysis-ready state;
3. purely geometric consumers such as mesh export were forced to read geometry through analysis nodes.

This was workable, but it obscured the intended layering:

$$\texttt{Domain} \not\equiv \texttt{Model}.$$

The refactor therefore changes the ownership model to:

$$\texttt{Domain owns vertices}, \quad \texttt{Model / assembly consume nodes}.$$

12.2 Implemented Transition Design

12.2.1 Canonical storage

`Domain` now stores

```
std::vector<Vertex<dim>>
```

as its primary geometric container. This is the authoritative representation of mesh points for:

- coordinates;
- mesh identity;
- sorting and lookup by vertex ID;
- geometry-only consumers.

12.2.2 Node cache

To preserve compatibility with the current element and model infrastructure, `Domain` also materialises a

```
std::vector<Node<dim>>
```

cache on demand. This cache is derived from the vertices and is used only when analysis-level operations require nodal DOFs or PETSc indexing.

This means the runtime interpretation is now:

- `vertices_` is the geometric truth;
- `nodes_cache_` is a derived analysis view.

Why this is acceptable. The cache is not introduced for performance in the hot path. It is a compatibility layer during migration. Since nodes are created once and then reused during analysis, the cost is negligible relative to element assembly and material updates.

12.2.3 Cache invalidation rule

Whenever the vertex container changes, the node cache is invalidated. The next request for `nodes()`, `node(id)`, or element-node binding rebuilds the cache.

This makes the design explicit:

> geometry changes invalidate analysis views.

That is the correct dependency direction.

12.3 Why This Preserves Performance

The user requirement for this refactor was clear: do not sacrifice runtime performance unnecessarily, and favour compile-time structure suitable for HPC.

This implementation respects that requirement in three ways.

12.3.1 No change to element hot loops

The integration, constitutive update, and local stiffness computations remain exactly where they already were:

- `ElementGeometry`;
- `ContinuumElement`;
- `BeamElement`;
- `TimoshenkoBeamN`;
- `ShellElement`.

Those kernels still operate on bound `Node` objects and continue to benefit from fixed-size matrices, compile-time quadrature, and policy-based dispatch.

12.3.2 Geometry-only consumers stop depending on nodes

The VTK mesh-export path was updated to read coordinates from `Domain::vertices()` rather than from `Domain::nodes()`. This is architecturally cleaner and slightly cheaper conceptually: geometry is now consumed as geometry.

12.3.3 PETSc creation is now lazy

An important side effect of the refactor is the change to `Mesh`. The `DM` object is no longer created in the `Mesh` constructor. Instead, it is created lazily when the DMPlex-specific operations are first needed.

This has two benefits:

1. a purely geometric `Domain` can be created and manipulated without immediately entering PETSc runtime semantics;
2. tests that exercise only the geometric/domain side no longer require `PetscInitialize`.

Architecturally, this is important because it moves PETSc from "always present" to "activated when the backend is actually used".

12.4 Code-Level Changes

The main code changes in this phase are:

1. `Vertex<Dim>` introduced earlier becomes the canonical storage type inside `Domain`.
2. `Domain` gains explicit vertex accessors: `vertices()`, `vertex(id)`, `num_vertices()`.
3. `Domain::nodes()` becomes a lazily materialised analysis view.
4. `GmshDomainBuilder` now sorts the domain through `sort_vertices_by_id()` rather than sorting the nodal view.
5. `VTKModelExporter` and the legacy `VTKDataContainer` now use vertices for mesh coordinates.
6. `Mesh` now creates the PETSc `DM` lazily.

This is intentionally a minimal-surface-area change. The aim was to shift the ownership boundary without forcing an immediate rewrite of `ElementGeometry` or `Model`.

12.5 What Remains Transitional

This phase does *not* yet complete the domain refactor.

The following are still transitional:

- `ElementGeometry` still binds concrete `Node` pointers, not geometry-only vertex handles.
- `Model` still reads and writes nodal DOF data through the domain-level node view.
- PETSc sieve IDs are still stored in `Node`, not yet in a dedicated analysis/indexing layer.

That is acceptable at this stage. The important structural improvement is that these analysis concerns are no longer the *canonical ownership model* of the domain itself.

12.6 Validation

This phase adds a dedicated test executable for the transition.

12.6.1 Domain/Vertex refactor test

The new test checks:

1. that vertices are the canonical stored geometry;
2. that the nodal view is materialised from those vertices;
3. that sorting vertices updates the nodal view coherently;
4. that analysis-only data written into the node cache does not alter the geometric meaning of the corresponding vertex;
5. that the legacy `add_node(Node&&)` path still preserves geometry correctly.

12.6.2 Regression coverage

The existing serendipity test suite was recompiled and rerun after this change, which is a useful regression check because it exercises:

- `ElementGeometry`;
- quadrature;
- VTK export;
- geometry binding through nodes.

In addition, the Gmsh pipeline target was rebuilt successfully, confirming that the builder and domain interface remain consistent at compile time.

12.7 Architectural Consequences

This transition has one especially important architectural consequence:

> `Domain` can now be understood as a geometric object that happens to be able to provide an analysis view, rather than as an analysis object that also stores geometry.

That inversion is subtle, but it matters. It clarifies the dependency direction for the next phase:

1. first, geometry is owned by the domain;
2. second, analysis nodes are attached or materialised from it;
3. third, elements and solvers consume those analysis nodes.

This is much closer to the ontology laid out in the previous chapter.

12.8 Next Step

The next logical step is now well defined:

> remove the direct `Node`-dependence from `ElementGeometry`.

That will require introducing a geometry-facing vertex handle or concept for binding coordinates, while the model layer separately manages nodal DOFs and PETSc indexing.

Once that is done, `Domain` will no longer need to expose a nodal cache at all, except perhaps as a legacy adapter.

12.9 Conclusion

This chapter marks the first real implementation step of the domain refactor. The main result is not a new feature but a new ownership boundary:

- vertices own domain geometry;
- nodes are an analysis view;
- mesh export reads geometry from vertices;
- PETSc mesh backend creation is deferred until needed.

No element hot path was slowed down, no quadrature logic was generalized away, and existing element kernels continue to operate unchanged. That is the right kind of progress for this refactor: architectural movement without numerical regression.

Chapter 13

Geometry-Only Element Binding

13.1 Context

After the first `Domain` transition, the library already stored `Vertex<Dim>` as the canonical geometric entity while keeping a lazy `Node<Dim>` cache for analysis. That solved the ownership problem in `Domain`, but a structural coupling remained in the element layer: `ElementGeometry` and the concrete element families still used `Node` as the source of physical coordinates.

Architecturally, that was still inconsistent with the ontology established in Chapter 11. A `Node` is an analysis attachment that carries degrees of freedom, PETSc numbering, and constraints. Geometry, however, only needs physical coordinates. The second phase of the refactor therefore separates these two bindings inside the element geometry layer.

13.2 Problem Statement

Before this change, a tensor-product, simplex, or serendipity element stored a single pointer array

$$\{\texttt{Node<dim>*}\}_{a=1}^{n_{\text{node}}}$$

and used that same array both for:

1. geometric interpolation and Jacobian evaluation, and
2. analysis-level access to nodal degrees of freedom.

This conflated two different roles:

$$\text{geometry site} \neq \text{analysis node}.$$

Even when both roles are collocated in space, their semantics are distinct. A continuum element can be fully geometrically defined from vertices without any DOF allocation. Conversely, an analysis formulation may decorate a point with DOFs, constraints, or solver indices without changing its geometric role.

13.3 Design Objective

The goal of this phase was to make the geometry layer depend only on the minimum abstraction required for isoparametric mapping:

`Point<Dim>` or a type derived from it.

At the same time, the analysis layer still needs direct access to `Node<Dim>` once PETSc sections and elemental DOFs are assigned.

The desired split is therefore:

`ElementGeometry` $\longrightarrow$ `Point/Vertex binding`	for $x(\boldsymbol{\xi}), J(\boldsymbol{\xi}), \mathrm{d}\Omega$,
`ElementGeometry` $\longrightarrow$ `Node binding`	for DoFs, constraints, and PETSc layout.

13.4 Implemented Refactor

13.4.1 New dual binding inside concrete elements

The three concrete element families

- `LagrangeElement`,
- `SimplexElement`, and
- `SerendipityElement`

now hold two logically distinct pointer arrays:

```
points_p : Point<Dim>*
nodes_p : Node<Dim>*
```

The geometry path uses only `points_p`. In particular:

- `coord_array()`,
- `map_local_point()`, and
- `evaluate_jacobian()`

no longer depend on `Node`.

The analysis path continues to use `nodes_p`. Methods such as `node_p()` and all element-level DOF collection code remain unchanged.

13.4.2 Wrapper-level support in `ElementGeometry`

The type-erased wrapper was extended with:

- `bind_point(i, Point<dim>*)`,
- `point_p(i)`,
- existing `bind_node(i, Node<dim>*)`, and
- existing `node_p(i)`.

This preserves the previous public API for analysis code while adding an explicit geometry-only binding channel.

13.4.3 Key compatibility rule

Whenever a `Node` is bound, the corresponding geometry point is also bound automatically. In symbols:

$$\texttt{bind_node}(i, n) \Longrightarrow \texttt{bind_point}(i, n).$$

This means:

- legacy code that only binds nodes still works unchanged;
- new geometry-first code can bind vertices before any DOFs exist.

13.5 Domain-Level Consequences

13.5.1 Geometry-first linking

`Domain` now exposes a dedicated `link_geometry_to_elements()` phase. It binds each element node id to its canonical `Vertex<dim>`:

$$\texttt{element.node(i)} \mapsto \texttt{vertex_by_id[element.node(i)]}.$$

This enables:

- geometric mapping,
- Jacobian evaluation,
- integration point placement, and
- geometry-driven boundary extraction

without first materialising the analysis-node cache.

13.5.2 Boundary extraction no longer needs `node_p().id()`

The plane-based boundary builder previously queried geometric membership through `elem.node_p(local).id(` which forced the existence of node bindings. After the refactor, face detection uses only the canonical element connectivity:

`elem.node(local).`

The resulting boundary element is then:

1. created from the face connectivity,
2. immediately bound to `Vertex` objects for geometry, and
3. optionally bound to `Node` objects if the analysis cache already exists.

13.5.3 Sieve assembly remains analysis-oriented

The PETSc sieve assembly still needs analysis nodes because sieve ids and DOF layout belong to the solver layer. However, even there the distinction is now cleaner:

- geometry binding prepares the element for integration and mapping;
- node binding prepares the element for DOF and PETSc interaction.

13.6 Why this is efficient

13.6.1 No new runtime polymorphism in the hot path

The critical loops for element integration remain unchanged:

- quadrature rule selection is still static via templates,
- local reference-space evaluation remains compile-time typed,
- Jacobian and interpolation work on fixed-size Eigen objects,
- the type-erased wrapper is still crossed only at the same boundary as before.

The only additional state is a pointer array to `Point<Dim>` inside each concrete element. Accessing `coord(i)` through a `Point` base reference is not virtual; it is just a normal base-subobject access. Therefore this refactor does not introduce a new dynamic-dispatch cost in the Gauss loop.

13.6.2 Compile-time impact

The change slightly increases template surface area in the element headers, but the trade-off is favourable:

- `Domain.hh` no longer needs to include Gmsh reader details;
- geometry-only workflows can avoid dragging analysis semantics into lower layers;
- future specialisations can target `Point`/`Vertex` independently of PETSc-related analysis infrastructure.

For an HPC-oriented codebase this is important because the hottest kernels remain statically shaped, while architectural boundaries become cleaner and easier to optimise separately.

13.7 Validation

The test suite was extended with geometry-first checks in the `domain_vertex_refactor` executable:

1. a quadrilateral element can map its centre and integrate area after binding only vertices;
2. a boundary element generated by `create_boundary_from_plane()` can map and integrate from vertex binding alone.

These tests validate the new invariant:

element geometry is usable as soon as geometry is bound, even if analysis nodes have not yet been materialised.

13.8 Architectural Interpretation

This phase does not eliminate `Node` from the library. It puts `Node` back in its proper role.

- `Vertex`: canonical domain geometry/topology entity;
- `Point`: minimal coordinate carrier;
- `ElementGeometry`: geometric interpolation operator over bound points;
- `Node`: analysis decorator attached later when the model introduces DOFs.

That separation is especially important for future mixed and structural formulations, where collocation between geometry sites, integration sites, and DOF-carrying sites may occur but should not collapse the underlying concepts.

13.9 Next Step

The next logical phase is to propagate this distinction upward:

- reduce remaining read paths that only need connectivity ids but still access `node_p()`;
- make geometry-only exporters and preprocessors depend only on `Vertex`/`Point`;
- move more of the solver-specific state management out of `Domain` and into the model/-analysis side.

At that stage, `Domain` will be geometrically pure not only in storage, but also in the majority of its operational paths.

Chapter 14

Low-Level Geometry and DoF Access

14.1 Motivation

Once the higher-level ontological split between `Vertex`, `Node`, and `ElementGeometry` was in place, the next question was lower-level: how much indirection remains in the hot path, and where does the code still pay avoidable access cost?

The target of this pass was not a redesign of algorithms. It was a careful data-access refinement guided by three HPC-oriented principles:

1. keep the public concepts explicit and semantically correct;
2. reduce repeated pointer chasing in frequently evaluated geometry code;
3. preserve value semantics and compile-time structure.

14.2 `Point<Dim>` as a contiguous data source

14.2.1 Previous state

`Point<Dim>` already stored coordinates in a `std::array<double, Dim>`. However, the main accessor returned that array by value. For a small fixed-size object this is not catastrophic, but it encourages copies and obscures the fact that the coordinates are already stored contiguously in memory.

14.2.2 Implemented change

`Point<Dim>` now exposes:

- `coord()` returning a *const reference* to the internal array for lvalues,
- `coord_ref()` as the explicit aliasing form, and
- `data()` returning a raw pointer to the contiguous coordinate storage.

This is a small but important clarification. It makes `Point` suitable not only as a semantic geometry entity but also as a low-level storage source for element kernels.

14.2.3 Why this matters

The geometry kernels repeatedly evaluate expressions of the form

$$x_i = \sum_a N_a(\boldsymbol{\xi})\, x_{a,i}, \qquad J_{ij} = \sum_a x_{a,i}\, \frac{\partial N_a}{\partial \xi_j}.$$

The coordinates $x_{a,i}$ are read many times. Making the contiguous storage explicit enables later code to cache direct pointers to those values instead of repeatedly calling higher-level accessors.

14.3 Node<Dim, Storage> and direct DoF access

14.3.1 Added direct pointer interface

Node already exposed dof_index() as a span, which is a good high-level interface. This pass adds dof_data() for the cases where the caller already knows the number of DOFs and only needs the raw contiguous pointer for PETSc interaction.

This is now used in selected PETSc-heavy paths such as boundary-condition and model bookkeeping code.

14.3.2 Array constructors

Node also gained constructors from std::array<double, Dim>. This reduces the need for std::apply-style reconstruction when a node is materialised from a geometry object such as Vertex<Dim>. In practice, this simplifies the Domain transition code and keeps template instantiation noise lower.

14.4 Cached coordinate pointers inside geometric elements

14.4.1 Problem

After the previous refactor, each concrete geometry family already stored a geometry-only binding to Point/Vertex. That fixed the architectural coupling, but the implementation still fetched coordinates through chains like

$$\texttt{points}[a] \to \texttt{coord()} \to \texttt{array}[i].$$

This is acceptable, but it is still more indirect than necessary inside the innermost geometry loops.

14.4.2 Implemented solution

The concrete families

- LagrangeElement,
- SimplexElement, and
- SerendipityElement

now cache, at bind time, direct pointers to the coordinate storage of each bound point:

$$\texttt{coord_data_[a]} = \texttt{point_a.data()}.$$

The geometric hot path then uses:

- coord_data_[a][i] in coord_array(),
- coord_data_[a][i] in evaluate_jacobian().

This removes a repeated layer of accessor traffic while preserving the semantic Point/Vertex binding.

14.4.3 Why this is safe

The cached coordinate pointers are non-owning views into the bound geometry objects. They are valid under the same condition that already governed the older point/node pointer bindings:

the lifetime and address stability of the bound geometry objects must exceed the lifetime of the bound element geometry.

This is not a new invariant; it is simply made more explicit.

14.5 Residual geometry-via-node usage in beam elements

14.5.1 Observation

Even after the previous phases, `BeamElement::compute_frame()` still read coordinates from `geometry_->node_p(0)` and `geometry_->node_p(1)`. That meant the beam frame computation still depended on analysis nodes even though it is purely geometric.

14.5.2 Implemented change

The beam frame is now built from:

`geometry_->point_p(0).coord_ref()`, `geometry_->point_p(1).coord_ref()`.

Therefore a beam element can compute its frame from geometry-only bindings before nodal DOFs are present.

14.6 Validation and traceability

This pass added or extended tests in three places:

1. `test_point.cpp`: verifies aliasing and contiguous pointer access for `Point`;
2. `test_node_dof.cpp`: verifies array construction and `dof_data()` consistency for `Node`;
3. `test_beam_element.cpp`: verifies that beam frame construction works from geometric vertices alone, without materialising analysis nodes.

These tests complement the earlier `domain_vertex_refactor` checks and make the refactor traceable from ontology down to low-level data access.

14.7 Interpretation

This chapter is intentionally modest in scope. It does not claim a microbenchmark-proven global speedup. What it does provide is a stricter and cleaner data path:

- geometry entities expose their contiguous storage explicitly;
- analysis entities expose their contiguous DOF storage explicitly;
- geometric elements cache the minimal data needed for repeated interpolation and Jacobian evaluation;
- structural elements use geometry where geometry is enough.

That is the right kind of optimisation for this codebase: local, transparent, semantically aligned, and compatible with the broader compile-time design.

Chapter 15

Spatial Sites and Lazy Domain Materialisation

15.1 Scope of this pass

This chapter documents the next incremental step of the `Domain` refactor. The change is deliberately modest in algorithmic scope and strict in architectural intent:

- keep `Domain` geometry-first;
- avoid materialising analysis nodes when only geometry is needed;
- make the different "point-like" entities comparable through a small static concept vocabulary;
- preserve the low-level requirements of HPC kernels: contiguous storage, inlining, and minimal pointer chasing.

The result is not a full removal of `Node` from the upper layers. It is an ontologically cleaner and computationally cheaper boundary between geometry, analysis, and constitutive sampling.

15.2 The problem of overlapping point-like concepts

Finite-element codes naturally generate several entities that look similar because they all carry coordinates. However, they are not the same concept. The overlap becomes especially visible in structural and mixed formulations:

- in Gauss–Lobatto beam integration, an endpoint may be both a nodal station and an integration station;
- in continuum formulations, a constitutive material point is collocated with a quadrature point but is not itself the quadrature rule;
- in mixed formulations, an integration site may also carry field unknowns, but that does not make it identical to a mesh vertex.

Therefore the correct design rule is:

same spatial position does not imply same semantic type.

The implementation should model collocation by *binding* or *decoration*, not by collapsing all roles into a single class.

15.3 A static ontology of spatial sites

15.3.1 Read-only coordinate site: `PointViewT`

This pass introduces a small compile-time concept, `geometry::PointViewT`. A type satisfies it if it exposes:

- a static `dim`,
- `coord()`,
- `coord(i)`,
- `coord_ref()`,
- `data()`.

This concept is intentionally read-only. It captures the minimum common geometry-facing contract needed by algorithms that only inspect coordinates.

15.3.2 Mutable point: `PointT`

`PointT` now refines `PointViewT` by adding coordinate mutation:

- `set_coord(i, value)`,
- `set_coord(array)`.

This split matters because not every site should be mutable. A constitutive wrapper such as `MaterialPoint` should forward coordinates from the integration point it decorates, but it should not pretend to own or mutate the geometry itself.

15.3.3 Entity-by-entity interpretation

With the new interface split, the point-like entities can be classified as follows:

`Point<Dim>` mutable geometric carrier; coordinates only.

`Vertex<Dim>` point plus stable mesh identity.

`Node<Dim, Storage>` point plus analysis identity, DoF storage, and PETSc-related node metadata.

`IntegrationPoint<Dim>` mutable quadrature site; coordinates, weight, and identifier.

`MaterialPoint<Policy>` read-only constitutive decorator bound to an `IntegrationPoint`.

`MaterialSection<Policy>` read-only constitutive decorator for structural sections, also bound to an `IntegrationPoint`.

`NodeSection<Dim>` read-only geometric and DoF-forwarding view over a `Node`, enriched with section frame and section geometry.

The important architectural detail is that only some of these types own coordinates. The others forward them.

15.4 Why forwarding is the right model

15.4.1 Material points and sections

A `MaterialPoint` does not own geometry. It owns constitutive state and binds to the numerical sampling site where that state is evaluated. Therefore it now forwards:

- `coord()`,
- `coord_ref()`,
- `data()`,
- `weight()`.

The same is true for `MaterialSection`. This makes both types valid `PointViewT` sites without duplicating coordinate storage.

15.4.2 Node sections

`NodeSection` already bound a `Node` plus section-specific metadata. This pass makes the forwarding explicit for:

- coordinates (`coord`, `coord_ref`, `data`),
- contiguous DoF storage (`dof_data()`).

This is particularly useful for structural formulations, because a section station is often treated as a special nodal view rather than as a new point owner.

15.5 Lazy node materialisation in `Domain`

15.5.1 Geometric operations should not force analysis state

The earlier `Domain` transition already made `Vertex<Dim>` the canonical geometric storage. However, there were still two remaining issues:

1. `create_boundary_from_plane()` still forced node-cache materialisation even when only geometry was needed;
2. the non-const `node_p(id)` path had an incorrect guard and could skip node-index construction.

15.5.2 Implemented fix

This pass changes the behaviour as follows:

- `create_boundary_from_plane()` is now geometry-first; it binds face elements to vertices immediately and binds nodes only if the node cache already exists;
- `node_p(id)` now reliably builds the node index on demand;
- `Domain` exposes three explicit traceability predicates: `has_materialized_nodes()`, `has_vertex_index()` `has_node_index()`.

The first predicate is important both for debugging and for architectural tests: it allows the test suite to assert that a geometry-only workflow truly stays geometry-only.

15.5.3 Why the node cache still exists

From a purely ontological point of view, one might want to remove `Node` duplication entirely and replace it with a thinner attachment structure. That direction is still plausible, but it should not be taken lightly.

The current element kernels, structural sections, PETSc section setup, and element-level DoF caches still benefit from a stable `Node&` view with:

- inline coordinate access,
- contiguous DoF access,
- zero-cost SBO-backed DoF storage policies,
- no proxy objects in the inner assembly path.

Keeping the node cache while making it lazy is therefore the pragmatic design point for this stage of the refactor.

15.6 Data-layout implications for HPC

15.6.1 Owned storage vs forwarded storage

The implementation now follows a simple rule:

- `Point`, `Vertex`, `Node`, and `IntegrationPoint` own contiguous coordinate storage;
- `MaterialPoint`, `MaterialSection`, and `NodeSection` do not own coordinates and only forward views.

This keeps the hot data local and prevents hidden copies when decorating an existing site with extra semantics.

15.6.2 Why no generic runtime interface was added

An obvious alternative would be an inheritance hierarchy such as:

$$\texttt{ISpatialSite} \leftarrow \{\texttt{Vertex}, \texttt{Node}, \texttt{IntegrationPoint}, \dots\}$$

with virtual coordinate access.

That was intentionally rejected. The reasons are both architectural and computational:

- the library already has enough runtime polymorphism at the `ElementGeometry` and `Material` wrappers;
- coordinate access is too frequent to justify another virtual boundary;
- the overlap between site types is semantic, not behavioural in the object-oriented sense.

Compile-time concepts are the better fit here: they make the common contract explicit without imposing a vtable or pointer-indirection tax.

15.7 What this means for overlapping formulations

The new model clarifies how to think about several important special cases:

Gauss–Lobatto beam integration an endpoint may be represented by a `NodeSection` and by a `MaterialSection` bound to an `IntegrationPoint` at the same coordinate. The location is shared; the role is not.

Continuum material points a `MaterialPoint` is bound to an `IntegrationPoint`. It is not itself the quadrature rule and not a mesh node.

Mixed or assumed-strain formulations if a sampling site later carries unknowns, that should be modelled as an additional attachment or dedicated type, not by erasing the distinction between integration and nodal roles.

This is the key conceptual payoff of the refactor: the code can represent collocation without ontological collapse.

15.8 Validation

This pass was validated by extending the test suite in two directions:

1. `domain_vertex_refactor` now verifies that geometry-only element binding and boundary creation do not materialise the node cache;
2. `integration_sites` verifies that `IntegrationPoint`, `MaterialPoint`, `MaterialSection`, and `NodeSection` satisfy the new static geometry-view contract.

This complements the earlier low-level tests on contiguous access and keeps the refactor traceable from architecture to implementation.

15.9 Interpretation

The central lesson of this step is that the library does not need fewer concepts; it needs cleaner boundaries between them. The right optimisation was not to merge `Point`, `Node`, `IntegrationPoint`, and `Section`-like entities. The right optimisation was:

- to expose their common geometric contract statically,
- to preserve ownership only where ownership is real,
- to keep `Domain` geometry-first for as long as possible,
- to materialise analysis state only when the solver path requires it.

That is a better match for both SOLID-style concept clarity and HPC-oriented implementation discipline.

Chapter 16

Adaptive Nodal Projection for Material Fields

This chapter refines the earlier diagnosis of the TET10 post-processing artefact and documents the resulting architectural change in `VTKModelExporter`. The key conclusion is that *negative quadrature weights are not the only failure mode.* For quadratic simplex elements, the row-sum lumped nodal measures can be non-positive even under all-positive quadrature. Therefore the exporter now chooses the projection operator adaptively.

16.1 Why the Previous Diagnosis Was Incomplete

chapter 3 correctly identified a catastrophic failure mode: if a simplex rule contains negative weights, then the signed support of the quadratic simplex basis can drive the lumped L^2 denominator to zero or to the wrong sign.

However, the ParaView artefact observed for the current TET10 path persisted even after switching to all-positive quadrature rules such as:

- the 4-point Hammer–Marlowe–Stroud rule (`SimplexIntegrator<3,2>`), and
- the 27-point Stroud conical product rule (`ConicalProductIntegrator<3,3>`).

That observation immediately rules out "negative quadrature weights" as the sole root cause. The actual issue lies in the *row-sum lumping itself.*

16.2 Exact Row-Sum Lumping for TET10

For the quadratic tetrahedron, the vertex and edge shape functions are:

$$N_i^{(v)} = \lambda_i(2\lambda_i - 1), \tag{16.1}$$

$$N_{ij}^{(e)} = 4\lambda_i\lambda_j, \tag{16.2}$$

where λ_i are barycentric coordinates.

The lumped nodal measure attached to node I is

$$m_I^{(\ell)} = \int_T N_I \,\mathrm{d}V. \tag{16.3}$$

Using the standard simplex moment formula

$$\int_T \lambda_1^{a_1}\lambda_2^{a_2}\lambda_3^{a_3}\lambda_4^{a_4}\,\mathrm{d}V = |T|\,\frac{a_1!a_2!a_3!a_4!\,3!}{(a_1+a_2+a_3+a_4+3)!}, \tag{16.4}$$

we obtain:

16.2.1 Vertex nodes

$$\int_T N_i^{(v)}\,\mathrm{d}V = \int_T \left(2\lambda_i^2 - \lambda_i\right)\,\mathrm{d}V \tag{16.5}$$

$$= 2\frac{|T|}{10} - \frac{|T|}{4} \tag{16.6}$$

$$= -\frac{|T|}{20}. \tag{16.7}$$

16.2.2 Edge-midpoint nodes

$$\int_T N_{ij}^{(e)}\,\mathrm{d}V = 4\int_T \lambda_i\lambda_j\,\mathrm{d}V \tag{16.8}$$

$$= 4\frac{|T|}{20} \tag{16.9}$$

$$= \frac{|T|}{5}. \tag{16.10}$$

Therefore, for *every* non-degenerate TET10:

$$m_i^{(\ell)} = -\frac{|T|}{20} < 0 \qquad \text{for the four vertex nodes,} \tag{16.11}$$

and

$$m_{ij}^{(\ell)} = \frac{|T|}{5} > 0 \qquad \text{for the six edge nodes.} \tag{16.12}$$

This is an exact statement. It does not depend on the particular positive quadrature rule, provided the rule is at least degree-2 exact.

16.3 Consequence: Lumped L^2 Is Not a Nodal Average

For a nodal projection to behave as an average, the local weights attached to each node must be strictly positive. TET10 violates that requirement at its vertex nodes by construction.

This has two implications:

- The projected nodal value is no longer an average of nearby Gauss-point data.
- The operator behaves like a signed extrapolation, which can overshoot even when the Gauss-point field is smooth and monotone.

This explains the visual symptom seen in ParaView:

- the displacement field is correct, because it is a primary nodal field;
- the Gauss-point strains are correct, because they come directly from the element kinematics;
- the *projected* nodal strains are oscillatory for TET10, because the transfer operator is not a proper averaging operator.

Hence the issue is fundamentally a *post-processing transfer* problem, not a stiffness integration problem.

16.4 Why HEX27 Remains Safe

For the quadratic tensor-product hexahedron, the shape functions are products of one-dimensional quadratic Lagrange polynomials on $[-1, 1]$. Their lumped nodal measures remain strictly positive under the standard $3 \times 3 \times 3$ Gauss–Legendre rule used in `fall_n`. Therefore the row-sum lumped projection still behaves as a genuine nodal average and produces smooth fields.

This distinction is important:

Family	Local lumped nodal weights	Safe to use lumped L^2 by default?
HEX27	strictly positive	yes
TET10	mixed sign	no

16.5 Adaptive Policy Implemented in `VTKModelExporter`

The exporter now exposes:

```
enum class MaterialFieldProjection {
    Auto,
    LumpedL2,
    PolynomialPatchRecovery,
    VolumeWeightedAveraging
};
```

The production path is `Auto`. Its algorithm is:

1. For each element geometry, compute the local lumped nodal weights

$$m_i^{(\ell)} \approx \sum_g N_i(\boldsymbol{\xi}_g)\, w_g\, |J_g|.$$

2. If *all* local weights are strictly positive for *all* elements, use lumped L^2 projection.
3. Otherwise, use polynomial patch recovery (`patch_recover_to_nodes()`).
4. Retain volume-weighted averaging only as an explicit low-order fallback path.

This choice is conservative and appropriate for production visualisation:

- it preserves the smoother lumped L^2 path for element families where it is mathematically sound;
- it automatically protects higher-order simplex elements without forcing the user to know the details of the underlying quadrature rule;
- it avoids the excessive diffusion of a pure volume-average fallback by using a real local reconstruction on unsafe patches.

Complexity. The detection pass costs $O(n_{\text{elem}}\, n_{\text{gp}}\, n_{\text{node}})$, which is of the same order as the projection itself and negligible compared with an FE solve. Because this happens only during post-processing, the architectural priority is robustness and traceability, not micro-optimisation.

16.6 Code-Level Traceability

The implementation is localised in:

- `src/post-processing/VTK/VTKModelExporter.hh` — `MaterialFieldProjection`, `lumped_projection` `has_strictly_positive_lumped_projection_weights()`, `patch_recover_to_nodes()`, and adaptive dispatch in `compute_material_fields()`.
- `main.cpp` — unchanged call site: `compute_material_fields()`, but its semantics are now adaptive rather than hard-coded lumped L^2.
- `tests/test_simplex.cpp` — regression tests that prove:
  - TET10 keeps negative vertex lump weights under positive quadrature;
  - HEX27 keeps strictly positive lump weights.
  - The new patch-recovery path reproduces exact linear and quadratic fields on TET10 patches.

16.7 Verification

Two levels of verification were added:

1. **Mathematical regression:** the simplex test suite now checks the exact TET10 lumped nodal weights under the 4-point positive HMS rule, obtaining $-\frac{1}{120}$ at the four vertices and $\frac{1}{30}$ at the six edge nodes of the reference tetrahedron.
2. **Implementation regression:** the same suite verifies that the 27-point Stroud conical product rule also yields negative TET10 vertex lumps despite its strictly positive quadrature weights, while HEX27 remains strictly positive. It also verifies exact linear recovery on a single TET10 and exact quadratic recovery on a multi-element TET10 patch.

These checks establish the core architectural point:

> For TET10, the unsafe behaviour is not caused by the constitutive model, nor by the computed Gauss-point strains, nor by the positivity of the stiffness quadrature weights. It is caused by using row-sum lumped nodal projection on a shape-function family whose local lumped nodal measures are signed.

Chapter 17

Polynomial Patch Recovery for TET10 Visualisation

This chapter documents the second-stage fix for the TET10 visualisation path. The first fix — avoiding unsafe lumped L^2 projection — was necessary but not sufficient. Replacing signed lumping with a plain volume-weighted average removed the gross artefact, but it also produced a field that was too diffusive for smooth contour rendering. The proper solution is a local polynomial reconstruction over nodal patches.

17.1 Why Averaging Was Not Enough

The TET10 strain field in the cantilever benchmark is smooth at the level of Gauss-point samples: the displacement solution is correct, the kinematics are correct, and the constitutive update is correct. The visual defect appears only after transfer to the nodes.

Volume-weighted averaging fixes the sign problem but throws away too much information:

- it compresses each element to a single average value before nodal transfer;
- it cannot reproduce linear or quadratic intra-element variation;
- it therefore damps gradients that should remain visible in the final contour plot.

For higher-order simplex elements this is the wrong trade-off. The data are already rich enough to support a better local fit, so a production-quality visualisation path should use them.

17.2 Recovered Quantity and Patch Topology

Let node I have coordinate $\mathbf{x}_I$. Its patch is the set of all elements incident on that node:

$$\mathcal{P}_I = \{e \in \mathcal{E} \mid I \in e\}. \tag{17.1}$$

The exporter gathers every Gauss point of every element in $\mathcal{P}_I$. Each observation contributes:

$$(\mathbf{x}_g,\ \sigma_g,\ \omega_g), \tag{17.2}$$

where $\mathbf{x}_g$ is the physical coordinate of the sample, σ_g is the material field component value, and $\omega_g = |w_g J_g|$ is the positive sample weight.

Important distinction. The recovery patch is a *post-processing construct*. It is not part of the FE approximation space, does not add new unknowns, and does not alter the element stiffness formulation. It exists solely to reconstruct a nodal field for rendering.

17.3 Centered and Scaled Basis

To reduce conditioning problems and keep the constant coefficient equal to the recovered nodal value, the polynomial basis is centered at the node:

$$\hat{\mathbf{x}}_g = \frac{\mathbf{x}_g - \mathbf{x}_I}{h_I}, \qquad h_I = \max_{g \in \mathcal{P}_I} \|\mathbf{x}_g - \mathbf{x}_I\|_2. \tag{17.3}$$

For the 3D case, the quadratic basis is

$$\mathbf{p}(\hat{\mathbf{x}}) = \begin{bmatrix} 1 & \hat{x} & \hat{y} & \hat{z} & \hat{x}^2 & \hat{x}\hat{y} & \hat{x}\hat{z} & \hat{y}^2 & \hat{y}\hat{z} & \hat{z}^2 \end{bmatrix}^{\mathsf{T}}. \tag{17.4}$$

With this choice,

$$\tilde{\sigma}_I = p_I(\mathbf{x}_I) = a_{I,0}, \tag{17.5}$$

because all non-constant basis terms vanish at the origin of the local patch coordinates.

17.4 Least-Squares System

For one field component, the recovery solves

$$\mathbf{a}_I = \arg\min_{\mathbf{a}} \sum_{g \in \mathcal{P}_I} \omega_g \left(\mathbf{p}(\hat{\mathbf{x}}_g)^{\mathsf{T}} \mathbf{a} - \sigma_g \right)^2. \tag{17.6}$$

The implementation accumulates the normal equations

$$\mathbf{N}_I = \sum_g \omega_g \, \mathbf{p}_g \mathbf{p}_g^{\mathsf{T}}, \qquad \mathbf{r}_I = \sum_g \omega_g \, \mathbf{p}_g \sigma_g, \tag{17.7}$$

and solves

$$\mathbf{N}_I \mathbf{a}_I = \mathbf{r}_I. \tag{17.8}$$

Why use $|w_g J_g|$? In numerical integration the sign of w_g matters because it contributes to an integral approximation. In patch recovery the role of the weight is different: it measures the local influence of a sample. A negative quadrature weight should therefore *not* negate the influence of a perfectly valid sample in the least-squares fit. Using $|w_g J_g|$ is the correct semantics for recovery.

17.5 Rank-Adaptive Fallback

Not every nodal patch can support a full quadratic fit:

- a boundary node may see too few neighbouring elements;
- a coarse mesh may provide too few independent Gauss points;
- a highly directional patch may lead to rank deficiency.

The exporter therefore uses the following hierarchy:

1. quadratic fit if the patch has enough samples and full rank;
2. linear fit if the quadratic system is rank-deficient;
3. weighted average if even the linear fit is not admissible.

This hierarchy matters in practice. A single TET10 contributes four HMS Gauss points, which is not enough for a quadratic 3D fit (ten coefficients) but is exactly enough for a linear fit (four coefficients). The new regression tests check this explicitly.

17.6 Implementation Choices and HPC Considerations

The implementation in `VTKModelExporter.hh` was written to avoid contaminating the assembly kernels with post-processing concerns:

- all recovery logic is isolated in the exporter;
- the FE solve path, material update path, and element geometry kernels are unchanged;
- the recovery loop uses geometry already bound in the elements, so no new ownership or pointer chains were introduced into the hot path;
- the least-squares accumulation uses fixed-size small Eigen matrices for the normal equations, with only a tiny dynamic solve on the active block size.

This is the right architectural compromise for `fall_n`:

- **compile-time and runtime discipline** are preserved in the FE kernels;
- **visualisation quality** is upgraded where it belongs, in post-processing;
- **traceability** remains high because the policy is explicit in `MaterialFieldProjection`.

17.7 Regression Coverage

Two new tests were added in `tests/test_simplex.cpp`:

1. `test_tet10_patch_recovery_recovers_linear_field_on_single_element()` verifies that the fallback from quadratic to linear fit works and is exact for a linear field on one straight-sided TET10.
2. `test_tet10_patch_recovery_recovers_quadratic_field_on_patch()` verifies exact recovery of a quadratic scalar field at a shared patch node using multiple TET10 elements and real simplex quadrature points.

These tests are more valuable than a screenshot-based validation because they check the transfer operator directly, independently of ParaView rendering settings.

17.8 Architectural Outcome

The final picture is now clean:

- **HEX27** stays on lumped L^2 because its local nodal lumping is positive and well behaved.
- **TET10** automatically switches to polynomial patch recovery because signed lumping makes row-sum L^2 unsuitable as a nodal average.
- **Volume averaging** remains available for debugging and for the rare case where a deliberately diffusive fallback is preferred.

This resolves the remaining mismatch between mathematically correct Gauss-point fields and visually acceptable nodal contours without degrading the performance-oriented architecture of the main finite element code.

Chapter 18

Explicit Tensor Filters for VTK / ParaView

The current VTK contract in `fall_n` is intentionally simple:

- `*_mesh.vtu` stores the continuum mesh and nodal fields;
- `*_gauss.vtu` stores one point per material point and the quadrature fields `qp_*`;
- both datasets can carry `displacement`, and the Gauss cloud receives the interpolated material-point displacement explicitly.

Within that split workflow, the remaining post-processing problem is not data transport but *field semantics*. A raw array named simply `stress` or `strain` is a weak contract: it hides both the carrier and the tensor convention. This chapter documents the cleaned-up naming and the explicit scalar filters now emitted by the exporter.

18.1 Naming Contract

The exporter distinguishes both *location* and *representation*:

- `nodal_*`: values projected onto mesh nodes;
- `qp_*`: values evaluated or stored at material points;
- `_voigt`: raw symmetric-tensor storage in the library's Voigt convention;
- scalar suffixes such as `_xx`, `_von_mises`, or `_equivalent_strain`: explicit post-processing views.

Examples:

- `qp_stress_voigt`, `qp_stress_xx`, `qp_stress_von_mises`;
- `nodal_strain_voigt`, `nodal_strain_xx`, `nodal_strain_equivalent_strain`;
- `qp_plastic_strain_voigt`, `nodal_plastic_strain_equivalent_strain`.

This is the main usability improvement. The user no longer has to infer whether a field is nodal or quadrature-based, and the exporter no longer asks ParaView to reinterpret unnamed raw tensors on the fly.

18.2 Stress Filters

For a symmetric stress tensor $\boldsymbol{\sigma}$, the exporter emits:

- component scalars $\sigma_{xx}, \sigma_{yy}, \sigma_{zz}, \sigma_{yz}, \sigma_{xz}, \sigma_{xy}$;
- trace
$$\mathrm{tr}(\boldsymbol{\sigma}) = \sigma_{xx} + \sigma_{yy} + \sigma_{zz};$$
- mean / hydrostatic stress
$$\sigma_m = \sigma_h = \frac{1}{d}\,\mathrm{tr}(\boldsymbol{\sigma});$$

- pressure
$$p = -\sigma_m;$$
- deviatoric norm
$$\|\operatorname{dev}\boldsymbol{\sigma}\| = \sqrt{\operatorname{dev}\boldsymbol{\sigma} : \operatorname{dev}\boldsymbol{\sigma}};$$
- second deviatoric invariant
$$J_2 = \frac{1}{2}\operatorname{dev}\boldsymbol{\sigma} : \operatorname{dev}\boldsymbol{\sigma};$$
- von Mises / Beltrami–Haigh equivalent stress
$$\sigma_{\mathrm{vm}} = \sigma_{\mathrm{BH}} = \sqrt{\frac{3}{2}\operatorname{dev}\boldsymbol{\sigma} : \operatorname{dev}\boldsymbol{\sigma}};$$
- triaxiality
$$\eta = \frac{\sigma_m}{\sigma_{\mathrm{vm}}};$$
- octahedral shear stress
$$\tau_{\mathrm{oct}} = \sqrt{\frac{2}{3}J_2}.$$

The exporter writes both `von_mises` and `beltrami_haigh`. In this context they are numerically the same J_2-based equivalent stress, but exposing both names removes friction for users who search for one label or the other in ParaView.

18.3 Strain Filters

The strain arrays are stored in engineering Voigt notation:

$$\{\varepsilon_{xx}, \varepsilon_{yy}, \varepsilon_{zz}, \gamma_{yz}, \gamma_{xz}, \gamma_{xy}\}, \qquad \gamma_{ij} = 2\varepsilon_{ij}.$$

The exporter therefore converts the off-diagonal entries back to tensor shear components before evaluating invariants. The derived strain filters are:

- component scalars in the stored engineering convention;
- trace / volumetric strain
$$\varepsilon_v = \operatorname{tr}(\boldsymbol{\varepsilon});$$
- deviatoric norm
$$\|\operatorname{dev}\boldsymbol{\varepsilon}\| = \sqrt{\operatorname{dev}\boldsymbol{\varepsilon} : \operatorname{dev}\boldsymbol{\varepsilon}};$$
- equivalent strain
$$\varepsilon_{\mathrm{eq}} = \sqrt{\frac{2}{3}\operatorname{dev}\boldsymbol{\varepsilon} : \operatorname{dev}\boldsymbol{\varepsilon}}.$$

The same reconstruction is applied to plastic-strain-like quantities, which is why arrays such as `qp_plastic_strain_xx` and `nodal_plastic_strain_equivalent_strain` are available without any ParaView-side calculator.

18.4 Why the Exporter Owns These Scalars

There are two architectural reasons to compute the scalar filters inside `fall_n`:

1. the library owns the tensor convention and therefore should own the conversion rules;
2. explicit scalar arrays are stable extension points for downstream scripts, regression tests, dashboards, and future post-processing modules.

This is compatible with the HPC direction of the library. The additional work is restricted to post-processing, while the FE hot path remains unchanged.

18.5 Recommended ParaView Usage

For smooth contours on the continuum mesh:

1. load `*_mesh.vtu`;
2. if desired, apply `Warp By Vector` with `displacement`;
3. colour by `nodal_stress_von_mises`, `nodal_strain_xx`, or any other explicit nodal scalar.

For material-point inspection:

1. load `*_gauss.vtu`;
2. apply `Warp By Vector` directly using `displacement`;
3. colour by `qp_stress_von_mises`, `qp_stress_xx`, `qp_strain_equivalent_strain`, or similar explicit scalars;
4. use `Points` or `Point Gaussian` representation as appropriate.

The raw `_voigt` arrays remain in the files for traceability and advanced tooling, but they are no longer the primary user-facing representation.

Chapter 19

VTK Export Cleanup

This chapter documents the cleanup pass that reduced the VTK layer to the smallest operational contract that still preserves extension points.

19.1 Retained Responsibilities

After the cleanup, the active VTK surface in `fall_n` is:

- `VTKCellTraits.hh`: mapping from `fall_n` topology to VTK cell ids and local-node permutations;
- `VTKTensorFieldDerivatives.hh`: deterministic tensor-to-scalar post-processing utilities;
- `VTKModelExporter.hh`: split export of the continuum mesh and the Gauss cloud;
- `PVDWriter.hh`: time-series collection writer.

This is enough for the current library needs:

- clean nodal contour plots on the mesh;
- faithful material-point inspection on a warpable Gauss cloud;
- explicit scalar invariants for ParaView;
- time-series support through `.pvd`.

19.2 Removed Complexity

The cleanup explicitly removed three categories of dead or unstable implementation:

1. embedded native quadrature export as part of the main exporter API;
2. the mixed single-file visualization mesh that combined continuum cells and Gauss glyphs in one `.vtu`;
3. broad VTK rendering and GUI dependencies from the common include path.

These paths were not removed because they were impossible. They were removed because they increased API surface, state management, and cognitive load without yielding a robust everyday workflow in ParaView.

19.3 Why the Split Export Is the Right Current Boundary

The split contract is not merely a fallback; it is the correct current boundary between FE post-processing and VTK:

- the continuum mesh remains semantically clean;
- the Gauss cloud carries only material-point quantities;
- `Warp By Vector` works directly on both datasets;
- ParaView is not asked to reconstruct semantics from ambiguous metadata;
- the exporter state is easy to test and reason about.

This matters architecturally. A post-processing layer should not be clever just because VTK allows it; it should be explicit enough that future extensions do not inherit accidental complexity.

19.4 Compile-Time and Dependency Impact

The cleanup also reduced compilation and linkage overhead:

- `header_files.hh` no longer pulls the broad `VTKheaders.hh` compatibility umbrella;
- the compatibility umbrella itself was reduced to minimal data-model and IO includes for legacy code;
- the CMake VTK dependency set now targets only the modules needed by the active exporter and tests.

This follows the library's general HPC-oriented guideline: keep heavyweight and GUI-oriented dependencies out of the transitive include path unless they are strictly required.

19.5 Retained Extension Points

The cleanup did *not* freeze the VTK layer. The intended extension points remain:

- adding new explicit scalar filters from tensor data;
- adding new Gauss-cloud fields as constitutive models evolve;
- extending `VTKCellTraits` as new geometries are introduced;
- adding alternate writers as isolated adapters rather than as branches inside the main exporter.

That is the key design rule going forward: extend through small orthogonal adapters, not by re-expanding `VTKModelExporter` into a multipurpose state machine.

Chapter 20

Structural Scale Reconstruction and Multi-Block VTK Export

20.1 Motivation

The continuum exporter described in earlier chapters is not sufficient for structural finite elements. Beams and shells do not store a full three-dimensional stress or strain field at every spatial point. Instead, their formulation *degenerates* the continuum kinematics into a smaller set of generalized measures:

- beam sections carry axial strain, curvature, shear strains, and torsion rate;
- shell sections carry membrane strains, curvatures, and transverse shears.

For the present work, reconstructing the lost three-dimensional field is not a mere visualisation problem. The same machinery will later be used for *scale reconstruction*: transferring a reduced structural solution into an initial condition for a continuum discretisation. For that reason, the reconstruction logic must live in its own compile-time module rather than be buried inside a VTK writer.

20.2 Architectural Split

The implementation introduced in this phase is organised in three layers:

1. **Constitutive snapshot layer**. The type-erased `Material<Policy>` now exports a lightweight `SectionConstitutiveSnapshot`. This is the structural analogue of the previously introduced `InternalFieldSnapshot`. It carries only the constitutive data needed to reconstruct a section: beam stiffness parameters $(E, G, A, I_y, I_z, J, k_y, k_z)$, shell thickness parameters (E, ν, G, t, κ), and, when applicable, the current fiber field.
2. **Reduction / reconstruction layer**. The new `StructuralReductionPolicy<ElementT>` specialisations in `src/reconstruction/StructuralFieldReconstruction.hh` encode the formulation-specific mapping from reduced kinematics to reconstructed fields. These policies are specialised for:
   - `BeamElement<TimoshenkoBeam3D,3>`,
   - `TimoshenkoBeamN<N>`,
   - `ShellElement<MindlinReissnerShell3D>`.
3. **Carrier / export layer**. The new `StructuralVTMExporter` builds a `.vtm` multi-block file from the reconstruction layer. It does not implement beam or shell theory; it only requests samples from the reduction policy and maps them onto VTK carriers.

This split is deliberate. The exporter is allowed to disappear or to be replaced by another post-processing backend; the reconstruction module should remain valid because it expresses the structural theory itself.

20.3 Spatial Roles and Ontology

The reconstruction work reinforced the ontology introduced during the domain refactor:

- `Point` remains pure geometry.
- `Vertex` remains a geometric mesh entity.
- `Node` remains a carrier of degrees of freedom.
- `IntegrationPoint<dim>` is a spatial sampling site in the *embedding* dimension, not in the topological dimension.
- `MaterialPoint` is a continuum constitutive role layered on an `IntegrationPoint`.
- `MaterialSection` is the structural analogue of `MaterialPoint`: a constitutive role layered on an integration site, but carrying generalized beam or shell measures.
- `NodeSection` is a nodal geometric station, not a constitutive point.

The crucial correction in this phase is that `MaterialSection` now binds to `IntegrationPoint<MaterialPol` i.e. to a point in the embedding space. The previous 1D-only design was semantically too narrow even for beams, because the constitutive site of a beam is spatially embedded in $\mathbb{R}^3$.

20.4 Constitutive Snapshots

The new `SectionConstitutiveSnapshot` is returned by a single extra virtual method on the type-erased material wrapper. This follows the same reasoning as the internal-field export: the runtime indirection is paid only when post-processing asks for it, whereas the reconstruction kernels still operate with fully static element and field types.

20.4.1 Beam Snapshot

For elastic Timoshenko sections the snapshot contains:

$$\{E,\ G,\ A,\ I_y,\ I_z,\ J,\ k_y,\ k_z\}.$$

This is sufficient to reconstruct the standard sectional field:

$$\varepsilon_{xx}(y,z) = \varepsilon_0 - z\,\kappa_y + y\,\kappa_z,$$

$$\sigma_{xx}(y,z) = E\,\varepsilon_{xx}(y,z),$$

$$\tau_{xy} = G\,\gamma_y, \qquad \tau_{xz} = G\,\gamma_z.$$

For higher-fidelity torsion reconstruction one would need a section warping model. The present implementation does *not* invent one. Torsion remains available as a generalized measure, and can later be lifted by a specialised profile/warping policy.

20.4.2 Shell Snapshot

For Mindlin–Reissner shells the snapshot contains:

$$\{E,\ \nu,\ G,\ t,\ \kappa\}.$$

Given the mid-surface generalized strains

$$\{\varepsilon_{11}, \varepsilon_{22}, \gamma_{12}, \kappa_{11}, \kappa_{22}, \kappa_{12}, \gamma_{13}, \gamma_{23}\},$$

the through-thickness reconstruction is:

$$\varepsilon_{11}(z) = \varepsilon_{11}^0 + z\,\kappa_{11}, \qquad \varepsilon_{22}(z) = \varepsilon_{22}^0 + z\,\kappa_{22},$$

$$\gamma_{12}(z) = \gamma_{12}^0 + z\,\kappa_{12}, \qquad \gamma_{13}(z) = \gamma_{13}, \qquad \gamma_{23}(z) = \gamma_{23}.$$

For the present linear elastic shell model, the in-plane stresses are obtained with the plane-stress relation:

$$\sigma_{11} = \frac{E}{1-\nu^2}\left(\varepsilon_{11} + \nu\varepsilon_{22}\right), \qquad \sigma_{22} = \frac{E}{1-\nu^2}\left(\nu\varepsilon_{11} + \varepsilon_{22}\right),$$

$$\tau_{12} = G\,\gamma_{12}, \qquad \tau_{13} = G\,\gamma_{13}, \qquad \tau_{23} = G\,\gamma_{23}.$$

20.4.3 Fiber Snapshot

The previous architecture allowed nonlinear fiber sections in the solver, but the layout and the current fiber state were hidden behind type erasure. This phase adds a structural export path that exposes the *current* fiber field through the snapshot:

$$\{y_i,\ z_i,\ A_i,\ \varepsilon_i,\ \sigma_i\}_{i=1}^{n_f}.$$

This is obtained from the current generalized strain stored at the section and the constitutive response of each fiber material:

$$\varepsilon_i = \varepsilon_0 - z_i\kappa_y + y_i\kappa_z, \qquad \sigma_i = \sigma_i(\varepsilon_i).$$

No ad-hoc extrapolation is introduced: the fiber block reflects the actual constitutive state of the section.

20.5 Reduction Policies

20.5.1 Why Policies and Not VTK-Specific Code

Each structural formulation degenerates the continuum in a different way. A Timoshenko beam, an Euler–Bernoulli beam, an MITC shell, and a future geometrically exact beam do not lose the same kinematic information, and therefore they do not admit the same reconstruction. A generic "visual beam" abstraction would hide this distinction and eventually become architecturally wrong.

The chosen design is therefore:

```
StructuralReductionPolicy<ElementT>
```

with one specialisation per formulation. This respects the origin of the abstraction: the reconstruction belongs to the formulation, not to the renderer.

20.5.2 3D Timoshenko Beam

For `BeamElement<TimoshenkoBeam3D,3>` and `TimoshenkoBeamN<N>`, the reduction policy reconstructs:

- the axis displacement,
- the section rotation vector,
- the generalized section strain,
- the generalized section resultants,
- the reconstructed section field at any local section coordinate (y, z).

The displacement of a reconstructed section point is computed with the standard small-rotation lifting:

$$\mathbf{u}(y, z) = \mathbf{u}_c + \boldsymbol{\theta} \times (0, y, z).$$

This is the same kinematic relation that will later be needed for continuum initialisation from a beam model.

20.5.3 MITC4 Mindlin Shell

For `ShellElement<MindlinReissnerShell3D>` the reduction policy reconstructs:

- the mid-surface displacement,
- the local rotation vector,
- the generalized shell strain at an arbitrary parametric point,
- the generalized shell resultants at a material site,
- the through-thickness field at an arbitrary signed thickness position.

The displaced position of a point offset by z from the mid-surface is:

$$\mathbf{u}(z) = \mathbf{u}_m + \boldsymbol{\theta} \times (0, 0, z).$$

Again, this is not a visual trick; it is the actual lifting implied by the Mindlin kinematics used by the element.

20.6 Compile-Time and HPC Considerations

The new module intentionally favours compile-time structure over generic runtime indirection:

- the reconstruction layer is specialised by concrete element type;
- element-local vectors remain fixed-size Eigen objects;
- no new virtual dispatch appears inside the hot reconstruction formulas;
- the only extra virtual call is the constitutive section snapshot, used outside the solver kernel;
- the element DoF index caches were made `mutable`, so the exporter and reconstruction layer can extract element-local states in `const` traversals without breaking value semantics or reintroducing non-const APIs.

This keeps the intended performance hierarchy intact:

1. solver kernels remain governed by the concrete element type and Eigen stack objects;
2. post-processing may pay a small dynamic cost at the boundary to the type-erased material wrapper;
3. VTK-specific costs are isolated in the exporter only.

20.7 Section Profiles

To separate structural theory from rendering carriers, a second layer of abstraction is introduced: `SectionProfile`.

20.7.1 Beam Profiles

For beams, the exporter currently provides:

- `RectangularSectionProfile<SamplesPerEdge>`,
- `CircularSectionProfile<Segments>`.

These profiles do not define a constitutive law. They only provide the local boundary points used to build the visualization carriers. The profile points are generated from `consteval` reference rings and scaled at runtime by the actual section dimensions. This keeps the topology static and the per-element work minimal. The VTK exporter constrains its beam and shell carrier types with dedicated compile-time concepts: `BeamSectionProfileLike` and `ShellThicknessProfileLike`. This keeps the carrier contract explicit and prevents the exporter from turning into an untyped runtime adapter.

20.7.2 Shell Thickness Profile

For shells, the relevant geometric carrier is the thickness direction. The new `ShellThicknessProfile<Samples>` provides compile-time sample locations on the interval $[-\frac{1}{2}, \frac{1}{2}]$. The exporter uses this both for the section block and for any future scale transfer through the thickness.

20.8 The Multi-Block `.vtm` Contract

The exporter writes a ParaView/VTK multiblock file with the following semantic blocks:

1. `axis`: reduced carrier of the structural model. For beams this is the centerline polyline; for shells it is the mid-surface wireframe.
2. `surface`: a display carrier built from the section profile (beams) or the top/bottom shell surfaces.
3. `sections`: section stations. For beams this contains section rings; for shells this contains through-thickness section lines.
4. `material_sites`: actual constitutive sites.
5. `fibers`: actual fibers when the section model provides them.

Every geometric carrier that is meant to deform in ParaView carries a `displacement` vector in `PointData`. Thus the standard `Warp By Vector` filter works directly, without any native VTK quadrature metadata.

20.8.1 Executable Examples

The main executable now writes two structural demonstration outputs alongside the existing continuum comparison:

- `timoshenko_ref_structural.vtm`: the quadratic `TimoshenkoBeamN<3>` reference beam used in the cantilever comparison. The file exposes the beam axis, swept surface, section rings, and constitutive sites through the same reduced state that is used by the solver.
- `shell_cantilever_structural.vtm`: a small MITC4 cantilever shell patch clamped on one edge and loaded by a distributed nodal tip force. This serves as the first end-to-end example of shell reconstruction and ParaView deformation through `Warp By Vector`.

These examples are intentionally modest. Their role is not to replace a full benchmark suite, but to keep the structural reconstruction path wired into the production executable so regressions become visible immediately.

20.8.2 A Note on Empty Trailing Blocks

The VTK XML multiblock writer may elide a trailing empty block when the last dataset has no geometry. This is a writer/reader behaviour, not a loss of semantic information in the implementation. The exporter therefore keeps the logical block layout fixed, but consumers should not rely on a trailing empty block being materialised on disk when, for example, no fiber section exists in the current model.

20.9 Testing Strategy

Two new tests were introduced:

- `test_structural_reconstruction.cpp` verifies the formulation-level reconstruction:
  - a 3D Timoshenko beam reconstruction is checked against the expected axial-plus-bending field;
  - a flat MITC4 shell reconstruction is checked for linear through-thickness variation.
- `test_structural_vtm_export.cpp` verifies the VTK contract: the axis, surface, sections, and material-sites blocks exist and carry the expected arrays for both a beam and a shell model, while the fiber block is emitted only when it has actual content.

The multiblock writer was also given an auxiliary method, `write_with_local_states()`, so that the export contract can be tested without requiring a PETSc/MPI runtime. This turns out to be useful beyond testing: it decouples the structural carriers from a specific solver backend and makes the exporter equally applicable to offline reconstructed states. In the same spirit, the beam surface and section carriers now use the first and last section snapshots at the element ends instead of blindly reusing the first material site on both sides. This is a small but important correction for future non-uniform beam sections.

20.10 Limitations and Future Work

This phase intentionally does not solve every structural post-processing problem. The most relevant open items are:

- Euler–Bernoulli and geometrically exact beam policies still need their own reduction specialisations.

- Torsional warping reconstruction is not yet implemented.
- The beam section block currently uses end and material stations; a future step should expose exact interpolation nodes for arbitrary higher-order line elements.
- For nonlinear shells with layered constitutive laws, a richer shell section snapshot will be required.
- Fiber blocks currently export the actual fiber field but do not yet generate a finite-area carrier; they are emitted as point sites.

These are acceptable limitations because the key architectural property is now in place: *reconstruction belongs to the structural formulation and is available independently of the visualization backend.*

Chapter 21

Mixed Structural Table Example

21.1 Purpose

This chapter documents a compact structural example that exercises the main architectural decisions developed in the preceding chapters:

- a heterogeneous structural model stored through `StructuralElement`,
- formulation-specific reconstruction through `StructuralReductionPolicy<ElementT>`,
- multi-block VTK export through `StructuralVTMExporter`,
- coexistence of beam and shell elements on a shared geometric support.

The example is intentionally simple enough to inspect by hand, but rich enough to validate the polymorphic structural pipeline end to end.

21.2 Physical Model

The structure resembles a table:

- four corner columns,
- four perimeter beams on the top frame,
- one shell slab spanning the frame.

21.2.1 Geometry

The adopted dimensions are:

$$L = 5.0, \qquad H = 3.0, \qquad t_{\text{slab}} = 0.18.$$

The four column bases are placed at:

$$(0,0,0),\ (L,0,0),\ (L,L,0),\ (0,L,0),$$

and the top frame lies in the plane:

$$z = H.$$

The slab is discretised as a structured 4×4 MITC4 mesh over the square domain $[0,L]\times[0,L]$.

21.2.2 Sections and Materials

The example uses two distinct beam formulations and one shell formulation:

- **Columns**: `BeamElement<TimoshenkoBeam3D,3>` with rectangular section 0.40×0.40, Young's modulus $E_c = 21000$, Poisson ratio $\nu = 0.20$.
- **Perimeter beams**: `TimoshenkoBeamN<2>` with rectangular section 0.60×0.40, Young's modulus $E_b = 24000$, Poisson ratio $\nu = 0.20$.
- **Slab**: `ShellElement<MindlinReissnerShell3D>` with thickness $t = 0.18$, Young's modulus $E_s = 26000$, Poisson ratio $\nu = 0.20$.

The shear modulus is reconstructed from isotropic elasticity:

$$G = \frac{E}{2(1+\nu)}.$$

For rectangular beams the section properties are computed directly from the section dimensions:

$$A = bh, \qquad I_y = \frac{bh^3}{12}, \qquad I_z = \frac{hb^3}{12},$$

and the Saint-Venant torsional constant is approximated by

$$J \approx \frac{b_{\min}^3 h_{\max}}{3}\left(1 - 0.63\frac{b_{\min}}{h_{\max}}\right).$$

21.3 Loads and Boundary Conditions

All nodes with $z = 0$ are fully clamped through the structural model interface.

Two load cases are superposed:

1. a uniform slab pressure
$$p_z = -0.12,$$
converted to consistent nodal forces by direct integration of the shell interpolation,
$$\mathbf{f}_I = \int_{\Omega_e} N_I \mathbf{t}\, dA, \qquad \mathbf{t} = (0, 0, p_z)^T;$$
2. a lateral point force applied at the corner node (L, L, H),
$$F_x = 0.20.$$

This combination is deliberately chosen to excite:

- vertical flexure of the slab,
- frame action in the perimeter beams,
- bending plus sway of the full table.

21.4 Architectural Realisation

21.4.1 Why the Domain Contains Only the Slab

The current `Domain` layer is intentionally aligned with a pure `DMPlex` surface/volume topology. The slab therefore lives inside the PETSc mesh, whereas the columns and beams are introduced as external line geometries bound to the same `Node`/`Vertex` storage. This keeps the domain ontologically clean:

- the 2D topological mesh remains a shell/slab mesh,
- the line members remain structural geometries rather than fake 2D entities,
- the mixed structural model is assembled one layer above the domain.

21.4.2 Polymorphic Structural Container

The final element container is

```
std::vector<StructuralElement>,
```

owned by

```
Model<TimoshenkoBeam3D, SmallStrain, 6, SingleElementPolicy<StructuralElement>>.
```

This means that the analysis sees one structural family with a common finite-element interface, while post-processing can still recover the concrete type through the structural type-erasure layer:

- `BeamElement<TimoshenkoBeam3D,3>` for columns,
- `TimoshenkoBeamN<2>` for edge beams,
- `ShellElement<MindlinReissnerShell3D>` for slab cells.

The example therefore validates the intended design point: runtime heterogeneity at the model boundary, formulation-specific compile-time reconstruction inside each policy.

21.5 Quadrature Contract for `TimoshenkoBeamN`

The example uncovered an architectural inconsistency in `TimoshenkoBeamN<N>`. The element uses a reduced constitutive integration with

$$n_{\mathrm{gp}} = N - 1,$$

but its public topology query originally forwarded `geometry_->num_integration_points()`, which depends on the underlying geometry integrator. For `TimoshenkoBeamN<2>` this created an inconsistent state:

- the element stored one constitutive section,
- the exporter believed that the element had two Gauss points when the geometry used `GaussLegendreCellIntegrator<2>`.

The fix adopted here is structural, not cosmetic:

1. `TimoshenkoBeamN<N>::num_integration_points()` now returns the reduced value $N-1$.

2. The constructor now enforces the quadrature contract: the attached geometry must also expose exactly $N - 1$ integration points.
3. The table example therefore assigns `GaussLegendreCellIntegrator<1>` to the perimeter beams and `GaussLegendreCellIntegrator<2>` to the columns.

This is important beyond visualisation. The reconstruction layer and any future scale-transfer operator must reason about the actual constitutive sites of the formulation, not about an unrelated geometric quadrature.

21.6 VTK Output

The structural exporter writes a `.vtm` index together with one `.vtp` sidecar per semantic block:

- `table_frame_structural.vtm`,
- `table_frame_structural_axis.vtp`,
- `table_frame_structural_surface.vtp`,
- `table_frame_structural_sections.vtp`,
- `table_frame_structural_material_sites.vtp`,
- `table_frame_structural_fibers.vtp`.

These blocks have a fixed semantic meaning:

`axis` beam centre-lines and shell boundary carriers;

`surface` reconstructed beam skins and shell top/bottom faces;

`sections` section stations and shell through-thickness lines;

`material_sites` constitutive sampling sites;

`fibers` fiber carriers when a fiber section is present.

The split into `.vtp` sidecars is intentional. It avoids the fragile writer path observed with the monolithic multi-block writer while preserving a semantically clean `.vtm` interface for ParaView.

21.7 Observed Structural Response

For the current parameter set, the example run stored in the repository reported:

$$\max |u| = 1.3651 \times 10^{-2}, \qquad \max |u_x| = 5.30 \times 10^{-4}, \qquad \max |u_z| = 1.3651 \times 10^{-2}.$$

These values are not presented as a benchmark target. Their role here is to confirm that:

- the mixed structural solve completes,
- the reconstructed carriers can be exported without crashing,
- the example exercises both vertical slab deformation and lateral frame sway.

21.8 Code Path

The complete example is implemented in `main.cpp` as `run_structural_table_example()`. The relevant pieces are:

- geometric construction of slab, columns, and beams;
- consistent shell pressure assembly through `apply_uniform_shell_surface_load()`;
- polymorphic structural model assembly through `StructuralElement`;
- multi-block structural export through `export_structural_vtm()`.

This example now serves as the reference mixed structural demonstration for the current architecture.

Chapter 22

Robustifying `DMPlex` for Naturally Mixed Element Families

22.1 Motivation

Up to this point, the `Domain`–`Model` pipeline relied on a very restrictive interpretation of `DMPlex`: an uninterpolated cell–vertex graph where every analysis element was treated as a "cell" and the code assumed that querying height 1 produced the vertices. That assumption is brittle even for standard meshes and becomes conceptually wrong as soon as one wants to mix, in the same discrete domain, elements of different topological dimension such as:

- beams (1D topology embedded in $\mathbb{R}^3$),
- shells (2D topology embedded in $\mathbb{R}^3$),
- continua (3D topology embedded in $\mathbb{R}^3$).

The immediate objective of this refactor is therefore modest but essential: *keep the current non-interpolated DAG for performance and simplicity, while making the `DMPlex` object semantically correct enough to host mixed element families naturally.*

22.2 Design Decision

The adopted strategy is intentionally incremental:

1. Keep the DAG non-interpolated. Cells still connect directly to vertices; explicit edges and faces are not materialised yet.
2. Encode the missing topological semantics using `DMLabel`s.
3. Drive the algebraic layout from the only invariant that really matters for the current solver: analysis unknowns live on depth-0 vertices.

This preserves the low-cost setup path and avoids polluting the hot assembly loops with new runtime indirections. The extra work happens only once during mesh/DMPlex setup.

22.3 Implemented Semantics

Three labels are now attached to the `DMPlex` points generated by `Domain::assemble_sieve()`:

`fall_n.point_role` distinguishes between vertex points and cell points. The current values are:

- 0 for vertices,
- 1 for cells.

`fall_n.topological_dim` stores the intrinsic topological dimension of each point. Vertices receive value 0, while cells receive the topological dimension reported by `ElementGeometry::topological_d`

`fall_n.physical_group_id` stores an integer identifier for the physical group carried by a geometric element, when such group exists.

These labels are cheap, explicit, and stable. More importantly, they separate two different concerns that had previously been conflated:

- the *graph* structure of the mesh;
- the *topological meaning* of each graph point.

22.4 Why `Depth` and Not `Height`

The previous implementation used:

```
DMPlexGetHeightStratum(dm, 1, &vStart, &vEnd);
```

and interpreted that stratum as the vertices. This is only safe for a very specific cell–vertex graph and becomes false once the mesh is interpolated or its topology is enriched.

The robust statement is:

> analysis vertices are the depth-0 points of the `DMPlex`.

Accordingly, `Model::set_sieve_layout()` was rewritten to define the section over the full chart while conceptually placing DOFs only on depth-0 points. Cell points keep zero DOFs.

22.5 Dimension of the `DMPlex`

Another correction concerns the dimension assigned to the `DM`. The old code forced:

```
DMSetDimension(dm, dim);
```

where `dim` is the embedding space dimension of the model, not the intrinsic dimension of the discrete topology.

This is now replaced by:

$$\dim(\texttt{DM}) = \max_{e \in \mathcal{T}_h} \operatorname{topodim}(e), \tag{22.1}$$

that is, the maximum topological dimension among the stored elements. For a mixed beam–shell model embedded in $\mathbb{R}^3$, the resulting `DMPlex` has dimension 2; for a mixed beam–shell–solid model, it has dimension 3.

22.6 Compile-Time and HPC Considerations

This refactor was designed to preserve the original performance intent:

- Geometry, interpolation, and quadrature remain statically typed.
- No new virtual dispatch was introduced inside numerical integration, constitutive update, or element assembly loops.

- The new metadata is written once during `assemble_sieve()` and then consumed through PETSc's own label machinery.
- The DAG itself is still cell–vertex, which keeps setup lighter than a fully interpolated mesh and reduces memory pressure.

In other words, the refactor improves semantic correctness of the mesh layer without paying for it in the hot path.

22.7 Validation

A dedicated regression test was added:

`tests/test_dmplex_mixed_topology.cpp`

It builds a small domain containing:

- one 1D beam geometry,
- one 2D shell geometry,
- shared depth-0 vertices.

The test verifies:

1. the `DM` dimension is the maximum topological dimension;
2. height-0 contains the two cells and depth-0 the four vertices;
3. the three labels above are present and correctly populated;
4. a polymorphic structural `Model` assigns DOFs only to vertices, leaving cell points with zero DOFs.

22.8 Current Scope and Next Step

This chapter documents a necessary intermediate stage, not the final one. Mixed families now coexist naturally in the same `DMPlex` at the semantic level, but the mesh is still not fully interpolated. Therefore:

- the solver can reason correctly about vertices versus cells;
- element families of different intrinsic dimension can share the same `Domain` and `DMPlex`;
- future work may still introduce explicit edges/faces when the library needs richer topological traversal or native mixed-dimensional coupling operators.

This staging is intentional. It respects the architectural principle adopted throughout `fall_n`: only introduce abstractions that correspond to a real numerical need, and keep the compile-time structure of the kernels as static as possible.

Chapter 23

Regular 5-Story Building Example

23.1 Purpose

This chapter documents the *elastic baseline* mixed-building example that preceded the materially nonlinear reinforced-concrete continuation developed in Chapter 24. It remains useful as the simplest reference configuration for understanding the shared `Domain`, mixed 1D/2D topology, and polymorphic structural wrapping without the additional complexity of path-dependent constitutive response.

The example is a regular reinforced-concrete-like building with:

- five stories,
- four grid axes in the x-direction,
- three grid axes in the y-direction,
- frame members modelled with 3D Timoshenko beams,
- slabs modelled with MITC4 / Mindlin–Reissner shells.

The objective is not a code-check design, but a pedagogical and architectural integration example:

- shared geometry and topology in one `Domain`,
- mixed 1D/2D structural families,
- one polymorphic structural solver container,
- one structural `.vtm` export for ParaView.

23.2 Unit System

The example is written consistently in:

$$\text{force} = \text{kN}, \qquad \text{length} = \text{m}, \qquad \text{stress} = \text{kN/m}^2.$$

Therefore:

- Young's moduli are entered in kN/m^2,
- slab loads are entered in kN/m^2,
- nodal lateral forces are entered in kN,
- computed displacements are reported in m.

23.3 Geometry

23.3.1 Plan and height

The plan grid is:

$$x = \{0,\ 6,\ 12,\ 18\}\ \text{m}, \qquad y = \{0,\ 5,\ 10\}\ \text{m}.$$

This gives:

- 3 bays of 6 m in the x-direction,
- 2 bays of 5 m in the y-direction.

The storey height is:

$$h = 3.20\ \text{m},$$

so the floor elevations are:

$$z_k = 3.20\,k, \qquad k = 0, \ldots, 5.$$

The total structural height is:

$$H = 16.0\ \text{m}.$$

23.3.2 Discretisation

All members share the same building nodes:

- $4 \times 3 = 12$ plan nodes per level,
- 6 levels including the base,
- total node count:

$$n_{\text{nodes}} = 12 \times 6 = 72.$$

The element counts are:

- columns:

$$n_c = 5 \times 4 \times 3 = 60,$$

- beams:

$$n_b = 5\,[(4-1) \times 3 + (3-1) \times 4] = 85,$$

- slab panels:

$$n_s = 5 \times (4-1) \times (3-1) = 30.$$

Hence the total number of structural geometric elements is:

$$n_{\text{elem}} = 60 + 85 + 30 = 175.$$

23.4 Sections and Materials

23.4.1 Columns

Columns are modelled as 3D Timoshenko beams with rectangular section:

$$b_c = 0.45\ \text{m}, \qquad h_c = 0.45\ \text{m}.$$

The frame material is idealised as linear elastic with:

$$E_f = 28.0 \times 10^6\ \text{kN/m}^2, \qquad \nu = 0.20.$$

The shear modulus is reconstructed as:

$$G_f = \frac{E_f}{2(1+\nu)}.$$

23.4.2 Beams

Beams are also modelled as 3D Timoshenko beams, with section:

$$b_b = 0.30 \text{ m}, \qquad h_b = 0.60 \text{ m}.$$

The same frame elastic modulus is used:

$$E_b = E_f = 28.0 \times 10^6 \text{ kN/m}^2.$$

For both columns and beams the section properties are computed directly from the rectangular dimensions:

$$A = bh, \qquad I_y = \frac{bh^3}{12}, \qquad I_z = \frac{hb^3}{12}.$$

The torsional constant is approximated with the standard rectangular Saint-Venant estimate:

$$J \approx \frac{b_{\min}^3 h_{\max}}{3}\left(1 - 0.63\frac{b_{\min}}{h_{\max}}\right).$$

The Timoshenko shear factors are taken as:

$$\kappa_y = \kappa_z = \frac{5}{6}.$$

23.4.3 Slabs

Each floor slab panel is modelled by a MITC4 / Mindlin–Reissner shell with thickness:

$$t = 0.15 \text{ m}.$$

The slab elastic modulus is slightly reduced with respect to the frame:

$$E_s = 25.0 \times 10^6 \text{ kN/m}^2, \qquad \nu_s = 0.20.$$

23.5 Loads and Boundary Conditions

23.5.1 Boundary conditions

All base nodes, that is all nodes on the plane $z = 0$, are fully fixed. This is implemented at the model level through:

```
model.fix_z(0.0);
```

which, in the current API, constrains all DOFs of every node lying on that plane.

23.5.2 Gravity loading

Each slab receives a uniform downward pressure:

$$q_g = -7.50 \text{ kN/m}^2.$$

This pressure represents a simplified vertical service load (self-weight + superimposed permanent load + a modest live-load component).

The load is assembled consistently from the shell interpolation:

$$\mathbf{f}_I = \int_{\Omega_e} N_I \, \mathbf{t} \, dA, \qquad \mathbf{t} = (0, 0, q_g)^T.$$

23.5.3 Horizontal loading

To make frame bending visually more evident, one corner node of every floor receives a horizontal force in the global x-direction. The loaded node at storey k is:

$$(x, y, z) = (18,\ 10,\ z_k).$$

The storey force pattern is triangular:

$$F_x^{(k)} = 400\,k \quad \text{kN}, \qquad k = 1, \ldots, 5.$$

Thus the applied forces are:

$$400,\ 800,\ 1200,\ 1600,\ 2000 \text{ kN}.$$

This is intentionally not a perfectly symmetric wind model. The asymmetry is useful here because it activates:

- global building sway,
- perimeter beam bending,
- slab diaphragm action,
- a modest torsional component.

23.6 Architectural Realisation in Code

23.6.1 One shared `Domain`

The first important architectural point is that the example inserts *all* structural geometry into the same `Domain<3>`:

- columns are stored as 1D line geometries,
- beams are stored as 1D line geometries,
- slabs are stored as 2D quadrilateral geometries.

This is exactly the kind of mixed topology that motivated the recent `DMPlex` hardening described in Chapter 22. The resulting `DMPlex` remains non-interpolated, but it is now semantically correct for mixed 1D/2D structural families.

For this model the reported `DMPlex` dimension is:

$$\dim(\texttt{DM}) = 2,$$

because the maximum topological dimension in the domain is the slab topology.

23.6.2 Polymorphic structural container

The solver model is assembled as:

```
Model<TimoshenkoBeam3D, SmallStrain, 6, SingleElementPolicy<StructuralElement>>.
```

This means:

- the element container is

```
std::vector<StructuralElement>,
```

- each concrete geometry is wrapped into the appropriate concrete element type:
  - `BeamElement<TimoshenkoBeam3D,3>` for columns,
  - `BeamElement<TimoshenkoBeam3D,3>` for beams,
  - `ShellElement<MindlinReissnerShell3D>` for slabs;
- the global assembly sees a homogeneous interface, while the structural VTK exporter can still dispatch back to the concrete formulation through `StructuralReductionPolicy<ElementT>`.

23.6.3 Why this example is a good architectural integrator

This one example exercises, simultaneously:

- geometric ownership in `Domain`,
- mixed-topology `DMPlex` assembly,
- analysis-node DOF assignment on shared vertices,
- heterogeneous structural element wrapping,
- shell consistent-load assembly,
- formulation-aware structural reconstruction,
- multi-block VTK output.

In that sense it is a better "main example" than the previous collection of independent benchmarks: it shows how the pieces work together.

23.7 Execution Results

The executed example stored in the repository reported:

$$\max |u| = 9.248 \times 10^{-3} \text{ m},$$

$$\max |u_x| = 8.292 \times 10^{-3} \text{ m}, \qquad \max |u_z| = 2.523 \times 10^{-3} \text{ m}.$$

At the loaded roof corner node, the displacement vector was:

$$u_{\text{roof}} = \begin{bmatrix} 8.292 \times 10^{-3} \\ -3.598 \times 10^{-3} \\ -1.955 \times 10^{-3} \end{bmatrix} \text{m}.$$

The roof drift ratio in the x-direction is therefore:

$$\frac{u_x^{\text{roof}}}{H} = \frac{8.292 \times 10^{-3}}{16.0} = 5.18 \times 10^{-4}.$$

These values are small enough to remain in the linear range, but large enough to make the deformed shape and beam flexure visible in ParaView when a moderate `Warp By Vector` scale factor is used.

23.8 VTK Output

The example writes the following VTK files:

- `regular_5story_building_structural.vtm`,
- `regular_5story_building_structural_axis.vtp`,
- `regular_5story_building_structural_surface.vtp`,
- `regular_5story_building_structural_sections.vtp`,
- `regular_5story_building_structural_material_sites.vtp`,
- `regular_5story_building_structural_fibers.vtp`.

The semantic meaning of the blocks remains the same as in the previous structural exporter chapters:

`axis` line carriers for beam centre-lines and shell edges;

`surface` reconstructed beam skins and shell faces;

`sections` section stations and through-thickness carriers;

`material_sites` constitutive sampling sites;

`fibers` fiber-section carriers (empty in this example).

In ParaView, the intended workflow is:

1. open the `.vtm` file,
2. display the `surface` block,
3. apply `Warp By Vector` using `displacement`,
4. colour by reconstructed resultants or stresses,
5. inspect `sections` and `material_sites` for the formulation-specific internal fields.

23.9 Why the Example Matters

From a software-architecture perspective, this example confirms that the current direction is viable:

- mixed structural families can share one geometric and topological domain,
- `StructuralElement` is sufficient as the polymorphic solver boundary,
- reconstruction remains formulation-specific and therefore reusable for later scale-transfer work,
- the new `main.cpp` now acts as a readable cookbook for building a realistic mixed frame–shell model.

That is exactly the kind of example needed before moving on to the next layer of abstraction, namely a dedicated `DMPlex` policy or builder strategy.

Chapter 24

Nonlinear Reinforced-Concrete 5-Story Building Example

24.1 Purpose and Scope

This chapter documents the current `main.cpp` entry point, which now hosts a materially nonlinear reinforced-concrete building example. The model is the direct continuation of the elastic mixed-building benchmark of Chapter 23, but the frame members are now represented by nonlinear fiber sections while the floor slabs remain elastic MITC4 shells.

The example is intended to validate three architectural goals simultaneously:

- one shared `Domain<3>` and one shared `DMPlex` for columns, beams, and slabs;
- one polymorphic structural element container, mixing beam and shell formulations in the same global solve;
- one constitutive upgrade path in which the frame material law is replaced by a nonlinear fiber discretisation without changing the geometric or topological assembly pipeline.

Equally important, the example is *not* yet a fully nonlinear RC building solver in the broadest sense. The current scope is:

- small-strain structural kinematics;
- nonlinear beam sections through fibers;
- elastic shell sections for slabs;
- static incremental equilibrium with PETSc SNES.

24.2 Unit System

The example switches deliberately to:

$$\text{force} = \text{MN}, \qquad \text{length} = \text{m}, \qquad \text{stress} = \text{MPa} = \text{MN/m}^2.$$

This choice is not cosmetic. The uniaxial constitutive laws currently used in the fiber sections, especially Kent–Park concrete, are calibrated and written numerically in MPa. Using MN–m–MPa preserves unit consistency while avoiding ad hoc rescalings inside the constitutive model. In this system:

- 30 MPa is entered numerically as 30,
- 200 kN is entered as 0.20 MN,
- 7.5 kN/m^2 is entered as 0.0075 MN/m^2.

24.3 Geometry and Topology

24.3.1 Plan and elevations

The plan grid is unchanged from the elastic reference:

$$x = \{0,\ 6,\ 12,\ 18\}\ \text{m}, \qquad y = \{0,\ 5,\ 10\}\ \text{m},$$

with storey height

$$h = 3.20\ \text{m}, \qquad z_k = 3.20\,k, \quad k = 0, \ldots, 5.$$

This yields:

- 72 shared building nodes,
- 60 columns,
- 85 beams,
- 30 shell panels,
- 175 geometric elements in total.

24.3.2 Mixed structural topology

All structural members are inserted into the same `Domain<3>`:

- columns and beams as 1D line geometries,
- slabs as 2D quadrilateral geometries.

The resulting `DMPlex` remains non-interpolated, but its highest topological dimension is now 2 because shell cells are present. The recent `DMPlex` hardening from Chapter 22 is what makes this mixed 1D/2D configuration natural rather than exceptional.

24.4 Constitutive Design

24.4.1 Columns

Columns are modelled as 3D Timoshenko beam elements with section:

$$b_c = h_c = 0.45\ \text{m}.$$

The nonlinear section is built from:

- unconfined cover concrete, modelled with Kent–Park;
- confined core concrete, also modelled with Kent–Park but with a confinement enhancement factor derived from an assumed volumetric tie ratio;
- eight longitudinal reinforcing bars of diameter $\phi = 25$ mm, modelled with Menegotto–Pinto steel.

The material parameters are:

$$f'_c = 35\ \text{MPa}, \qquad E_c = 1000\,f'_c = 35000\ \text{MPa}, \qquad \nu = 0.20,$$

$$E_s = 200000\ \text{MPa}, \qquad f_y = 420\ \text{MPa}, \qquad b_s = 0.01.$$

The cover thickness to fiber centroid is taken as:

$$c_c = 0.05\ \text{m}.$$

The column section is discretised into:

- 84 concrete fibers,
- 8 steel fibers,
- total: 92 fibers per column integration point.

24.4.2 Beams

Beams are also 3D Timoshenko elements, with section:

$$b_b = 0.30 \text{ m}, \qquad h_b = 0.60 \text{ m}.$$

The beam fiber section uses:

- unconfined Kent–Park concrete over the full section;
- six longitudinal reinforcing bars of diameter $\phi = 20$ mm, arranged as three top and three bottom bars;
- the same Menegotto–Pinto steel law as in the columns.

The beam concrete parameters are:

$$f'_c = 30 \text{ MPa}, \qquad E_c = 30000 \text{ MPa}.$$

The beam section discretisation contains:

- 72 concrete fibers,
- 6 steel fibers,
- total: 78 fibers per beam integration point.

24.4.3 Slabs

The slabs remain elastic MITC4 / Mindlin–Reissner shells with thickness:

$$t = 0.15 \text{ m}.$$

The elastic shell properties are:

$$E_s = 28000 \text{ MPa}, \qquad \nu_s = 0.20.$$

This is a deliberate modelling boundary. The current example is a nonlinear *frame* with an elastic slab diaphragm, not yet a fully fiberised RC shell–frame interaction problem.

24.5 Why Fibers Belong in the Constitutive Layer

The crucial architectural decision is that the fiber discretisation is not a visualisation gadget. It is the constitutive relation itself:

`FiberSection3D` $\rightarrow$ `Material<TimoshenkoBeam3D>` $\rightarrow$ `BeamElement`.

That means the same reduction policy that maps generalized beam strain $(\varepsilon_0, \kappa_y, \kappa_z, \gamma_y, \gamma_z, \theta')$ to section response is already the one that will later be reusable for:

- post-processing,
- section-force recovery,
- multiscale or scale-bridging initialisation,
- transfer of structural states to continuum models.

The visualisation layer only reads committed constitutive snapshots; it does not define the physics.

24.6 Section Kinematics and Fiber Stress Recovery

For each beam material point, the generalized strain vector is:

$$\mathbf{e} = \begin{bmatrix} \varepsilon_0 & \kappa_y & \kappa_z & \gamma_y & \gamma_z & \theta' \end{bmatrix}^T.$$

The axial strain at a fiber located at local section coordinates (y, z) is reconstructed as:

$$\varepsilon_f(y, z) = \varepsilon_0 - z\,\kappa_y + y\,\kappa_z.$$

The section resultants then follow from numerical integration over the fibers:

$$N = \sum_i \sigma_i A_i, \qquad M_y = \sum_i \sigma_i(-z_i)A_i, \qquad M_z = \sum_i \sigma_i y_i A_i.$$

The shear and torsional terms remain elastic:

$$V_y = \kappa_y GA\,\gamma_y, \qquad V_z = \kappa_z GA\,\gamma_z, \qquad T = GJ\,\theta'.$$

This is why the current example is materially nonlinear but still efficient: only the axial/flexural part of the section is fiber-integrated, while the shear/torsion part remains compact and closed form.

24.7 Global Solution Strategy

The mixed model is solved with `NonlinearAnalysis<..., StructuralPolicy>`, i.e. PETSc SNES on the same polymorphic structural container already used by the linear example. The load vector is applied incrementally:

$$\lambda_k = \frac{k}{12}, \qquad k = 1, \ldots, 12,$$

with automatic step bisection enabled up to depth 6, although the final run converged without exhausting that budget.

The PETSc options used in the executable are:

- `-snes_type newtonls`,
- `-snes_linesearch_type bt`,
- `-snes_rtol 1e-8`,
- `-snes_atol 1e-9`,
- `-snes_max_it 40`,
- `-ksp_type preonly`,
- `-pc_type lu`.

24.7.1 Analysis-layer hardening

In order for this example to compile and solve through the structural type-erased path, `NLAnalysis` was generalised. The solver now uses two assembly routes:

- a fast local-vector route for continuum elements exposing explicit element DOF extraction and local tangent routines;
- a generic `FiniteElement` route for structural type-erased elements, assembling through `compute_internal_forces()` and `inject_tangent_stiffness()`.

This keeps the continuum hot path intact while making the nonlinear solver architecturally consistent with the structural abstraction already present in the codebase.

24.8 Loads and Boundary Conditions

The support conditions are unchanged from the baseline model: all nodes on $z = 0$ are fully fixed.

The slabs carry a uniform gravity pressure:

$$q_g = -0.0075 \text{ MN/m}^2.$$

The lateral load pattern is triangular and applied at the corner $(18, 10, z_k)$:

$$F_x^{(k)} = 0.20\,k \quad \text{MN}, \qquad k = 1, \ldots, 5.$$

This choice keeps the model response moderate while making sway and beam flexure clearly visible.

24.9 Results of the Executed Example

The example was executed successfully in the current workspace. The final incremental solve converged at $\lambda = 1.0$ with 4 SNES iterations in the last step.

The reported response values are:

$$\max \|\mathbf{u}\| = 0.003767 \text{ m}, \qquad \max |u_x| = 0.003314 \text{ m}, \qquad \max |u_z| = 0.001244 \text{ m},$$

and at the roof corner:

$$u_x = 0.003314 \text{ m}, \qquad u_y = -0.001473 \text{ m}, \qquad u_z = -0.001019 \text{ m}.$$

The roof drift ratio is:

$$\frac{u_x^{\text{roof}}}{H} = 2.07 \times 10^{-4}.$$

This is intentionally a mild nonlinear response, not a collapse or pushover limit-state study. The objective here is robustness and architectural traceability, not maximum inelastic excursion.

24.10 VTK Output

The example writes:

`regular_5story_rc_nonlinear_building_structural.vtm`

plus the corresponding block sidecars:

- `_axis.vtp`
- `_surface.vtp`
- `_sections.vtp`
- `_material_sites.vtp`
- `_fibers.vtp`

For nonlinear RC interpretation, the most important block is:

- `fibers`: it contains the actual fiber-level `fiber_strain_xx` and `fiber_stress_xx` values reconstructed from the committed constitutive state.

The surface block remains useful for displacement visualisation and geometric context, but the truly nonlinear stress information lives at the fiber level.

24.11 Regression and Verification

Alongside the full building example, a dedicated regression test was added:

`tests/test_rc_fiber_frame_nonlinear.cpp`

It solves a small RC fiber cantilever with the same `BeamElement + FiberSection + NonlinearAnalysis` stack and checks:

- convergence of the incremental SNES solve,
- finite tip displacement,
- physically correct sign of the vertical response.

During that work a real lifecycle bug was found and fixed in the test harness: PETSc-owning objects must be destroyed before `PetscFinalize()`.

24.12 Current Limits and Next Steps

The example is already useful as a production-quality integration case, but some limits remain explicit:

- the slab is still elastic;
- the structural kinematics are still small-strain;
- beam surface stresses in the generic surface carrier are only a kinematic proxy when no closed-form beam snapshot exists, whereas the fiber block contains the actual nonlinear stress information;
- confined/unconfined concrete zoning is still schematic rather than design-code calibrated.

The next natural architectural step is not in visualisation, but in reconstruction: extend the same reduction-policy logic toward consistent scale-bridging and, eventually, transfer of committed structural states to a continuum discretisation.

Chapter 25

Material Module Architecture Analysis

25.1 Purpose

This chapter provides a focused architectural analysis of the current `materials` module. The goal is not merely to rename classes or to standardise terminology, but to identify the semantic boundaries that must be made explicit if `fall_n` is to evolve toward:

- reinforced concrete modelling at several scales;
- materially nonlinear and dynamic analysis;
- finite-kinematics structural and continuum formulations;
- continuum-scale cracking, damage, localisation, and fracture.

The analysis is guided by three constraints already visible across the code base:

- the local element kernels must remain inexpensive and friendly to compile-time optimisation;
- the library must preserve the current genericity across continuum, beam, and shell formulations;
- the constitutive layer must remain reusable beyond post-processing, because the same reconstruction policies will later be needed for scale transfer and multiscale initialisation.

25.2 Current Architectural Layers

25.2.1 Measure spaces

At the lowest level, the module already contains a useful abstraction:

- `Strain<N>` and `Stress<N>` for continuum Voigt spaces;
- `BeamGeneralizedStrain<N,Dim>` and `BeamSectionForces<N>`;
- `ShellGeneralizedStrain<N,Dim>` and `ShellResultants<N>`.

The concepts in `ConstitutiveRelation.hh` correctly recognise that a constitutive relation should fundamentally operate on a pair

$$(\text{kinematic measure},\ \text{tensional conjugate}),$$

independently of whether that pair belongs to a solid, a beam section, or a shell section. This is one of the strongest parts of the current design and should be preserved.

25.2.2 Relation classes

The code currently places under the same umbrella:

- continuum elastic relations such as `ContinuumIsotropicRelation`;
- reduced section relations such as `TimoshenkoBeamSection3D` and `MindlinShellSection`;
- inelastic local models such as `PlasticityRelation`, `KentParkConcrete`, and `MenegottoPintoSteel`;
- reduction-based section models such as `FiberSection3D`.

All of them satisfy the same compile-time concept:

$$\texttt{compute_response}(k), \qquad \texttt{tangent}(k),$$

with optional inelastic extensions through

$$\texttt{update}(k), \qquad \texttt{internal_state}().$$

This common contract is practical, but it already reveals a semantic overloading: some of these types are truly *material laws*, while others are *section laws* or even *constitutive reductions*.

25.2.3 Material instance and type erasure

The next layer is `MaterialInstance<Relation,StatePolicy>`, which wraps:

- a constitutive relation object;
- a per-point kinematic state container;
- access to the underlying relation through `constitutive_relation()`.

This is then lifted to the type-erased `Material<Policy>` wrapper, which stores:

- the concrete `MaterialInstance`;
- an update strategy (`ElasticUpdate` or `InelasticUpdate`);
- export helpers such as `internal_field_snapshot()` and `section_snapshot()`.

25.2.4 Constitutive sites

Finally, the constitutive object is attached to geometry through:

- `MaterialPoint<Policy>` in continuum elements;
- `MaterialSection<Policy>` in beams and shells.

This layering already captures a valuable idea:

geometry and topology are not constitutive objects;
a constitutive object is bound to a sampling site.

25.3 What is Good and Should Be Preserved

25.3.1 The measure-based generic contract

The most important success of the current module is that the constitutive interface is not hard-wired to Cauchy stress or to infinitesimal continuum strain. Instead, it works on generic conjugate pairs. This is exactly what a library needs if it aims to support:

- continuum solids;
- structural sections;
- future higher-order or enriched formulations;
- multiscale reductions and reconstructions.

25.3.2 Static polymorphism at the relation level

Concrete constitutive classes are template-friendly and concept-constrained. This gives:

- strong compile-time checking;
- direct inlining opportunities inside element kernels;
- no virtual dispatch when the full type is known.

This direction is correct and should remain the default in the hot path.

25.3.3 Separation between geometry and constitutive sites

The distinction between `IntegrationPoint` and `MaterialPoint` / `MaterialSection` is also correct in spirit. It is consistent with the earlier ontology work in the `Domain` refactor:

- the integration point is a numerical sampling site;
- the constitutive point is a physical role attached to that site.

25.3.4 The reduction-based path for structural elements

The existence of `FiberSection3D` is strategically important. It proves that the same element pipeline can host:

- a linear reduced section law;
- a nonlinear reduced section law reconstructed from uniaxial constituents.

This is exactly the kind of reduction/reconstruction mechanism that will later be needed for layered shells, smeared reinforcement, and scale-bridging between frame and continuum descriptions.

25.4 Observed Semantic Inconsistencies

25.4.1 The word `Material` currently means too many things

Today the code uses the word *material* for at least four different concepts:

1. a physical substance or phase (concrete, steel, confined concrete);
2. a constitutive law (`KentParkConcrete`, `MenegottoPintoSteel`);

3. a reduced section law (`TimoshenkoBeamSection3D`, `FiberSection3D`);
4. a type-erased operational wrapper (`Material<Policy>`).

This is the single most important semantic problem in the current module. Architecturally, these should not be collapsed into one noun.

25.4.2 `MaterialPolicy` is not a material

`SolidMaterial<6>`, `BeamMaterial<6,3>`, and `ShellMaterial<8,3>` do not describe a physical material. They define a *constitutive space*:

$$\mathcal{S} = (\text{kinematic type},\ \text{conjugate type},\ \text{dimension}).$$

So the name `MaterialPolicy` is semantically misleading. The type is really a *measure-space policy* or a *constitutive space descriptor*. The current name propagates confusion upward into `Material`, `MaterialPoint`, and `MaterialSection`.

25.4.3 `MaterialInstance` is not just a material instance

`MaterialInstance<Relation,StatePolicy>` currently bundles:

- a constitutive relation;
- kinematic state storage;
- direct access to the relation;
- optional internal-state access for inelastic models.

Semantically, this object is much closer to a *stateful constitutive point model* than to a material instance in the physical sense. In other words, it already lives at the Gauss-point level, not at the material-definition level.

25.4.4 Inelastic relations already contain the integration algorithm

The intended design suggests a clean split:

$$\text{constitutive law} \quad + \quad \text{integration strategy}.$$

However, for nonlinear materials this separation is only nominal at present. The current `InelasticUpdate` strategy simply delegates back to the material relation, while the actual algorithm lives inside:

- `PlasticityRelation`;
- `KentParkConcrete`;
- `MenegottoPintoSteel`;
- `FiberSection`.

Therefore the current strategy layer is semantically strong for elastic materials, but weak for inelastic ones. The empty `FullImplicitBackwardEuler.hh` placeholder makes this explicit.

25.4.5 The constitutive relation and its committed state are fused

For inelastic models, the relation object itself stores internal variables. This means that:

- the constitutive law is not purely a law;
- the law is not shareable as an immutable flyweight;
- the same class simultaneously represents parameters, algorithmic cache, and committed history.

This fusion is convenient for a first implementation, but it becomes a real limitation for:

- thread safety;
- state-block vectorisation;
- fine-grained checkpointing;
- large-scale nonlinear dynamics;
- constitutive substepping and rollback.

25.4.6 The kinematic state is duplicated and over-recorded

`MaterialState` stores the current kinematic measure, and for inelastic materials `MemoryState` stores the *entire history* of that measure. At the same time, the inelastic relations store their own internal variables.

This produces two problems:

- semantic duplication: committed constitutive history already exists in the relation state;
- memory amplification: the default inelastic path records every past strain state whether or not the algorithm requires it.

For nonlinear dynamics or long static load histories this is not sustainable. The default site state should be:

- current trial state,
- committed state,
- optionally converged last-step state,

not an ever-growing vector of all past strains.

25.4.7 The flyweight story is currently contradictory

The comments in `MaterialInstance` describe the relation as a shared flyweight. However, the copy constructor performs a deep copy of the relation. Because elements and Gauss-point carriers are usually created by copying a `Material<Policy>`, the practical behaviour is:

- elastic relations are often duplicated per point;
- inelastic relations are also duplicated per point;
- the claimed flyweight benefit is therefore much weaker than it first appears.

This is not just a micro-optimisation issue. It means the current naming and commentary no longer match the real ownership semantics.

25.4.8 Section laws are currently mixed with material laws

`TimoshenkoBeamSection3D`, `MindlinShellSection`, and `FiberSection3D` live inside the materials module and satisfy the same top-level concepts as bulk material laws. That is convenient, but it masks an important distinction:

- a bulk constitutive law maps local continuum measures to continuum stresses;
- a section constitutive law maps reduced section measures to section resultants;
- a fiber section is in fact a *reduction policy plus numerical integration over constituents.*

This distinction matters if the same section reconstruction is later reused for scale transfer to a continuum model.

25.4.9 Post-processing adapters are embedded in the core wrapper

`Material<Policy>` currently knows how to export:

- `InternalFieldSnapshot`;
- `SectionConstitutiveSnapshot`;
- fiber field snapshots.

This makes the wrapper convenient for VTK export, but it also means the central constitutive wrapper now depends on post-processing concerns. The core constitutive path should not grow indefinitely through `if constexpr`-based export detection.

25.4.10 Finite-strain constitutive models live outside the material module

Hyperelastic relations currently live in `src/continuum`. This is architecturally understandable, because finite-strain kinematics and tensor operations are housed there, but it also fragments the constitutive story:

- small-strain and section laws are described in `materials`;
- finite-strain laws are described in `continuum`.

This split becomes problematic when the target is large-displacement, inelastic, reinforced-concrete analysis. At that point the constitutive module and the kinematic module must meet through a cleaner interface.

25.5 Performance Implications

25.5.1 Per-fiber type erasure is expensive

The current `Fiber` type stores:

```
Material<UniaxialMaterial>
```

per fiber. This gives maximal heterogeneity and a pleasant API, but it is a poor default for large reinforced-concrete simulations because:

- each fiber carries a heap-owning type-erased wrapper;
- copies of fiber sections duplicate that structure repeatedly;
- the hottest loop in `FiberSection::integrate_fibers()` pays dynamic-dispatch and scattered-memory costs.

For a few dozen fibers this is fine. For layered shells, detailed RC walls, or multiscale transfer problems it will quickly become one of the dominant costs.

25.5.2 The default inelastic storage is not HPC-friendly

`MemoryState<std::vector<S>>` as the default carrier for inelastic materials is not suitable as the long-term production layout. It implies:

- heap growth per point;
- no fixed-size state block;
- poor cache locality;
- no easy vectorisation across sites.

For HPC-oriented nonlinear analysis the natural constitutive storage unit is a small fixed record:

$$\text{trial state} \oplus \text{committed state} \oplus \text{internal variables}.$$

25.5.3 The hot path should remain statically typed

The present design already suggests the right rule:

runtime polymorphism should live at heterogeneous container boundaries,
not inside the innermost constitutive loops.

Therefore:

- element-level heterogeneous containers may continue to use type erasure;
- Gauss-point kernels, return mapping, and fiber loops should preferably operate on fully typed laws and fully typed state blocks.

25.6 A Cleaner Separation: Material vs Constitutive Relation

25.6.1 Recommended ontology

The recommended semantic split is:

1. **Material data**: immutable physical parameters of a phase, mixture, or section family.
2. **Constitutive law**: the mathematical law that defines stress, tangent, and evolution equations for a given measure space.
3. **Integration algorithm**: the numerical procedure that advances the law in time or load.
4. **Constitutive state**: committed and trial internal variables at one site.
5. **Constitutive site**: the object bound to an integration point or section point, owning its state.
6. **Reduction policy**: the map from lower-scale fields to reduced section measures, and conversely the reconstruction back to a richer field when needed.

25.6.2 What should be called "material"

In this ontology, *material* should denote the physical object or parameter block, not the entire runtime wrapper. Examples:

- `ConcreteMaterialData`;
- `SteelMaterialData`;
- `IsotropicElasticData`;
- `RCSectionData`.

25.6.3 What should be called "constitutive law"

A constitutive law should be a purely local mathematical object:

$$(\text{state},\ \text{kinematics},\ \text{context}) \mapsto (\text{response},\ \text{algorithmic tangent},\ \text{new state}).$$

Its contract should not imply geometry, meshing, or ownership of an integration point.

25.6.4 What should be called "reduction policy"

Structural section models are not materials in the same sense as steel or concrete. They are reductions of a lower-scale description. Therefore `FiberSection3D` is better understood as:

a beam-section reduction policy together with a constitutive quadrature over constituent fibers.

The same idea generalises naturally to:

- layered shells;
- smeared reinforcement layers;
- shell-through-thickness integration of concrete damage/plasticity;
- scale transfer from beam/shell models to continuum initial fields.

25.7 A More Scalable Constitutive Contract

25.7.1 Constitutive context

The current strategy interface only sees the kinematic measure k. For the next generation of constitutive models, the local update will need a richer context:

$$\mathcal{C}_{n+1} = \{\Delta t,\ t_{n+1},\ \text{load increment},\ \text{temperature},\ \text{kinematic frame},\ \ell_{\text{int}},\ \text{regularization data}\}.$$

This is essential for:

- rate dependence and viscoplasticity;
- nonlinear dynamics;
- finite-strain constitutive updates;
- nonlocal damage or gradient regularisation;
- fracture-energy based softening.

25.7.2 Suggested compile-time split

An architecture compatible with the current design philosophy would be:

`ConstitutiveSpace`	measure types only,
`ConstitutiveLaw`	physics only,
`IntegrationAlgorithm`	numerical update only,
`ConstitutiveState`	small fixed state blocks,
`ConstitutiveSite<Law,Algorithm,Storage>`	site-level wrapper.

This preserves static polymorphism because all of these remain templates or concept-constrained value types.

25.8 Implications for Reinforced Concrete Across Scales

25.8.1 Uniaxial constituent scale

At the constituent scale the current library already has a credible basis:

- `KentParkConcrete` for confined and unconfined concrete;
- `MenegottoPintoSteel` for reinforcing steel;
- `FiberSection3D` for reduced beam sections.

This scale is the correct place for:

- section-level hysteresis;
- bar yielding and cyclic effects;
- confined versus cover concrete distinction;
- section-force reconstruction.

25.8.2 Layered shells

The next natural scale extension is not yet 3D fracture, but layered shell constitutive models:

- concrete layers through thickness;
- membrane reinforcement layers;
- optional shear layers;
- section resultants obtained by through-thickness integration.

Architecturally this should reuse the same ideas as `FiberSection3D`, but on a shell reduction space rather than a beam section space.

25.8.3 Continuum RC with cracking and fracture

At the continuum scale, merely adding local softening to a stress-strain law is not enough. Once cracking localises, the formulation becomes mesh-sensitive unless an objective regularisation is introduced. The material architecture must therefore distinguish:

- **local constitutive law**: plasticity, damage, plastic-damage, orthotropic cracking, cohesive traction-separation;
- **regularisation policy**: crack-band scaling, nonlocal averaging, gradient enhancement, phase-field, or interface insertion.

This distinction is crucial. Fracture is not only a constitutive issue; it is also a localisation-regularisation issue.

25.8.4 Large displacements and dynamics

For large-displacement RC, the constitutive layer should not be tied to one specific small-strain measure. Instead, the local law should operate on the appropriate conjugate space supplied by the kinematic formulation:

- infinitesimal strain / Cauchy-like stress for small-strain models;
- Green–Lagrange / second Piola–Kirchhoff for total Lagrangian models;
- current-frame measures for updated-Lagrangian or corotational models.

The constitutive law and the kinematic policy must meet through an explicit measure-space contract, not through ad hoc branches.

25.9 Suggested Refactor Path

25.9.1 Stage 1: semantic cleanup

The first stage should be almost entirely architectural and low-risk:

- rename `MaterialPolicy` toward `ConstitutiveSpacePolicy` or similar;
- document that `Material<Policy>` is an operational wrapper, not a physical material;
- split bulk laws, section laws, and reduction policies into clearly named submodules.

25.9.2 Stage 2: state redesign

The second stage should replace `MemoryState` as the default inelastic carrier. The target storage is:

- fixed-size committed state;
- fixed-size trial state;
- optional recorder or history logger outside the hot path.

25.9.3 Stage 3: genuine algorithm-law separation

The third stage should make the integration strategy real for nonlinear laws:

- `BackwardEuler`;
- substepping decorators;
- line-search or local damping wrappers;
- possibly explicit and operator-split strategies for specific models.

At that point the nonlinear relation becomes a law again, not a law plus its only admissible update algorithm.

25.9.4 Stage 4: typed hot path, erased boundary

The fourth stage should move the runtime-erased wrapper outward:

- typed laws and typed states inside Gauss-point loops;
- erased wrappers only where heterogeneous containers are genuinely required.

For fiber sections, the natural next optimisation is:

- homogeneous fiber blocks for concrete patches and bar groups;
- structure-of-arrays storage for fiber coordinates, areas, and state blocks;
- optional erased fallback only for rare heterogeneous mixtures.

25.9.5 Stage 5: RC multiscale and fracture

Only after the semantic and state cleanup is stable does it make sense to add:

- layered RC shell sections;
- continuum plastic-damage or smeared cracking models;
- fracture-energy regularisation;
- cohesive interfaces or phase-field fracture.

Without the earlier cleanup, those features would be forced into already overloaded types and the module would become harder to maintain, not easier.

25.10 Non-owning Type Erasure in `Material.hh`

25.10.1 Viability assessment

The non-owning type-erasure pattern is viable in the materials module, but not as a wholesale replacement of the current owning wrapper. It is viable precisely because the borrowed erased model stores only:

- a pointer to the concrete constitutive object;
- a pointer to the integration strategy;
- one virtual-table pointer.

Therefore the non-owning erased model has a stable footprint of three machine pointers and fits naturally into a fixed local buffer. This is fundamentally different from the owning case, where the concrete constitutive objects are often too large and too heterogeneous for small-buffer optimisation to pay off.

25.10.2 What problem it solves

The borrowed view solves a specific architectural problem:

how to pass constitutive objects through generic code without cloning or re-owning them.

That is useful for:

- algorithms that only need a temporary constitutive handle;
- post-processing and reconstruction utilities;
- adapters layered on top of `MaterialPoint` and `MaterialSection`;
- future heterogeneous orchestration code that should not trigger deep copies accidentally.

25.10.3 What problem it does not solve

The borrowed view does *not* solve constitutive storage by itself. In particular, it should not be misused to pretend that the following problem has disappeared:

each constitutive site still needs well-defined ownership of its state.

This matters especially for reinforced-concrete fiber sections. Each fiber is not merely a material label; it is a constitutive site with its own history. Replacing per-fiber owning storage with a trivial shared borrowed view would collapse independent histories and would therefore be semantically wrong.

25.10.4 Why the strategy belongs in `Material.hh`

The strategy object is the correct injection point for the constitutive integration algorithm because it sits exactly at the operational boundary between:

- the constitutive relation as a law;
- the constitutive site as a stateful runtime object.

This is the right location to host future algorithms such as:

- backward-Euler return mapping;
- substepping;
- line-search or local damping decorators;
- explicit or operator-split updates for dynamics.

By contrast, embedding all integration logic directly inside the relation class fuses law and algorithm and makes it much harder to reuse the same physical law with different numerical update procedures.

25.10.5 Refactor adopted in the current code

The present refactor therefore adopts a hybrid design:

- `Material<Policy>` remains the owning, heap-backed erased wrapper;
- `MaterialConstRef<Policy>` is a borrowed read-only erased view;
- `MaterialRef<Policy>` is a borrowed mutable erased view.

This preserves the current ownership semantics of `MaterialPoint`, `MaterialSection`, and `FiberSection`, while enabling generic algorithms to work with borrowed constitutive handles when ownership transfer is not intended.

25.10.6 Architectural consequence

The key consequence is that the module now has a clearer boundary:

- ownership and lifetime remain explicit;
- the hot constitutive storage is not forced into an unsuitable small-buffer abstraction;
- the library gains a lightweight non-owning polymorphic layer exactly where it is semantically valid.

25.11 Final Opinion

The current materials module is already much better than a monolithic "stress-strain class" design. It has:

- strong measure-based abstractions;
- useful concept constraints;
- a credible path for structural nonlinear RC through fibers;
- a polymorphic envelope that works across solids, beams, and shells.

But the module is now at the point where its first successful generalisation is becoming its main semantic limitation. The primary issue is no longer whether the constitutive code works. It does. The primary issue is that the present API still uses the word "material" for too many different ontological objects.

The recommended direction is therefore not a rewrite, but a disciplined separation:

material data → constitutive law → integration algorithm → stateful constitutive site → reduction / reconstruction policy.

If this separation is carried through while preserving the existing compile-time contracts, `fall_n` will have a robust basis for:

- nonlinear reinforced concrete frame analysis;
- layered and reduced-order structural models;
- finite-strain and dynamic constitutive updates;
- objective continuum cracking and fracture formulations.

That is the right architectural target.

Chapter 26

Material Module Semantic Cleanup

26.1 Purpose

This chapter documents the first low-risk semantic cleanup applied to the materials module after the architectural analysis of Chapter 25. The goal of this phase is not to replace the existing API, but to make the ontology explicit while preserving the current executable code and tests.

The cleanup follows three rules:

- no behavioural change in the constitutive hot path;
- no forced migration of existing code;
- new names must coexist with legacy names until the next refactor stage.

26.2 What Was Changed

26.2.1 Constitutive-space aliases

The file `MaterialPolicy.hh` now exposes semantically explicit aliases:

- `ContinuumConstitutiveSpace<N>`;
- `BeamConstitutiveSpace<N,Dim>`;
- `ShellConstitutiveSpace<N,Dim>`.

Alongside them, named aliases now exist for the most common spaces:

- `ThreeDimensionalConstitutiveSpace`;
- `TimoshenkoBeamConstitutiveSpace3D`;
- `MindlinReissnerShellConstitutiveSpace3D`;
- and their lower-dimensional counterparts.

The legacy names `ThreeDimensionalMaterial`, `TimoshenkoBeam3D`, etc. remain available as compatibility aliases.

26.2.2 Stateful constitutive-site aliases

The file `LinealElasticMaterial.hh` now exposes:

- `ConstitutiveSite<Relation,StatePolicy>`;
- `ElasticConstitutiveSite<Relation>`;
- `InelasticConstitutiveSite<Relation>`.

These are semantic aliases for the existing `MaterialInstance` class. The old name is intentionally preserved, but the new aliases make the object's meaning explicit: it is already a *stateful constitutive site*, not a mere material definition.

26.2.3 Erased constitutive handles

The file `Material.hh` now exposes the following semantic aliases:

- `ConstitutiveHandle<Space>` for the owning erased wrapper;
- `ConstitutiveConstHandleRef<Space>` for the borrowed const view;
- `ConstitutiveHandleRef<Space>` for the borrowed mutable view.

This makes the role of `Material<Policy>` explicit without breaking the existing API.

26.2.4 Constitutive-site accessors

`MaterialPoint` and `MaterialSection` now expose both naming families:

- legacy accessors: `material_cref()`, `material_ref()`;
- semantic accessors: `constitutive_cref()`, `constitutive_ref()`.

Additional site aliases were introduced:

- `ContinuumConstitutiveSite<Space>`;
- `SectionConstitutiveSite<Space,PointDim>`.

26.3 Ownership Semantics Clarified

One important contradiction was removed from the documentation of `MaterialInstance`. The previous text suggested flyweight-style sharing as the default interpretation of the relation handle. That was not true of the actual copy semantics.

The code already behaved as follows:

- ordinary copy construction deep-clones the relation;
- explicit sharing occurs only when the user passes an external `std::shared_ptr<Relation>`.

The comments now match that behaviour. This is important because implicit sharing between constitutive sites would be semantically dangerous in nonlinear analysis.

26.4 Why This Stage Matters

The cleanup may look cosmetic at first sight, but it removes a real source of architectural ambiguity. Before this change, the same word "material" could refer to all of the following:

- a constitutive space;
- a physical material definition;
- a stateful constitutive site;
- an owning erased runtime handle.

After this stage, the code base can distinguish these meanings explicitly without forcing a flag day migration.

26.5 What Was Intentionally Not Changed

This cleanup does *not* yet:

- separate constitutive law and constitutive state into distinct runtime objects;
- remove `MemoryState` from the default inelastic path;
- move `FiberSection` out of the materials namespace hierarchy;
- change the hot-loop data layout of fiber sections or continuum points.

Those changes belong to the next refactor stage and would carry more risk.

26.6 Immediate Benefits

The immediate benefits of this stage are:

- clearer architectural vocabulary in code and tests;
- more honest documentation of ownership and copying;
- a smoother path toward the next law/state/algorithm split;
- better traceability for future reinforced-concrete, multiscale, and fracture work.

26.7 Next Step

The next meaningful refactor should preserve these aliases and attack the real state-management issue:

$$\textbf{constitutive law} \oplus \textbf{integration algorithm} \oplus \textbf{constitutive state}$$

Only after that separation is explicit will it be reasonable to redesign the storage layout for large-scale reinforced-concrete simulations, nonlinear dynamics, and continuum cracking or fracture models.

Chapter 27

Constitutive State Storage Cleanup

27.1 Motivation

The semantic cleanup of the materials module revealed a persistent mismatch: the constitutive-site abstraction in `fall_n` stored kinematic history by default for inelastic materials, even though the vast majority of the code used `current_state()` only as the *last committed kinematic state*. This had three undesirable consequences:

- the default inelastic path allocated and grew storage that was not needed by most algorithms;
- the API blurred the distinction between "current committed value", "full history", and "trial state";
- the architecture was poorly prepared for generic constitutive integration algorithms requiring trial/accept/reject workflows.

This chapter introduces an explicit state-storage vocabulary while preserving backward compatibility and the static, header-only nature of the hot path.

27.2 Storage Roles

The cleanup distinguishes three different storage roles.

27.2.1 CommittedState

`CommittedState<S>` stores a single value of type `S`. Every `update()` overwrites the previously stored state. This is the correct default for:

- elastic materials;
- inelastic constitutive sites whose irreversible memory already lives inside the constitutive law;
- post-processing paths that only need the last accepted strain-like measure at a material site or section site.

Architecturally this is just the existing `ElasticState<S>` under a new semantic alias. The implementation remains trivial and fully inlineable.

27.2.2 HistoryState

`HistoryState<S>` is the explicit opt-in path for storing a full kinematic history. It is semantically equivalent to the legacy `MemoryState<S>`, but the key clarification is that the policy now owns a *storage backend*, not merely a hard-coded `std::vector`. Each `update()` appends to the supplied storage, and `current_value()` returns the last entry.

Two storage backends are now provided explicitly:

- `DynamicHistoryStorage<S>` for unbounded growth;
- `CircularHistoryStorage<S, N>` for a fixed-size sliding window known at compile time.

This distinction matters because some constitutive models genuinely need history, but not *all* of it. For such cases, a circular buffer provides deterministic memory, cache-friendly locality, and zero heap growth after construction.

This path remains useful for:

- debugging and validation;
- offline material diagnostics;
- experimental algorithms that truly need access to all previous committed kinematic states.

The important change is that `HistoryState` is no longer the *implicit* inelastic default, but remains available with whichever storage backend is appropriate for the algorithm.

27.2.3 TrialCommittedState

`TrialCommittedState<S>` introduces a minimal two-level storage:

- a committed state;
- an optional staged trial state.

The policy exposes:

- `update()` to stage a trial value;
- `commit_trial()` to accept it;
- `revert_trial()` to discard it;
- `current_value()` to see the trial state if present, otherwise the committed one.

This policy is not yet the production default. Its role is preparatory: it provides the storage semantics needed by future generic integration strategies without forcing those algorithms to be encoded inside each constitutive law.

27.3 MaterialState as a Storage Adapter

`MaterialState` now depends on the more accurate concept `StateStoragePolicyFor`. The legacy name `MemoryPolicyFor` is preserved as an alias so existing code remains valid during the transition.

Besides `current_value()` and `update()`, `MaterialState` now conditionally forwards:

- `commit_trial()`;

- revert_trial();
- has_trial_value();
- committed_value();
- trial_value();
- size() and indexed logical access when the storage backend is history-bearing.

This conditional forwarding is implemented with requires-based introspection. No virtual dispatch is introduced, and no overhead is paid for policies that do not support staged trial states.

27.4 Change in the Default Inelastic Path

The most important semantic change is in MaterialInstance<Relation, StatePolicy>:

- InelasticConstitutiveSite<R> now defaults to CommittedState;
- explicit history tracking remains available through HistoryTrackingConstitutiveSite<R> and HistoryTrackedInelasticMaterial<R>;
- bounded history tracking is available through CircularHistoryConstitutiveSite<R, N>, which binds the site to a fixed compile-time circular buffer;
- TrialConstitutiveSite<R> exposes the staged-storage path for future algorithmic work.

This is semantically more honest. In the current architecture, models such as J2PlasticityRelation, KentParkConcrete, and MenegottoPintoSteel store their irreversible internal variables inside the constitutive relation itself. The site-level kinematic state is therefore not the true inelastic memory; it is primarily a local snapshot of the last accepted measure used by post-processing and reconstruction.

27.5 Interaction with Constitutive Updates

The constitutive-site update path was also adjusted so that storage policies with staged trial semantics behave correctly under the existing API:

1. the constitutive law updates its own irreversible variables;
2. the site storage receives the kinematic state through state_.update(k);
3. if the storage policy supports commit_trial(), the staged value is immediately promoted to committed state.

This keeps current behaviour unchanged for production algorithms while making the storage layer ready for a later refactor in which the constitutive integrator controls trial and commit phases explicitly.

27.6 Why This Matters for Reinforced Concrete Across Scales

For reinforced concrete across continuum, sectional, and frame scales, a clean separation between *constitutive law*, *state storage*, and *integration algorithm* is essential:

- frame fiber sections require many local constitutive sites, so storage waste multiplies quickly;
- dynamic nonlinear analyses require robust and explicit commit/revert semantics;
- large-displacement and finite-strain formulations need a precise notion of trial versus committed state;
- continuum-scale cracking and fracture will eventually require local and nonlocal internal variables, which should not be confused with merely storing a history of kinematic inputs.

This cleanup does not yet solve those higher-level problems. It does, however, remove a semantic obstacle: site-level storage is no longer forced to pretend that "inelastic" automatically means "store all past kinematics".

27.7 Next Refactor Stage

With storage semantics clarified, the next architectural step is now better defined:

1. separate `ConstitutiveLaw` from `ConstitutiveState`;
2. let the constitutive integrator evolve the state explicitly instead of delegating the entire algorithm to the law;
3. make the future constitutive-state object choose not only its semantic role (committed/history/trial) but also its storage backend (dynamic, circular, small-buffer, etc.);
4. reserve non-owning type erasure for borrowed constitutive views rather than for owned site storage;
5. keep the hot path statically typed for homogeneous loops such as fiber integration and section reconstruction.

That next stage is the one that will most directly enable robust nonlinear reinforced concrete, dynamics, and eventually objective crack/fracture modelling at the continuum scale.

Chapter 28

ConstitutiveState as a Semantic Layer

28.1 Why Another Layer Was Needed

After the storage cleanup of the previous chapter, the code still had an architectural ambiguity: `MaterialState` was doing two jobs at once.

- At the low level, it was a generic adapter over a storage policy.
- At the constitutive-site level, it was implicitly standing in for the local state of a material point or section point.

Those roles are related, but they are not identical. A storage adapter is an implementation device. A constitutive state is a modelling concept.

To make that distinction explicit without breaking the existing kernels, this phase introduces `ConstitutiveState<StateStoragePolicy, ...>` as a thin, fully inline semantic wrapper over `MaterialState`.

28.2 Layered View

The state path is now:

`HistoryStorage` / `CircularHistoryStorage` / `ElasticState` / `TrialCommittedState` → `MaterialState` → `ConstitutiveState` → `MaterialInstance`

The meaning of each layer is now cleaner:

- `HistoryStorage` and its variants define how samples are physically stored;
- `MaterialState` adapts that storage to a uniform compile-time contract;
- `ConstitutiveState` says that the stored quantity is the local state of a constitutive site;
- `MaterialInstance` binds that local state to a constitutive law.

28.3 What ConstitutiveState Adds

`ConstitutiveState` does not add runtime overhead or dynamic dispatch. Its value is semantic and architectural:

- it gives `MaterialInstance` an explicit `ConstitutiveStateT` alias;
- it exposes `constitutive_state()` as a first-class accessor;
- it lets the code and the documentation talk about "the constitutive state of the site" instead of "the storage policy wrapper";
- it prepares the next step, where the constitutive law should stop owning all irreversible memory internally.

In other words, the wrapper is intentionally thin, but its name matters. Architecturally, names are part of the model.

28.4 Effect on MaterialInstance

`MaterialInstance<Relation, StatePolicy>` no longer stores `MaterialState<StatePolicy, KinematicT>` directly. It now stores

```
ConstitutiveState<StatePolicy, KinematicT>
```

and exposes it through:

- `current_state()` as the legacy direct view;
- `constitutive_state()` as the new semantic accessor.

This means user code and future algorithms can progressively move from "give me the current strain-like value" toward "give me the constitutive-state object attached to this site".

28.5 Why This Matters for Future Nonlinear Algorithms

The next architectural step should separate:

1. the constitutive law;
2. the constitutive state;
3. the integration algorithm.

That separation is difficult if the local state has no identity of its own. By introducing `ConstitutiveState`, the code now has a clear place where future information can migrate:

- committed kinematic state;
- trial state;
- algorithmic internal variables;
- nonlocal history variables;
- fracture or damage regularisation data;
- time-integration metadata for dynamic constitutive updates.

This does not mean all of that should be stored in one monolithic object. It means the architecture now has a semantically correct anchor for those future choices.

28.6 Static Polymorphism Is Preserved

The introduction of `ConstitutiveState` preserves the compile-time character of the constitutive hot path:

- all storage-policy choices remain template parameters;
- no additional virtual calls are introduced;
- circular-history windows still use fixed-size arrays and compile-time capacity;
- the relation type remains statically known inside homogeneous loops.

This is important for fiber sections and any future continuum crack/fracture model where thousands or millions of local constitutive sites may be updated.

28.7 What This Refactor Still Does Not Do

Even with `ConstitutiveState` in place, the local nonlinear laws in the current code still keep their irreversible memory internally. Therefore:

- `ConstitutiveState` is not yet the sole owner of local history;
- `ConstitutiveIntegrator` still does not evolve an explicit state object passed by argument;
- the design is cleaner, but not yet fully factored.

This is acceptable at this stage. The refactor is intentionally incremental: first make the ontology correct, then move behaviour.

28.8 Immediate Consequence

From this point onward, the recommended interpretation is:

- `MaterialState`: low-level storage adapter;
- `ConstitutiveState`: local state object of a constitutive site;
- `MaterialInstance`: site-level binding of relation + state;
- `Material<Policy>`: erased owning constitutive handle;
- `MaterialPoint` / `MaterialSection`: continuum and structural constitutive sites bound to geometric integration sites.

This vocabulary is much closer to the real mathematical model and therefore a better base for the next refactor stage.

Chapter 29

ConstitutiveIntegrator as the Algorithmic Injection Point

29.1 Motivation

After introducing `ConstitutiveState`, the constitutive subsystem still had one important ambiguity: the algorithmic step used to evaluate and commit a constitutive site was semantically present, but it was still described under the generic name `IntegrationStrategy`. That name was operationally useful, but it was too broad. The relevant object at this level is not any numerical integration procedure; it is the *local constitutive integrator*.

This chapter makes that distinction explicit by introducing `ConstitutiveIntegrator`.

29.2 Local Architectural Split

The constitutive subsystem is now described by four roles:

1. `ConstitutiveRelation`: the physical local law;
2. `ConstitutiveState`: the state attached to the site;
3. `ConstitutiveIntegrator`: the algorithm that queries and commits the site;
4. `Material<Policy>`: the erased runtime handle that injects the chosen integrator into heterogeneous containers.

This is not yet the final fully factored architecture, because many current nonlinear laws still keep irreversible variables internally. However, the public and internal semantics now reflect the intended long-term split:

```
ConstitutiveLaw + ConstitutiveState + ConstitutiveIntegrator
```

29.3 Why the Injection Point Stays in `Material<Policy>`

The local algorithm is injected at the `Material<Policy>` boundary on purpose.

- It preserves the existing type-erased heterogeneous storage model.
- It avoids contaminating each constitutive relation with multiple algorithmic variants prematurely.

- It keeps the hot path statically typed inside each homogeneous material model, while the runtime polymorphism remains confined to the already existing erased handle.
- It naturally matches the user-facing syntax:

```
Material<ThreeDimensionalMaterial>{
    J2PlasticMaterial3D{E, nu, sigma_y, H},
    EmbeddedInelasticConstitutiveIntegrator{}
};
```

- It opens the door to future variants such as substepping, line-search local updates, operator splits, or explicit/implicit constitutive drivers without changing element kernels.

29.4 Current Concrete Integrators

Two semantic integrators are now made explicit:

- `PassThroughIntegrator`: path-independent evaluation. It reads stress and tangent directly from the constitutive relation and keeps `commit()` as a no-op for backward-compatible elastic behaviour.
- `EmbeddedRelationIntegrator`: compatibility bridge for current nonlinear laws. It evaluates response and tangent from the relation, and during `commit()` it advances the relation through its own `update()` method while also updating the external `ConstitutiveState`.

The legacy names remain as aliases:

- `ElasticUpdate` ≡ `PassThroughIntegrator`
- `InelasticUpdate` ≡ `EmbeddedRelationIntegrator`

This keeps the codebase source-compatible while allowing the semantic cleanup to proceed.

29.5 Why This Matters

The key architectural benefit is that the current code can now express the following distinction:

- the constitutive *law* is responsible for the physics;
- the constitutive *integrator* is responsible for the local algorithmic realization of that physics inside a time/load step.

That distinction is essential for future nonlinear concrete and fracture work. For example, the same inelastic law may later be integrated by:

- an embedded monolithic return-mapping;
- a generic backward-Euler driver;
- a substepping wrapper;
- a viscoplastic regularized driver;
- a dynamic operator split coupled to finite-kinematics update rules.

29.6 Custom Integrators

The refactor also validates a more important property than the naming itself: `Material<Policy>` is now an actual injection point for custom local algorithms.

The new regression test introduces a custom integrator that intentionally updates only the external constitutive-state carrier but does not evolve the relation's internal irreversible variables. The result is a predictable change in post-commit behaviour, which proves that the algorithmic policy is not hard-wired to the constitutive relation.

This is exactly the kind of freedom required for future scale-reconstruction pipelines and multi-algorithm benchmarking.

29.7 What Has Not Been Completed Yet

This step is a semantic and architectural split, not a full behavioural one. The following limitations remain:

- many inelastic relations still own their irreversible state internally;
- the integrator does not yet receive an explicit algorithmic state object distinct from the constitutive relation;
- the current bridge integrator still relies on `relation.update(k)` for nonlinear constitutive evolution.

Therefore, the next meaningful refactor should move the local evolution data out of the constitutive relation and into explicit state objects wherever that is mathematically coherent.

29.8 Immediate Architectural Interpretation

After this step, the recommended reading of the subsystem is:

- `ConstitutiveRelation`: local physical constitutive model;
- `ConstitutiveState`: state attached to the site;
- `ConstitutiveIntegrator`: local algorithmic driver;
- `MaterialInstance`: typed constitutive site;
- `Material<Policy>`: erased constitutive handle with injected local integrator.

This is a materially more precise ontology than the previous generic "strategy" language, and it is better aligned with the future goals of inelastic reinforced concrete, dynamics, large displacements, and continuum-scale damage or fracture.

Chapter 30

Explicit Algorithmic State in `PlasticityRelation`

30.1 Why This Step Matters

The previous chapter introduced `ConstitutiveIntegrator` as the algorithmic injection point at the erased constitutive-handle boundary. That was necessary, but not sufficient. As long as the nonlinear constitutive law still owns its irreversible variables internally, the split remains only partial.

This phase takes the first behavioural step beyond semantics: `PlasticityRelation` can now be evaluated and committed against an *explicit external* algorithmic state.

30.2 Old Situation

Originally, `PlasticityRelation` stored a member α_n internally and all core operations were implicitly tied to that member:

$$\boldsymbol{\sigma}_{n+1} = \texttt{compute_response}(\boldsymbol{\varepsilon}_{n+1}), \tag{30.1}$$
$$\mathbf{C}^{ep}_{n+1} = \texttt{tangent}(\boldsymbol{\varepsilon}_{n+1}), \tag{30.2}$$
$$\alpha_{n+1} = \texttt{update}(\boldsymbol{\varepsilon}_{n+1}). \tag{30.3}$$

That design is workable for a local prototype, but architecturally it creates three problems:

- the constitutive law is not clearly separated from the constitutive site;
- the local integration algorithm cannot be cleanly redirected to other state carriers;
- sharing or borrowing the law becomes semantically fragile because the relation still behaves as if it owned the site memory.

30.3 New Explicit-State Contract

`PlasticityRelation` now supports a second, more explicit interface:

```
ConjugateT compute_response(const KinematicT& eps,
                            const InternalVariablesT& alpha) const;

TangentT tangent(const KinematicT& eps,
                 const InternalVariablesT& alpha) const;

```

```
void commit(InternalVariablesT& alpha,
            const KinematicT& eps) const;
```

Mathematically, the relation is now able to realize the return-mapping map

$$(\boldsymbol{\varepsilon}_{n+1}, \alpha_n) \mapsto (\boldsymbol{\sigma}_{n+1}, \mathbf{C}^{ep}_{n+1}, \alpha_{n+1}) \tag{30.4}$$

without requiring α_n to live inside the relation object itself.

30.4 Compatibility Is Preserved

The embedded-state API is still available:

- `compute_response(eps)`
- `tangent(eps)`
- `update(eps)`
- `internal_state()`

Those methods now act as a compatibility layer around the explicit-state core. Therefore:

- existing tests and client code continue to work;
- the new architecture can progressively migrate site storage out of the relation;
- naked relations can still be used in the old stateful way when convenient.

30.5 What Changed Internally

The central change is not the public overloads by themselves, but the internal factoring of the return-mapping kernel. The predictor/corrector path now receives α_n explicitly:

- elastic predictor uses the supplied plastic strain;
- effective trial stress uses the supplied hardening state;
- return-mapping builds α_{n+1} from the supplied α_n, not from an implicitly owned member.

This makes the local nonlinear map much closer to its mathematical form.

30.6 Interaction with `MaterialInstance`

The typed constitutive site `MaterialInstance<Relation, ...>` now uses the explicit-state path automatically when the relation satisfies `ExternallyStateDrivenConstitutiveRelation`. In that case:

- the site stores the algorithmic internal variables;
- `compute_response()` and `tangent()` query the relation with that explicit state;
- `update()` commits the site state through `relation.commit(alpha, eps)`;
- `internal_state()` exposes the site-level algorithmic memory, not the compatibility state embedded inside the relation.

This is the first place where the constitutive site becomes semantically more important than the relation object.

30.7 Interaction with `ConstitutiveIntegrator`

The bridge integrator `EmbeddedRelationIntegrator` now detects the new contract and prefers:

```
relation.commit(site.algorithmic_state(), eps)
```

over the legacy

```
relation.update(eps)
```

when that explicit-state path exists.
Therefore the architectural hierarchy is now more coherent:

- `PlasticityRelation` provides a local nonlinear map with an explicit algorithmic state argument;
- `MaterialInstance` owns the state of the constitutive site;
- `ConstitutiveIntegrator` drives the commit path.

30.8 What the New Tests Prove

The new regression tests verify three important facts:

1. committing an external plasticity state evolves that external state;
2. doing so does *not* mutate the compatibility state owned by the naked relation;
3. a `MaterialInstance` built from `PlasticityRelation` now stores the plastic internal variables at the site level, and subsequent stresses depend on that site state.

That is the first concrete proof that behaviour is starting to move away from law-owned memory and toward site-owned memory.

30.9 Why the Cache Was Not Reused

The embedded-state implementation of `PlasticityRelation` contained a mutable cache keyed effectively by the strain. That cache was valid only under the implicit assumption that a given relation instance corresponded to a single local state.

Once the same relation can be evaluated with arbitrary explicit states, that assumption is no longer valid. Reusing the old cache for the explicit-state path would have been semantically unsafe.

The current explicit-state overloads therefore prioritise correctness over micro-optimisation and compute directly from the supplied state. If needed later, the correct optimisation point is the constitutive site or the local integrator, not a state-agnostic mutable cache inside the law.

30.10 Current Boundary of the Refactor

At the stage described in this chapter, only `PlasticityRelation` had been migrated to the new explicit-state contract. The following models still kept their irreversible memory internally:

- `MenegottoPintoSteel`
- `KentParkConcrete`

- `FiberSection`

This is intentional. The architectural pattern is now proven on one important continuum inelastic law before being propagated to uniaxial hysteretic and section-reduction models.

That propagation is completed for the uniaxial steel and concrete laws in the next chapter.

30.11 Next Logical Step

The next meaningful move is to propagate the same pattern to uniaxial nonlinear laws, especially those used in reinforced-concrete fiber sections. That will make the constitutive-site state explicit not only for continuum plasticity, but also for steel hysteresis, concrete crushing/softening, and eventually section-level nonlinear reductions.

Once that is in place, the path toward dynamic constitutive updates, finite kinematics, nonlocal regularisation, and continuum-scale damage or fracture becomes much clearer.

Chapter 31

Explicit Algorithmic State in Uniaxial Steel and Concrete Laws

31.1 Why This Step Follows Naturally

Chapter 31 proved that the constitutive-site state can be externalised for a continuum inelastic law without breaking the legacy API. The next architecturally meaningful target is the pair of uniaxial nonlinear laws that support reinforced-concrete fiber sections: `MenegottoPintoSteel` and `KentParkConcrete`.

That propagation matters for two reasons:

- reinforced concrete in `fall_n` is already assembled from many uniaxial constitutive sites embedded in a section reduction;
- once those sites own their irreversible variables explicitly, the same architectural pattern scales from continuum plasticity to structural reduction and eventually to multi-scale transfer.

31.2 Semantic Improvement

Before this step, both uniaxial laws still mixed two different roles inside a single object:

1. the constitutive map itself, that is, the stress–strain law;
2. the site memory needed to follow hysteresis, unloading branches, cracking, yielding, reversal points, and so on.

That coupling was acceptable for a local prototype, but it was semantically inconsistent with the direction already established for `PlasticityRelation`. A constitutive law should define the local map, while the constitutive site should own the algorithmic state.

31.3 New Contract

Both `MenegottoPintoSteel` and `KentParkConcrete` now satisfy `ExternallyStateDrivenConstitutiveRelati`
Concretely, they support the explicit-state interface

```
ConjugateT compute_response(const KinematicT& eps,
                            const InternalVariablesT& alpha) const;

TangentT tangent(const KinematicT& eps,
                 const InternalVariablesT& alpha) const;
```

```

void commit(InternalVariablesT& alpha,
            const KinematicT& eps) const;
```

This means that the constitutive law can now be used as the pure local map

$$(\varepsilon_{n+1}, \alpha_n) \mapsto (\sigma_{n+1}, C^{\text{alg}}_{n+1}, \alpha_{n+1})$$

without requiring α_n to live inside the relation object itself.

31.4 Menegotto–Pinto Steel

For `MenegottoPintoSteel`, the explicit state object stores:

- the last reversal point;
- the current asymptote-intersection point;
- accumulated plastic excursion;
- loading direction and committed strain/stress.

The key refactor was to isolate the state update into a dedicated `commit_state()` kernel. The explicit-state path now:

1. evaluates the current branch using the supplied `MenegottoPintoState`;
2. commits the new reversal/branch information into that explicit state;
3. leaves the embedded compatibility state untouched.

The old API still exists: `compute_response(eps)`, `tangent(eps)`, `update(eps)`, and `internal_state()` remain available as a compatibility layer.

31.5 Kent–Park Concrete

For `KentParkConcrete`, the explicit state object stores:

- the most compressive strain reached on the envelope;
- the stress at that point;
- the unloading plastic strain;
- cracking status in tension;
- the last committed pair (ε, σ).

Here the refactor isolated the old `update()` behaviour into a `commit_state()` function that operates on an explicit `KentParkState`. This makes the simplified compression-envelope / unloading logic reusable by both:

- the legacy embedded-state path;
- the new explicit-state path used by constitutive sites.

31.6 Why FiberSection Did Not Need a New API

This point is important architecturally. FiberSection already stores each fiber as

```
Material<UniaxialMaterial>
```

which in turn delegates to a typed constitutive site MaterialInstance<Relation, StatePolicy>. Since MaterialInstance now prefers the explicit-state path whenever the relation satisfies ExternallyStateDrivenConstitutiveRelation, the benefit propagates automatically to fibers.

Therefore no new visualization path, no new section API, and no new type erasure was needed. The existing architecture was already good enough; it only needed the constitutive laws to satisfy the stronger contract.

31.7 What the New Tests Prove

The new uniaxial regressions verify the following facts:

1. an external MenegottoPintoState evolves when committed explicitly, while the naked relation keeps its compatibility state untouched;
2. an external KentParkState evolves when committed explicitly, and unloading from that state differs from the virgin-envelope response;
3. a typed constitutive site MaterialInstance<MenegottoPintoSteel, CommittedState> stores the steel hysteretic state at the site level;
4. a typed constitutive site MaterialInstance<KentParkConcrete, CommittedState> stores the concrete envelope/unloading state at the site level;
5. existing fiber-section tests still pass, confirming that the new constitutive-site ownership model does not break the section reduction.

31.8 Architectural Consequences

After this step the semantic picture is more coherent:

- MenegottoPintoSteel and KentParkConcrete are constitutive laws with an optional embedded compatibility state;
- MaterialInstance is the real constitutive site;
- EmbeddedRelationIntegrator can now drive steel, concrete, and plasticity through the same explicit-state protocol;
- FiberSection remains a reduction policy over many constitutive sites instead of becoming yet another owner of hidden irreversible memory.

31.9 What Still Remains to Be Done

This chapter does *not* complete the materials refactor. The following steps are still pending:

- move the same pattern into section-level inelastic reductions where it is still mixed with law logic;

- let specialized constitutive integrators replace the currently embedded update rules when substepping or more elaborate algorithms are needed;
- introduce regularized damage / fracture models for continuum concrete so that cracking can be represented objectively with respect to the mesh.

31.10 Strategic Importance for Reinforced Concrete Across Scales

This propagation is small in terms of code size, but large in architectural value. Reinforced concrete across scales requires:

- uniaxial steel and concrete at the fiber level;
- section reductions for beams, columns, and shells;
- continuum models with explicit kinematics, inertia, and possibly damage or fracture;
- future transfer of reconstructed fields across scales.

Externalising the algorithmic state at the uniaxial level is the first place where these scales start to line up under the same constitutive-site abstraction. That is the real reason this step matters.

Chapter 32

Yield Function Customization and Constitutive Curve Visualisation

32.1 Why Introduce an Explicit Yield Function?

Up to this point the plasticity architecture already had three explicit compile-time axes:

- `YieldCriterion`: geometry of the admissible surface in stress space;
- `HardeningLaw`: evolution of the admissible radius or position;
- `FlowRule`: direction of irreversible strain increment.

That is already a good decomposition, but semantically one piece was still implicit: the scalar yield function value

$$f(\boldsymbol{\sigma}, \alpha)$$

that decides whether the trial state is admissible or not.

In the original implementation, that scalar was assembled directly inside `PlasticityRelation` as

$$f = q(\boldsymbol{\sigma}) - \sigma_y(\alpha).$$

This is mathematically standard, but architecturally it hides a real customization point.

32.2 Criterion vs Function

The distinction matters:

- a *yield criterion* describes the shape of the surface, for example von Mises or Drucker–Prager;
- a *yield function* is the scalar map that evaluates the current trial state against that surface and the evolving hardening state.

For classical associative plasticity they are closely related, but they are not identical concepts. The criterion gives the stress measure $q(\boldsymbol{\sigma})$ and its gradient; the yield function combines that measure with the hardening law into a scalar overstress.

32.3 New Compile-Time Contract

The new concept is `YieldFunctionPolicy<F, N, Y, H>`. It requires

```
f.value(yield, trial, hardening, state) -> double
```

where:

- `yield` is the `YieldCriterion`;
- `trial` is the effective trial state;
- `hardening` is the `HardeningLaw`;
- `state` is the hardening-law state.

The default implementation is `StandardYieldFunction`, which reproduces the previous behaviour exactly:

$$f = q(\texttt{trial}) - \sigma_y(\texttt{state}).$$

32.4 How `PlasticityRelation` Uses It

`PlasticityRelation` is now parameterised as

```
PlasticityRelation<Policy,
                   YieldCriterion,
                   HardeningLaw,
                   FlowRule,
                   YieldFunction>
```

with `YieldFunction = StandardYieldFunction` by default.

This means the architectural axes are now:

1. measure space / constitutive policy;
2. yield-surface geometry;
3. hardening evolution;
4. flow direction;
5. scalar yield-function evaluation.

32.5 Important Current Limitation

The current return-mapping algorithm is still the standard backward-Euler radial-return form. Therefore the new `YieldFunction` policy is architecturally explicit, but algorithmically it is still expected to remain compatible with the same correction structure.

In practice, this means the present implementation is best suited to yield functions that preserve the same derivative structure as the classical overstress map, for example shifted or scaled variants that do not change the underlying flow/tangent derivation qualitatively.

This is not a weakness of the concept itself; it is simply an honest statement about the current integrator. If later a different local algorithm is added, the `YieldFunction` axis is already explicit and can be reused.

32.6 Why This Separation Helps

The gain is mostly semantic today, but it matters for future work:

- classical $f = q - \sigma_y$;
- capped or shifted overstress maps;
- pressure-sensitive surfaces with the same hardening but different scalar evaluation;
- dynamic/viscoplastic extensions where the overstress enters a rate law.

Separating the scalar yield function early is cheap and removes one more implicit coupling from the plasticity kernel.

32.7 Constitutive Protocol Sampling

The new header `ConstitutiveProtocol.hh` introduces a tiny solver-free utility for material tests:

```
sample_constitutive_protocol(site, history,
                             abscissa_of, ordinate_of)
```

It applies a prescribed history of kinematic states and records:

- abscissa value, typically strain or generalized strain;
- ordinate value, typically stress or generalized force;
- path parameter (currently the step index);
- discrete step number.

The commit path is resolved at compile time:

- if the object exposes `commit(k)`, it is used;
- otherwise, if it exposes `update(k)`, that path is used.

This lets the same utility work for:

- raw constitutive relations with embedded state;
- typed constitutive sites `MaterialInstance<...>`;
- type-erased `Material<Policy>` handles.

32.8 Why the Protocol Is Strain-Driven

The present utility is displacement/strain-controlled on purpose. Local constitutive relations are naturally evaluated as

$$\boldsymbol{\varepsilon} \mapsto \boldsymbol{\sigma}.$$

Force-controlled material tests would require solving a local inverse problem at each step, which belongs to a different abstraction level. Nothing in the current design prevents that later; it is simply not mixed into the present utility.

32.9 VTK Representation of Material Curves

The first implementation exported constitutive protocols as geometric `vtkPolyData` polylines. That representation is valid, but it is not the most natural carrier when the intent is a two-dimensional chart. ParaView treats `vtkPolyData` as geometry, not as tabular series, so the user ends up looking at a line embedded in the xy-plane instead of a stress– strain plot.

The stabilized workflow now uses `vtkTable` as the primary carrier. Each constitutive series is written as an individual `.vtt` file, which ParaView can open directly in chart-oriented views. The geometric `.vtp` route is still available as an auxiliary export, but it is no longer the recommended path for material calibration or hysteresis inspection.

For each sample, the table stores:

- `strain` (or the chosen abscissa name);
- `stress` (or the chosen ordinate name);
- `step`;
- `path_parameter`.

The writer also generates a lightweight CSV manifest that records which series were exported and where their corresponding `.vtt` files live. This is helpful both for ParaView and for lightweight scripting or spreadsheet-based inspection.

Because a data object alone cannot force ParaView to leave the standard render view and switch into a chart view, the bundle now also emits a small companion Python script:

`material_hysteresis_curves_paraview_chart.py`

This script opens the generated `.vtt` files and constructs an `XYChartView` automatically. In practice, this is the closest thing to "open the file and see the constitutive curve immediately" that ParaView supports while still keeping the actual curve data in a proper tabular format.

32.10 Curves Generated by the New Test

The regression suite now writes:

- `material_hysteresis_curves_menegotto_cyclic.vtt`
- `material_hysteresis_curves_kent_park_cyclic.vtt`
- `material_hysteresis_curves_j2_backbone.vtt`
- `material_hysteresis_curves_manifest.csv`
- `material_hysteresis_curves_paraview_chart.py`

In ParaView, the intended workflow is now:

1. either open one of the `.vtt` files manually and place it in a *Line Chart View*,
2. or run `material_hysteresis_curves_paraview_chart.py` from ParaView's Python shell to create the chart view automatically;
3. use `strain` as the x-axis array and `stress` as the plotted series;
4. inspect `step` or `path_parameter` when loading, unloading, and reversals need to be highlighted.

This distinction is important. A `.vtp` file is a geometric object and therefore shows up naturally in the three-dimensional render view. A `.vtt` file is a table, so ParaView treats it as chart data. That is precisely why it is the correct primary format for constitutive loops.

The first two show true hysteretic behaviour:

- steel reversal with Menegotto–Pinto smooth transition and Bauschinger-type response;
- concrete compression/unloading/reloading with cracking and tension cut-off in Kent–Park.

The J2 block is kept as a backbone-style reference for the current local plasticity implementation.

32.11 What the New Tests Actually Verify

Two kinds of behaviour are now checked:

1. **Architectural composition**: a custom compile-time `YieldFunction` changes stress and tangent while the rest of the plasticity composition remains unchanged.
2. **Post-processing contract**: the VTK writer produces valid chart-ready `vtkTable` datasets with named columns that can be read back and inspected.

This is important because it validates not only mathematics, but also the intended user workflow for constitutive debugging and calibration.

32.12 Relevance for Reinforced Concrete

For reinforced concrete across scales, graphical constitutive inspection is not optional. The steel and concrete laws often look acceptable numerically while still behaving incorrectly under reversal, unloading, cracking, confinement, or stiffness recovery. The new protocol sampler and VTK curve writer give a direct way to inspect that behaviour from the same codebase that later runs the structural analysis.

This is especially useful when calibrating:

- reinforcement hysteresis;
- confined versus unconfined concrete;
- fiber-section assembly;
- future damage or fracture laws in continuum concrete.

32.13 Strategic Next Step

The next logical move is to reuse this protocol infrastructure for more general constitutive diagnostics:

- generalized force–deformation curves for beam and shell sections;
- cyclic protocols for section reductions and fiber sections;
- eventually, local traction–separation laws and continuum damage / fracture models.

That would extend the same workflow from uniaxial laws to reduced structural models and later to continuum inelasticity.

Chapter 33

Decoupling the Yield Function from the Return Algorithm

33.1 Motivation

Making the `YieldFunction` explicit was an important semantic step, but it did not yet remove the deepest coupling in the local plasticity kernel: `PlasticityRelation` still contained a hard-coded radial-return algorithm. That coupling is acceptable for classical small-strain J_2 plasticity, but it becomes a real architectural limitation as soon as the library needs to support:

- cutting-plane or closest-point schemes;
- viscoplastic overstress integration;
- substepping or adaptive local solves;
- pressure-sensitive surfaces with different local correction logic;
- damage-plasticity or capped plasticity where the local admissibility problem is no longer the same scalar radial-return update.

If the return algorithm stays embedded in the constitutive law, then every new local scheme forces a new constitutive class. That is exactly the kind of semantic drift that the previous chapters were trying to remove.

33.2 New Separation

The plasticity architecture now exposes six independent compile-time axes:

1. constitutive space / measure policy;
2. yield criterion;
3. hardening law;
4. flow rule;
5. yield function;
6. return algorithm.

The new policy lives in `ReturnAlgorithm.hh` under the concept `ReturnAlgorithmPolicy<A, Relation>`. The contract is intentionally narrow:

```
algorithm.integrate(relation, total_strain, alpha)
    -> Relation::ReturnMapResultT
```

This means the algorithm works on:

- a concrete constitutive relation that exposes a typed plasticity kernel;
- a total kinematic state;
- an explicit algorithmic state α.

33.3 What Remains Inside `PlasticityRelation`

`PlasticityRelation` is still the owner of the constitutive physics:

- elastic predictor;
- effective trial state for kinematic hardening;
- scalar yield-function evaluation;
- flow direction;
- hardening modulus;
- plastic internal-variable evolution;
- consistent tangent formula.

What moved out is the *algorithmic orchestration* of those pieces.

That is the right cut. The law keeps the constitutive mathematics; the return algorithm decides how the local admissibility problem is solved.

33.4 Kernel API for Algorithms

To avoid friend-based hacks or dynamic polymorphism, the relation now exposes a small public kernel API:

- `elastic_predictor(...)`
- `effective_trial(...)`
- `evaluate_yield_function(...)`
- `hardening_modulus(...)`
- `flow_direction(...)`
- `consistency_increment(...)`
- `corrected_stress(...)`
- `evolve_internal_variables(...)`
- `consistent_tangent(...)`
- `make_elastic_result(...)`

This interface is not intended as user-facing high-level API. It is an algorithm-support surface that allows compile-time return algorithms to be implemented outside the constitutive law without paying runtime dispatch.

33.5 Default Algorithm

The legacy behaviour is preserved by `StandardRadialReturnAlgorithm`. It implements the same backward-Euler radial-return correction that used to live inside `PlasticityRelation`. Therefore the existing J_2 path remains backward compatible.

The important architectural change is not a different numerical answer, but the fact that the local solve is no longer hard-wired to the law itself.

33.6 What the New Test Demonstrates

The regression suite adds a deliberately simple alternative algorithm: `HalfStepReturnAlgorithm`. It reuses the same constitutive kernel but applies only half of the classical correction increment. This is not a production algorithm; it is a proof of separation.

The test checks that:

- the custom algorithm satisfies `ReturnAlgorithmPolicy`;
- the stress response changes;
- the algorithmic tangent changes;
- the rest of the constitutive composition remains the same.

This is the right kind of regression: it proves that changing the local algorithm does not require redefining the yield criterion, hardening, flow, or yield function.

33.7 Why This Matters for Future Material Models

This split is strategically important for the material roadmap discussed in the material-module analysis chapter. Reinforced concrete across scales will eventually need models such as:

- concrete damage-plasticity;
- fracture-regularized softening;
- cyclic degradation with nested loading surfaces;
- rate effects and dynamic overstress;
- large-strain constitutive updates.

Those models are not only "different yield functions". They often require different *local integration algorithms*. By making that axis explicit now, the architecture stops conflating:

- the surface being checked;
- the scalar admissibility map;
- the nonlinear method used to restore admissibility.

33.8 Immediate Boundary

The current split is honest but still partial:

- the default tangent formula remains the standard small-strain rate-independent J_2 formula;
- the kernel methods exposed by `PlasticityRelation` still encode assumptions specific to that family;
- more general return algorithms may need richer kernel contracts or even different state objects.

That is acceptable. The present goal is not to solve every future material model today; it is to stop blocking them with a hard-coded radial return.

33.9 Recommended Next Step

The next correct move is to apply the same discipline to richer local models:

- introduce a non-associative or pressure-sensitive return algorithm;
- let the local algorithm request its own residual/Jacobian assembly if the scalar closed form is not available;
- eventually separate `ConstitutiveKernel` from `ConstitutiveIntegrator` for continuum damage/fracture models.

At that point the library will have a genuinely extensible foundation for developing nonlinear concrete models beyond classical metal plasticity.

Chapter 34

Continuum Module Cleanup and the Finite-Strain Constitutive Interface

34.1 Motivation

The continuum module already contained the essential tensor infrastructure for large displacements and finite strains:

- deformation and stress tensors in `Tensor2`, `SymmetricTensor2`, and `Tensor4`;
- kinematic formulations in `SmallStrain`, `TotalLagrangian`, and `UpdatedLagrangian`;
- hyperelastic models written directly in tensor form.

However, at the `ContinuumElement` /`Material<>` boundary, the contract was still essentially

`engineering Voigt strain` $\longrightarrow$ `stress/tangent`.

This was acceptable for infinitesimal strain and also acceptable as an adapter for Green–Lagrange hyperelasticity, but semantically it was still too narrow: the constitutive side could not explicitly see the deformation gradient $\mathbf{F}$, the active stress measure, or the distinction between infinitesimal and Green–Lagrange strain.

That is the exact point where future finite-strain plasticity, large displacement RC continuum models, and eventually crack/fracture models will need a cleaner interface.

34.2 Problem Statement

Before this refactor, the continuum path looked like:

`KinematicPolicy::evaluate()` $\Rightarrow$ `gp.strain_voigt` $\Rightarrow$ `StateVariableT` $\Rightarrow$ `MaterialPoint::compute_r`

This had three architectural drawbacks:

1. The element knew only a flat constitutive input, not the richer continuum kinematics from which it came.
2. Finite-strain relations were forced to masquerade as small-strain `Strain<N>` relations even when the real primitive was $\mathbf{F}$ or $\mathbf{E}$.
3. The interface did not clearly document which work-conjugate pair was active for each formulation.

34.3 New Carrier: `ConstitutiveKinematics`

To fix that semantic compression, the continuum module now provides `ConstitutiveKinematics<dim>`. It is a continuum-only carrier that contains:

- the active engineering strain vector used by the current formulation;
- the infinitesimal strain tensor;
- the Green–Lagrange strain tensor;
- the deformation gradient $\mathbf{F}$;
- $\det \mathbf{F}$;
- explicit measure tags: `StrainMeasureKind` and `StressMeasureKind`.

This carrier is not a replacement for `Strain<N>`. It is the continuum-side bridge that preserves the old interface as a fallback while opening a better path for finite kinematics.

34.4 Mapping from Kinematic Policies

The helper

```
make_constitutive_kinematics<KinematicPolicy>(gp)
```

maps the Gauss-point bundle returned by `KinematicPolicy::evaluate()` into the richer constitutive carrier.

Small strain

For `SmallStrain`, the carrier is interpreted as:

$$\boldsymbol{\varepsilon} = \nabla^s \mathbf{u}, \tag{34.1}$$

$$\mathbf{F} = \mathbf{I}, \tag{34.2}$$

$$\det \mathbf{F} = 1, \tag{34.3}$$

with active measure

$$\text{(infinitesimal strain, Cauchy stress)}.$$

Total Lagrangian

For `TotalLagrangian`, the carrier is interpreted as:

$$\mathbf{F} = \mathbf{I} + \nabla_0 \mathbf{u}, \tag{34.4}$$

$$\mathbf{E} = \frac{1}{2}(\mathbf{F}^T\mathbf{F} - \mathbf{I}), \tag{34.5}$$

with active measure

$$\text{(Green–Lagrange strain, 2nd Piola–Kirchhoff stress)}.$$

Updated Lagrangian

For `UpdatedLagrangian`, the constitutive carrier is now interpreted as:

$$\mathbf{e} = \frac{1}{2}\left(\mathbf{I} - \mathbf{b}^{-1}\right), \tag{34.6}$$

$$\mathbf{b} = \mathbf{F}\mathbf{F}^T, \tag{34.7}$$

with active measure

$$\text{(Almansi strain, Cauchy stress)}.$$

This is the spatial counterpart of the total-Lagrangian pair $(\mathbf{E}, \mathbf{S})$ and it is the natural route for current-configuration constitutive laws.

34.5 Optional Direct Continuum Interface

The constitutive side now has an optional refinement:

```
ContinuumKinematicsAwareConstitutiveRelation
```

If a constitutive relation implements

$$\texttt{compute_response(ConstitutiveKinematics<dim>)} \tag{34.8}$$

$$\texttt{tangent(ConstitutiveKinematics<dim>)} \tag{34.9}$$

then the erased `Material<>` handle will forward the richer carrier directly. Otherwise it falls back to the legacy conversion

$$\texttt{ConstitutiveKinematics} \rightarrow \texttt{StateVariableT}.$$

This keeps the existing code working while making the finite-strain interface available immediately.

34.6 Hyperelastic Relations

`HyperelasticRelation<Model>` now implements the direct continuum carrier overload. Internally it consumes the Green–Lagrange strain tensor stored in the carrier:

$$\mathbf{S} = \frac{\partial W}{\partial \mathbf{E}}, \qquad \mathbb{C} = \frac{\partial^2 W}{\partial \mathbf{E}^2}.$$

This change is architecturally important because it removes the need for a finite-strain law to pretend that its natural interface is only a Voigt vector. The old `Strain<N>` adapter is preserved, but it is no longer the only semantic entry point.

34.7 Changes in `ContinuumElement`

`ContinuumElement` now evaluates kinematics as before, but it no longer immediately collapses them into a flat constitutive input. The local assembly loop now does:

1. evaluate the Gauss-point kinematics through the selected `KinematicPolicy`;
2. build a `ConstitutiveKinematics<dim>` carrier;
3. ask the type-erased material point for stress and tangent through that carrier;

4. fall back automatically to `StateVariableT` if the constitutive law does not provide a richer overload.

This is the correct direction for large-displacement and finite-strain continuum modelling because the element is no longer hardwired to the idea that "constitutive input = one Voigt vector".

34.8 Compile-Time and Performance Considerations

The refactor was designed so that:

- the hot path inside a concrete constitutive law remains statically dispatched;
- the erased boundary still pays the same category of cost as before (virtual call through `Material<>`);
- legacy integrators that only know `KinematicT` remain valid;
- direct continuum overloads are purely additive.

In other words, the new interface broadens the semantic contract without forcing a runtime penalty inside the concrete law implementation.

34.9 Limitations After This Step

This cleanup does *not* mean the full finite-strain continuum stack is finished.

The main remaining limitations are:

- the spatial route is now explicit for continuum hyperelastic laws, but finite-strain inelastic spatial laws still need their own local-state and return-algorithm infrastructure;
- there is not yet an explicit continuum-specific `ConstitutiveState` split for finite-strain plasticity or damage;
- finite-strain internal-variable evolution still needs a more general residual/Jacobian-based local integration contract beyond the current small-strain J2-oriented path.

34.10 Tests Added

The new test suite verifies:

- correct construction of `ConstitutiveKinematics` from `SmallStrain` and `TotalLagrangian`;
- direct continuum-carrier consistency for `SVKRelation<3>` and `NeoHookeanRelation<3>`;
- correct propagation of the new interface through the erased `Material<ThreeDimensionalMaterial>` handle.

34.11 Architectural Outcome

This step completes an important semantic cleanup of the continuum module:

> kinematics, constitutive driving variables, and constitutive law entry points are no longer implicitly collapsed into the same object.

That is a necessary precondition for the next stages:

- finite-strain plasticity with explicit internal state;
- large-displacement RC continuum models;
- damage/plasticity couplings;
- crack-band or other regularised fracture models for continuum RC.

Chapter 35

Spatial Updated-Lagrangian Constitutive Interface

35.1 Motivation

Chapter 34 introduced a continuum-side carrier that exposed $\mathbf{F}$, $\det \mathbf{F}$ and explicit strain/stress measure tags at the erased `Material<>` boundary. The next missing step was to let the `UpdatedLagrangian` formulation use a genuinely spatial pair instead of silently reusing the reference pair $(\mathbf{E}, \mathbf{S})$.

For many future models that is not optional. Current-configuration constitutive laws are the natural setting for:

- large-displacement plasticity written in terms of Cauchy or Kirchhoff stress;
- rate-based models and objective stress rates;
- contact, FSI and other couplings that consume spatial tractions and current normals directly.

35.2 Reference and Spatial Conjugate Pairs

For the total-Lagrangian formulation the standard conjugate pair is

$$(\mathbf{E}, \mathbf{S}),$$

where

$$\mathbf{F} = \mathbf{I} + \nabla_0 \mathbf{u}, \tag{35.1}$$

$$\mathbf{E} = \frac{1}{2}\left(\mathbf{F}^T\mathbf{F} - \mathbf{I}\right). \tag{35.2}$$

For the updated-Lagrangian formulation the natural spatial pair is

$$(\mathbf{e}, \boldsymbol{\sigma}),$$

where $\mathbf{e}$ is the Almansi strain,

$$\mathbf{b} = \mathbf{F}\mathbf{F}^T, \tag{35.3}$$

$$\mathbf{e} = \frac{1}{2}\left(\mathbf{I} - \mathbf{b}^{-1}\right), \tag{35.4}$$

and $\boldsymbol{\sigma}$ is the Cauchy stress.

The two pairs are linked through Piola transformations:

$$\boldsymbol{\sigma} = \frac{1}{J}\mathbf{F}\mathbf{S}\mathbf{F}^T, \tag{35.5}$$

$$\mathbf{S} = J\mathbf{F}^{-1}\boldsymbol{\sigma}\mathbf{F}^{-T}, \tag{35.6}$$

with $J = \det \mathbf{F}$.

35.3 Why the Spatial Carrier Matters

The previous implementation already contained the mathematics needed to build the spatial path, but the erased constitutive interface still compressed the interaction into "some Voigt strain" leading to two semantic problems:

1. the constitutive law could not tell whether the incoming stress measure was meant to be $\mathbf{S}$ or $\boldsymbol{\sigma}$;
2. the updated-Lagrangian element path still assembled with a reference-style carrier at the element/material interface.

This refactor resolves that ambiguity by making the active pair explicit at compile time in the kinematic policy and explicit at runtime in the continuum carrier tags.

35.4 Updated-Lagrangian Carrier

The continuum carrier now stores all of the following simultaneously:

- engineering Voigt form of the active strain measure;
- infinitesimal strain;
- Green–Lagrange strain;
- Almansi strain;
- deformation gradient $\mathbf{F}$ and $J = \det \mathbf{F}$;
- the active strain and stress measure tags.

For `UpdatedLagrangian`, the active tags are

`StrainMeasureKind::almansi`, `StressMeasureKind::cauchy`.

This means that a constitutive relation receiving the carrier can decide at the entry point whether it should produce:

- the reference response $\mathbf{S}$ and $\mathbb{C}$, or
- the spatial response $\boldsymbol{\sigma}$ and $\rfloor$.

35.5 Push-Forward of the Constitutive Tangent

If a hyperelastic model is naturally written in terms of $\mathbf{S} = \partial W/\partial \mathbf{E}$ and $\mathbb{C} = \partial^2 W/\partial \mathbf{E}^2$, then the spatial tangent used by the updated-Lagrangian assembly is the push-forward of $\mathbb{C}$:

$$\rfloor_{ijkl} = \frac{1}{J} F_{iI} F_{jJ}\, \mathbb{C}_{IJKL}\, F_{kK} F_{lL}.$$

In the present implementation that transformation is handled at the relation level for direct continuum-aware laws such as `HyperelasticRelation`. The same direct overload that previously returned $\mathbf{S}$ now returns $\boldsymbol{\sigma}$ when the carrier announces a Cauchy-conjugate path.

35.6 Element-Level Updated-Lagrangian Assembly

The updated-Lagrangian element route now uses:

$$\nabla_x N_I = \nabla_X N_I \mathbf{F}^{-1}, \tag{35.7}$$

$$\mathbf{b}(\nabla_x N) = \text{spatial small-strain } B\text{-operator}, \tag{35.8}$$

$$\delta W_{\text{int}} = \int_{\Omega_n} \boldsymbol{\sigma} : \delta \mathbf{d} \, \mathrm{d}v. \tag{35.9}$$

Because the implementation still integrates over the reference quadrature domain attached to the original geometry, the conversion

$$\mathrm{d}v = J \, \mathrm{d}V$$

is applied explicitly inside `ContinuumElement`. This is the reason the element path now multiplies the updated-Lagrangian contributions by $J = \det \mathbf{F}$.

At the discrete level, the internal force and tangent take the form

$$\mathbf{f}_{\text{int}} = \int_{\Omega_0} J \, \mathbf{b}^T \tilde{\boldsymbol{\sigma}} \, \mathrm{d}V, \tag{35.10}$$

$$\mathbf{K}_{\text{mat}} = \int_{\Omega_0} J \, \mathbf{b}^T \tilde{\rfloor} \, \mathbf{b} \, \mathrm{d}V, \tag{35.11}$$

$$\mathbf{K}_{\sigma} = \int_{\Omega_0} J \, \mathbf{k}_{\sigma}(\nabla_x N, \boldsymbol{\sigma}) \, \mathrm{d}V. \tag{35.12}$$

35.7 Architectural Consequences

This step is important because it removes the last semantic shortcut in the continuum large-displacement path:

> `UpdatedLagrangian` is no longer "TL in disguise" at the generic element/material boundary for hyperelastic continuum laws.

The resulting architecture has three useful properties:

1. **Static specialization is preserved.** The kinematic policy still selects the path at compile time.
2. **The erased material interface remains additive.** Old laws keep working through the legacy `KinematicT` fallback.
3. **Spatial finite-strain laws now have a natural slot.** Future Cauchy-based plasticity or rate-based models can consume the same carrier without pretending to be reference-measure laws.

35.8 Tests Added

The new regression coverage verifies:

- the updated-Lagrangian carrier exposes Almansi strain and Cauchy stress tags correctly;
- `HyperelasticRelation` returns the push-forwarded Cauchy stress and spatial tangent when the carrier requests the spatial path;
- the erased `Material<ThreeDimensionalMaterial>` handle forwards that spatial path without losing the richer semantics;
- `UpdatedLagrangian::evaluate_from_gradients()` now returns the spatial B operator and the Almansi engineering strain.

35.9 Remaining Limits

The spatial route is now available for continuum hyperelasticity, but it is not yet the full finite-strain inelastic infrastructure. The next steps remain:

- a finite-strain `ConstitutiveState` split for continuum plasticity and damage;
- local residual/Jacobian contracts for nonlinear constitutive updates in the spatial setting;
- objective-rate or multiplicative-decomposition models when the library moves beyond hyperelastic and small-strain-inelastic ingredients.

35.10 References

Bibliography

[1] J. Bonet, A. J. Gil, and R. D. Wood, *Nonlinear Solid Mechanics for Finite Element Analysis: Statics*, 2nd ed., Cambridge University Press, 2008.

[2] T. Belytschko, W. K. Liu, B. Moran, and K. Elkhodary, *Nonlinear Finite Elements for Continua and Structures*, 2nd ed., Wiley, 2014.

[3] J. C. Simo and T. J. R. Hughes, *Computational Inelasticity*, Springer, 1998.

Chapter 36

Local Consistency Residual and Jacobian as Independent Customization Points

36.1 Motivation

The previous material refactors had already separated:

- the *yield function* from the yield-surface geometry;
- the *return algorithm* from the constitutive ingredients;
- the *constitutive state* from the low-level storage backend.

However, one coupling still remained inside the local plastic solve: the algorithm knew too much about the specific scalar equation being solved. In the classical radial-return setting this is easy to hide because one often writes a closed-form update for the plastic multiplier increment $\Delta\gamma$. That shortcut does not scale well to future models.

In particular, the next generations of models needed by this library:

- pressure-sensitive plasticity,
- nonlinear hardening laws,
- finite-strain multiplicative plasticity,
- damage-plasticity and crack-regularised constitutive updates,

all tend to be expressed as local nonlinear residual/Jacobian problems rather than as one hard-coded formula for $\Delta\gamma$.

36.2 Classical Local Plasticity Problem

In the present small-strain rate-independent setting, the constitutive update is still organised around the elastic predictor and the plastic corrector:

$$\boldsymbol{\sigma}^{\mathrm{tr}} = \mathbb{C}_e : (\boldsymbol{\varepsilon}_{n+1} - \boldsymbol{\varepsilon}_n^p)\,, \tag{36.1}$$

$$f^{\mathrm{tr}} = q(\boldsymbol{\sigma}^{\mathrm{tr}}) - \sigma_y(\alpha_n). \tag{36.2}$$

If $f^{\mathrm{tr}} \leq 0$, the step is elastic. Otherwise the constitutive site must solve a local nonlinear problem for the plastic correction. In the simplest radial-return case this can be written as a scalar consistency equation

$$r(\Delta\gamma) = 0.$$

The important architectural observation is that this scalar equation is not the same concept as the nonlinear algorithm used to solve it.

36.3 Architectural Split

The implementation now distinguishes four independent compile-time roles:

1. **Yield criterion**: geometry of the admissible surface.
2. **Yield function**: scalar overstress map.
3. **Consistency residual / Jacobian**: definition of the local nonlinear equation and its derivative.
4. **Return algorithm**: the nonlinear solve strategy itself.

This leads to the following staging:

`YieldCriterion` → `YieldFunction` → `ConsistencyResidual/Jacobian` → `ReturnAlgorithm`.

That separation is more than naming hygiene. It is exactly the pattern needed when the library later moves from scalar J2 updates to local residual/Jacobian systems in finite strains.

36.4 Default Residual

The new default residual evaluates the corrected state semantically rather than re-deriving the current closed-form denominator by hand. It computes:

1. corrected stress $\boldsymbol{\sigma}(\Delta\gamma)$;
2. evolved internal variables $\alpha(\Delta\gamma)$;
3. corrected trial state reconstructed from $\boldsymbol{\sigma}(\Delta\gamma)$;
4. effective state after optional backstress shift;
5. residual
$$r(\Delta\gamma) = f(\boldsymbol{\sigma}(\Delta\gamma), \alpha(\Delta\gamma))\,.$$

This is slower than a hand-derived one-line formula, but it is the right default seam because it keeps the residual faithful to the constitutive model rather than to one particular radial-return algebra.

36.5 Default Jacobians

Two Jacobian paths are now available.

Closed-form Jacobian

The fast default for the present associated J2 family remains a closed-form derivative:

$$r'(\Delta\gamma) = -\sqrt{\frac{2}{3}}\,(3G + H)\,,$$

evaluated through the current constitutive kernel.

Finite-difference Jacobian

A generic numerical derivative is also available:

$$r'(\Delta\gamma) \approx \frac{r(\Delta\gamma + h) - r(\Delta\gamma - h)}{2h}.$$

This is not the preferred production path for hot local loops, but it is important for development:

- it provides a correctness baseline;
- it lets a new material model become usable before its exact local Jacobian has been derived;
- it mirrors the type of prototyping stage often needed for complex finite-strain or damage models.

36.6 Newton Consistency Algorithm

With residual and Jacobian split out, the library now provides a generic Newton solver for the scalar consistency problem:

$$r(\Delta\gamma_k) = 0, \tag{36.3}$$

$$\Delta\gamma_{k+1} = \Delta\gamma_k - \frac{r(\Delta\gamma_k)}{r'(\Delta\gamma_k)}. \tag{36.4}$$

The initial guess reuses the current closed-form estimate of the J2 radial return. This is intentional:

- for the present model family it gives a high-quality starting point;
- for future model families it still keeps the Newton solver as a clean, reusable algorithmic shell.

36.7 Why This Matters for Finite Strains

Finite-strain plasticity is rarely implemented as a direct analogue of the small-strain radial return. Even when the unknown remains scalar, the local problem is usually expressed in terms of a residual/Jacobian pair attached to:

- multiplicative splits,
- Kirchhoff or Mandel stresses,
- logarithmic or objective rates,
- internal tensorial variables.

From that perspective, the present refactor is strategically important:

> the code now has an explicit place where the local nonlinear constitutive equation lives, and that place is independent from the nonlinear solver.

That is the exact abstraction needed to grow from the current small-strain J2 path into finite-strain plasticity and eventually damage/fracture regularized models.

36.8 Verification

The regression suite now checks three things:

- a Newton-based local solve reproduces the current standard radial return for the existing J2 family;
- the same Newton algorithm remains usable when the Jacobian is replaced by a finite-difference policy;
- changing only the consistency residual changes the final constitutive response, proving that the residual is now a real customization point.

36.9 Architectural Outcome

After this step, the local constitutive update is no longer just:

$$\texttt{YieldFunction} + \texttt{ReturnAlgorithm}.$$

It is now:

$$\texttt{YieldFunction} + \texttt{ConsistencyResidual} + \texttt{ConsistencyJacobian} + \texttt{ReturnAlgorithm}.$$

That is a much better foundation for the next stages:

- finite-strain plasticity with explicit continuum state;
- local residual/Jacobian systems of dimension larger than one;
- pressure-sensitive and damage-coupled return algorithms;
- fracture-oriented local solvers and regularization interfaces.

36.10 References

Bibliography

[1] J. C. Simo and T. J. R. Hughes, *Computational Inelasticity*, Springer, 1998.

[2] E. A. de Souza Neto, D. Perić, and D. R. J. Owen, *Computational Methods for Plasticity: Theory and Applications*, Wiley, 2008.

[3] M. A. Crisfield, *Non-Linear Finite Element Analysis of Solids and Structures, Vol. 2: Advanced Topics*, Wiley, 1997.

Chapter 37

A Generic Local Nonlinear Problem Framework for Constitutive Updates

37.1 Motivation

The previous refactor split the classical small-strain plastic update into three compile-time axes:

- the yield function,
- the consistency residual and its Jacobian,
- the return algorithm.

That split is already useful, but it still leaves one structural assumption in place: the local nonlinear problem is scalar. In the current J_2 path the unknown is only the plastic-multiplier increment $\Delta\gamma$, and the local solve is

$$r(\Delta\gamma) = 0.$$

This is too narrow for the next generation of constitutive models that the library aims to support:

- finite-strain plasticity based on multiplicative decomposition,
- coupled damage-plasticity,
- pressure-sensitive plasticity with additional local variables,
- local fracture regularization variables,
- rate-dependent or mixed local constitutive updates.

In those models the local unknown is generally a vector

$$\mathbf{x} \in \mathbb{R}^m,$$

and the constitutive update is written as a local nonlinear system

$$\mathbf{R}(\mathbf{x}) = \mathbf{0},$$

with a consistent local Jacobian

$$\mathbf{K}(\mathbf{x}) = \frac{\partial \mathbf{R}}{\partial \mathbf{x}}.$$

The right architectural move is therefore to promote the *local nonlinear problem itself* to a first-class compile-time abstraction.

37.2 Architectural Split

This phase introduces three layers.

37.2.1 Local Problem Contract

The new header `src/materials/local_problem/LocalNonlinearProblem.hh` defines a generic concept:

- `UnknownT`: the local unknown type,
- `ResidualT`: the local residual type,
- `JacobianT`: the local Jacobian type,
- `initial_guess(relation, context)`,
- `residual(relation, context, x)`,
- `jacobian(relation, context, x)`,
- `residual_norm(r)`.

The design intentionally keeps the `context` type open. For the current small-strain plasticity path it stores the trial state, the algorithmic state, the flow direction, and the trial overstress. For future finite-strain models the same slot can carry

$$\mathbf{F}_{n+1}, \quad \mathbf{C}_{n+1}, \quad \mathbf{b}_{n+1}, \quad \Delta t, \quad \alpha_n,$$

or any other local constitutive data required by the update.

37.2.2 Generic Newton Solver

The header `src/materials/local_problem/NewtonLocalSolver.hh` implements a reusable Newton iteration:

$$\mathbf{K}(\mathbf{x}^{(i)})\,\Delta\mathbf{x}^{(i)} = -\mathbf{R}(\mathbf{x}^{(i)}),$$
$$\mathbf{x}^{(i+1)} = \mathbf{x}^{(i)} + \Delta\mathbf{x}^{(i)}.$$

The implementation is generic over the local unknown type:

- if the unknown is scalar, the update reduces to $-R/K$,
- if the unknown is a fixed-size Eigen vector, the update is solved as a small dense linear system.

This matters for HPC-oriented design because the type of the local unknown remains fixed at compile time, and the solver does not introduce virtual dispatch into the constitutive hot path.

37.2.3 Scalar Consistency as an Adapter

The header `src/materials/constitutive_models/non_lineal/plasticity/ScalarConsistencyProblem.h` turns the current scalar consistency update into a `LocalNonlinearProblem`.

Thus, the current plasticity route is reinterpreted as the special case

$$x = \Delta\gamma, \qquad R(x) = r(\Delta\gamma), \qquad K(x) = \frac{\mathrm{d}r}{\mathrm{d}\Delta\gamma}.$$

This is the important architectural result: the present implementation remains valid, but it now lives inside a more general framework that no longer assumes scalar local updates.

37.3 Return Mapping as a Specialization of the General Framework

The new `LocalNonlinearReturnAlgorithm<LocalProblem, LocalSolver>` in `src/materials/constitutive` acts as the generic bridge between:

- a constitutive relation that can build a local update context,
- a local problem definition,
- a local nonlinear solver.

The old user-facing `NewtonConsistencyReturnAlgorithm<Residual, Jacobian, MaxIterations>` is kept as a compatibility wrapper. Internally, it now instantiates

`ScalarConsistencyProblem<Residual, Jacobian>`

and

`NewtonLocalSolver<MaxIterations>`.

This gives two immediate benefits:

- backward compatibility for the existing small-strain J_2 path,
- a direct path to future vector-valued local problems.

37.4 Why This Matters for Large Displacements and Finite Strains

Finite-strain inelastic constitutive updates are typically not expressible as a single scalar consistency correction. In multiplicative elastoplasticity, for example, one often solves for combinations of:

- a plastic multiplier increment,
- an updated plastic metric or elastic left Cauchy–Green tensor,
- hardening variables,
- damage or fracture-driving variables.

The local problem then takes the block form

$$\mathbf{R}(\mathbf{x}) = \begin{bmatrix} R_1(\mathbf{x}) \\ R_2(\mathbf{x}) \\ \vdots \\ R_m(\mathbf{x}) \end{bmatrix} = \mathbf{0},$$

with a block Jacobian

$$\mathbf{K}(\mathbf{x}) = \begin{bmatrix} \partial R_1/\partial x_1 & \cdots & \partial R_1/\partial x_m \\ \vdots & \ddots & \vdots \\ \partial R_m/\partial x_1 & \cdots & \partial R_m/\partial x_m \end{bmatrix}.$$

The current refactor does not yet implement a full finite-strain plastic law, but it removes a key architectural obstacle: the local constitutive solver no longer assumes that the unknown is scalar.

37.5 Verification

This phase adds two important regression checks:

- the generic `LocalNonlinearReturnAlgorithm<>` reproduces the current small-strain radial-return response and tangent;
- the generic Newton local solver converges on a fixed-size vector two-equation problem independent of plasticity.

The second test is intentionally simple. Its value is architectural: it proves that the new framework already supports vector local problems without any extra branching in the solver.

37.6 Strategic Outcome

At this point the local constitutive stack is factored as:

- `YieldFunction`: admissibility scalar,
- `ConsistencyResidual / Jacobian`: local equation ingredients,
- `ReturnAlgorithm`: correction strategy,
- `LocalNonlinearProblem`: abstract local system definition,
- `NewtonLocalSolver`: reusable nonlinear solver.

This is the right level of generality for the next stages:

- finite-strain elastoplasticity with vector local unknowns,
- damage-plasticity with coupled internal variables,
- fracture-oriented local updates regularized at constitutive level,
- objective-rate or multiplicative algorithms integrated through the same erased `Material<>` boundary.

37.7 References

Bibliography

[1] J. C. Simo and T. J. R. Hughes, *Computational Inelasticity*, Springer, 1998.

[2] E. A. de Souza Neto, D. Perić, and D. R. J. Owen, *Computational Methods for Plasticity: Theory and Applications*, Wiley, 2008.

[3] C. Miehe, "Numerical computation of algorithmic (consistent) tangent moduli in large-strain computational inelasticity," *Computer Methods in Applied Mechanics and Engineering*, 134(3–4):223–240, 1996.

Chapter 38

Splitting Newton into Linear-Solve and Step-Control Policies

38.1 Motivation

Once local constitutive updates are written as nonlinear problems

$$\mathbf{R}(\mathbf{x}) = \mathbf{0},$$

it is tempting to treat Newton as a single algorithmic block. That is still too coarse for an extensible constitutive framework.

In practice, a Newton-like local solve contains at least two secondary algorithmic choices:

- how the linearized correction

  $$\mathbf{K}(\mathbf{x}^{(i)})\Delta\mathbf{x}^{(i)} = -\mathbf{R}(\mathbf{x}^{(i)})$$

  is solved;
- how the candidate step $\Delta\mathbf{x}^{(i)}$ is accepted, damped, or line-searched.

Those are not merely implementation details. They are real extension points:

- scalar division versus dense LU versus custom direct solvers,
- full Newton versus fixed damping versus backtracking,
- future PETSc/KSP or PETSc/SNES-based local experiments.

Therefore, even when the outer algorithm is "Newton", the library should not hard-code its internal sub-policies.

38.2 Architectural Split

This phase introduces two new compile-time seams in `src/materials/local_problem`.

38.2.1 Local Linear Solve Policy

`LocalLinearSolver.hh` defines the policy

$$\Delta\mathbf{x} = \mathcal{L}(\mathbf{K}, \mathbf{R}),$$

through the concept `LocalLinearSolvePolicy`.

The default implementation is:

- scalar division for one-dimensional local problems,
- dense LU for fixed-size vector problems.

This is intentionally simple, but it places the dependency in the right place. If a future constitutive model wants a custom block elimination or a PETSc/KSP adapter, the change belongs to this policy layer, not to the constitutive law.

38.2.2 Local Step-Control Policy

`LocalStepControl.hh` defines the update acceptance layer:

$$\Delta \mathbf{x}_{\text{accepted}} = \mathcal{S}(\mathbf{x}, \Delta \mathbf{x}, \|\mathbf{R}\|).$$

Two policies are provided:

- `FullStepControl`, which accepts the full Newton correction;
- `BacktrackingResidualStepControl`, which searches for a reduced step that decreases the residual norm.

The key point is again architectural: line search is not fused into Newton, but appears as a compile-time policy.

38.3 Newton as an Assembler of Policies

After this change, `NewtonLocalSolver<MaxIterations, LinearSolvePolicy, StepControlPolicy>` is no longer a monolithic Newton implementation. It is a small orchestrator:

1. evaluate residual and Jacobian,
2. call the injected linear solve policy,
3. call the injected step-control policy,
4. update the local unknown.

This is a better match to the long-term goals of the library. It preserves static polymorphism in the hot loop while exposing each real algorithmic choice as a separately replaceable type.

38.4 Why This Matters for Continuum Inelasticity at Finite Strains

Finite-strain constitutive updates are often more fragile than the current small-strain J_2 scalar return:

- the local unknown may be vector-valued,
- the Jacobian may be poorly conditioned,
- unrestricted Newton steps may violate admissibility or internal constraints,
- different models may benefit from different line-search or trust-region strategies.

For that reason, treating Newton as an injectable outer policy but hard-coding its substeps would still be too rigid. The present split is what keeps the continuum route genuinely open.

38.5 PETSc Compatibility Path

The local-problem architecture is intentionally broad enough that a future PETSc-based local solver can fit without changing the constitutive law interface. A PETSc adapter would only need to satisfy the same generic solver contract:

- accept a local problem,
- evaluate residual/Jacobian through callbacks,
- return a solved local state `solution`.

Whether that adapter uses:

- a direct dense local solve,
- a PETSc `KSP`,
- or a PETSc `SNES` line-search method,

is then an algorithmic choice at the solver layer, not a change in `PlasticityRelation`, `Material<>`, or `ContinuumElement`.

38.6 Verification

The regression suite now checks:

- concept conformance for the linear-solve and step-control policies;
- convergence of the generic vector local problem under the default Newton sub-policies;
- convergence of the same local problem under a custom damped step control.

The last point is important. It proves that the Newton implementation is not architecturally special: it already works as a host for interchangeable sub-policies.

38.7 Strategic Outcome

The constitutive local-solver stack is now factored as:

- `LocalNonlinearProblem`: physics-level local system,
- `LocalLinearSolvePolicy`: linearized correction,
- `LocalStepControlPolicy`: step acceptance,
- `LocalNonlinearSolverPolicy`: outer nonlinear algorithm,
- `ReturnAlgorithm`: constitutive update driver.

This is the right level of openness for the next step:

- finite-strain local vector problems driven by `ConstitutiveKinematics`,
- damage/fracture-oriented local updates,
- alternative nonlinear solvers and PETSc-based experiments.

38.8 References

Bibliography

[1] J. C. Simo and T. J. R. Hughes, *Computational Inelasticity*, Springer, 1998.

[2] E. A. de Souza Neto, D. Perić, and D. R. J. Owen, *Computational Methods for Plasticity: Theory and Applications*, Wiley, 2008.

[3] C. T. Kelley, *Iterative Methods for Linear and Nonlinear Equations*, SIAM, 1995.

Chapter 39

Continuum Local Problems Driven by Constitutive Kinematics

39.1 Motivation

The previous phases opened two necessary extension points:

- the continuum constitutive carrier `ConstitutiveKinematics<dim>`, which makes the active kinematic and stress measures explicit;
- the generic local nonlinear-problem and nonlinear-solver framework, which no longer assumes a scalar consistency equation.

What was still missing was the bridge between those two abstractions.

For large-displacement and finite-strain constitutive models the local update is not naturally written in terms of a flat engineering strain vector alone. The local problem typically depends on a richer set of continuum data, for example

$$\mathbf{F}_{n+1}, \qquad J_{n+1} = \det \mathbf{F}_{n+1}, \qquad \mathbf{E}_{n+1}, \qquad \mathbf{e}_{n+1},$$

together with the committed internal variables α_n.

The right architectural move is therefore to define a continuum-local problem in terms of:

- a continuum kinematic context,
- an explicit committed algorithmic state,
- a vector local unknown
$$\mathbf{x} \in \mathbb{R}^m,$$
- a residual
$$\mathbf{R}(\mathbf{x}; \mathcal{K}_{n+1}, \alpha_n) = \mathbf{0},$$
- and a local Jacobian
$$\mathbf{K}_{\text{loc}} = \frac{\partial \mathbf{R}}{\partial \mathbf{x}}.$$

39.2 Context and Result Carriers

The new header `src/materials/local_problem/ContinuumLocalProblem.hh` adds two reusable semantic carriers.

39.2.1 Continuum Context

The generic context

```
continuum_local_problem::Context<Relation, TrialState, Auxiliary>
```

stores:

- the continuum carrier $\mathcal{K}_{n+1} =$ `ConstitutiveKinematics<dim>`,
- the committed internal state α_n,
- optional trial-state data,
- optional auxiliary data.

This keeps the infrastructure open at compile time. A future model may use the optional slots for quantities such as:

- trial Mandel stress,
- elastic left Cauchy–Green tensor,
- plastic metric variables,
- damage driving forces,
- local fracture regularization variables.

39.2.2 Continuum Update Result

The generic result carrier

```
continuum_local_problem::UpdateResult<Relation>
```

stores:

- the constitutive response,
- the algorithmic tangent,
- the updated algorithmic state,
- an `inelastic` flag.

That carrier is intentionally small. It is the minimal bridge needed between the local constitutive solve and the continuum element routine.

39.3 Continuum Local Problem Policy

The concept `ContinuumLocalProblemPolicy<Problem, Relation>` extends the generic `LocalNonlinearProbl` contract with continuum-specific semantics:

- the relation must satisfy `ExternallyStateDrivenContinuumRelation`;
- the local context must expose `kinematics` and `committed_state`;
- the problem must provide:
  - `make_context(relation, kin, alpha)`,

- `is_inelastic(relation, context)`,
- `elastic_result(relation, context)`,
- `finalize(relation, context, unknown)`.

This split is important. The nonlinear solver only knows how to solve

$$\mathbf{R}(\mathbf{x}) = \mathbf{0}.$$

The physics of:

- when the update is elastic,
- how the continuum context is assembled,
- how the solved unknown is mapped back to stress, tangent and algorithmic state,

belongs to the local problem itself.

39.4 Continuum Local Integration Algorithm

The new compile-time driver

```
ContinuumLocalIntegrationAlgorithm<LocalProblem, LocalSolver>
```

is the continuum-side analogue of the constitutive return-mapping wrappers introduced earlier.

Its logic is intentionally small:

1. build a context from the continuum kinematics and committed state;
2. check whether the update is elastic;
3. if not, solve the local problem with the injected solver;
4. reconstruct stress, tangent and updated state from the solved unknown.

This means the algorithmic seam remains open at compile time:

- `NewtonLocalSolver` is only one possible `LocalNonlinearSolverPolicy`;
- other solvers can be injected without modifying the local problem or the constitutive relation;
- the same continuum-local problem can be tested with different solver policies for robustness studies.

39.5 Why This Matters for Finite Strains

Finite-strain inelasticity is often written in terms of local unknowns that are vector-valued even when the global element kinematics are standard. Typical examples include:

- multiplicative plasticity with unknowns such as $\Delta\gamma$ and tensorial plastic-flow variables;
- damage-plasticity with
$$\mathbf{x} = [\Delta\gamma, d, \kappa]^T;$$
- local phase-field or gradient-enhanced constitutive updates with additional driving variables.

In those settings the local constitutive solve is naturally expressed as

$$\mathbf{R}(\mathbf{x}; \mathbf{F}_{n+1}, \mathbf{E}_{n+1}, \mathbf{e}_{n+1}, \alpha_n) = \mathbf{0},$$

not as a scalar consistency equation in one variable.

The present refactor does not yet implement a full finite-strain plastic or damage law. What it does is remove the last architectural assumption that would have blocked such laws: the local constitutive framework is no longer structurally tied to scalar updates or to a flattened strain-only context.

39.6 Verification Strategy

The regression added in `tests/test_continuum_local_problem.cpp` uses a deliberately simple finite-strain-ready toy relation:

- the relation satisfies `ExternallyStateDrivenContinuumRelation`;
- the local problem uses a two-component unknown vector;
- the context is built from `ConstitutiveKinematics<3>`;
- the same problem is solved with:
  - `NewtonLocalSolver`,
  - a one-shot direct solver injected as a different local solver policy.

This test is intentionally architectural rather than physical. Its purpose is to prove three things:

1. the continuum carrier is sufficient as the input to a vector local constitutive problem;
2. the nonlinear solver is genuinely injected and replaceable;
3. the local-problem framework already supports the shape needed by future finite-strain inelastic models.

39.7 Strategic Outcome

At this point the constitutive architecture provides independent compile-time customization for:

- constitutive law ingredients,
- local residual and Jacobian definitions,
- local nonlinear solver,
- linearized local solve,
- local step control,
- continuum kinematic context,
- continuum-local reconstruction of
$$(\boldsymbol{\sigma}, \mathbf{c}, \alpha_{n+1}).$$

This is the right base for the next stage:

- finite-strain plasticity with multiplicative decomposition,

- pressure-sensitive and damage-plasticity models,
- local fracture or crack-driving internal variables at constitutive level,
- eventual PETSc-backed local constitutive experiments without changing the relation or element interfaces.

39.8 References

Bibliography

[1] J. C. Simo and T. J. R. Hughes, *Computational Inelasticity*, Springer, 1998.

[2] E. A. de Souza Neto, D. Perić, and D. R. J. Owen, *Computational Methods for Plasticity: Theory and Applications*, Wiley, 2008.

[3] J. Bonet, A. J. Gil, and R. D. Wood, *Nonlinear Solid Mechanics for Finite Element Analysis: Statics*, 2nd ed., Cambridge University Press, 2008.

[4] C. Miehe, "Numerical computation of algorithmic (consistent) tangent moduli in large-strain computational inelasticity," *Computer Methods in Applied Mechanics and Engineering*, 134(3–4):223–240, 1996.

Chapter 40

Integrating Continuum Local Problems at the Material Boundary

40.1 Motivation

Chapter 39 introduced a generic local nonlinear problem driven by `ConstitutiveKinematics<dim>`. That was the necessary abstraction step, but it was not yet sufficient for real use in the library. A constitutive framework is only operational when the local problem can be consumed through the same public boundary used by elements and material sites:

- `Material<Policy>`,
- `MaterialPoint<Policy>`,
- and, later, section-level constitutive sites built on the same handle.

The present phase performs that actual integration. The new `ContinuumLocalProblemIntegrator<LocalPr LocalSolver>` is a constitutive-integrator policy injected at the `Material<>` boundary. This keeps the public constitutive API stable while opening a finite-strain path that is still fully customizable at compile time.

40.2 Architectural Position

After this step, the continuum constitutive stack is:

1. a constitutive relation
$$\mathcal{R},$$
2. an explicit algorithmic state
$$\alpha_n,$$
3. an injected local problem
$$\mathbf{R}(\mathbf{x}; \mathcal{K}_{n+1}, \alpha_n) = \mathbf{0},$$
4. an injected local nonlinear solver,
5. an injected constitutive integrator at the erased `Material<>` boundary.

In code, that last point matters. `Material<>` remains the uniform polymorphic handle seen by the rest of the library, but it is no longer tied to:

- direct constitutive evaluation only,

- embedded return-mapping only,
- or small-strain kinematic carriers only.

The continuum-local path is therefore not a parallel API. It is a first-class integration path through the existing constitutive boundary.

40.3 Prediction and Commit Semantics

This integration step also fixes an important semantic point.

For a rate-independent local constitutive update, evaluating the local problem at a given kinematic state should generally be side-effect free:

$$\sigma_{n+1}^{\mathrm{alg}} = \mathcal{G}(\mathcal{K}_{n+1}, \alpha_n),$$

where $\mathcal{G}$ denotes the local constitutive solve.

That means:

- `compute_response(kin)` predicts the algorithmic response,
- `tangent(kin)` predicts the associated algorithmic tangent,
- `commit(kin)` persists the updated internal state and updates the site kinematic state.

This is a better contract than using `compute_response()` as a hidden mutation step. The distinction is especially important for:

- repeated tangent evaluations inside a global Newton iteration,
- material-curve drivers,
- rollback/restart logic,
- future PETSc-based local solvers,
- and transfer to scale-reconstruction workflows.

In other words, the local constitutive solve is *algorithmic*, but its state persistence is still explicit.

40.4 Mathematical Role of the Boundary Integrator

Given:

- a continuum carrier $\mathcal{K}_{n+1}$,
- a committed algorithmic state α_n,
- a local problem with unknown $\mathbf{x}$,

the boundary integrator performs:

1. build the local context
$$\mathcal{C}_{n+1} = \mathcal{C}(\mathcal{K}_{n+1}, \alpha_n),$$
2. solve the local nonlinear system
$$\mathbf{R}(\mathbf{x}; \mathcal{C}_{n+1}) = \mathbf{0},$$

3. reconstruct the constitutive result

$$(\sigma_{n+1}, \mathbb{C}^{\text{alg}}_{n+1}, \alpha_{n+1}) = \mathcal{F}(\mathbf{x}, \mathcal{C}_{n+1}),$$

4. on commit, store α_{n+1} and the corresponding kinematic state.

The essential architectural point is that none of those steps are hard-coded inside `Material<>`. The erased handle delegates them to the injected integrator, which itself delegates to the injected local problem and local solver.

40.5 Compile-Time Extension Points Preserved

The new path remains open at compile time in every important direction:

- **Local problem**: different finite-strain models may define their own context, unknown vector, residual and reconstruction logic.
- **Local solver**: Newton is only one `LocalNonlinearSolverPolicy`; it can be replaced by damped, quasi-Newton, line-search or PETSc-backed solvers.
- **Constitutive integrator**: `Material<>` only depends on the integrator contract, not on the particular local-problem type.
- **Constitutive site**: the same integration path is available through `MaterialPoint<>`, which is the actual consumer at continuum Gauss points.

This keeps the direction aligned with the long-term goals:

- finite-strain plasticity,
- damage-plasticity,
- fracture-oriented local updates,
- and multiscale transfer from structural to continuum models.

40.6 Verification

The regression in `tests/test_continuum_local_problem.cpp` now checks the complete path:

- direct use of `ContinuumLocalIntegrationAlgorithm<LocalProblem, Solver>`,
- integration through `Material<ThreeDimensionalMaterial>`,
- integration through `MaterialPoint<ThreeDimensionalMaterial>`.

The material-handle test is intentionally semantic:

- prediction is verified to be side-effect free,
- commit is verified to persist the site kinematics,
- the committed response is checked against a reference constitutive site with the same explicit algorithmic state.

This is the right contract for the next step. The infrastructure is no longer limited to an isolated continuum-local helper; it now participates in the real constitutive boundary used by the rest of the codebase.

40.7 References

Bibliography

[1] J. C. Simo and T. J. R. Hughes, *Computational Inelasticity*, Springer, 1998.

[2] J. Bonet and R. D. Wood, *Nonlinear Continuum Mechanics for Finite Element Analysis*, 2nd ed., Cambridge University Press, 2008.

[3] E. A. de Souza Neto, D. Perić, and D. R. J. Owen, *Computational Methods for Plasticity: Theory and Applications*, Wiley, 2008.

Chapter 41

First Real Finite-Strain Inelastic Continuum Law

41.1 Motivation

Chapter 40 completed the mechanical integration of the continuum-local infrastructure at the real `Material<>` boundary, but only through a synthetic regression law. That was enough to validate the architecture, not enough to validate the continuum inelastic route itself.

The next stable step is therefore to plug that infrastructure into an actual finite-strain inelastic constitutive law. The goal of this chapter is modest and deliberate:

- introduce a first real continuum inelastic model;
- keep all nonlinear-solver pieces injectable at compile time;
- preserve the existing small-strain and hyperelastic interfaces;
- expose a physically meaningful internal variable through snapshots and VTK export.

The chosen model is an isotropic scalar damage law built on top of a hyperelastic backbone. It is not the final concrete model of the library, but it is a correct and useful first continuum inelastic law because it already needs:

- finite-strain kinematics,
- an external algorithmic state,
- a local update problem,
- solver injection,
- post-processing of an inelastic internal variable.

41.2 Constitutive Structure

Let $\mathbf{E}$ denote the Green–Lagrange strain, and let the undamaged hyperelastic free energy be

$$\psi_0 = \psi_0(\mathbf{E}).$$

The damaged stored energy is taken as

$$\psi(\mathbf{E}, d) = g(d)\, \psi_0(\mathbf{E}),$$

where $d \in [0,1]$ is a scalar damage variable and $g(d)$ is a degradation function. In the present implementation,

$$g(d) = k_{\text{res}} + (1 - k_{\text{res}})(1 - d)^2,$$

with a small residual stiffness $k_{\text{res}} > 0$ to avoid a completely singular material tangent.

The second Piola–Kirchhoff stress is then

$$\mathbf{S} = g(d)\,\mathbf{S}_0(\mathbf{E}),$$

with $\mathbf{S}_0 = \partial\psi_0/\partial\mathbf{E}$. Likewise, in this first stable version the algorithmic tangent is taken as the degraded undamaged tangent:

$$\mathbb{C} \approx g(d)\,\mathbb{C}_0.$$

This is a secant-like algorithmic choice rather than a fully consistent linearization of the damage evolution law. That limitation is explicit and acceptable for the first stable integration step.

41.3 Driving Variable and History Variable

The damage-driving quantity is chosen as the norm of the positive spectral part of $\mathbf{E}$:

$$Y(\mathbf{E}) = \|\langle \mathbf{E} \rangle_+\|\,,$$

where $\langle \cdot \rangle_+$ retains only positive principal strains.

This choice prevents compressive strains from driving damage in the present model, which is a reasonable first approximation for tensile-dominated damage. The history variable is

$$\kappa_{n+1} = \max(\kappa_n, Y_{n+1}),$$

and the scalar damage is updated as

$$d(\kappa) = \begin{cases} 0, & \kappa \le \kappa_0, \\ 1 - \exp\left(-\dfrac{\kappa - \kappa_0}{\kappa_f}\right), & \kappa > \kappa_0. \end{cases}$$

The constitutive state used by the relation is therefore

$$\alpha = \{\kappa, d\}.$$

41.4 Local Constitutive Problem

The update is expressed as a local nonlinear problem through the generic continuum-local framework developed in Chapter 39. For the present rate-independent isotropic damage law the local residual is particularly simple:

$$R(\kappa) = \kappa - \max(\kappa_n, Y_{n+1}).$$

Its Jacobian is

$$\frac{\partial R}{\partial \kappa} = 1.$$

This scalar problem is intentionally simple, but architecturally important: the constitutive law is now expressed through the same local-problem route that later finite-strain plasticity, damage-plasticity, nonlocal damage, or capped models will use. The nonlinear algorithm itself is not hard-coded inside the law.

41.5 Compile-Time Extension Points

The new relation is open at compile time along the same axes established in the previous chapters:

- **hyperelastic backbone**: any `HyperelasticModelConcept` may be used;
- **damage-driving force**: the law accepts a compile-time `DrivingForceT`;
- **damage evolution**: the scalar softening law is injected as `DamageEvolutionT`;
- **local problem**: the local update is not hard-coded into the relation, but expressed through `damage::RateIndependentDamageLocalProblem`;
- **nonlinear algorithm**: Newton is only one admissible local solver; the tests also inject a direct exact solver to verify that the solver is genuinely interchangeable.

This is precisely the architectural property needed later for research work: the constitutive kernel does not depend on a specific Newton implementation, and the local-problem contract is broad enough to host other algorithms, including PETSc-based local solvers.

41.6 Reference and Spatial Paths

Because the law is continuum-aware, the same relation accepts both:

- a reference path using $(\mathbf{E}, \mathbf{S})$;
- a spatial path using $(\mathbf{e}, \boldsymbol{\sigma})$.

Given the degraded reference stress

$$\mathbf{S} = g(d)\,\mathbf{S}_0(\mathbf{E}),$$

the spatial Cauchy stress is obtained by the standard push-forward

$$\boldsymbol{\sigma} = \frac{1}{J}\mathbf{F}\mathbf{S}\mathbf{F}^T.$$

The same logic is used for the spatial tangent, which is obtained by push-forward of the undamaged material tangent and then degraded by $g(d)$.

41.7 Integration at the Material Boundary

The stable boundary now works as follows:

1. `ContinuumElement` builds a `ConstitutiveKinematics<dim>` carrier.
2. `Material<>` forwards that carrier to an injected `ContinuumLocalProblemIntegrator`.
3. The integrator solves the local damage problem using an injected local solver.
4. The resulting state is committed only through `Material::commit(...)`; predictive evaluation remains side-effect free.
5. `InternalFieldSnapshot` exports the scalar damage variable for post-processing, and `VTKModelExporter` now emits: `qp_damage` and `nodal_damage`.

41.8 Tests Added

The new regression file verifies:

- damage remains inactive below the threshold and the relation reduces to the undamaged hyperelastic backbone;
- damage grows under tension and does not heal upon unloading;
- the spatial updated-Lagrangian path returns the degraded Cauchy stress and degraded pushed-forward tangent;
- the same local problem can be solved with Newton or with an exact custom solver injected at compile time;
- the relation integrates correctly through `Material<ThreeDimensionalMaterial>` and through `MaterialPoint<ThreeDimensionalMaterial>`;
- the internal-field snapshot now exposes the scalar damage variable.

41.9 What This Enables Next

This chapter does not yet solve finite-strain concrete damage or fracture in their final research form. What it does is remove another architectural barrier:

> The continuum inelastic path now has a real finite-strain law with external state, local solver injection, spatial/reference duality, and exportable internal variables.

That makes the next steps much more concrete:

- finite-strain plasticity with vector-valued local unknowns;
- coupled damage-plasticity for concrete;
- crack-band or nonlocal regularisation of scalar damage;
- fracture-oriented continuum models built on the same local-problem contract.

41.10 References

Bibliography

[1] J. C. Simo and J. W. Ju, *Strain- and stress-based continuum damage models. I. Formulation*, International Journal of Solids and Structures, 23(7), 821–840, 1987.

[2] C. Miehe, *Discontinuous and continuous damage evolution in Ogden-type large-strain elastic materials*, European Journal of Mechanics A/Solids, 14(4), 697–720, 1995.

[3] J. C. Simo and T. J. R. Hughes, *Computational Inelasticity*, Springer, 1998.

[4] J. Bonet, A. J. Gil, and R. D. Wood, *Nonlinear Solid Mechanics for Finite Element Analysis: Statics*, 2nd ed., Cambridge University Press, 2008.

[5] E. A. de Souza Neto, D. Perić, and D. R. J. Owen, *Computational Methods for Plasticity: Theory and Applications*, Wiley, 2008.

Chapter 42

Stabilising the Finite-Strain Damage Route

42.1 Motivation

Chapter 41 introduced the first real finite-strain inelastic continuum law in the library, but intentionally in its most conservative form: a scalar local problem and a degraded secant tangent. That was the right first cut to validate the architecture, but it still left two weaknesses:

- the local problem was too special, and therefore did not exercise the vector-valued local-problem framework that future continuum damage-plasticity and fracture-oriented laws will need;
- the tangent was only secant-like, so active loading did not expose a consistent linearisation of the damage update.

This chapter documents the stabilised version of that route. The objective is not to over-specialise the model, but to keep the implementation open to compile-time extension while removing the most obvious provisional pieces.

42.2 State and Local Unknown

The algorithmic state remains

$$\alpha = \{\kappa, d\},$$

where κ is the history variable and d is the scalar damage variable.

The stabilised local problem no longer solves only for κ. Instead, it solves for the vector

$$\mathbf{x} = \begin{bmatrix} \kappa \\ d \end{bmatrix}.$$

This is a small change mathematically, but a large one architecturally: the finite-strain damage law now follows the same fixed-size vector local problem interface that future coupled constitutive models will need.

42.3 Vector Local Problem

For the present rate-independent isotropic law,

$$\kappa_{n+1} = \max(\kappa_n, Y_{n+1}), \qquad d_{n+1} = D(\kappa_{n+1}).$$

The local problem is written as

$$\mathbf{R}(\mathbf{x}) = \begin{bmatrix} R_1(\kappa, d) \\ R_2(\kappa, d) \end{bmatrix} = \begin{bmatrix} \kappa - \max(\kappa_n, Y_{n+1}) \\ d - D(\kappa) \end{bmatrix} = \mathbf{0}.$$

Its Jacobian is

$$\mathbf{K} = \frac{\partial \mathbf{R}}{\partial \mathbf{x}} = \begin{bmatrix} 1 & 0 \\ -D'(\kappa) & 1 \end{bmatrix}.$$

In the current model this system is triangular, so Newton still converges in a trivial manner. However, that is no longer the architectural point. The important point is that the constitutive infrastructure now sees a *vector-valued local problem* rather than a special scalar shortcut.

42.4 Consistent Tangent During Active Damage Loading

The constitutive law is

$$\mathbf{S}(\mathbf{E}, d) = g(d)\, \mathbf{S}_0(\mathbf{E}),$$

with $\mathbf{S}_0 = \partial\psi_0/\partial\mathbf{E}$ and $g(d)$ the scalar degradation function.

When the loading is active, i.e. when the updated state satisfies

$$\kappa_{n+1} = Y_{n+1},$$

the algorithmic tangent is no longer purely secant. Differentiating

$$\mathbf{S} = g(d(\kappa(\mathbf{E})))\, \mathbf{S}_0(\mathbf{E}),$$

gives

$$\mathbb{C}_{\text{alg}} = g(d)\, \mathbb{C}_0 + \mathbf{S}_0 \otimes \frac{\partial g}{\partial \mathbf{E}}.$$

Using the chain rule,

$$\frac{\partial g}{\partial \mathbf{E}} = \frac{\partial g}{\partial d} \frac{\partial d}{\partial \kappa} \frac{\partial \kappa}{\partial Y} \frac{\partial Y}{\partial \mathbf{E}}.$$

For the present rate-independent model, during active loading $\partial\kappa/\partial Y = 1$, so

$$\frac{\partial g}{\partial \mathbf{E}} = g'(d)\, D'(\kappa)\, \frac{\partial Y}{\partial \mathbf{E}}.$$

During unloading or below threshold, the history variable is frozen and the additional term vanishes. The tangent then reduces again to the degraded secant form

$$\mathbb{C}_{\text{alg}} = g(d)\, \mathbb{C}_0.$$

42.5 Driving-Force Gradient

The current driving variable is the norm of the positive spectral part of the Green–Lagrange strain,

$$Y(\mathbf{E}) = \|\langle \mathbf{E} \rangle_+\|.$$

Let

$$\mathbf{E}_+ = \sum_a \langle \lambda_a \rangle_+\, \mathbf{n}_a \otimes \mathbf{n}_a,$$

where λ_a and $\mathbf{n}_a$ are the principal strains and principal directions of $\mathbf{E}$. For $Y > 0$,

$$\frac{\partial Y}{\partial \mathbf{E}} = \frac{\mathbf{E}_+}{\|\mathbf{E}_+\|}.$$

That is the derivative now implemented in `PositiveGreenLagrangeEquivalentStrain`. In code, the derivative is exposed with respect to the engineering-Voigt strain vector used by the element formulation, which keeps the constitutive tangent directly compatible with the existing assembly path.

42.6 Compile-Time Extension Points

The stabilised implementation preserves the library's compile-time openness:

- **Driving force policy**: any policy satisfying `DamageDrivingForcePolicy` may still drive the law.
- **Differentiable driving force**: if a policy additionally exposes `gradient(...)` or `gradient_wrt_engine` the law can build a more consistent tangent. If not, it falls back cleanly.
- **Damage evolution policy**: any `DamageEvolutionPolicy` remains admissible.
- **Differentiable evolution**: if the policy exposes `damage_derivative(...)` and `degradation_derivati` the rank-one correction is activated during loading. Otherwise the law degrades to the secant tangent without breaking the interface.
- **Local solver**: Newton is still only one admissible local algorithm. The tests continue to inject an exact direct solver to verify that the local-problem interface remains solver-agnostic.

This is the key architectural point: the law does not become less general by becoming more consistent. It becomes more faithful *when the injected policies provide the required derivatives*, and remains conservative otherwise.

42.7 Verification Performed

The regression suite now verifies:

- the vector local problem produces the same state, response, and tangent under both Newton and an injected exact solver;
- active loading produces an algorithmic tangent that matches finite differences of the fully integrated constitutive response;
- unloading reduces to the degraded secant tangent, as expected from a frozen history variable;
- the spatial updated-Lagrangian path remains correct for stress and tangent under unloading, where the secant form is exact for the present model.

42.8 What Remains Open

Even after this stabilisation, the route is intentionally not closed:

- the model remains local and scalar;
- no crack-band or nonlocal regularisation is introduced yet;
- the spatial tangent is still obtained through push-forward of the reference tangent, which is acceptable for the present path but not yet the final word for general finite-strain inelasticity;
- coupled finite-strain plasticity-damage still requires a higher-rank local state and a genuinely vector-valued constitutive residual.

That said, the current route is now stable enough to be a credible base layer for those next developments.

42.9 References

Bibliography

[1] J. C. Simo and J. W. Ju, *Strain- and stress-based continuum damage models. I. Formulation*, International Journal of Solids and Structures, 23(7), 821–840, 1987.

[2] C. Miehe, *Discontinuous and continuous damage evolution in Ogden-type large-strain elastic materials*, European Journal of Mechanics A/Solids, 14(4), 697–720, 1995.

[3] J. C. Simo and T. J. R. Hughes, *Computational Inelasticity*, Springer, 1998.

[4] J. Bonet, R. D. Wood, and A. J. Gil, *Nonlinear Solid Mechanics for Finite Element Analysis: Statics*, 2nd ed., Cambridge University Press, 2008.

[5] E. A. de Souza Neto, D. Perić, and D. R. J. Owen, *Computational Methods for Plasticity: Theory and Applications*, Wiley, 2008.

Chapter 43

Convergence Master Plan: Closing the Design-Implementation Gap

Chapters 26–43 describe a sophisticated constitutive and kinematic framework—yield functions, return-mapping, state objects, local solvers, Updated Lagrangian kinematics, damage models. However, the actual running code (`Model`, `Analysis`, `ContinuumElement`) does not yet implement most of these designs. This chapter proposes a strict, sequential plan to close that gap, organised in phases that respect dependency order.

43.1 Risk Assessment

1. **Design-Implementation Gap** (*critical*). 18 chapters of constitutive design (ch26–ch43) remain conceptual; only the first few are reflected in compiled tests.
2. **PETSc Resource Leaks** (*high*). Manually matched `Create`/`Destroy` calls across multiple classes; any early-return or exception loses the handle.
3. **Single Element Type Container** (*high*). `Model` stores `std::vector<ElemT>`, precluding mixed continuum + frame assemblages needed for RC.
4. **No Material State Commit/Revert Protocol** (*high*). Required by every implicit nonlinear solver for trial steps.
5. **No Geometric Stiffness Term** (*medium*). Tangent is purely material; large-displacement stability (P–Δ) cannot be captured.
6. **No Time-Integration Infrastructure** (*medium*). Newmark / HHT / Generalized-α and mass assembly are needed for the seismic target.
7. **MPI Scalability** (*low, but architectural*). Local-only vectors and sequential assembly will not scale beyond single-node runs.

43.2 Phase 0 — PETSc RAII and Error Discipline

Goal: Eliminate resource leaks and surface PETSc errors as C++ exceptions. This is a prerequisite for every subsequent phase, because correct cleanup under early-return or exception is impossible with manual `Destroy` calls.

- Introduce move-only RAII wrappers: `OwnedVec`, `OwnedMat`, `OwnedKSP`, `OwnedSNES`, `OwnedTS`, `OwnedSection`.

- Provide a macro `FALL_N_PETSC_CHECK(expr)` that throws on nonzero error codes (debug mode).
- Refactor `Model`, `LinearAnalysis`, `NonlinearAnalysis`, `DynamicAnalysis` to use the wrappers; replace every manual destructor with `= default`.

Details and implementation are documented in Chapter 44.

43.3 Phase 1 — Constitutive State Protocol

Goal: Every material model must expose a three-operation protocol enabling trial evaluation, commit, and revert of internal state:

1. `compute_response(ε)` — evaluate stress and tangent at a trial strain, storing the result in a *tentative* state buffer.
2. `commit_state()` — promote the tentative state to "converged" (called after Newton convergence).
3. `revert_state()` — discard the tentative state and restore the last converged state (called on step failure or bisection).

This protocol is already designed in Chapters 28–31. Phase 1 wires it through `ContinuumElement` so that `NonlinearAnalysis` and `DynamicAnalysis` can call `commit()` / `revert()` at the solver level.

43.4 Phase 2 — Element Contract and Heterogeneous Containers

Goal: Replace the single `std::vector<ElemT>` in `Model` with a type-erased container that can hold continuum, frame, and shell elements simultaneously.

- Define a **C++20 concept** `FiniteElement` with required operations: `inject_K(Mat)`, `inject_f(Vec)`, `extract_element_dofs(Vec)`, `commit_state()`, `revert_state()`.
- Implement a type-erased wrapper (virtual dispatch or `std::any` with visitor) so that `Model` stores `std::vector<std::unique_ptr<ElementBase>>` or an equivalent `AnyElement` value type.
- Update `Model::setup()` to register elements from multiple `PhysicalGroups`, each with its own element type.

43.5 Phase 3 — Newton–Raphson Protocol in Model

Goal: Make `NonlinearAnalysis` a proper Newton solver with convergence control.

- `Model::assemble_residual(Vec u_local, Vec R_global)` — assemble $\mathbf{R} = \mathbf{f}_{\text{int}} - \mathbf{f}_{\text{ext}}$.
- `Model::assemble_tangent(Vec u_local, Mat K_t)` — assemble the consistent tangent stiffness.
- These two operations form the callback pair for PETSc SNES.
- Convergence norms, line-search, bisection, and arc-length strategies are configured at the `Analysis` level.

Vertical Slice Gate

After Phase 3, a complete vertical slice must pass:

> *A 2D plane-stress patch test with J_2 plasticity must converge under Newton–Raphson with commit/revert, using the RAII wrappers, and produce correct load-displacement output.*

Until this gate passes, Phases 4–6 are not started.

43.6 Phase 4 — Finite-Strain Kinematics

Goal: Implement the Updated Lagrangian (UL) framework designed in Chapters 36–38.

- Compute the deformation gradient $\mathbf{F} = \mathbf{I} + \nabla \mathbf{u}$ at each integration point from the element shape function gradients.
- Evaluate the spatial tangent modulus via the constitutive interface (Chapter 35).
- Assemble the geometric stiffness contribution K_σ alongside the material tangent K_m:

$$K_t = K_m + K_\sigma, \qquad (K_\sigma)_{IiJj} = \delta_{ij} \int_{\Omega_n} \sigma_{kl} \frac{\partial N_I}{\partial x_k} \frac{\partial N_J}{\partial x_l} \, dv.$$

- Update element volumes and shape function gradients after each converged step (reference configuration update).

43.7 Phase 5 — Dynamic and Seismic Infrastructure

Goal: Provide time-integration algorithms and seismic loading facilities.

- Assemble a consistent or lumped mass matrix $\mathbf{M}$.
- Implement Rayleigh damping $\mathbf{C} = \alpha \, \mathbf{M} + \beta \, \mathbf{K}_0$.
- Integrate using PETSc TS with Generalized-α (`TSALPHA2`) for second-order systems:

$$\mathbf{M} \, \ddot{\mathbf{u}} + \mathbf{C} \, \dot{\mathbf{u}} + \mathbf{f}_{\text{int}}(\mathbf{u}) = \mathbf{f}_{\text{ext}}(t).$$

- Support ground-motion input via influence vectors $\mathbf{M} \, \hat{\mathbf{g}}$.

Note: The `DynamicAnalysis` class already implements much of this infrastructure. Phase 5 integrates it with Phases 1–4 (material state protocol, heterogeneous elements, finite-strain tangent).

43.8 Phase 6 — MPI Scalability

Goal: Remove single-process bottlenecks.

- Replace local vector assembly with PETSc's `DMLocalToGlobal` / `DMGlobalToLocal` scatter patterns (already partially in place).
- Ensure element-level operations are partition-local; use ghost cells for overlap regions via `DMPlexDistribute`.
- Profile with `-log_view` and verify weak scaling up to $O(10^3)$ cores.

43.9 Summary and Dependency Graph

Phase	Name	Depends on	Risk addressed
0	RAII + Error Discipline	—	Resource leaks
1	Constitutive State Protocol	0	No commit/revert
2	Element Contract	0	Single element type
3	NR Protocol in Model	1, 2	Incomplete NR
	Vertical Slice Gate	3	Design-impl gap
4	Finite-Strain Kinematics	3	No geometric stiffness
5	Dynamic / Seismic	4	No time integration
6	MPI Scalability	5	Single-node only

Chapter 44

Phase 0: PETSc RAII and Error Discipline

This chapter documents the implementation of Phase 0 from the master plan (Chapter 43): wrapping every PETSc handle in a move-only RAII class and replacing manual `Destroy` calls throughout the codebase.

44.1 Motivation

PETSc objects (`Vec`, `Mat`, `KSP`, `SNES`, `TS`, `PetscSection`) follow a C-style `Create/Destroy` lifecycle. The existing code managed these with explicit destructor logic:

```
~Model() {
    if (Kt_)           MatDestroy(&Kt_);
    if (nodal_forces_) VecDestroy(&nodal_forces_);
    // ... 10+ more lines
}
```

This approach has three problems:

1. **Leak on early return.** If a method calls `VecCreate` then exits before reaching the destructor (thrown exception, early `return`, failed assertion), the handle is leaked.
2. **Error in cleanup.** Forgetting to add a new member to the destructor is an easy mistake as classes grow.
3. **Unchecked errors.** PETSc routines return `PetscErrorCode`, but the codebase silently discarded it. A failed allocation or invalid argument went unnoticed until a mysterious crash later.

44.2 Design: Thin Wrappers with Implicit Conversion

Each wrapper follows the same pattern. We illustrate with `OwnedVec`; the others (`OwnedMat`, `OwnedKSP`, etc.) are identical up to the handle type and the corresponding `Destroy` function.

44.2.1 Invariants

- **Move-only.** Copy construction and copy assignment are deleted. Move transfers ownership and nullifies the source.

- **Implicit conversion.** `operator Vec() const` returns the raw handle, so the wrapper can be passed directly to any PETSc function that takes a `Vec` by value.
- **Pointer-to-member.** `ptr()` returns `Vec*`, for use with PETSc creation functions that take an output pointer (`VecCreate(..., &v)`).
- **Boolean test.** `explicit operator bool()` returns `true` iff the handle is non-null (guards conditional creation).
- **Destructor calls `Destroy`.** If the handle is non-null, the destructor calls the corresponding PETSc destroy function. This is the entire point of RAII.

44.2.2 Interface (abridged)

```
namespace petsc {

class OwnedVec {
    Vec v_{nullptr};
public:
    OwnedVec() = default;
    explicit OwnedVec(Vec v) : v_{v} {}

    ~OwnedVec() { if (v_) VecDestroy(&v_); }

    OwnedVec(OwnedVec&& o) noexcept : v_{o.v_} { o.v_ = nullptr; }
    OwnedVec& operator=(OwnedVec&& o) noexcept {
        if (this != &o) { reset(); v_ = o.v_; o.v_ = nullptr; }
        return *this;
    }

    OwnedVec(const OwnedVec&)            = delete;
    OwnedVec& operator=(const OwnedVec&) = delete;

    operator Vec() const { return v_; }
    Vec  get()     const { return v_; }
    Vec* ptr()           { reset(); return &v_; }

    explicit operator bool() const { return v_ != nullptr; }

    Vec release() { Vec t = v_; v_ = nullptr; return t; }

    void reset() {
        if (v_) { VecDestroy(&v_); v_ = nullptr; }
    }
};

} // namespace petsc
```

Key design choice: `ptr()` resets before returning. This ensures that calling `DMCreateGlobalVector(dm, v.ptr())` does *not* leak a previously held handle. The pattern mirrors `std::unique_ptr::reset()` before `release()`.

44.2.3 Full Wrapper Set

Wrapper	PETSc type	Destroy function
OwnedVec	Vec	VecDestroy
OwnedMat	Mat	MatDestroy
OwnedKSP	KSP	KSPDestroy
OwnedSNES	SNES	SNESDestroy
OwnedTS	TS	TSDestroy
OwnedSection	PetscSection	PetscSectionDestroy

All are located in `src/petsc/` and collected by the convenience header `src/petsc/PetscRaii.hh`.

44.3 Error Checking Macro

A single macro wraps every PETSc call:

```
#define FALL_N_PETSC_CHECK(expr)                                    \
    do {                                                             \
        PetscErrorCode ierr_ = (expr);                               \
        if (ierr_) throw petsc::PetscError(__FILE__, __LINE__,       \
                                           #expr, ierr_);            \
    } while (0)
```

The exception type `petsc::PetscError` stores file, line, the stringified expression, and the error code. In release mode the macro compiles to a no-op unless `FALL_N_PETSC_CHECK_RELEASE` is defined.

Defined in `src/petsc/check.hh`.

44.4 Refactored Classes

44.4.1 Model

Before:

```
Mat Kt_{nullptr};
Vec nodal_forces_{nullptr};
Vec current_state_{nullptr};
Vec imposed_solution_{nullptr};
PetscSection dof_section{nullptr};

~Model() {
    if (Kt_)              MatDestroy(&Kt_);
    if (nodal_forces_)    VecDestroy(&nodal_forces_);
    if (current_state_)   VecDestroy(&current_state_);
    if (imposed_solution_) VecDestroy(&imposed_solution_);
    /* ... 4 more lines ... */
}
```

After:

```
petsc::OwnedMat     Kt_{};
petsc::OwnedVec     nodal_forces_{};
petsc::OwnedVec     current_state_{};
```

```
petsc::OwnedVec     imposed_solution_{};
petsc::OwnedSection dof_section_{};

~Model() = default;
```

All creation calls were changed from `DMCreateLocalVector(dm, &v)` to `FALL_N_PETSC_CHECK(DMCreateLoc v.ptr())`.

Public accessors return the raw handle via implicit conversion: `return current_state_.get();` (or simply `return current_state_;`).

44.4.2 LinearAnalysis

Raw `KSP`, `Mat`, and `Vec` members replaced with `OwnedKSP`, `OwnedMat`, `OwnedVec`. Manual destructor removed.

44.4.3 NonlinearAnalysis

Raw `SNES`, `Mat`, and `Vec` members replaced. Local temporaries (`f_full`, `U_snap`) in the bisection algorithm are now `OwnedVec` instances whose lifetime is scope-bounded—no explicit `VecDestroy` needed.

44.4.4 DynamicAnalysis

Raw `TS`, `Mat` (M_, C_, J_, K0_), and `Vec` (U_, V_, F_work_, f_ext_work_) replaced. The `GroundMotionInfo` struct's `influence` field changed from raw `Vec` to `petsc::OwnedVec`. The 15-line manual destructor collapses to `= default`.

Static callbacks. The PETSc TS callbacks (`I2Function`, `I2Jacobian`, `Monitor`) access owned members via `self->M_`, which works transparently thanks to the implicit `operator Mat()` conversion—the PETSc C API receives the raw handle by value.

44.5 File Layout

```
src/
├── petsc/
│   ├── check.hh ........................ FALL_N_PETSC_CHECK macro + PetscError
│   ├── OwnedVec.hh
│   ├── OwnedMat.hh
│   ├── OwnedKSP.hh
│   ├── OwnedSNES.hh
│   ├── OwnedTS.hh
│   ├── OwnedSection.hh
│   └── PetscRaii.hh ........................................ convenience include-all
├── model/
│   └── Model.hh ............................................................ refactored
└── analysis/
    ├── LinearAnalysis.hh ................................................... refactored
    ├── NLAnalysis.hh ....................................................... refactored
    └── DynamicAnalysis.hh .................................................. refactored
```

44.6 Validation Criteria

Phase 0 is considered complete when:

1. The project compiles with no warnings related to PETSc handles.
2. No class contains a manual `Destroy` call for owned PETSc objects.
3. Every PETSc creation/query call that can fail is wrapped in `FALL_N_PETSC_CHECK`.
4. Existing tests (`fall_n_tests`, `fall_n_continuum_test`, `fall_n_dynamic_test`, etc.) pass without regressions.
5. LeakSanitizer reports no new PETSc-related leaks (existing suppressions in `lsan.supp` remain valid).

Chapter 45

Phase 1: Constitutive State Protocol

This chapter documents Phase 1 of the master plan (Chapter 43). The original scope called for introducing a trial/committed state protocol through the full constitutive chain. A deep audit of the codebase revealed that this protocol *already exists* across every architectural layer, from storage policy up to the SNES solver boundary. This chapter records the audit, maps the complete commit chain with its mathematical foundations, and identifies the minor gaps that remain for future phases.

45.1 Phase 1 Scope Revision

Chapter 43 defined four Phase 1 deliverables:

1. Define a C++20 concept `ConstitutivePolicy` requiring `commit`, `compute_response`, `tangent`.
2. Refactor `MaterialPoint` so every quadrature site stores committed *and* trial state.
3. Adapt elastic constitutive policies to satisfy the concept.
4. Implement one inelastic model with `commit`/`revert` (Von Mises J_2 plasticity).

After a thorough audit of `src/materials/`, `src/elements/`, and `src/analysis/`, all four deliverables were found to be **already implemented**:

#	Deliverable	Status
1	Constitutive concept hierarchy	`ConstitutiveRelation` + `ConstitutiveIntegratorConcept`
2	Trial/committed state at each site	`TrialCommittedState<S>` + `ConstitutiveState<...>`
3	Elastic adaptation	`PassThroughIntegrator` + `ElasticRelation`
4	Inelastic model with commit	`PlasticityRelation` + `EmbeddedRelationIntegrator`

Consequently, Phase 1 was re-scoped to: (a) comprehensive audit and documentation of the existing protocol, (b) verification that the commit chain is complete from analysis to storage, and (c) identification of gaps for future phases (notably the absence of an explicit `revert` at the type-erased boundary).

45.2 Mathematical Framework

45.2.1 Trial/Committed State Protocol

The incremental solution of a nonlinear boundary-value problem by Newton–Raphson requires a clear distinction between *converged* (committed) and *tentative* (trial) states at each constitutive

site. Denoting by n the load step and by k the Newton iteration:

- **Committed state $\boldsymbol{\alpha}_n$**: the internal variable set at the end of step n, after global convergence has been verified. This is the *reference* state for step $n+1$.
- **Trial state $\boldsymbol{\alpha}_{n+1}^{(k)}$**: the tentative internal variables computed during iteration k of step $n+1$. This state must *never* overwrite the committed state until the global solver converges.

The protocol at each constitutive site is:

1. **Evaluate** (side-effect free): Given the trial strain $\boldsymbol{\varepsilon}_{n+1}^{(k)}$ and committed internal variables $\boldsymbol{\alpha}_n$, compute the stress response and algorithmic tangent:

$$\boldsymbol{\sigma}_{n+1}^{(k)} = \hat{\boldsymbol{\sigma}}\left(\boldsymbol{\varepsilon}_{n+1}^{(k)}, \boldsymbol{\alpha}_n\right), \tag{45.1}$$

$$\mathbb{C}_{n+1}^{(k)} = \left.\frac{\partial \hat{\boldsymbol{\sigma}}}{\partial \boldsymbol{\varepsilon}}\right|_{\boldsymbol{\varepsilon}_{n+1}^{(k)}, \boldsymbol{\alpha}_n}. \tag{45.2}$$

   These evaluations do *not* modify the internal state.

2. **Commit** (after global convergence): Promote trial state to committed:

$$\boldsymbol{\alpha}_{n+1} \leftarrow \hat{\boldsymbol{\alpha}}\left(\boldsymbol{\varepsilon}_{n+1}^{(\mathrm{conv})}, \boldsymbol{\alpha}_n\right).$$

3. **Revert** (on solver divergence): Discard all trial computations; internal state remains at $\boldsymbol{\alpha}_n$. In the current SNES-driven architecture, revert is implicit: if Newton does not converge, `commit()` is simply never called.

45.2.2 Constitutive Tangent in the Newton System

The global Newton update at iteration k solves

$$\underbrace{\mathbf{K}_t^{(k)}}_{\text{tangent stiffness}} \delta\mathbf{u}^{(k)} = -\underbrace{\left(\mathbf{f}_{\text{int}}^{(k)} - \mathbf{f}_{\text{ext}}\right)}_{\text{residual}}, \tag{45.3}$$

where

$$(\mathbf{K}_t)_{IJ} = \int_\Omega \mathbf{B}_I^T\, \mathbb{C}_{n+1}^{(k)}\, \mathbf{B}_J\, d\Omega + \underbrace{\int_\Omega \nabla N_I \cdot \boldsymbol{\sigma}_{n+1}^{(k)} \cdot \nabla N_J\, d\Omega}_{\text{geometric stiffness } K_\sigma}$$

The geometric stiffness K_σ is assembled only under `TotalLagrangian` and `UpdatedLagrangian` kinematic policies. For `SmallStrain`, $K_\sigma = 0$.

The critical requirement is that both $\boldsymbol{\sigma}(\boldsymbol{\varepsilon})$ and $\mathbb{C}(\boldsymbol{\varepsilon})$ are evaluated as **pure functions** of the trial kinematics and committed internal state. This guarantees that Newton iterations are reproducible and that a diverged step leaves no corrupted state.

45.3 The Complete Commit Chain

The constitutive state protocol is implemented across six architectural layers. This section traces the commit path from solver to storage.

45.3.1 Layer 1: Storage Policy

File: `src/materials/MaterialStatePolicy.hh`

The storage policy controls how state values are persisted:

`ElasticState<S>` Single value, no history. `commit_trial()` is not available (constrained away by SFINAE).

`TrialCommittedState<S>` Stores two copies: `committed_` and `trial_`. Provides:

- `commit_trial()` — copies trial to committed, clears the trial flag.
- `revert_trial()` — clears the trial value, restores the committed state.
- `committed_value()` / `trial_value()` — accessors.
- `has_trial_value()` — boolean flag.

This is the storage policy used by all path-dependent constitutive models.

45.3.2 Layer 2: Constitutive State

Files: `src/materials/MaterialState.hh`, `src/materials/ConstitutiveState.hh`

`ConstitutiveState<StoragePolicy, StateVariableTypes...>` adds semantic meaning above the raw storage. It conditionally exposes `commit_trial()` and `revert_trial()` only when the underlying storage policy supports them (via C++20 `requires` expressions). This is the single point where the trial/committed protocol is semantically anchored.

45.3.3 Layer 3: Constitutive Integrator

File: `src/materials/ConstitutiveIntegrator.hh`

Three integrator strategies inject the algorithmic policy at the `Material<>` boundary:

`PassThroughIntegrator` Elastic path. `compute_response()` and `tangent()` delegate directly to the constitutive relation. `commit()` is an intentional no-op.

`EmbeddedRelationIntegrator` Inelastic path (compatibility bridge). Delegates `compute_response()` and `tangent()` to the relation (which may use an external algorithmic state). On `commit()`, calls:

1. `relation.update(`ε`)` or `relation.commit(`$\boldsymbol{\alpha}$`, `ε`)` — updates internal variables.
2. `site.constitutive_state().commit_trial()` — promotes trial to committed.

`ContinuumLocalProblemIntegrator` Advanced continuum path for finite-strain local problems. Uses a `ContinuumLocalIntegrationAlgorithm` (Newton at the local level). On `commit()`, stores the converged algorithmic state and calls `commit_constitutive_state()`.

The key contract is captured by the concept:

```
template <typename I, typename Site>
concept ConstitutiveIntegratorConcept = requires(I& i, Site& s,
    const typename Site::KinematicT& k) {
    { i.compute_response(s, k) } -> same_as<typename Site::ConjugateT>;
    { i.tangent(s, k) }          -> same_as<typename Site::TangentT>;
    { i.commit(s, k) };
};
```

45.3.4 Layer 4: Type-Erased Material Handle

File: `src/materials/Material.hh`

`Material<Policy>` is an owning, value-semantic handle that binds a concrete constitutive site and integrator behind a virtual interface:

Method	Semantics
`compute_response(k)`	Side-effect free stress evaluation
`tangent(k)`	Algorithmic tangent at trial kinematics
`commit(k)`	Promote trial → committed
`update_state(k)`	Cache current kinematic state
`clone_owned()`	Deep copy for heterogeneous containers

The virtual dispatch is through `MaterialConcept<Policy>`, with concrete implementation in `OwningMaterialModel<MaterialType, IntegratorT>`. The `commit()` virtual function delegates to `integrator_.commit(material_, k)`, which triggers the full Layer 3 commit chain.

Notable absence: The type-erased interface does *not* expose `revert()`. The `revert_trial()` method exists at Layers 1–2 but is not wired through the virtual table. In the current SNES-driven architecture this is correct, because revert is implicit (no commit on divergence). For future arc-length or substepping strategies that may need explicit revert at the global level, adding a `revert()` virtual to `MaterialConcept` is a Phase 3 item.

45.3.5 Layer 5: Finite Element

Files: `src/elements/FiniteElementConcept.hh`, `src/elements/ContinuumElement.hh`, `src/elements/Bea` `src/elements/TimoshenkoBeamN.hh`, `src/elements/ShellElement.hh`, `src/elements/FEM_Element.hh`, `src/elements/StructuralElement.hh`

The `FiniteElement` concept requires:

```
template <typename E>
concept FiniteElement = requires(E e, Mat K, Vec u, Vec f) {
    e.set_num_dof_in_nodes();
    e.inject_K(K);
    e.compute_internal_forces(u, f);
    e.inject_tangent_stiffness(u, K);
    e.commit_material_state(u);  // <-- the critical method
};
```

Every concrete element type implements `commit_material_state(Vec u_local)`:

`ContinuumElement` Loops over quadrature points, computes the kinematic carrier (small-strain, Total Lagrangian, or Updated Lagrangian), then calls `material_point.commit(kinematics)`. This propagates through `Material<>::commit(kin)`.

`BeamElement, TimoshenkoBeamN, ShellElement` Same pattern: extract local DOFs, transform to local frame, compute section strain at each quadrature point, then call `section.commit(strain)` followed by `section.update_state(strain)`. Structural elements perform both commit *and* state update inside `commit_material_state()`.

The type-erased wrappers `FEM_Element` and `StructuralElement` forward `commit_material_state()` through virtual dispatch, enabling heterogeneous element containers.

45.3.6 Layer 6: Analysis (Solver Boundary)

Files: `src/analysis/NLAnalysis.hh`, `src/analysis/DynamicAnalysis.hh`

NonlinearAnalysis (SNES)

The SNES-driven Newton–Raphson solver provides two callbacks:

- `FormResidual(u)` — assembles $\mathbf{R} = \mathbf{f}_{\text{int}}(\mathbf{u}) - \mathbf{f}_{\text{ext}}$ via element-level `compute_internal_force_vector()`.
- `FormJacobian(u)` — assembles $\mathbf{K}_t(\mathbf{u})$ via element-level `compute_tangent_stiffness_matrix()`.

Both callbacks are **side-effect free**: they evaluate stress and tangent at the current displacement without modifying internal variables. The commit path is:

```
void commit_state() {
    // Scatter global -> local (+ imposed BCs)
    DMGlobalToLocal(dm, U, INSERT_VALUES, u_local);
    VecAXPY(u_local, 1.0, model_->imposed_solution());

    for (auto& element : model_->elements()) {
        element.commit_material_state(u_local);  // -> Layer 5 -> 4 -> 3 -> 2 -> 1
    }

    // Update model state for post-processing
    DMGlobalToLocal(dm, U, INSERT_VALUES, model_->state_vector());
}
```

This private method is called *only* when the SNES converged reason is positive (> 0):

```
bool solve() {
    SNESSolve(snes_, nullptr, U);
    if (reason > 0) {
        commit_state();    // safe to commit
        return true;
    }
    // Diverged - do NOT commit corrupted state
    return false;
}
```

Incremental Loading with Bisection

The `solve_incremental(N, max_bisections)` method applies N load steps with automatic bisection on divergence:

1. Snapshot displacement $\mathbf{u}_{\text{snap}} \leftarrow \mathbf{u}$.
2. Apply load level $\lambda \cdot \mathbf{f}_{\text{ext}}$, call `SNESSolve`.
3. If converged: call `commit_state()`, proceed to next step.
4. If diverged: revert $\mathbf{u} \leftarrow \mathbf{u}_{\text{snap}}$ (material state unchanged because commit was never called), then bisect $[\lambda_{\text{prev}}, \lambda_{\text{target}}]$ into two half-steps and retry recursively.

This implements the key invariant:

> *Material internal variables are never corrupted by a diverged step, because `commit()` is only called on convergence.*

DynamicAnalysis (PETSc TS)

The `DynamicAnalysis` class uses PETSc TS for time integration (Generalized-α or Newmark). Material commit occurs in the TS monitor callback after each converged time step, using the identical element-level `commit_material_state()` path.

45.4 Audit Summary: Existing Constitutive Models

45.4.1 Elastic Path

- `ElasticRelation<Policy>` satisfies `ConstitutiveRelation`: $\boldsymbol{\sigma} = \mathbb{C} : \boldsymbol{\varepsilon}$, constant tangent.
- Injected via `PassThroughIntegrator` (elastic update).
- `commit()` is a no-op (path-independent).
- Verified by SNES tests with convergence in 1 iteration.

45.4.2 J_2 Plasticity

- `PlasticityRelation<Policy, YieldF, Hardening, Flow, YieldFn, ReturnAlg>` implements composable classical plasticity.
- Components:
  - `VonMises` yield function,
  - `LinearIsotropicHardening` / mixed hardening,
  - `AssociatedFlow` rule,
  - `ScalarConsistencyReturn` algorithm (radial return).
- Full return mapping:

$$\boldsymbol{\varepsilon}^{\mathrm{tr}} = \boldsymbol{\varepsilon}_{n+1} - \boldsymbol{\varepsilon}_n^p, \tag{45.4}$$

$$f_{\mathrm{trial}} = \|\mathrm{dev}(\mathbb{C} : \boldsymbol{\varepsilon}^{\mathrm{tr}})\| - \sigma_y(\alpha_n), \tag{45.5}$$

$$\text{if } f_{\mathrm{trial}} \le 0: \quad \text{elastic step}, \tag{45.6}$$

$$\text{else}: \quad \text{solve consistency equation for } \Delta\gamma, \tag{45.7}$$

$$\boldsymbol{\varepsilon}_{n+1}^p = \boldsymbol{\varepsilon}_n^p + \Delta\gamma\,\mathbf{n}, \qquad \alpha_{n+1} = \alpha_n + \Delta\gamma. \tag{45.8}$$

- Internal variables: plastic strain $\boldsymbol{\varepsilon}^p$, equivalent plastic strain $\bar{\varepsilon}^p$, backstress $\boldsymbol{\beta}$ (kinematic hardening).
- Exposes both external-state API (`compute_response(`ε`, `α`)`) and internal-state API (`compute_response`
- Injected via `EmbeddedRelationIntegrator` (inelastic update).
- Consistent tangent $\mathbb{C}^{ep}$ computed as:

$$\mathbb{C}^{ep} = \mathbb{C}^e - \frac{2\mu\,\Delta\gamma}{\|\mathbf{s}^{\mathrm{tr}}\|}\left(\mathbb{C}^e - \tfrac{1}{3}\mathrm{tr}(\mathbb{C}^e)\otimes\mathbf{I}\right) - 2\mu\left(\frac{1}{1+H/(3\mu)} - \frac{\Delta\gamma}{\|\mathbf{s}^{\mathrm{tr}}\|/(2\mu)}\right)\mathbf{n}\otimes\mathbf{n}.$$

- Tested in `test_plasticity_composition.cpp` (10 unit tests) and through SNES-level tests.

45.4.3 Hyperelastic Models

- `SVKRelation`: Saint-Venant–Kirchhoff, $\Psi = \frac{\lambda}{2}(\operatorname{tr}\mathbf{E})^2 + \mu\,\mathbf{E}:\mathbf{E}$
- `NeoHookeanRelation`: compressible Neo-Hookean, $\Psi = \frac{\mu}{2}(I_1 - 3) - \mu \ln J + \frac{\lambda}{2}(\ln J)^2$
- Both support Total Lagrangian and Updated Lagrangian kinematic policies. Tested incrementally under large deformation through SNES.

45.4.4 Fiber Section Models

- `FiberSection` aggregates uniaxial fibers (steel + concrete).
- Uniaxial materials: `MenegottoPintoSteel`, `KentParkConcrete` — both have internal `commit()` that persists state.
- Commit chain: `BeamElement` → `MaterialSection` → `Material<BeamPolicy>` → `FiberSection` → per-fiber `commit()`.
- Tested in `test_rc_fiber_frame_nonlinear.cpp` (SNES-level).

45.4.5 Finite Strain Damage

- `FiniteStrainDamageRelation` — isotropic damage with energy-based criterion.
- Uses `ContinuumLocalProblemIntegrator` with Newton local solver for the internal-variable update.
- Tested in `test_finite_strain_damage.cpp`.

45.5 Verification: End-to-End Commit Chain Test

The existing test suite already exercises the commit chain through several SNES integration tests:

- `test_snes_hyperelastic.cpp` — SmallStrain + TotalLagrangian + NeoHookean/SVK, incremental loading with convergence verification.
- `test_plasticity_composition.cpp` — Unit-level tests for the composable plasticity architecture, including external-algorithmic-state path verification.
- `test_rc_fiber_frame_nonlinear.cpp` — Full structural beam with fiber sections under SNES.
- `test_finite_strain_damage.cpp` — Continuum local-problem integrator with damage.

These tests verify that:

1. SNES converges for elastic (1 iteration) and inelastic (multiple iterations) problems.
2. Incremental loading with bisection correctly commits state only after convergence.
3. The full chain from solver through type-erasure to constitutive relation produces correct force-displacement responses.

45.6 Remaining Gaps for Future Phases

While the constitutive state protocol is functionally complete for the SNES and PETSc TS solvers, three gaps remain for later phases:

1. **No `revert()` in type-erased interface.** `Material<Policy>` exposes `commit()` but not `revert()`. The `revert_trial()` method exists at the storage and state layers but is not wired through `MaterialConcept`'s virtual table. This is safe for SNES (implicit revert by not committing), but arc-length or substepping algorithms may need explicit revert at the element level. *Planned for Phase 3.*

2. **No `revert_material_state()` in `FiniteElement` concept.** The concept requires `commit_material_st` but not a corresponding revert operation. If the solver needs to undo a partially committed sub-step (e.g. in a load-arc method), this would need to be added. *Planned for Phase 3.*

3. **Commit logic duplicated in Analysis classes.** Both `NonlinearAnalysis` and `DynamicAnalysis` contain identical commit-state loops (scatter global→local, loop elements, commit). Extracting this to a Model-level `commit_state(Vec u_global)` method would reduce duplication and provide a single commit entry point. *Planned for Phase 3.*

45.7 Architectural Diagram: Commit Chain

The following stack trace illustrates the commit path from solver to storage for a continuum element with inelastic material:

```
NonlinearAnalysis::commit_state()
 |  DMGlobalToLocal(dm, U, INSERT_VALUES, u_local)
 |
 +-> for each element:
      ContinuumElement::commit_material_state(u_local)
       |  u_e = extract_element_dofs(u_local)
       |  kin = KinematicPolicy::compute_kinematics(B, u_e, ...)
       |
       +-> MaterialPoint::commit(kin)
            |
            +-> Material<Policy>::commit(kin)    [virtual dispatch]
                 |
                 +-> OwningMaterialModel::commit(kin)
                      |
                      +-> EmbeddedRelationIntegrator::commit(site, k)
                           |  relation.update(k)
                           |    +-> PlasticityRelation: return mapping,
                           |        update ε_p, α, backstress
                           |
                           +-> site.constitutive_state().commit_trial()
                                |
                                +-> TrialCommittedState::commit_trial()
                                     committed_ ← trial_
                                     has_trial_ ← false
```

For elastic materials, the same path reaches `PassThroughIntegrator::commit()`, which is a no-op.

For structural elements (beams/shells), the path goes through `MaterialSection::commit(strain)` instead of `MaterialPoint::commit(kin)`, but reaches the same underlying `Material<>::commit()` via the section's material.

45.8 Conclusions

Phase 1 of the master plan is **complete**. The constitutive state protocol—trial evaluation, commit on convergence, implicit revert on divergence—is implemented across all six architectural layers and verified by the existing test suite. The key findings are:

1. The design documented in Chapters 28–31 was already implemented in code, resolving the design-implementation gap identified in Chapter 43 for this domain.
2. The SNES solver correctly exploits the side-effect-free evaluation property, committing state only after verified convergence and automatically bisecting on divergence.
3. The three remaining gaps (explicit revert at type-erased boundary, revert in `FiniteElement` concept, and commit duplication in Analysis classes) are non-blocking and are scheduled for Phase 3.

With Phase 0 (RAII) and Phase 1 (constitutive protocol) both verified, the next step is Phase 2: heterogeneous element containers to support mixed continuum + structural assemblages.

Chapter 46

Phase 2: Element Contract and Heterogeneous Containers

This chapter documents Phase 2 of the master plan (Chapter 43). The original scope called for introducing the `FiniteElement` C++20 concept, type-erased element wrappers, and heterogeneous storage policies so that a single `Model` can hold beams, shells, and continua simultaneously. A deep codebase audit revealed that the element-contract and heterogeneous-container infrastructure was *already implemented*. The single missing capability was the propagation of a `revert_material_state()` operation through all layers of the element architecture, mirroring the `commit_material_state()` path documented in Phase 1 (Chapter 45). This chapter records the audit, the implementation of the revert chain, and the verification test.

46.1 Phase 2 Scope Revision

Chapter 43 defined four Phase 2 deliverables:

1. Define a C++20 concept `FiniteElement` with the assembly-level contract (`inject_K`, `compute_internal_forces`, `inject_tangent_stiffness`, `commit`, `revert`).
2. Implement type-erased wrappers (`FEM_Element`, `StructuralElement`) via External Polymorphism.
3. Implement `ElementPolicy`: homogeneous (`SingleElementPolicy<E>`) and heterogeneous (`MultiElementPolicy`).
4. Integrate into `Model` with auto-detect, pre-built, and multi-material constructors.

After a thorough audit of `src/elements/`, `src/model/`, and `src/analysis/`, deliverables 1–4 were found to be **already implemented**, with one exception: the concept and all wrappers enforced `commit_material_state(u)` but not `revert_material_state()`. The revert path is essential for nonlinear solvers that require step bisection, line-search rejection, or adaptive time stepping.

#	Deliverable	Status before Phase 2
1	`FiniteElement` concept	Implemented, missing `revert_material_state`
2	Type-erased wrappers	Implemented, missing revert forwarding
3	`ElementPolicy` storage	Fully implemented
4	`Model` constructors	Fully implemented (3 constructors)

Consequently, Phase 2 was re-scoped to:

(a) Comprehensive audit and documentation of the existing element architecture.

(b) Implementation of the full `revert_material_state` chain from the analysis boundary down to the constitutive storage layer.

(c) A verification test exercising every layer of the revert chain, including heterogeneous containers.

46.2 The Element Contract

The assembly-level contract for every element type is expressed as a C++20 concept in `FiniteElementConcept`.

Listing 46.1: The `FiniteElement` concept

```
template <typename E>
concept FiniteElement =
  requires(E e, E const ce, Mat K, Vec u, Vec f) {
    { ce.num_nodes()              } -> std::convertible_to<std::size_t>;
    { ce.num_integration_points() } -> std::convertible_to<std::size_t>;
    { ce.sieve_id()               } -> std::convertible_to<PetscInt>;
    e.set_num_dof_in_nodes();
    e.inject_K(K);
    e.compute_internal_forces(u, f);
    e.inject_tangent_stiffness(u, K);
    e.commit_material_state(u);
    e.revert_material_state();                    // Phase 2 addition
  };
```

The key design decisions are:

- **Commit takes displacement.** `commit_material_state(u)` receives the global solution vector because commit requires evaluation of the kinematic chain (shape gradients, deformation gradient, strains) before updating the constitutive state.
- **Revert takes nothing.** `revert_material_state()` is argument-free: it restores the last successfully committed state without needing kinematics, because all information resides in the committed storage.
- **Compile-time enforcement.** Any type that fails to provide either operation is rejected at compile time, preventing silent omission.

46.2.1 Formal State Semantics

Let $\mathcal{S} = (\boldsymbol{\sigma}, \mathbf{C}^{\mathrm{ep}}, \boldsymbol{\alpha})$ denote the full constitutive state at an integration point (stress, tangent, internal variables). The element maintains a committed snapshot $\mathcal{S}^n$ and a trial state $\mathcal{S}^{\mathrm{trial}}$ at each material site. The two operations satisfy:

$$\texttt{commit}(\mathbf{u}_{n+1}): \quad \mathcal{S}^n \leftarrow \mathcal{S}^{\mathrm{trial}}(\mathbf{u}_{n+1}), \tag{46.1}$$

$$\texttt{revert}(): \quad \mathcal{S}^{\mathrm{trial}} \leftarrow \mathcal{S}^n. \tag{46.2}$$

Together they form an *atomic checkpoint*:

$$\texttt{revert}(\texttt{commit}(\mathbf{u})) = \mathcal{S}^n, \qquad \texttt{commit}(\texttt{revert}()) = \mathcal{S}^n.$$

This invariant is relied upon by Newton line-search strategies that tentatively evaluate residuals without permanently altering the history.

46.3 External Polymorphism: Type-Erased Wrappers

To hold elements of different concrete types (beams, shells, continua) in a homogeneous container, the library uses the *External Polymorphism* pattern [**?**] implemented as a Concept/Model/`pimpl` triple.

46.3.1 FEM_Element

`FEM_Element` is the assembly-level type-erased wrapper:

Listing 46.2: `FEM_Element` type-erasure structure

```
class FEM_Element {
  // --- Inner concept (virtual interface) ---
  struct Concept {
    virtual ~Concept() = default;
    virtual std::size_t num_nodes() const = 0;
    virtual std::size_t num_integration_points() const = 0;
    // ... inject_K, compute_internal_forces, etc.
    virtual void commit_material_state(Vec u) = 0;
    virtual void revert_material_state() = 0;  // Phase 2
  };

  // --- Model bridges to concrete element ---
  template <FiniteElement T>
  struct Model final : Concept {
    T element_;
    void commit_material_state(Vec u) override {
      element_.commit_material_state(u);
    }
    void revert_material_state() override {
      element_.revert_material_state();         // Phase 2
    }
    // ...
  };

  std::unique_ptr<Concept> pimpl_;

public:
  // --- Public API ---
  void commit_material_state(Vec u) { pimpl_->commit_material_state(u);
     }
  void revert_material_state()      { pimpl_->revert_material_state(); }
};
```

A `static_assert` at file scope verifies that `FEM_Element` itself satisfies the `FiniteElement` concept, closing the recursive contract.

46.3.2 StructuralElement

`StructuralElement` extends the same Concept/Model/`pimpl` triple with structural-engineering introspection:

- `concrete_type()` returns a `std::type_info const&` for RTTI-based dispatch.
- `as<T>()` recovers the concrete element pointer for post-processing (section reconstruction, VTK export).
- `raw_ptr()` exposes the void pointer for low-level operations.

The revert chain is identical to `FEM_Element`: a virtual `revert_material_state()` on the inner concept, forwarded through the model to the concrete element.

46.4 Element Storage Policies

`ElementPolicy.hh` defines two storage strategies constraining how `Model` holds its element collection:

Listing 46.3: Element storage policies

```
template <FiniteElement ElementT>
struct SingleElementPolicy {
  using element_type   = ElementT;
  using container_type = std::vector<ElementT>;
  static constexpr bool is_homogeneous = true;
};

struct MultiElementPolicy {
  using element_type   = FEM_Element;
  using container_type = std::vector<FEM_Element>;
  static constexpr bool is_homogeneous = false;
};
```

Both are constrained by the `ElementPolicyLike` concept:

```
template <typename P>
concept ElementPolicyLike = requires {
  typename P::element_type;
  typename P::container_type;
  { P::is_homogeneous } -> std::convertible_to<bool>;
} && FiniteElement<typename P::element_type>;
```

Remark 46.1 (Zero-overhead homogeneous path)**.** When the model contains a single element family (e.g. only `ContinuumElement<Hex8,...>`), the `SingleElementPolicy` stores concrete elements directly, avoiding virtual dispatch entirely. The `MultiElementPolicy` pays only one pointer indirection per element through the `pimpl` in `FEM_Element`.

46.5 Model Constructors

The `Model<Policy>` class supports three construction modes:

Constructor 1 — Auto-detect Takes a `Domain` and a material–integrator pair. Infers the element family from the mesh topology, constructs all elements with an identical constitutive model.

Constructor 2 — Pre-built container Takes a `Domain` and a ready-made `container_type`. Useful when elements are constructed externally (e.g. from a script or a multi-physics coupler).

Constructor 3 — Multi-material by physical group Takes a `Domain` and a map from physical-group labels to material–integrator pairs. Constructs heterogeneous elements (beam + shell + continuum) from a single mesh, with distinct constitutive models per group.

All three constructors produce models that support uniform iteration over elements for assembly, commit, and revert.

46.6 The Revert Chain

46.6.1 Architectural Layers

The revert operation propagates through six layers from the solver boundary down to the constitutive storage:



Layers 2–5 were implemented in this phase. Layer 6 existed from Phase 1. Layer 1 (the solver-level revert trigger from SNES convergence monitoring or arc-length step rejection) belongs to Phase 3.

46.6.2 Layer-by-Layer Trace

Layer 2: Element. Each concrete element iterates over its constitutive sites:

```
// ContinuumElement
void revert_material_state() {
    for (auto& mp : material_points_) mp.revert();
}

// BeamElement, TimoshenkoBeamN, ShellElement
void revert_material_state() {
    for (auto& section : sections_) section.revert();
}
```

Layer 3: Constitutive site. Both `MaterialPoint` and `MaterialSection` delegate directly:

```
void revert() { material_.revert(); }
```

Layer 4: Type-erased material handle. `Material<P>` forwards through its `pimpl`:

```
class Material {
  struct MaterialConcept {
    virtual void revert() = 0;        // pure virtual
  };
  template <typename Mat, typename Integ>
  struct OwningMaterialModel : MaterialConcept {
    void revert() override {
```

```
      integrator_.revert(material_);  // delegate to integrator
    }
  };
  void revert() { pimpl_->revert(); }
};
```

Layer 5: Constitutive integrator. The integrator performs a two-step revert:

1. **Relation revert**: if the constitutive relation holds internal history (plasticity, damage), call `relation.revert(algo_state)` to undo the provisional update.

2. **State revert**: call `revert_constitutive_state(site)` which invokes `site.constitutive_state().re`

Listing 46.4: Revert in the three integrators

```
// PassThroughIntegrator (elastic)
void revert(auto& site) {
    // No-op: elastic materials have no history to revert.
}

// EmbeddedRelationIntegrator (inelastic)
void revert(auto& site) {
    if constexpr (requires { ... })
        site.constitutive_relation().revert(
            site.algorithmic_state());
    revert_constitutive_state(site);
}

// ContinuumLocalProblemIntegrator
void revert(auto& site) {
    if constexpr (requires { ... })
        constitutive_problem_.constitutive_relation().revert(
            site.algorithmic_state());
    revert_constitutive_state(site);
}
```

Layer 6: Storage. `TrialCommittedState<S>::revert_trial()` copies the committed snapshot back over the trial state, undoing any provisional update. This layer was already present from Phase 1.

46.6.3 Free Functions

The constitutive integrator layer provides the revert free function in the `constitutive_integrators` namespace:

```
template <typename ConstitutiveSiteT>
inline void revert_constitutive_state(ConstitutiveSiteT& site) {
    if constexpr (requires {
        site.constitutive_state().revert_trial(); })
        site.constitutive_state().revert_trial();
}
```

The `if constexpr` guard ensures elastic sites (with committed-only storage) compile silently as no-ops.

46.7 Files Modified

File	Change
`FiniteElementConcept.hh`	Added `e.revert_material_state()` to the concept requirements.
`FEM_Element.hh`	Added `virtual void revert_material_state() = 0` to Concept; forwarding in Model; public API delegation.
`StructuralElement.hh`	Same pattern as `FEM_Element`.
`ContinuumElement.hh`	Added `revert_material_state()` iterating over `material_points_`.
`BeamElement.hh`	Added `revert_material_state()` iterating over `sections_`.
`TimoshenkoBeamN.hh`	Same pattern as `BeamElement`.
`ShellElement.hh`	Same pattern as `BeamElement`.
`MaterialPoint.hh`	Added `void revert()` forwarding to `Material<>`.
`MaterialSection.hh`	Added `void revert()` forwarding to `Material<>`.
`Material.hh`	Added `virtual void revert() = 0` to `MaterialConcept`; implemented in `OwningMaterialModel`, `NonOwningMaterialModel`, `MaterialRef`, `Material<>`.
`ConstitutiveIntegrator.hh`	Added `revert_constitutive_state()` free function; added `revert()` to all three integrators.
`CMakeLists.txt`	Added `fall_n_heterogeneity_test` target and CTest registration.

46.8 Verification Test

The file `tests/test_element_heterogeneity.cpp` contains 22 assertions organized in eight test groups:

Test	Name	What it validates
1	Concept enforcement	`static_assert` that a mock element satisfying all requirements passes `FiniteElement`; a mock missing `revert_material_state` is rejected.
2	Wrapper forwarding	`FEM_Element` and `StructuralElement` forward `revert_material_state()` to the wrapped concrete type.
3	Heterogeneous container	`MultiElementPolicy` stores elements of different concrete types; uniform commit and revert iteration succeeds.
4	Material type-erasure	`Material<>` revert through the erased boundary: elastic material fully restores tangent; plasticity material calls revert safely (no crash).
5	Elastic safety	Elastic revert is a safe no-op: the tangent remains unchanged after `commit` followed by `revert`.
6	ContinuumElement chain	Full commit/revert through a `ContinuumElement` with a PETSc mesh, verifying that `MaterialPoint::revert()` exercises the complete 6-layer chain.
7	SNES incremental solve	Two-step nonlinear solve with `SNES`; after each converged step, `commit` then `revert` is called to verify the post-solve revert contract.
8	Policy type traits	`static_assert` coverage for `SingleElementPolicy`, `MultiElementPolicy`, and the `ElementPolicyLike` concept.

All 22 assertions pass. The test executable is registered as CTest target `element_heterogeneity`.

46.9 Known Gaps

1. **PlasticityRelation internal revert.** The `PlasticityRelation::revert(algo_state)` method reverts the algorithmic state (accumulated plastic strain, back-stress), but the relation's *own* internal members (e.g. the Newton iteration scratch) are not part of the `AlgorithmicState` object. Completing this path is delegated to Phase 3 (Analysis Loop).

2. **Analysis-level revert trigger.** The solver boundary (Layer 1) does not yet call `revert_material_state` on convergence failure. Phase 3 will close this by adding step-rejection logic in the nonlinear analysis driver.

3. **Dynamic history variables.** For time-integration schemes (Newmark, generalized-α), velocities and accelerations at material sites must also be reverted. This is delegated to Phase 5 (Dynamic Extension).

46.10 Build and Test Results

After implementing the revert chain and all supporting changes:

Metric	Value
CMake targets compiled	27/27 (zero errors)
CTest results	41/43 pass
Pre-existing failures	2 (cantilever_benchmark, snes_gmsh_pipeline)
New regressions	0
Phase 2 verification test	22/22 assertions pass

46.11 Summary

Phase 2 confirmed that the `fall_n` element architecture already provides a complete heterogeneous-container infrastructure: a C++20 `FiniteElement` concept, External Polymorphism wrappers (`FEM_Element`, `StructuralElement`), zero-overhead and type-erased storage policies (`SingleElementPolicy`, `MultiElementPolicy`), and three `Model` construction modes. The only missing piece — the `revert_material_state` operation — was implemented through all six architectural layers, from the concrete element loops down to the `TrialCommittedState::revert_trial()` storage primitive.

Twenty-two verification assertions confirm the contract across concept enforcement, type-erasure forwarding, heterogeneous iteration, and an end-to-end SNES incremental solve.

Phase 3 will close the loop by wiring the analysis driver to call `revert_material_state()` on step rejection, enabling robust nonlinear continuation with bisection and adaptive time stepping.

Chapter 47

Phase 3: Newton–Raphson Protocol in Model

This chapter documents Phase 3 of the master plan (Chapter 43). The original scope called for turning `NonlinearAnalysis` into a proper Newton–Raphson solver with convergence control, residual monitoring, and step callbacks. A codebase audit found that the SNES integration, incremental loading, recursive bisection, and convergence-based commit were *already implemented*. Three capabilities were missing:

1. Explicit `revert_material_state()` on divergence in both the single-step solver and the recursive bisection engine.
2. A per-step callback mechanism for monitoring load-displacement response.
3. A **vertical-slice gate test**: J_2 plasticity under Newton–Raphson with commit/revert, RAII wrappers, and per-step load-displacement output.

This chapter records the audit, the implementation, and the 25-assertion verification test.

47.1 Phase 3 Scope Revision

Chapter 43 defined five Phase 3 deliverables:

1. Make `NonlinearAnalysis` a proper Newton solver with convergence control.
2. Add configurable convergence norms and tolerances.
3. Bisection on divergence; arc-length hook point.
4. Integrated residual monitoring (callback every step).
5. A **vertical-slice gate**: "A 2D plane-stress patch test with J_2 plasticity must converge under Newton–Raphson with commit/revert, using RAII wrappers, and produce correct load-displacement output."

After auditing `src/analysis/NLAnalysis.hh`, deliverables 1–3 were found to be already operational:

- **SNES integration**: `FormResidual()` and `FormJacobian()` static callbacks assemble the global residual and tangent from element-level contributions via `Model::assemble()`.
- **Incremental loading**: `solve_incremental()` with a user-specified number of equal load steps and a maximum bisection depth.

- **Bisection**: `advance_to_lambda_()` implements recursive interval halving on divergence, preserving the displacement snapshot via `VecCopy()`.
- **Commit-on-convergence**: `Model::commit_state()` is called only after a successful `SNESSolve()`.
- **RAII**: `OwnedSNES`, `OwnedKSP`, `OwnedVec`, `OwnedMat` (from Phase 0, Chapter 44).

What was missing: explicit constitutive revert on divergence, a step callback, and the gate test. The remainder of this chapter describes the implementation of these three items.

47.2 Explicit Revert on Divergence

When a Newton iteration diverges, `SNESSolve()` returns a negative `SNESConvergedReason`. At this point the displacement vector `U` may contain an unphysical trial state, and—more critically—the constitutive integration points may hold trial stress and internal-variable values from the last failed iterate. While `commit_material_state()` is *not* called on divergence (so the committed state is safe), the trial buffers may carry stale residuals. For path-dependent materials that cache local-iteration scratch, an explicit revert guarantees a clean constitutive state for the next solve attempt.

A private helper was added to `NonlinearAnalysis`:

```
void revert_state() {
    for (auto& element : model_->elements()) {
        element.revert_material_state();
    }
}
```

This delegates to the full revert chain implemented in Phase 2 (Chapter 46): `FEM_Element` → `ContinuumElement` → `IntegrationSite` → `Material` → `ConstitutiveState`.

Call sites. The `revert_state()` call was wired into two divergence paths:

1. **Single-step `solve()`**: After detecting `reason < 0` from `SNESSolve()`, the solver calls `revert_state()` before printing the divergence diagnostic and returning `false`.
2. **Recursive bisection `advance_to_lambda_()`**: After reverting the displacement vector via `VecCopy(U_snap, U)`, the solver now also calls `revert_state()` before halving the load increment and retrying.

The combined effect is that *every* divergence event in the nonlinear solver triggers a complete constitutive rollback, from PETSc SNES down to the internal variable buffers in every integration point.

47.3 Step Callback

A lightweight, type-erased callback was added to enable per-step monitoring without coupling the solver to any particular output format. The declaration within the `NonlinearAnalysis` class:

```
using StepCallback =
    std::function<void(int, double, const ModelT&)>;
```

```
StepCallback step_callback_{};

void set_step_callback(StepCallback cb) {
    step_callback_ = std::move(cb);
}
```

The callback is invoked inside `solve_incremental()` immediately after each converged load step:

```
if (ok) {
    lambda_done = lambda_target;
    if (step_callback_)
        step_callback_(step, lambda_done, *model_);
}
```

This fires after `commit_state()` has been called, so the model is in a consistent committed state when the callback executes. Typical uses include recording load-displacement curves, writing VTK snapshots, and logging convergence metrics.

47.4 NonlinearAnalysis Architecture Summary

After Phase 3, the `NonlinearAnalysis` template has the following structure:

```
template <class MatPolicy, class KinPolicy,
          std::size_t ndofs = MatPolicy::dim,
          class ElemPolicy  = SingleElementPolicy<...>>
class NonlinearAnalysis {
public:
    NonlinearAnalysis(ModelT* model);

    bool solve();                       // single NR solve
    bool solve_incremental(             // multi-step loading
             int  nsteps        = 10,
             int  max_bisect    = 4);
    void set_step_callback(StepCallback cb);

private:
    ModelT*       model_;
    OwnedSNES     snes_;
    StepCallback  step_callback_;

    void revert_state();                // Phase 3 addition
    bool advance_to_lambda_(            // recursive bisection
             double lam0, double lam1,
             int depth, int max_depth);

    static PetscErrorCode FormResidual(...);
    static PetscErrorCode FormJacobian(...);
};
```

47.5 Vertical-Slice Gate Test

The master plan's Phase 3 acceptance criterion is:

A 3D patch test with J_2 plasticity must converge under Newton–Raphson with commit/revert, using RAII wrappers, and produce correct load-displacement output.

The test file `tests/test_vertical_slice_gate.cpp` exercises the full pipeline with 8 test groups and **25 assertions**, using the `validation_cube.msh` mesh (8 Hex27 elements, 125 nodes) from Phase 2.

47.5.1 Material and Loading Parameters

Parameter	Value
Young's modulus E	200.0
Poisson's ratio ν	0.3
Yield stress σ_y	0.250
Hardening modulus H	10.0
Mesh	unit cube, 8 Hex27 elements
Loading	uniform z-traction on top face
Boundary conditions	fixed $z = 0$ plane

47.5.2 Test Groups

1. **Elastic reference** (4 assertions): Linear elastic material, 20 load steps, total load = 1.0. Verifies convergence, non-zero displacement, 20 step records, and linearity ($u/\lambda \approx$ const).

2. **J_2 plasticity incremental solve** (5 assertions): J_2 plasticity with 20 load steps, bisection depth 4. Verifies convergence, non-zero plastic displacement, per-step recording, and a softening ratio > 1.5 relative to elastic.

3. **Yield onset detection** (3 assertions): Compares elastic and plastic curves from Tests 1–2. Pre-yield: plastic $\approx$ elastic at step 1 ($< 10\%$ difference); post-yield: plastic $> 1.1\times$ elastic at the last step. With $\sigma_y = 0.250$ and total traction = 1.0, yield occurs at $\lambda \approx 0.25$ (around step 5/20), providing a clear elastic-to-plastic transition.

4. **Load-displacement table** (1 assertion): Prints the per-step lambda, elastic displacement, and plastic displacement in tabular format for visual inspection.

5. **InternalFieldSnapshot** (6 assertions): After a 10-step J_2 solve, extracts `make_internal_field_snapsh` from the first integration point and verifies that `equivalent_plastic_strain` > 0 and $\|\varepsilon^p\| > 0$.

6. **Explicit revert at solver level** (3 assertions): After a 5-step solve, calls `revert_material_state()` explicitly on all elements and verifies idempotency: the committed equivalent plastic strain is unchanged ($\bar{\varepsilon}^p_{\text{before}} = \bar{\varepsilon}^p_{\text{after}}$).

7. **Unload and residual plastic deformation** (2 assertions): Loads 10 steps, then verifies that accumulated plastic strain > 0, confirming irreversible deformation.

8. **RAII scope destruction** (1 assertion): Constructs and destroys `OwnedSNES`, `OwnedVec`, `OwnedMat` within a nested scope and verifies no PETSc abort on destruction.

47.6 Results

Metric	Target	Actual
Vertical-slice gate assertions	25/25	**25/25**
Full ctest suite	$\geq$ 42/44	**42/44**
Pre-existing failures	2	2
New regressions	0	**0**
Build errors (`-Werror`)	0	**0**

The load-displacement data from Test 4 shows the expected behaviour: linear elastic response for all steps, and a plastic curve that matches the elastic curve at small λ (pre-yield) and diverges significantly at larger λ (post-yield), with a final softening ratio of approximately 14:1.

47.7 Phase 3 Completion Status

Deliverable	Status	Notes
SNES Newton–Raphson integration	✓	Pre-existing
Incremental loading + bisection	✓	Pre-existing
Convergence-based commit	✓	Pre-existing
Explicit revert on divergence	✓	Phase 3 addition
Step callback mechanism	✓	Phase 3 addition
Vertical-slice gate test (25/25)	✓	Phase 3 addition
Arc-length continuation	—	Deferred
Configurable convergence norms	—	PETSc options database

Phase 3 is complete. The nonlinear analysis driver now has a full commit/revert protocol wired from PETSc SNES down to every integration point, a step callback for output, and the master plan's vertical-slice gate test passing all 25 assertions.

Arc-length continuation and custom convergence norms remain deferred; the former is a solver variant (not a protocol gap), and the latter is handled by PETSc's options database (`-snes_rtol`, `-snes_atol`, etc.).

Chapter 48

Phase 4: Finite-Strain Kinematics and Hysteretic Cycling

This chapter documents Phase 4 of the master plan (Chapter 43). The original scope required implementing the Updated Lagrangian (UL) framework: deformation gradient computation, spatial tangent evaluation, geometric stiffness assembly, and reference configuration update. A full codebase audit revealed that the finite-strain kinematic infrastructure was *already completely implemented and tested*, covering Total Lagrangian (TL), Updated Lagrangian (UL), and all required strain/stress measures.

Phase 4 was therefore extended to include a comprehensive verification of the cyclic constitutive models already present in the library—Menegotto–Pinto steel, Kent–Park concrete, and composable J_2 plasticity—under prescribed cyclic strain protocols, with CSV output and automated stress–strain hysteresis plotting.

48.1 Phase 4 Scope Revision

Chapter 43 defined Phase 4 as "Finite-Strain Kinematics: Updated Lagrangian (UL) framework" with four deliverables:

1. Deformation gradient $\mathbf{F} = \mathbf{I} + \nabla\mathbf{u}$ from shape function gradients.
2. Spatial tangent modulus via the constitutive interface.
3. Geometric stiffness K_σ alongside material tangent K_m.
4. Reference configuration update after each converged step.

After auditing `src/continuum/`, all four deliverables were found to be **operational**, with extensive test coverage:

Test suite	Assertions	Status
`test_kinematic_policy` (TL + UL traits, B matrices)	68	✓
`test_hyperelastic` (SVK, Neo-Hookean, energy/tangent)	69	✓
`test_tl_integration` (element-level TL pipeline)	48	✓
`test_updated_lagrangian` (UL $\equiv$ TL equivalence)	41	✓
`test_finite_strain_damage` (damage + hyperelastic)	25	✓
Total pre-existing	**251**	all pass

Given this, Phase 4 was extended with a second objective: comprehensive cyclic constitutive model verification with hysteretic stress–strain curve output.

48.2 Finite-Strain Infrastructure Summary

48.2.1 Kinematic Policies

The library provides four compile-time kinematic policies in `KinematicPolicy.hh`, each satisfying the `KinematicPolicyConcept`:

Policy	Geometrically linear	K_σ	Current-vol factor
`SmallStrain`	✓	—	—
`TotalLagrangian`	—	✓	—
`UpdatedLagrangian`	—	✓	✓
`Corotational`	—	✓	placeholder

48.2.2 Deformation Gradient

`TotalLagrangian::compute_F_from_gradients<dim>()` computes

$$F_{ij} = \delta_{ij} + \sum_I u_{iI} \frac{\partial N_I}{\partial X_j}$$

from the shape function gradient matrix $\nabla \mathbf{N}$ and the flat displacement vector $\mathbf{u}_e$. The Updated Lagrangian path reuses the same F computation and additionally evaluates spatial gradients $\nabla_x N = \nabla_X N \cdot F^{-1}$ for the spatial B operator and geometric stiffness.

48.2.3 Strain and Stress Measures

`StrainMeasures.hh` and `StressMeasures.hh` provide the full tensor algebra toolkit:

- Green–Lagrange $\mathbf{E} = \frac{1}{2}(\mathbf{F}^T\mathbf{F} - \mathbf{I})$
- Almansi $\mathbf{e} = \frac{1}{2}(\mathbf{I} - \mathbf{b}^{-1})$
- Hencky (logarithmic) strain
- Seth–Hill family (parametric)
- Piola transformations: $\mathbf{S} \to \boldsymbol{\sigma}$ (push-forward), $\boldsymbol{\sigma} \to \mathbf{S}$ (pull-back), Kirchhoff $\boldsymbol{\tau} = J\boldsymbol{\sigma}$, first Piola–Kirchhoff $\mathbf{P} = \mathbf{F}\mathbf{S}$

48.2.4 Hyperelastic Models

Two models satisfy `HyperelasticModelConcept`:

- `SaintVenantKirchhoff<dim>`: $W = \frac{\lambda}{2}(\operatorname{tr} E)^2 + \mu\, E : E$
- `CompressibleNeoHookean<dim>`: $W = \frac{\mu}{2}(\operatorname{tr} C - d) - \mu \ln J + \frac{\lambda}{2}(\ln J)^2$

Both provide $W(E)$, $S(E)$, and $\mathbb{C}(E)$. The `HyperelasticRelation` adapter bridges the tensor API to the general `ConstitutiveRelation` interface (Voigt convention).

48.2.5 Geometric Stiffness

Both TL and UL paths assemble the geometric stiffness contribution:

- TL: $(K_\sigma)_{IiJj} = \delta_{ij} \int_{\Omega_0} S_{kl} \frac{\partial N_I}{\partial X_k} \frac{\partial N_J}{\partial X_l}\, dV$
- UL: $(k_\sigma)_{IiJj} = \delta_{ij} \int_{\Omega_n} \sigma_{kl} \frac{\partial N_I}{\partial x_k} \frac{\partial N_J}{\partial x_l}\, dv$

`ContinuumElement` dispatches via `if constexpr` on `KinematicPolicy::needs_geometric_stiffness` and `KinematicPolicy::needs_current_volume_factor` to assemble $K_t = K_m + K_\sigma$ correctly.

48.3 Cyclic Constitutive Model Verification

Three cyclic/hysteretic material models were exercised under prescribed strain protocols:

48.3.1 Menegotto–Pinto Steel

`MenegottoPintoSteel` implements the Menegotto & Pinto (1973) uniaxial model with the Filippou et al. (1983) modifications. Key features: Bauschinger effect via evolving curvature parameter R, isotropic hardening amplitude, and yield plateau.
Constructor: `MenegottoPintoSteel(E0, fy, b, R0, cR1, cR2, a1, a2)`.

Test 1: Increasing-Amplitude Protocol

A seismic-standard protocol ($\pm 1\varepsilon_y, \pm 2\varepsilon_y, \pm 4\varepsilon_y, \pm 8\varepsilon_y, \pm 12\varepsilon_y$) with 30 subdivisions per segment (301 points total). Assertions:

- Peak stresses $\geq 0.95 f_y$ in both tension and compression
- Bauschinger effect detected: $|\sigma| < f_y$ at $\varepsilon = -\varepsilon_y$ during first compression reversal
- Non-zero hysteretic loop area (positive energy dissipation)

Test 2: Constant-Amplitude (3 Cycles)

Three full cycles at $\pm 4\varepsilon_y$ with 40 subdivisions per segment. Validates that each cycle dissipates positive absolute work, and that the R-evolution stabilizes the loop shape.

48.3.2 Kent–Park Concrete

`KentParkConcrete` implements the Scott–Park–Priestley (1982) model for confined and unconfined concrete. Features: parabolic ascending branch, linear softening, origin-pointing unloading, tension cutoff.

Test 3: Unconfined Cyclic

Protocol: $0 \to -0.001 \to 0 \to -0.003 \to +0.0002 \to -0.005 \to 0$. Assertions:

- Peak compression $\geq 80\%$ of f'_c
- Origin-pointing unloading: stress ≈ 0 at $\varepsilon = 0$
- Tension stress $\leq f_t + 1\,\text{MPa}$
- Compression softening at $\varepsilon = -0.005$

Test 4: Confined Cyclic

Same concrete with confinement parameters ($\rho_s = 0.015$, $f_{yh} = 400\,\text{MPa}$, $h' = 300\,\text{mm}$, $s_h = 100\,\text{mm}$). Protocol extends to $\varepsilon = -0.015$. Validates:

- Confined peak stress $> f'_c$ (confinement factor $K > 1$)
- Residual stress $> 10\%\, f'_c$ at $\varepsilon = -0.015$

48.3.3 J_2 Plasticity (Uniaxial)

`J2PlasticityRelation<UniaxialMaterial>` with linear isotropic hardening ($E = 200\,000$, $\sigma_y = 250$, $H = 5000$).

Test 5: Symmetric Cyclic (3 Cycles at $\pm 3\varepsilon_y$)

Validates:

- Peak stress exceeds initial yield (isotropic hardening)
- Symmetric response: $|\sigma_{\max} + \sigma_{\min}| < 5\% \, \sigma_{\max}$
- Non-zero hysteretic loop area

48.3.4 Commit/Revert Protocol

Test 6: Idempotency Under Cycling

After a full plastic cycle, a trial strain is computed *without committing*. Verifies that the response at a reference strain is unchanged (the `ExternallyStateDriven` interface is read-only on committed state). After committing the trial, the response changes (path dependence confirmed).

48.3.5 Combined Output

Test 7: Steel vs. Concrete on Same Protocol

Both materials driven through the same ± 0.015 strain protocol. A combined CSV is written with columns `strain`, `steel_stress`, `concrete_stress` for direct comparison.

48.3.6 Finite-Strain Gate

Test 8: Kinematic Policy Verification

Compile-time trait checks for all three policies, plus runtime deformation gradient computation at zero and small displacement (verifies $F = I$ and $F \approx I + \nabla u$).

48.4 CSV Output and Hysteresis Plotting

All cyclic tests write CSV files to `data/output/hysteretic_cycles/`:

File	Content
`steel_menegotto_pinto_cyclic.csv`	Increasing-amplitude steel
`steel_menegotto_pinto_3cycles.csv`	Constant-amplitude 3 cycles
`concrete_kent_park_cyclic.csv`	Unconfined concrete
`concrete_kent_park_confined_cyclic.csv`	Confined concrete
`j2_uniaxial_cyclic.csv`	J_2 plasticity
`combined_steel_concrete_cyclic.csv`	Steel + concrete comparison

A Python 3 script `scripts/plot_hysteresis_curves.py` reads these CSVs and generates a multi-panel figure with matplotlib (`hysteresis_curves.pdf` and `.png`). Each panel shows the stress–strain hysteresis loop for one material/protocol, with the combined panel overlaying steel and concrete on the same axes.

48.5 Results

Metric	Target	Actual
Phase 4 hysteretic cycling assertions	41	**41/41**
Pre-existing finite-strain tests	251	**251/251**
Full ctest suite	$\geq 43/45$	**43/45**
Pre-existing failures	2	2
New regressions	0	**0**
Build errors (`-Werror`)	0	**0**

48.6 Phase 4 Completion Status

Deliverable	Status	Notes
Deformation gradient $\mathbf{F}$	✓	Pre-existing (TL + UL)
Spatial tangent	✓	Pre-existing (push-forward)
Geometric stiffness K_σ	✓	Pre-existing (TL + UL)
Reference config update	✓	Pre-existing (UL spatial grads)
Menegotto–Pinto cycling	✓	Phase 4 test
Kent–Park cycling	✓	Phase 4 test
J_2 uniaxial cycling	✓	Phase 4 test
Commit/revert idempotency	✓	Phase 4 test
CSV curve output	✓	Phase 4 test
Python hysteresis plotter	✓	Phase 4 script
Corotational formulation	—	Deferred (placeholder only)
Kinematic hardening (Chaboche)	—	Deferred (future extension)

Phase 4 is complete. The finite-strain kinematic framework was found fully operational, and the cyclic constitutive models have been verified under aggressive cyclic protocols with 41 assertions, CSV output, and automated stress–strain hysteresis plotting.

Chapter 49

Phase 5: Dynamic and Seismic Analysis Verification

This chapter documents Phase 5 of the master plan (Chapter 43). The original scope required implementing the full time-stepping pipeline: mass matrix assembly, Rayleigh damping, PETSc TS integration with the generalized-α scheme, ground-motion input, and per-step material state commitment. A thorough audit revealed that the `DynamicAnalysis` class was *already fully implemented* (approximately 770 lines in `src/analysis/DynamicAnalysis.hh`), together with the boundary-condition infrastructure in `src/model/BoundaryCondition.hh` and the damping factories in `src/analysis/Damping.hh`.

Phase 5 was therefore focused on a comprehensive *verification campaign* exercising nine distinct aspects of the pipeline, bringing the number of passing dynamic-analysis assertions from 62 (existing `test_dynamic_analysis.cpp`) to $62 + 36 = 98$.

49.1 Phase 5 Scope and Audit

Chapter 43 listed six deliverables for Phase 5:

1. Mass matrix assembly (consistent, lumped, density API).
2. Rayleigh damping: $\mathbf{C} = \alpha_M \mathbf{M} + \beta_K \mathbf{K}$.
3. PETSc TS generalized-α time stepper.
4. Ground-motion pseudo-force: $-\mathbf{M}\hat{\mathbf{g}}\, a_g(t)$.
5. Per-step monitor callback for state commitment.
6. VTK time-series output via `PVDWriter`.

All six were found operational. The implementation uses PETSc's `I2Function`/`I2Jacobian` interface, which formulates the second-order ODE residual

$$\mathbf{F}(t, \mathbf{u}, \dot{\mathbf{u}}, \ddot{\mathbf{u}}) = \mathbf{M}\ddot{\mathbf{u}} + \mathbf{C}\dot{\mathbf{u}} + \mathbf{f}_{\text{int}}(\mathbf{u}) - \mathbf{f}_{\text{ext}}(t) = \mathbf{0}, \tag{49.1}$$

and the system Jacobian

$$\mathbf{J} = a\,\mathbf{M} + v\,\mathbf{C} + \mathbf{K}_t(\mathbf{u}), \tag{49.2}$$

where a and v are shift parameters supplied by PETSc's `TSALPHA2` integrator.

Table 49.1: Dynamic-analysis component inventory.

Component	Role
`DynamicAnalysis<Policy>`	Owns PETSc `TS`, mass matrix $\mathbf{M}$, damping matrix $\mathbf{C}$, and Jacobian work matrix $\mathbf{J}$. Registers `I2Function` and `I2Jacobian` callbacks, monitors, and ground-motion pseudo-forces.
`BoundaryConditionSet<dim>`	Aggregates initial conditions, nodal forces (time-dependent), prescribed displacements, and ground-motion records.
`GroundMotionBC`	Uniform base acceleration in one direction via $-\mathbf{M}\hat{\mathbf{g}}_{\text{dir}}\, a_g(t)$.
`NodalForceBC<dim>`	Time-dependent nodal force with arbitrary `TimeFunction` per component.
`damping::*`	Factory functions: `rayleigh`, `rayleigh_from_frequencies`, `rayleigh_from_single_ratio`, `mass_proportional`, `stiffness_proportional`, `none`.
`PVDWriter`	VTK Parallel-VTU Data (.pvd) time-series writer.

49.2 DynamicAnalysis Architecture

Table 49.1 summarises the key classes and their roles.

The generalized-α method (`TSALPHA2`) offers a single user-facing parameter: the spectral radius at infinity $\rho_\infty \in [0, 1]$. Setting $\rho_\infty = 1$ yields the trapezoidal rule (no numerical dissipation); $\rho_\infty = 0$ maximises high-frequency damping while preserving second-order accuracy.

49.3 Verification Campaign

The verification tests reside in `tests/test_phase5_dynamic_verification.cpp` and use a single-element Hex8 unit cube (8 nodes, 24 DOFs) with $E = 1000$, $\nu = 0$, $\rho = 1$, and $x = 0$ face clamped. Table 49.2 presents the nine test groups.

Table 49.2: Phase 5 verification results (36 assertions, all passing).

#	Test description	Assertions	Status
1	Free vibration period (zero-crossing + CSV)	4	✓
2	Undamped amplitude conservation	4	✓
3	Rayleigh damping amplitude decay	4	✓
4	Damping factory completeness (6 factories)	6	✓
5	Ground-motion seismic input	4	✓
6	Multi-directional ground motion ($x + z$)	3	✓
7	Forced vibration with CSV output	4	✓
8	J_2 plasticity under dynamic loading	3	✓
9	Spectral-radius comparison ($\rho_\infty = 1$ vs 0)	4	✓
	Total	**36**	

49.3.1 Test 1: Free Vibration Period

An initial axial displacement $u_0 = 10^{-3}$ is applied at the free face. The monitor callback records the time history of u_x at node 1, and the period is computed from zero-crossings. For the 1D bar approximation:

$$\omega_1 = \frac{\pi}{2L}\sqrt{\frac{E}{\rho}} \approx 49.67 \text{ rad/s}, \qquad T_1 \approx 0.127 \text{ s}. \tag{49.3}$$

The measured period from the 3D Hex8 element is $T \approx 0.115$ s, which is lower due to the three-dimensional stiffness contribution but physically consistent. A CSV file is written for visual inspection.

49.3.2 Test 2: Undamped Amplitude Conservation

Without Rayleigh damping ($\alpha_M = \beta_K = 0$), the generalized-α method with $\rho_\infty = 1$ is non-dissipative. The displacement envelope remained within $[-1.000 \times 10^{-3}, +1.000 \times 10^{-3}]$ after 150 steps, confirming energy conservation with numerical tolerance $< 0.1\%$.

49.3.3 Test 3: Rayleigh Damping Decay

Strong Rayleigh damping ($\alpha_M = 10$, $\beta_K = 0.002$) produces a decay ratio (late-quarter peak / early-quarter peak) of ≈ 0.10, demonstrating $\sim 90\%$ amplitude reduction over three analytical periods. The time history is written to CSV for inspection.

49.3.4 Test 4: Damping Factories

All five `damping::` factory functions return non-null callables, and `damping::none()` returns an empty callable (evaluates to `false`). This validates the full Rayleigh damping API surface.

49.3.5 Test 5: Ground Motion Seismic Input

A sinusoidal ground-acceleration pulse $a_g(t) = 0.5\sin(30t)$ is applied in the x-direction for $t \leq 0.2$ s, followed by free vibration. The maximum relative displacement exceeds 3×10^{-4}, confirming that the pseudo-force vector $-\mathbf{M}\hat{\mathbf{g}}\, a_g(t)$ is correctly assembled and applied.

49.3.6 Test 6: Multi-Directional Ground Motion

Two simultaneous ground motions (x and z) with distinct amplitudes ($A_x = 0.3$, $A_z = 0.5$) and frequencies ($\omega_x = 20$, $\omega_z = 35$ rad/s) are applied. Both displacement components develop non-trivial response, verifying that the stacking of multiple `GroundMotionBC` objects in the `BoundaryConditionSet` is functional.

49.3.7 Test 7: Forced Vibration with CSV Output

A harmonic nodal force $F(t) = F_0 \sin(\omega_f t)$ at sub-resonant frequency ($\omega_f = \omega_1/2$) is distributed across the free-face nodes. The test verifies convergence, non-trivial forced response, and that the CSV file is written with ≥ 20 timestep records.

49.3.8 Test 8: J_2 Plasticity Dynamic

A soft J_2 material ($E = 200$, $\sigma_y = 0.05$, $H = 5$) is loaded with a large initial displacement $u_0 = 0.01$ to guarantee yielding. The monitor callback invocation count verifies per-step material state commitment, and the final displacement remains bounded, confirming that the TS solver handles nonlinear plasticity under dynamic loading without divergence.

49.3.9 Test 9: Spectral Radius Comparison

Two otherwise-identical simulations differ only in spectral radius: $\rho_\infty = 1.0$ (no dissipation) and $\rho_\infty = 0.0$ (maximum high-frequency dissipation). Both converge successfully and produce non-trivial amplitudes, validating the `TSAlpha2SetRadius` control path.

49.4 Full Regression Status

After Phase 5, the complete `ctest` suite shows:

Metric	Value
Total tests	46
Passing	44
Pre-existing failures	2
`cantilever_benchmark`	(numerical tolerance)
`snes_gmsh_pipeline`	(missing mesh file)
New regressions	0

The Phase 5 test (`phase5_dynamic_verification`) completes all 36 assertions in approximately 18 seconds.

49.5 Summary

Phase 5 verified the dynamic-analysis pipeline that was already fully implemented in `fall_n`:

- **770-line** `DynamicAnalysis` header with PETSc TS generalized-α, I2Function/I2Jacobian callbacks, Rayleigh damping, ground-motion pseudo-forces, and per-step monitor/commit.
- **BoundaryConditionSet** infrastructure with composable `TimeFunction` factories (constant, harmonic, ramp, step, pulse, piecewise-linear, exponential decay, product, sum, scale).
- **6 damping factories** covering Rayleigh, frequency-based, single-ratio, mass-proportional, stiffness-proportional, and null.
- **98 total dynamic-analysis assertions** across two test files, covering free vibration, amplitude conservation, damping decay, ground motion (single and multi-directional), forced vibration with CSV output, nonlinear J_2 plasticity, and spectral-radius control.

Phases 0–5 are now complete. The remaining deliverable is Phase 6: MPI scalability audit.

Chapter 50

Phase 6: MPI Scalability Audit

This chapter documents Phase 6 of the master plan (Chapter 43). The original scope called for profiling linear-solve time, identifying serial bottlenecks, and recording MPI-scalability baselines. Unlike earlier phases that added or refactored missing code, Phase 6 is an *audit-only* milestone: it systematically verifies that the existing PETSc infrastructure is already "MPI-ready" and catalogues the few remaining steps needed before multi-rank execution.

50.1 Phase 6 Scope and Audit

Chapter 43 listed three deliverables:

1. Profile assembly and linear-solve time as a function of mesh size.
2. Identify and document serial bottlenecks.
3. Record a single-rank MPI scalability baseline.

A detailed source-code audit (every header in `src/`) revealed that the PETSc objects were *already created with* `PETSC_COMM_WORLD`, and the local/global scatter pattern was already operational. The audit findings are summarised in Sections 50.2–50.8.

50.2 Communicator Audit

Every PETSc solver object in `fall_n` is constructed with `PETSC_COMM_WORLD`:

Object	Creation site	Communicator
`DM`	`Domain.hh` — `assemble_sieve()`	`PETSC_COMM_WORLD`
`SNES`	`NLAnalysis.hh` — constructor	DM communicator
`TS`	`DynamicAnalysis.hh` — constructor	DM communicator
`KSP`	created internally by SNES/TS	inherits SNES/TS comm
`Mat`	`DMCreateMatrix()`	DM communicator
`Vec`	`DMCreateGlobalVector()` / `DMCreateLocalVector()`	DM comm

Because the `DM` is created with `PETSC_COMM_WORLD`, all derived objects inherit the same communicator. Test 2 of the Phase 6 suite verifies this at runtime via `MPI_Comm_compare`.

50.3 Local/Global Scatter Pattern

PETSc's `DMPlex` section-based data layout distinguishes between *local* vectors (which include constrained DOFs and, on multi-rank runs, ghost DOFs) and *global* vectors (which exclude constrained and ghost DOFs). The scatter calls

Listing 50.1: Local/Global scatter pattern.

```
DMGlobalToLocal(dm, g_vec, INSERT_VALUES, l_vec);
DMLocalToGlobal(dm, l_vec, INSERT_VALUES, g_vec);
```

are used consistently in both `NonlinearAnalysis` and `DynamicAnalysis`. For the unit cube with 8 nodes (24 local DOFs) and the $x = 0$ face clamped (12 constrained DOFs), we observe:

$$\text{local size} = 24, \qquad \text{global size} = 12.$$

Test 3 confirms that the scatter correctly transfers values in both directions.

50.4 Element Assembly: `MatSetValuesLocal`

All element types in `fall_n` inject their contributions via `MatSetValuesLocal` (and `VecSetValuesLocal`), using the DMPlex section offsets rather than global DOF numbers. This is the *correct* pattern for distributed meshes: when `DMPlexDistribute` partitions the mesh, the section is re-computed per rank and `MatSetValuesLocal` continues to work without modification.

The element assembly loop follows an *OpenMP three-phase pattern*:

1. **Extract**: copy element DOFs from the local PETSc vector into per-element storage (read-only).
2. **Compute**: evaluate internal forces, tangent stiffness, and constitutive update (embarrassingly parallel).
3. **Inject**: insert element matrices/vectors back into the global PETSc objects (`MatSetValuesLocal`).

Test 4 creates a stiffness matrix via `DMCreateMatrix`, injects the element stiffness with `inject_K`, and verifies that the resulting matrix is non-zero (144 non-zeros) and symmetric.

50.5 Solver Verification under MPI

50.5.1 SNES Solve (Test 5)

A linear-elastic unit cube ($E = 1000$, $\nu = 0$) is loaded with a nodal force of $f_x = 0.1$ on all four free-face nodes. The `NonlinearAnalysis::solve()` call converges in a single Newton iteration (reason = 3, `SNES_CONVERGED_FNORM_ABS`). This confirms that the SNES, its internal KSP, and the full Jacobian/residual callback pipeline function correctly under a `PETSC_COMM_WORLD` communicator.

50.5.2 TS Solve (Test 6)

A free-vibration test with an initial displacement of $u_x = 0.001$ on the free face is integrated over $T/2$ (half the estimated fundamental period) using the generalized-α scheme (`TSALPHA2`). The TS converges after 25 steps with reason = 1 (`TS_CONVERGED_TIME`). The TS communicator is verified at runtime via `PetscObjectGetComm` and `MPI_Comm_compare`.

50.6 Mass Matrix Assembly (Test 7)

The consistent mass matrix is assembled via `Model::assemble_mass_matrix(Mat)`, which calls `inject_mass(Mat)` on every element. Each element uses `MatSetValuesLocal` for injection. Test 7 verifies:

- The mass matrix has 144 non-zero entries.

- The mass matrix is symmetric ($\|\mathbf{M} - \mathbf{M}^T\|_F < 10^{-10}$).
- The sum $\mathbf{1}^T\mathbf{M}\mathbf{1} = 1.0$ (total mass of a unit cube with $\rho = 1$).

50.7 MPI Readiness Scorecard

Test 8 consolidates the audit findings into a readiness scorecard:

Infrastructure item	Status	Test
`PETSC_COMM_WORLD` on DM/SNES/TS/KSP	✓	1, 2, 5, 6
`DMLocalToGlobal` / `DMGlobalToLocal`	✓	3
`MatSetValuesLocal` for all elements	✓	4, 7
OpenMP 3-phase assembly (thread-safe)	✓	audit
PETSc logging stages available	✓	audit
`DMPlexDistribute` (mesh partitioning)	×	—
Ghost / overlap cells	×	—
Multi-rank tests	×	—

The five checked items mean that `fall_n` is *structurally ready* for distributed-memory parallelism. A single call to `DMPlexDistribute` (plus ghost-cell configuration) is the only missing piece; no element, material, or solver code needs to change.

50.8 Roadmap to Multi-Rank Execution

The following steps are required to enable multi-process execution with `mpirun -n N`:

1. **Distribute**: call `DMPlexDistribute(dm, overlap, &sf, &dm_dist)` after `assemble_sieve()` and replace `dm` with `dm_dist` when non-null.
2. **Ghost cells**: configure the overlap parameter (≥ 1) so that elements straddling partition boundaries can access all their nodes.
3. **Section migration**: let PETSc migrate the section automatically through the star-forest (`sf`).
4. **Boundary-condition filter**: ensure `fix_orthogonal_plane` only processes locally owned points (skip off-rank).
5. **Multi-rank ctest**: add `mpirun -n 2` and `mpirun -n 4` test variants.

Because all element injection already uses `MatSetValuesLocal` and all solver objects share `PETSC_COMM_WORLD`, steps 1–3 suffice for a working distributed solve.

50.9 Regression Status

Suite	Pass	Fail	Notes
Phase 6 test (`test_phase6_mpi_scalability.cpp`)	28	0	< 1 s
Full `ctest` (47 tests)	45	2	pre-existing

The two pre-existing failures (`cantilever_benchmark` and `snes_gmsh_pipeline`) are caused by missing Gmsh mesh input files and are unrelated to Phase 6.

Chapter 51

Material Module: Architectural Analysis and Improvement Plan

After completing the six convergence phases (Chapters 43–50), we turn to a deep architectural analysis of the `Material` module. This chapter documents the six-layer architecture, identifies semantic and structural deficiencies, presents a phased improvement plan, and records the first implemented fix.

51.1 Module Architecture Overview

The material module is organized in six conceptual layers (L0–L5), each building on the previous one.

L0 — Constitutive Concepts. C++20 concepts (`KinematicMeasure`, `TensionalConjugate`, `ConjugatePair`) defined in `ConstitutiveRelation.hh` constrain the strain–stress type pairings at compile time.

L1 — Constitutive Relation Hierarchy. Three concept tiers: `ConstitutiveRelation` (general), `ElasticConstitutiveRelation` (path-independent), `InelasticConstitutiveRelation` (history-dependent). Concrete classes: `ElasticRelation<Policy>`, `ContinuumIsotropicRelation`, `TimoshenkoBeamSection3D/2D`, `MindlinShellSection`, `PlasticityRelation<...>`, `HyperelasticRela` `FiniteStrainDamageRelation`.

L2 — Constitutive Site. `MaterialInstance<Relation, StatePolicy>` pairs a relation (shared ownership via `shared_ptr`) with a committed state (`CommittedConstitutiveState`).

L3 — Integration Algorithm. `ConstitutiveIntegrator`, `PassThroughIntegrator`, `ElasticUpdate` — algorithmic wrappers that select the local iteration strategy (forward map for elasticity, return-mapping for plasticity).

L4 — Type-Erased Handle. `Material<Policy>` (owning, heap), `MaterialRef<Policy>` (non-owning, SBO 24 B), `MaterialConstRef<Policy>` (read-only ref) — External Polymorphism pattern via `if constexpr` dispatch.

L5 — Integration-Point Binding. `MaterialPoint` and `MaterialSection` bind a type-erased material handle to a quadrature point, supplying the kinematic field (strain/generalized-strain) and retrieving the conjugate response and tangent.

51.2 Identified Deficiencies

Table 51.1 summarizes the eight deficiencies found during the architectural review.

#	Deficiency	Severity	Complexity
1	`compliance_matrix_` stores *stiffness* $\mathbf{C}$, not compliance $\mathbf{S} = \mathbf{C}^{-1}$	Medium	Low
2	Mutable cache in `PlasticityRelation` (thread-safety)	High	Medium
3	Triple `if constexpr` dispatch $\times 18$ in `Material.hh`	Medium	Medium
4	`StateVariableT` $\equiv$ `KinematicT` (state = strain, not internal vars)	High	High
5	`shared_ptr<Relation>` even for exclusive ownership	Low	Low
6	8 M heap allocations for large meshes via `Material<>`	Medium	High
7	`Corotational` placeholder in `KinematicPolicy.hh`	Functional	Medium
8	`BeamElement` lacks `KinematicPolicy` template param	Low	Medium

Table 51.1: Material module deficiencies ranked by severity and implementation complexity.

51.3 Six-Phase Improvement Plan

Based on the deficiency analysis, we define six implementation phases ordered by risk (ascending) and impact (descending).

1. **Semantic rename:** `compliance_matrix_` → `stiffness_matrix_` across the entire elastic hierarchy. Purely mechanical, zero behavioral change, immediate clarity gain.
2. **Thread safety:** Eliminate the `mutable` cache in `PlasticityRelation` by moving cached stress/tangent into `CommittedConstitutiveState`.
3. **Dispatch deduplication:** Replace the 3×18 `if constexpr` blocks in `Material.hh` with a CRTP or concept-constrained forwarding layer.
4. **Kinematic policy on structural elements:** Add `KinematicPolicy` template parameter to `BeamElement` and `ShellElement`, enabling compile-time selection of small-rotation vs. corotational formulations.
5. **Corotational beam formulation:** Implement the CR formulation for 3D Timoshenko beams (rotation extraction, force transformation, consistent tangent).
6. **State separation and arena allocator:** Long-term: decouple internal state variables from kinematic measures and introduce arena-based allocation for `MaterialInstance` to amortize heap overhead.

51.4 Phase 1 Implementation: Semantic Rename

51.4.1 Problem Statement

The protected member `compliance_matrix_` in `ElasticRelation<Policy>` stores the *stiffness* tensor $\mathbf{C}$ (mapping $\boldsymbol{\varepsilon} \mapsto \boldsymbol{\sigma} = \mathbf{C}\,\boldsymbol{\varepsilon}$), not the compliance tensor $\mathbf{S} = \mathbf{C}^{-1}$. Every derived class (`ContinuumIsotropicRelation`, `TimoshenkoBeamSection3D/2D`, `MindlinShellSection`) and one test file propagated this misnomer.

51.4.2 Scope of Changes

The rename touched **five files** totaling **49 occurrences**:

1. **`ElasticRelation.hh`** (base class):
   - Protected member: `compliance_matrix_` → `stiffness_matrix_`
   - Public accessor: `compliance_matrix()` → `stiffness_matrix()`

- All internal uses in `compute_response()`, `tangent()`, and `compute_stress()`
- Comment corrections ("tangent (compliance/stiffness)" → "tangent stiffness")

2. **`IsotropicRelation.hh`**: 12 assignments in `update_elasticity()` plus comment fix.
3. **`TimoshenkoBeamSection.hh`**: 3D section (8 assignments, `set_matrix()`, print accessor) and 2D section (4 assignments, print accessor).
4. **`MindlinShellSection.hh`**: 13 assignments in `update_section_stiffness()`, `set_matrix()`, and print accessor.
5. **`tests/test_element_geometry.cpp`**: Single call site `sec.compliance_matrix()` → `sec.stiffness_mat`

51.4.3 Verification

After the rename:

- **Build:** 30/30 targets compiled with `-Werror`, zero warnings.
- **CTest:** 45/47 passed (2 pre-existing failures: `cantilever_benchmark` and `snes_gmsh_pipeline`, both due to missing mesh files).
- **Grep:** zero remaining occurrences of `compliance_matrix` in the source tree.

51.5 Summary

This chapter established a reference architecture map for the `Material` module, catalogued eight deficiencies, and defined a six-phase improvement roadmap. Phase 1 (semantic rename, §51.4), Phase 2 (thread safety, §51.6), Phase 3 (kinematic dispatch consolidation, §51.7), Phase 4 (kinematic policy on structural elements, §51.8), Phase 5 (corotational beam formulation, §51.9), and Phase 6 (state separation, arena allocator, and dynamic infrastructure, §51.10) have been implemented and verified. All six phases build with `-Werror`, pass the full CTest regression (45/47, same two pre-existing failures), and the corotational dynamic RC building example (§51.11) demonstrates the complete analysis pipeline.

51.6 Phase 2 Implementation: Thread-Safe Constitutive Relations

51.6.1 Problem Statement

Three inelastic constitutive relation classes used `mutable` member variables to implement a performance cache: after `compute_response(`ε`)` populates the stress and tangent, a subsequent call to `tangent(`ε`)` with the same strain can return the cached tangent without re-running the integration algorithm.

The affected classes were:

- `PlasticityRelation<Policy, YieldF, Hardening, Flow, YieldFn, ReturnAlg>`
- `KentParkConcrete`
- `MenegottoPintoSteel`

Each declared four `mutable` cache members:

```
mutable ConjugateT  last_stress_{};
mutable TangentT    last_tangent_{};
mutable bool        cache_valid_{false};
mutable StrainVecT  last_strain_cache_{...};
```

This pattern causes two problems:

1. **Thread safety:** Methods marked `const` mutate shared state without synchronization. In a parallel assembly loop, two threads evaluating the same relation concurrently could produce data races (undefined behavior under the C++ memory model).

2. **Semantic dishonesty:** A `const` method that writes to `mutable` members violates the principle that `const` means "logically observable state does not change." The cache *is* observable (it changes the return path of `tangent()`).

51.6.2 Why the Cache Was Unnecessary

All three classes satisfy `ExternallyStateDrivenConstitutiveRelation` (Level 3 concept). When used through `MaterialInstance<Relation>`, the 2-argument overloads are selected:

```
// MaterialInstance:
if constexpr (ExternallyStateDrivenConstitutiveRelation<Relation>) {
    return relation_->compute_response(k, this->algorithmic_state());
    return relation_->tangent(k, this->algorithmic_state());
}
```

These 2-argument overloads are purely functional—they never read or write the cache. The 1-argument overloads (which do use the cache) are legacy fallbacks that are never exercised in production.

51.6.3 Scope of Changes

For each of the three classes:

1. Removed the four `mutable` cache member declarations.

2. Simplified `compute_response(const KinematicT&)` to call the integration kernel and return the result directly, without writing to the cache.

3. Simplified `tangent(const KinematicT&)` to always recompute (no cache-hit check).

4. Removed `cache_valid_ = false` from `update()`.

The 2-argument overloads and the `commit()` method were already cache-free and required no changes.

51.6.4 Verification

- **Build:** 8 recompiled targets, zero warnings (`-Werror`).

- **CTest:** 45/47 passed (same 2 pre-existing failures).

- **Grep:** zero remaining `mutable` in `PlasticityRelation.hh`, `KentParkConcrete.hh`, and `MenegottoPintoSteel.hh`.

- Key plasticity tests passed: `plasticity_composition`, `material_strategy`, `phase4_hysteretic_cycle` `rc_fiber_frame_nonlinear`, `vertical_slice_gate`, `nonlinear_validation`.

51.7 Phase 3 Implementation: Kinematic Dispatch Consolidation

51.7.1 Problem Statement

The type-erased model classes in `Material.hh` (`OwningMaterialModel`, `NonOwningMaterialConstModel`, `NonOwningMaterialModel`) each override `compute_response()`, `tangent()`, and `commit()` for the full `ConstitutiveKinematics<dim>` argument. Every override repeated an identical `if constexpr` block:

```
if constexpr (requires { integrator.method(material, kin); }) {
    return integrator.method(material, kin);
} else {
    return integrator.method(
        material,
        continuum::make_kinematic_measure<StateVariableT>(kin));
}
```

This check prefers the continuum-aware integrator overload when available and falls back to the reduced kinematic measure otherwise. The pattern appeared **eight times** across the three model classes, tripling the maintenance burden and the risk of inconsistent modifications.

51.7.2 Solution: Dispatch Helper Functions

Three free-function templates were introduced inside `namespace impl`, immediately before the model class definitions:

`dispatch_response` Dispatches `integrator.compute_response(material, kin)`.

`dispatch_tangent` Dispatches `integrator.tangent(material, kin)`.

`dispatch_commit` Dispatches `integrator.commit(material, kin)` (`void` return).

Each helper is templated on `StateVariableT`, `IntegratorT`, `MaterialT`, and the spatial dimension `Dim`. The callers pass their integrator and material by reference (value semantics for the owning model, dereferenced pointers for the non-owning models):

```
// OwningMaterialModel
return dispatch_response<StateVariableT>(integrator_, material_, kin);

// NonOwningMaterialModel
return dispatch_response<StateVariableT>(*integrator_, *material_, kin);
```

51.7.3 Scope of Changes

- **File modified:** `src/materials/Material.hh`.
- **Lines removed:** 8 `if constexpr` blocks (≈72 lines of boilerplate).
- **Lines added:** 3 dispatch helpers (≈45 lines, single source of truth).
- **Net reduction:** ≈27 lines.
- No changes to the public API, concept hierarchy, or `ConstitutiveIntegrator` implementations.

51.7.4 Verification

- **Build:** 12 recompiled targets, zero warnings (`-Werror`).
- **CTest:** 45/47 passed (same 2 pre-existing failures).
- All continuum-path tests passed: `snes_hyperelastic`, `tl_integration`, `updated_lagrangian`, `finite_strain_damage`, `continuum_local_problem`.
- All structural-path tests passed: `beam_element`, `beam_n_element`, `rc_fiber_frame_nonlinear`, `nonlinear_validation`.

51.8 Phase 4 Implementation: Kinematic Policy on Structural Elements

51.8.1 Problem Statement

The `BeamElement` class hard-coded its kinematic assumptions: the element frame (rotation matrix $\mathbf{R}$ and length L) was computed once from the reference configuration and never updated, the global-to-local transformation was a fixed block-diagonal rotation $\mathbf{T} = \text{blockdiag}(\mathbf{R}^T, \mathbf{R}^T)$, and no geometric stiffness contribution was possible.

This prevented compile-time selection of alternative formulations (e.g., corotational or updated-Lagrangian beams) without duplicating the entire element class—a gap already solved for continuum elements by the `KinematicPolicy` template parameter in `ContinuumElement<MaterialPolicy, ndof, KinematicPolicy>`.

51.8.2 Design: `BeamKinematicPolicyConcept`

A new header `src/elements/BeamKinematicPolicy.hh` introduces a minimal concept and two concrete policies:

`beam::BeamKinematicPolicyConcept`. A policy type `P` must expose two `static constexpr bool` traits:

- `P::is_geometrically_linear` — controls whether the element frame is fixed or updated each iteration.
- `P::needs_geometric_stiffness` — controls whether a geometric stiffness $\mathbf{K}_\sigma$ is appended to the tangent.

`beam::FrameData<Dim>`. A lightweight result struct carrying $\mathbf{R} \in \mathbb{R}^{d\times d}$ and $L \in \mathbb{R}$.

`beam::SmallRotation`. Default policy; preserves the original behavior:

- `compute_frame<Dim>(x0, x1)`: one-time computation from reference node coordinates. 2D: $\mathbf{e}_1 = (x_1 - x_0)/L$, $\mathbf{e}_2 = 90°$ rotation. 3D: Gram–Schmidt with a reference vector.
- `update_frame`: identity (returns the reference frame unchanged).
- `extract_local_dofs`: $\mathbf{u}_{\text{loc}} = \mathbf{T}\,\mathbf{u}_{\text{glob}}$.

`beam::Corotational`. Crisfield-style CR policy (Phase 5, below).

Both policies satisfy a `static_assert` against the concept at the point of definition.

51.8.3 Template Signature Change

The `BeamElement` class template gains a third parameter with a default:

```
template <typename BeamPolicy,
          std::size_t Dim = BeamPolicy::dim,
          typename KinematicPolicy = beam::SmallRotation,
          typename AsmPolicy = assembly::DirectAssembly>
class BeamElement { ... };
```

Because `KinematicPolicy` has a default, all existing instantiations compile unchanged:

```
BeamElement<TimoshenkoBeam2D, 2>   // SmallRotation, DirectAssembly
BeamElement<TimoshenkoBeam3D, 3>   // SmallRotation, DirectAssembly
```

51.8.4 Internal Refactoring

The two formerly private members `R_` and `length_` were replaced by two `beam::FrameData<Dim>` structs:

`frame0_`: Reference-configuration frame, computed once in `compute_frame()` and immutable thereafter.

`frame_n_`: Current-configuration frame. For `SmallRotation` this is always identical to `frame0_`; for `Corotational` it is recomputed at each Newton iteration via `update_current_frame()`.

Key method changes:

- `compute_frame()` delegates to `KinematicPolicy::compute_frame<Dim>(x`$_0$`, x`$_1$`)` and stores the result in both `frame0_` and `frame_n_`.
- A new helper `update_current_frame(u_e)` extracts nodal coordinates and displacements, calls `KinematicPolicy::update_frame<Dim>()`, and stores the result in `frame_n_`.
- `compute_internal_forces()` now conditionally calls `update_current_frame()` via `if constexpr (!KinematicPolicy::is_geometrically_linear)`, followed by `KinematicPolicy::extrac` instead of a raw $\mathbf{T} \cdot \mathbf{u}$.
- `inject_tangent_stiffness()` follows the same guard for the frame update and appends the geometric stiffness when `KinematicPolicy::needs_geometric_stiffness` is true.
- `commit_material_state()` mirrors the same conditional frame update and local-DOF extraction.
- Shape-function derivatives `dN1_ds()`, `dN2_ds()` use `frame_n_.length` so that `SmallRotation` keeps the reference length and `Corotational` uses the current length.
- Accessors `element_length()` and `rotation_matrix()` now read from `frame_n_`. New accessors `reference_frame()` and `current_frame()` expose the full `FrameData` bundles.

51.8.5 Verification

- **Build:** 44 recompiled targets, zero warnings (`-Werror`, clang++-20, C++23).
- **CTest:** 45/47 passed (same 2 pre-existing mesh-file failures).
- All beam tests passed: `beam_element`, `beam_n_element`, `rc_fiber_frame_nonlinear`, `nonlinear_validation`.

51.9 Phase 5 Implementation: Corotational Beam Formulation

51.9.1 Formulation Overview

The corotational (CR) approach decomposes element motion into a rigid-body component and a deformational component. At each Newton iteration:

1. **Current chord.** Compute the deformed node positions $\mathbf{x}_i^n = \mathbf{X}_i + \mathbf{u}_i$ and form the current chord direction $\mathbf{e}_1^n = (\mathbf{x}_1^n - \mathbf{x}_0^n)/l_n$, where $l_n = \|\mathbf{x}_1^n - \mathbf{x}_0^n\|$ is the current length.

2. **Corotated frame.** Build the rotation matrix $\mathbf{R}^n$ from $\mathbf{e}_1^n$ and a smoothly evolved transverse axis. In 3D, the reference $\mathbf{e}_2^0$ is projected onto the plane perpendicular to $\mathbf{e}_1^n$ and renormalized.

3. **Deformational DOFs.** Extract local DOFs by filtering the rigid rotation of the chord:

   2D (6 DOFs): $u_1^{\text{def}} = 0$, $v_1^{\text{def}} = 0$, $\theta_1^{\text{def}} = \theta_1 - \alpha$ (rigid chord rotation α), $u_2^{\text{def}} = l_n - l_0$, $v_2^{\text{def}} = 0$, $\theta_2^{\text{def}} = \theta_2 - \alpha$.

   3D (12 DOFs): Translate into the corotated frame; subtract the incremental rigid rotation from nodal rotations via $\boldsymbol{\theta}_i^{\text{loc}} = \mathbf{R}^n \boldsymbol{\theta}_i^{\text{glob}} - \boldsymbol{\delta\theta}$, where $\boldsymbol{\delta\theta}$ is the axial vector of $\mathbf{R}^n(\mathbf{R}^0)^T$.

4. **Local response.** Evaluate the small-rotation Timoshenko formulation with the deformational DOFs and the current length l_n (the B matrix shape-function derivatives use l_n instead of l_0).

5. **Global forces.** Transform back via the corotational projector.

6. **Geometric stiffness.** Append $\mathbf{K}_\sigma$ from the axial force N:

$$(\mathbf{K}_\sigma)_{ij} = \frac{N}{l_n}\,\delta_{v_i v_j}\ ,$$

   acting on the transverse DOF pairs (v_1, v_2) in 2D and (u_{y_1}, u_{y_2}), (u_{z_1}, u_{z_2}) in 3D.

References: Crisfield, *Non-Linear Finite Element Analysis of Solids and Structures*, Vol. 1, §7.3; Battini & Pacoste (2002).

51.9.2 Implementation in `beam::Corotational`

The policy provides four static template functions:

`compute_frame<Dim>`: Delegates to `SmallRotation::compute_frame` for the initial (reference) frame computation.

`update_frame<Dim>`: Computes $\mathbf{x}_i^n = \mathbf{X}_i + \mathbf{u}_i$ and rebuilds the element chord. In 3D, the reference $\mathbf{e}_2$ is projected and renormalized. Degeneracy is handled by falling back to the reference-vector algorithm.

`extract_local_dofs<Dim, TotalDofs>`: Filters the rigid chord rotation:

- 2D: computes $\alpha = \arctan(\sin\alpha, \cos\alpha)$ from $\mathbf{e}_1^n \cdot \mathbf{e}_1^0$ and the cross-product, then $\theta_i^{\text{def}} = \theta_i^{\text{glob}} - \alpha$.
- 3D: computes $\mathbf{R}_{\text{rigid}} = (\mathbf{R}^n)^T\,\mathbf{R}^0$, extracts the axial vector $\boldsymbol{\delta\theta}$ from the skew-symmetric part, and subtracts it from each node's rotations expressed in the corotated frame.

`geometric_stiffness<Dim, TotalDofs, NumStrains>`: Builds $\mathbf{K}_\sigma$ from the axial force component of the section force vector. 2D: 4×4 sub-block on (v_1, v_2). 3D: two 4×4 sub-blocks on (u_{y_1}, u_{y_2}) and (u_{z_1}, u_{z_2}).

51.9.3 Integration with BeamElement

The BeamElement methods use if constexpr guards keyed to the policy traits to enable CR-specific code paths at zero cost when SmallRotation is selected:

```
if constexpr (!KinematicPolicy::is_geometrically_linear) {
    update_current_frame(u_e);  // recompute R_n, l_n
}
auto u_def = KinematicPolicy::template
    extract_local_dofs<Dim, total_dofs>(...);
...
if constexpr (KinematicPolicy::needs_geometric_stiffness) {
    K_local += KinematicPolicy::template
        geometric_stiffness<Dim, total_dofs, num_strains>(...);
}
```

For SmallRotation, the compiler eliminates these branches entirely, producing the same binary as the original hard-coded element.

51.9.4 Scope of Changes

- **New file:** src/elements/BeamKinematicPolicy.hh — beam::FrameData<Dim>, BeamKinematicPolicy SmallRotation (88 lines), Corotational (255 lines).
- **Modified file:** src/elements/BeamElement.hh — template signature extended, R_/length_ replaced by frame0_/frame_n_, five methods refactored to delegate to the policy.
- **No test files modified:** existing instantiations pick up SmallRotation by default.

51.9.5 Verification

- **Build:** 44 recompiled targets, zero warnings (-Werror).
- **CTest:** 45/47 passed (same 2 pre-existing failures: cantilever_benchmark and snes_gmsh_pipeline, both missing .msh files).
- All beam-path tests passed: beam_element, beam_n_element, rc_fiber_frame_nonlinear, nonlinear_validation.
- **Note on ShellElement:** The shell element (MITC4 Mindlin–Reissner) was not refactored in this phase. A corotational shell formulation requires additional machinery (mid-surface rotation parametrization, drilling DOF stabilization) and is deferred to a future phase.

51.10 Phase 6 Implementation: State Separation, Arena Allocator, and Dynamic Infrastructure

Phase 6 is the final convergence phase. It addresses Deficiencies 4 and 6 from the catalogue (§**??**): (i) the conflation of kinematic state with internal constitutive variables changes, and (ii) the heap-allocation overhead of per-integration-point Material<P> objects. Additionally, it adds the mass-matrix infrastructure necessary to enable DynamicAnalysis with structural elements.

51.10.1 State Separation: `InternalStateOf` Trait

The library's constitutive pipeline identifies "state" with the kinematic measure (`StateVariableT` ≡ `KinematicT`). For elastic models this is sufficient, but inelastic relations carry persistent internal variables (plastic strain, damage) stored inside the relation object itself, invisible to the element layer.

Phase 6 introduces a compile-time trait to decouple these roles:

```
// Primary template: if R has no internal state, return NoInternalState.
template <typename R> struct InternalStateOf {
    using type = NoInternalState;
};

// Specialization: R::InternalVariablesT exists → use it.
template <typename R>
  requires requires { typename R::InternalVariablesT; }
struct InternalStateOf<R> {
    using type = typename R::InternalVariablesT;
};

template <typename R>
using InternalStateOf_t = typename InternalStateOf<R>::type;

template <typename R>
concept HasSeparatedInternalState =
    !std::same_as<InternalStateOf_t<R>, NoInternalState>;
```

This is backward-compatible: existing elastic relations yield `NoInternalState`; existing inelastic relations that already define `InternalVariablesT` are detected automatically.

51.10.2 Arena Allocator: `MonotonicArena` and `ArenaAllocator<T>`

For large meshes with millions of integration points, each `Material<P>` incurs two heap allocations (one `shared_ptr` for the relation, one `unique_ptr` for the pimpl). `MonotonicArena` pre-allocates a contiguous buffer and provides $O(1)$ bump-pointer allocation:

```
class MonotonicArena {
    std::unique_ptr<std::byte[]> buffer_;
    std::size_t capacity_, offset_{0};
public:
    explicit MonotonicArena(std::size_t bytes);
    void* allocate(std::size_t size, std::size_t align);
    template <typename T, typename... Args>
    T* construct(Args&&... args);
    void reset() noexcept;   // reclaim all memory in O(1)
};
```

An STL-compatible adapter `ArenaAllocator<T>` wraps the arena for use with `std::vector` or any allocator-aware container. A convenience factory `bulk_create_materials()` creates N `Material<P>` objects from a single arena allocation.

51.10.3 Mass Matrix Support for Structural Elements

The `DynamicAnalysis` solver requires a consistent mass matrix ($\mathbf{M}$). Prior to Phase 6, only `ContinuumElement` had mass-matrix support; `BeamElement` and `ShellElement` provided no such

method, and the `StructuralElement` wrapper had no virtual slot for it.

Phase 6 adds:

1. A `density_` member, `set_density()`, and `density()` on both `BeamElement` and `ShellElement`.
2. A `compute_consistent_mass_matrix()` method on each:
   - **Beam:** $M_e = \rho \sum_{\text{gp}} w \cdot dm \cdot \mathbf{N}^\top \mathbf{N}$, where $\mathbf{N}$ is the 3×12 translational shape-function matrix (Hermite interpolation), transformed to the global frame via $\mathbf{T}^\top M_{\text{loc}} \mathbf{T}$.
   - **Shell:** same pattern but with 3×24 translational $H(a)$ shape functions for 4 nodes $\times$ 6 DOFs.
3. `inject_mass(Mat M)` on both element types: assembles M_e into the PETSc global mass matrix using `MatSetValuesLocal`.
4. In `StructuralElement` (type-erased wrapper): virtual slots `density()`, `set_density()`, `inject_mass()` with SFINAE bridges in the `Model<T>` layer.

51.10.4 Standalone-Vector Interface for DynamicAnalysis

The `DynamicAnalysis` solver uses a three-phase parallel assembly pattern that operates on `Eigen::VectorXd` / `Eigen::MatrixXd` objects rather than PETSc vectors and matrices directly. This requires:

- `extract_element_dofs(Vec)` → `Eigen::VectorXd`
- `compute_internal_force_vector(const VectorXd&)` → `VectorXd`
- `compute_tangent_stiffness_matrix(const VectorXd&)` → `MatrixXd`
- `get_dof_indices()` → `const vector<PetscInt>&`

These methods were already present in `ContinuumElement` but absent from `BeamElement` and `ShellElement`. Phase 6 adds them to both structural element types and exposes them through the `StructuralElement` virtual interface with SFINAE guards for elements that do not provide them.

51.10.5 Verification

- **Build:** 80 targets, zero warnings (`-Werror`).
- **CTest:** 45/47 passed (same 2 pre-existing failures).
- The corotational dynamic RC building example (§51.11) exercises all Phase 6 additions: density setting, mass assembly, standalone-vector interface, and time integration.

51.11 Corotational Dynamic RC Building Example

This section documents the main executable example that showcases the complete analysis pipeline: nonlinear fibre sections, corotational kinematics, consistent mass matrices, Rayleigh damping, and VTK time-series output.

51.11.1 Structural Configuration

The model is a regular 5-storey reinforced-concrete building:

Parameter	Value
Plan grid	4×3 axes, $6\,\mathrm{m} \times 5\,\mathrm{m}$ bays
Stories / height	5 / 3.20 m each ($H_{\mathrm{tot}} = 16\,\mathrm{m}$)
Nodes	72
Columns ($0.45 \times 0.45\,\mathrm{m}$)	60 (corotational)
Beams ($0.30 \times 0.60\,\mathrm{m}$)	85 (corotational)
Slabs ($t = 0.15\,\mathrm{m}$)	30 (elastic MITC4)

51.11.2 Materials

- **Columns:** RC fibre section. Concrete: Kent–Park confined ($f'_c = 35\,\mathrm{MPa}$, volumetric ratio $\rho_s = 0.015$, $f_{yh} = 420\,\mathrm{MPa}$, tie spacing $s_h = 0.10\,\mathrm{m}$) plus unconfined cover. Steel: Menegotto–Pinto ($E_s = 200\,\mathrm{GPa}$, $f_y = 420\,\mathrm{MPa}$, $b = 0.01$), 8 bars $\phi 25\,\mathrm{mm}$.
- **Beams:** RC fibre section. Unconfined Kent–Park ($f'_c = 30\,\mathrm{MPa}$) for all concrete patches. Menegotto–Pinto steel, 6 bars $\phi 20\,\mathrm{mm}$.
- **Slabs:** Elastic isotropic Mindlin shell ($E = 28\,\mathrm{GPa}$, $\nu = 0.20$).

51.11.3 Kinematic Formulation

All frame elements (columns and beams) use the `beam::Corotational` policy from Phase 5. This enables large displacements and rotations at the global level while preserving the Timoshenko beam B-matrix in the co-rotated local frame:

$$\mathbf{f}_{\mathrm{int}}^{\mathrm{global}} = \mathbf{T}(\theta_n)^\top \sum_{\mathrm{gp}} w \cdot dm \cdot \mathbf{B}_{\mathrm{loc}}^\top \boldsymbol{\sigma}(\mathbf{B}_{\mathrm{loc}}\,\mathbf{u}_{\mathrm{loc}}) \tag{51.1}$$

where $\mathbf{T}(\theta_n)$ is the element rotation matrix updated at each Newton iteration from the current nodal positions.

51.11.4 Dynamic Parameters

Parameter	Value
Density (RC)	$2400\,\mathrm{kg/m^3} = 2.4 \times 10^{-3}\,\mathrm{MN\,s^2/m^4}$
Damping ratio ξ	5%
Rayleigh ω_1	$12.57\,\mathrm{rad/s}$ ($T_1 = 0.50\,\mathrm{s}$)
Rayleigh ω_3	$62.83\,\mathrm{rad/s}$ ($T_3 = 0.10\,\mathrm{s}$)
Time integrator	Generalised-α (`TSALPHA2`, $\rho_\infty = 0.9$)
Time step Δt	$0.005\,\mathrm{s}$
Total time T	$5.0\,\mathrm{s}$ ($\sim$1000 steps)

Rayleigh damping is computed as $\mathbf{C} = \alpha_M \mathbf{M} + \beta_K \mathbf{K}_0$, with coefficients derived from the two target frequencies and the damping ratio:

$$\alpha_M = \frac{2\,\xi\,\omega_1\omega_3}{\omega_1 + \omega_3}, \qquad \beta_K = \frac{2\,\xi}{\omega_1 + \omega_3}. \tag{51.2}$$

51.11.5 Loading Protocol

1. **Gravity:** constant slab self-weight pressure $p_z = -7.5\,\mathrm{kN/m^2}$, applied as consistent nodal forces from shell quadrature.

2. **Cyclic lateral:** sinusoidal excitation at each story level, triangularly distributed:

$$f_x^{\mathrm{lat}}(t) = F_0 \cdot \frac{\ell}{N_s} \cdot \mathrm{envelope}(t) \cdot \sin\!\Big(\frac{2\pi t}{T_{\mathrm{exc}}}\Big), \tag{51.3}$$

   where $F_0 = 0.10\,\mathrm{MN}$, $T_{\mathrm{exc}} = 0.50\,\mathrm{s}$ (near T_1 to amplify response), ℓ = story level, and $\mathrm{envelope}(t) = \min(t/t_{\mathrm{ramp}},\, 1)$ with $t_{\mathrm{ramp}} = 1\,\mathrm{s}$.

51.11.6 Solution Strategy

The equation of motion

$$\mathbf{M}\,\ddot{\mathbf{u}} + \mathbf{C}\,\dot{\mathbf{u}} + \mathbf{f}_{\mathrm{int}}(\mathbf{u}) = \mathbf{f}_{\mathrm{ext}}(t) \tag{51.4}$$

is solved via PETSc's implicit second-order time stepping with the I_2 interface. At each time step, PETSc performs a nonlinear solve (Newton with line search) on the residual

$$\mathbf{F}(t, \mathbf{u}, \dot{\mathbf{u}}, \ddot{\mathbf{u}}) = \mathbf{M}\ddot{\mathbf{u}} + \mathbf{C}\dot{\mathbf{u}} + \mathbf{f}_{\mathrm{int}}(\mathbf{u}) - \mathbf{f}_{\mathrm{ext}}(t) = \mathbf{0}, \tag{51.5}$$

and the Jacobian

$$\mathbf{J} = \mathbf{K}_t(\mathbf{u}) + v\,\mathbf{C} + a\,\mathbf{M}, \tag{51.6}$$

where v and a are shift parameters provided by the time integrator.

51.11.7 VTK Time-Series Output

Every 20th converged step triggers a VTK snapshot via `StructuralVTMExporter`, producing multi-block `.vtm` files (beam axis, surface, fibre, section sub-blocks + shell surface). A `PVDWriter` collects all timesteps into a single `.pvd` collection file for ParaView animation.

Chapter 52

Corotational Dynamic RC Building Example

This chapter documents the transition of the five-story RC building example from small-rotation static analysis (Chapter 24) to a *corotational dynamic* formulation. Three major topics are covered:

1. the corotational beam kinematics and their integration into the existing structural pipeline;
2. a critical bug found and fixed in the VTK displacement-field reconstruction for corotational elements;
3. an analysis of the kinematic incompatibility between linear Mindlin–Reissner shells and corotational beams, and its consequences for numerical stability.

52.1 Motivation and Scope

The small-rotation formulation used in Chapter 24 treats each beam element as geometrically linear: the transformation matrix $\mathbf{T}$ is evaluated once from the reference configuration and is never updated. This is adequate for load levels where each storey drift remains well below 1%. For seismic or extreme-wind scenarios, however, the building can develop inter-storey drifts of 2–5% or more, at which point the geometric nonlinearity encoded in P-Δ effects and large rotations becomes essential.

The current chapter therefore upgrades the frame elements to the `beam::Corotational` kinematic policy while keeping the same material model (nonlinear fiber sections), the same global topology, and the same `DynamicAnalysis` PETSc time-stepping infrastructure. The floor slabs remain elastic Mindlin–Reissner shells.

52.2 Corotational Beam Kinematics

52.2.1 Conceptual Framework

The corotational formulation decomposes the total motion of a beam element into:

1. a *rigid-body* component (translation and rotation of the element chord), and
2. a *deformational* component (local strains measured in the corotated frame).

The fundamental idea is that a small-strain B-matrix evaluated in the *rotating* local frame captures effectively the same physics as a geometrically exact formulation, at a fraction of the implementation complexity.

Let $\mathbf{x}_0, \mathbf{x}_1 \in \mathbb{R}^3$ be the reference nodal positions and $\mathbf{u}_0, \mathbf{u}_1$ the corresponding global displacement vectors. The *current* nodal positions are

$$\hat{\mathbf{x}}_i = \mathbf{x}_i + \mathbf{u}_i, \qquad i = 0, 1. \tag{52.1}$$

The current chord vector is $\hat{\mathbf{d}} = \hat{\mathbf{x}}_1 - \hat{\mathbf{x}}_0$, with current element length

$$l_n = \|\hat{\mathbf{d}}\|. \tag{52.2}$$

52.2.2 Corotated Frame Update

In three dimensions the corotated frame $\mathbf{R}_n$ is constructed as follows:

$$\mathbf{e}_1 = \frac{\hat{\mathbf{d}}}{l_n}, \tag{52.3}$$

$$\tilde{\mathbf{e}}_2 = \mathbf{e}_{2,\text{ref}} - \left(\mathbf{e}_{2,\text{ref}} \cdot \mathbf{e}_1\right) \mathbf{e}_1, \tag{52.4}$$

$$\mathbf{e}_2 = \frac{\tilde{\mathbf{e}}_2}{\|\tilde{\mathbf{e}}_2\|}, \tag{52.5}$$

$$\mathbf{e}_3 = \mathbf{e}_1 \times \mathbf{e}_2. \tag{52.6}$$

Here $\mathbf{e}_{2,\text{ref}} = \mathbf{R}_0^\top \mathbf{i}_2$ is the reference cross-section y-axis. The projection onto the plane normal to the current chord ensures smooth frame evolution even for moderate rotations. In the degenerate case $\|\tilde{\mathbf{e}}_2\| < 10^{-12}$ the algorithm falls back to the reference-vector construction.

In the implementation, frame update is *embedded* inside every element method that requires the current configuration:

```
// BeamElement.hh
Eigen::VectorXd compute_internal_force_vector(const Eigen::VectorXd& u_e
    )
{
    if constexpr (!KinematicPolicy::is_geometrically_linear) {
        update_current_frame(u_e);   // recompute R_n from (x+u)
    }
    auto T = transformation_matrix();    // T = blkdiag(R_n, R_n)
    auto u_loc = KinematicPolicy::extract_local_dofs(u_g, frame0_,
        frame_n_, T);
    // ... B_local, sigma, f_loc ...
    return (T.transpose() * f_loc).eval();
}
```

This design ensures the frame is self-consistently updated at every Newton iteration without requiring explicit calls from the analysis driver.

52.2.3 Deformational DOF Extraction

The `beam::Corotational::extract_local_dofs` function strips the rigid-body motion from the global DOFs. For a 3D two-node beam with 12 global DOFs $[\mathbf{u}_1, \boldsymbol{\theta}_1, \mathbf{u}_2, \boldsymbol{\theta}_2]$:

$$\mathbf{u}_{\text{def}} = \begin{bmatrix} 0 \\ 0 \\ 0 \\ \boldsymbol{\theta}_{1,\text{loc}} - \boldsymbol{\alpha} \\ \Delta l \\ 0 \\ 0 \\ \boldsymbol{\theta}_{2,\text{loc}} - \boldsymbol{\alpha} \end{bmatrix}, \tag{52.7}$$

where $\Delta l = l_n - l_0$ is the axial elongation, and $\boldsymbol{\alpha}$ is the rigid-body rotation vector extracted from the relative rotation between $\mathbf{R}_n$ and $\mathbf{R}_0$.

Crucially, node 1 has *zero* translational deformation (it is the local origin) and node 2 has only an axial component Δl. This has fundamental consequences for post-processing, as discussed in section 52.4.

52.2.4 Tangent Stiffness and Geometric Contribution

The tangent stiffness in global coordinates is

$$\mathbf{K}_t = \mathbf{T}^\mathsf{T} \underbrace{\sum_{g=1}^{n_g} w_g \, |J|_g \, \mathbf{B}_g^\mathsf{T} \, \mathbf{C}_{t,g} \, \mathbf{B}_g}_{\mathbf{K}_{\mathrm{loc}}} \mathbf{T} + \mathbf{T}^\mathsf{T} \, \mathbf{K}_\sigma \, \mathbf{T}, \tag{52.8}$$

where $\mathbf{K}_\sigma$ is the geometric stiffness due to the element resultants. Both terms are computed in `BeamElement::compute_tangent_stiffness_matrix`; the geometric stiffness is enabled by the compile-time flag `KinematicPolicy::needs_geometric_stiffness = true` for the corotational policy.

52.3 Dynamic Analysis Configuration

The dynamic analysis uses the same `DynamicAnalysis` class documented in Chapter 49, with PETSc's `TSALPHA2` generalized-α integrator.

52.3.1 Loading and Ramps

To avoid dynamic shock and ensure a gradual transition to the loaded state, the external force function is defined as

$$\mathbf{f}_{\mathrm{ext}}(t) = g(t) \, \mathbf{f}_{\mathrm{grav}} + h(t) \, \sin\!\left(\tfrac{2\pi t}{T_{\mathrm{exc}}}\right) \mathbf{f}_{\mathrm{lat}}, \tag{52.9}$$

with the ramp functions

$$g(t) = \min\!\left(\tfrac{t}{t_{\mathrm{grav}}},\ 1\right), \qquad h(t) = \begin{cases} 0 & \text{if } t < t_{\mathrm{grav}}, \\ \min\!\left(\dfrac{t - t_{\mathrm{grav}}}{t_{\mathrm{lat}} - t_{\mathrm{grav}}},\ 1\right) & \text{otherwise.} \end{cases} \tag{52.10}$$

The gravity ramp $g(t)$ linearly increases over $t_{\mathrm{grav}} = 1.0\,\mathrm{s}$ to avoid a step function in the mass-proportional gravity load. The lateral cyclic loading $h(t)$ is delayed until the gravity ramp completes and then smoothly increases over the interval $[t_{\mathrm{grav}},\ t_{\mathrm{lat}}]$ with $t_{\mathrm{lat}} = 1.5\,\mathrm{s}$.

52.3.2 Time-Integration Parameters

A technical detail of the implementation is that the TS-specific options are set *programmatically after* `solver.setup()`, because `TSSetFromOptions()` (called internally by `setup()`) would otherwise overwrite them from the PETSc options database:

```
solver.setup();
{
    TS ts = solver.get_ts();
    TSAlpha2SetRadius(ts, 0.9);
    TSAdapt adapt;
    TSGetAdapt(ts, &adapt);
    TSAdaptSetType(adapt, TSADAPTNONE);
    TSSetMaxSNESFailures(ts, 5);
}
```

Table 52.1: Dynamic analysis parameters for the corotational RC building.

Parameter	Value	Notes
Spectral radius ρ_∞	0.9	High-frequency dissipation
Time step Δt	0.005 s	1000 steps for $T_f = 5\,\mathrm{s}$
Adaptive stepping	off	`TSADAPTNONE`
Max SNES failures	5	Allow temporary divergence
KSP type	`preonly`	Direct solve
PC type	`lu`	LU factorization
Damping	Rayleigh	$\xi = 5\%$ at $(T_1, T_3) = (0.5,\, 0.1)\,\mathrm{s}$
Lateral amplitude	0.005 MN	Per node per storey
Excitation period	0.5 s	Near first-mode period

52.4 VTK Displacement Reconstruction for Corotational Beams

52.4.1 The Problem: Disconnected Elements in Warp-by-Vector

When the VTK multi-block exporter was first used with corotational beam elements, ParaView's *Warp by Vector* filter showed every beam element as a disconnected fragment: each element appeared to deform independently, with gaps at every shared node.

The root cause lies in how displacement was reconstructed for the VTK carrier. The original code in `StructuralVTMExporter` computed displacement at a sampling point ξ as

$$\mathbf{u}_{\mathrm{vis}}(\xi) = \mathbf{R}_n^{\mathsf{T}} \left[\mathbf{u}_{\mathrm{center,loc}}(\xi) + \boldsymbol{\theta}_{\mathrm{loc}}(\xi) \times \mathbf{d}_{\mathrm{offset}}\right], \tag{52.11}$$

where $\mathbf{u}_{\mathrm{center,loc}}$ is the centerline translation in the *local corotated frame* and $\boldsymbol{\theta}_{\mathrm{loc}}$ is the local rotation vector.

For `beam::SmallRotation`, $\mathbf{u}_{\mathrm{center,loc}}$ contains the full translational field (small-rotation $\mathbf{T}$ simply rotates global DOFs into the local frame). The formula $\mathbf{R}^{\mathsf{T}} \cdot \mathbf{u}_{\mathrm{loc}}$ correctly recovers the global displacement.

For `beam::Corotational`, however, $\mathbf{u}_{\mathrm{center,loc}}$ contains only the *deformational* part computed from eq. (52.7): node 1 translations are $(0, 0, 0)$ and node 2 translations are $(\Delta l, 0, 0)$. The rigid-body displacement has been deliberately stripped. Formula (52.11) therefore returns only the deformational contribution, which is typically several orders of magnitude smaller than the actual nodal displacement.

Since each element independently produces a tiny deformational displacement relative to its own corotated frame, the Warp filter offsets every element by a different vector — and the mesh *appears disconnected*.

52.4.2 The Fix: Global DOF Interpolation

The fix introduces a new method in `BeamElement`:

```
Eigen::Vector3d sample_displacement_global(double xi, Vec u_petsc) const
{
    Eigen::VectorXd u_e = extract_element_dofs(u_petsc);
    const double n1 = N1(xi), n2 = N2(xi);
    Eigen::Vector3d u_glob = Eigen::Vector3d::Zero();
    u_glob[0] = n1 * u_e[0] + n2 * u_e[6];
    u_glob[1] = n1 * u_e[1] + n2 * u_e[7];
    u_glob[2] = n1 * u_e[2] + n2 * u_e[8];
    return u_glob;
}
```

This method extracts the *global* element DOFs directly from the PETSc solution vector and interpolates them using the standard linear shape functions $N_1(\xi), N_2(\xi)$. Because these are the actual nodal displacements (not the corotation-filtered deformational DOFs), the resulting field is continuous across element boundaries.

At an off-axis sampling point with section offset $\mathbf{d}_{\text{off}} = (0, y, z)$, the corrected formula becomes

$$\mathbf{u}_{\text{vis}}(\xi, y, z) = \underbrace{N_1(\xi)\,\mathbf{u}_1 + N_2(\xi)\,\mathbf{u}_2}_{\text{rigid + deformational (global)}} + \underbrace{\mathbf{R}_n^{\mathsf{T}}\left[\boldsymbol{\theta}_{\text{loc}}(\xi) \times \mathbf{d}_{\text{off}}\right]}_{\text{section rotation contribution}}, \tag{52.12}$$

where $\mathbf{u}_1, \mathbf{u}_2$ are the global nodal displacement vectors. The first term captures the total (rigid + deformational) centerline motion; the second term adds the rotation-dependent offset that varies across the cross-section.

52.4.3 Affected Reconstruction Sites

The `StructuralVTMExporter` produces five VTK blocks for each structural model. Table 52.2 lists every displacement reconstruction site that was corrected.

Table 52.2: Displacement reconstruction sites corrected for corotational compatibility. "Single" refers to the homogeneous-element exporter; "mixed" to the `StructuralElement`-based exporter.

Block	Exporter	Method	Description
axis	single	`append_station`	Centerline displacement via `sample_displacement_glob`
axis	mixed	`append_station`	Same—dispatched through `dispatch_supported_struc`
surface	single	`reconstruct_beam_point`	Off-axis displacement with section offset
surface	mixed	`reconstruct_beam_point`	Same—via `detail::reconstruct_beam_point`
sections	single	`reconstruct_beam_point`	Section profile points at each station
sections	mixed	`reconstruct_beam_point`	Same—dispatched
fibers	single	inline $\mathbf{R}^{\mathsf{T}} \cdot \mathbf{u}_{\text{loc}}$	Per-fiber displacement at Gauss points
fibers	mixed	inline $\mathbf{R}^{\mathsf{T}} \cdot \mathbf{u}_{\text{loc}}$	Same—dispatched

The fix for the surface and sections blocks was centralised in the `reconstruct_beam_point` helper function by adding an optional `Vec` parameter. When a non-null PETSc vector is provided and the element supports `sample_displacement_global`, the corrected formula (52.12) is used:

```
if constexpr (requires { element.sample_displacement_global(xi, u_petsc)
    ; }) {
    if (u_petsc) {
        out.displacement = element.sample_displacement_global(xi,
            u_petsc)
            + R.transpose() * theta.cross(offset_local);
    } else {
        out.displacement = R.transpose() * u_local;
    }
} else {
    out.displacement = R.transpose() * u_local;
}
```

The `if constexpr` / `requires` guard ensures zero overhead for formulations where the original reconstruction is correct (e.g. shells, small-rotation beams). The runtime null-check on the PETSc vector allows unit tests—which use a mock model with `state_vector() = nullptr`—to fall back transparently.

52.4.4 Type Dispatch for Corotational Elements

The mixed exporter's `dispatch_supported_structural` function, which performs runtime type recovery from `StructuralElement`, was extended with the corotational beam type:

```
// StructuralVTMExporter.hh -- dispatch_supported_structural
else if (auto* p = wrapped.template as<
    BeamElement<TimoshenkoBeam3D, 3, beam::Corotational>>()) {
    fn(*p);
}
```

Without this entry the exporter threw `std::runtime_error` because the element type name (including the full `beam::Corotational` template argument) did not match any registered concrete type.

52.5 Kinematic Incompatibility: Linear Shell vs. Corotational Beam

52.5.1 Diagnosis: Numerical Divergence in the Mixed Model

Despite correct convergence of SNES at each time step, the simulation exhibited growing displacements during the gravity ramp, with the maximum lateral displacement exceeding several metres within a fraction of a second—far beyond physically reasonable deformation for the applied load level.

Investigation revealed that the source of instability is not the corotational beam formulation itself, but rather the **kinematic incompatibility between the geometrically nonlinear beams and the geometrically linear shells** at shared nodes.

52.5.2 Root Cause Analysis

Table 52.3 contrasts the relevant kinematic assumptions.

Table 52.3: Kinematic behaviour comparison at shared beam-shell nodes.

Aspect	BeamElement (Corotational)	ShellElement (Linear)
Local frame $\mathbf{R}$	Updated every Newton iteration	Fixed at reference configuration
Strain measure	Corotational local (small in rotating frame)	Infinitesimal ($\boldsymbol{\varepsilon} = \mathbf{B}_0\,\mathbf{R}_0\,\mathbf{u}_e$)
Geometric stiffness $\mathbf{K}_\sigma$	Yes	No
Transformation $\mathbf{T}$	$\mathbf{T}(\mathbf{R}_n)$, updated	$\mathbf{T}(\mathbf{R}_0)$, fixed
$\mathbf{f}_{\text{int}}$ for large $\mathbf{u}_e$	Physically correct	Linearly extrapolated

The fundamental problem is that when the beams undergo large rotations, the shared nodes move significantly. The shell elements connected to those same nodes see large nodal displacement vectors $\mathbf{u}_e$, but compute their internal forces as

$$\mathbf{f}_{\text{int}}^{\text{shell}} = \mathbf{T}_0^{\mathsf{T}} \sum_g w_g\,|J|_g\,\mathbf{B}_g^{\mathsf{T}}\,\boldsymbol{\sigma}(\underbrace{\mathbf{B}_g\,\mathbf{T}_0\,\mathbf{u}_e}_{\text{linearly extrapolated strain}}). \tag{52.13}$$

For an elastic shell with stiffness matrix $\mathbf{D}$, this reduces to

$$\mathbf{f}_{\text{int}}^{\text{shell}} = \underbrace{\mathbf{T}_0^{\mathsf{T}}\Big(\sum_g w_g\,|J|_g\,\mathbf{B}_g^{\mathsf{T}}\,\mathbf{D}\,\mathbf{B}_g\Big)\mathbf{T}_0}_{\mathbf{K}_0}\,\mathbf{u}_e. \tag{52.14}$$

The internal force grows linearly with $\mathbf{u}_e$, without any geometric correction. Specifically:

- Rigid-body rotations of the shell generate *spurious* membrane and bending strains because the reference-frame B-matrix does not distinguish rotation from deformation.
- There is no geometric stiffness contribution from the shell, so any destabilising P-Δ effect at the beam-shell junction is not captured.
- The equilibrium at shared nodes is therefore inconsistent: the beam provides geometrically correct forces while the shell provides linearly extrapolated forces.

52.5.3 Physical Interpretation

Consider a storey slab that rigid-body translates laterally by $u_x = 50\,\text{mm}$ due to inter-storey drift. In the corotational beam formulation, this translation is absorbed by the frame update and produces no spurious strain. In the linear shell formulation, however, the same 50 mm lateral displacement of all four shell nodes generates a fictitious membrane strain of order

$$\varepsilon_{\text{spurious}} \approx \frac{u_x}{L_{\text{panel}}} = \frac{0.05}{6.0} \approx 8.3 \times 10^{-3}, \tag{52.15}$$

which for a Young's modulus $E \approx 28{,}000\,\text{MPa}$ yields a spurious membrane stress of $\sigma_{\text{spurious}} \approx 233\,\text{MPa}$—clearly nonphysical for an elastic slab subjected only to lateral drift.

The resulting spurious forces from the shell "push back" against the beam displacements, creating an artificial stiffening effect initially. As the beam elements rotate further and the shell forces grow linearly, the force imbalance can trigger oscillatory behaviour or outright divergence in the time integrator.

52.5.4 Formal Statement of the Incompatibility

More formally, the corotational beam's internal force satisfies the *objectivity* requirement:

$$\mathbf{f}_{\text{int}}^{\text{beam}}(\mathbf{Q}\,\mathbf{u}) = \mathbf{Q}\,\mathbf{f}_{\text{int}}^{\text{beam}}(\mathbf{u}) \tag{52.16}$$

for any superposed rigid-body rotation $\mathbf{Q}$, because the corotational filter removes $\mathbf{Q}$ before computing local strains.

The linear shell, in contrast, does not satisfy objectivity:

$$\mathbf{f}_{\text{int}}^{\text{shell}}(\mathbf{Q}\,\mathbf{u}) = \mathbf{K}_0\,\mathbf{Q}\,\mathbf{u} \neq \mathbf{Q}\,\mathbf{K}_0\,\mathbf{u} \quad \text{(in general)}. \tag{52.17}$$

At shared nodes, the global equilibrium requires

$$\mathbf{f}_{\text{int}}^{\text{beam}} + \mathbf{f}_{\text{int}}^{\text{shell}} + \mathbf{f}_{\text{inertia}} + \mathbf{f}_{\text{damping}} = \mathbf{f}_{\text{ext}}, \tag{52.18}$$

but the lack of objectivity in the shell term introduces *configuration-dependent* artificial forces that pollute the equilibrium. The magnitude of this pollution grows with the deviation from the reference configuration.

52.6 Resolution Strategies

Three paths can resolve the kinematic incompatibility:

Option A: Corotational shell formulation. Implement `beam::Corotational`-style frame update for `ShellElement`: at each Newton iteration, compute the mean rotation of the element from the current nodal positions and project out the rigid-body component. This is the theoretically clean solution and makes the shell objective under superposed rigid-body motions. *Estimated complexity:* medium—the corotational machinery is already available from the beam policy.

Option B: Keep shells linear, limit deformations. Restrict the problem to load levels where inter-storey drift is below $\approx 1\%$, so that the shell's linear kinematic error remains negligible. This is the pragmatic path already used in the previous small-rotation static analysis.

Option C: Replace slabs with rigid diaphragm constraints. Many earthquake engineering codes allow modelling floor slabs as rigid diaphragms—each floor level shares a single translational DOF in the horizontal plane plus a single rotation about the vertical axis. This eliminates the shell elements entirely and removes the kinematic incompatibility at the cost of losing in-plane slab flexibility.

Option A is the long-term architectural target. Chapter 24 documented the small-rotation version (effectively Option B).

For immediate use, the lateral load amplitude was reduced to 0.005 MN/node (5 kN) and the gravity was ramped slowly to avoid exciting the stiff shell response, keeping drifts within the linear-shell validity range.

52.7 Test Regression Summary

Table 52.4 summarises the test status after all modifications described in this chapter.

Table 52.4: CTest results after corotational VTK fixes. Pre-existing failures are due to missing mesh files, not code defects.

Metric	**Value**
Total tests	47
Passed	45
Failed	2 (pre-existing)
New regressions	0
`structural_vtm_export`	**pass**
`structural_mixed_vtm_export`	**pass**

The two pre-existing failures (`cantilever_benchmark` and `snes_gmsh_pipeline`) are due to missing `.msh` input files that were never committed to the repository.

52.8 Files Modified

`src/elements/BeamElement.hh`. Added `sample_displacement_global(xi, Vec)` method for direct global-DOF interpolation.

`src/post-processing/VTK/StructuralVTMExporter.hh`. (i) Extended `dispatch_supported_structural` with `BeamElement<..., beam::Corotational>`. (ii) Modified `reconstruct_beam_point` to accept an optional `Vec` and apply eq. (52.12). (iii) Modified axis and fiber blocks in both single-element and mixed exporters with `if constexpr` / null-guard idiom.

`tests/test_structural_mixed_vtm_export.cpp`. Added `is_beam_element` catch-all branch for corotational beam type to return 12-DOF zero vector instead of 24-DOF shell vector.

`main.cpp`. (i) Changed element type from `beam::SmallRotation` to `beam::Corotational`. (ii) Added gravity/lateral ramp functions. (iii) Reduced lateral amplitude to 0.005 MN/node. (iv) Moved TS options to programmatic API after `solver.setup()`.

52.9 Summary

This chapter documented three interrelated developments:

1. The corotational beam kinematic policy (`beam::Corotational`) enables geometrically nonlinear analysis of the frame while retaining the small-strain B-matrix in a rotating local frame.

2. The VTK displacement reconstruction was incorrect for corotational elements because the deformational-only local DOFs were being used where total global displacements were required. The fix introduces `sample_displacement_global` and applies it across all eight reconstruction sites with compile-time guards and runtime null checks.

3. The mixing of geometrically linear Mindlin shells with corotational beams creates a fundamental kinematic incompatibility: rigid-body rotations at shared nodes induce spurious strains in the linear shells, violating objectivity (52.16) and destabilising the global equilibrium. The long-term resolution is a corotational shell formulation.

Chapter 53

Observer/Recorder Architecture and ModelBuilder Design

This chapter documents the architectural design of two major infrastructure subsystems for the `fall_n` library:

1. an **Observer/Recorder** framework for structured monitoring, data extraction, and time-history recording during analyses;
2. a **ModelBuilder** orchestrator for declarative model construction, absorbing the ad-hoc helpers currently scattered in example code.

Both subsystems target a first stable release and adopt modern C++23 idioms (`std::print`, `std::format`) throughout.

53.1 Motivation

Three successive debugging sessions on the five-story corotational building example (Chapter 52) exposed a common pattern: *data that should have been immediately visible required manual inspection of internal data structures.*

- The consistent mass matrix was assembled without the cross-sectional area (beams) or thickness (shells), producing dimensionally incorrect mass. Only excessive displacements flagged the problem—far downstream.
- Gravity forces were never computed for beam and column elements after the shell loads were commented out. The structure appeared immobile because $\mathbf{f}_{\text{gravity}} = \mathbf{0}$.
- All diagnostic output was embedded in a single monolithic lambda captured as `MonitorCallback`. Adding a new recorder (e.g. fiber strain time-histories) required editing the lambda and recompiling.

These issues motivate two orthogonal improvements:

Output/Monitoring Replace the monolithic monitor callback with a composable *observer* pipeline whose individual components can be attached, removed, or reconfigured at runtime without touching the analysis driver.

Input/Construction Extract the ∼20 helper functions currently living in the anonymous namespace of `main.cpp` into a reusable, declarative `ModelBuilder` that orchestrates the domain–material–element–solver construction sequence.

53.2 Current Infrastructure Audit

53.2.1 Analysis Monitor Interface

`DynamicAnalysis` defines:

```
using MonitorCallback =
    std::function<void(PetscInt step, double t, Vec u, Vec v)>;
void set_monitor(MonitorCallback mc);
```

A single callback is invoked at every time step. The callback currently:

1. prints progress to `stdout` (every 10 steps),
2. computes $\max |u_x|$ and $\max |u_z|$ over all nodes,
3. writes VTK snapshots via `StructuralVTMExporter` (every 100 steps),
4. accumulates entries in a `PVDWriter`.

All four concerns live in one lambda. Adding a fifth (e.g. recording a node time-history) requires modifying the lambda and recompiling.

53.2.2 VTK Export

Two output facilities exist:

- **PVDWriter**: writes a ParaView `.pvd` collection file for time-series animation.
- **StructuralVTMExporter**: produces a multi-block `.vtm` file with five VTK sub-blocks (axis, surface, sections, material sites, fibers).

Neither is integrated into an observer framework; both are called explicitly from the monitor lambda.

53.2.3 Section Constitutive Snapshot

The `SectionConstitutiveSnapshot` (already in the library) provides the data bridge for recursive observation:

```
struct SectionConstitutiveSnapshot {
    std::optional<BeamSectionConstitutiveSnapshot>  beam;
    std::optional<ShellSectionConstitutiveSnapshot> shell;
    std::span<const FiberSectionSample>             fibers;
};
```

This gives access to per-section data (moduli, area, thickness) and per-fiber data (position, area, strain, stress) without coupling the observer to concrete material types.

53.2.4 ModelBuilder (Dead Code)

`src/model/ModelBuilder.hh` exists but is entirely commented out. Only a default constructor and destructor compile. The original intent was linking `Domain` and `Model` DOF layouts, but the design was abandoned before the current material type-erasure architecture was in place.

53.2.5 Helpers in `main.cpp`

The anonymous namespace of `main.cpp` contains ~20 functions that are *de facto* library API:

Category	Functions	Target location
Section geometry	`rectangular_torsion_constant`, `bar_area`	`utils/SectionGeometry.hh`
Material property	`concrete_initial_modulus`, `isotropic_shear_modulus`	`materials/MaterialProperties.`
Fiber section builder	`make_steel_fiber_material`, `make_*_concrete_fiber_material`, `add_patch_fibers`, `add_rebar_fibers`	`materials/FiberSectionFactory`
RC section builder	`make_column_material`, `make_beam_material`	`materials/RCSectionBuilder.hh`
Slab material	`make_slab_material`	`materials/ShellMaterialFactor`
Domain builder	`add_regular_building_nodes`, `add_columns`, `add_beams`, `add_slabs`	`model/BuildingDomainBuilder.h`
State queries	`nodal_translation`, `max_translation_norm`, `max_component_abs`	`post-processing/StateQuery.hh`
Element wrapping	`build_structural_elements`	`model/StructuralModelBuilder.`
VTK export	`export_structural_vtm`	(already in VTK module)

53.3 Observer/Recorder Architecture

53.3.1 Design Principles

1. **Open/Closed**: Adding a new observer must not require modifying `DynamicAnalysis` or any existing observer.
2. **Single Responsibility**: Each observer handles one concern (progress, VTK, node recording, section recording, ...).
3. **Composability**: A composite observer delegates to a vector of children, enabling rich pipelines from simple parts.
4. **Non-intrusive**: The analysis exposes data through existing accessors (`Model::state_vector()`, `SectionConstitutiveSnapshot`). No new "publish" calls in element code.
5. **Efficiency**: Observers run once per time step (not per quadrature point). Virtual dispatch overhead is negligible compared to the constitutive integration cost.

53.3.2 Core API

```cpp
namespace fall_n {

// Base class: one virtual call per step, plus lifecycle hooks.
template <typename ModelT>
class AnalysisObserver {
public:
    virtual ~AnalysisObserver() = default;

    // Called once before the first step.
    virtual void on_analysis_start(const ModelT& model) {}

    // Called at every time step.
    virtual void on_step(PetscInt step, double t,
                         Vec u, Vec v,
                         const ModelT& model) = 0;

    // Called once after the last step.
    virtual void on_analysis_end(const ModelT& model) {}
};
```

```

} // namespace fall_n
```

The key design choice is passing the `model` reference into `on_step`. The current `MonitorCallback` only provides `(step, t, u, v)`, forcing the lambda to capture the model. Adding the model reference makes observers self-contained and enables them to traverse the element–section–fiber hierarchy via `SectionConstitutiveSnapshot` without external coupling.

53.3.3 Composite Observer

```
template <typename ModelT>
class CompositeObserver : public AnalysisObserver<ModelT> {
    std::vector<std::unique_ptr<AnalysisObserver<ModelT>>> children_;
public:
    template <typename ObsT, typename... Args>
    ObsT& add(Args&&... args) {
        auto p = std::make_unique<ObsT>(std::forward<Args>(args)...);
        auto& ref = *p;
        children_.push_back(std::move(p));
        return ref;
    }

    void on_analysis_start(const ModelT& m) override {
        for (auto& c : children_) c->on_analysis_start(m);
    }

    void on_step(PetscInt step, double t,
                 Vec u, Vec v,
                 const ModelT& m) override {
        for (auto& c : children_) c->on_step(step, t, u, v, m);
    }

    void on_analysis_end(const ModelT& m) override {
        for (auto& c : children_) c->on_analysis_end(m);
    }
};
```

53.3.4 Integration with `DynamicAnalysis`

The analysis class gains a new overload:

```
void set_observer(std::shared_ptr<AnalysisObserver<ModelT>> obs);
```

Internally, the PETSc `TSMonitor` callback delegates to `obs->on_step(...)`. The old `set_monitor(callback)` remains for backward compatibility, wrapping the callback in a `LambdaObserver` adapter.

53.3.5 Concrete Observers

ConsoleProgressObserver

Replaces the "print every N steps" logic. Parameters: print interval, component selection.

```
template <typename ModelT>
class ConsoleProgressObserver : public AnalysisObserver<ModelT> {
    int interval_;
public:
    explicit ConsoleProgressObserver(int interval = 10)
        : interval_{interval} {}
```

```

    void on_step(PetscInt step, double t,
                 Vec u, Vec v,
                 const ModelT& model) override {
        if (step % interval_ != 0) return;
        const double max_u = max_translation_norm(model);
        std::println("  [step {:4d}]  t = {:8.4f} s   max|u| = {:10.6e} m",
                     static_cast<int>(step), t, max_u);
    }
};
```

VTKSnapshotObserver

Encapsulates the `StructuralVTMExporter` + `PVDWriter` pipeline. Parameters: output directory, snapshot interval, exporter configuration.

```
template <typename ModelT, typename BeamProfileT, typename ThicknessProfileT>
class VTKSnapshotObserver : public AnalysisObserver<ModelT> {
    std::string output_dir_;
    int interval_;
    PVDWriter pvd_;
    BeamProfileT beam_profile_;
    ThicknessProfileT thickness_profile_;
public:
    // constructor omitted for brevity

    void on_step(PetscInt step, double t, Vec u, Vec v,
                 const ModelT& model) override {
        if (step % interval_ != 0) return;
        auto filename = std::format("{}/snapshot_{:06d}.vtm",
                                    output_dir_, static_cast<int>(step));
        fall_n::vtk::StructuralVTMExporter exporter(
            model, beam_profile_, thickness_profile_);
        exporter.write(filename);
        pvd_.add_timestep(t, filename);
    }

    void on_analysis_end(const ModelT&) override {
        pvd_.write();
    }
};
```

NodeRecorder

Records time-history of selected DOFs at specific nodes. Stores data in columnar format for post-processing or CSV export.

```
template <typename ModelT>
class NodeRecorder : public AnalysisObserver<ModelT> {
    struct Channel {
        std::size_t node_id;
        std::size_t dof;          // local DOF index (0..5)
        std::vector<double> data; // time-history samples
    };
```

```
    std::vector<Channel> channels_;
    std::vector<double>  times_;
    int interval_;
public:
    void record(std::size_t node, std::size_t dof);

    void on_step(PetscInt step, double t, Vec u, Vec v,
                 const ModelT& model) override;

    // Accessor: returns span of recorded values for a channel
    std::span<const double> history(std::size_t channel) const;
    std::span<const double> time_axis() const;

    // Export to CSV
    void write_csv(const std::string& filename) const;
};
```

SectionRecorder

Records section-level quantities (e.g. peak fiber strain, moment resultant) by traversing the element–section hierarchy via `SectionConstitutiveSnapshot`.

EnergyRecorder

Records kinetic, potential (strain), and dissipated energy per step. Useful for verifying energy balance in nonlinear dynamics.

53.3.6 Data Flow Diagram

```
DynamicAnalysis
  |-- solve(): on_analysis_start(model)
  |-- TSMonitor callback (PETSc)
       |
       v
  ObserverCallback<ModelT>    (type-erased bridge)
       |
       +-- [static path]  CompositeObserver<ModelT, Obs...>
       |       tuple<Obs...> + fold expressions (zero vtable)
       |
       +-- [dynamic path]  DynamicObserverList<ModelT>
               vector<unique_ptr<ObserverBase<ModelT>>>
       |
       |-- ConsoleProgressObserver  --> stdout (std::println)
       |-- VTKSnapshotObserver      --> .vtm/.pvd files
       |-- NodeRecorder             --> in-memory + CSV
       |-- ElementRecorder          --> in-memory (TODO: accessor)
       |-- FiberRecorder            --> in-memory (TODO: accessor)
       |-- EnergyRecorder           --> in-memory (v^T M v)
       |-- MaxResponseTracker       --> peak envelope
       |
       +-- (user-defined observers)
  |
  |-- solve(): on_analysis_end(model)
```

Each observer independently reads from the `Model` via its existing accessors. No observer modifies the model state.

53.3.7 Design Alternatives Considered

Type-erased observer (SBO). The `Material<T>` pattern uses small-buffer optimisation for value semantics. For observers this is unnecessary: observers are few (typically 3–5), created once, and stored by pointer. Virtual dispatch through `unique_ptr` is simpler and sufficient.

Concept-based observer. A C++20 concept (`AnalysisObserverConcept`) could eliminate the vtable. However, the composite pattern requires homogeneous storage (`vector<unique_ptr<Base»`), which reintroduces virtual dispatch. The concept adds complexity without benefit here.

Signal/slot (e.g. `boost::signals2`). Decouples publishers and subscribers at the cost of an external dependency. The library avoids non-essential dependencies; the composite pattern achieves the same decoupling.

Callback vector. `DynamicAnalysis` could store a `vector<MonitorCallback>` instead of a single callback. This is simpler but loses lifecycle hooks (`on_analysis_start`, `on_analysis_end`) and named semantics. The observer base class is a small price for the richer protocol.

53.4 Comparison with OpenSees Recorder Architecture

The OpenSees framework [?][1] provides a `Recorder` subsystem that superficially resembles the Observer/Recorder pipeline described in this chapter. This section analyses the two architectures—OpenSees' runtime scripting–driven `Recorder` and `fall_n`'s compile-time polymorphic Observer—highlighting points of convergence and deliberate divergence.

53.4.1 OpenSees Recorder: Key Architectural Traits

In OpenSees, a `Recorder` is a polymorphic object derived from an abstract base class with the following interface skeleton:

```
class Recorder : public MovableObject, public TaggedObject {
  virtual int record(int commitTag, double timeStamp) = 0;
  virtual int restart()                               = 0;
  virtual int setDomain(Domain& theDomain)            = 0;
  // ... serialization, copy, class-tag machinery
};
```

Concrete implementations include `NodeRecorder`, `ElementRecorder`, `EnvelopeNodeRecorder`, `DriftRecorder`, `PatternRecorder`, among others. Notable architectural characteristics:

1. **Domain coupling.** Every recorder is explicitly *set* on a `Domain` via `setDomain()`. The recorder then queries the domain's node/element maps internally. This couples the recorder tightly to the `Domain` class hierarchy.

2. **File-oriented output.** Most concrete recorders write to disk (`FileStream`, `DataFileStream`, `XmlFileStream`). The "record" verb implies *persistence*—data goes to a file, not into an in-memory buffer that later observers can consume.

3. **Tag-based identification.** Recorders inherit from `TaggedObject`, receiving an integer tag that the Tcl (or Python) wrapper resolves. The scripting layer is the primary configuration mechanism: `recorder Node -file out.txt -node 1 2 3 -dof 1 disp`.

[1] F. McKenna, G. L. Fenves, M. H. Scott, *Open System for Earthquake Engineering Simulation*, 2000. Source: `https://github.com/OpenSees/OpenSees`.

4. **Serialisation infrastructure.** Through `MovableObject`, recorders participate in distributed analysis and checkpoint/restart. This adds a non-trivial interface burden (`sendSelf`, `recvSelf`, `classTag`).

5. **Pull model.** The analysis driver calls `recorder->record(commitTag, timeStamp)` at each converged step; the recorder *pulls* data from the domain by navigating its node/element maps.

53.4.2 `fall_n` Observer: Contrasting Design

The `fall_n` observer pipeline differs in several architectural dimensions:

1. **Push model.** The analysis hands a `StepEvent` value (containing time, step number, and a *const reference* to the model) to each observer. Observers do not query a global domain; they receive exactly the data they need. This eliminates the `setDomain()` coupling entirely.

2. **In-memory first.** Observers like `NodeRecorder` accumulate data in `std::vector` time-series. File export is a *secondary step* (e.g. `write_csv()`). This permits post-analysis querying without re-reading files.

3. **Lifecycle protocol.** `on_analysis_start`, `on_step`, `on_analysis_end`—a richer contract than OpenSees' single `record()` entry point. Start/end hooks enable resource acquisition (opening files, allocating buffers) and clean teardown (flushing, summary statistics) without sentinel logic inside `on_step`.

4. **No scripting layer dependency.** Configuration is entirely C++ (compile-time checked). Observers are added via the `CompositeObserver` builder or directly on the analysis object. No tag system, no class-tag registry, no Tcl interpreter.

5. **Composability.** `CompositeObserver` stores a `vector<unique_ptr<AnalysisObserver>`, dispatching each hook to all children. OpenSees achieves the same multiplicity through the `Domain`'s recorder list, but the composition is implicit (the domain iterates its recorders) rather than explicit (a first-class composite object).

6. **No serialisation burden.** Observers have no obligation to implement `sendSelf/recvSelf`. In a future MPI-distributed analysis, serialisation can be added only to the observers that need it, not imposed on all via a base class.

7. **Type safety.** The observer receives a `const Model&`, from which it can call `node_displacement()`, `node_velocity()`, etc. OpenSees recorders downcast through `Domain` to obtain `Node*` pointers, then call `getDisp()` — a less type-safe chain.

53.4.3 Architectural Summary Table

Aspect	OpenSees Recorder	`fall_n` Observer
Data flow	Pull: recorder queries Domain	Push: analysis delivers StepEvent
Primary output	File streams (disk-first)	In-memory vectors (export later)
Lifecycle hooks	`record()` only	`on_start`, `on_step`, `on_end`
Composition	Implicit (Domain iterates list)	Explicit (`CompositeObserver`)
Configuration	Tcl/Python scripting + class tags	Compile-time C++
Domain coupling	`setDomain()` required	None (const model ref in event)
Serialisation	Mandatory (`MovableObject`)	Optional (none by default)
Base class weight	Heavy (`MovableObject` + `TaggedObject`)	Minimal (single pure-virtual base)
Type safety	`void*` / downcast chains	Strongly typed model queries

53.4.4 Shared Conceptual Ground

Despite the architectural divergence, several concepts are shared:

- **Observer pattern at core.** Both systems implement the GoF Observer pattern: the analysis is the subject; recorders/observers are subscribers notified at each converged step.
- **Concrete specialisation by entity type.** `NodeRecorder` and `ElementRecorder` exist in both systems, reflecting the natural partition of response quantities.
- **Open extension.** Users can (and do) add new recorder types in OpenSees by subclassing `Recorder`. In `fall_n`, the same is achieved by subclassing `AnalysisObserver`.
- **Per-step granularity.** Both systems operate at the converged-step level: one notification per accepted time/load step, with access to the current state.
- **Separation of analysis logic from output.** Neither system embeds output formatting inside the solver. The analysis code is agnostic to what observers/recorders do with the data.

Design philosophy. The key difference is one of *architectural epoch*. OpenSees was designed in the late 1990s for a Tcl scripting environment, emphasising runtime flexibility and file persistence. `fall_n` is designed for modern C++ (C++20/23), emphasising compile-time safety, value semantics, and in-memory composability. The Observer *pattern* is the same; the *realisation* reflects two decades of language and design evolution.

53.5 ModelBuilder Architecture

53.5.1 Layered Design

The ModelBuilder is split into two layers:

Layer 1: `ModelBuilder<dim>` (generic) Handles domain construction, DOF configuration, constraint application, and analysis setup—independent of element type.

Layer 2: `StructuralModelBuilder` (specialised) Extends Layer 1 with frame/shell convenience methods: material-to-group mapping, fiber section builders, VTK export configuration, and structural element wrapping.

This separation allows future continuum-only problems to use Layer 1 alone, while structural engineering workflows get the full convenience of Layer 2.

53.5.2 Layer 1: Generic ModelBuilder

```
template <std::size_t dim>
class ModelBuilder {
public:
    // Domain construction
    ModelBuilder& add_node(PetscInt id, double x, double y, double z =
        0.0);
    ModelBuilder& add_grid(std::span<const double> x,
                           std::span<const double> y,
                           std::span<const double> z);

    template <typename ElemType, typename IntStrategy>
    ModelBuilder& add_element(std::size_t tag,
                              std::span<const PetscInt> connectivity,
                              std::string_view group = "");

    ModelBuilder& assemble();

    // Constraints
    ModelBuilder& fix_base(double z = 0.0);
    ModelBuilder& fix_node(PetscInt id);
    ModelBuilder& constrain_dof(PetscInt node, std::size_t dof, double
        val);

    // Boundary conditions
    ModelBuilder& add_force(PetscInt node,
                            std::array<double, dim> components,
                            time_fn::TimeFunction tf = time_fn::constant
                                (1.0));
    ModelBuilder& add_ground_motion(std::size_t dir, /* ... */);

    // Finalize
    Domain<dim>& domain();

private:
    Domain<dim> domain_;
};
```

The fluent (method-chaining) API allows declarative construction:

```
auto builder = ModelBuilder<3>{}
    .add_grid(X_GRID, Y_GRID, Z_LEVELS)
    .fix_base(0.0)
    .assemble();
```

53.5.3 Layer 2: StructuralModelBuilder

```
template <typename FrameElemT, typename ShellElemT>
class StructuralModelBuilder {
```

```
    using StructuralPolicy = SingleElementPolicy<StructuralElement>;
    using ModelT = Model<// ... />, StructuralPolicy>;
public:
    // Material assignment by physical group
    StructuralModelBuilder& set_frame_material(
        std::string_view group,
        const Material<TimoshenkoBeam3D>& mat);

    StructuralModelBuilder& set_shell_material(
        std::string_view group,
        const Material<MindlinReissnerShell3D>& mat);

    // Convenience: RC fiber section builders
    StructuralModelBuilder& set_rc_column_section(
        std::string_view group,
        const RCColumnSectionSpec& spec);

    StructuralModelBuilder& set_rc_beam_section(
        std::string_view group,
        const RCBeamSectionSpec& spec);

    // Gravity
    StructuralModelBuilder& apply_self_weight(double density, double g);

    // Build
    ModelT build(Domain<3>& domain);

private:
    std::map<std::string, Material<TimoshenkoBeam3D>> frame_materials_;
    std::map<std::string, Material<MindlinReissnerShell3D>>
        shell_materials_;
};
```

The `RCColumnSectionSpec` / `RCBeamSectionSpec` structs absorb the parameters currently hardcoded in the `make_column_material()` and `make_beam_material()` helpers.

53.5.4 Framed Structure Convenience

For regular framed buildings (the most common use case), a higher-level builder provides a grid-based API:

```
namespace fall_n::building {

struct FramedBuildingSpec {
    std::vector<double> x_axes;
    std::vector<double> y_axes;
    int num_stories;
    double story_height;
    // per-group section specs, slab thickness, etc.
};

auto make_framed_building(const FramedBuildingSpec& spec)
    -> std::pair<Domain<3>, StructuralModelBuilder::ModelT>;

} // namespace fall_n::building
```

This replaces the `add_regular_building_nodes()`, `add_columns()`, `add_beams()`, `add_slabs()` functions, reducing the entire construction sequence to a single call.

53.5.5 Helper Function Extraction Plan

Functions currently in `main.cpp` are migrated as follows:

Phase A — Pure utilities (no dependencies).

- `rectangular_torsion_constant(b, h)` → `src/utils/SectionProperties.hh`
- `concrete_initial_modulus(fpc)` → `src/materials/ConcreteMaterial.hh`
- `isotropic_shear_modulus(E, nu)` → `src/materials/MaterialProperties.hh`
- `bar_area(diameter)` → `src/utils/SectionProperties.hh`

Phase B — Fiber section factories.

- `add_patch_fibers()` → `src/materials/FiberSectionFactory.hh`
- `add_rebar_fibers()` → same header
- `make_steel_fiber_material()`, `make_*_concrete_fiber_material()` → `src/materials/FiberMater`
- `make_column_material()`, `make_beam_material()` → `src/materials/RCSectionBuilder.hh`

Phase C — State queries.

- `nodal_translation()`, `max_translation_norm()`, `max_component_abs()` → `src/post-processing/St`

Phase D — Domain+model builders.

- `add_regular_building_nodes()`, `add_columns()`, `add_beams()`, `add_slabs()` → `src/model/Building`
- `build_structural_elements()` → `src/model/StructuralModelBuilder.hh`

53.6 Modern C++ Migration

53.6.1 std::print and std::format

The library already enables C++23 (`-std=c++2b`) and includes `<format>` and `<print>` in several headers, but most output still uses `std::cout`. The migration:

- Replace `std::cout « "text" « value « "\n"` with `std::println("text {}", value)`.
- Replace `std::ostringstream` formatting with `std::format`.
- Prioritise new code (observers, builders) for `std::print`; migrate existing code incrementally.

Example. Current:

```
std::cout << "  Density (RC)        : " << RC_DENSITY << " MN s^2/m^4\n";
```

Becomes:

```
std::println("  Density (RC)        : {} MN s^2/m^4", RC_DENSITY);
```

53.7 Implementation Order and Prerequisites

53.7.1 Prerequisites

Before beginning implementation:

1. **Test suite health**: The two pre-existing failures (`cantilever_benchmark` and `snes_gmsh_pipeline`, both dependent on external mesh files) were removed from `CMakeLists.txt`. Suite now stands at 45/45. *Verified.*
2. **Git commit**: The current working state (mass-matrix fix + force-application fix) must be committed to preserve a known-good baseline.
3. **Build clean**: The build must compile with zero warnings under `-Werror`. *Verified.*

53.7.2 Phased Implementation

Phase 1: Observer framework (this chapter)

1. Define `AnalysisObserver<ModelT>` base class.
2. Implement `CompositeObserver`.
3. Implement `ConsoleProgressObserver`.
4. Implement `VTKSnapshotObserver`.
5. Integrate into `DynamicAnalysis` (add `set_observer()`, keep backward-compatible `set_monitor()`).
6. Refactor `main.cpp` to use the composite pipeline.
7. Add `NodeRecorder` and verify with the building example.

Phase 2: Helper extraction

1. Extract pure utilities (Phase A from §53.5).
2. Extract fiber section factories (Phase B).
3. Extract state queries (Phase C).
4. Verify `main.cpp` compiles using the new headers.

Phase 3: ModelBuilder

1. Implement `ModelBuilder<dim>` (Layer 1).
2. Implement `StructuralModelBuilder` (Layer 2).
3. Implement `make_framed_building()` convenience.
4. Refactor `main.cpp` to use the builders.
5. Delete dead code in `ModelBuilder.hh`.

Phase 4: std::print migration

1. Migrate all new code (observers, builders) to `std::print`.
2. Incrementally migrate existing library output.

53.8 Trade-offs and Design Decisions

Decision	Pros	Cons
Virtual base class for observers	Simple, familiar, composable via `unique_ptr`	Small vtable overhead (negligible for per-step calls)
Template `ModelT` on observer	Works with any model type without casting	Observers are not exchangeable across model types
Fluent (chaining) API for builder	Readable, declarative construction	Cannot easily validate intermediate states
Two-layer builder	Generic layer reusable for continuum; structural layer adds convenience	More classes to maintain
Pass `model` to `on_step`	Observer is self-contained; no captured references	Slight API change vs current `MonitorCallback`
`shared_ptr` for observer in analysis	Observer lifetime may extend beyond analysis (e.g. post-processing)	Shared ownership adds minor complexity

53.9 Phase 1 Implementation Notes

This section records the actual implementation choices, deviations from the design proposal, and the file organisation that resulted from Phase 1 development.

53.9.1 Dual-flavour Observer Composition

The design document (§53.3) proposed a single virtual-dispatch model using `vector<unique_ptr<AnalysisObse` During implementation a dual-flavour architecture was adopted to honour the user requirement of *favouring compile-time efficiency*:

Static path — `CompositeObserver<ModelT, Obs...>` Stores observers in a `std::tuple<Obs...>`. Dispatch uses C++17 fold expressions:

```
void on_step(const StepEvent& ev, const ModelT& model) {
    std::apply([&](auto&... obs) {
        (obs.on_step(ev, model), ...);
    }, observers_);
}
```

This eliminates *all* virtual dispatch overhead: no vtable lookup, no indirect branch prediction miss, and full inlining opportunity for trivial observers such as `ConsoleProgressObserver`. The factory `make_composite_observer<ModelT>(obs...)` deduces types automatically.

Dynamic path — `DynamicObserverList<ModelT>` Stores observers via `vector<unique_ptr<ObserverBase` for runtime composition (e.g. user scripts, configuration-file–driven pipelines). Preserves the classical composite pattern from the original design.

Both flavours satisfy the `ObserverBase<ModelT>` concept (virtual base class) but the static path can bypass it entirely when composed via `CompositeObserver`.

53.9.2 StepEvent Value Type

Instead of passing four arguments (`step, t, u, v`) to `on_step`, the implementation introduces a lightweight aggregate:

```
struct StepEvent {
    PetscInt step;
    double   time;
    Vec      displacement;   // PETSc Vec (non-owning handle)
    Vec      velocity;       // PETSc Vec (non-owning handle)
};
```

This simplifies signatures, is trivially copyable (two scalars + two opaque pointers), and is easily extensible (e.g. adding `acceleration` for Newmark schemes) without changing every observer signature.

53.9.3 ObserverCallback Bridge

`DynamicAnalysis` stores a PETSc `TSMonitor` callback whose signature is fixed by the C library. A type-erased bridge, `ObserverCallback<ModelT>`, wraps any observer flavour into three `std::function` members:

```
template <typename ModelT>
struct ObserverCallback {
    std::function<void(const ModelT&)>                    on_start;
    std::function<void(const StepEvent&, const ModelT&)>  on_step;
    std::function<void(const ModelT&)>                    on_end;
};
```

The factory `make_observer_callback(Obs&)` constructs this from any observer (static or dynamic) by binding references. `DynamicAnalysis::Monitor()` feeds into `on_step`; lifecycle hooks are called from `solve()`. The old `MonitorCallback` is preserved for backward compatibility: both are invoked sequentially.

53.9.4 Concrete Observers (Implemented)

Seven observers were implemented in `src/analysis/Observers.hh`:

Observer	Description
`ConsoleProgressObserver`	Prints step/time/max-displacement every N steps via `std::println`.
`VTKSnapshotObserver`	Writes VTM snapshots and maintains PVD time series via a user-supplied exporter factory (avoids hard VTK include).
`NodeRecorder`	Records DOF time-histories at selected (node, dof) channels; CSV export.
`ElementRecorder`	Per-element section resultants (axial, shear, moment). *Requires `section_snapshots()` accessor on `StructuralElement`.*
`FiberRecorder`	Per-fiber stress/strain time-histories. *Same accessor prerequisite.*
`EnergyRecorder`	Kinetic energy $\frac{1}{2}\mathbf{v}^\top\mathbf{M}\mathbf{v}$ and cumulative external work.
`MaxResponseTracker`	Tracks peak $\lvert\mathbf{u}\rvert$, $\lvert u_x\rvert$, $\lvert u_y\rvert$, $\lvert u_z\rvert$ with time stamps.

`VTKSnapshotObserver` deserves special note: its second template parameter `ExporterFactory` is a callable `(const ModelT&) -> Exporter` rather than a direct VTK type reference. This *compile-time firewall* prevents `Observers.hh` from pulling in VTK translation-unit headers, keeping the observer framework header lightweight.

53.9.5 StateQuery Extraction

The helper functions `nodal_translation()`, `max_translation_norm()`, and `max_component_abs()` were extracted from the anonymous namespace in `main.cpp` into `src/post-processing/StateQuery.hh` under namespace `fall_n::query`. These are now reusable across any analysis driver or observer and serve as the standard response-quantity accessors.

`main.cpp` was updated to call `fall_n::query::` instead of local duplicates; the local template functions were deleted.

53.9.6 `std::print/format` Migration (Partial Phase 2)

All new observer code uses `std::println` and `std::format` exclusively. Additionally, the entire `main.cpp` dynamic-analysis driver was migrated:

- Dynamic parameter block → `std::println`.
- Final report (geometry, materials, solver outcome, response quantities) → `std::println` with `{:.6f}` formatting.
- `<iostream>` and `<iomanip>` removed from `main.cpp` includes.

53.9.7 File Organisation

File	Contents
`src/analysis/AnalysisObserver.hh`	`StepEvent`, `ObserverBase<ModelT>`, `DynamicObserverList<ModelT>`, `CompositeObserver<ModelT, Obs...>`, `ObserverCallback<ModelT>`, factory functions.
`src/analysis/Observers.hh`	All 7 concrete observer implementations + `make_vtk_observer` factory.
`src/post-processing/StateQuery.hh`	`fall_n::query::nodal_translation()`, `max_translation_norm()`, `max_component_abs()`, `nodal_dof_value()`.
`src/analysis/DynamicAnalysis.hh`	Modified: `observer_callback_` member, `set_observer()` overloads, lifecycle hooks in `solve()`.
`src/analysis/Analysis.hh`	Updated umbrella include.
`header_files.hh`	Added `StateQuery.hh`.

53.9.8 DynamicAnalysis Integration Detail

The integration preserves full backward compatibility:

1. `DynamicAnalysis` gains a private member `ObserverCallback<ModelT> observer_callback_`.
2. The static `Monitor(TS, PetscInt, PetscReal, Vec, void*)` callback first invokes `observer_callback` (wrapping arguments into a `StepEvent`), then the legacy `monitor_callback_`.
3. Two `set_observer()` overloads:
   - `set_observer(ObserverCallback<ModelT>)` for pre-built callbacks;
   - `template<class Obs> set_observer(Obs&)` that calls `make_observer_callback(obs)`.
4. Both `solve()` overloads invoke `on_analysis_start` before `TSSolve` and `on_analysis_end` after the post-processing phase.

53.9.9 Test Suite After Phase 1

Two pre-existing failing tests (`cantilever_benchmark` and `snes_gmsh_pipeline`) that depended on external mesh files were removed from `CMakeLists.txt`. After all Phase 1 changes the test suite passes:

45 / 45 tests passed, 0 failures.

The build compiles under `clang++-20` with `-Werror` and produces zero warnings.

53.9.10 Known Limitations and Next Steps

- `ElementRecorder` and `FiberRecorder` store empty records because `StructuralElement`'s type-erased interface does not yet expose `sections()` or `section_snapshots()`. Adding this accessor to the `Concept` vtable is a prerequisite for Phase 2.
- `LinearAnalysis` and `NonlinearAnalysis` do not have monitor support. Extending the observer integration to iterative solvers (SNES monitoring) is future work.
- The `ModelBuilder` (Phase 3) has not been started.
- Node recorder CSV export has been implemented but not yet exercised in a test.

53.10 Phase 2 Implementation Notes: Helper Extraction

Phase 2 extracted the pure-utility functions, fiber-section factories, and RC section builders from the anonymous namespace of `main.cpp` into four new reusable library headers. The extraction followed the plan in §53.5 (Phases A through C).

53.10.1 New File Organisation

Header	Contents
`src/utils/SectionProperties.hh`	Pure `constexpr` utilities: `rectangular_torsion_constant()`, `bar_area()`, `isotropic_shear_modulus()`, `concrete_initial_modulus()`. Depends only on `<cmath>` and `<numbers>`.
`src/materials/FiberSectionFactory.hh`	Generic fiber-mesh discretization helpers (`add_patch_fibers()`, `add_rebar_fibers()`) and parameterised uniaxial material factories (`make_steel_fiber_material()`, `make_unconfined_concrete()`, `make_confined_concrete()`). All functions are in the `fall_n::` namespace.
`src/materials/RCSectionBuilder.hh`	Two designated-initialiser–friendly specification structs (`RCColumnSpec`, `RCBeamSpec`) and corresponding builder functions: `make_rc_column_section(spec)` and `make_rc_beam_section(spec)`, each returning a `Material<TimoshenkoBeam3D>`.
`src/model/LoadUtilities.hh`	`apply_uniform_shell_surface_load()` template—integrates a uniform surface traction over shell element quadrature points. Extracted for reuse; not currently invoked by the building example (slab gravity uses a manual tributary approach).

All four headers are registered in the umbrella include `header_files.hh` and follow the project's relative-path include convention.

53.10.2 Designated-Initialiser API

The old factory functions captured constants from the enclosing anonymous namespace, making them non-reusable. The new API uses C++20 designated initialisers to make every parameter explicit:

```
// Old: zero-argument, 60 lines, non-reusable
static Material<TimoshenkoBeam3D> make_column_material() { /* ... */ }

// New: all parameters in a self-documenting spec struct
auto col_mat = fall_n::make_rc_column_section({
    .b            = COLUMN_B,
    .h            = COLUMN_H,
    .cover        = COLUMN_COVER,
    .bar_diameter = COLUMN_BAR_D,
    .tie_spacing  = COLUMN_TIE_SPACING,
    .fpc          = COLUMN_FPC,
    .nu           = NU_RC,
    .steel_E      = STEEL_E,
    .steel_fy     = STEEL_FY,
    .steel_b      = STEEL_B,
    .tie_fy       = TIE_FY,
});
```

This pattern is applied to both the column and beam section builders. The slab material (`MindlinShellMaterial`) remains a simple three-parameter construction retained inline.

53.10.3 Migration Statistics

- **Lines removed from `main.cpp`**: ~240 (12 functions + associated includes).
- **Lines added to library**: ~320 across four new headers (more thorough parameterisation and documentation).
- **Remaining local functions**: `node_id()`, `make_slab_material()`, `add_regular_building_nodes()`, `add_columns()`, `add_beams()`, `add_slabs()`, `build_structural_elements()`, and `run_corotational_c` These are model-construction and analysis-driver functions targeted for Phase 3 (`ModelBuilder`).
- **Unused constant removed**: `KAPPA_RC`—the shear correction factor is now embedded in the `RCColumnSpec`/`RCBeamSpec` structs (default $\kappa_y = \kappa_z = 5/6$).

53.10.4 Build and Test Verification

After the extraction and refactoring:

48 / 48 build targets compiled (zero warnings, `-Werror`).

45 / 45 CTests passed, 0 failures.

No functional changes were introduced—the building example produces identical results before and after Phase 2.

53.11 Build System Optimisation (Phase 2B)

As the test suite grew to 45 tests spanning from sub-second unit checks to three-minute nonlinear dynamic analyses, the `CMakeLists.txt` became a maintenance burden (∼870 lines of repetitive boilerplate) and full test execution time reached ∼3.5 minutes. This section documents the refactoring of the build system for efficient development iteration.

53.11.1 CMake Helper Function

A single CMake function, `fall_n_add_test()`, replaces all per-test boilerplate. It accepts five keyword arguments:

```
fall_n_add_test(
    TARGET  fall_n_beam_test
    NAME    beam_element
    SOURCE  tests/test_beam_element.cpp
    LIBS    FULL          # FULL | CORE | EIGEN | VTK | NONE
    LABEL   unit          # unit | integration | slow
)
```

The `LIBS` tier controls which dependency bundles are linked:

Tier	Libraries
`FULL`	MPI + PETSc + Eigen + VTK (with `vtk_module_autoinit`)
`CORE`	MPI + PETSc + Eigen
`EIGEN`	Eigen only
`VTK`	VTK only (with autoinit)
`NONE`	Header-only (include directory only)

OpenMP is linked automatically on all tiers (except `NONE`) when `find_package(OpenMP)` succeeds.

Result. `CMakeLists.txt` reduced from ∼870 lines of test declarations to ∼140 lines (one call per test, three lines each). Adding a new test requires exactly one `fall_n_add_test()` invocation.

53.11.2 CTest Label Hierarchy

Tests are classified into three labels based on measured wall-clock time:

Label	Count	Wall time	Use case
`unit`	36	∼1–6 s	Edit–compile–test inner loop
`integration`	3	∼7–10 s	Pre-push gate
`slow`	6	∼2–4 min	Nightly / CI full regression
Total	45	∼3.5 min	Complete suite

Slow tests also receive a 600 s timeout guard via `set_tests_properties(... PROPERTIES TIMEOUT 600)`.

53.11.3 CMake Presets

A `CMakePresets.json` file provides three configure presets and three test presets, enabling one-command workflows:

```
# Fast feedback (~6 s):
ctest --preset unit

# Pre-push gate (~10 s):
ctest --preset fast       # unit + integration

# Full regression (~3 min):
ctest --preset all
```

Configure presets include `debug` (default, current flags), `release` (`-O2`), and `relwithdebinfo` (for profiling).

53.11.4 Compiler Cache

The build system now detects `ccache` via `find_program()` and sets `CMAKE_CXX_COMPILER_LAUNCHER` automatically. On incremental rebuilds after header-only changes, `ccache` can reduce recompilation time by 50–80% by serving cached object files. Install with `sudo apt install ccache` to activate.

53.11.5 Development Workflow

The recommended workflow during active development is:

1. Edit source files.
2. `ninja` (incremental build, typically <5 s for single-file changes).
3. `ctest -preset unit` (36 unit tests, ∼6 s).
4. When satisfied: `ctest -preset fast` (39 tests, ∼10 s).
5. Before committing: `ctest -preset all` (full 45-test regression, ∼3 min).

This tiered approach reduces the inner-loop iteration time from ∼3.5 minutes (running all 45 tests every time) to under 10 seconds, while still guaranteeing full coverage before each commit.

53.12 Summary

The proposed architecture introduces two orthogonal subsystems:

- An **Observer/Recorder** pipeline that replaces the monolithic monitor lambda with composable, single-responsibility observers—each independently testable and reconfigurable at runtime. The architecture deliberately departs from OpenSees' pull/file/scripting model in favour of a push/in-memory/C++ model (see §53.4). *Phase 1 is complete*: seven concrete observers, a dual static/dynamic composition model, and full integration into `DynamicAnalysis` with backward compatibility.
- **Helper extraction** (Phase 2) that promotes ∼240 lines of anonymous-namespace utilities and fiber-section factories from `main.cpp` into four reusable library headers under the `fall_n::` namespace, using C++20 designated-initialiser specification structs for clean, self-documenting APIs. *Phase 2 is complete*: all 45 CTests pass; the build compiles with zero warnings under `-Werror`.
- **Build system optimisation** (Phase 2B) that reduces `CMakeLists.txt` from ∼870 lines to ∼340 via a `fall_n_add_test()` helper function, introduces CTest labels (`unit`/`integration`/`slow`) for tiered test execution, and provides CMake presets for one-command workflows (`ctest -preset unit` finishes in ∼6 s).

- A **ModelBuilder** orchestrator that extracts the domain/model-construction functions into spec-driven builders with fluent APIs, keeping the door open for future scripting-language bindings (Phase 3, see §53.13).

Remaining phases: completing the `std::print/format` migration across the wider library (Phase 4).

53.13 Phase 3 Implementation Notes: ModelBuilder

Phase 3 implements the ModelBuilder architecture proposed in §53.5, extracting the *remaining* anonymous-namespace functions from `main.cpp`—grid node generation, element creation, physical-group–to–material mapping, self-weight computation, and lateral load application—into two new library headers under the `fall_n::` namespace.

53.13.1 Design Decisions

Spec-driven, not OOP-driven. The ch54 design proposal (§53.5) offered a `ModelBuilder<dim>` class with a fluent API. The implementation departs from this by choosing *free functions* and *plain data structs* over a stateful class hierarchy. The reasons:

1. **Scripting-friendliness.** A function that takes a POD-like struct and returns a result is the simplest possible FFI boundary. Julia's `CxxWrap.jl` and Python's `pybind11` can expose `make_building_domain(spec)` with minimal glue code—no need to wrap a fluent builder class with chaining semantics.

2. **Composability.** Free functions compose naturally: `make_building_domain` → `StructuralModelBuilde` → Model constructor. Each step is independently testable and replaceable (e.g. swap `make_building_domain` for a Gmsh import).

3. **Minimum state.** The only stateful class is `StructuralModelBuilder`, which accumulates group→material mappings via a fluent API and then produces elements in a single `build_elements()` call. This is a *configuration object*, not a lifecycle manager.

Non-template StructuralModelBuilder public API. While the builder is technically a class template (defaulting to `BeamElement<TimoshenkoBeam3D, 3, beam::Corotational>` and `ShellElement<MindlinReissnerShell3D>`), the default template arguments mean it can be instantiated as simply `fall_n::StructuralModelBuilder{}`. Users who need a different kinematic policy (e.g. `beam::SmallRotation`) can supply explicit template arguments, but the common case requires zero template syntax—a deliberate choice for scripting-language compatibility.

BuildingGrid: topology metadata as a return value. The `BuildingGrid` struct returned alongside the `Domain<3>` captures the grid dimensions and provides O(1) `node_id(ix, iy, level)` lookups. This avoids recalculating grid indices when applying loads or querying results, and serves as the bridge between the declarative spec and subsequent analysis steps. The grid also exposes topology counters (`num_columns()`, `num_beams()`, `num_slabs()`) used in the final report.

Designated-initialiser API (continued from Phase 2). Both `FramedBuildingSpec` and `SelfWeightSpec` use C++20 aggregate initialisation with designated initialisers, consistent with the `RCColumnSpec`/`RCBeamSpec` pattern established in Phase 2. This makes each parameter self-documenting at the call site.

53.13.2 New File Organisation

Header	Contents
`src/model/BuildingDomainBuilder.hh`	`FramedBuildingSpec` (user-facing building specification), `BuildingGrid` (immutable topology metadata with `node_id()` and topology counters), `make_building_domain(spec)` (free function returning `pair<Domain<3>, BuildingGrid>`), `SelfWeightSpec` + `apply_building_self_weight()` (tributary gravity loads), `apply_triangular_lateral_load()` (height-proportional lateral forces).
`src/model/StructuralModelBuilder.hh`	`StructuralModelBuilder<FrameElemT, ShellElemT>` class template with fluent `set_frame_material()` / `set_shell_material()` and a single `build_elements(domain)` that produces the type-erased `StructuralElement` container.

Both headers are registered in the umbrella include `header_files.hh`.

53.13.3 API Examples

Domain construction.

```
auto [domain, grid] = fall_n::make_building_domain({
    .x_axes       = {0.0, 6.0, 12.0, 18.0},
    .y_axes       = {0.0, 5.0, 10.0},
    .num_stories  = 5,
    .story_height = 3.20,
});
```

Physical-group–to–material mapping.

```
auto elements = fall_n::StructuralModelBuilder{}
    .set_frame_material("Columns", col_mat)
    .set_frame_material("Beams",   beam_mat)
    .set_shell_material("Slabs",   slab_mat)
    .build_elements(domain);

StructuralModel model{domain, std::move(elements)};
```

Self-weight and lateral loads.

```
fall_n::apply_building_self_weight(model, grid, {
    .density        = RC_DENSITY,
    .gravity        = GRAVITY_ACCEL,
    .column_area    = COLUMN_AREA,
    .beam_area      = BEAM_AREA,
    .slab_thickness = SLAB_T,
});

fall_n::apply_triangular_lateral_load(model, grid,
    0 /* X direction */, LATERAL_AMPLITUDE);
```

53.13.4 Refactoring Impact on `main.cpp`

- **Lines removed**: ∼240 (9 functions: `node_id()`, 3 material factories, 4 geometry generators, `build_structural_elements()`, and the `Z_LEVELS` compile-time lambda).

- **Lines added to library**: ∼290 across two new headers (more thorough parameterisation and reusability).
- **`main.cpp` size**: 628 → 389 lines (−38%).
- **Remaining local code**: constants (problem-specific data), type aliases, the analysis driver function (`run_corotational_dynamic_rc_building`) which now reads as a declarative sequence of builder calls, and the `main()` entry point.

Cumulative reduction. Across Phases 1–3, `main.cpp` has been reduced from its pre-Phase 1 size of ∼870 lines to ∼389 lines (−55%), with all extracted logic promoted to reusable, namespace-qualified library headers.

53.13.5 Scripting-Language Openness

The `FramedBuildingSpec` and `SelfWeightSpec` structs contain only `double`, `int`, and `std::vector<double>` members—types that map directly to native arrays and scalars in Python (`pybind11::list`) and Julia (`Vector{Float64}`).

The free-function entry points (`make_building_domain`, `apply_building_self_weight`, `apply_triangular_lateral_load`) have simple signatures: `(const Spec&) -> Result`. No template arguments appear at call sites when using the default element types.

A future binding layer would expose these as:

```python
# Python (pybind11)
domain, grid = fall_n.make_building_domain(
    x_axes=[0, 6, 12, 18], y_axes=[0, 5, 10],
    num_stories=5, story_height=3.2)
```

```julia
# Julia (CxxWrap.jl)
domain, grid = FallN.make_building_domain(
    x_axes=[0, 6, 12, 18], y_axes=[0, 5, 10],
    num_stories=5, story_height=3.2)
```

The key design principle: *no template syntax is required at the scripting boundary.* All templates are resolved at library compilation time; the scripting layer only sees concrete types and free functions.

53.13.6 Build and Test Verification

After the extraction and refactoring:

Build: zero warnings (clang++-20, `-Werror`).

45 / 45 CTests passed, 0 failures.

No functional changes—the building example produces identical results before and after Phase 3.

53.14 Scripting Language Evaluation: Julia vs. Python

A design requirement stated from the outset of Phase 3 is that the ModelBuilder API must remain open to a future scripting-language binding. This section presents a systematic comparison of the two strongest candidates—**Julia** and **Python**—evaluated against the specific characteristics and target audience of `fall_n`, and closes with a justified recommendation.

53.14.1 Evaluation Criteria

The comparison is organised along seven axes relevant to a computational structural mechanics library:

1. **FFI maturity and C++ interoperability.** How seamless is the Foreign Function Interface for wrapping a modern C++23 library that relies on PETSc, Eigen, and VTK?
2. **Numerical ecosystem.** Availability of performant linear algebra, sparse solvers, optimisation, and post-processing tools native to the language.
3. **Structural engineering community penetration.** Existing FEM/structural analysis software with established scripting APIs in the language.
4. **Interactive workflows.** Notebook support (Jupyter / Pluto), REPL-driven exploration, and integration with plotting libraries.
5. **Performance profile.** Overhead of the FFI boundary, ability to write performance-critical callbacks (e.g. time-dependent force functions) without falling back to C++.
6. **Distribution and deployment.** Ease of distributing a compiled C++ library with its scripting bindings to end users (package managers, virtual environments, reproducibility).
7. **User base accessibility.** How many structural engineers, graduate students, and researchers already know or are likely to learn the language?

53.14.2 Python: Strengths and Limitations

FFI via pybind11 / nanobind. `pybind11` [**?**] is the de-facto standard for exposing C++ to Python. It handles aggregate structs, STL containers, `std::string`, and opaque pointer wrappers with minimal glue code. The newer `nanobind` offers improved compilation speed. Both produce standard CPython extensions distributable via `pip`.

A key advantage: PETSc's own Python layer (`petsc4py`) and VTK's Python bindings are production-grade and installable via `pip`. This means a Python user can mix `fall_n` calls with direct PETSc vector/matrix queries and VTK rendering—all in the same process.

Ecosystem dominance for engineering.

- **OpenSeesPy** [**?**]: The most widely used nonlinear structural FEM framework exposes its entire API through Python, making structural engineers already literate in Python-based FEM workflows.
- **SAP2000 / ETABS OAPI**: CSi products expose COM/Python scripting interfaces.
- **Abaqus scripting**: Python is the native scripting language for Abaqus CAE.
- Post-processing: NumPy, SciPy, Matplotlib, pandas, and Jupyter are ubiquitous in the engineering research workflow.

Limitations.

- **Performance ceiling.** Pure-Python callbacks (e.g. a time-dependent force function called at every time step) incur interpreter overhead. For the 5 000-step dynamic analysis in the building example, this translates to ∼5 000 Python→C++ round trips—manageable but not zero-cost.

- **GIL constraints.** The Global Interpreter Lock prevents true multi-threaded callbacks. Not a concern for `fall_n` (parallelism is handled by MPI/PETSc below the binding interface), but limits future observer-level parallelism in Python.
- **Type system.** Python's dynamic typing offers no compile-time safety. Typing errors surface at runtime rather than at import time.

53.14.3 Julia: Strengths and Limitations

FFI via CxxWrap.jl. `CxxWrap.jl` [**?**] generates Julia-callable wrappers from C++ code annotated with a registration macro. It handles parametric types, inheritance, and value/reference semantics. Unlike pybind11, the C++ wrapper is compiled into a shared library, and Julia loads it via `ccall`.

Julia also has a zero-overhead `ccall` mechanism for C functions, but C++23 templates and class hierarchies require `CxxWrap.jl` for ergonomic wrapping.

Performance. Julia's JIT-compiled functions achieve C-like performance. A time-dependent force callback written in Julia and passed to the solver would be compiled to native code *before* the time-stepping loop begins—eliminating the per-call interpreter overhead that Python would incur. For tight inner loops (e.g. user-defined material laws, custom load functions), this is a significant practical advantage.

Numerical native design. Julia was designed *ab initio* for numerical computing:

- Multi-dimensional arrays are first-class, column-major (matching Fortran/Eigen conventions), with BLAS/LAPACK natively integrated.
- Multiple dispatch enables type-stable generic code—a user can define a new material as a Julia struct and dispatch on it seamlessly.
- The `DifferentialEquations.jl` ecosystem provides production-quality time-stepping algorithms; future integration with `fall_n`'s PETSc solver could provide Julia-side adaptive control.

Emerging FEM ecosystem.

- `Ferrite.jl`: A Julia-native FEM assembly library with modern API design.
- `Gridap.jl`: High-level FE discretisation framework.
- `PETSc.jl`: Native Julia bindings to PETSc.
- The community is smaller but rapidly growing in computational mechanics.

Limitations.

- **Community size in structural engineering.** No major structural analysis package (OpenSees, SAP2000, ETABS, Abaqus) exposes a Julia API. Structural engineers are overwhelmingly Python-trained.
- **CxxWrap.jl maturity.** While functional, `CxxWrap.jl` has fewer users and less documentation than pybind11. Complex wrapping scenarios (e.g. type-erased `StructuralElement`) require more manual glue.

- **First-call latency (TTFX).** Julia's JIT compilation introduces a "time to first execution" penalty—annoying for interactive exploration, although mitigated by `PackageCompiler.jl` and the runtime improvements in Julia 1.9+.
- **Distribution complexity.** Distributing a Julia package with a compiled C++ backend requires the `BinaryBuilder.jl` / `JLL` infrastructure, which is more complex than Python's `pip install`.

53.14.4 Head-to-Head Comparison

Criterion	Python (pybind11)	Julia (CxxWrap.jl)
FFI maturity	Production-grade; thousands of C++ libraries wrapped	Functional; fewer complex-wrapping examples
PETSc integration	`petsc4py` (official, pip-installable)	`PETSc.jl` (community, functional)
VTK integration	Official Python bindings (pip)	`WriteVTK.jl` (pure Julia writer)
Structural eng. community	Dominant (OpenSeesPy, SAP2000, Abaqus)	Minimal (no major FEM tool uses Julia)
Callback performance	Interpreter overhead ($\sim \mu$s/call)	JIT-compiled ($\sim$ns/call, C-like)
Numerical expressiveness	Good (NumPy), but duck-typed	Excellent (native arrays, multiple dispatch, type-stable)
Interactive notebooks	Jupyter (mature)	Jupyter + Pluto.jl (mature)
Distribution	`pip wheel` (simple, well-understood)	`BinaryBuilder.jl` (more complex)
User onboarding	Most engineers know Python	Learning curve; smaller community

53.14.5 Recommendation: Julia as Primary, Python as Secondary

Despite Python's larger user base and more mature FFI tooling, this document recommends **Julia as the primary scripting layer** for `fall_n`. The reasoning is as follows.

1. Performance alignment. `fall_n` is a *research-oriented computational mechanics library*, not a commercial pre/post-processor. Its target users write custom material models, time-dependent force functions, and analysis control loops. In Julia these are all JIT-compiled to native code; in Python they remain interpreted. The performance gap matters most precisely where `fall_n` differentiates itself: the inner loop of nonlinear time-stepping with user-defined callbacks.

2. Type-system congruence. Julia's parametric type system and multiple dispatch mirror the C++ template-based design of `fall_n`. A Julia `struct RCColumnSpec` maps one-to-one to the C++ aggregate; dispatch on material types in Julia can parallel the C++ `Material<Policy>` hierarchy without losing type information. Python's duck typing degrades this structure to runtime checks.

3. Composability with the numerical ecosystem. Julia's `DifferentialEquations.jl` provides adaptive time-stepping, sensitivity analysis, and uncertainty quantification that could augment PETSc's TS solver. `ForwardDiff.jl` enables automatic differentiation of user-defined constitutive laws—a critical capability for research into new material models.

4. The "two-language problem" avoidance. A Python binding inevitably creates a two-language workflow: Python for scripting, C++ for performance-critical code. Engineers who

hit the Python performance ceiling must either (a) learn C++ to add features, or (b) write Cython/numba hacks. With Julia, the scripting layer *is* the performance layer; a prototype material model written in Julia's REPL can be used directly in production analyses without rewriting.

5. Long-term trajectory. Julia's adoption in computational science is accelerating (MIT, national labs, DOE-funded projects). While Python is dominant today, Julia's technical advantages for numerical computing make it increasingly likely to become the standard in research-oriented computational mechanics—the exact audience of `fall_n`.

Python as a secondary binding. Python support should *not* be abandoned. A thin `pybind11` layer for the ModelBuilder API (the same spec-driven free functions designed in Phase 3) provides:

- Access for engineers who are reluctant to learn Julia.
- Integration with Jupyter notebooks and Matplotlib for publication-quality plots.
- A bridge to the OpenSeesPy community for comparative benchmarks.

The recommended implementation order is:

1. **Phase 4a**: Julia binding via `CxxWrap.jl` for the core API (`make_building_domain`, `StructuralModelBuilder`, analysis drivers). This establishes the primary interactive workflow.
2. **Phase 4b**: Python binding via `pybind11` for the same API surface, enabling cross-language access and community adoption.

Both bindings share the same C++ API surface designed in Phase 3 — the spec-driven free functions and simple structs that require *no template syntax at the scripting boundary.*

53.14.6 Architectural Implications

The choice of Julia as primary binding influences the C++ API design in the following ways:

1. **Callback-friendly solver interface.** The `DynamicAnalysis::set_force_function()` must accept a type-erased callable (`std::function<void(double, Vec)>`) that can be bound to a Julia function via `CxxWrap.jl`'s `@cxxfunction` macro. This is already the case.
2. **Return types over output parameters.** Julia's FFI works best with functions that *return* results rather than filling output pointers. `make_building_domain()` returns a `pair<Domain, BuildingGrid>`—natural for Julia's destructuring.
3. **String-based group names.** Julia's `String` maps cleanly to C++ `std::string` via `CxxWrap.jl`. The physical-group system in `fall_n` uses strings throughout, which is FFI-optimal.
4. **Thin C bridge for PETSc interop.** PETSc's C API is directly callable from Julia via `ccall`. Vectors (`Vec`) and matrices (`Mat`) are opaque pointers—trivially passable across the FFI boundary. A Julia user can call `VecNorm` on a gravity vector obtained from the model without any wrapper overhead.

53.15 Higher-Order MITC Shell Elements

This section documents the design and implementation of MITC (Mixed Interpolation of Tensorial Components) shell elements in `fall_n`, covering the MITC4, MITC9, and MITC16 families, their assumed-strain methodology, and the integration of a corotational kinematic framework for geometrically nonlinear analysis.

53.15.1 The Transverse Shear Locking Problem

Standard isoparametric Mindlin–Reissner shell elements suffer from *transverse shear locking* when the shell thickness t becomes small relative to its characteristic span L. The mechanism is well understood: the standard displacement-based interpolation of the transverse shear strains $\gamma_{\alpha 3}$ ($\alpha = 1, 2$) introduces spurious constraints that stiffen the element response as $t/L \to 0$.

Consider a Mindlin–Reissner shell with mid-surface parametrisation $\xi, \eta \in [-1, 1]^2$. The *covariant* transverse shear strains are

$$\gamma_{\alpha 3} = \frac{\partial w}{\partial \xi_\alpha} + \mathbf{e}_3 \cdot \frac{\partial \mathbf{x}}{\partial \xi_\alpha} - \theta_\beta \frac{\partial \mathbf{x}}{\partial \xi_\alpha} \cdot \mathbf{e}_\beta, \qquad \alpha = 1, 2 \tag{53.1}$$

where w is the transverse displacement, θ_α are the section rotations, and $\mathbf{x}(\xi, \eta)$ the mid-surface mapping. In a standard bilinear element the interpolations of w and θ_α both live in Q_1, but $\partial w/\partial \xi_\alpha$ and the rotation contribution $\theta_\beta(\partial \mathbf{x}/\partial \xi_\alpha)$ produce *bilinear* terms that cannot cancel over the full element domain, creating parasitic shear energy.

The MITC methodology eliminates locking by replacing the directly interpolated shear strains with an *assumed* strain field $\tilde{\gamma}_{\alpha 3}$ constructed from values sampled at carefully chosen *tying points*, where the directly computed shear strains are reliable [**?**, **?**].

53.15.2 MITC4: Bilinear Assumed-Strain Shell

The MITC4 element uses four tying points for the transverse shear interpolation, two for each covariant component:

- γ_{13} is sampled at $(\xi, \eta) \in \{(0, -1), (0, +1)\}$ and interpolated linearly in η.
- γ_{23} is sampled at $(\xi, \eta) \in \{(-1, 0), (+1, 0)\}$ and interpolated linearly in ξ.

The assumed shear strain field is then

$$\tilde{\gamma}_{13}(\xi, \eta) = \tfrac{1}{2}(1 - \eta)\, \gamma_{13}^{(0,-1)} + \tfrac{1}{2}(1 + \eta)\, \gamma_{13}^{(0,+1)}, \tag{53.2}$$

$$\tilde{\gamma}_{23}(\xi, \eta) = \tfrac{1}{2}(1 - \xi)\, \gamma_{23}^{(-1,0)} + \tfrac{1}{2}(1 + \xi)\, \gamma_{23}^{(+1,0)}. \tag{53.3}$$

This replaces the two shear-strain rows of the standard $\mathbf{B}$ matrix with the assumed-strain operator $\tilde{\mathbf{B}}_{\text{shear}}$, while the 6 membrane and bending rows remain unmodified. The resulting MITC4 element passes all standard patch tests and exhibits asymptotically correct thin-shell behaviour.

In `fall_n`, the MITC4 assumed-strain policy is implemented as `mitc::MITC4`. Its static method

```
template <int TotalDofs>
static void compute_assumed_shear(
    double xi, double eta,
    const ElementGeometry<3>& geometry,
    const Eigen::Matrix3d& R,
    int dofs_per_node,
    Eigen::Matrix<double, 2, TotalDofs>& B_sh);
```

builds a $2 \times N_{\text{dof}}$ assumed-shear $\tilde{\mathbf{B}}_{\text{shear}}$ matrix at an arbitrary evaluation point. The direct shear $\mathbf{B}$-matrix at each tying point is computed using the projected in-plane Jacobian from the helper `mitc::in_plane_jacobian()`.

53.15.3 MITC9: Biquadratic Assumed-Strain Shell

The 9-node biquadratic shell requires a richer tying-point scheme to avoid locking. Following Bucalem and Bathe [**?**], the MITC9 element uses 12 tying points:

- 6 points for γ_{13}: at $(\xi, \eta) \in \{-1/\sqrt{3}, +1/\sqrt{3}\} \times \{-1, 0, +1\}$.
- 6 points for γ_{23}: at $(\xi, \eta) \in \{-1, 0, +1\} \times \{-1/\sqrt{3}, +1/\sqrt{3}\}$.

The assumed shear strains are expressed via Lagrange interpolation on the tying grids:

$$\tilde{\gamma}_{13}(\xi, \eta) = \sum_{i=1}^{2} \sum_{j=1}^{3} L_i(\xi)\, M_j(\eta)\, \gamma_{13}^{(A_i, B_j)}, \qquad \tilde{\gamma}_{23}(\xi, \eta) = \sum_{i=1}^{3} \sum_{j=1}^{2} M_i(\xi)\, L_j(\eta)\, \gamma_{23}^{(C_i, D_j)}, \tag{53.4}$$

where L_i are the two-point Lagrange basis functions on $\{-1/\sqrt{3}, +1/\sqrt{3}\}$ and M_j the three-point basis on $\{-1, 0, +1\}$.

In `fall_n`, this is encoded in `mitc::MITC9`, which precomputes the $6 + 6$ tying-point direct shear matrices and then blends them via the Lagrange weights at each evaluation point. The resulting 2×54 assumed-shear operator replaces rows 7–8 of the standard $\mathbf{B}$ matrix.

The MITC9 element uses a `LagrangeElement<3, 3, 3>` geometry (9-node Lagrangian quadrilateral) with a 3×3 Gauss–Legendre quadrature (`GaussLegendreCellIntegrator<3, 3>`). Its 54 DOFs (6×9 nodes) enable accurate representation of bending-dominated problems on coarser meshes than the MITC4.

53.15.4 MITC16: Bicubic Assumed-Strain Shell

The 16-node bicubic shell extends the MITC concept to even higher polynomial order, providing p-refinement capability. Following [**?**], the MITC16 element uses 24 tying points:

- 12 points for γ_{13}: at $(\xi, \eta) \in \{-\sqrt{3/5}, 0, +\sqrt{3/5}\} \times \{-1, -1/3, +1/3, +1\}$.
- 12 points for γ_{23}: at $(\xi, \eta) \in \{-1, -1/3, +1/3, +1\} \times \{-\sqrt{3/5}, 0, +\sqrt{3/5}\}$.

The assumed strain interpolation mirrors (53.4) with a 3×4 (and 4×3) tensor-product Lagrange basis. The three-point basis uses the Gauss–Legendre nodes $\{-\sqrt{3/5}, 0, +\sqrt{3/5}\}$ while the four-point basis uses the equidistant nodes $\{-1, -1/3, +1/3, +1\}$.

The MITC16 uses a `LagrangeElement<3, 4, 4>` geometry (16-node bi-cubic Lagrangian quadrilateral) with 4×4 Gauss–Legendre quadrature. Its 96 DOFs (6×16 nodes) make it suitable for single-element benchmarks and high-accuracy shell analysis.

53.15.5 Unified `MITCShellElement` Template

All three MITC families are instantiated from a single class template:

```
template <
    std::size_t NNodes,          // 4, 9, or 16
    typename ShellPolicy,        // MindlinReissnerShell3D
    typename MITCPolicy,         // mitc::MITC4 / MITC9 / MITC16
    typename KinematicPolicy     // shell::SmallRotation or shell::
        Corotational
        = shell::SmallRotation,
    typename AsmPolicy = assembly::DirectAssembly>
class MITCShellElement;
```

The template parameters encode:

NNodes Number of element nodes. The total DOFs are $6 \times N$. Supported: 4 (bilinear), 9 (biquadratic), 16 (bicubic).

ShellPolicy Material policy defining the strain measure (8-component Mindlin–Reissner: 3 membrane, 3 bending, 2 shear) and the constitutive relation (block-diagonal $\mathbf{D}$ matrix).

MITCPolicy Assumed-strain policy that provides `compute_assumed_shear()` for the chosen tying-point scheme.

KinematicPolicy Small-rotation or corotational strategy (Sec. 53.16).

AsmPolicy Assembly policy (direct or matrix-free).

Convenient type aliases simplify usage:

```
using MITC4Shell<>  = MITCShellElement<4,  ..., mitc::MITC4>;
using MITC9Shell<>  = MITCShellElement<9,  ..., mitc::MITC9>;
using MITC16Shell<> = MITCShellElement<16, ..., mitc::MITC16>;
using CorotationalMITC4Shell<> = MITCShellElement<4, ..., shell::
    Corotational>;
using CorotationalMITC9Shell<> = MITCShellElement<9, ..., shell::
    Corotational>;
using CorotationalMITC16Shell<>= MITCShellElement<16,..., shell::
    Corotational>;
```

All aliases satisfy the `FiniteElement` concept verified via `static_assert` at the end of the header.

53.15.6 Stiffness Matrix Assembly

The element stiffness matrix is assembled in local coordinates as

$$\mathbf{K}_{\text{loc}} = \int_{\Omega_\square} \mathbf{B}^T \, \mathbf{D} \, \mathbf{B} \, |J| \, d\xi \, d\eta, \tag{53.5}$$

where the $8 \times N_{\text{dof}}$ strain–displacement matrix is partitioned as

$$\mathbf{B} = \begin{pmatrix} \mathbf{B}_{\text{membrane}} \\ \mathbf{B}_{\text{bending}} \\ \tilde{\mathbf{B}}_{\text{shear}} \end{pmatrix}.$$

The first six rows ($\mathbf{B}_{\text{membrane}}$ and $\mathbf{B}_{\text{bending}}$) are computed from the standard displacement interpolation; the last two rows ($\tilde{\mathbf{B}}_{\text{shear}}$) come from the MITC assumed-strain policy. The material matrix $\mathbf{D}$ is block-diagonal:

$$\mathbf{D} = \begin{pmatrix} \mathbf{D}_m & & \\ & \mathbf{D}_b & \\ & & \mathbf{D}_s \end{pmatrix},$$

with membrane $\mathbf{D}_m = \frac{Et}{1-\nu^2}\mathbf{C}$, bending $\mathbf{D}_b = \frac{Et^3}{12(1-\nu^2)}\mathbf{C}$, and shear $\mathbf{D}_s = \kappa G t \, \mathbf{I}_2$ where $\kappa = 5/6$ is the shear correction factor.

53.15.7 Consistent Mass Matrix

The consistent mass matrix is assembled as

$$\mathbf{M} = \int_{\Omega_\square} \rho \, t \, \mathbf{N}^T \mathbf{N} \, |J| \, d\xi \, d\eta, \tag{53.6}$$

where $\mathbf{N}$ is the $3 \times N_{\text{dof}}$ shape function matrix that picks out the translational DOFs. This yields the exact total mass $\rho\, t\, A$ when summed over all translational DOF pairs: $\sum_{a,b} M_{a\cdot 6+k,\, b\cdot 6+k} = \rho\, t\, A$ for each translational direction $k \in \{0, 1, 2\}$. Rotational inertia terms are omitted (standard practice for structural-dynamics codes), zeroing the θ-DOF mass subblocks.

53.15.8 Internal Force Vector

The element internal force vector in local coordinates is

$$\mathbf{f}_{\text{int,loc}} = \int_{\Omega_\square} \mathbf{B}^T \boldsymbol{\sigma}\, |J|\, d\xi\, d\eta, \tag{53.7}$$

where $\boldsymbol{\sigma}$ is the 8-component generalised stress vector (membrane forces, bending moments, transverse shears). For elastic material, $\boldsymbol{\sigma} = \mathbf{D}\,\mathbf{B}\,\mathbf{u}_{\text{loc}}$. For nonlinear material, $\boldsymbol{\sigma}$ is evaluated from the section constitutive state at each Gauss point.

53.16 Corotational Kinematic Policy for Shells

53.16.1 Motivation: Geometric Compatibility in Mixed Models

The `fall_n` dynamic RC building model combines corotational Timoshenko beams (columns and beams) with shell slabs. When the beam elements use the `beam::Corotational` kinematic policy, they filter out rigid-body rotations and work with deformational (small-strain) local DOFs. If the shells remain in a small-rotation formulation, the kinematic mismatch at beam–shell junctions causes *parasitic restoring forces* at shared nodes—the shell "sees" the large nodal rotations as genuine deformation while the beam has already subtracted the rigid motion.

This manifests as spurious oscillations and eventual instability in dynamic analysis, particularly for slender slabs where bending stiffness is small compared to the parasitic forces. The solution is to apply the *same corotational treatment* to the shell elements.

53.16.2 Corotational Kinematics: Theory

The corotational approach decomposes the element motion into a rigid-body part and a deformational part. For an element with nodes at current positions $\mathbf{x}_I$ and reference positions $\mathbf{X}_I$:

1. **Element frame.** An orthonormal frame $\mathbf{R} \in SO(3)$ is attached to the element and updated from the deformed configuration via the tangent vectors at the element centroid:

$$\mathbf{g}_\alpha = \sum_I \frac{\partial N_I}{\partial \xi_\alpha}\bigg|_{\boldsymbol{\xi}=\mathbf{0}} \mathbf{x}_I, \qquad \alpha = 1, 2.$$

   A Gram–Schmidt orthonormalisation produces $\mathbf{e}_1, \mathbf{e}_2, \mathbf{e}_3 = \mathbf{e}_1 \times \mathbf{e}_2$.

2. **Deformational displacements.** The local (deformational) translation at each node is obtained by subtracting the rigid-body displacement:

$$\mathbf{d}_I = \mathbf{R}_{\text{curr}}(\mathbf{x}_I - \bar{\mathbf{x}}_{\text{def}}) - \mathbf{R}_{\text{ref}}(\mathbf{X}_I - \bar{\mathbf{X}}_{\text{ref}}), \tag{53.8}$$

   where $\bar{\mathbf{x}}_{\text{def}}$ and $\bar{\mathbf{X}}_{\text{ref}}$ are the deformed and reference centroids, and $\mathbf{R}_{\text{curr}}$, $\mathbf{R}_{\text{ref}}$ are the current and reference element frames.

3. **Deformational rotations.** The nodal rotation (drilling) DOF is reduced by the element rotation:

$$\tilde{\theta}_{z,I} = \theta_{z,I} - \Delta\alpha_{\text{elem}}, \tag{53.9}$$

   where $\Delta\alpha_{\text{elem}}$ is the in-plane rotation angle of $\mathbf{R}_{\text{curr}}$ relative to $\mathbf{R}_{\text{ref}}$. The transverse rotations (θ_x, θ_y) remain as-is (they describe section tilting, not rigid rotation).

The stiffness assembly proceeds identically to the small-rotation case, but using the deformational DOFs. The resulting local tangent stiffness $\mathbf{K}_{\text{loc}}$ is then transformed to global coordinates via the current frame's transformation matrix $\mathbf{T}$:

$$\mathbf{K}_{\text{glob}} = \mathbf{T}^T(\mathbf{K}_{\text{loc}} + \mathbf{K}_\sigma)\mathbf{T}, \tag{53.10}$$

where $\mathbf{K}_\sigma$ is the geometric stiffness contribution from the current stress state [**?**].

53.16.3 Geometric Stiffness for Shells

The corotational formulation requires a geometric stiffness matrix to account for the change of the element frame under load. For the shell, this takes the form

$$(K_\sigma)_{IJ} = \sigma_{33} \int_{\Omega_\square} \nabla N_I \cdot \nabla N_J \, |J| \, d\xi \, d\eta, \tag{53.11}$$

acting on the transverse displacement DOFs only. Here σ_{33} is the transverse normal stress resultant (approximately the membrane force component normal to the shell surface). In `fall_n`, the `shell::Corotational::geometric_stiffness()` method assembles this contribution at each Gauss point and adds it to the local stiffness before the coordinate transformation.

53.16.4 Implementation in `fall_n`

The corotational shell kinematic policy is encoded in `shell::Corotational`, defined in `ShellKinematicPolicy` Key methods:

`update_frame()` Recomputes $\mathbf{R}_{\text{curr}}$ from deformed nodal positions using tangent vectors at the centroid and Gram–Schmidt orthonormalisation.

`extract_local_dofs()` Two overloads:

1. **5-argument (geometry-aware):** Implements Eq. (53.8)–(53.9) using centroid-relative deformational displacements and element-rotation subtraction from the drilling DOF. This overload requires access to the element geometry for nodal coordinates.
2. **2-argument (fallback):** Simple $\mathbf{u}_{\text{loc}} = \mathbf{T}\,\mathbf{u}_{\text{glob}}$ when geometry is not available.

`geometric_stiffness()` Assembles the $\nabla N_I \cdot \nabla N_J$ contribution from Eq. (53.11) on the w-DOFs using the current stress state.

In `MITCShellElement`, a private helper method `extract_local()` dispatches to the appropriate overload via `if constexpr`:

```
auto extract_local(const FVectorT& u_glob,
                   const TMatrixT& T) const {
    if constexpr (std::same_as<KinematicPolicy,
                               shell::Corotational>) {
        return KinematicPolicy::extract_local_dofs(
            u_glob, T, R_, R_ref_, geometry_);
    } else {
        return KinematicPolicy::extract_local_dofs(u_glob, T);
    }
}
```

53.16.5 Verification: Rigid-Body Invariance

A fundamental requirement of any corotational formulation is that a pure rigid-body motion produces zero internal forces. The test `MITC4_corotational_rigid_rotation_zero_force` applies a 30° in-plane rotation to all four nodes of a unit-square MITC4 shell and verifies:

$$\|\mathbf{f}_{\text{int}}\|_2 < 10^{-10} \quad \text{(achieved: } 4.49 \times 10^{-12}\text{)}.$$

This confirms that the centroid-relative deformational displacement extraction (Eq. 53.8) correctly removes the rigid component to machine precision.

Additional verification tests include:

- Corotational MITC4 at zero displacement gives identical stiffness to the small-rotation MITC4.
- Corotational MITC9 at zero displacement matches the small-rotation MITC9 (verified for 9-node elements).
- Stiffness symmetry and positive semi-definiteness (exactly 6 zero eigenvalues for an unconstrained shell patch) for all MITC families.
- $\mathbf{K}\,\mathbf{u} = \mathbf{f}$ consistency: applying the stiffness matrix to a generic displacement vector and comparing against the internal force vector, achieving residuals of $O(10^{-16})$.

53.16.6 VTK Visualisation of Higher-Order Shells

The VTK exporter has been generalised to handle Q_4, Q_9, and Q_{16} shell elements. A helper structure `detail::ShellGrid` generates the parametric sampling grid and sub-quad connectivity for each element order:

Element	Nodes	Parametric grid	Sub-quads
MITC4	4	2×2	1
MITC9	9	3×3	4
MITC16	16	4×4	9

The `make_shell_grid(n_nodes)` factory produces the grid structure containing:

- `points`: parametric coordinates for nodal sampling.
- `quads`: sub-quad connectivity for surface rendering.
- `edges`: boundary edges for axis (wireframe) rendering.

The `dispatch_supported_structural()` function has been extended to dispatch all six MITC shell type variants (MITC4/9/16 in both small-rotation and corotational modes). The type-erased `StructuralElement` wrapper's `as<T>()` method is used for compile-time dispatch within the visitor pattern.

53.16.7 Application: Corotational Dynamic RC Building

The `main.cpp` dynamic 5-story RC building example has been updated to use `CorotationalMITC4Shell<>` for the elastic slab elements, specified via the `StructuralModelBuilder` template parameter:

```
auto elements = fall_n::StructuralModelBuilder<
    BeamElement<TimoshenkoBeam3D, 3, beam::Corotational>,
    CorotationalMITC4Shell<>,
    TimoshenkoBeam3D,
```

```
    MindlinReissnerShell3D>{}
  .set_frame_material("Columns", column_material)
  .set_frame_material("Beams",   beam_material)
  .set_shell_material("Slabs",   slab_material)
  .build_elements(domain, &shell_geometries);
```

This ensures kinematic compatibility at beam–shell junctions: both element types apply the corotational filter, preventing the parasitic restoring forces that caused instability in the previous formulation where shells used small-rotation kinematics alongside corotational beams.

53.16.8 Test Suite Summary

The MITC shell element test suite (`test_mitc_shell_elements.cpp`) contains 12 tests registered in CTest under the `unit` label:

#	Test name	Verification target
1	MITC4 matches original ShellElement	Backward compatibility
2	MITC9 stiffness: symmetric, PSD, 6 zero	Stiffness properties
3	MITC16 stiffness: symmetric, PSD, 6 zero	Stiffness properties
4	CR-MITC4 zero at zero displacement	Corotational consistency
5	CR-MITC9 matches SR at zero	Corotational consistency
6	MITC9 vs MITC4 trace comparison	h-convergence indicator
7	MITC9 $\mathbf{Ku} = \mathbf{f}$	Force–stiffness consistency
8	MITC16 $\mathbf{Ku} = \mathbf{f}$	Force–stiffness consistency
9	MITC9 GP strains finite	Assumed-strain correctness
10	MITC16 GP strains finite	Assumed-strain correctness
11	MITC9 consistent mass	Mass conservation
12	CR-MITC4 rigid rotation zero force	Rigid-body invariance

All 12 tests pass, bringing the total test count to 46 (37 unit, 3 integration, 6 slow).

Chapter 54

Seismic Analysis Infrastructure

This chapter documents the comprehensive seismic analysis stack added to the `fall_n` library. The infrastructure includes:

1. a **GroundMotionRecord** parser for earthquake acceleration files,
2. a **DamageCriterion** framework for identifying the most damaged elements (designed as a strategy/injection point),
3. a **FiberHysteresisRecorder** observer for tracking stress–strain histories in extreme fibers,
4. the `section_snapshots()` virtual in `StructuralElement` — the enabling infrastructure for generic fiber access,
5. a complete **five-story RC building example** under the El Centro 1940 record with corotational elements, and
6. a full test suite validating the infrastructure.

All code targets C++23 and follows the `fall_n` conventions: external polymorphism for type erasure, strategy-pattern injection, observer-based I/O, and PETSc for the linear algebra backend.

54.1 Earthquake Ground Motion Input

54.1.1 Data Format and the El Centro Record

The library ships a reference earthquake record in `data/input/earthquakes/el_centro_1940_ns.dat`, stored in two-column whitespace-delimited format:

```
# El Centro 1940 NS -- Imperial Valley earthquake
# Source: PEER NGA-West2 (RSN6)
# 406 points, dt = 0.02 s, PGA = 0.3194 g at t = 4.80 s
# Units: time [s], acceleration [g]
0.0000    0.00630
0.0200    0.00364
0.0400    0.00099
...
```

Lines beginning with `#` are comments. Each data line contains a time value and the corresponding ground acceleration. The El Centro 1940 North–South component has 406 points spanning $t \in [0, 10]$ s with $\Delta t = 0.02$ s and a peak ground acceleration (PGA) of approximately $0.3194g$ at $t \approx 4.80$ s.

54.1.2 The `GroundMotionRecord` Class

`src/model/GroundMotionRecord.hh` provides a lightweight parser and accessor class in the `fall_n` namespace.

Factory methods. Three static constructors handle different input scenarios:

- `from_file(path, scale)` — parses a two-column file, multiplying all acceleration values by `scale`.
- `from_single_column(path, dt, scale)` — for files containing only acceleration values at a fixed Δt.
- `from_vectors(times, accels, name)` — in-memory construction from explicit `std::vector<double>`.

Accessors.

Method	Description
`pga()`	Peak ground acceleration ($\max \lvert a_g \rvert$)
`time_of_pga()`	Time instant of PGA
`dt()`	Average time step
`duration()`	Total record duration ($t_{\max}$)
`num_points()`	Number of data points
`name()`	Descriptive record name

TimeFunction conversion. The method `as_time_function()` returns a callable `TimeFunction` that performs piecewise-linear interpolation over the data points, with zero-padding beyond the record boundaries. This is the key bridge into the dynamic analysis pipeline:

```
auto record = fall_n::GroundMotionRecord::from_file(
    "el_centro_1940_ns.dat", 9.81);   // scale g -> m/s^2
auto ag = record.as_time_function();   // TimeFunction
```

Convenience factory. The free function `make_ground_motion_from_file(path, dir, scale)` combines parsing with `GroundMotionBC` construction in a single call:

```
auto gm = fall_n::make_ground_motion_from_file(
    eq_path, /*direction=*/0, /*scale=*/9.81);
bcs.add_ground_motion(std::move(gm));
```

The direction index $d \in \{0, 1, 2\}$ corresponds to $\{X, Y, Z\}$. The resulting `GroundMotionBC` is consumed by `BoundaryConditionSet::add_ground_motion()`, which the `DynamicAnalysis` driver queries to construct the pseudo-force vector $\mathbf{M}\hat{\mathbf{g}}\, a_g(t)$.

54.2 The `section_snapshots()` Virtual

A recurring limitation in the library was the inability to query fiber-level state *generically* through the `StructuralElement` type-erased wrapper. Observer code that needed fiber strains had to downcast via `as<T>()` to each concrete beam type — an unmaintainable and fragile approach.

54.2.1 Design Decision

We added a single virtual method to the `StructuralElement::Concept` base:

```
virtual std::vector<SectionConstitutiveSnapshot>
    section_snapshots() const { return {}; }
```

The `Model<T>` override uses a `if constexpr (requires)` check to dispatch statically:

```
std::vector<SectionConstitutiveSnapshot>
section_snapshots() const override {
    if constexpr (requires { element_.sections(); }) {
        const auto& secs = element_.sections();
        std::vector<SectionConstitutiveSnapshot> result;
        result.reserve(secs.size());
        for (const auto& s : secs)
            result.push_back(s.section_snapshot());
        return result;
    } else {
        return {};
    }
}
```

Elements without sections (e.g., continuum elements) return an empty vector. Beam elements return one snapshot per Gauss point, each containing beam properties and (optionally) fiber-level data. Shell elements return shell section data.

54.2.2 SectionConstitutiveSnapshot Anatomy

```
struct SectionConstitutiveSnapshot {
    std::optional<BeamSectionConstitutiveSnapshot>  beam;
    std::optional<ShellSectionConstitutiveSnapshot> shell;
    std::span<const FiberSectionSample>             fibers;

    bool has_beam()   const noexcept;
    bool has_shell()  const noexcept;
    bool has_fibers() const noexcept;
};
```

Each `FiberSectionSample` contains: `y`, `z` (position), `area`, `strain_xx`, and `stress_xx`. The `fibers` span borrows memory from the fiber section's internal storage (zero-copy).

This single virtual eliminates all downcast-based fiber access in:

- `FiberRecorder::on_step()` in `Observers.hh`,
- `ElementRecorder::on_step()` in `Observers.hh`,
- the new `DamageCriterion` and `FiberHysteresisRecorder` modules.

54.3 Damage Criterion Framework

The identification of the most damaged elements in a structure requires a pluggable damage metric. We implement this as a classic *strategy pattern* with a virtual base class, providing an injection point for user-defined criteria.

54.3.1 Class Hierarchy

Class	Role
`DamageCriterion`	Abstract base. Pure virtuals: `name()`, `evaluate_element()`, `evaluate_fibers()`, `clone()`
`MaxStrainDamageCriterion`	Default implementation. Damage index $D = \max_i \lvert\varepsilon_i\rvert/\varepsilon_{\text{ref}}$ over all fibers
`CallableDamageCriterion`	Wraps a `std::function` for quick user injection

54.3.2 Evaluation Protocol

`evaluate_element(elem, idx, u)` returns an `ElementDamageInfo` containing:

- `element_index` — global index in the model,
- `damage_index` — scalar damage measure $D \in [0, \infty)$,
- `max_gp` — Gauss point with highest fiber damage,
- `max_fiber` — fiber index within that GP.

`evaluate_fibers(elem, idx, u)` returns a `std::vector<FiberDamageInfo>`, one per fiber, with per-fiber position (y, z), strain ε, stress σ, and individual damage index.

Both methods receive the raw PETSc `Vec u` (current displacement) for criteria that need element-local state beyond what `section_snapshots()` provides.

54.3.3 MaxStrainDamageCriterion

The default criterion evaluates

$$D_i = \frac{|\varepsilon_{xx,i}|}{\varepsilon_{\text{ref}}}, \qquad D = \max_i D_i \tag{54.1}$$

where ε_{ref} is a user-supplied reference strain (typically the yield strain $\varepsilon_y = f_y/E_s$). Values $D > 1$ indicate yielding.

54.3.4 CallableDamageCriterion and `make_damage_criterion`

For rapid prototyping, users can inject a lambda:

```
auto custom = fall_n::make_damage_criterion(
    "ParkAng",
    [](const StructuralElement& elem,
       std::size_t idx, Vec u) -> ElementDamageInfo {
        // user logic here
        return {idx, damage_index};
    });
```

The `CallableDamageCriterion` owns the function object and supports `clone()` for deep copying.

54.3.5 DamageTracker Observer

`DamageTracker<ModelT>` is a composable observer that evaluates the damage criterion at configurable intervals:

- `on_step()`: evaluates all elements, maintains a sorted ranking and a peak (envelope) ranking.
- `on_analysis_end()`: prints the top-N most damaged elements across the entire analysis.

```
fall_n::MaxStrainDamageCriterion criterion(eps_yield);
fall_n::DamageTracker<ModelT> tracker(criterion, /*interval=*/10);
```

54.4 Fiber Hysteresis Recorder

The `FiberHysteresisRecorder<ModelT>` observer discovers fibers at the first step, classifies them by material type (concrete vs. steel), and records complete stress–strain time-histories $(\varepsilon_{xx}(t), \sigma_{xx}(t))$ for later hysteresis plotting.

54.4.1 Architecture

Fiber classification. A user-injected `FiberClassifier` function maps each `FiberSectionSample` to a `FiberMaterialClass`:

```
enum class FiberMaterialClass { Concrete, Steel, Unknown };

using FiberClassifier = std::function<
    FiberMaterialClass(const FiberSectionSample&,
                       std::size_t elem_idx)>;
```

The default classifier uses a heuristic based on the initial tangent stiffness (stress/strain ratio at the snapshot), but users can override it.

Discovery phase. On the first time step, the observer iterates all target elements, calls `section_snapshots()`, and creates a `FiberTrack` for each fiber with classification metadata.

Recording. Each subsequent step appends (ε, σ) to the corresponding track.

Post-analysis. `write_hysteresis_csv(basename)` exports two CSV files: `_concrete.csv` and `_steel.csv`, each with columns: `elem, gp, fiber, y, z, peak_damage, eps_1, sig_1, eps_2, sig_2, ...`

54.4.2 Integration with DamageCriterion

After the analysis, the recorder internally runs the configured `DamageCriterion` (default: `MaxStrainDamageCri` to sort fibers by peak damage. The `top_fibers(mat_class)` method returns the top-N most damaged tracks of a given material class, providing exactly the "extreme fibers" requested for hysteresis plots.

54.5 Observer Wiring: FiberRecorder and ElementRecorder

Prior to this work, `FiberRecorder::on_step()` and `ElementRecorder::on_step()` in `Observers.hh` contained `TODO` stubs. Both now use `section_snapshots()` to populate their internal data structures:

FiberRecorder. Each step, the recorder iterates elements, obtains snapshots with `has_fibers()`, and stores per-fiber strain/stress from the `FiberSectionSample` span.

ElementRecorder. Each step, the recorder extracts beam section properties (E, G, A, I_y, I_z, J) from `BeamSectionConstitutiveSnapshot` or shell properties from the `ShellSectionConstitutiveSnapsho`

54.6 Five-Story RC Building Under El Centro

`main_seismic.cpp` implements a complete seismic analysis example:

54.6.1 Structural Configuration

Parameter	Value
Stories	5
Story height	3.0 m
Bay width	5.0 m
Column section	0.50×0.50 m RC
Beam section	0.30×0.50 m RC
Slab thickness	0.15 m
Concrete f'_c	28 MPa (Kent–Park)
Steel f_y	420 MPa (Menegotto–Pinto)

54.6.2 Element Formulations

- **Columns and beams:** `BeamElement<TimoshenkoBeam3D, 3, beam::Corotational>` with fiber sections built via `make_rc_column_section` and `make_rc_beam_section`.
- **Slabs:** `CorotationalMITC4Shell<>` (MITC4 assumed-strain shell with corotational kinematics) using `MindlinShellMaterial`.

The combination of corotational beams with MITC4 shells avoids the membrane locking of standard displacement-based shells and maintains numerical stability under large rotations.

54.6.3 Loading Sequence

1. **Gravity ramp**: self-weight applied as a quasi-static ramp over the first time steps.
2. **Ground motion**: the El Centro 1940 NS record (scaled to m/s^2) applied in the X-direction via `BoundaryConditionSet::add_ground_motion()`. The `DynamicAnalysis` driver pre-computes the influence vector $\mathbf{M}\hat{\mathbf{g}}$ and applies the pseudo-force $a_g(t)\,\mathbf{M}\hat{\mathbf{g}}$ at each time step.

54.6.4 Observer Pipeline

The example configures a six-component `CompositeObserver`:

1. `ProgressPrinter`: per-step summary,
2. `FiberRecorder`: fiber-level data,
3. `ElementRecorder`: element-level data,
4. `ResponseRecorder`: time-history at selected nodes,
5. `VTMExporter`: VTK output for visualization,
6. `DamageTracker`: damage ranking (every 10 steps),

7. `FiberHysteresisRecorder`: hysteresis curves export.

After the analysis, the `DamageTracker` prints the top-10 most damaged elements, and the `FiberHysteresisRecorder` exports hysteresis CSV files for the extreme concrete and steel fibers.

54.6.5 Time Integration

The implicit Generalized-α method (`TSALPHA2` in PETSc) is used with:

- $\Delta t = 0.005$ s,
- Rayleigh damping (α_M, β_K targeting $\xi = 5\%$ for the first two modes),
- total duration $T = 10.0$ s (matching the record length).

54.7 Test Suite

`tests/test_seismic_infrastructure.cpp` validates the full infrastructure stack with nine test functions and 33 individual assertions:

#	Test	Assertions
1	Parse El Centro record	5
2	`TimeFunction` evaluation	5
3	Scale factor ($g \to$ m/s^2)	1
4	`section_snapshots()` beam fibers	4
5	`section_snapshots()` elastic beam	3
6	`MaxStrainDamageCriterion`	3
7	`CallableDamageCriterion`	5
8	`GroundMotionBC` integration	5
9	`section_snapshots()` for shells	2
	Total	33

Tests 4–6 use a standalone `BeamFixture3D` that constructs beam elements without a `Domain`:

```
struct BeamFixture3D {
    Node<3> n0{0, 0.0, 0.0, 0.0};
    Node<3> n1{1, 0.0, 0.0, 3.0};
    LagrangeElement3D<2> element{...};
    GaussLegendreCellIntegrator<2> integrator{};
    ElementGeometry<3> geom{element, integrator};
    BeamFixture3D() { geom.set_sieve_id(0); }
};
```

Test 9 uses an analogous `ShellFixture3D` with four nodes and a `LagrangeElement3D<2,2>`.

54.8 Build System Integration

54.8.1 CMake Targets

Two targets were added to `CMakeLists.txt`:

- `fall_n_seismic`: the five-story RC building example (`main_seismic.cpp`), linked against MPI, PETSc, Eigen3, VTK, OpenMP, and matplot++.
- `fall_n_seismic_infra_test`: the unit test executable, registered with CTest (label: `unit`).

54.8.2 Header Organization

- `src/model/GroundMotionRecord.hh` is included by `header_files.hh`.
- `src/analysis/DamageCriterion.hh` and `src/analysis/FiberHysteresisRecorder.hh` are included via `src/analysis/Analysis.hh`.

54.9 Design Rationale

54.9.1 Why a Virtual on StructuralElement?

The alternative to adding `section_snapshots()` would be runtime type-switching with `as<T>()` for every concrete element type. This violates the Open–Closed Principle: every new element type would require updating every observer. The virtual approach confines knowledge of "how to extract sections" to the element's `Model<T>` specialization.

The `if constexpr (requires { element_.sections(); })` guard uses C++20 concepts at compile time to enable the override only for elements that have sections, making the virtual a zero-overhead pass-through for element types that do not.

54.9.2 Why Strategy Pattern for Damage?

Seismic damage metrics vary widely:

- maximum strain (implemented as default),
- Park–Ang index [**?**],
- inter-story drift ratio,
- energy-based criteria,
- user-defined combinations.

Making the criterion a pluggable strategy allows researchers to inject domain-specific metrics *without modifying library code*. The `CallableDamageCriterion` enables one-line injection via lambda.

54.9.3 Why a Separate Hysteresis Recorder?

Hysteresis curves require per-fiber, per-step time-series $(\varepsilon(t), \sigma(t))$. This is fundamentally different from the snapshot-based `FiberRecorder` (latest step only) or the scalar `DamageTracker` (peak ranking only). A dedicated observer avoids polluting existing components with time-history storage responsibilities.

54.10 Summary of Files

File	Purpose
`data/input/earthquakes/el_centro_1940_ns.dat`	El Centro 1940 NS record (406 points)
`src/model/GroundMotionRecord.hh`	Parser, accessors, `TimeFunction` conversion
`src/analysis/DamageCriterion.hh`	`DamageCriterion` ABC, `MaxStrain`, `Callable`, `DamageTracker`
`src/analysis/FiberHysteresisRecorder.hh`	Fiber hysteresis tracking and CSV export
`src/elements/StructuralElement.hh`	Added `section_snapshots()` virtual
`src/analysis/Observers.hh`	Wired `FiberRecorder`/`ElementRecorder` via `section_snapshots()`
`main_seismic.cpp`	Five-story corotational RC building example
`tests/test_seismic_infrastructure.cpp`	9 tests, 33 assertions

Chapter 55

Seismic RC Building: Results and Analysis

This chapter presents and analyses the numerical results obtained from the nonlinear dynamic simulation of a five-story reinforced-concrete (RC) building subjected to the El Centro 1940 earthquake record. The analysis was carried out using the `fall_n_seismic` executable with nonlinear fiber sections and small-strain beam kinematics. All post-processing figures were generated with a Julia helper script (`scripts/plot_seismic_rc_results.jl`).

55.1 Problem Description

55.1.1 Structural Geometry

The model represents a regular five-story building with a 4×3-axis floor plan. The grid axes are located at $x = \{0, 6, 12, 18\}$ m and $y = \{0, 5, 10\}$ m, giving three bays of 6 m in the x-direction and two bays of 5 m in the y-direction. The storey height is $h_s = 3.20$ m for all five levels, producing a total building height of $H = 16.0$ m.

The structural system consists of:

- **Columns**: 3D Timoshenko beam elements with cross section $b \times h = 0.50 \times 0.50$ m, cover of 40 mm, longitudinal bars of $\phi\,25$ mm, and tie spacing of 100 mm.
- **Beams**: 3D Timoshenko beam elements with cross section 0.30×0.60 m, cover of 40 mm, and longitudinal bars of $\phi\,20$ mm.
- **Slabs**: MITC4 Mindlin–Reissner shell elements with thickness $t = 0.15$ m (linear elastic).

55.1.2 Material Properties

Table 55.1: Material properties used in the seismic RC building analysis.

Component	Property	Value	Unit
Columns — concrete	f'_c	35	MPa
Beams — concrete	f'_c	28	MPa
Reinforcing steel	E_s	200 000	MPa
	f_y	420	MPa
	strain-hardening b	0.01	—
Slab (elastic)	E	25 000	MPa
	ν	0.20	—

The concrete behaviour is modelled with the **Kent–Park** law, which captures compressive stress degradation and confinement effects from the transverse reinforcement. Longitudinal steel

uses the **Menegotto–Pinto** model with a strain-hardening ratio of $b = 0.01$, providing smooth hysteretic transitions during load reversals.

Both column and beam sections are discretised into fibers: concrete patches covering the cross-sectional area and individual rebar fibers with their respective areas. The fiber classification criterion used in the hysteresis recorder identifies fibers with area < 0.001 m^2 as steel, and the remainder as concrete.

55.1.3 Mass and Damping

The RC density is $\rho = 2400$ kg/m^3 ($= 2.4 \times 10^{-3}$ MN·s^2/m^4 in the adopted unit system). **Rayleigh damping** with a target ratio $\xi = 5\%$ is applied at two reference frequencies:

$$\omega_1 = \frac{2\pi}{T_1} \approx 10.47 \text{ rad/s} \quad (T_1 = 0.60 \text{ s}), \qquad \omega_3 = \frac{2\pi}{T_3} \approx 52.36 \text{ rad/s} \quad (T_3 = 0.12 \text{ s}). \tag{55.1}$$

These correspond to the estimated first and third modal periods of the building frame.

55.2 Seismic Input: El Centro 1940

The ground-motion excitation is the **El Centro 1940 NS component** (S00E), recorded at El Centro Array #9 (USGS Station 117) during the May 18, 1940 Imperial Valley earthquake ($M_w = 6.9$). This record is one of the most widely used accelerograms in earthquake engineering and is included in the library as `data/input/earthquakes/el_centro_1940_ns.dat`.

Key characteristics of the record:

- **PGA**: 0.3194 $g \approx 3.13$ m/s^2
- **Duration**: 10.0 s (primary energy concentrated in the first ~5 s)
- **Sampling**: $\Delta t = 0.02$ s (50 samples/s) for $t \in [0, 8]$ s; coarser sampling thereafter
- **Total data points**: 405

The acceleration is applied as a **uniform base excitation** in the x-direction via the `BoundaryConditionSet` ground-motion interface. Figure 55.1 shows the complete accelerogram with the analysis window highlighted.



Figure 55.1: El Centro 1940 NS component: acceleration time history in units of g. The red marker indicates the PGA at $t \approx 2.12$ s. The shaded region marks the 10 s analysis window used in the simulation.

55.3 Analysis Configuration

The time-stepping parameters are summarised in Table 55.2.

Table 55.2: Time integration and solver parameters.

Parameter	Value	Description
Gravity ramp time	1.00 s	Linear ramp from 0 to full g
Total time	10.0 s	First 10 s of El Centro record
Time step Δt	0.005 s	2000 steps in total
VTK output interval	50 steps	1 VTK frame every 0.25 s
Damage eval. interval	10 steps	Every 0.05 s

The **PETSc TS** integrator with the **Generalised-α** scheme (`TSALPHA2`) is used, with spectral radius $\rho_\infty = 0.9$ for moderate high-frequency dissipation. No adaptive time-stepping is employed (`TSADAPTNONE`). The nonlinear system at each step is solved with **Newton–Raphson** (`SNES newtonls`, backtracking line search), using a direct LU solver (`KSP preonly + PC lu`). A tolerance of up to 10 SNES failures is allowed before aborting.

Gravity loads are computed from the element self-weight (columns, beams, and slabs), assembled into a global force vector, and applied with a linear ramp during the first 1.0 s. The seismic acceleration is then superimposed as a pseudo-force $\mathbf{f}_{\text{eq}}(t) = -\mathbf{M}\,\hat{\mathbf{e}}_x\,a_g(t)$.

55.4 Observer Pipeline

The simulation employs a composite observer chain with six components:

1. **ConsoleProgressObserver** — prints progress every 20 steps (5% increments).
2. **VTK Time-Series Exporter** — writes `seismic_building_NNNNNN.vtm` multiblock files every 50 steps, including axis, fiber, material site, section, and surface representations via the `StructuralVTMExporter`.
3. **NodeRecorder** — records the displacement DOFs (u_x, u_y, u_z) of the roof corner node (node 71) at every step, exported to `roof_displacement.csv`.
4. **MaxResponseTracker** — tracks peak translational responses.
5. **DamageTracker** — evaluates a `MaxStrainDamageCriterion` (with reference strain $\varepsilon_{\text{ref}} = f_y/E_s = 0.0021$) every 10 steps, reporting the 10 most-damaged elements.
6. **FiberHysteresisRecorder** — selects the 5 most extreme concrete and 5 most extreme steel fibers (by the same damage criterion) and records their full stress–strain histories, exported to `hysteresis_concrete.csv` and `hysteresis_steel.csv`.

55.5 Results

55.5.1 Concrete Fiber Response

Figure 55.2 shows the stress–strain hysteresis loops of the five most-strained concrete fibers in element 6 (a first-story base column). All fibers exhibit compressive strains only, with a maximum compressive strain of $\varepsilon_{\min} \approx -6.47 \times 10^{-5}$ and a corresponding peak stress of $\sigma_{\min} \approx -2.23$ MPa.

This represents only **6.4% of the compressive capacity** ($f'_c = 35$ MPa), confirming that the concrete remains firmly in the linear elastic regime under this seismic excitation. The hysteresis curves are effectively linear, showing no evidence of cracking or crushing. The stress build-up during the first second corresponds to the gravity-ramp phase.



Figure 55.2: Concrete fiber hysteresis curves (stress vs. strain) for the five most-damaged concrete fibers in element 6 (base column). All fibers track nearly identical paths, indicating a predominantly axial (gravity-dominated) response.

55.5.2 Steel Fiber Response

Figure 55.3 presents the hysteresis curves for the five most-strained steel (rebar) fibers in the same base column (element 6). The peak compressive strain reaches $\varepsilon_{\min} \approx -6.48 \times 10^{-5}$ with a corresponding stress of $\sigma_{\min} \approx -12.95$ MPa.

Compared to the steel yield strain $\varepsilon_y = f_y/E_s = 420/200{,}000 = 0.0021$ and yield stress $f_y = 420$ MPa, the demand represents only **3.1% of the steel yield strain** and **3.1% of the yield stress**. The steel fibers remain entirely elastic throughout the analysis, and the Menegotto–Pinto law behaves as a linear model.

55.5.3 Stress Time Histories

Figures 55.4 and 55.5 show the stress time histories of the representative concrete and steel fibers, respectively. Both responses exhibit a clear three-phase behaviour:

1. **Gravity ramp** ($0 \le t \le 1$ s): stresses build up linearly as the self-weight load is gradually applied.
2. **Strong-motion phase** ($1 < t \lesssim 6$ s): stress oscillations are visible, driven by the seismic acceleration. The amplitude of these oscillations is small compared to the static gravity stress.
3. **Free-vibration decay** ($t > 6$ s): the oscillations attenuate due to Rayleigh damping, and the stresses tend toward steady-state gravity values.

55.5.4 Combined Response Overview

Figure 55.6 provides a four-panel summary of the seismic input and structural response, showing: (a) the ground acceleration; (b) concrete fiber hysteresis; (c) steel fiber hysteresis; (d) combined stress time histories.



Figure 55.3: Steel fiber hysteresis curves (stress vs. strain) for the five most-damaged rebar fibers in element 6. The response is fully linear and well below yield.



Figure 55.4: Concrete fiber stress time history (element 6, fiber 31). The gravity ramp is visible in [0, 1] s, followed by seismically-induced oscillations.



Figure 55.5: Steel fiber stress time history (element 6, fiber 86). The pattern is analogous to the concrete fiber, with larger absolute stresses due to the higher steel modulus.



Figure 55.6: Combined panel: (a) El Centro ground acceleration, (b) concrete hysteresis, (c) steel hysteresis, (d) fiber stress histories.

55.6 Discussion and Interpretation

55.6.1 Demand-to-Capacity Ratios

Table 55.3 summarises the demand-to-capacity ratios (DCR) for the most-stressed fibers.

Table 55.3: Demand-to-capacity summary for the base column fibers.

Material	Peak strain	Capacity strain	Peak stress [MPa]	DCR [%]
Concrete	-6.47×10^{-5}	-2.0×10^{-3} (typical ε_{c0})	-2.23	6.4
Steel	-6.48×10^{-5}	-2.1×10^{-3} (ε_y)	-12.95	3.1

The DCRs of approximately 3–6% indicate that the structure is substantially overdesigned for this level of seismic demand. This is physically consistent with the characteristics of the building: 0.50×0.50 m columns with $f'_c = 35$ MPa provide very high stiffness and strength for a five-story structure subjected to a moderate PGA of $0.32\,g$.

55.6.2 Gravity Dominance

A notable feature of the results is the dominance of gravity loads over seismic effects. The stress time histories show that the bulk of the compressive stress is developed during the gravity ramp (0–1 s), with the subsequent seismic oscillations producing relatively small perturbations about the gravity-induced stress state. This observation is consistent with the fact that:

- the building is stiff (estimated $T_1 \approx 0.60$ s), resulting in small lateral displacements;
- the columns carry significant axial load from five storeys of self-weight plus slab dead load;
- the PGA of $0.32\,g$ is moderate relative to the structural capacity.

55.6.3 Essentially Elastic Behaviour

Both the concrete and steel fiber responses stay well within the linear elastic range. The maximum concrete strain of $\varepsilon \approx 6.5 \times 10^{-5}$ is more than an order of magnitude below the typical peak strain $\varepsilon_{c0} \approx 2 \times 10^{-3}$ at which the Kent–Park model reaches peak stress. Similarly, the steel strain is roughly 30 times below yield ($\varepsilon_y = 0.0021$).

This means that, for this particular configuration:

1. The nonlinear Kent–Park and Menegotto–Pinto laws degenerate to their initial linear branches.
2. No hysteretic energy dissipation occurs through material nonlinearity; all damping is provided by the Rayleigh mechanism.
3. The results would be virtually identical to a linear-elastic analysis with cracked-section stiffnesses.

This is not a deficiency of the solver but rather a physical consequence of the chosen geometry, materials, and loading intensity. The example primarily serves as a **verification case** for the seismic analysis infrastructure: ground-motion input, consistent mass, Rayleigh damping, the observer pipeline, VTK output, and the fiber hysteresis recorder all operate correctly through a full 10 s dynamic analysis.

55.6.4 Pathways to Inelastic Response

To exercise the full nonlinear hysteretic behaviour of the Kent–Park and Menegotto–Pinto models, future analyses could:

- Scale the ground-motion amplitude (e.g. PGA $= 1.0\,g$);
- Reduce column and beam dimensions to lower the stiffness and strength reserve;
- Increase the number of storeys or the storey mass;

- Switch to the corotational formulation for P–Δ effects, amplifying the demand.

55.7 VTK Visualisation

The analysis generates a time series of VTK multiblock files (`.vtm`) at an interval of 50 time steps (0.25 s), resulting in approximately 86 frames covering the full 10 s simulation. Each frame includes five polydata blocks:

1. **Axis** (`_axis.vtp`): the beam centreline representation.
2. **Fibers** (`_fibers.vtp`): resolved fiber locations at each Gauss point.
3. **Material sites** (`_material_sites.vtp`): integration point locations with constitutive data.
4. **Sections** (`_sections.vtp`): reconstructed sectional profiles.
5. **Surface** (`_surface.vtp`): the outer shell surface for slab visualisation.

A ParaView PVD collection file (`seismic_building.pvd`) is also generated, enabling animated playback of the full time history.

55.8 Summary

- The five-story RC building was analysed under 10 s of the El Centro 1940 NS record (PGA = $0.32\,g$) using nonlinear fiber beam elements, elastic shell slabs, consistent mass, and 5% Rayleigh damping.
- The concrete and steel fibers remained in the elastic regime, with demand-to-capacity ratios of 6.4% and 3.1%, respectively.
- The gravity-induced axial compression dominates the stress state in the base column fibers.
- The simulation serves as a successful integration test of the full seismic analysis infrastructure: earthquake parsing, dynamic time integration, composite observer pipeline, VTK export, and fiber hysteresis recording.
- Pushing the structure into the inelastic range requires either amplifying the ground motion or reducing the structural capacity.

Chapter 56

Ko–Bathe Plastic-Fracturing Concrete Model

This chapter documents the implementation of a two-dimensional plastic-fracturing concrete model following the formulation proposed by Ko and Bathe [**?**] for finite element analysis. The model combines three physical mechanisms—*fracturing*, *plasticity*, and *cracking*—in a strain-driven framework suitable for plane stress problems. The implementation is contained in a single header file, `KoBatheConcrete.hh`, and satisfies all concept levels of the `fall_n` constitutive interface.

56.1 Theoretical Background

The model belongs to the family of *plastic-fracturing* constitutive relations for concrete, which recognise that the nonlinear behaviour of concrete under multi-axial loading arises from three distinct phenomena [**?**, **?**]:

(i) **Fracturing:** progressive degradation of the elastic tangent moduli as internal micro-cracking develops under compression.

(ii) **Plasticity:** irrecoverable strains that accumulate once the failure envelope is reached.

(iii) **Cracking:** discrete tensile fracture planes (smeared) that form when the maximum principal stress exceeds the tensile capacity.

These three mechanisms are coupled through the octahedral stress invariants and operate in sequence within each strain increment: compressive stiffness degrades via fracturing; if the resulting stress state violates a yield surface, plasticity activates; if the local tensile stress exceeds the crack function, a smeared crack is initiated.

56.1.1 Octahedral Stress Invariants

The model uses stress invariants as driving quantities for both fracturing and cracking. For a plane stress state $\boldsymbol{\sigma} = (\sigma_{xx}, \sigma_{yy}, \tau_{xy})^T$ with $\sigma_{zz} = 0$, the principal stresses are

$$\sigma_1 = \frac{\sigma_{xx} + \sigma_{yy}}{2} + \sqrt{\left(\frac{\sigma_{xx} - \sigma_{yy}}{2}\right)^2 + \tau_{xy}^2}, \qquad \sigma_2 = \frac{\sigma_{xx} + \sigma_{yy}}{2} - \sqrt{\left(\frac{\sigma_{xx} - \sigma_{yy}}{2}\right)^2 + \tau_{xy}^2},$$

with $\sigma_3 = 0$. The octahedral normal stress and the deviatoric invariant read

$$\sigma_o = \frac{\sigma_1 + \sigma_2}{3}, \tag{56.1}$$

$$\tau_o = \frac{\sqrt{2\,J_2}}{3} = \frac{1}{3}\sqrt{\sigma_{ij}^{\mathrm{dev}}\,\sigma_{ij}^{\mathrm{dev}}}, \tag{56.2}$$

where $J_2 = (\sigma_1^2 + \sigma_2^2 - \sigma_1\sigma_2)/3$ is the second deviatoric stress invariant for plane stress ($\sigma_3 = 0$). The sign convention is engineering: compression gives $\sigma_o < 0$.

Note: The paper's τ_o (Eq. 2b in [**?**]) is $\sqrt{2J_2}/3$, which differs from the classical octahedral shear stress $\tau_{\text{oct}} = \sqrt{2J_2/3}$ by a factor of $\sqrt{3}$.

56.1.2 Fracturing Mechanism

The ascending non-linear branch of the stress–strain curve is captured entirely by degrading the elastic moduli. The secant bulk and shear moduli are defined as *rational* functions (Eqs. 10a–b in [**?**]):

$$K_s(\sigma_o) = \frac{K_e}{1 + A\,(-\sigma_o/f_c')^{\,b-1}}, \tag{56.3}$$

$$G_s(\tau_o) = \frac{G_e}{1 + c\,(\tau_o/f_c')^{\,d-1}}, \tag{56.4}$$

where K_e and G_e are the initial elastic moduli, f_c' is the uniaxial compressive strength, and A, b, c, d are empirically fitted coefficients depending on f_c' (see Section 56.1.6). The formula (56.3) applies for $-\sigma_o/f_c' \leq 2$; an extended branch is defined for higher confinement.

The fracture history is driven by the *maximum* octahedral invariants ever reached:

$$\bar{\sigma}_o = \min_{t' \leq t} \sigma_o(t'), \qquad \bar{\tau}_o = \max_{t' \leq t} \tau_o(t').$$

During unloading $\sigma_o > \bar{\sigma}_o$, the moduli remain frozen at their last-degraded values, representing the irreversibility of micro-cracking.

The tangent moduli follow from differentiation (Eqs. 11a–b):

$$K_c = \frac{K_e}{1 + A\,b\,(-\bar{\sigma}_o/f_c')^{\,b-1}}, \tag{56.5}$$

$$G_c = \frac{G_e}{1 + c\,d\,(\bar{\tau}_o/f_c')^{\,d-1}}. \tag{56.6}$$

Confining pressure σ_{id}. A confining pressure correction is introduced (Eq. 10b in the paper):

$$\sigma_{\text{id}} = \frac{k\,f_c'\,(\tau_o/f_c')^n}{1 + l\,(-\sigma_o/f_c')^m}, \tag{56.7}$$

which is subtracted from the volumetric stress contribution:

$$\sigma_{ij} = 2\,G_s\,e_{ij}^{\text{dev}} + K_s\,e_{kk}\,\delta_{ij} - \sigma_{\text{id}}\,\delta_{ij}. \tag{56.8}$$

Given K and G, the plane stress constitutive matrix is

$$\mathbf{C}^{\text{ps}} = \frac{E}{1-\nu^2}\begin{bmatrix} 1 & \nu & 0 \\ \nu & 1 & 0 \\ 0 & 0 & \frac{1-\nu}{2} \end{bmatrix}, \qquad E = \frac{9KG}{3K+G}, \quad \nu = \frac{3K-2G}{2(3K+G)}.$$

56.1.3 Compression Coordinate System

Plasticity yield surfaces are defined not in principal-stress space but in a *compression coordinate* system. Given the principal elastic strains ($\varepsilon_1 \geq \varepsilon_2$), define the compressive magnitudes (positive in compression)

$$D_1 = \max(-\varepsilon_1,\, 0), \qquad D_2 = \max(-\varepsilon_2,\, 0),$$

and the compression coordinates

$$\tilde{e}_1 = D_2 - D_1 \geq 0 \qquad \text{(deviatoric compression)}, \tag{56.9}$$

$$\tilde{e}_2 = D_1 + D_2 \geq 0 \qquad \text{(volumetric compression)}. \tag{56.10}$$

For the plasticity yield functions, these are mapped to a set of three elastic coordinates:

$$\hat{e}_1 = \frac{|\tilde{e}_2|}{\sqrt{3}}, \qquad \hat{e}_2 = \tilde{e}_1, \qquad \hat{e}_3 = \frac{\tilde{e}_2}{2},$$

corresponding to hydrostatic, uniaxial, and biaxial loading paths respectively.

56.1.4 Plasticity Yield Surfaces

Three yield functions are defined in the compression coordinate space (Eq. 15c–d in [**?**]):

$$f_1 = |\hat{e}_1| - f'_c\, f_{p1}(\hat{e}_{p1}) \leq 0, \tag{56.11}$$

$$f_2 = \hat{e}_2 - f'_c\, f_{p2}(\hat{e}_{p2}) \leq 0, \tag{56.12}$$

$$f_3 = \hat{e}_3 - f'_c\, f_{p3}(\hat{e}_{p3}) \leq 0, \tag{56.13}$$

where $\hat{e}_{pj}$ are effective plastic strains accumulated per surface (Eq. 15b). The failure curves (Eq. 15d) are:

$$f_{p1}(\hat{e}_{p1}) = c_{p1}\left(1 + \frac{\hat{e}_{p1} - a}{a}\right)^{-s} \hat{e}_{p1}, \tag{56.14}$$

$$f_{p2}(\hat{e}_{p2}) = c_{p2} \exp\left[-\left(\frac{\hat{e}_{p2}}{c_2}\right)^{m_2}\right] \hat{e}_{p2}, \tag{56.15}$$

$$f_{p3}(\hat{e}_{p3}) = c_{p3} \exp\left[-\left(\frac{\hat{e}_{p3}}{c_3}\right)^{m_3}\right] \hat{e}_{p3}, \tag{56.16}$$

with fixed constants $c_{p1} = 3$, $c_{p2} = 36$, $c_{p3} = 12$ and hydrostatic parameters $a = 2.5 \times 10^{-5}$, $s = 0.8$.

The Appendix C coefficients m_2, c_2, m_3, c_3 are coupling parameters that depend on the hydrostatic effective plastic strain $\hat{e}_{p1}$ (Eqs. C.1–C.2 in the paper):

$$m_2 = \frac{1}{\ln\left(\sqrt{2/3}\,\alpha_2/(\beta_2\,\hat{\varepsilon}_{p2})\right)}, \qquad c_2 = (\beta_2\,\hat{\varepsilon}_{p2})\, m_2^{1/m_2}, \tag{56.17}$$

$$\alpha_2 = 1 + 0.575\,(e_{cp2})^{0.315}, \qquad \beta_2 = 1 + 8.4\,(e_{cp2})^{0.25}, \tag{56.18}$$

$$e_{cp2} = \max(0,\ K_e\,\hat{e}_{p1} - 0.45), \qquad e_{cp3} = \max(0,\ K_e\,\hat{e}_{p1} - 2.17), \tag{56.19}$$

with reference plastic strains $\hat{\varepsilon}_{p2} = 0.0012$ and $\hat{\varepsilon}_{p3} = 0.0025$.

The return mapping uses a Newton iteration per active surface (Eqs. 27–29): for each $f_j > 0$, solve

$$f_j = \hat{e}_j - \Delta\lambda_j - f'_c\, f_{pj}(\hat{e}_{pj} + \sqrt{2/3}\,\Delta\lambda_j) = 0$$

for $\Delta\lambda_j \geq 0$ using

$$\Delta\lambda_j^{(I+1)} = \Delta\lambda_j^{(I)} - \frac{f_j^{(I)}}{-1 - \sqrt{2/3}\,\partial(f'_c f_{pj})/\partial\hat{e}_{pj}}.$$

56.1.5 Cracking Mechanism

Tensile cracking is governed by a Menetréy–Willam crack function in the octahedral stress plane (Eq. 16 in [**?**]):

$$g(\sigma_o, \tau_o) = \tau_o - \frac{0.944\, f'_c}{w(e)} \left(t_p - \frac{\sigma_o}{f'_c} \right)^{0.724}, \tag{56.20}$$

where $t_p = f_t / f'_c$ is the tensile-to-compressive strength ratio, and $w(e)$ is an elliptic function of the eccentricity parameter:

$$w(e) = \frac{4(1-e^2)\cos^2\theta + (2e-1)^2}{2(1-e^2)\cos\theta + (2e-1)\sqrt{4(1-e^2)\cos^2\theta + 5e^2 - 4e}}, \tag{56.21}$$

$$e = 0.670551\,(t_p - \sigma_o / f'_c)^{0.133}. \tag{56.22}$$

A crack initiates when $g > 0$ *and* the maximum principal stress is tensile.

The model tracks up to two orthogonal smeared cracks in each material point. The second crack, when formed, is forced to be perpendicular to the first. Each crack possesses:

- a fixed normal direction $\mathbf{n}$,
- an opening strain ε_{nn} (projected normal strain),
- a maximum historical opening strain $\bar{\varepsilon}_{nn}$,
- a closing flag (re-contact when $\varepsilon_{nn} < 0$).

Cracked tangent (Eq. 21). After a crack forms, the tangent matrix is modified in the crack-local coordinate system with stiffness retention parameters:

$$E_{nn} = \eta_N\, \lambda_a \qquad \text{(normal, } \eta_N = 0.0001\text{)}, \tag{56.23}$$

$$G_{ns} = \eta_S\, G_c \qquad \text{(shear, } \eta_S = 0.1\text{)}. \tag{56.24}$$

Tension softening (Eqs. 22–23). For the softening branch between peak and ultimate strains:

$$\varepsilon_{tp} = \frac{f'_c\, t_p}{K_e + \frac{4}{3}\, G_e}, \tag{56.25}$$

$$\varepsilon_{tu} = \frac{2\, G_f}{f'_c\, t_p\, l_b}, \tag{56.26}$$

$$C_{ts} = -\frac{f_t}{\varepsilon_{tp} - \varepsilon_{tu}}, \tag{56.27}$$

where G_f is the fracture energy (N/mm) and l_b is the characteristic element length (mm). When $\varepsilon_{tp} \le \varepsilon_{nn} \le \varepsilon_{tu}$, the normal stiffness E_{nn} is replaced by C_{ts}. When the crack closes ($\varepsilon_{nn} < 0$), full compressive normal stiffness is restored (*re-contact*).

56.1.6 Material Parameters

All coefficients are derived from a single primary parameter: the uniaxial compressive strength f'_c (in MPa, positive).

Elastic moduli (Eq. A.1).

$$K_e = 11000 + 3.2\, f'_c \text{ (MPa)}, \qquad G_e = 9224 + 136\, f'_c + 3296 \times 10^{-15}\, (f'_c)^{8.273} \text{ (MPa)}. \tag{56.28}$$

Fracture degradation (Eqs. A.2–A.4). For $f'_c \leq 31.7$ MPa:

$$A = 0.516, \quad c = 3.573, \quad d = 2.12 + 0.0183\, f'_c, \quad m = -2.415, \quad n = 1.0. \tag{56.29}$$

For all f'_c:

$$b = 2{+}1.81{\times}10^{-8}\,(f'_c)^{4.461}, \quad k = \frac{4}{1 + 1.087\,(\max(f'_c - 15, 0.1))^{0.23}}, \quad l = 0.222{+}0.01086\, f'_c{-}0.000122\,(f'_c)^2. \tag{56.30}$$

For $f'_c > 31.7$ MPa, A, c, d, m, n have extended formulas (see Appendix A of [**?**]).

Tension. The tensile strength ratio follows the fib Model Code approximation

$$t_p = 0.3\,(f'_c)^{-1/3}, \quad \text{clamped to} \quad t_p \in [0.05,\, 0.10]. \tag{56.31}$$

Softening and crack retention. The fracture energy is taken as $G_f = 0.06$ N/mm (default), the element length as $l_b = 100$ mm (default), and the stiffness retention factors as $\eta_N = 0.0001$, $\eta_S = 0.1$.

Table 56.1 summarises the default parameter set for $f'_c = 30$ MPa.

Table 56.1: Default derived parameters for $f'_c = 30$ MPa.

Parameter	**Value**	**Unit**
K_e	11 096	MPa
G_e	13 310	MPa
E	28 524	MPa
ν	0.072	—
A	0.516	—
b	2.07	—
c	3.573	—
d	2.669	—
k	1.32	—
l	0.438	—
m	−2.415	—
n	1.0	—
t_p	0.0965	—
$f_t = t_p f'_c$	2.90	MPa

56.2 Implementation Architecture

The implementation resides in a single header:

`src/materials/constitutive_models/non_lineal/KoBatheConcrete.hh`

and consists of three C++ types.

56.2.1 KoBatheParameters

A plain aggregate containing all material coefficients derived from f'_c at construction time. Includes the elastic moduli, fracture degradation coefficients, confining pressure parameters, tension parameters, and plasticity failure curve constants.

```
struct KoBatheParameters {
    double fc, Ke, Ge, Ee, nue;
    double A_coeff, b_coeff, c_coeff, d_coeff;
    double k_coeff, l_coeff, m_coeff, n_coeff;
    double tp, Gf, lb;
    static constexpr double cp1=3, cp2=36, cp3=12;
    static constexpr double eps_p2_ref=0.0012, eps_p3_ref=0.0025;
    static constexpr double hydro_a=2.5e-5, hydro_s=0.8;
    static constexpr double eta_N=0.0001, eta_S=0.1;

    explicit KoBatheParameters(double fc_MPa,
        double tp_ratio=0.0, double Gf_Nmm=0.06, double lb_mm=100.0);
};
```

56.2.2 KoBatheState

The internal history variable set tracks:

- **Fracture history:** maximum octahedral invariants $\bar{\sigma}_o$ and $\bar{\tau}_o$.
- **Plastic strain:** $\boldsymbol{\varepsilon}^p$ in Voigt format $(\varepsilon^p_{xx}, \varepsilon^p_{yy}, \gamma^p_{xy})$.
- **Effective plastic strains:** $\hat{e}_{p1}, \hat{e}_{p2}, \hat{e}_{p3}$ per yield surface.
- **Crack state:** number of cracks (0, 1, or 2), normal directions, opening strains, and closure flags.
- **Committed total strain:** for state tracking.

The state provides accessors `eps_p()` and `eps_bar_p()` for integration with the library's `InternalFieldSnapsho` post-processing system.

56.2.3 KoBatheConcrete

The main constitutive class satisfying the `fall_n` concept hierarchy:

- **Level 1:** `ConstitutiveRelation` — `compute_response(k, alpha)`, `tangent(k, alpha)`, `commit(alpha, k)`.
- **Level 2b:** `InelasticConstitutiveRelation` — `compute_response(k)`, `tangent(k)`, `update(k)`, `internal_state()`.
- **Level 3:** Combines Level 1 and Level 2b.

56.2.4 Algorithm Flow

Algorithm 1 summarises the evaluation procedure.

56.3 VTK Visualization

The Ko–Bathe model is integrated with the library's VTK post-processing infrastructure via the `InternalFieldSnapshot` mechanism. The following fields are exported at each integration (Gauss) point for visualization in ParaView:

Input : Total strain $\boldsymbol{\varepsilon}$, previous state α_n
Output: Stress $\boldsymbol{\sigma}$, tangent $\mathbf{C}$, updated state α_{n+1}
$\boldsymbol{\varepsilon}^e \leftarrow \boldsymbol{\varepsilon} - \boldsymbol{\varepsilon}_n^p$; `// Elastic strain`
$(K_s, G_s, K_c, G_c, \sigma_{\mathrm{id}}) \leftarrow$ fracture moduli from $(\bar{\sigma}_{o,n}, \bar{\tau}_{o,n})$;
$\boldsymbol{\sigma} \leftarrow \mathbf{C}^{\mathrm{ps}}(K_s, G_s)\,\boldsymbol{\varepsilon}^e - \sigma_{\mathrm{id}}\,\boldsymbol{\delta}$; `// Eq.` (56.8)
$(\sigma_o, \tau_o) \leftarrow$ invariants of $\boldsymbol{\sigma}$; `// Eqs.` (56.1)-(56.2)
Update history: $\bar{\sigma}_o \leftarrow \min(\bar{\sigma}_{o,n}, \sigma_o)$, $\bar{\tau}_o \leftarrow \max(\bar{\tau}_{o,n}, \tau_o)$;
Recompute moduli and stress with updated history;
$\mathbf{C}_{\mathrm{tan}} \leftarrow \mathbf{C}^{\mathrm{ps}}(K_c, G_c)$;
if *max principal stress* > 0 ***and*** $g(\sigma_o, \tau_o) > 0$ **then**
  Initiate new crack with normal along max principal direction;
end
Update crack opening strains, closure flags;
Apply cracking to $\boldsymbol{\sigma}$ and $\mathbf{C}_{\mathrm{tan}}$ via η_N, η_S;
$(\hat{e}_1, \hat{e}_2, \hat{e}_3) \leftarrow$ compression coordinates;
if *any* $f_j > 0$ *(yield violated)* **then**
  Newton return mapping per surface $\rightarrow$ update $\boldsymbol{\varepsilon}^p, \hat{e}_{pj}$;
  $\boldsymbol{\varepsilon}^e \leftarrow \boldsymbol{\varepsilon} - \boldsymbol{\varepsilon}^p$;
  $\boldsymbol{\sigma} \leftarrow \mathbf{C}_{\mathrm{sec}}\,\boldsymbol{\varepsilon}^e - \sigma_{\mathrm{id}}\,\boldsymbol{\delta}$;
end
return $(\boldsymbol{\sigma}, \mathbf{C}_{\mathrm{tan}}, \alpha_{n+1})$;

Algorithm 1: Ko–Bathe constitutive evaluation.

Oriented fracture planes. The crack normal vectors `qp_crack_normal_1` and `qp_crack_normal_2` are stored as 3-component vectors $(n_x, n_y, 0)$. In ParaView, these can be displayed using the *Glyph* filter:

1. Load the Gauss cloud `.vtu` file.
2. Apply the Glyph filter with Glyph Type = Disc or Arrow.
3. Set "Orientation" to `qp_crack_normal_1`.
4. Set "Scale" to `qp_num_cracks` or a constant.
5. Set "Masking Mode" to threshold ≥ 1 on `qp_num_cracks` to show only cracked points.

This produces a visualization of oriented fracture planes at each integration point where cracks have formed.

Implementation details. The snapshot path uses compile-time detection:

- `KoBatheState::eps_p()` $\rightarrow$ `plastic_strain`
- `KoBatheState::eps_bar_p()` $\rightarrow$ `equivalent_plastic_strain`
- `KoBatheState::num_cracks` $\rightarrow$ `InternalFieldSnapshot::num_cracks`
- `KoBatheState::crack_normals` $\rightarrow$ promoted to 3D vectors
- `KoBatheState::sigma_o_max`, `tau_o_max` $\rightarrow$ fracture history scalars

Table 56.2: VTK Gauss-point fields exported for the Ko–Bathe concrete model.

Field name	Components	Description
`qp_stress_voigt`	N_{voigt}	Cauchy stress tensor (standard)
`qp_strain_voigt`	N_{voigt}	Total strain tensor (standard)
`qp_plastic_strain_voigt`	N_{voigt}	Plastic strain tensor
`qp_equivalent_plastic_strain`	1	$\sqrt{\hat{e}_{p1}^2 + \hat{e}_{p2}^2 + \hat{e}_{p3}^2}$
`qp_num_cracks`	1	Number of active cracks (0, 1, 2)
`qp_crack_normal_1`	3	Normal to crack 1 (3D vector)
`qp_crack_normal_2`	3	Normal to crack 2 (3D vector)
`qp_crack_strain_1`	1	Opening strain across crack 1
`qp_crack_strain_2`	1	Opening strain across crack 2
`qp_crack_closed_1`	1	Closure flag: 1.0 = closed
`qp_crack_closed_2`	1	Closure flag: 1.0 = closed
`qp_sigma_o_max`	1	Max octahedral normal stress
`qp_tau_o_max`	1	Max octahedral shear stress

56.4 Concept Satisfaction

The implementation satisfies the three-level concept hierarchy at compile time, verified via `static_assert`:

```
static_assert(ConstitutiveRelation<KoBatheConcrete>);
static_assert(InelasticConstitutiveRelation<KoBatheConcrete>);
static_assert(ExternallyStateDrivenConstitutiveRelation<KoBatheConcrete
    >);
```

56.5 Test Suite

The test suite in `tests/test_ko_bathe_concrete.cpp` comprises eight groups (31 checks), all passing:

1. **Compile-time concept checks** (3 static assertions).
2. **Parameter derivation** for $f'_c = 30$ MPa.
3. **Elastic response** at small strain.
4. **Uniaxial compression** curves for $f'_c = 21$ and 30 MPa, exported to CSV.
5. **Biaxial compression** (equibiaxial and proportional).
6. **Tension cracking** with crack formation and softening.
7. **Fracture moduli degradation** (stiffness reduction verification).
8. **Commit/update cycle consistency** (Level 1 vs Level 2b agreement).

56.6 Design Decisions

1. **Single header.** Consistent with the library's header-only philosophy.



Figure 56.1: Schematic uniaxial compression response: nonlinear ascending (fracturing) and post-peak descent (plasticity).

2. **Rational vs. exponential moduli.** The paper's formulation (56.3)–(56.4) uses rational degradation functions (not exponential), giving a better match to the experimental ascending branch.

3. **Secant–tangent distinction.** Secant moduli (K_s, G_s) for stress; tangent moduli (K_c, G_c) for the algorithmic tangent matrix.

4. **Confining pressure $\sigma_{\mathbf{id}}$.** The stress includes a confining pressure correction (Eq. (56.7)) that accounts for triaxial effects even in the plane stress setting.

5. **Plane stress only.** Extension to 3D requires generalising the compression coordinates, yield surfaces, and crack normal tracking to three orthogonal planes.

6. **VTK integration.** The snapshot-based export provides crack normal vectors as 3D fields for direct ParaView Glyph rendering of oriented fracture planes at integration points.

56.7 Possible Extensions

- **Full 3D generalisation**: extend compression coordinates to all three principal directions; add a third crack plane.
- **Consistent tangent for plasticity**: derive the full algorithmic tangent including the plastic correction.
- **Rate effects**: temperature and strain-rate dependence through modification of the fracture degradation functions.
- **Mesh-adjusted softening**: use actual element sizes from the mesh for the characteristic length l_b.

Chapter 57

Building `fall_n` on Windows (MSYS2/UCRT64)

This chapter documents the full procedure to configure, compile, and run `fall_n` on a 64-bit Windows machine using the MSYS2 UCRT64 toolchain. Every step is reproducible from a clean Windows install and does not require Visual Studio, WSL, or any other Unix compatibility layer beyond MSYS2 itself.

57.1 Prerequisites and Motivations

`fall_n` targets C++23 and depends on several scientific libraries (PETSc, Eigen, VTK, MS-MPI) that are either unavailable or extremely inconvenient to build from source under the MSVC ABI. The chosen toolchain is:

- **MSYS2 UCRT64** — a MinGW-w64 environment based on the Universal C Runtime (UCRT), which ships as a standard component of modern Windows. All packages are installed via the `pacman` package manager, giving reproducible binary packages without local compilation.
- **GCC 15.2** — full C++23 support including `<print>`, `std::expected`, ranges, and concepts.
- **Ninja 1.13 + CMake 4.2** — fast incremental builds.
- **Microsoft MPI (MS-MPI)** — the official MPI runtime for Windows, required by PETSc at link time and at runtime.

The companion library versions used and verified to work are summarised in Table 57.1.

57.2 Step 1 — Install MSYS2

Download the MSYS2 installer from `https://www.msys2.org` and run it. The default installation path is `C:\msys64`. After installation, open the **MSYS2 UCRT64** terminal (not the plain MSYS2 terminal) from the Start menu.

Update the base system before installing anything:

```
pacman -Syu          # update database + core packages; close and reopen
pacman -Su           # finish updating remaining packages
```

Table 57.1: Dependency versions verified on Windows (MSYS2 UCRT64, March 2026).

Library	MSYS2 package name	Version	Notes
GCC	`mingw-w64-ucrt-x86_64-gcc`	15.2.0	C++23
CMake	`mingw-w64-ucrt-x86_64-cmake`	4.2.3	
Ninja	`mingw-w64-ucrt-x86_64-ninja`	1.13.2	
pkg-config	`mingw-w64-ucrt-x86_64-pkgconf`	2.x	
Eigen	`mingw-w64-ucrt-x86_64-eigen3`	5.0.1	header-only
PETSc	`mingw-w64-ucrt-x86_64-petsc`	3.24.5	double/MPI/opt
VTK	`mingw-w64-ucrt-x86_64-vtk`	9.5.2	
MS-MPI SDK	`mingw-w64-ucrt-x86_64-msmpi`	10.1.1	headers+stubs
nlohmann-json	`mingw-w64-ucrt-x86_64-nlohmann-json`	3.12.0	VTK dep
fast_float	`mingw-w64-ucrt-x86_64-fast_float`	8.2.4	VTK dep
utf8cpp	`mingw-w64-ucrt-x86_64-utf8cpp`	4.0.6	VTK dep
MS-MPI runtime	`winget: Microsoft.msmpi`	10.1.12	runtime DLL

57.3 Step 2 — Install Build Tools and Dependencies

All subsequent commands are executed inside the **MSYS2 UCRT64** terminal. Install the compiler toolchain and build tools first:

```
pacman -S \
  mingw-w64-ucrt-x86_64-gcc \
  mingw-w64-ucrt-x86_64-cmake \
  mingw-w64-ucrt-x86_64-ninja \
  mingw-w64-ucrt-x86_64-pkgconf
```

Then install the scientific libraries and their transitive dependencies:

```
pacman -S \
  mingw-w64-ucrt-x86_64-eigen3 \
  mingw-w64-ucrt-x86_64-petsc \
  mingw-w64-ucrt-x86_64-vtk \
  mingw-w64-ucrt-x86_64-msmpi \
  mingw-w64-ucrt-x86_64-nlohmann-json \
  mingw-w64-ucrt-x86_64-fast_float \
  mingw-w64-ucrt-x86_64-utf8cpp
```

Remark 57.1. The packages `nlohmann-json`, `fast_float`, and `utf8cpp` are direct dependencies of the MSYS2 VTK 9.5.2 package and must be installed separately — they are not pulled in automatically. Omitting them causes CMake's `find_package(VTK)` to fail with missing component errors.

Remark 57.2. The MSYS2 PETSc package uses the pkg-config name `petsc-dmo` (double-precision, MPI-enabled, optimized build). The legacy name `PETSc` used in the original Linux `CMakeLists.txt` does not exist; see section 57.8 for the necessary `pkg_search_module` adjustment.

57.4 Step 3 — Install the MS-MPI Runtime

The `mingw-w64-ucrt-x86_64-msmpi` pacman package provides the MS-MPI *SDK* (headers and import libraries) needed to compile and link MPI programs. However, the *runtime DLL* (`msmpi.dll`) is distributed separately by Microsoft and must be installed on every machine that will *run* executables linked against MS-MPI (including during `ctest`).

Install the runtime using winget from a regular Windows PowerShell or Command Prompt (not from inside MSYS2):

```
winget install Microsoft.msmpi --accept-package-agreements
```

This installs `mpiexec.exe` to `C:\Program Files\Microsoft MPI\Bin\` and registers `msmpi.dll` in the Windows system search path. Without this step all PETSc-linked executables will abort at startup with exit code `0xc0000135` (DLL NOT FOUND).

57.5 Step 4 — Configure the CMake Build

Clone (or copy) the repository to a convenient location, e.g. `C:\MyLibs\fall_n`. All remaining commands are executed inside the **MSYS2 UCRT64** terminal.

Create a build directory, configure, and generate:

```
cd /c/MyLibs/fall_n
mkdir -p build && cd build
cmake .. --preset win-debug
```

The `win-debug` preset is defined in `CMakePresets.json` and activates only on Windows hosts. It selects the UCRT64 Ninja generator and sets `CMAKE_BUILD_TYPE=Debug`.

A successful configuration ends with output similar to:

```
-- Configuring done (3.6s)
-- Generating done (0.5s)
-- Build files have been written to: C:/MyLibs/fall_n/build
```

57.6 Step 5 — Compile

From the build directory, invoke Ninja:

```
ninja -j8          # build everything (main + seismic + all 48 tests)
ninja -j8 fall_n   # build only the main executable
```

On a modern 8-core machine the full build (including the Matplot++ dependency fetched via `FetchContent`) takes approximately 4–6 minutes. The following executables are produced in the build directory:

- `fall_n.exe` — main structural analysis executable;
- `fall_n_seismic.exe` — seismic analysis entry point;
- 48 test executables (`fall_n_*_test.exe`).

57.7 Step 6 — Run the Tests

```
ctest -L unit -j4              # fast unit tests only (~4 s)
ctest -L 'unit|integration' -j4
ctest -j4                      # all 48 tests
```

Expected results on a clean install: **44/48 tests pass**. The 4 remaining failures are not related to the Windows port; they are caused by missing mesh and seismic data files that are not included in the repository:

- `seismic_infrastructure`: requires `data/input/earthquakes/el_centro_1940_ns.dat`;

- `nonlinear_validation`, `vertical_slice_gate`: require `tests/validation_cube.msh`;
- `boundary_conditions`: requires `data/input/Beam_LagCell_Ord1_30x6x3.msh`.

57.8 CMake Modifications for Windows Compatibility

This section documents every change that was made to `CMakeLists.txt` and `CMakePresets.json` relative to the original Linux build system. All changes are guarded by platform conditions so the file remains fully functional on Linux without modification.

57.8.1 MinGW-specific compiler and linker flags

GCC on MinGW-w64 requires two flags that are not needed on Linux:

1. **`-lstdc++exp`** — The C++23 `<print>` header (`std::print`, `std::println`) is implemented in a separate experimental static library on MinGW. Without this flag all translation units that include `<print>` fail at link time with undefined references to `_ZSt5printB5cxx11...`.
2. **`-Wa,-mbig-obj`** — The PE/COFF object file format (used on Windows) limits the number of sections in a single `.obj` file to 65 535. Template-heavy translation units in `fall_n` (particularly those including PETSc and VTK headers) exceed this limit and cause the assembler to abort with the error *"too many sections (73659 > 65535)"*. This flag enables the *big-obj* format which raises the limit to over four billion sections.

The corresponding CMake block added to `CMakeLists.txt` is:

```
if(MINGW AND CMAKE_CXX_COMPILER_ID STREQUAL "GNU")
  link_libraries(stdc++exp)
  add_compile_options(-Wa,-mbig-obj)

  # VTK DLLs on MinGW do not export inline template member functions.
  # Predefine these guards to skip the extern template declarations
  # and allow the compiler to instantiate the functions locally.
  add_compile_definitions(
    VTK_AOS_DATA_ARRAY_TEMPLATE_EXTERN
    VTK_GDA_TEMPLATE_EXTERN
  )
endif()
```

57.8.2 VTK extern-template linking fix

This is the most subtle Windows-specific issue. VTK uses *explicit template instantiation* to reduce compile times: the class template `vtkAOSDataArrayTemplate<T>` (and its ancestor `vtkGenericDataArray`
is fully instantiated inside the `libvtkCommonCore.dll` shared library, while all consumer translation units use `extern template` declarations (gated by the macro `VTK_USE_EXTERN_TEMPLATE`, unconditionally defined in `vtkCompiler.h`) to suppress local re-instantiation.

On Linux and macOS this mechanism works perfectly: the shared library exports the symbols and the dynamic linker resolves them at load time. On Windows with MinGW, however, the `extern template` suppression interacts poorly with the PE/COFF `__declspec(dllimport)` mechanism. In particular, *inline methods* such as

```
// vtkAOSDataArrayTemplate.h (line 87)
void SetValue(vtkIdType valueIdx, ValueType value) {
  this->Buffer->GetBuffer()[valueIdx] = value;
}
```

are *already inlined* into the DLL's callers at the time the DLL is built; they are *not emitted as distinct exported symbols*. Yet `extern template class VTKCOMMONCORE_EXPORT vtkAOSDataArrayTemplate<` instructs the consumer translation unit to *not* instantiate the template locally and to expect the symbol from the DLL import library — a symbol that does not exist. The linker then fails with:

```
undefined reference to
  `vtkAOSDataArrayTemplate<long long>::SetValue(long long, long long)'
undefined reference to
  `vtkAOSDataArrayTemplate<int>::SetValue(int, int)'
undefined reference to
  `vtkAOSDataArrayTemplate<double>::SetValue(double, double)'
```

The fix is to predefine the guard macros `VTK_AOS_DATA_ARRAY_TEMPLATE_EXTERN` and `VTK_GDA_TEMPLATE_E` before any VTK header is processed. These macros wrap the `extern template` declarations inside `#ifndef` guards:

```
// vtkAOSDataArrayTemplate.h (abbreviated)
#ifdef VTK_USE_EXTERN_TEMPLATE
#ifndef VTK_AOS_DATA_ARRAY_TEMPLATE_EXTERN   // <-- guard
#define VTK_AOS_DATA_ARRAY_TEMPLATE_EXTERN
extern template class VTKCOMMONCORE_EXPORT vtkAOSDataArrayTemplate<
    double>;
// ... 12 more explicit instantiations ...
#endif
#endif
```

By predeclaring `VTK_AOS_DATA_ARRAY_TEMPLATE_EXTERN` (and the analogous `VTK_GDA_TEMPLATE_EXTERN` for the base class), the `extern template` block is skipped and the compiler instantiates the inline methods locally from the `.h` + `.txx` pair shipped with the package. This is the correct semantics on MinGW: small inline methods should never have been placed behind DLL-import stubs in the first place.

57.8.3 PETSc C++ macro fallbacks

The MSYS2 PETSc 3.24.5 package was compiled as a pure-C library (`PETSC_CLANGUAGE_C = 1`). As a result, two macros required by the C++ PETSc headers are absent from `petscconf.h`:

- `PETSC_FUNCTION_NAME_CXX` — the C++ equivalent of `__FUNCTION__`, used in error-handling macros such as `PetscCall` for stack-trace annotation.
- `PETSC_CXX_RESTRICT` — the C++ spelling of the `restrict` qualifier.

Missing either macro causes compile errors of the form *"PETSC_FUNCTION_NAME_CXX was not declared"*. The fix uses CMake's `CheckSymbolExists` to detect their absence and defines fallbacks:

```
include(CheckSymbolExists)
set(CMAKE_REQUIRED_INCLUDES ${PETSC_INCLUDE_DIRS})
check_symbol_exists(PETSC_FUNCTION_NAME_CXX "petscconf.h"
                    _HAVE_PETSC_FN_CXX)
if(NOT _HAVE_PETSC_FN_CXX)
  add_compile_definitions(
    PETSC_FUNCTION_NAME_CXX=__PRETTY_FUNCTION__)
endif()
check_symbol_exists(PETSC_CXX_RESTRICT "petscconf.h"
                    _HAVE_PETSC_CXX_RESTRICT)
if(NOT _HAVE_PETSC_CXX_RESTRICT)
```

```
  add_compile_definitions(PETSC_CXX_RESTRICT=__restrict__)
endif()
```

57.8.4 PETSc pkg-config name

The original `CMakeLists.txt` searched for PETSc via `pkg_search_module(PETSC REQUIRED IMPORTED_TARGET PETSc)`. The MSYS2 package registers the library under the name `petsc-dmo` (double, MPI, optimized). The search was widened to try multiple names:

```
pkg_search_module(PETSC REQUIRED IMPORTED_TARGET
                  PETSc petsc petsc-dmo petsc-dso)
```

57.8.5 Source directory macro

Hardcoded absolute Unix paths of the form `/home/sechavarriam/MyLibs/fall_n/` existed in `main.cpp`, `main_seismic.cpp`, and thirteen test files. These were replaced with a compile-time macro that resolves to the actual source tree regardless of platform or user name:

```
# CMakeLists.txt
add_compile_definitions(
  FALL_N_SOURCE_DIR="${CMAKE_SOURCE_DIR}")
```

Usage in source code:

```
#ifdef FALL_N_SOURCE_DIR
  static const std::string BASE =
      std::string(FALL_N_SOURCE_DIR) + "/";
#else
  static const std::string BASE = "./";
#endif
```

57.8.6 Windows CMake preset

A `win-debug` preset was added to `CMakePresets.json`:

```
{
  "name": "win-debug",
  "displayName": "Windows Debug (MSYS2 UCRT64)",
  "generator": "Ninja",
  "binaryDir": "${sourceDir}/build",
  "cacheVariables": { "CMAKE_BUILD_TYPE": "Debug" },
  "condition": {
    "type": "equals",
    "lhs": "${hostSystemName}",
    "rhs": "Windows"
  }
}
```

57.9 Source-Code Portability Fixes

Besides the build-system changes, several source files required modifications to compile cleanly with GCC on Windows.

57.9.1 ushort is not a standard type

The file `src/utils/index.hh` used `ushort` as a template non-type parameter:

```
template <ushort... N>  // non-standard: ushort is a POSIX extension
```

GCC on MinGW does not declare `ushort` in the global namespace. The fix replaces it with the standard `unsigned short`:

```
template <unsigned short... N>
```

57.9.2 %zu format specifier in PetscPrintf

The MSYS2 PETSc runtime's `PetscPrintf` does not recognise the `%zu` format specifier for `std::size_t` on this platform. Occurrences were replaced with `%d` and an explicit `(int)` cast:

```
// Before
PetscPrintf(PETSC_COMM_WORLD,
    "T_measured = %.6f (from %zu crossings)\n",
    T_measured, crossings.size());

// After
PetscPrintf(PETSC_COMM_WORLD,
    "T_measured = %.6f (from %d crossings)\n",
    T_measured, (int)crossings.size());
```

57.9.3 Unused-variable warning in tests

GCC 15 with `-Werror=unused-but-set-variable` rejected a variable in `tests/test_kinematic_policy.cpp` that was assigned but never read after the assignment. The fix adds `[[maybe_unused]]`:

```
[[maybe_unused]] Eigen::Vector<double, 3> E_from_B = gp.B * u_e;
```

57.10 Runtime PATH Considerations

The UCRT64 runtime libraries (`libvtkCommonCore.dll`, `libpetsc-dmo.dll`, `libgcc_s_seh-1.dll`, etc.) reside in `C:\msys64\ucrt64\bin`. This directory is automatically on `PATH` inside MSYS2 terminal sessions.

When executables are launched *outside* MSYS2 (e.g. from PowerShell, Explorer, or a CI runner) they will fail with `0xc0000135` unless the UCRT64 bin path is added to the system or user `PATH`, or the DLLs are copied alongside the executables.

For CTest invocations the recommended approach is to run from within the MSYS2 UCRT64 terminal, where the path is already configured:

```
# Open MSYS2 UCRT64 terminal, then:
cd /c/MyLibs/fall_n/build
ctest -L unit -j4 --output-on-failure
```

Alternatively, add the UCRT64 bin directory permanently to the Windows system environment variables via *System Properties* → *Environment Variables* → *System Variables* → *Path*.

57.11 Summary of All Changes

Table 57.2 lists every file that was modified and the corresponding reason.

Table 57.2: Files modified for Windows/MinGW compatibility.

File	Change
`CMakeLists.txt`	MinGW flags (`-lstdc++exp`, `-Wa,-mbig-obj`); PETSc fallback macros; `pkg_search_module` widened; VTK extern-template guards; `FALL_N_SOURCE_DIR` macro; compiler flag guard for MSVC vs. GCC.
`CMakePresets.json`	Added `win-debug` preset.
`main.cpp`	Replaced hardcoded `/home/...` path with `FALL_N_SOURCE_DIR` macro.
`main_seismic.cpp`	Same as `main.cpp`.
`src/utils/index.hh`	`ushort` → `unsigned short`.
13 test files under `tests/`	Replaced hardcoded Unix paths with `FALL_N_SOURCE_DIR`; replaced `/tmp/` with `std::filesystem::temp_directory_path()`.
`tests/test_kinematic_policy.cpp`	Added `[[maybe_unused]]` to suppress GCC 15 unused-variable warning.
`tests/test_phase5_dynamic_verification.cpp`	Replaced `%zu` with `%d` in `PetscPrintf` format string.

Chapter 58

Incremental Control Policy for Nonlinear Analysis

This chapter documents the design, implementation, and testing of the `IncrementalControlPolicy` abstraction, which generalises the incremental stepping strategy of `NonlinearAnalysis` from hardcoded proportional load control to an injectable, compile-time policy. Three concrete schemes are provided: `LoadControl` (backward-compatible default), `DisplacementControl` (single or multi-DOF pushover), and `CustomControl<F>` (user-supplied callable for maximum flexibility). An `ArcLengthControl` stub is included for future development.

58.1 Motivation and Problem Statement

The original implementation of `NonlinearAnalysis::advance_to_lambda_` contained three hardcoded lines that coupled the class to proportional load control:

```
VecCopy(f_full, f_ext);
VecScale(f_ext, lambda_target);
ctx_.f_ext = f_ext;
```

This prevented using the existing bisection infrastructure for:

- **Displacement control** — prescribing displacement increments at specific DOFs (pushover analysis, post-peak softening).
- **Mixed control** — combining load scaling with prescribed displacements.
- **Custom ramps** — non-linear load paths, conditional logic, or external coupling.
- **Arc-length control** (future) — parametrising the solution path by its arc-length to traverse limit points.

The goal was to extract this logic into a *compile-time injectable policy* that:

(i) preserves zero overhead (monomorphised at compile time),

(ii) is backward-compatible (existing code compiles without changes),

(iii) enables displacement control, custom ramps, and future arc-length,

(iv) integrates seamlessly with the existing bisection engine.

58.2 Design Decision: Function-Level Template

Two injection points were considered:

Class-level template parameter Add `CS` to the class template parameter list of `NonlinearAnalysis<..., CS>`. This forces the control scheme to be fixed at object construction time and pollutes the type name.

Function-level template parameter Make `solve_incremental` a member function template accepting the scheme by value:

```
template <typename CS>
bool solve_incremental(int num_steps, int max_bisections, CS scheme
    );
```

The type `CS` is deduced from the argument via CTAD; a default overload taking no scheme calls with `LoadControl{}`.

The function-level approach was chosen because:

- The same `NonlinearAnalysis` object can solve with different schemes in sequence (e.g., load-controlled pre-load followed by displacement-controlled pushover).
- No additional member state is introduced: the scheme is a stack-local value, passed through the recursion.
- The default overload `solve_incremental(num_steps)` is 100% backward-compatible — no existing call site needs changes.
- CTAD deduces `CS`, so client code never spells the type:

```
nl.solve_incremental(20, 4, DisplacementControl{42, 0, 0.01});
```

This follows the same philosophy as the project's existing policy-based patterns (`MaterialPolicy`, `KinematicPolicy`, `LocalStepControlPolicy`), but at the function level rather than the class level, offering greater flexibility without additional coupling.

58.3 The `IncrementalControlPolicy` Concept

The concept constrains any type `S` that can set the system state for a scalar control parameter `p`:

```
template <typename S, typename ModelT>
concept IncrementalControlPolicy = requires(
    S& scheme, double p, Vec f_full, Vec f_ext, ModelT* model)
{
    scheme.apply(p, f_full, f_ext, model);
};
```

The single required expression `scheme.apply(p, f_full, f_ext, model)` sets the complete system state for the control parameter `p`:

- `p` — control parameter in $[0, 1]$. At $p = 0$ the system is unloaded; at $p = 1$ the full reference load or target displacement is reached.
- `f_full` — reference external force vector (read-only, the unscaled load at $p = 1$).
- `f_ext` — external force vector to fill. Consumed by the SNES residual callback.
- `model` — pointer to the `Model` object, giving access to `update_imposed_value()`, the constraint map, etc.

58.3.1 The Absolute-State Invariant

Remark 58.1 (Absolute invariant). `apply(p, ...)` must be *absolute*: for any value of `p`, calling `apply(p, ...)` fully determines the system state, regardless of the previous call history. This is essential for correctness of the bisection engine.

When a Newton step diverges, the bisection engine:

1. Reverts the displacement field $\mathbf{u}$ to its snapshot.
2. Reverts the material state to the last committed values.
3. Calls `scheme.apply(p_current, ...)` to restore the control state.

Because `apply()` is absolute, step 3 requires no save/restore logic inside the scheme itself — the system state is a pure function $f(p)$ of the control parameter. This eliminates an entire class of state management bugs and keeps the scheme implementations stateless and trivially correct.

58.4 Concrete Implementations

58.4.1 `LoadControl` — Proportional Load Scaling

The default scheme extracts the original three-line logic:

```
struct LoadControl {
    template <typename ModelT>
    void apply(double p, Vec f_full, Vec f_ext,
               [[maybe_unused]] ModelT*) const
    {
        VecCopy(f_full, f_ext);
        VecScale(f_ext, p);
    }
};
```

At each step k of N, the external force vector is set to $\mathbf{f}_{\text{ext}} = p \cdot \mathbf{f}_{\text{full}}$ where $p = k/N$. The model pointer is unused. This is the identity refactoring of the original code and serves as the default:

```
nl.solve_incremental(10);            // LoadControl{} implicit
nl.solve_incremental(10, 4, LoadControl{});  // explicit
```

58.4.2 `DisplacementControl` — Prescribed-DOF Pushover

Controls one or more DOFs linearly with p, with optional proportional load scaling:

```
struct DisplacementControl {
    struct PrescribedDOF {
        std::size_t node;
        std::size_t dof;
        double      target;
    };

    std::vector<PrescribedDOF> controlled_dofs;
    double load_scale{0.0};

    // Single DOF
    DisplacementControl(std::size_t node, std::size_t dof,
```

```
                        double target, double scale = 0.0);

    // Multi-DOF
    DisplacementControl(std::vector<PrescribedDOF> dofs,
                        double scale = 0.0);

    template <typename ModelT>
    void apply(double p, Vec f_full, Vec f_ext, ModelT* model) {
        VecCopy(f_full, f_ext);
        VecScale(f_ext, p * load_scale);
        for (const auto& [node, dof, target] : controlled_dofs) {
            model->update_imposed_value(node, dof, p * target);
        }
    }
};
```

At control parameter p:

$$u_{\text{imposed},i} = p \cdot \texttt{target}_i, \tag{58.1}$$

$$\mathbf{f}_{\text{ext}} = p \cdot \texttt{load_scale} \cdot \mathbf{f}_{\text{full}}. \tag{58.2}$$

The controlled DOFs must have been pre-constrained via `constrain_dof()` before `Model::setup()`, so that the DM section includes the boundary condition. The `apply()` call only updates the *value* of an existing constraint (not the section structure), using `Model::update_imposed_value()`.

Typical usage for a pushover analysis at node 42, DOF 0, with target displacement 0.01:

```
M.constrain_dof(42, 0, 0.0);    // register constraint before setup
M.setup();

NonlinearAnalysis<ThreeDimensionalMaterial> nl{&M};
nl.solve_incremental(20, 4, DisplacementControl{42, 0, 0.01});
```

58.4.3 `CustomControl<F>` — Maximum Flexibility

Wraps any callable with signature `void(double, Vec, Vec, ModelT*)` into a policy-satisfying object:

```
template <typename F>
struct CustomControl {
    F apply_fn;

    template <typename ModelT>
    void apply(double p, Vec f_full, Vec f_ext, ModelT* model) {
        apply_fn(p, f_full, f_ext, model);
    }
};

template <typename F> CustomControl(F) -> CustomControl<F>;

template <typename F>
auto make_control(F&& f) {
    return CustomControl<std::decay_t<F>>{std::forward<F>(f)};
}
```

This enables arbitrary control strategies without defining a named class. Example with a square-root ramp combined with displacement control:

```
nl.solve_incremental(10, 4, make_control(
```

```
    [](double p, Vec f_full, Vec f_ext, auto* model) {
        VecCopy(f_full, f_ext);
        VecScale(f_ext, std::sqrt(p));
        model->update_imposed_value(42, 0, p * 0.01);
    }
));
```

The CTAD deduction guide and `make_control()` factory work in tandem: the factory perfectly forwards the callable and strips references, while the deduction guide enables direct aggregate initialisation when desired.

58.4.4 Arc-Length Control (Stub)

An `ArcLengthControl` stub is placed in `IncrementalControl.hh` for future development. Arc-length (Riks) methods require augmenting the SNES system to the unknowns $(\mathbf{u}, \lambda)$ with a constraint equation:

$$\|\Delta\mathbf{u}\|^2 + \Delta\lambda^2\|\mathbf{f}\|^2 = \Delta s^2,$$

where s is the arc-length parameter. The control parameter becomes s rather than p, and the stepping engine must reinterpret its meaning accordingly. This is marked with a `static_assert` guard preventing accidental instantiation.

58.5 `Model::update_imposed_value()`

The `DisplacementControl` scheme needs to update the imposed value of a constraint at each step without rebuilding the DM section or retraversing all nodes. The existing `fill_imposed_solution()` method is $O(N)$ — it walks every node in the domain — which is unacceptable inside the stepping loop.

A new $O(1)$ method was added to `Model`:

```
void update_imposed_value(std::size_t node_idx,
                          std::size_t local_dof,
                          double value) noexcept
{
    // 1. Update in-memory constraint map (O(log n) amortised)
    constrain_dof(node_idx, local_dof, value);

    // 2. Direct write to PETSc imposed-solution Vec (O(1))
    auto& node = domain_->node(node_idx);
    auto  all_dofs = node.dof_index();
    PetscScalar val = static_cast<PetscScalar>(value);
    VecSetValueLocal(global_imposed_solution_.get(),
                     all_dofs[local_dof], val, INSERT_VALUES);
    VecAssemblyBegin(global_imposed_solution_.get());
    VecAssemblyEnd(global_imposed_solution_.get());
}
```

This method:

1. Calls `constrain_dof()` to update the constraint map (the same map used by `fill_imposed_solution()`)
2. Writes the new value directly into the PETSc Vec via `VecSetValueLocal()`, using the DOF's local index from the node. This avoids the full-domain traversal.
3. Calls `VecAssemblyBegin/End` to flush the value (required by PETSc even for sequential vectors).

Remark 58.2. The DOF must have been registered as constrained *before* `setup()` so that the DM section includes the boundary condition. `update_imposed_value()` only updates the value, not the topological structure.

58.6 Changes to `NonlinearAnalysis`

58.6.1 Renamed Control Parameter

The load factor λ was renamed to the generic control parameter p throughout the implementation. The stepping function `advance_to_lambda_` became `advance_to_p_`. Print messages were updated accordingly. This reflects the fact that the control parameter may represent load scaling, displacement fraction, or any other monotonic path parameter.

58.6.2 Template Structure

The two modified functions are now templates on the control scheme:

```
// Backward-compatible overload
bool solve_incremental(int num_steps, int max_bisections = 4);

// General form
template <typename CS>
bool solve_incremental(int num_steps, int max_bisections, CS scheme);

// Bisection engine (private)
template <typename CS>
bool advance_to_p_(CS& scheme, Vec f_full,
                   double p_current, double p_target,
                   int bisections_left);
```

The backward-compatible overload delegates to the general form with `LoadControl{}` as the default scheme. A `static_assert` in the general form enforces the concept:

```
static_assert(IncrementalControlPolicy<CS, ModelT>,
    "CS must satisfy IncrementalControlPolicy<CS, ModelT>");
```

58.6.3 Integration with the Bisection Engine

The bisection engine (`advance_to_p_`) received minimal changes. The only modification is the replacement of the three hardcoded lines with a single call:

```
// Before (hardcoded):
VecCopy(f_full, f_ext);
VecScale(f_ext, lambda_target);
ctx_.f_ext = f_ext;

// After (policy-driven):
scheme.apply(p_target, f_full, f_ext, model_);
ctx_.f_ext = f_ext;
```

The snapshot/revert logic for the displacement field $\mathbf{u}$ and material state is unchanged. After a diverged step, the engine calls `scheme.apply(p_current, ...)` to restore the control state before bisecting — this is correct because `apply()` is absolute (see Remark 58.1).

The full bisection algorithm is summarized in Algorithm 2.

```
Input: scheme, f_full, p_current, p_target, budget
Output: true if p_target reached, false otherwise
u_snap ← u;
scheme.apply(p_target);
Solve SNES;
if converged then
    Commit material state;
    return true;
else
    u ← u_snap;
    Revert material state;
    scheme.apply(p_current) ;                    // restore control state
    if budget = 0 then
        return false;
    else
        p_mid ← (p_current + p_target)/2;
        if not advance_to_p_(scheme, p_current, p_mid, budget−1) then return false;
        return advance_to_p_(scheme, p_mid, p_target, budget−1);
    end
end
```

Algorithm 2: Policy-driven bisection engine (`advance_to_p_`).

58.7 Relationship with Existing Policy Patterns

The `IncrementalControlPolicy` fits naturally into the project's policy-based architecture. Table 58.1 contextualises it alongside existing abstractions.

Table 58.1: Policy abstractions in `fall_n` at different scales.

Scale	Concept / Interface	Implementations
Material (local)	`LocalStepControlPolicy`	`FullStepControl`, `BacktrackingResidualStepCon`
Dynamic analysis	`ForceEvaluator` (`std::function`)	Lambdas, closures
Static NL	`IncrementalControlPolicy`	`LoadControl`, `DisplacementControl`, `CustomControl<F>`

The key difference from `LocalStepControlPolicy` (which also uses C++20 concepts) is the injection point: the local step control is a class-level template parameter of the material, while the incremental control is a function-level template on `solve_incremental`. This reflects their different scopes: material policies are fixed for the lifetime of an element, while the incremental control strategy may change between analysis phases.

The `ForceEvaluator` pattern used in `DynamicAnalysis` relies on `std::function` for type-erasure (suitable for time-dependent forces that vary at runtime). In contrast, `IncrementalControlPolicy` uses compile-time polymorphism because the control scheme is typically fixed for an entire `solve_incremental` call and performance in the inner loop is critical.

58.8 File Summary

Table 58.2 summarises all changes made.

Table 58.2: Files created or modified for the incremental control policy.

File	Type	Description
`src/analysis/IncrementalControl.hh`	New	Concept + `LoadControl` + `DisplacementControl` +
`src/analysis/NLAnalysis.hh`	Modified	Template `solve_incremental` + `advance_to_p_`
`src/model/Model.hh`	Modified	Added `update_imposed_value()`
`src/analysis/Analysis.hh`	Modified	Added include for `IncrementalControl.hh`
`tests/test_incremental_control.cpp`	New	6 tests, 14 assertions
`CMakeLists.txt`	Modified	Registered test target

58.9 Testing

Six unit tests validate the implementation across all control schemes. The test file `tests/test_incremental_co` creates a minimal 3D unit-cube model (single hexahedral element, elastic material) and exercises:

1. **LoadControl (default call)** — `solve_incremental(3)` with no explicit scheme; verifies backward compatibility and convergence in 3 steps.
2. **LoadControl (explicit)** — `solve_incremental(3, 4, LoadControl{})` produces the same result.
3. **DisplacementControl (single DOF)** — Constrains node 1 x-DOF with target 0.01; verifies convergence and that the imposed solution vector is non-zero at the controlled DOF.
4. **DisplacementControl (multi-DOF)** — Four nodes controlled simultaneously; verifies convergence.
5. **CustomControl via `make_control`** — Lambda with $\sqrt{p}$ load ramp; verifies convergence.
6. **Concept satisfaction (compile-time)** — Static assertions that `LoadControl`, `DisplacementControl`, and `CustomControl<...>` satisfy `IncrementalControlPolicy`.

All 14 assertions pass. The existing 30 commit-chain tests and the heterogeneity test (which uses `solve_incremental`) also pass without modification, confirming backward compatibility.

58.10 Usage Guide

58.10.1 Load Control (Default)

No changes to existing code:

```
NonlinearAnalysis<ThreeDimensionalMaterial> nl{&M};
nl.solve_incremental(10);        // LoadControl implicit, 10 steps
nl.solve_incremental(10, 4);     // same with explicit bisection depth
```

58.10.2 Displacement-Controlled Pushover

```
// Pre-constrain the controlled DOF (zero initial value)
M.constrain_dof(42, 0, 0.0);
M.setup();

NonlinearAnalysis<ThreeDimensionalMaterial> nl{&M};
// Push node 42, dof 0 to displacement 0.01 in 20 steps
nl.solve_incremental(20, 4, DisplacementControl{42, 0, 0.01});
```

58.10.3 Multi-DOF Displacement Control with Proportional Load

```
nl.solve_incremental(20, 4, DisplacementControl{
    {{10, 0, 0.01}, {11, 0, 0.01}, {12, 0, 0.01}},
    0.5   // load_scale: 50% of reference load
});
```

58.10.4 Custom Control

```
nl.solve_incremental(10, 4, make_control(
    [](double p, Vec f_full, Vec f_ext, auto* model) {
        VecCopy(f_full, f_ext);
        VecScale(f_ext, std::sqrt(p));   // sqrt ramp
        model->update_imposed_value(42, 0, p * 0.01);
    }
));
```

58.10.5 Sequential Multi-Phase Analysis

Because the scheme is a function-level parameter, the same `NonlinearAnalysis` object can be reused with different schemes:

```
NonlinearAnalysis<ThreeDimensionalMaterial> nl{&M};

// Phase 1: gravity load (proportional)
nl.solve_incremental(5, 4, LoadControl{});

// Phase 2: displacement-controlled pushover
nl.solve_incremental(20, 4, DisplacementControl{42, 0, 0.05});
```

This is a direct benefit of the function-level template design over a class-level template parameter.

Chapter 59

Steppable Dynamic Analysis with StepDirector

This chapter documents the design, implementation, and testing of the single-step API for `DynamicAnalysis` and the `StepDirector` abstraction for condition-based breakpoints. Together these enable pausing a dynamic simulation at specified conditions, inspecting or modifying the model, changing integration parameters, and resuming — all without modifying the analysis class itself.

59.1 Motivation

The batch `solve(t_final, dt)` interface of `DynamicAnalysis` delegates the entire time-stepping loop to PETSc's `TSSolve`, which runs from $t = 0$ to t_{final} in a single call. While convenient, this monolithic interface prevents several important use cases:

- **Pause & inspect:** Capture the solution at specific times to couple with external models, extract quantities of interest, or generate intermediate output.
- **Runtime reconfiguration:** Change the time step Δt, switch the integration scheme (e.g. from implicit Generalized-α to explicit Euler), or modify boundary conditions mid-simulation.
- **Multi-phase analysis:** Run a static preload phase (via `NonlinearAnalysis`), transfer the state, and continue with a dynamic phase with different control logic.
- **Condition-based stopping:** Terminate or pause when a displacement exceeds a threshold, a damage variable reaches a limit, or an external convergence criterion is met.

The design goal is to provide these capabilities with zero overhead on the existing batch API and minimal modifications to the class.

59.2 Design

59.2.1 Single-Step API on DynamicAnalysis

Three new public methods expose single-step control:

```
bool step();                                    // one time step
StepVerdict step_to(double t_target);           // advance to t
StepVerdict step_n(int n);                      // advance n steps
```

`step()` wraps PETSc's `TSStep(ts_)` with the bookkeeping required for manual single-step control:

1. Reset the convergence reason to `TS_CONVERGED_ITERATING` (PETSc refuses to step if the TS is flagged as already converged).
2. Set the step budget to `current_step() + 1` via `TSSetMaxSteps`.
3. Set a sufficiently large `TSSetMaxTime` to avoid time-limit convergence.
4. Call `TSStep(ts_)`.
5. Check `TSGetConvergedReason`: return `true` if the reason is non-negative (converged or max-steps reached), `false` on divergence.

The Monitor callback registered in `setup()` is invoked automatically by PETSc during `TSStep`, so the full post-step pipeline (material commit, model state update, observer notification) runs without duplication.

59.2.2 Extracted `post_step_` Method

The material commit, model state vector update, and observer/monitor notification logic was extracted from the static `Monitor` callback into a private member function:

```
void post_step_(PetscInt step, double t, Vec U, Vec V);
```

The static `Monitor` callback becomes a thin trampoline:

```
static PetscErrorCode Monitor(TS ts, PetscInt step,
                              PetscReal t, Vec U, void* ctx)
{
    auto* self = static_cast<Context*>(ctx)->self;
    Vec V;
    TS2GetSolution(ts, &U, &V);
    self->post_step_(step, t, U, V);
    return PETSC_SUCCESS;
}
```

This refactoring keeps the Monitor API surface unchanged while enabling direct invocation from future code paths where the PETSc monitor is not active.

59.2.3 Runtime Reconfiguration

Four additional methods allow runtime parameter changes between steps:

```
void   set_time_step(double dt);
double get_time_step() const;
void   set_integration_method(TSType type);
void   set_director(StepDirector<ModelT> dir);
```

`set_integration_method` wraps `TSSetType` and allows switching between `TSALPHA2`, `TSNEWMARK`, `TSEULER`, `TSRK`, etc. at runtime.

59.3 StepDirector — Condition-Based Breakpoints

59.3.1 StepVerdict Enum

The director protocol uses a three-valued verdict:

```cpp
enum class StepVerdict {
    Continue,    // keep stepping
    Pause,       // return control to caller (resumable)
    Stop         // terminate the analysis
};
```

The ordering Continue < Pause < Stop enables a `most_restrictive(a, b)` combinator for composing multiple directors.

59.3.2 StepDirector Type Alias

A `StepDirector<ModelT>` is a type-erased callable:

```cpp
template <typename ModelT>
using StepDirector = std::function<
    StepVerdict(const StepEvent&, const ModelT&)>;
```

The director is evaluated *after* every converged step in `step_to()` and `step_n()`. This guarantees the model is in a fully consistent, committed state when the caller inspects it upon a `Pause` verdict.

59.3.3 Convenience Factories

The `step_director` namespace provides ready-made directors:

Factory	Description
`pause_at_times({`$t_1, t_2, \ldots$`})`	Pause when $t \geq t_i$ (each breakpoint fires once)
`pause_every_n(`N`)`	Pause every N steps
`pause_on(`F`)`	Pause when predicate $F(\text{ev}, \text{model})$ is true
`stop_on(`F`)`	Stop when predicate $F(\text{ev}, \text{model})$ is true
`compose(`$d_1, d_2, \ldots$`)`	Most restrictive verdict of all directors

59.3.4 Integration with DynamicAnalysis

The `step_to` and `step_n` methods accept an optional director parameter. A persistent director can also be set via `set_director()`.

```cpp
// Pause at specific times
auto dir = step_director::pause_at_times<MyModel>({1.0, 2.5});
auto verdict = solver.step_to(10.0, dir);
if (verdict == StepVerdict::Pause) {
    // inspect model, modify BCs, change dt, etc.
    solver.step_to(10.0, dir);   // resume
}
```

59.4 Backward Compatibility

The existing `solve(t_final, dt)` and `solve(t_start, t_final, dt)` methods remain unchanged and continue to use PETSc's `TSSolve` internally. No existing call site is affected. The Monitor callback extraction is a pure refactoring with no behavioral change for the batch API.

Test 9 in the verification suite confirms that `step_to(t)` produces results *identical* to `solve(t, dt)` (difference = 0), validating that the single-step pathway is numerically equivalent to the batch pathway.

59.5 Verification

A dedicated test suite (`test_steppable_dynamic.cpp`) validates 10 scenarios with 32 assertions:

Test	Description	Assertions
1	`step()` — single time step convergence	5
2	`step_n(10)` — exact step count	3
3	`step_to(t)` — target time reached	3
4	`pause_at_times` breakpoint	5
5	`pause_every_n` periodic pause	4
6	`pause_on` custom condition	2
7	`compose` directors	2
8	Runtime Δt change	3
9	Equivalence: step-by-step = batch solve	3
10	`stop_on` termination	2
	Total	**32**

All 32 assertions pass. Additionally, the full existing test suite (46/50, with 4 pre-existing failures due to missing data files) passes unchanged, confirming backward compatibility.

59.6 Files Modified and Created

File	Action	Purpose
`src/analysis/StepDirector.hh`	Created	`StepVerdict` + `StepDirector<ModelT>` + factories
`src/analysis/DynamicAnalysis.hh`	Modified	`post_step_()`, `step()`, `step_to()`, `step_n()`, reconfig
`src/analysis/Analysis.hh`	Modified	Added `StepDirector.hh` include
`tests/test_steppable_dynamic.cpp`	Created	10 tests, 32 assertions
`CMakeLists.txt`	Modified	Registered `fall_n_steppable_dynamic_test`

59.7 Future Directions

This infrastructure enables the remaining phases of the unified steppable solver plan:

Phase C — SteppableSolver concept: Unify `NonlinearAnalysis` and `DynamicAnalysis` under a common concept with `step()`, `step_to()`, and `current_time()`. An `AnalysisState` struct will enable cross-engine state transfer.

Phase D — AnalysisDirector: A high-level orchestrator that sequences multiple analysis phases (static preload → dynamic excitation → static gravity redistribution), with automatic state transfer and observer lifecycle management.

Chapter 60

Unified Steppable Solver — Phase C

60.1 Motivation

Chapter 59 introduced `IncrementalControlPolicy` for injectable load-stepping strategies in `NonlinearAnalysis`, while Chapter 60 added single-step control (`step()`, `step_to()`, `step_n()`) and condition-based breakpoints (`StepDirector`) to `DynamicAnalysis`.

Phase C closes the gap by:

1. Defining a C++23 **concept** `SteppableSolver` that both engines satisfy.
2. Extending `NonlinearAnalysis` with the same single-step API already available in `DynamicAnalysis`.
3. Providing `AnalysisState`, a lightweight snapshot struct for cross-engine state transfer.

The result is a unified stepping protocol: any algorithm templated on `SteppableSolver` works identically with static or dynamic solvers.

60.2 The `SteppableSolver` Concept

```
namespace fall_n {

template <typename S>
concept SteppableSolver = requires(S& solver, const S& csolver,
                                   double target, int n)
{
    { solver.step()          } -> std::convertible_to<bool>;
    { solver.step_to(target) } -> std::same_as<StepVerdict>;
    { solver.step_n(n)       } -> std::same_as<StepVerdict>;
    { csolver.current_time() } -> std::convertible_to<double>;
    { csolver.current_step() } -> std::convertible_to<PetscInt>;
};

} // namespace fall_n
```

The "time axis" has engine-specific semantics:

- **DynamicAnalysis**: physical time t (seconds).
- **NonlinearAnalysis**: control parameter $p \in [0, 1]$ (0 = unloaded, 1 = full load/displacement).

Both engines advance monotonically along their axis and share the same `StepVerdict` / `StepDirector` infrastructure from Chapter 60.

60.3 NonlinearAnalysis Single-Step API

60.3.1 Initialization

Before calling `step()`, the user must initialize the stepping state with `begin_incremental()`:

```
NonlinearAnalysis<Policy> nl{&model};

// Default load control, 10 steps, max 4 bisection levels
nl.begin_incremental(10);

// Or with an explicit control scheme
nl.begin_incremental(10, 4, DisplacementControl{1, 0, 0.01});
```

Internally, `begin_incremental()` calls `setup()`, zeroes the solution vector, captures the reference force vector $\mathbf{f}_{\text{full}}$, computes the increment size $\Delta p = 1/N$, and type-erases the control scheme into a `std::function` for subsequent calls.

60.3.2 Stepping

```
bool ok = nl.step();            // advance one increment (dp)
auto v  = nl.step_to(0.5);     // advance to p = 0.5
auto v  = nl.step_n(3);        // advance 3 increments
```

Each `step()` call:

1. Computes $p_{\text{target}} = p_{\text{done}} + \Delta p$.
2. Calls the bisection engine `advance_step_impl_(p_done, p_target, max_bisections)`.
3. On convergence: updates p_{done}, increments the step counter, fires the step callback, and calls `model_.update_elements_state()`.
4. Returns `true` on convergence, `false` on divergence.

60.3.3 Runtime Reconfiguration

```
nl.set_increment_size(0.05);    // change dp at runtime
nl.set_director(my_director);   // install a StepDirector
```

The `StepDirector` factories from Chapter 60 work identically: `pause_at_times`, `pause_every_n`, `pause_on`, `stop_on`, and `compose`.

In the `StepEvent` passed to the director:

- `step` = load step count.
- `time` = control parameter p.
- `displacement` = global displacement vector $\mathbf{U}$.
- `velocity` = `nullptr` (no velocity in static analysis).

60.4 Type-Erased Bisection Engine

The original `advance_to_p_<CS>()` is templated on the control scheme type. For the single-step API, where the scheme type is erased at `begin_incremental()` time, we add a non-template companion `advance_step_impl_()` that uses the stored `std::function<void(double, Vec, Vec, ModelT*)>`.

The algorithm is identical (snapshot, apply, solve, commit-or-bisect) but operates on the member `apply_fn_` and `f_full_` instead of template parameters. The original templated version is preserved for backward compatibility of `solve_incremental()`.

60.5 AnalysisState — Cross-Engine Transfer

```
namespace fall_n {

struct AnalysisState {
    Vec      displacement{nullptr};
    Vec      velocity{nullptr};       // nullptr for static
    double   time{0.0};
    PetscInt step{0};
};

} // namespace fall_n
```

Both `NonlinearAnalysis` and `DynamicAnalysis` provide `get_analysis_state()` returning a snapshot with borrowed PETSc vectors. Typical usage for a preload → dynamic handoff:

```
// Phase 1: static preload
NonlinearAnalysis<Policy> nl{&model};
nl.begin_incremental(10);
nl.step_to(1.0);

auto state = nl.get_analysis_state();

// Phase 2: dynamic excitation (transfer displacement)
DynamicAnalysis<Policy> dyn{&model};
dyn.set_initial_displacement(state.displacement);
dyn.step_to(10.0);
```

60.6 Verification

#	Test	Assertions
1	`SteppableSolver` concept satisfaction (NL + Dynamic)	2
2	NL `begin_incremental + step()`	6
3	NL `step_n(n)`	6
4	NL `step_to(p)`	6
5	NL `step_to + pause_at_times`	6
6	NL `step_to + pause_on` (custom condition)	2
7	NL `set_increment_size` (runtime dp change)	4
8	NL equivalence (step-by-step vs `solve_incremental`)	7
9	NL `get_analysis_state`	5
10	Dynamic `get_analysis_state`	4
	Total	**48**

Test 8 confirms exact equivalence: the step-by-step path produces $\|\Delta\mathbf{u}\| = 0$ compared to the batch `solve_incremental()` path.

All 47/51 suite tests pass (4 pre-existing data-file failures unchanged).

60.7 Files

`src/analysis/SteppableSolver.hh`
: `SteppableSolver` concept + `AnalysisState` struct.

`src/analysis/NLAnalysis.hh`
: Added: stepping state members, `begin_incremental()`, `step()`, `step_to()`, `step_n()`, `current_time()`, `current_step()`, `set_director()`, `set_increment_size()`, `get_analysis_state()`, `advance_step_impl_()`.

`src/analysis/DynamicAnalysis.hh`
: Added: `get_analysis_state()`, `SteppableSolver.hh` include.

`src/analysis/Analysis.hh`
: Added: `SteppableSolver.hh` include.

`tests/test_steppable_solver.cpp`
: 10 tests, 48 assertions.

`CMakeLists.txt`
: Registered `fall_n_steppable_solver_test`.

Chapter 61

AnalysisDirector — Multi-Phase Orchestrator (Phase D)

61.1 Motivation

Real structural analysis workflows rarely consist of a single solver invocation. A typical seismic assessment, for example, involves:

1. **Static preload:** gravity and imposed dead loads via `NonlinearAnalysis` ($p : 0 \to 1$).
2. **Dynamic excitation:** earthquake ground motion via `DynamicAnalysis` ($t : 0 \to T$).
3. **Static redistribution:** post-event settling via `NonlinearAnalysis` again.

Each phase may use a different solver engine and different configurations, yet they share structural state: the displacement at the end of the preload becomes the initial condition for the dynamic phase, and the post-earthquake displacement feeds the redistribution phase.

Chapters 59–61 built the individual components (incremental control, step director, steppable-solver concept, analysis state transfer). Phase D assembles them into a single orchestrator: `AnalysisDirector`.

61.2 Design Decisions

61.2.1 Type-Erased Phase Callbacks

The director is *not* templated on solver types. Instead, each phase is a `std::function<AnalysisState(const AnalysisState&)>`: the callback receives the output of the previous phase (or a default-constructed state for the first phase) and returns its own output.

This design gives maximum flexibility:

- The caller decides how to create, configure, and destroy each solver.
- Different phases can use entirely different engines (`NonlinearAnalysis`, `DynamicAnalysis`, or any future solver satisfying `SteppableSolver`).
- Boundary conditions, observers, and loads can be freely modified between phases without the director knowing their details.

The trade-off is that the director cannot impose compile-time guarantees on solver types. This is acceptable because the director is a *workflow* coordinator, not a solver abstraction.

61.2.2 Borrowed State and Lifetime

`AnalysisState` stores *borrowed* PETSc `Vec` references (see Chapter 61). This implies a critical lifetime constraint:

> **Rule:** The solver that produced an `AnalysisState` must remain alive while any subsequent phase reads its state.

In practice, this means solvers that participate in state transfer should be constructed *outside* the phase callbacks, so their `Vec` resources outlive the inter-phase handoff. The tests in this chapter demonstrate this pattern explicitly.

61.2.3 Failure Semantics

A phase signals failure by returning an `AnalysisState` with `displacement == nullptr`. The director supports two modes:

- **Abort-on-failure (default):** the phase sequence stops immediately; remaining phases are not executed.
- **Continue-on-failure:** all phases execute regardless of prior failures. Useful for robustness studies or post-mortem analysis.

61.2.4 Phase Gating

An optional `PhaseGateCallback` can be attached to any phase. The gate receives the *previous* phase's `PhaseOutcome` and returns a boolean: `true` to proceed, `false` to skip.

Typical gates include:

- Only run a dynamic phase if the preload reached full load: `prev.state.time >= 0.9`.
- Only run a redistribution phase if the excitation succeeded: `prev.status == PhaseStatus::Succeeded`.

61.3 Architecture

61.3.1 Core Types

```
namespace fall_n {

enum class PhaseStatus { Succeeded, Failed, Skipped };

struct PhaseOutcome {
    std::string    name;
    PhaseStatus    status{PhaseStatus::Skipped};
    double         elapsed_seconds{0.0};
    AnalysisState  state{};
};

struct DirectorReport {
    std::vector<PhaseOutcome> phases;
    bool        all_succeeded() const noexcept;
    std::size_t num_succeeded() const noexcept;
    std::size_t num_failed()    const noexcept;
    void        print_summary() const;
```

```
};

using PhaseCallback     = std::function<AnalysisState(const AnalysisState&)>;
using PhaseGateCallback = std::function<bool(const PhaseOutcome&)>;

} // namespace fall_n
```

61.3.2 AnalysisDirector API

```
class AnalysisDirector {
public:
    // Registration
    AnalysisDirector& add_phase(std::string name, PhaseCallback cb);
    AnalysisDirector& add_phase(std::string name, PhaseCallback cb,
                                PhaseGateCallback gate);
    AnalysisDirector& set_continue_on_failure(bool);

    // Execution
    DirectorReport run();

    // Queries
    std::size_t num_phases() const noexcept;
};
```

The `add_phase()` overloads return `*this` for chaining.

61.3.3 Execution Algorithm

`run()` iterates over registered phases in order:

1. **Gate check:** if the phase has a gate and the previous phase's outcome exists, evaluate the gate. If it returns `false`, record the phase as `Skipped` and continue to the next phase.
2. **Execute:** call the phase callback with the current `AnalysisState`. Measure wall-clock time via `std::chrono::steady_clock`.
3. **Classify:** if the returned state has a non-null displacement, mark `Succeeded` and update the current state. Otherwise, mark `Failed`.
4. **Abort check:** if the phase failed and `continue_on_failure` is `false`, break.

The initial state for the first phase is a default-constructed `AnalysisState` (all null, time 0, step 0).

61.4 Bug Fix: `solve_incremental` State Synchronisation

During Phase D testing, a latent inconsistency was discovered: `NonlinearAnalysis::solve_incremental()` uses a *local* variable `p_done` for bookkeeping, but never updates the *member* `p_done_` used by `get_analysis_state()`.

This meant that calling `get_analysis_state()` after `solve_incremental()` would report $p = 0$ and step $= 0$ regardless of the actual terminal state.

61.4.1 Fix Applied

After the solve loop and element state update, the batch path now synchronises with the single-step state:

```
model_->update_elements_state();

// Synchronise single-step state so get_analysis_state()
// reflects the terminal position even when called after
// the batch solve_incremental() path.
p_done_     = p_done;
step_count_ = steps_done;
```

This ensures that `get_analysis_state()` is consistent regardless of whether the solve was performed via the batch API (`solve_incremental`) or the step-by-step API (`begin_incremental + step()`).

61.5 Usage Example

```
// Setup model (shared across phases)
Model<Policy> model(domain, material);
model.fix_x(0.0);
model.setup();
model.set_density(2400.0);  // concrete

// Create solvers outside callbacks for lifetime safety
NonlinearAnalysis<Policy> nl{&model};
DynamicAnalysis<Policy>   dyn{&model};

AnalysisDirector director;

director.add_phase("gravity", [&](const AnalysisState&) {
    nl.solve_incremental(10);
    return nl.get_analysis_state();
});

director.add_phase("earthquake", [&](const AnalysisState& prev) {
    dyn.set_initial_displacement(prev.displacement);
    dyn.set_time_step(0.005);
    dyn.step_to(30.0);
    return dyn.get_analysis_state();
});

auto report = director.run();
report.print_summary();
```

Output:

```
AnalysisDirector - Phase Summary
+--+----------------+------+------+
|  # | Phase                          | Status    | Time (s)   |
+--+----------------+------+------+
|  1 | gravity                        | OK        |      0.042 |
```

```
|  2 | earthquake                     | OK        |     12.340 |
+--+----------------+------+------+
All 2 phases completed successfully.
```

61.6 Verification

#	Test	Assertions
1	Empty director	5
2	Single phase (static)	7
3	Two-phase state threading	6
4	Static preload → Dynamic excitation (multi-engine)	9
5	Abort-on-failure	4
6	Continue-on-failure mode	6
7	Phase gate callback (pass and block)	5
8	DirectorReport summary queries	4
9	Three-phase pipeline (preload → excite → redistribute)	7
10	Phase timing (`elapsed_seconds > 0`)	1
	Total	**54**

Test 4 is the integration highlight: it performs a static preload with `NonlinearAnalysis`, transfers the displacement via `AnalysisState` to `DynamicAnalysis`, and verifies that the dynamic solver correctly inherits the deformed configuration.

Test 9 demonstrates the full three-phase pipeline (preload → excitation → redistribution) on a shared model, confirming that state threads correctly through all transitions.

All 52/52 suite tests pass.

61.7 Test Infrastructure Improvements

During Phase D, four pre-existing test failures (from Phase C) were resolved. All four had the same root cause: **missing data files**.

61.7.1 MSHReader Defensive Fix

The mesh reader `MSHReader` (in `src/mesh/gmsh/ReadGmsh.hh`) silently printed an error to `std::cerr` when a mesh file was not found, then proceeded to return to the caller with an uninitialised stream. Downstream code (in `GmshDomainBuilder`) would then dereference null pointers and crash with a segmentation fault.

Fix: replaced the `std::cerr` message with a `throw std::runtime_error(...)`, providing a clear diagnostic and preventing silent null-pointer dereferences.

61.7.2 Mesh File Generation

The test data files (`.msh` meshes and earthquake records) are excluded from version control via `.gitignore`. A Python script `scripts/generate_test_data.py` was created to regenerate them using the Gmsh Python API (v4.15.1):

`tests/validation_cube.msh`
: Second-order hexahedral mesh ($2 \times 2 \times 2$, 8 Hex27 elements, 125 nodes). Generated from `validation_cube.geo` via `gmsh.model.mesh.generate(3)` + `setOrder(2)`.

`data/input/Beam_LagCell_Ord1_30x6x3.msh`
: First-order hexahedral mesh ($30 \times 6 \times 3$, 540 Hex8 elements, 868 nodes). Box geometry $[0, 10] \times [0, 0.4] \times [0, 0.8]$, transfinite meshing via Gmsh API.

data/input/earthquakes/el_centro_1940_ns.dat
: Synthetic earthquake record (501 points, $\Delta t = 0.02\,\mathrm{s}$, PGA $= 0.3194g$ at $t = 4.80\,\mathrm{s}$). Jennings envelope with random-phase sinusoids mimicking the El Centro 1940 NS component.

Key insight: hand-writing MSH 4.1 format files programmatically appeared to produce correct meshes (node/element counts matched) but caused `SNES DIVERGED_FNORM_NAN` at iteration 0. Using the Gmsh API guarantees correct node ordering and element connectivity, resolving the issue completely.

61.8 Files

src/analysis/AnalysisDirector.hh
: `PhaseStatus`, `PhaseOutcome`, `DirectorReport`, `PhaseCallback`, `PhaseGateCallback`, `AnalysisDirecto` class.

src/analysis/NLAnalysis.hh
: Modified: `solve_incremental()` now synchronises `p_done_` and `step_count_` at completion.

src/analysis/Analysis.hh
: Added: `AnalysisDirector.hh` include.

src/mesh/gmsh/ReadGmsh.hh
: Modified: `std::cerr` → `throw std::runtime_error` on file-not-found.

tests/test_analysis_director.cpp
: 10 tests, 54 assertions.

scripts/generate_test_data.py
: Gmsh API mesh generator + synthetic earthquake record generator.

CMakeLists.txt
: Registered `fall_n_analysis_director_test`.

61.9 Phase Summary

Phase	Component	Chapter	Status
A	Single-step API (`DynamicAnalysis`)	60	Complete
B	StepDirector + factories	60	Complete
C	SteppableSolver concept + NL step API	61	Complete
D	AnalysisDirector orchestrator	62	Complete

The four-phase architecture provides a complete workflow construction kit: individual steps (Phase A), conditional breakpoints (Phase B), a unified solver concept (Phase C), and a multi-phase orchestrator (Phase D). Together, they enable arbitrary analysis sequences — from a simple static solve to a multi-phase seismic assessment — with full state transfer and lifecycle control.

Chapter 62

Analysis & Model Architecture — Comprehensive Reference

62.1 Overview

The `fall_n` framework organises finite-element analysis into two principal modules:

`src/model/`
: Describes *what* is being analysed: the finite element model, its degrees of freedom, boundary conditions, material points, and state snapshots.

`src/analysis/`
: Describes *how* the model is solved: linear, nonlinear, and dynamic solvers; incremental load control; step-level observation; and multi-phase orchestration.

Both modules are policy-based (templates) at the inner core and type-erased (callbacks, `std::function`) at the system boundary. This gives zero-cost inner loops and maximum composability at the API surface.

The next sections dissect each module by:

- Header inventory and dependency graph,
- Class-level architecture diagrams,
- Extension points with concrete tutorials,
- Semantic analysis and naming conventions.

62.2 Analysis Module Architecture

62.2.1 Header Inventory

The analysis module comprises 13 header files, all flat in `src/analysis/` (no subdirectories):

Header	Lines	Role
`AnalysisObserver.hh`	∼320	`StepEvent`, `ObserverBase`, `DynamicObserverList`, `CompositeObserver`, `ObserverCallback`
`IncrementalControl.hh`	∼170	`IncrementalControlPolicy` concept + `LoadControl`, `DisplacementControl`, `CustomControl`
`StepDirector.hh`	∼180	`StepVerdict` enum, `StepDirector<ModelT>` type alias, 5 factories
`SteppableSolver.hh`	∼70	`SteppableSolver` concept + `AnalysisState` struct
`Damping.hh`	∼100	`DampingAssembler` functor + Rayleigh factories
`LinearAnalysis.hh`	∼95	PETSc KSP wrapper (single solve)
`NLAnalysis.hh`	∼870	PETSc SNES Newton–Raphson solver with automatic bisection
`DynamicAnalysis.hh`	∼1000	PETSc TS transient solver (generalized-α, Newmark)
`AnalysisDirector.hh`	∼280	Multi-phase orchestrator with state threading
`Observers.hh`	∼800	7 concrete observers (console, VTK, node/element/fiber recorders, energy, max-response)
`DamageCriterion.hh`	∼320	Damage-based stopping criterion (observer)
`FiberHysteresisRecorder.hh`	∼330	Fiber-level hysteresis recorder (observer)
`Analysis.hh`	∼50	Module aggregator (includes all of the above in dependency order)

62.2.2 Dependency Graph

The include relationships form a layered DAG:



`Analysis.hh` is a pure aggregator: it includes everything in dependency order so that a single `#include "Analysis.hh"` brings the entire module into scope.

62.2.3 Class-Level Architecture

The analysis module is organised around four design pillars:

1. **Concepts as contracts.** `IncrementalControlPolicy`, `SteppableSolver`, and `StepDirector<ModelT>` are not base classes — they are C++23 concepts or type aliases for `std::function`. Solvers satisfy these contracts structurally; no inheritance is required.

2. **Solver engines as monolithic templates.** `LinearAnalysis`, `NonlinearAnalysis`, and `DynamicAnalysis` are class templates parametrised by `MaterialPolicy`, `KinematicPolicy`, `ndofs`, and `ElemPolicy`. Each wraps a PETSc solver object (KSP, SNES, TS) with RAII ownership.

3. **Observer pattern for non-intrusive recording.** Observers decouple data recording from the solver loop. Two flavours exist: compile-time (`CompositeObserver`) and runtime (`DynamicObserverList`). Both are integrated via a single `ObserverCallback` trampoline.

4. **Orchestration at the top.** `AnalysisDirector` composes solver phases using type-erased callbacks (`PhaseCallback`). State flows between phases through `AnalysisState`.

62.2.4 Solver Engine Anatomy

All three solver engines share a common internal structure:

Aspect	**LinearAnalysis**	**NLAnalysis**	**DynamicAnalysis**
PETSc solver	KSP	SNES	TS
Equation	$Ku = f$	$R(u) = f_{\text{int}}(u) - f_{\text{ext}} = 0$	$M\ddot{u} + C\dot{u} + f_{\text{int}}(u) = f_{\text{ext}}(t)$
Callbacks	none	`FormResidual`, `FormJacobian`	`I2Function`, `I2Jacobian`, `Monitor`
Stepping	single solve	incremental + bisection	time integration
State commit	post-solve	per converged step	per converged step
Observer	none	`step_callback_` (legacy)	`ObserverCallback` + `MonitorCallback`
Single-step	no	`step()/step_to()/step_n()`	no
SteppableSolver	no	yes	yes

NonlinearAnalysis internals. The file is organised as follows:

1. *Private members:* model pointer, PETSc objects (SNES, Vec, Mat), timer, callbacks, single-step state, context struct.
2. *Static PETSc callbacks:* `FormResidual`, `FormJacobian` — these are `static` member functions matching PETSc's C API. The `Context` struct provides the `void*` bridge.
3. *State management:* `commit_state()`, `revert_state()`.
4. *Public query API:* `converged_reason()`, `num_iterations()`, `timer()`.
5. *Setup.*
6. *Solve API:* `solve()`, `solve_incremental()`.
7. *Bisection engine:* `advance_to_p_()`, `advance_step_impl_()`.
8. *Single-step API:* `begin_incremental()`, `step()`, `step_to()`, `step_n()`.
9. *Accessors:* `current_time()`, `current_step()`.
10. *State transfer:* `get_analysis_state()`.
11. *Constructor/destructor.*

DynamicAnalysis internals.

1. *Private members:* model pointer, PETSc objects (TS, Mat ×4, Vec ×4), configuration callbacks, observer pipelines, ground-motion data.
2. *Static PETSc callbacks:* `I2Function`, `I2Jacobian`, `Monitor`.
3. *Private helpers:* `post_step_()`, `assemble_initial_stiffness()`, `setup_ground_motion_influence()`.

4. *Configuration API:* density, damping, forces, BCs, observers.
5. *Setup.*
6. *Initial conditions.*
7. *Single-step API:* `step()`, `step_to()`, `step_n()`.
8. *Runtime reconfiguration:* `set_time_step()`, `set_director()`.
9. *Batch solve:* `solve(t_final, dt)`, `solve(t0, t1, dt)`.
10. *Post-solve accessors:* displacement, velocity, matrices, `get_analysis_state()`.
11. *Constructor/destructor.*

62.2.5 Incremental Control Policies

The incremental solver in `NonlinearAnalysis` accepts any control strategy satisfying:

```
template <typename S, typename ModelT>
concept IncrementalControlPolicy = requires(
    S& scheme, double p, Vec f_full, Vec f_ext, ModelT* model)
{
    scheme.apply(p, f_full, f_ext, model);
};
```

The `apply()` method is **absolute**: for a given p, it fully determines the system state. This idempotency is critical for bisection rollback — no save/restore logic is needed in the scheme itself.

Three built-in policies are provided:

Policy	Semantics
`LoadControl`	$f_{\text{ext}} = p \cdot f_{\text{full}}$ (proportional scaling, default)
`DisplacementControl`	Prescribed DOF $u_D = p \cdot u_{\text{target}}$; optional $f_{\text{ext}} = p \cdot \alpha \cdot f_{\text{full}}$
`CustomControl<F>`	User-supplied $\lambda(p)$ via `make_control(fn)`

Planned: `ArcLengthControl` (Riks method) requires augmenting the SNES system to (u, λ) with a spherical constraint.

62.2.6 Observer Architecture



- **Static path** (`CompositeObserver`): observers stored in a `std::tuple`, fold-expanded at compile time. Zero virtual dispatch. Use when the observer set is fixed at compile time.
- **Dynamic path** (`DynamicObserverList`): observers behind `unique_ptr<ObserverBase>`, virtual dispatch per step. Negligible cost compared to constitutive evaluation. Use when observers are configured at runtime.
- **Integration**: `DynamicAnalysis::set_observer()` stores an `ObserverCallback` — a struct of three `std::function` fields (`on_start`, `on_step`, `on_end`). The `make_observer_callback<Model` factory bridges any observer-like object to this interface.

Concrete observers.

Observer	Purpose
`ConsoleProgressObserver`	Print step/time to stdout every N steps
`VTKSnapshotObserver`	Write VTU/VTM files at intervals
`NodeRecorder`	Record displacement/velocity at selected nodes
`ElementRecorder`	Record element-level fields
`FiberRecorder`	Record fiber-level σ–ε history
`EnergyRecorder`	Track kinetic, strain, and external work
`MaxResponseTracker`	Track peak displacement/acceleration
`DamageCriterion`	Evaluate damage-based stopping criteria
`FiberHysteresisRecorder`	Record fiber-level hysteresis loops

62.2.7 StepDirector and SteppableSolver

Both `NonlinearAnalysis` and `DynamicAnalysis` satisfy the `SteppableSolver` concept (Chapter 60). The "time axis" has engine-specific semantics:

Engine	Time axis	Range
`NonlinearAnalysis`	Control parameter p	$[0, 1]$
`DynamicAnalysis`	Physical time t	$[0, T]$

The `StepDirector<ModelT>` is a `std::function<StepVerdict(const StepEvent&, const ModelT&)>` evaluated after each converged step. Five factories cover common patterns:

1. `pause_at_times` — pause at listed breakpoints.
2. `pause_every_n` — pause every N steps.
3. `pause_on(pred)` — pause when a predicate fires.
4. `stop_on(pred)` — terminate on a predicate.
5. `compose` — combine directors (most restrictive wins).

62.2.8 AnalysisDirector (Orchestration)

Multi-phase workflows are coordinated by `AnalysisDirector` (Chapter 61). Key design choices:

- Director is *not* templated — phases are type-erased `PhaseCallback = std::function<AnalysisState(c AnalysisState&)>`.
- State flows automatically: the output of phase n becomes the input of phase $n+1$.
- Optional `PhaseGateCallback` for inter-phase decisions.
- Returns a `DirectorReport` with per-phase timing and status.

62.3 Model Module Architecture

62.3.1 Header Inventory

The model module comprises 12 header files in `src/model/`:

Header	Lines	Role
`DoFStorage.hh`	∼400	3 DOF storage policies + concept; default used by `Domain`
`DoF.hh`	∼130	Legacy DOF handler (superseded by `DoFStorage`; retained for transition)
`MaterialPoint.hh`	∼130	Lightweight spatial site carrying material reference
`ModelState.hh`	∼140	Serialisable state snapshot (displacement, velocity, time)
`NodeSelector.hh`	∼330	Concept-based composable node selection (by id, label, box, functor)
`Model.hh`	∼550	Core FEA model: elements, PETSc section, constraints, forces
`ModelBuilder.hh`	∼80	*Dormant* — original domain↔model linker (all code commented)
`BoundaryCondition.hh`	∼690	Time-dependent boundary conditions, IC, ground motion
`LoadUtilities.hh`	∼50	Helper to apply nodal loads
`BuildingDomainBuilder.hh`	∼350	Generates multi-story regular building meshes
`StructuralModelBuilder.hh`	∼150	High-level builder for beam/shell structural models
`GroundMotionRecord.hh`	∼280	Parser for seismic acceleration records (CSV/column)

62.3.2 The `Model<>` Template

`Model` is the central aggregate: it owns the PETSc data structures and connects the domain, elements, materials, and boundary conditions.

```
template <
    typename MaterialPolicy,
    typename KinematicPolicy = continuum::SmallStrain,
    std::size_t ndofs = MaterialPolicy::dim,
    typename ElemPolicy = SingleElementPolicy<
        ContinuumElement<MaterialPolicy, ndofs, KinematicPolicy>>
>
class Model;
```

Template parameters:

`MaterialPolicy`
: Defines the constitutive dimension (`dim`), strain/stress types. Examples: `ThreeDimensionalMateri` `PlaneMaterial`, `UniaxialMaterial`.

`KinematicPolicy`
: Selects the kinematic formulation. Options: `SmallStrain`, `TotalLagrangian`, `UpdatedLagrangian`, `Corotational`.

`ndofs`
: Degrees of freedom per node (defaults to `dim` for solid elements; 6 for structural beam/shell).

`ElemPolicy`
: Storage policy for elements. `SingleElementPolicy` stores a homogeneous `std::vector<ElementT>` `MultiElementPolicy` stores `std::vector<FEM_Element>` (type-erased, heterogeneous).

Responsibilities.

1. **PETSc section management**: creates and configures the `PetscSection` on the DMPlex, assigning DOF counts per mesh point.
2. **Element storage**: owns the element container; provides `elements()` accessor for iteration.
3. **Global vectors**: `force_vector()`, `imposed_solution()`, `state_vector()` — PETSc local vectors managed via RAII.
4. **Constraint management**: `constrain_dof()`, `update_imposed_value()` — manipulates the DM section to enforce essential BCs.
5. **Stiffness injection**: `inject_K(Mat)` — assembles the global tangent stiffness by iterating over elements.
6. **Mass assembly**: `assemble_mass_matrix(Mat)` for dynamics.
7. **State capture**: `capture_state()` / `restore_state()` for checkpoint/restart.

62.3.3 Boundary Condition Framework

The `BoundaryConditionSet<dim>` class provides a declarative API for time-dependent boundary conditions:

- **Nodal forces:** point loads with time modulation.
- **Prescribed displacements:** essential BCs with time functions.
- **Initial conditions:** displacement and velocity ICs.
- **Ground motions:** seismic input (direction + acceleration record).

Integration with `DynamicAnalysis`:

```
BoundaryConditionSet<3> bcs;
bcs.add_force(node_selector, {0, 0, -1000}, linear_ramp);
bcs.add_prescribed(base_nodes, 0, ground_motion_fn);
bcs.add_ground_motion(0, accel_fn);

dyn.set_boundary_conditions(bcs);
dyn.set_initial_conditions(bcs);
```

62.3.4 NodeSelector: Composable Node Queries

`NodeSelector` uses a concept + combinator pattern:

```
template <typename S>
concept NodeSelectorConcept = requires(const S& sel, const Node& n) {
    { sel(n) } -> std::convertible_to<bool>;
};
```

Built-in selectors:

- `ByNodeId{ids}` — select by explicit node ids.
- `ByLabel{label}` — select by physical group label.
- `ByBoundingBox{min, max}` — spatial selection.
- `ByPredicate{fn}` — arbitrary predicate.

Combinators: `operator&&`, `operator||`, `operator!` produce composed selectors. All are value types (no heap allocation).

62.3.5 Semantic Analysis

`DoF.hh` vs. `DoFStorage.hh`

The legacy `DoF_Interface`/`DoF_Handler` classes use `shared_ptr` and a mutable public

member style inconsistent with the rest of the framework. `DoFStorage.hh` replaces them with three clean storage policies (`FixedDoFStorage`, `DynamicDoFStorage`, `PetscDoFStorage`). The old header is retained only for downstream compatibility and should be removed when all consumers migrate.

`ModelBuilder.hh`
All code is commented out. The original purpose (linking Domain to Model) has been absorbed by `StructuralModelBuilder` and `GmshDomainBuilder`. The empty shell is kept to avoid breaking `header_files.hh` includes.

`MaterialPoint.hh`
Correctly named: it represents a spatial location carrying a material reference (a Gauss point with material identity).

`ModelState.hh`
Clean naming; captures a serialisable snapshot of the model.

62.4 Extension Points

62.4.1 Adding a New Solver Engine

To add a new analysis engine (e.g., explicit dynamics or eigenvalue analysis):

1. **Create the header** in `src/analysis/`. Use the same template signature (`MaterialPolicy`, `KinematicPolicy`, `ndofs`, `ElemPolicy`) for compatibility.
2. **Wrap the PETSc solver** (e.g., `EPS` for eigenvalue) with RAII via `petsc::OwnedXxx`.
3. **Implement the solve API**. If the engine supports stepping, provide `step()`, `step_to()`, `step_n()`, `current_time()`, `current_step()` to satisfy `SteppableSolver`.
4. **Provide `get_analysis_state()`** returning an `AnalysisState` for integration with `AnalysisDirector`.
5. **Register in `Analysis.hh`** by adding an include in the "Solver engines" section.

```
// Example skeleton:
template <typename MaterialPolicy, ...>
class EigenvalueAnalysis {
    ModelT* model_;
    petsc::OwnedEPS eps_;
public:
    void solve(int num_modes);
    auto eigenvalues() const -> std::vector<double>;
    auto eigenvector(int i) const -> Vec;

    explicit EigenvalueAnalysis(ModelT* model);
};
```

62.4.2 Adding a New Observer

Runtime observer (recommended for most use cases):

1. Derive from `ObserverBase<ModelT>`.
2. Override `on_step()` (required) and optionally `on_analysis_start()` / `on_analysis_end()`.
3. Add to a `DynamicObserverList` via `list.add<MyObs>(args...)`.

```
template <typename ModelT>
class DriftObserver : public fall_n::ObserverBase<ModelT> {
    double max_drift_{0};
public:
    void on_step(const fall_n::StepEvent& ev,
                 const ModelT& model) override
    {
        double drift = compute_interstory_drift(ev.displacement, model);
        max_drift_ = std::max(max_drift_, drift);
    }
    double max_drift() const { return max_drift_; }
};
```

Compile-time observer (for maximum performance): Implement the three methods (`on_analysis_start`, `on_step`, `on_analysis_end`) as regular member functions (no inheritance needed), then pass to `make_composite_observer`.

62.4.3 Adding a New Incremental Control Policy

Any type satisfying `IncrementalControlPolicy` can be passed to `solve_incremental()` or `begin_incremental()`:

```
struct MyPolicy {
    template <typename ModelT>
    void apply(double p, Vec f_full, Vec f_ext, ModelT* model) {
        // p ∈ [0,1] - must be absolute (idempotent for any p)
        VecCopy(f_full, f_ext);
        VecScale(f_ext, std::sin(p * M_PI / 2.0));  // sine ramp
    }
};

nl.solve_incremental(20, 4, MyPolicy{});
```

Alternatively, use `make_control(lambda)` for one-off policies:

```
auto scheme = make_control([](double p, Vec f_full, Vec f_ext, auto* m) {
    VecCopy(f_full, f_ext);
    VecScale(f_ext, p * p);  // quadratic ramp
});
nl.solve_incremental(10, 4, scheme);
```

62.4.4 Adding a New StepDirector

Step directors are plain callables. Use `pause_on` or `stop_on` for quick construction, or write a full `std::function`:

```
// Stop when inter-story drift exceeds 2%
auto dir = fall_n::step_director::stop_on(
    [](const fall_n::StepEvent& ev, const auto& model) {
        return max_interstory_drift(model) > 0.02;
    }
);
solver.set_director(dir);
```

62.5 Usage Tutorials

62.5.1 Tutorial 1: Simple Linear Static Analysis

```
#include "header_files.hh"

int main(int argc, char** argv) {
    PetscInitialize(&argc, &argv, nullptr, nullptr);
    {
        // 1. Build domain from Gmsh
        auto [domain, groups] = GmshDomainBuilder<3>::from_file("mesh.msh");

        // 2. Create model with elastic material
        auto material = make_elastic_3d(E, nu);
        Model<ThreeDimensionalMaterial> model(&domain);
        model.add_elements(material, groups["solid"]);
        model.apply_forces(groups["load"], {0, 0, -1000});
        model.constrain_nodes(groups["base"], {0, 1, 2});
        model.setup();

        // 3. Solve
        LinearAnalysis la(&model);
        la.solve();

        // 4. Post-process
        VTKModelExporter exporter("result.vtu");
        exporter.write(model);
    }
    PetscFinalize();
}
```

62.5.2 Tutorial 2: Nonlinear Incremental with Displacement Control

```
// Pushover analysis: node 42, direction X, target displacement 0.05 m
NonlinearAnalysis nl(&model);
DisplacementControl dc{42, 0, 0.05};
nl.solve_incremental(50, /*max_bisections=*/4, dc);
```

62.5.3 Tutorial 3: Dynamic Seismic Analysis with Observers

```
DynamicAnalysis dyn(&model);
dyn.set_density(2400.0);  // kg/m^3
dyn.set_rayleigh_damping(omega1, omega2, 0.05);  // 5% at two frequencies
dyn.set_boundary_conditions(bcs);
dyn.set_initial_conditions(bcs);

// Compose observers
auto obs = make_composite_observer<ModelT>(
    ConsoleProgressObserver<ModelT>{100},
    VTKSnapshotObserver<ModelT>{"output/", 50, profile, thickness},
    NodeRecorder<ModelT>{{42, 99}, {0, 1, 2}, 1}
);
dyn.set_observer(obs);
```

```
// Solve
dyn.solve(30.0, 0.01);  // 30 seconds, dt = 0.01 s

// Access recorded data
auto& recorder = obs.get<2>();
auto history = recorder.get_history(42, 0);  // node 42, dof 0
```

62.5.4 Tutorial 4: Multi-Phase Analysis with AnalysisDirector

```
AnalysisDirector director;

// Phase 1: Static gravity preload
director.add_phase("gravity", [&](const AnalysisState& prev) {
    NonlinearAnalysis nl(&model);
    nl.solve_incremental(10);
    return nl.get_analysis_state();
});

// Phase 2: Dynamic seismic excitation
director.add_phase("seismic", [&](const AnalysisState& prev) {
    DynamicAnalysis dyn(&model);
    dyn.set_initial_displacement(prev.displacement);
    dyn.set_boundary_conditions(bcs);
    dyn.solve(30.0, 0.01);
    return dyn.get_analysis_state();
});

auto report = director.run();
report.print_summary();
```

62.5.5 Tutorial 5: Single-Step Control with StepDirector

```
NonlinearAnalysis nl(&model);
nl.begin_incremental(100);  // 100 load steps

// Step to half load, pause every 10 steps
auto dir = fall_n::step_director::pause_every_n<ModelT>(10);

while (nl.current_time() < 1.0 - 1e-14) {
    auto verdict = nl.step_to(1.0, dir);

    if (verdict == fall_n::StepVerdict::Pause) {
        // Inspect model between steps
        auto u_max = get_max_displacement(model);
        std::cout << "p = " << nl.current_time()
                  << ", u_max = " << u_max << "\n";

        if (u_max > threshold) break;  // early termination
    }

    if (verdict == fall_n::StepVerdict::Stop) {
```

```
        std::cerr << "Analysis diverged!\n";
        break;
    }
}
```

62.6 Cross-Module Dependency Map

The full framework follows a strict layered dependency:



No layer may depend on a higher layer. The only allowed cross-layer access is downward. The `header_files.hh` aggregator includes all layers in bottom-up order.

62.7 Ontological Critique

This section critically examines the semantic coherence of the framework's naming conventions.

Well-aligned names.

- `NonlinearAnalysis` / `DynamicAnalysis` / `LinearAnalysis`: clear solver-type distinction.
- `SteppableSolver`: accurately describes the stepping protocol (not "Solver" alone, which is too generic).
- `AnalysisDirector`: orchestrator pattern, correctly signalling "directs" rather than "is."
- `StepDirector`: breakpoint evaluator, distinct from `AnalysisDirector` in scope.
- `IncrementalControlPolicy`: "control" + "policy" maps precisely to the Strategy pattern.
- `NodeSelector`: composable predicate — "selector" is a well-established pattern name.
- `BoundaryConditionSet`: "set" correctly denotes a collection of BCs, not a single BC.

Areas for future refinement.

- `DoF.hh` / `DoF_Interface` / `DoF_Handler`: the "Interface" / "Handler" distinction is unclear. Superseded by `DoFStorage` (clean policy-based design); remove when possible.
- `ModelBuilder`: dormant. The name conflicts with the active `StructuralModelBuilder` and `BuildingDomainBuilder`. Remove or rename to `LegacyModelBuilder` before reuse.

- `Observers.hh`: the filename is generic; consider `ConcreteObservers.hh` or splitting into per-concern files if the file grows further.
- `ElemPolicy` template parameter: "Policy" is accurate for the storage strategy, but could be confused with `MaterialPolicy` or `KinematicPolicy` which govern physics. A name like `StoragePolicy` would reduce ambiguity.

62.8 Code Cleanup Summary

The following changes were applied as part of this architectural review:

1. **`Analysis.hh`**: Removed stale `ANALYSIS CONCEPT : TODO` comment. Reordered includes into five labelled groups following the dependency graph: concepts/types → damping → solvers → orchestration → observers. Added module-level documentation comment.

2. **`DoF.hh`**: Fixed include-guard typo (`DEGGREE` → `DEGREE`).

3. **`header_files.hh`**: Updated the `DoF.hh` transition comment to match current reality.

4. **`ModelBuilder.hh`**: Added a `DORMANT` banner explaining the class's status, its historical role, and the active replacements (`StructuralModelBuilder`, `GmshDomainBuilder`).

All 52 tests pass after these changes.

62.9 Summary

The Analysis and Model modules form a coherent, extensible architecture:

- **Analysis**: concepts define contracts (`SteppableSolver`, `IncrementalControlPolicy`); template engines wrap PETSc solvers with RAII; observers decouple recording; `AnalysisDirector` composes multi-phase workflows.
- **Model**: the `Model<>` template aggregates domain, elements, and PETSc structures; `BoundaryConditionSet` provides a declarative BC API; `NodeSelector` enables composable queries; builders specialise construction for structural and building models.
- **Extension**: new solvers, observers, control policies, and step directors can be added without modifying existing code — the Open/Closed principle is consistently respected.
- **Ontology**: naming is generally precise and well-aligned; legacy artifacts (`DoF.hh`, `ModelBuilder.hh`) are documented and quarantined for future removal.

Chapter 63

Multiscale Seismic Analysis Framework

63.1 Motivation

Seismic assessment of reinforced-concrete buildings requires analysis at multiple resolutions. At the *global* scale, a structural model composed of beam, column, and shell elements captures the overall response under earthquake excitation. At the *local* scale, critical regions identified during the global analysis demand three-dimensional continuum modelling to resolve stress concentrations, cracking patterns, and confinement effects.

Bridging these scales requires:

- parsing earthquake records from international databases,
- generating irregular building domains,
- transitioning between analysis fidelity levels during the same simulation,
- creating prismatic continuum meshes aligned to structural members,
- transferring kinematic fields from beam sections to continuum boundaries,
- orchestrating the creation and management of multiple sub-models.

This chapter documents the six implementation phases that add these capabilities to `fall_n`. Each phase was developed with a test suite that verifies the new functionality in isolation and in composition with existing infrastructure.

63.2 Phase 0: Earthquake Parser Infrastructure

63.2.1 Problem Statement

Earthquake records are distributed in numerous national formats. Before this work, `GroundMotionRecord` supported only two-column and single-column text files. Real-world seismic studies require reading at least:

K-NET (Japan) Header block with origin time, station code, sampling frequency, and a `Scale Factor` line, followed by integer counts that must be multiplied by the scale factor and converted from gal (cm/s^2) to m/s^2.

COSMOS V2 (USA) Multi-line headers with a record count, fixed-width columns of floating-point values, and a physical-units indicator (cm/s^2).

63.2.2 Implementation

The new parsers are added as static factory methods on `GroundMotionRecord`:

```
static GroundMotionRecord from_knet(const std::string& path);
static GroundMotionRecord from_cosmos_v2(const std::string& path);
static GroundMotionRecord from_auto(const std::string& path);
```

K-NET parser. The parser reads the `Sampling Freq(Hz)` and `Scale Factor` fields from the header. A line starting with `Scale Factor` triggers the end of the header; all subsequent non-empty lines are parsed as whitespace-separated integers, multiplied by the scale factor, and converted.

COSMOS V2 parser. The COSMOS V2 format stores the number of data points and the sampling interval in a header line matching the pattern `<N> <...> at <dt> sec`. Data begins after the last header line and consists of fixed-width columns (typically 10 characters) of floating-point values.

Auto-detection. `from_auto` inspects the file's first lines for format signatures:

- Lines containing `Scale Factor` ⇒ K-NET,
- Lines containing `(Uncorrected)` or `COSMOS` ⇒ COSMOS V2,
- Otherwise: two-column or single-column text.

Trimming. A `trim(t_start, t_end)` method filters the record to a time window, discarding samples outside $[t_{\text{start}}, t_{\text{end}}]$ and re-indexing the retained samples from $t = 0$.

63.2.3 Verification

The test suite (`test_ground_motion_parsers.cpp`) includes 33 checks covering:

- K-NET: record count, time step, unit conversion (gal → m/s^2), first/last sample values, peak acceleration;
- COSMOS V2: record count, time step, unit conversion, peak search;
- Auto-detection: correct dispatch for K-NET, COSMOS, and two-column files;
- Trim: window boundary enforcement, time re-indexing, invariance under full-window trim.

63.3 Phase 1: L-Shaped Building Domain Builder

63.3.1 Problem Statement

The existing `BuildingDomainBuilder` creates rectangular floor-plan grids. Real buildings frequently have L-shaped, T-shaped, or other irregular plans. The minimum extension is to support *cutout* regions where cells are omitted from an otherwise rectangular grid.

63.3.2 Design

Rather than introducing a union-of-rectangles approach, the cutout is defined via a predicate `is_active(ix, iy)` that returns `false` for grid cells that lie inside the removed corner. The specification is extended with a `CutoutSpec`:

```
struct CutoutSpec {
    int start_ix, start_iy;   // lower-left corner (grid indices)
    int end_ix, end_iy;       // exclusive upper-right corner
};
```

When a cutout is present, the builder:

1. skips inactive cells during element creation,
2. compresses the node-ID map to eliminate unused nodes, and
3. re-counts elements to produce correct totals.

63.3.3 Verification

The test suite (`test_l_shaped_building.cpp`) contains 39 checks:

- Node and element counts for rectangular, single-cutout, and multi-cutout configurations;
- Correct element-count reductions (e.g. a 4×4 grid with a 2×2 cutout loses the correct number of beam and shell elements);
- Self-weight application on L-shaped domains;
- Edge cases: full cutout (no active cells), zero-size cutout identity.

63.4 Phase 2: Linear–Nonlinear Transition

63.4.1 Problem Statement

A full nonlinear dynamic analysis is computationally expensive. For many earthquake records, the structure responds linearly for most of the excitation and enters nonlinear behaviour only during the strong motion phase. A *transition* strategy runs a cheaper linear analysis until a threshold is exceeded, then switches to a nonlinear solver with the full state transferred at the switching instant.

63.4.2 Design

The `TransitionDirector` module provides:

`make_displacement_threshold_director<ModelT>(u_max)` Returns a `StepDirector` that pauses the solver when the maximum nodal displacement exceeds $u_{\max}$.

`make_damage_threshold_director<ModelT>(criterion, limit)` Returns a `StepDirector` that pauses when a damage criterion (supplied via `DamageCriterion`) exceeds the specified limit.

`ExceedanceReport` Provides per-node exceedance data: which nodes exceeded a displacement threshold and by how much. Uses `DMGlobalToLocal` scatter to correctly handle constrained DOFs.

The transition workflow composes with the `AnalysisDirector` (Chapter 61):

1. Phase A: `DynamicAnalysis` with a displacement-threshold step director. When the director fires, the phase ends and returns its `AnalysisState`.
2. Phase B: A new `DynamicAnalysis` (possibly with different material parameters) resumes from the transferred state.

Critical implementation note. The `AnalysisState` returned by `DynamicAnalysis` contains *borrowed* PETSc `Vec` objects. The owning `DynamicAnalysis` must remain alive while the state is consumed. In the AnalysisDirector phase-callback design, this means the DynA (RAII wrapper) must be constructed *outside* the lambda that returns the state, not inside it.

63.4.3 Verification

The test suite (`test_linear_nl_transition.cpp`) contains 43 checks across 5 tests:

- Displacement threshold triggers pause at the correct step;
- State vectors (displacement, velocity, acceleration) transfer correctly between phases;
- Two-phase pipeline: threshold detection → state transfer → continuation;
- Exceedance report: identifies correct nodes, reports correct magnitudes, handles constrained DOFs via `DMGlobalToLocal`.

63.5 Phase 3: Prismatic Hex Mesh Builder

63.5.1 Problem Statement

Continuum sub-models for critical beam sections require structured hexahedral meshes. The mesh must be *prismatic*: a rectangular cross-section extruded along the beam axis, with known correspondence between mesh faces and beam endpoints.

63.5.2 Design

The builder is implemented in `PrismaticDomainBuilder.hh` and provides:

`PrismaticSpec` Specification struct holding cross-section dimensions (`width`, `height`), extrusion length, subdivision counts (`nx`, `ny`, `nz`), and a coordinate frame (`origin`, `e_x`, `e_y`, `e_z`).

`make_prismatic_domain(spec)` Constructs a `Domain<3>` with hex8 elements and returns both the domain and a `PrismaticGrid` index object.

`PrismaticGrid` Provides:

- `node_id(ix, iy, iz)` — structured-grid node index,
- `nodes_on_face(face)` — boundary node lists, and
- `total_nodes()`, `total_elements()`.

`PrismFace` Enumeration: `MinX`, `MaxX`, `MinY`, `MaxY`, `MinZ`, `MaxZ`.

`align_to_beam(A, B, up, w, h, nx, ny, nz)` Utility that converts beam endpoint coordinates and an "up" vector into a `PrismaticSpec` aligned to the beam element.

Node coordinates are generated in local frame $x \in [-w/2, w/2]$, $y \in [-h/2, h/2]$, $z \in [0, L]$ and then transformed to global coordinates via the specification's orthonormal frame.

63.5.3 Verification

The test suite (`test_prismatic_mesh.cpp`) contains 34 checks:

- Node and element counts for various subdivision levels;
- Node coordinate bounds (ensure all nodes lie within the expected bounding box);
- Face extraction (correct count, all nodes on the expected plane);
- `align_to_beam`: frame orthogonality, axis alignment, length computation;
- Rotated beams: non-axis-aligned configurations.

63.6 Phase 4: Beam–Continuum Field Transfer

63.6.1 Problem Statement

Given the deformed state of a beam element, we need to prescribe displacement boundary conditions on a prismatic continuum sub-model. The transfer must respect the Timoshenko beam kinematic hypothesis: at any section point (y, z) in the beam's local frame,

$$\mathbf{u}(y, z) = \mathbf{u}_c + \boldsymbol{\theta} \times \begin{pmatrix} 0 \\ y \\ z \end{pmatrix}, \tag{63.1}$$

where $\mathbf{u}_c$ is the centerline translation and $\boldsymbol{\theta}$ the section rotation vector, both expressed in the beam's local frame. The global displacement is then $\mathbf{u}_{\text{global}} = \mathbf{R}^T \mathbf{u}(y, z)$, where $\mathbf{R}$ maps global to local coordinates.

63.6.2 Design

The module is implemented in `FieldTransfer.hh` and provides:

`SectionKinematics` Snapshot struct containing: centroid position, local displacement and rotation, rotation matrix, generalized strains (ε_0, κ_y, κ_z, γ_y, γ_z, twist), and material properties (E, G, ν).

`section_displacement_at(kin, y, z)` Evaluates (63.1) and returns the global-frame displacement.

`displacement_at_global_point(kin, P)` Projects a global point P into the beam's local frame to extract (y, z), then delegates to `section_displacement_at`.

`section_stress_at(kin, y, z)` Computes Cauchy stress from beam generalized strains:

$$\sigma_{xx} = E(\varepsilon_0 - z\kappa_y + y\kappa_z), \quad \tau_{xy} = G\gamma_y, \quad \tau_{xz} = G\gamma_z.$$

`section_strain_at(kin, y, z)` Returns the corresponding strain tensor in Voigt form.

`compute_boundary_displacements(kin, domain, node_ids)` For each boundary node, reads coordinates from the domain, projects into the beam local frame, and evaluates the section displacement. Returns a vector of (node ID, displacement) pairs.

`build_beam_submodel(element, u_loc, spec)` Template convenience function that creates a prismatic mesh aligned to a beam element and computes boundary conditions at both end faces. This function uses `extract_section_kinematics` to read beam state (intended for future integration when the beam element exposes the required interpolation interface).

63.6.3 Verification

The test suite (`test_field_transfer.cpp`) contains 34 checks across 7 tests:

- *Pure translation*: uniform displacement at all section points;
- *Pure bending*: linear displacement proportional to y, with antisymmetry about the centroid;
- *Stress reconstruction*: σ_{xx} linear in z, τ_{xy} constant, off-diagonal stresses zero;
- *Global point projection*: consistency between `displacement_at_global_point` and `section_displaceme`
- *Boundary displacement mapping*: prismatic mesh face nodes receive correct BCs from beam kinematics;
- *Sub-model pipeline*: compose `align_to_beam`, `make_prismatic_domain`, and `compute_boundary_displa` end-to-end;
- *Rotated beam*: non-axis-aligned frame with 45° rotation in the xy-plane.

63.7 Phase 5: MultiscaleCoordinator

63.7.1 Problem Statement

Given a global structural analysis with potentially many beam elements, a subset of elements will be flagged as "critical" by damage or displacement criteria. Each critical element requires a continuum sub-model. The `MultiscaleCoordinator` orchestrates the creation, population, and management of all sub-models from a single entry point.

63.7.2 Design

The coordinator follows a three-step workflow:

1. **Register critical elements.** For each element that exceeds a threshold, the user supplies an `ElementKinematics` descriptor containing:
   - element ID,
   - `SectionKinematics` at both ends ($\xi = -1$ and $\xi = +1$),
   - endpoint coordinates and up-direction.
2. **Build sub-models** via `build_sub_models(spec)`. For each registered element, the coordinator:
   (a) calls `align_to_beam` to compute the prismatic specification,
   (b) calls `make_prismatic_domain` to create the mesh,
   (c) calls `compute_boundary_displacements` for both end faces.
3. **Access and reporting.**
   - `sub_models()` returns the collection of `MultiscaleSubModel` objects, each containing the domain, grid, kinematics, and boundary conditions.
   - `report()` provides a `MultiscaleReport` with aggregate statistics: element/node counts, maximum and mean boundary displacements.

The coordinator is designed as a *one-way downscaling* tool: it transfers information from the global beam scale to the local continuum scale. Coupling back (e.g. homogenising sub-model response into the global model) is left for future work.

Design decisions.

- The coordinator operates on `SectionKinematics` rather than on concrete element types. This avoids template dependencies on the global model's element policy and makes the coordinator testable without PETSc solver invocations.
- Each sub-model is fully self-contained: it owns its `Domain<3>`, `PrismaticGrid`, and boundary conditions.
- The coordinator is stateless with respect to the global model; it receives pre-extracted data.

63.7.3 Verification

The test suite (`test_multiscale_coordinator.cpp`) contains 37 checks across 7 tests:

- *Single element*: one critical element → one sub-model with correct mesh dimensions and boundary conditions;
- *Multi-element*: two critical elements → two independent sub-models with correct IDs;
- *Report statistics*: node/element counts, max/mean displacement, max ≥ mean invariant;
- *Clear and rebuild*: the coordinator can be reused across multiple analysis steps;
- *Zero displacement*: clamped element → zero BCs on all faces;
- *Mixed state*: one deformed and one undeformed element produce correct per-element BCs;
- *Rotated element*: beam along global Y with non-trivial rotation matrix; axial displacement correctly maps to global coordinates.

63.8 Integration and Dependency Map

The six phases form a dependency graph:

```
Phase 0 (parsers)      -+
Phase 1 (L-shape)      -+
                        +-→  Phase 2 (transition)  -→  Phase 5
Phase 3 (prismatic)    -+                                  ↑
                        +-→  Phase 4 (field transfer) --+
```

Phases 0, 1, and 3 are independent of each other and were developed in parallel. Phase 2 depends on Phase 0 (earthquake records) and Phase 1 (L-shaped domains). Phase 4 depends on Phase 3 (prismatic meshes). Phase 5 depends on Phases 2 and 4.

63.8.1 New Source Files

File	Phase	Description
`src/analysis/TransitionDirector.hh`	2	Threshold directors + exceedance
`src/model/PrismaticDomainBuilder.hh`	3	Prismatic hex mesh generator
`src/reconstruction/FieldTransfer.hh`	4	Beam→continuum kinematic bridge
`src/analysis/MultiscaleCoordinator.hh`	5	Downscaling orchestrator
`tests/test_ground_motion_parsers.cpp`	0	33 checks
`tests/test_l_shaped_building.cpp`	1	39 checks
`tests/test_linear_nl_transition.cpp`	2	43 checks
`tests/test_prismatic_mesh.cpp`	3	34 checks
`tests/test_field_transfer.cpp`	4	34 checks
`tests/test_multiscale_coordinator.cpp`	5	37 checks

63.8.2 Modified Source Files

- `src/model/GroundMotionRecord.hh` — K-NET, COSMOS V2, `trim`, `from_auto` factories.
- `src/model/BuildingDomainBuilder.hh` — cutout support for irregular floor plans.
- `src/analysis/DamageCriterion.hh` — added missing `<print>` and `<iostream>` includes.
- `header_files.hh` — includes for new modules.
- `CMakeLists.txt` — 6 new test registrations.

63.8.3 Test Summary

Phase	Checks	Status
Phase 0 (parsers)	33	**pass**
Phase 1 (L-shape)	39	**pass**
Phase 2 (transition)	43	**pass**
Phase 3 (prismatic)	34	**pass**
Phase 4 (field transfer)	34	**pass**
Phase 5 (coordinator)	37	**pass**
Total	**220**	
Full suite	58/58	**pass**

63.9 Completed Extensions (Phase 6)

All five items identified in the original Future Work section have been implemented. This section documents the resulting API additions.

63.9.1 Beam element interpolation interface (`BeamInterpolable`)

A C++20 concept `BeamInterpolable<B, U>` was added to `src/reconstruction/FieldTransfer.hh`. It constrains the template parameter of `extract_section_kinematics` and documents the minimal API that any beam element type must expose:

Listing 63.1: BeamInterpolable concept

```
template <typename B, typename U>
concept BeamInterpolable =
    requires(const B& beam, const U& u_loc, double xi,
             const std::array<double, 1>& xi_arr) {
        beam.geometry().map_local_point(xi_arr);
        { beam.rotation_matrix() };
        beam.sample_centerline_translation_local(xi, u_loc);
        beam.sample_rotation_vector_local(xi, u_loc);
        beam.sample_generalized_strain_local(xi, u_loc);
        beam.sections();
    };
```

The three sampling methods (`sample_*_local`) were already part of the `BeamElement` public API; the concept formalises that constraint and generates an informative compiler diagnostic if it is not satisfied.

63.9.2 Sub-model solve (`SubModelSolver`)

`src/reconstruction/SubModelSolver.hh` provides a self-contained solver for a single prismatic continuum sub-model:

Listing 63.2: SubModelSolver usage

```
fall_n::SubModelSolver solver(E, nu);          // linear-elastic material
fall_n::SubModelSolverResult res =
    solver.solve(coordinator.sub_models()[i]);

if (res.converged) {
    // Volume-averaged Voigt stress (global frame)
    Eigen::Vector<double,6> sig = res.avg_stress;
    double E_eff = res.E_eff;     // <sigma_xx> / <eps_xx>
    double G_eff = res.G_eff;     // <tau_xy>   / <gamma_xy>
}
```

Internally, `solve()` builds a `Model<ThreeDimensionalMaterial, SmallStrain, 3>` from the sub-model's `Domain<3>`, assigns Dirichlet boundary conditions at both end faces from the pre-computed `bc_min_z` and `bc_max_z` maps, and delegates to `NonlinearAnalysis` (rather than `LinearAnalysis`) because non-zero Dirichlet conditions require the full K_{fc} coupling term.

After convergence, all Gauss-point stresses and strains are volume-averaged, the von Mises maximum is recorded, and effective moduli are derived:

$$E_{\text{eff}} = \frac{\langle \sigma_{xx} \rangle}{\langle \varepsilon_{xx} \rangle}, \qquad G_{\text{eff}} = \frac{\langle \tau_{xy} \rangle}{\langle \gamma_{xy} \rangle}.$$

63.9.3 Bidirectional coupling (`HomogenizedBeamSection`)

`src/reconstruction/HomogenizedSection.hh` closes the downscale→upscale loop. Two free functions are provided:

`to_beam_local_stress`. Projects a global-frame average Voigt stress vector to the beam's local frame using the element rotation matrix R:

$$\boldsymbol{\sigma}_{\text{local}} = R\,\boldsymbol{\sigma}_{\text{global}}\,R^{\top}.$$

`homogenize`. Computes beam section resultants under the uniform-stress assumption:

$$N = A\,\sigma_{11}^{\text{local}}, \quad V_y = A\,\tau_{12}^{\text{local}}, \quad V_z = A\,\tau_{13}^{\text{local}}, \quad M_y = E_{\text{eff}}\,I_y\,\kappa_y, \quad M_z = E_{\text{eff}}\,I_z\,\kappa_z,$$

where $A = b\,h$, $I_y = b\,h^3/12$, and $I_z = h\,b^3/12$ for a rectangular cross-section.

Listing 63.3: Bidirectional coupling

```
auto hs = fall_n::homogenize(res, sub, width, height);
// hs.N, hs.Vy, hs.Vz, hs.My, hs.Mz
// hs.E_eff, hs.G_eff  (ready to update the global beam element)
```

63.9.4 PETSc TS state injection (`inject_dynamic_state`)

A template function in `src/analysis/TransitionDirector.hh` transfers a complete kinematic state — displacement, velocity, and time — into a target `DynamicAnalysis` object:

Listing 63.4: inject_dynamic_state

```
template <typename DynamicAnalysisT>
```

```
void inject_dynamic_state(DynamicAnalysisT& target,
                          Vec u_global, Vec v_global,
                          double t = 0.0);
```

Internally it calls `set_initial_displacement(u_global)`, `set_initial_velocity(v_global)`, and, when $t \neq 0$, `TSSetTime(target.get_ts(), t)`. Because `set_initial_*` performs a `VecCopy` into the live TS solution vector, the injection is safe both before and after `setup()` has been called.

63.9.5 Parallel sub-model creation (two-phase `build_sub_models`)

`MultiscaleCoordinator::build_sub_models()` was refactored into two sequential phases:

1. **Phase 1 — sequential mesh creation.** `DMPlex` mesh construction is not thread-safe in PETSc; all domains and grids are therefore built in a single sequential loop.
2. **Phase 2 — parallel BC computation.** Each sub-model's boundary displacements are independent pure-Eigen computations. With OpenMP available, this loop is parallelised via `#pragma omp parallel for schedule(static)`. On platforms without OpenMP the same code path runs sequentially.

The two-phase design is summarised in the code comment:

Listing 63.5: Two-phase build_sub_models

```
// Phase 1 (sequential): mesh creation via PETSc (not thread-safe)
for (std::size_t i = 0; i < n; ++i) { /* make_prismatic_domain */ }

// Phase 2 (parallel): BC computation is pure Eigen
#ifdef _OPENMP
#pragma omp parallel for schedule(static)
#endif
for (std::size_t i = 0; i < n; ++i) {
    sub.bc_min_z = compute_boundary_displacements(ek.kin_A, ...);
    sub.bc_max_z = compute_boundary_displacements(ek.kin_B, ...);
}
```

63.9.6 Test coverage

Seven unit tests in `tests/test_sub_model_solver.cpp` cover all new functionality and are registered in `CMakeLists.txt` under the `unit` label (`ctest -L unit`):

1. Zero-displacement BCs $\Rightarrow$ trivial (zero) solution.
2. Uniform axial extension $\Rightarrow \sigma_{xx} \approx E\varepsilon_0$, $E_{\text{eff}} \approx E$.
3. Homogenization consistency: $N = A\,\sigma_{xx}$.
4. `to_beam_local_stress` with $R = I$ leaves stress unchanged.
5. `to_beam_local_stress` with a 90° rotation swaps $\sigma_{xx} \leftrightarrow \sigma_{yy}$.
6. `homogenize()` returns $V_y = A\,\tau_{12}$, $V_z = A\,\tau_{13}$.
7. Parallel `build_sub_models`: two identical elements produce identical sub-models.

63.10 Phase 6: Sub-Model VTK Export and Transition Bug Fix

Two targeted extensions complete the multiscale pipeline and make it ready for post-processing in ParaView.

63.10.1 VTK export in SubModelSolver

`SubModelSolver::solve()` now accepts an optional second argument `vtk_prefix`. When non-empty, two VTK files are written immediately before returning the result:

Listing 63.6: SubModelSolver.hh – VTK export

```
SubModelSolverResult
solve(MultiscaleSubModel& sub, const std::string& vtk_prefix = "")
{
    // ... build Model M, apply BCs, solve SNES ...

    if (!vtk_prefix.empty()) {
        fall_n::vtk::VTKModelExporter exporter{M};
        exporter.set_displacement();
        exporter.compute_material_fields();
        exporter.write_mesh   (vtk_prefix + "_mesh.vtu");
        exporter.write_gauss_points(vtk_prefix + "_gauss.vtu");
    }
    return result;
}
```

- `*_mesh.vtu` – the deformed hex8 mesh with nodal displacements; suitable for visual inspection of the sub-model deformation pattern.
- `*_gauss.vtu` – a point cloud locating every Gauss point and carrying volume-averaged Voigt stress components $(\sigma_{xx}, \sigma_{yy}, \sigma_{zz}, \tau_{yz}, \tau_{xz}, \tau_{xy})$ and von Mises equivalent stress σ_{VM}.

63.10.2 TransitionDirector copy-constructibility fix

`std::function` requires its stored callable to be *copy-constructible*. The earlier implementation of `make_damage_threshold_director` captured the criterion clone in a `unique_ptr`, rendering the lambda non-copyable and producing a hard compiler error when stored in `std::function`.

The fix replaces the `unique_ptr` capture with a `shared_ptr`:

Listing 63.7: TransitionDirector.hh – shared_ptr fix

```
// Before (broken: unique_ptr capture is move-only)
auto crit_clone = criterion.clone();   // unique_ptr<DamageCriterion>
auto director = [report, crit = std::move(crit_clone)] (...) {...};

// After (correct: shared_ptr is copy-constructible)
auto crit_shared =
    std::shared_ptr<DamageCriterion>(criterion.clone());
auto director = [report, crit = crit_shared] (...) mutable {...};
```

The observable behaviour is unchanged; the fix only removes the compiler error and allows the lambda to be assigned to a `std::function<StepVerdict(const StepEvent&, const ModelT&)>`.

63.11 Elastic Verification Example

The program `main_multiscale.cpp` verifies the full downscale → solve → homogenize pipeline against elementary beam theory without requiring a running global analysis.

63.11.1 Physical scenario and hypotheses

A rectangular elastic column ($E = 30\,\text{GPa}$, $\nu = 0.20$, $b \times h = 0.30 \times 0.30\,\text{m}$) of height $L = 3.0\,\text{m}$ is subjected to simultaneous gravity and seismic loading:

$$N = -540\,\text{kN}, \qquad V_y = +60\,\text{kN}, \qquad M_z = +180\,\text{kN}\cdot\text{m}. \tag{63.2}$$

The beam is discretised into two equal elements of length $L_e = 1.5\,\text{m}$. Both elements are registered as critical; their boundary conditions are prescribed analytically from Bernoulli–Timoshenko cantilever theory:

$$\varepsilon_0 = \frac{N}{EA} = -\frac{540\,\text{kN}}{30\,\text{GPa} \times 0.09\,\text{m}^2} = -2.000 \times 10^{-4}, \tag{63.3}$$

$$\kappa_z(x) = \frac{V_y(L-x)}{EI_z} = \frac{60\,\text{kN}\cdot(3-x)\,\text{m}}{30\,\text{GPa} \times 6.75 \times 10^{-4}\,\text{m}^4}, \tag{63.4}$$

giving $\kappa_z(0) = 8.889 \times 10^{-3}\,\text{rad/m}$ at the fixed base and $\kappa_z(L_e) = 4.444 \times 10^{-3}\,\text{rad/m}$ at mid-height.

Each sub-model is a prismatic hex8 mesh, 3×3 divisions across the section and 6 elements along the axis, yielding $3 \times 3 \times 6 = 54$ elements and 112 nodes in a $0.30 \times 0.30 \times 1.5\,\text{m}$ domain.

63.11.2 Results

Table 63.1: Elastic multiscale verification – Part A (root element, $x = 0$–$1.5\,\text{m}$, single sub-model).

Quantity	Symbol	Computed	Expected	Error
Axial force	N [kN]	−546.41	−540.00	+1.2%
Lateral shear	V_y [kN]	+71.97	+60.00	+20.0%
Bending moment	M_z [kN·m]	+182.14	+180.00	+1.2%
Effective modulus	E_{eff} [GPa]	30.356	30.000	+1.2%
Shear modulus	G_{eff} [GPa]	12.500	12.500	0.0%
Max $\lvert\mathbf{u}\rvert$	– [mm]	8.333	8.333	0.0%

63.11.3 Discussion

Axial and bending accuracy (error ≈ 1.2%). Both N and M_z exceed the beam-theory value by approximately 1.2%. This systematic overestimation arises from the 3×3 cross-section mesh: the average stress $\langle\sigma_{xx}\rangle$ computed over nine integration cells captures the linear variation of the bending strain with mesh-size-dependent quadrature error. Refinement to a 5×5 grid reduces this error to below 0.2% in tests.

Shear overestimation (error ≈ 20%). The lateral shear $V_y = 71.97\,\text{kN}$ overestimates the reference 60 kN by approximately 20%. The uniform-stress homogenization formula $V_y = \langle\tau_{xy}\rangle\cdot A$ assumes a spatially uniform shear stress, whereas Timoshenko beam theory distributes shear parabolically over the section. On a 3×3 mesh this parabolic average is poorly approximated. The shear correction factor $\kappa_s = 5/6$ is applied at the beam element level; the continuum sub-model does not inherit this correction directly, which further contributes to the difference.

Effective moduli. $E_{\text{eff}} = 30.356\,\text{GPa}$ is within 1.2% of the material value; $G_{\text{eff}} = 12.500\,\text{GPa}$ is exact to four decimal places, confirming that the isotropic shear homogenization is correct and mesh-independent for uniform shear loading.

Convergence. The Newton–Krylov solver converges in 2 SNES iterations for the linear-elastic problem, reaching a relative residual below 10^{-6}, and the KSP (GMRES) solver requires 22 iterations to resolve the full compliance spectrum of the hex8 mesh.

Part B (both elements solved simultaneously under OpenMP) produces identical results for element 0 and $M_z = 91.07\,\text{kN}\cdot\text{m}$ for element 1 (expected $V_y(L - L_e) = 90\,\text{kN}\cdot\text{m}$, error +1.2%), confirming that the parallel build does not alter the physics.

63.11.4 Key code excerpt

Listing 63.8: main_multiscale.cpp – core pipeline

```
// 1. Prescribe section kinematics from beam theory
ElementKinematics ek = make_element_kinematics(0, 0.0, L_e, ...);

// 2. Register + build prismatic sub-model (3x3 section, 6 axial
   elements)
MultiscaleCoordinator coord;
coord.add_critical_element(ek);
coord.build_sub_models({b, h, /*nx=*/3, /*ny=*/3, /*nz=*/6});

// 3. Solve elastic continuum sub-model (Newton-Krylov)
SubModelSolver solver(E, nu);
auto result = solver.solve(coord.sub_models()[0]);

// 4. Homogenize: volume-averaged stress -> section resultants
auto hs = homogenize(result, coord.sub_models()[0], b, h);

// Results: N=-546.4 kN, Mz=182.1 kN*m, E_eff=30.36 GPa
```

63.12 Seismic Fiber-Section Multiscale Example

The program `main_multiscale_seismic.cpp` demonstrates the complete two-phase seismic multiscale workflow on a realistic RC frame subjected to the 2011 Tohoku earthquake.

63.12.1 Physical scenario

Earthquake record. The ground motion is the K-NET record from station MYG012 (Shiogama, Miyagi Prefecture), NS component of the 2011-03-11 Mw 9.0 Tohoku Earthquake. Parameters used:

- sampling interval $\Delta t = 0.01\,\text{s}$;
- analysis window trimmed to $[0, 120]\,\text{s}$;
- $\text{PGA} = 8.14\,\text{m/s}^2$ $(0.83\,g)$ at $t = 88.89\,\text{s}$.

Structural model. A three-story, one-bay × one-bay reinforced-concrete frame:

- plan: 6.0 m (X) × 5.0 m (Y);
- story height: 3.5 m;
- 16 nodes, 12 columns, 12 beams, 3 elastic slabs (⇒ 27 structural elements).

Material models. All beam/column elements use fibre-discretised cross-sections:

1. *Concrete fibres* – Kent–Park model (unconfined cover + confined Mander core for columns).
2. *Steel fibres* – Menegotto–Pinto model with kinematic hardening ratio $b = 0.01$.

Table 63.2: RC section material parameters.

Parameter	Symbol	Value	Unit
Columns ($0.45 \times 0.45\,m$)			
Concrete strength	f'_c	30	MPa
Steel yield strength	f_y	420	MPa
Steel elastic modulus	E_s	200 000	MPa
Hardening ratio	b	0.01	–
Bar diameter	ϕ	22	mm
Tie spacing	s	100	mm
Volumetric steel ratio	ρ_s	0.015	–
Number of fibres	–	92	–
Beams ($0.30 \times 0.50\,m$)			
Concrete strength	f'_c	25	MPa
Bar diameter	ϕ	19	mm
Number of fibres	–	78	–

Dynamic analysis parameters.

- Integrator: generalised-α (TSAlpha2), $\rho_\infty = 0.9$, $\Delta t = 0.01\,\mathrm{s}$.
- Rayleigh damping: $\xi = 5\%$ at $\omega_1 = 11.42\,\mathrm{rad/s}$ ($T_1 = 0.55\,\mathrm{s}$) and $\omega_3 = 52.36\,\mathrm{rad/s}$ ($T_3 = 0.12\,\mathrm{s}$).
- Excitation: uniaxial base acceleration in the X direction.

63.12.2 Two-phase analysis workflow

Phase 1 – Global nonlinear fiber-section analysis. The `DynamicAnalysis` solver advances in 0.01 s increments using a Newton–Krylov (SNES/KSP) nonlinear solver. At every step a `DamageTracker<StructModel>` observer evaluates a `MaxStrainDamageCriterion` at each element integration point:

$$d_i = \frac{\max_{\text{fibre}} |\varepsilon_{xx}|}{\varepsilon_y}, \qquad \varepsilon_y = \frac{f_y}{E_s} = \frac{420}{200\,000} = 0.0021. \tag{63.5}$$

A `make_damage_threshold_director` is created with threshold $d^* = 1.0$. The `step_to(T_MAX, director)` loop pauses the moment any fibre first reaches ε_y, returning `StepVerdict::Pause` and recording the trigger time, element index, and damage value in a `TransitionReport`.

Phase 2 – Local continuum sub-model. After the transition:

1. The current damage ranking is queried via `DamageTracker::peak_ranking()`. The top three beam/column elements with $d > 0.8$ are selected.
2. For each critical element, `StructuralElement::as<BeamElemT>()` provides a type-safe pointer to the concrete `BeamElement` object.

3. `extract_section_kinematics()` extracts ε_0, κ_y, κ_z, end displacements, and rotations at $\xi = \pm 1$ (both element ends).

4. These kinematics are packed into `ElementKinematics` and passed to `MultiscaleCoordinator::add_crit`

5. `build_sub_models()` creates one $4 \times 4 \times 8$ prismatic hex8 sub-model per critical element (0.45×0.45 m column section).

6. `SubModelSolver::solve(sub, vtk_prefix)` solves each sub-model elastically (ACI initial stiffness $E_c = 4700\sqrt{f'_c} \approx 25\,740$ MPa, $\nu = 0.20$) and writes VTK output files.

7. `homogenize()` converts volume-averaged stress to section resultants N, V_y, V_z, M_y, M_z.

63.12.3 Output

Three sets of VTK files are produced under `data/output/multiscale_seismic/`:

`yield_state.vtm` Multi-block dataset containing the global structural frame at the instant of first yielding: beam meshes, cross-section fibres, shell elements, and nodal displacements.

`sub_models/sub_{i}_mesh.vtu` Deformed continuum hex8 mesh for critical element i, with nodal displacements.

`sub_models/sub_{i}_gauss.vtu` Gauss-point cloud for critical element i carrying $\sigma_{xx}, \sigma_{yy}, \sigma_{zz}, \tau_{yz}, \tau_{xz}, \tau_{xy}, \sigma_{\mathrm{VI}}$

63.12.4 Key code excerpt

Listing 63.9: main_multiscale_seismic.cpp – two-phase workflow

```
// --- Phase 1: global nonlinear fiber-section dynamic analysis ---
MaxStrainDamageCriterion damage_crit{EPS_YIELD};
DamageTracker<StructModel> tracker{model, damage_crit};
solver.add_observer(tracker);

auto director =
    make_damage_threshold_director<StructModel>(damage_crit, 1.0);
solver.step_to(T_MAX, director);   // pauses at first yield

// --- Transition report ---
auto report = tracker.transition_report();
// report->trigger_time, report->critical_element

// --- Phase 2: extract kinematics, build sub-models, solve ---
for (auto e_idx : top3_damaged_beam_elements) {
    const auto* beam = model.elements()[e_idx].as<BeamElemT>();
    auto u_e   = model.elements()[e_idx].extract_element_dofs(u_local);
    auto kin_A = extract_section_kinematics(*beam, u_e, -1.0);
    auto kin_B = extract_section_kinematics(*beam, u_e, +1.0);
    coordinator.add_critical_element({e_idx, kin_A, kin_B, xA, xB});
}
coordinator.build_sub_models({COL_B, COL_H, 4, 4, 8});

SubModelSolver sub_solver{EC_COL, NU_RC};
for (std::size_t i = 0; i < coordinator.sub_models().size(); ++i) {
    auto result = sub_solver.solve(coordinator.sub_models()[i],
                                   OUT + "sub_models/sub_" +
                                   std::to_string(i));
    auto hs = homogenize(result, coordinator.sub_models()[i],
```

```
                                COL_B, COL_H);
    // hs.N, hs.Vy, hs.Mz, hs.E_eff, hs.G_eff
}
```

63.12.5 Numerical results

Phase 1 outcome. At the time of writing, the dynamic run has *not yet produced a valid* first-yield time t_y. This is no longer interpreted as a physical "elastic response" result; it is now understood as a diagnostic issue in the dynamic post-processing path. The chronology is important:

1. The first working seismic executable used the MYG012 record, but the code never called `solver.set_time_step(DT)` before `step_to()`. PETSc therefore advanced with its own default time step and heavy step subdivision. The original argument "$\varepsilon_{\max} = 0$ despite large PGA, therefore the section is not updating" was *wrong*; the run had not yet reached the strong-motion window at the expected physical time.

2. After forcing the intended time step, the diagnostics `|u|_inf` showed nonzero structural motion, so the earlier claim "the structure is not responding" was also false. What was actually happening was severe time-step compression near the P-wave arrival.

3. A second incorrect assumption was that adding `-snes_max_it`, `-snes_rtol`, `-snes_atol`, and `-ksp_max_it` after `solver.setup()` would affect the already-created PETSc solver objects. PETSc later reported these options as unused. This was corrected by moving the options before `setup()` and by setting tolerances directly on the live `SNES/KSP` objects.

4. The excitation was then changed from the late-peaking MYG012 window to the stronger near-fault MYG004 record, and the scale factor was made a runtime parameter to allow controlled sweeps.

5. The decisive instrumentation step was to print, at every 500 steps, the global displacement norm $|u|_\infty$, the local-state norm $|u_{\text{local}}|_\infty$, the maximum section generalized strain, and the maximum fibre strain reconstructed from `section_snapshots()`. These diagnostics showed a consistent pattern:

   - $|u|_\infty > 0$ in the PETSc time-step monitor,
   - $|u_{\text{local}}|_\infty = 0$ after localization,
   - section generalized strains remain zero,
   - reconstructed fibre strains remain zero.

   At this point the localization mechanism (PETSc section layout, constraint registration, `DMGlobalToLocal` API usage) was verified correct in isolation: a manual scatter inside the director lambda produced $|u_{\text{local}}| = 2.9 \times 10^{-4} > 0$. The problem was therefore *not* in the scatter itself.

6. The root cause was identified by instrumenting `post_step_()` with `printf+fflush` calls that *never appeared in output*, even though the observer callback invoked *from within* `post_step_()` was known to execute (it produced diagnostic output through the director lambda). This proved that the `TSMonitor` callback registered via `TSMonitorSet()` was **not being fired** by PETSc during `TSStep()` on this platform (Windows/MSYS2, PETSc 3.22).

   The architecture of `step_to()` was:

   (a) Call `step()` → `TSStep()` advances the global solution $\mathbf{U}^{n+1}$.

(b) Call the director callback to evaluate damage and decide whether to pause.

Step (b) read `model_->state_vector()`, which is a *local* PETSc vector that was supposed to be updated by `post_step_()` between (a) and (b). Since the `TSMonitor` never fired, the local state was never updated, and the damage criterion always saw identically zero.

Fix. The global-to-local scatter, imposition of Dirichlet values, and material state commitment were moved *directly* into `step_to()` and `step_n()`, immediately after `step()` and before the director call:

```
// Inside step_to(), after step():
DM dm;
TSGetDM(ts_, &dm);
Vec U_cur;
TS2GetSolution(ts_, &U_cur, nullptr);  // global solution
Vec scratch;
DMGetLocalVector(dm, &scratch);
DMGlobalToLocal(dm, U_cur, INSERT_VALUES, scratch);
VecAXPY(scratch, 1.0, model_->imposed_solution());
VecCopy(scratch, model_->state_vector());
DMRestoreLocalVector(dm, &scratch);
model_->commit_material_state(model_->state_vector());
// NOW call director -- it sees updated local state
```

This makes `step_to()` self-contained with respect to state synchronisation, regardless of whether `TSMonitor` fires.

Validation. With the fix applied, the dynamic analysis produces physically consistent results. Two scale-factor levels were tested:

- **Scale** = 2.0: peak damage index $d_{\max} = 0.663$ (66.3% of yield strain); no yielding detected in 100 s. This confirms the frame remains elastic under moderate amplification.
- **Scale** = 5.0: **first yield detected** at $t_y = 65.24$ s, with damage index $d = 1.034$ (fibre strain $\varepsilon = 2.172 \times 10^{-3} > \varepsilon_y = 2.1 \times 10^{-3}$). The critical elements are columns 0 and 2 (first-storey columns), consistent with the expected soft-storey mechanism under strong horizontal excitation.

The trigger time $t_y = 65.24$ s corresponds to $t = 95.24$ s in the original (untrimmed) record, which falls within the peak-PGA zone of the Tohoku main shock (PGA = 26.794 m/s^2 at the MYG004 station). The first-storey column failure mode is physically expected: the fixed-base columns carry the full horizontal shear from all three storeys while having the same cross-section as the upper columns.

Phase 2 sub-model results. Phase 2 sub-model extraction is currently blocked by a secondary bug: the section-level generalised strains (ε_0, κ_z) read from `FiberSection3D::current_state()` return zero despite the fibre-level strains being nonzero after commit. This prevents the beam-theory displacement field from being imposed as boundary conditions on the continuum sub-models. The table below is preserved as pending output; the sub-model kinematics extraction requires further investigation.

Once the section kinematics extraction is corrected, the effective Young's modulus E_{eff} should recover the ACI initial tangent stiffness $E_c = 4700\sqrt{f'_c}$ since the continuum sub-model uses linear elasticity; deviations below 2% are expected from mesh-size effects as demonstrated in the elastic verification (Section 63.11).

63.12.6 Infrastructure footprint

The seismic example exercises every component added during Phases 0–6:

Table 63.3: Pending sub-model results at first valid yielding (column elements, elastic sub-model $E_c = 25\,740\,\text{MPa}$, $\nu = 0.20$, $4 \times 4 \times 8$ mesh).

Sub-model	N [kN]	V_y [kN]	M_z [kN·m]	E_{eff} [GPa]	G_{eff} [GPa]
0 (col.)	—	—	—	—	—
1 (col.)	—	—	—	—	—
2 (col.)	—	—	—	—	—

- **Phase 0**: `GroundMotionRecord::from_knet()` parses the K-NET text file; `trim()` extracts the first 120 s.
- **Phase 1**: `LShapedBuildingDomainBuilder` (here used as a rectangular sub-case) constructs nodes and element connectivity.
- **Phase 2**: `DamageTracker` + `TransitionDirector` drive the linear-to-nonlinear transition without modifying the solver.
- **Phase 3**: `PrismaticDomainBuilder` generates one $4\times4\times8$ hex8 mesh per critical element.
- **Phase 4**: `FieldTransfer::transfer()` imposes the beam-theory displacement field as Dirichlet BCs on the sub-model boundary faces.
- **Phase 5**: `MultiscaleCoordinator` manages element registration, BC computation, and sub-model life-cycle.
- **Phase 6**: VTK output via `SubModelSolver::solve()` with `vtk_prefix` and global-frame export via `fall_n::vtk::StructuralVTMExporter`.

63.12.7 Multiscale functionality summary

Table 63.4 lists all classes and free functions that implement the multiscale framework, together with the phase in which they were introduced.

Table 63.4: Multiscale framework – complete functionality inventory.

Class / function	Phase	Role
`GroundMotionRecord`	0	K-NET/COSMOS parser, trim, PGA
`LShapedBuildingDomainBuilder`	1	RC frame domain + connectivity
`DamageTracker<ModelT>`	2	per-step element damage monitoring
`TransitionDirector`	2	pause/stop callback for `step_to`
`MaxStrainDamageCriterion`	2	fibre strain $\div\ \varepsilon_y$
`PrismaticDomainBuilder`	3	hex8 prismatic mesh on PETSc DMPlex
`FieldTransfer`	4	beam kinematics $\rightarrow$ hex BC
`ElementKinematics`	4	section kinematics at both element ends
`SectionKinematics`	4	$\varepsilon_0, \kappa_y, \kappa_z$, displ., rotation, E, G, ν
`MultiscaleCoordinator`	5	sub-model life-cycle manager
`SubModelSolver`	5	elastic continuum solve + homogenize
`homogenize()`	5	$\langle\sigma\rangle \rightarrow N, V, M$
`SubModelSolver::solve(,vtk)`	6	VTK export of deformed mesh + GP cloud
`StructuralVTMExporter`	6	global frame VTK at yield

Chapter 64

Ko–Bathe Concrete Model: Three-Dimensional Extension

Chapter 56 documented the plane-stress ($N = 3$) implementation of the Ko–Bathe plastic-fracturing concrete model. This chapter extends the formulation to the full three-dimensional stress space ($N = 6$), following the same algorithmic structure—fracturing, plasticity, cracking—but with the geometric and algebraic modifications required by six independent stress components and three potential crack planes.

The implementation resides in a single header, `KoBatheConcrete3D.hh` (∼620 lines), and reuses the `KoBatheParameters` structure from the 2D version without modification.

64.1 Voigt Convention and State Variables

The Voigt ordering follows the `fall_n` convention:

$$\boldsymbol{\sigma} = (\sigma_{xx},\ \sigma_{yy},\ \sigma_{zz},\ \tau_{yz},\ \tau_{xz},\ \tau_{xy})^T, \quad \boldsymbol{\varepsilon} = (\varepsilon_{xx},\ \varepsilon_{yy},\ \varepsilon_{zz},\ \gamma_{yz},\ \gamma_{xz},\ \gamma_{xy})^T, \tag{64.1}$$

where $\gamma_{ij} = 2\varepsilon_{ij}$ denotes engineering shear strain.

The internal state structure `KoBatheState3D` stores:

- **Fracture history**: $\sigma_{o,\max}$ and $\tau_{o,\max}$ (octahedral stress maxima driving stiffness degradation).
- **Plastic strain**: $\boldsymbol{\varepsilon}^p \in \mathbb{R}^6$ in Voigt notation, plus three effective plastic strains $\bar{\varepsilon}_1^p$, $\bar{\varepsilon}_2^p$, $\bar{\varepsilon}_3^p$ (compression coordinate hardening variables).
- **Crack data**: up to 3 orthogonal smeared cracks, each defined by a normal vector $\mathbf{n}_i \in \mathbb{R}^3$, opening strain $\varepsilon_{nn,i}$, maximum historical opening $\varepsilon_{nn,i}^{\max}$, and a closure flag.

64.2 Octahedral Stress Invariants in 3D

For a general three-dimensional stress state with principal stresses $\sigma_1 \geq \sigma_2 \geq \sigma_3$ obtained from the eigenvalue decomposition of the Cauchy stress tensor, the octahedral invariants are

$$\sigma_o = \frac{1}{3}(\sigma_1 + \sigma_2 + \sigma_3), \tag{64.2}$$

$$\tau_o = \frac{\sqrt{2\,J_2}}{3}, \qquad J_2 = \tfrac{1}{2}(s_1^2 + s_2^2 + s_3^2), \tag{64.3}$$

where $s_i = \sigma_i - \sigma_o$ are deviatoric principal stresses.

The Lode angle $\theta \in [0, \pi/3]$ is computed via

$$\cos(3\theta) = \frac{3\sqrt{3}}{2} \frac{J_3}{J_2^{3/2}}, \qquad J_3 = s_1\, s_2\, s_3. \tag{64.4}$$

The Lode angle governs the shape of the failure surface in the deviatoric plane through an elliptic interpolation function (see Section 64.7).

Reduction to plane stress. Setting $\sigma_3 = 0$ and computing the principal stresses from $(\sigma_{xx}, \sigma_{yy}, \tau_{xy})$ recovers the 2D octahedral invariants of Chapter 56.

64.3 Principal Strain Decomposition

The elastic strain tensor

$$\mathbf{E}^e = \begin{pmatrix} \varepsilon_{xx} & \varepsilon_{xy} & \varepsilon_{xz} \\ \varepsilon_{xy} & \varepsilon_{yy} & \varepsilon_{yz} \\ \varepsilon_{xz} & \varepsilon_{yz} & \varepsilon_{zz} \end{pmatrix}, \qquad \varepsilon_{ij} = \gamma_{ij}/2 \text{ for } i \neq j,$$

is decomposed by Eigen's `SelfAdjointEigenSolver` into sorted principal values $\varepsilon_1 \geq \varepsilon_2 \geq \varepsilon_3$ and an orthogonal eigenvector matrix $\mathbf{V}$. The rows of $\mathbf{V}$ are the principal directions, so that the rotation from global to principal coordinates is $\varepsilon^{\text{princ}} = \mathbf{V} \cdot \varepsilon^{\text{global}} \cdot \mathbf{V}^T$.

64.4 Compression Coordinates

Plasticity operates in a *compression coordinate* space derived from the compressive magnitudes of the principal elastic strains:

$$D_i = \max(-\varepsilon_i^e,\ 0), \qquad i = 1, 2, 3. \tag{64.5}$$

Since $\varepsilon_1 \geq \varepsilon_2 \geq \varepsilon_3$, we have $D_3 \geq D_2 \geq D_1 \geq 0$.

The three elastic strain coordinates that drive the yield surfaces are:

$$\hat{e}_1 = \frac{D_1 + D_2 + D_3}{\sqrt{3}} \qquad \text{(hydrostatic)}, \tag{64.6}$$

$$\hat{e}_2 = D_3 - D_1 \qquad \text{(deviatoric)}, \tag{64.7}$$

$$\hat{e}_3 = \frac{D_1 + D_2 + D_3}{2} \qquad \text{(biaxial)}. \tag{64.8}$$

Consistency with the 2D formulation. In the plane-stress case ($\varepsilon_3 = \sigma_{zz} = 0$, so $D_3 = 0$ whenever $\varepsilon_3 \geq 0$), the coordinates reduce to

$$\hat{e}_1 \to \frac{D_1 + D_2}{\sqrt{3}}, \qquad \hat{e}_2 \to D_2 - D_1, \qquad \hat{e}_3 \to \frac{D_1 + D_2}{2},$$

which is exactly the 2D definition in Chapter 56 (where $\tilde{e}_1 = D_2 - D_1$ and $\tilde{e}_2 = D_1 + D_2$, mapped to $\hat{e}_1 = \tilde{e}_2/\sqrt{3}$, $\hat{e}_2 = \tilde{e}_1$, $\hat{e}_3 = \tilde{e}_2/2$).

This definition—which uses the simple difference $D_3 - D_1$ rather than an invariant-based deviatoric radius $\sqrt{2J_{2,D}}$—ensures that the calibration constants ($c_{p2} = 36$, $c_{p3} = 12$, etc.) obtained for the 2D model remain valid in 3D without re-calibration.

64.5 Isotropic 3D Tangent Matrix

The secant and tangent constitutive matrices use the standard isotropic form

$$\mathbf{C}(K,G) = \begin{pmatrix} \lambda+2\mu & \lambda & \lambda & 0 & 0 & 0 \\ \lambda & \lambda+2\mu & \lambda & 0 & 0 & 0 \\ \lambda & \lambda & \lambda+2\mu & 0 & 0 & 0 \\ 0 & 0 & 0 & G & 0 & 0 \\ 0 & 0 & 0 & 0 & G & 0 \\ 0 & 0 & 0 & 0 & 0 & G \end{pmatrix}, \quad \lambda = K - \tfrac{2}{3}G, \quad \mu = G. \tag{64.9}$$

Here K and G are the *secant* bulk and shear moduli from the fracturing algorithm (identical scalar formulas as in 2D) or the *consistent* (tangent) moduli K_c, G_c.

64.6 Mandel Rotation for the Cracked Tangent

In 2D, applying crack modifications to the tangent matrix requires only a 3×3 rotation. In 3D, the analogous transformation involves a 6×6 matrix whose construction requires careful handling of the engineering/tensor shear distinction.

64.6.1 Mandel Notation

The *Mandel* (or normalised Voigt) representation scales the shear components by $\sqrt{2}$:

$$\boldsymbol{\sigma}^M = (\sigma_{11},\ \sigma_{22},\ \sigma_{33},\ \sqrt{2}\,\sigma_{23},\ \sqrt{2}\,\sigma_{13},\ \sqrt{2}\,\sigma_{12})^T.$$

In this notation, a rotation $\mathbf{R} \in \mathrm{SO}(3)$ applied to a second-order tensor corresponds to an *orthogonal* 6×6 matrix $\mathbf{Q}$ acting on the Mandel vector:

$$\boldsymbol{\sigma}^M_{\text{rot}} = \mathbf{Q}\,\boldsymbol{\sigma}^M, \qquad \mathbf{Q}^{-1} = \mathbf{Q}^T.$$

The orthogonality $\mathbf{Q}^T\mathbf{Q} = \mathbf{I}$ is the key property that makes Mandel notation attractive: fourth-order tensor transformations reduce to simple matrix products.

64.6.2 Construction of the Mandel Rotation Matrix

Given a rotation matrix $\mathbf{R}$ whose rows are the basis vectors $(\mathbf{n}, \mathbf{t}_1, \mathbf{t}_2)$ of the local crack frame, the 6×6 Mandel rotation matrix has four blocks:

Normal–Normal block (3×3, upper-left):

$$Q_{ij} = R_{ij}^2, \qquad i,j \in \{0,1,2\}.$$

Normal–Shear block (3×3, upper-right): For shear index $s \leftrightarrow (a,b)$ with convention $3 \to (1,2)$, $4 \to (0,2)$, $5 \to (0,1)$:

$$Q_{i,\,s+3} = \sqrt{2}\,R_{i,a}\,R_{i,b}.$$

Shear–Normal block (3×3, lower-left):

$$Q_{s+3,\,j} = \sqrt{2}\,R_{a,j}\,R_{b,j}.$$

Shear–Shear block (3×3, lower-right):

$$Q_{s_1+3,\,s_2+3} = R_{a_1,a_2}\,R_{b_1,b_2} + R_{a_1,b_2}\,R_{b_1,a_2}.$$

64.6.3 Engineering–Mandel Conversion

Conversion between the engineering Voigt matrix $\mathbf{C}^{\text{eng}}$ and the Mandel matrix $\mathbf{C}^M$ is performed via a diagonal scaling matrix $\mathbf{D} = \text{diag}(1, 1, 1, \sqrt{2}, \sqrt{2}, \sqrt{2})$:

$$\mathbf{C}^M = \mathbf{D}\,\mathbf{C}^{\text{eng}}\,\mathbf{D}^{-1}. \tag{64.10}$$

64.6.4 Cracked Tangent Application

For each active crack i with normal $\mathbf{n}_i$:

1. Build an orthonormal basis $(\mathbf{n}, \mathbf{t}_1, \mathbf{t}_2)$.
2. Construct the rotation matrix $\mathbf{R}$ with rows $(\mathbf{n}, \mathbf{t}_1, \mathbf{t}_2)$.
3. Convert $\mathbf{C}^{\text{eng}}$ to Mandel: $\mathbf{C}^M = \mathbf{D}\mathbf{C}\mathbf{D}^{-1}$.
4. Rotate to crack-local frame: $\mathbf{C}^M_{\text{loc}} = \mathbf{Q}\,\mathbf{C}^M\,\mathbf{Q}^T$.
5. In the local frame, modify the $(0, 0)$ component (normal stiffness):

$$C^M_{\text{loc}}(0,0) \leftarrow \begin{cases} C_{\text{intact}} & \text{if crack closed,} \\ C_{ts} & \text{if in softening zone } (\varepsilon_{tp} \le \varepsilon_{nn} \le \varepsilon_{tu}), \\ \eta_N \cdot C_{\text{intact}} & \text{otherwise (fully open).} \end{cases}$$

   Decouple the normal row/column: $C^M(0, j) = C^M(j, 0) = 0$ for $j \neq 0$. Apply shear retention: $C^M(4, 4) \leftarrow \eta_S \cdot C^M(4, 4)$, $C^M(5, 5) \leftarrow \eta_S \cdot C^M(5, 5)$.

6. Rotate back: $\mathbf{C}^M = \mathbf{Q}^T\,\mathbf{C}^M_{\text{loc}}\,\mathbf{Q}$.
7. Convert back to engineering: $\mathbf{C}^{\text{eng}} = \mathbf{D}^{-1}\mathbf{C}^M\mathbf{D}$.

Multiple cracks are applied sequentially; each crack modifies the tangent produced by the previous one.

64.7 Crack Initiation in 3D

A new crack is initiated when the maximum principal stress direction exceeds the crack function envelope. The crack function uses the Menetréy–Willam form with the Lode angle θ from Eq. (64.4):

$$g(\sigma_o, \tau_o, \theta) = \tau_o - \frac{0.944\, f'_c}{w(e, \theta)} \left(t_p - \frac{\sigma_o}{f'_c}\right)^{0.724}, \tag{64.11}$$

where $w(e, \theta)$ is the polar radius of an elliptic deviatoric cross-section:

$$w(e, \theta) = \frac{4(1 - e^2)\cos^2\theta + (2e - 1)^2}{2(1 - e^2)\cos\theta + (2e - 1)\sqrt{4(1 - e^2)\cos^2\theta + 5e^2 - 4e}},$$

and the eccentricity e depends on the current stress state:

$$e = 0.670551 \left(t_p - \frac{\sigma_o}{f'_c}\right)^{0.133}. \tag{64.12}$$

A crack initiates when $g > 0$. Its normal is the eigenvector corresponding to the largest principal stress. Additional cracks are orthogonalised:

- The second crack normal is projected to lie in the plane perpendicular to the first crack normal.
- The third crack normal is computed as the cross product of the first two normals.

This guarantees a mutually orthogonal set of up to three crack planes in 3D.

64.8 Plasticity Return Mapping

The plasticity algorithm operates on the same three yield surfaces as the 2D model (hydrostatic, uniaxial, biaxial), defined in the compression coordinate space of Section 64.4:

$$f_1 = \hat{e}_1 - f'_c\, f_{p1}(\bar{\varepsilon}_1^p), \tag{64.13}$$
$$f_2 = \hat{e}_2 - f'_c\, f_{p2}(\bar{\varepsilon}_2^p), \tag{64.14}$$
$$f_3 = \hat{e}_3 - f'_c\, f_{p3}(\bar{\varepsilon}_3^p). \tag{64.15}$$

The failure curves f_{p1}, f_{p2}, f_{p3} and their derivatives are identical to those in 2D (Chapter 56, Section "Yield Functions").

64.8.1 Back-Transform: Compression Coordinates to Global Voigt

The Newton iteration produces plastic multiplier increments $\Delta\lambda_1$ (hydrostatic), $\Delta\lambda_2$ (deviatoric), and $\Delta\lambda_3$ (biaxial; only updates the hardening variable $\bar{\varepsilon}_3^p$, no plastic flow).

The back-transform from compression coordinates to principal plastic strain increments is:

$$\Delta\varepsilon_1^p = -\left(\frac{\Delta\lambda_1}{\sqrt{3}} - \frac{\Delta\lambda_2}{2}\right), \tag{64.16}$$
$$\Delta\varepsilon_2^p = -\frac{\Delta\lambda_1}{\sqrt{3}}, \tag{64.17}$$
$$\Delta\varepsilon_3^p = -\left(\frac{\Delta\lambda_1}{\sqrt{3}} + \frac{\Delta\lambda_2}{2}\right). \tag{64.18}$$

This is the natural 3D extension of the 2D back-transform: the volumetric contribution $\Delta\lambda_1/\sqrt{3}$ is shared equally among all three principal directions, while the deviatoric contribution $\pm\Delta\lambda_2/2$ is added to the extreme directions (D_1 and D_3) symmetrically.

Principal to global. The principal plastic strain increment tensor $\Delta\varepsilon^p_{\text{princ}} = \text{diag}(\Delta\varepsilon_1^p, \Delta\varepsilon_2^p, \Delta\varepsilon_3^p)$ is rotated to the global frame using the eigenvector matrix $\mathbf{V}$:

$$\Delta\boldsymbol{\varepsilon}^p_{\text{global}} = \mathbf{V}^T \cdot \Delta\boldsymbol{\varepsilon}^p_{\text{princ}} \cdot \mathbf{V},$$

and the resulting tensor is mapped to Voigt form (with engineering shear $\gamma_{ij} = 2\varepsilon_{ij}$).

64.9 Full Algorithm

The 3D evaluation follows the same eight-step structure as the 2D model (Table 1 in [**?**]), with the dimensional extensions described above:

1. Elastic strain: $\boldsymbol{\varepsilon}^e = \boldsymbol{\varepsilon} - \boldsymbol{\varepsilon}^p$.
2. Principal decomposition of $\boldsymbol{\varepsilon}^e$ (eigenvalues + eigenvectors).
3. Fracture moduli K_s, G_s, σ_{id} from history ($\sigma_{o,\max}$, $\tau_{o,\max}$).
4. Secant stress: $\boldsymbol{\sigma} = \mathbf{C}(K_s, G_s)\,\boldsymbol{\varepsilon}^e - \sigma_{id}\,\boldsymbol{\delta}$.
5. Update fracture history (track envelope of σ_o, τ_o).
6. Cracking check: evaluate crack function (64.11); if $g > 0$ and fewer than 3 cracks exist, initiate new crack with orthogonality enforcement.
7. Update crack opening strains $\varepsilon_{nn,i}$; apply cracked tangent (Section 64.6); recompute stress.
8. Plasticity return mapping (Section 64.8); update $\boldsymbol{\varepsilon}^p$ and recalculate equilibrium stress.

64.10 Integration with the Sub-Model Solver

The 3D model is integrated into the multiscale sub-model solver chain through the `fall_n` type-erasure infrastructure:

```
InelasticMaterial<KoBatheConcrete3D> mat_inst{fc_MPa};
Material<ThreeDimensionalMaterial> mat{mat_inst, InelasticUpdate{}};
Model<ThreeDimensionalMaterial, SmallStrain, 3> M{domain, mat};
```

Here `InelasticMaterial<R>` is a type alias for `MaterialInstance<R, CommittedState>`, which wraps the constitutive relation `R` in an algorithmic state holder that provides the `commit()` / `revert()` interface required by the Newton–Raphson solver.

64.10.1 Operator-Splitting Crack Check

A critical convergence issue arises from the sharp transition between *uncracked* ($\mathbf{C} = \mathbf{C}_e$) and *cracked* ($\mathbf{C} = \eta_N \, \mathbf{C}_e$) tangent stiffness. When several Gauss points are near the crack-initiation threshold, the standard Newton procedure oscillates: an element cracks → stress drops → Newton update reverses the strain → element un-cracks → stress rises → element cracks again. This creates a non-convergent 2-cycle that no amount of damping, line-search tuning, or bisection can resolve.

The `evaluate()` function is pure-functional (copies the committed state and returns a modified copy without mutating the input), so the oscillation is between consistent but *different* branches of the stress function at each iteration—not from state mutation.

The fix is an *operator splitting* strategy: the `check_new_cracks` flag (default `true`) in `evaluate()` gates the crack-initiation check (Step 7). During Newton iterations, `compute_response()` and `tangent()` pass `false`; only `commit()` passes `true`. This means:

- During Newton iterations: the stress function $\boldsymbol{\sigma}(\boldsymbol{\varepsilon})$ is smooth—it uses only the *committed* crack state (no new cracks form). Newton converges reliably.
- At commit time: `evaluate()` runs with full crack checking, propagating any new cracks into the committed state.
- The next load step begins from the updated state, and Newton iteration proceeds smoothly again.

64.10.2 PETSc Solver Configuration

The sub-model solver uses incremental displacement control with 20 steps and 8 levels of recursive bisection:

```
PetscOptionsSetValue(nullptr, "-snes_linesearch_type", "basic");
PetscOptionsSetValue(nullptr, "-snes_max_it", "50");
PetscOptionsSetValue(nullptr, "-ksp_type", "preonly");
PetscOptionsSetValue(nullptr, "-pc_type", "lu");
constexpr int NUM_STEPS  = 20;
constexpr int MAX_BISECT = 8;
```

Key design choices:

- **Basic line search** (no backtracking): the committed-crack tangent still creates piecewise-smooth residuals that confuse the backtracking line search (PETSc reason $-6 =$ `SNES_DIVERGED_LINE_SEA` in v3.24). Basic line search takes the full Newton step and relies on the operator-splitting smoothness for convergence.
- **Direct LU**: always succeeds for the sub-model problem size (∼1350 DOFs).

- **20 steps with bisection**: each step imposes $\Delta p = 0.05$. At each commit boundary new cracks form, and the next step starts from a well-defined state.

64.11 Test Suite

The test file `tests/test_ko_bathe_concrete_3d.cpp` validates 23 checks across 10 test groups:

1. **Concept satisfaction** (3 compile-time `static_asserts`).
2. **3D elastic response**: tangent symmetry, positive diagonal, correct σ_{xx}, σ_{yy} for uniaxial strain.
3. **Uniaxial compression** curves for $f'_c = 21$ and 30 MPa (CSV export); peak stress within calibration bounds.
4. **Triaxial compression**: confinement increases peak mean stress beyond f'_c.
5. **Tension cracking**: positive peak tensile stress $\leq 2f_t$; crack normal aligned with the tension direction; 1 crack formed.
6. **Mandel rotation orthogonality**: hydrostatic strain produces equal normal stresses and vanishing shear.
7. **Biaxial compression**: enhanced strength beyond $0.5\, f'_c$.
8. **Commit cycle consistency**: external-state and internal-state evaluation paths produce identical stresses.
9. **Pure shear**: positive τ_{xy}, normal stresses ≈ 0.
10. **3D vs. 2D consistency**: uniaxial stress path comparison; maximum stress deviation within 50% of f'_c.

All 23/23 checks pass. The CSV output for the uniaxial compression curves allows visual comparison with the 2D model and the reference paper [**?**].

64.12 Discussion

Compression coordinate choice. An early implementation used $\hat{e}_2 = \sqrt{2\, J_{2,D}}$ (the deviatoric radius of the compressive strain vector $\mathbf{D}$) as a more "invariant-based" extension. However, this yields $\hat{e}_2 \approx 0.82\, \varepsilon_c$ under uniaxial compression (versus $\hat{e}_2 = \varepsilon_c$ with the current definition), delaying plasticity activation and producing peak stresses $\sim 3\times f'_c$. The direct difference $D_3 - D_1$ preserves consistency with the original 2D calibration constants.

Tangent conditioning and stiffness retention. The cracked tangent features stiffness retention factors $\eta_N = 0.20$ (normal) and $\eta_S = 0.50$ (shear), significantly larger than the 2D counterparts (10^{-4} and 0.1). The higher values improve SNES convergence without significantly affecting the structural response, since the sub-model elements are small ($\sim$10 cm) and the global behaviour is governed by the beam kinematics at the structural scale.

Newton convergence and operator splitting. The "pure-functional" design of `evaluate()` introduces a subtle convergence pathology. Because `compute_response()` always starts from the *committed* state (before the current load step), each Newton iteration re-evaluates the stress without memory of what happened in the previous iteration. Near the cracking threshold, this creates a non-convergent 2-cycle: trial strain crosses the threshold → crack forms (in the local copy) → stress drops → Newton update reverses the strain → no crack forms → stress rises → cycle repeats.

This 2-cycle manifests as PETSc convergence reason -6 (`SNES_DIVERGED_LINE_SEARCH` in v3.24, *not* `SNES_DIVERGED_LINEAR_SOLVE`, which is reason -3). The backtracking line search fails because the residual oscillates rather than decreasing monotonically.

The fix is operator splitting: the flag `check_new_cracks = false` is passed during Newton iterations (via `compute_response` and `tangent`), while `commit()` calls with `true` to allow new cracks to form only after convergence. Combined with the basic (full-step) line search, typical sub-model solves converge in 3–34 SNES iterations per load increment, with occasional bisections near $p \approx 0.95$.

Mandel vs. engineering Voigt. The Mandel notation transformation is central to the 3D cracked tangent. Using engineering Voigt directly would require separate transformation matrices for stress and strain ($\mathbf{T}_\sigma \neq \mathbf{T}_\varepsilon$), and the product $\mathbf{C}_{\text{rot}} = \mathbf{T}_\sigma^{-1}\,\mathbf{C}_{\text{loc}}\,\mathbf{T}_\varepsilon$ loses the symmetry guarantee. Mandel notation avoids this by ensuring $\mathbf{Q}^{-1} = \mathbf{Q}^T$, so that $\mathbf{C}_{\text{rot}}^M = \mathbf{Q}^T\,\mathbf{C}_{\text{loc}}^M\,\mathbf{Q}$ is symmetric whenever $\mathbf{C}_{\text{loc}}^M$ is.

Chapter 65

TrussElement: Embedded Rebar for Continuum Sub-Models

65.1 Motivation

The multiscale framework described in Chapter 63 extracts prismatic sub-model volumes around beam–column joints that exhibited yielding in the global structural analysis. These sub-models are discretised with hexahedral continuum elements and analysed with the Ko–Bathe concrete model (Chapter 64). However, a realistic concrete sub-model must include steel reinforcement.

Rather than modelling rebar with continuum elements (which would require extremely fine meshes), the standard approach in computational mechanics is to embed one-dimensional *truss* elements within the continuum mesh. When truss nodes coincide with hex element nodes, the two element types share degrees of freedom through the DMPlex sieve automatically—this is the **perfect-bond assumption**.

This chapter describes the implementation of a templated `TrussElement<Dim>` that:

- Models axial-only behaviour with a uniaxial constitutive law (e.g., Menegotto–Pinto steel),
- Integrates with the existing `FiniteElement` concept,
- Can be mixed with continuum elements in the same `Model` via `MultiElementPolicy` and `FEM_Element`,
- Supports both 2D and 3D spatial dimensions.

65.2 Formulation

65.2.1 Kinematics

Consider a bar element connecting nodes 0 and 1 with position vectors $\mathbf{x}_0$ and $\mathbf{x}_1$ in $\mathbb{R}^{\mathrm{Dim}}$. Define:

$$L = \|\mathbf{x}_1 - \mathbf{x}_0\|, \qquad \hat{\mathbf{e}} = \frac{\mathbf{x}_1 - \mathbf{x}_0}{L}, \tag{65.1}$$

where L is the element length and $\hat{\mathbf{e}}$ the unit direction vector. For 3D, $\hat{\mathbf{e}} = (\ell, m, n)^T$ with $\ell = \cos\alpha_x$, $m = \cos\alpha_y$, $n = \cos\alpha_z$ being the direction cosines.

The element has $2\,\mathtt{Dim}$ translational DOFs arranged as:

$$\mathbf{u}_e = (\mathbf{u}_0^T,\ \mathbf{u}_1^T)^T \in \mathbb{R}^{2\,\mathrm{Dim}}. \tag{65.2}$$

The axial strain is the projection of the displacement gradient onto the element axis:

$$\varepsilon = \hat{\mathbf{e}} \cdot \frac{\mathbf{u}_1 - \mathbf{u}_0}{L} = \mathbf{B}\,\mathbf{u}_e, \tag{65.3}$$

where the $1 \times 2\,\mathrm{Dim}$ strain–displacement matrix is:

$$\mathbf{B} = \frac{1}{L}\begin{pmatrix} -\hat{\mathbf{e}}^T & \hat{\mathbf{e}}^T \end{pmatrix} = \frac{1}{L}\begin{pmatrix} -\ell & -m & -n & \ell & m & n \end{pmatrix}. \tag{65.4}$$

Because the shape functions are linear, $\mathbf{B}$ is constant over the element—there is no spatial variation. A single Gauss point therefore integrates all element integrals exactly.

65.2.2 Stiffness Matrix

The element stiffness follows from the virtual work principle. With cross-sectional area A and elastic modulus E:

$$\mathbf{K}_e = A \int_0^L \mathbf{B}^T E\, \mathbf{B}\, \mathrm{d}x = A \cdot L \cdot E \cdot \mathbf{B}^T\mathbf{B}. \tag{65.5}$$

The integration factor $w \cdot |J| = L$ comes from the single-point Gauss rule on the reference interval $[-1, 1]$ with weight $w = 2$ and Jacobian $|J| = L/2$.

Expanding $\mathbf{B}^T\mathbf{B}$ for 3D:

$$\mathbf{K}_e = \frac{EA}{L}\begin{pmatrix} \hat{\mathbf{e}}\hat{\mathbf{e}}^T & -\hat{\mathbf{e}}\hat{\mathbf{e}}^T \\ -\hat{\mathbf{e}}\hat{\mathbf{e}}^T & \hat{\mathbf{e}}\hat{\mathbf{e}}^T \end{pmatrix}, \tag{65.6}$$

where $\hat{\mathbf{e}}\hat{\mathbf{e}}^T$ is the $\mathrm{Dim} \times \mathrm{Dim}$ projection operator onto the element axis. For an element aligned with the x-axis ($\hat{\mathbf{e}} = (1, 0, 0)^T$), only the K_{00}, K_{03}, K_{30}, K_{33} entries are non-zero.

65.2.3 Internal Forces

Given the current displacement $\mathbf{u}_e$, the internal force vector is:

$$\mathbf{f}_e = A \cdot L \cdot \sigma(\varepsilon) \cdot \mathbf{B}^T, \tag{65.7}$$

where $\sigma(\varepsilon)$ is the uniaxial stress computed by the constitutive model at the current strain $\varepsilon = \mathbf{B}\,\mathbf{u}_e$.

65.2.4 Tangent Stiffness

The consistent tangent stiffness for nonlinear material behaviour:

$$\mathbf{K}_t = A \cdot L \cdot E_t(\varepsilon) \cdot \mathbf{B}^T\mathbf{B}, \tag{65.8}$$

where $E_t = \partial\sigma/\partial\varepsilon$ is the algorithmic tangent modulus returned by the material model.

65.2.5 Mass Matrix

The consistent mass matrix for a 2-node bar with density ρ:

$$\mathbf{M}_e = \frac{\rho AL}{6}\begin{pmatrix} 2\mathbf{I} & \mathbf{I} \\ \mathbf{I} & 2\mathbf{I} \end{pmatrix}, \tag{65.9}$$

where $\mathbf{I}$ is the $\mathrm{Dim} \times \mathrm{Dim}$ identity matrix. This gives lumped entries $\rho AL/3$ on the diagonal and coupling terms $\rho AL/6$ on the off-diagonal blocks.

65.3 Implementation

The element resides in a single header file, `src/elements/TrussElement.hh` (∼230 lines), and is templated on the spatial dimension:

```
template <std::size_t Dim = 3>
class TrussElement {
    static_assert(Dim == 2 || Dim == 3);

    ElementGeometry<Dim>*       geometry_;
    Material<UniaxialMaterial> material_;  // 1 GP
    double                      area_;
    double                      L_;
    BMatrixT                    B_;        // precomputed (1 x 2*Dim)
    // ...
};
```

Key design decisions:

1. **Precomputed B-matrix.** Since $\mathbf{B}$ is constant for a 2-node element, it is computed once in the constructor from nodal coordinates and reused in all subsequent assembly calls. This avoids repeated geometry queries during nonlinear iterations.

2. **Direct `Material<UniaxialMaterial>` storage.** The element stores a type-erased uniaxial material handle directly, bypassing the `MaterialPoint` wrapper. This is necessary because `MaterialPoint` binds a material to an `IntegrationPoint<dim>` where `dim` is the *spatial* dimension—but the truss element lives in 3D space while its constitutive response is 1D.

3. **DOF cache pattern.** Following the same lazy-initialisation pattern as `ContinuumElement`, DOF indices are gathered from the `ElementGeometry` nodes on first use and cached for subsequent PETSc assembly calls.

4. **Concept satisfaction.** A `static_assert` at file scope verifies that both `TrussElement<3>` and `TrussElement<2>` satisfy the `FiniteElement` concept (Section 65.3.1).

65.3.1 FiniteElement Concept Compliance

The `FiniteElement` concept requires:

Method	ContinuumElement	TrussElement
`num_nodes()`	n (8, 20, ...)	2
`num_integration_points()`	n_{gp}	1
`sieve_id()`	from geometry	from geometry
`set_num_dof_in_nodes()`	Dim per node	Dim per node
`inject_K(Mat)`	$\int \mathbf{B}^T\mathbf{D}\mathbf{B}\, dV$	$ALE\, \mathbf{B}^T\mathbf{B}$
`compute_internal_forces(Vec,Vec)`	$\int \mathbf{B}^T\boldsymbol{\sigma}\, dV$	$AL\sigma\, \mathbf{B}^T$
`inject_tangent_stiffness(Vec,Mat)`	$\int \mathbf{B}^T\mathbf{D}_t\mathbf{B}\, dV$	$ALE_t\, \mathbf{B}^T\mathbf{B}$
`commit_material_state(Vec)`	per GP	single GP
`revert_material_state()`	per GP	single GP

The truss element assembles into the same global PETSc matrices via `MatSetValuesLocal` and `VecSetValues`, interoperating seamlessly with continuum elements in a mixed-topology model.

65.3.2 Integration with Mixed-Topology Models

When truss elements coexist with hex elements in the same DMPlex mesh, the model must use `MultiElementPolicy` (heterogeneous element storage via type-erased `FEM_Element` wrappers):

```
// Wrap both element types in FEM_Element
std::vector<FEM_Element> elements;
for (auto& hex : hex_elements)
    elements.emplace_back(std::move(hex));
for (auto& truss : truss_elements)
    elements.emplace_back(std::move(truss));

// Constructor 2: pre-built element vector
Model<MultiElementPolicy> model(domain, std::move(elements));
```

DOF coupling requires that truss nodes coincide with hex nodes in the DMPlex sieve. The `PrismaticDomainBuilder` generates the hex mesh with node positions at regular grid points; rebar elements are created by connecting pairs of these shared nodes along rebar paths.

65.4 Verification

A comprehensive unit test suite (`tests/test_truss_element.cpp`, ∼600 lines, 26 assertions) validates the implementation against analytical solutions.

65.4.1 Test Material

All tests use a Menegotto–Pinto steel model with very high yield stress ($f_y = 10^{12}$ MPa) to ensure purely elastic behaviour during verification:

$$E = 200\,000 \text{ MPa}, \quad f_y = 10^{12} \text{ MPa}, \quad b = 0.01. \tag{65.10}$$

Within the elastic range, $\sigma = E\varepsilon$ and $E_t = E$, giving analytically predictable stiffness and force values.

65.4.2 Geometry Tests

X-aligned bar (nodes at $(0, 0, 0)$ and $(2, 0, 0)$):

- `num_nodes` $= 2$, `num_integration_points` $= 1$.
- $L = 2.0$.

Diagonal bar (nodes at $(0, 0, 0)$ and $(1, 1, 1)$):

- $L = \sqrt{3}$.

65.4.3 Stiffness Tests

X-aligned bar ($A = 0.01$, $E = 200\,000$, $L = 2$):

$$\frac{EA}{L} = \frac{200\,000 \times 0.01}{2} = 1000. \tag{65.11}$$

Verified entries: $K_{00} = +1000$, $K_{03} = -1000$, $K_{33} = +1000$, $K_{11} = 0$ (transverse), $K_{22} = 0$ (transverse).

Diagonal bar ($\hat{\mathbf{e}} = (1/\sqrt{3},\, 1/\sqrt{3},\, 0)^T$ for a bar from origin to $(1, 1, 0, 0)$... actually $(1, 1, 1)$ with $\cos^2\alpha = 1/3$):

$$K_{00} = \frac{EA}{L}\cos^2\alpha = \frac{EA}{L}\cdot\frac{1}{3}, \quad K_{01} = \frac{EA}{L}\cos\alpha\cos\beta = \frac{EA}{L}\cdot\frac{1}{3}. \tag{65.12}$$

65.4.4 Internal Force Test

Imposing $\delta = 0.002$ axial elongation on the x-aligned bar:

$$\varepsilon = \frac{\delta}{L} = 0.001, \quad \sigma = E\varepsilon = 200, \quad F = \sigma A = 2.0 \text{ force units.} \tag{65.13}$$

Verified: $f_0 = -F$, $f_3 = +F$, $f_1 = f_4 = 0$.

65.4.5 Additional Tests

- **Tangent consistency**: $\mathbf{K}_t(\mathbf{u} = \mathbf{0}) = \mathbf{K}$ for elastic material (all 6×6 entries).
- **Commit/revert**: Material state after commit preserves strain; revert returns to last committed state.
- **FEM_Element wrapping**: `TrussElement<3>` wraps successfully in `FEM_Element` with preserved topology queries (`num_nodes`, `num_gp`, `sieve_id`).
- **Mass matrix**: Diagonal entries $M_{00} = 2\rho AL/6$, off-diagonal $M_{03} = \rho AL/6$, cross-direction $M_{01} = 0$.

All 26 assertions pass.

65.5 Discussion

The `TrussElement` completes the element infrastructure needed for reinforced concrete sub-models. With the concrete continuum modelled by hexahedral elements using `KoBatheConcrete3D` (Chapter 64) and steel reinforcement modelled by truss elements using `MenegottoPintoSteel`, the sub-model solver can now represent the composite behaviour of confined concrete with embedded rebar.

The **perfect-bond assumption** (shared nodes) is appropriate for well-confined regions typical of beam–column joints, where bond slip is negligible under monotonic and low-cycle fatigue loading.

The next step is integrating the `TrussElement` into the `SubModelSolver` (Chapter 63), which requires:

1. A rebar mesh generator that creates line elements sharing nodes with the hex mesh inside the prismatic sub-model volume.
2. Switching the model policy from `SingleElementPolicy` to `MultiElementPolicy`.
3. Assigning distinct materials: `KoBatheConcrete3D` for hex elements and `MenegottoPintoSteel` for truss elements.

Chapter 66

Reinforced Sub-Model Integration

Chapters 64 and 65 developed the two key ingredients for modelling reinforced-concrete prismatic sub-models: the Ko–Bathe three-dimensional concrete constitutive model and the `TrussElement<Dim>` embedded rebar element. This chapter describes how these are assembled into a unified sub-model solver via `MultiElementPolicy`, the reaction-force-based effective-modulus extraction, and a critical bug fix in the incremental analysis engine that affected all displacement-controlled nonlinear analyses with more than one load step.

66.1 Heterogeneous Element Assembly

A reinforced sub-model contains two distinct element types:

1. **Hex8 continuum elements** (`ContinuumElement<ThreeDimensionalMaterial, 3, SmallStrain>`) with the Ko–Bathe concrete law, discretising the concrete volume.
2. **Line2 truss elements** (`TrussElement<3>`) with a Menegotto–Pinto steel law, discretising longitudinal rebars.

Both element families share the same `Domain<3>` and the same DMPlex sieve. Truss elements connect pairs of hex nodes along the z-axis using `Line2` topology; because their nodes coincide with hex vertices, the perfect-bond assumption is enforced automatically through the shared degrees of freedom.

The heterogeneous collection is stored in a `std::vector<FEM_Element>` and managed by `MultiElementPolicy`, which erases element types behind the `FiniteElement` interface. The model is constructed with Constructor 2:

```
Model<Policy, SmallStrain, 3, MultiElementPolicy>
    M{sub.domain, std::move(all_elements)};
```

66.2 Domain Builder

The helper `make_reinforced_prismatic_domain()` in `PrismaticDomainBuilder.hh` extends the hex-only prismatic builder with embedded rebar:

1. Build the base prismatic hex mesh (nodes and `Hex8` cells).
2. For each bar in the `RebarSpec`, compute the grid indices (i_x, i_y) closest to the bar's cross-section position.
3. Create one `Line2` element per rebar segment between consecutive z-layers, reusing existing node IDs.

4. Return a `ReinforcedDomainResult` containing the domain, the grid, and a `RebarElementRange` that separates hex element indices $[0, n_{\text{hex}})$ from truss indices $[n_{\text{hex}}, n_{\text{total}})$.

Because the truss elements share hex nodes, the total node count is unchanged—only the element count grows.

66.3 Reaction-Based Effective Modulus

With `MultiElementPolicy`, the type-erased `FEM_Element` does not expose `material_points()`, so volume-averaged stress/strain extraction is not directly available. Instead, `solve_reinforced()` computes effective moduli from boundary reactions.

After the incremental nonlinear solve converges at $p = 1$, internal forces $\mathbf{f}_{\text{int}}$ are reassembled from the converged state vector. The z-component of the resultant reaction at the max-z face gives the axial force:

$$F_z = \sum_{i \in \mathcal{N}_{\max z}} f_{\text{int},z}^{(i)}, \qquad \sigma_{zz}^{\text{eff}} = \frac{F_z}{A}, \qquad E_{\text{eff}} = \frac{\sigma_{zz}^{\text{eff}}}{\varepsilon_{zz}^{\text{avg}}}, \tag{66.1}$$

where $A = w \times h$ is the cross-section area and $\varepsilon_{zz}^{\text{avg}} = \bar{u}_z^{\max z}/L$ is the average imposed strain.

66.4 Bug Fix: State Vector Accumulation in Incremental Solve

During the integration testing, the computed E_{eff} was found to be approximately 20× higher than the expected value of ∼28,500 MPa for fc = 30 concrete. Detailed diagnostics revealed that the model state vector at constrained (Dirichlet) nodes accumulated imposed displacements across all load increments, rather than reflecting only the final converged state.

66.4.1 Root Cause

The `commit_state()` method in `NonlinearAnalysis` updated the model's state vector as:

```
DMGlobalToLocal(dm, U, INSERT_VALUES, model_->state_vector());
VecAXPY(model_->state_vector(), 1.0, model_->imposed_solution());
```

PETSc's `DMGlobalToLocal` with `INSERT_VALUES` populates free-DOF entries from the global vector U but *does not touch* constrained entries—they retain whatever value was already stored. At each of the N incremental steps, `VecAXPY` adds $p_k \cdot u_{\text{imposed}}$ to the untouched constrained entries, producing a cumulative sum:

$$u_{\text{state}}^{(N)} = \sum_{k=1}^{N} p_k \cdot u_{\text{imposed}} = u_{\text{imposed}} \sum_{k=1}^{N} \frac{k}{N} = u_{\text{imposed}} \cdot \frac{N+1}{2}. \tag{66.2}$$

For $N = 20$ steps this gives a factor of 10.5×, exactly matching the observed displacement amplification ($u_{\text{state}} = 0.00105$ vs. $u_{\text{imposed}} = 0.0001$).

66.4.2 Fix

The fix is a single-line addition of `VecSet(model_->state_vector(), 0.0)` before the `DMGlobalToLocal` call:

```
VecSet(model_->state_vector(), 0.0);
DMGlobalToLocal(dm, U, INSERT_VALUES, model_->state_vector());
VecAXPY(model_->state_vector(), 1.0, model_->imposed_solution());
```

This ensures constrained entries start from zero at each commit, so the final state is exactly $0 + u_{\text{imposed}}$ as intended.

The same defensive zero-fill was applied to `DynamicAnalysis` and `LinearAnalysis` for consistency, even though those code paths were not affected in practice (they call the update only once, not in a loop).

66.4.3 Scope of Impact

The bug affected *any* incremental displacement-controlled nonlinear solve that:

- Used more than one load step ($N > 1$), **and**
- Read the model's `state_vector()` at constrained nodes after the solve (e.g., for reaction-force computation or post-processing).

The SNES convergence was *not* affected—the residual evaluation in `FormResidual` correctly zeroed its local vector before `DMGlobalToLocal`. Only the post-solve state vector used for post-processing was corrupted. This explains why the solver "converged" but the extracted reactions were wrong.

Note that the original `SubModelSolver::solve()` method extracted effective moduli from volume-averaged Gauss-point stresses (not from the state vector at constrained nodes), and therefore was not affected by this bug.

66.5 Validation

The integration test `test_reinforced_submodel.cpp` exercises the full pipeline with a $0.30 \times 0.30 \times 1.00$ m prismatic volume ($n_x = 2$, $n_y = 2$, $n_z = 4$), $f'_c = 30$ MPa concrete, and an imposed axial strain of $\varepsilon = 10^{-4}$.

Unreinforced case. With empty rebar, `solve_reinforced()` returns $E_{\text{eff}} = 28{,}420$ MPa, matching the analytical value $E_e \approx 28{,}513$ MPa from the Ko–Bathe elastic parameters ($K_e = 11{,}096$, $G_e = 13{,}304$, $E_e = 9K_eG_e/(3K_e + G_e)$) to within 0.3%.

Reinforced case. A single 16mm-equivalent rebar ($A_s = 0.0002$ m^2, $\rho = A_s/A = 0.22\%$) with $E_s = 200{,}000$ MPa steel adds $\Delta E \approx \rho \cdot E_s \approx 444$ MPa. The measured $E_{\text{eff}} = 28{,}865$ MPa gives $\Delta E = 445$ MPa, in excellent agreement with the mixture rule.

All 14 assertions in Tests 1 and 2 pass, verifying:

- Domain construction with mixed hex/truss topology (7 checks),
- Convergence of both unreinforced and reinforced solves,
- Positive E_{eff} in the physical range [10,000, 50,000] MPa,
- Reinforced $E_{\text{eff}} >$ unreinforced (rebar adds stiffness),
- Reinforced $E_{\text{eff}} < 2\times$ unreinforced (small ρ).

66.6 VTK Gauss-Point Export for Heterogeneous Models

The standard VTK export path in `VTKModelExporter` relies on compile-time access to `material_points()` and `get_geometry()` on each element. These methods are part of the concrete element types (e.g., `ContinuumElement`) but are *not* exposed through the `FiniteElement` concept or the type-erased `FEM_Element` wrapper, since they are post-processing concerns intentionally excluded from the core interface.

When the model uses `MultiElementPolicy`, the element type seen by `VTKModelExporter` is `FEM_Element`, and the existing `if constexpr` guard on `material_points()` silently skips all Gauss-point field collection. To enable crack and stress visualisation for reinforced sub-models, three extensions were made.

66.6.1 GaussFieldRecord and Virtual Dispatch

A lightweight aggregate `GaussFieldRecord` was added to `InternalFieldSnapshot.hh`:

```
struct GaussFieldRecord {
    std::vector<double> stress;
    std::vector<double> strain;
    std::vector<double> pstrain_storage;  // owned copy
    InternalFieldSnapshot snapshot;
};
```

The virtual method `collect_gauss_fields(Vec u_local)` was added to `FEM_Element`'s polymorphic Concept/Model chain. `ContinuumElement` implements it by iterating its `material_points_`, evaluating the constitutive response at the current state, and returning one `GaussFieldRecord` per integration point. `TrussElement` inherits the default (empty vector), since truss Gauss data is not meaningful for field visualisation.

66.6.2 Type-Erased Fallback in VTKModelExporter

In `compute_material_fields()`, a new `else if constexpr` branch handles the case where `material_points()` is unavailable but `collect_gauss_fields()` is available (i.e., the `FEM_Element` path). This branch:

1. Calls `element.collect_gauss_fields(state_vector)` for each element.
2. Unpacks stress, strain, and `InternalFieldSnapshot` fields (crack normals, closure state, fracture history, damage, plastic strain) into the same flat buffers used by the direct path.
3. Registers all buffers as VTK point-data arrays on the Gauss cloud.

Elements that return an empty record vector (e.g., trusses) are zero-filled, preserving array alignment with the global integration-point count.

66.6.3 Gauss Displacement Interpolation Guard

The existing `interpolate_gauss_displacement_field()` method calls `element.get_geometry()` to obtain reference-coordinate shape functions for interpolating nodal displacement to Gauss points. Since `get_geometry()` is not available on `FEM_Element`, the function body was wrapped with:

```
if constexpr (!requires(const element_type& e) {
                    e.get_geometry(); }) {
    return {};
} else { /* original body */ }
```

When geometry is unavailable, the Gauss displacement field is simply omitted from the VTK output. The Warp-by-Vector filter in ParaView can still be applied to the mesh export, where nodal displacements are always available.

66.6.4 Buffer Alignment for Mixed-Element Models

The fallback branch iterates `model_->elements()` and collects Gauss-point records from each element. For elements that return an empty record vector (e.g., truss elements), the code zero-fills the strain and stress buffers using the element's `num_integration_points()`. However, for `TrussElement`, this method returns 1 (the number of material evaluation points), while the underlying `ElementGeometry` has 2 quadrature points—the count that determines the VTK Gauss cloud size.

This mismatch caused Gauss-point arrays to have fewer entries than the point cloud, making VTK's reader abort all arrays with the error "`The data array in the element may be too short`". The fix uses the domain geometry's integration-point count (`domain.element(i).num_integration_po` for zero-filling instead of the element's material-point count:

```
const auto ngp_geom =
    domain_elements[elem_idx].num_integration_points();
```

Additionally, optional field buffers (crack normals, fracture history, damage, plastic strain) are padded to the total integration-point count with zeros after the main collection loop, ensuring every VTK point-data array matches the cloud size.

66.6.5 3D Crack Normal Snapshot

The `make_internal_field_snapshot()` function in `Material.hh` originally hardcoded the z-component of crack normals to 0.0:

```
n1 = {alpha.crack_normals[0][0],
      alpha.crack_normals[0][1], 0.0};
```

For `KoBatheConcrete3D`, crack normals are `Eigen::Vector3d`, so the third component was silently dropped. The fix uses a compile-time dispatch:

```
using NormalT =
    std::remove_cvref_t<decltype(alpha.crack_normals[0])>;
if constexpr (NormalT::SizeAtCompileTime >= 3)
    n1 = {alpha.crack_normals[0][0],
          alpha.crack_normals[0][1],
          alpha.crack_normals[0][2]};
else
    n1 = {alpha.crack_normals[0][0],
          alpha.crack_normals[0][1], 0.0};
```

66.6.6 VTK Writer Correction

The utility function `write_vtu()` originally called both `writer->Update()` and `writer->Write()`. On some VTK builds, the combination caused the writer to re-open the file during the second call, truncating the closing `</VTKFile>` tag and producing an unreadable file. Removing the redundant `Update()` call (since `Write()` already triggers the pipeline) resolved the issue.

66.7 VTK Crack Export Validation

Test 3 in `test_reinforced_submodel.cpp` exercises the full VTK pipeline under tension ($\varepsilon = 5 \times 10^{-4}$, well above the cracking threshold $f_t/E_e \approx 5.6 \times 10^{-5}$ for $f'_c = 30$ MPa). After the incremental solve, a `VTKModelExporter` writes both a mesh VTU and a Gauss-point cloud VTU. The test reads back the Gauss cloud with `vtkXMLUnstructuredGridReader` and verifies:

- The cloud contains 136 Gauss points (16×8 hex plus 4×2 truss).

- Stress and strain tensor component fields are present (`qp_stress_xx`, `qp_strain_xx`, `qp_stress_von_mises`).
- Crack fields are present (`qp_num_cracks`, `qp_crack_normal_1`, `qp_crack_strain_1`, `qp_crack_closed_1`
- Fracture history fields are present (`qp_sigma_o_max`, `qp_tau_o_max`).
- Equivalent plastic strain is present.
- At least one Gauss point is cracked (observed: 128/136, i.e. all hex points develop cracks under the imposed tension).
- The mesh VTU file also exists.

All 30 assertions across the three sub-tests pass, bringing the total test count to 62.

Chapter 67

L-Shaped RC Building under Bidirectional Seismic Excitation

This chapter presents the first integrated exercise of the complete multiscale framework developed in Chapters 64–66: a four-story reinforced-concrete frame with an L-shaped plan and a vertical setback, subjected to the bidirectional strong-motion record of the 2011 Tōhoku earthquake (K-NET station MYG004, Tsukidate, Miyagi prefecture). The analysis proceeds in two phases:

1. **Phase 1 (global, nonlinear fiber model):** The complete building frame, including floor slabs, is analysed dynamically under simultaneous NS and EW earthquake components. A `MaxStrainDamageCriterion` monitors all fibered elements in real time and halts the analysis when the damage index reaches a prescribed threshold.

2. **Phase 2 (local, reinforced continuum sub-models):** The most damaged column elements are downscaled to three-dimensional continuum sub-models (hex8 concrete with KoBatheConcrete3D plus embedded truss rebar) and evolved through the remaining earthquake with continuously updated boundary conditions from the global kinematics.

The example is implemented in `main_lshaped_rc.cpp` and exercises the following infrastructure: building domain builder with cutout support, RC fiber sections, bidirectional ground-motion application, composite observers, damage-threshold transition director, prismatic domain builder with rebar, sub-model evolver, and VTK multi-block export.

67.1 Building Geometry

The building has a regular grid plan of 3×2 bays (3 bays in X, 2 bays in Y) with 4 stories at 3.2 m each, totalling 12.8 m in height for the lower wing. Table 67.1 summarises the grid coordinates.

Table 67.1: Grid coordinates of the L-shaped building.

Direction	Coordinates
X	0, 5, 10, 15 m (bays of 5 m)
Y	0, 6, 12 m (bays of 6 m)
Z	0, 3.2, 6.4, 9.6, 12.8 m (stories of 3.2 m)

An L-shaped plan with a height irregularity (*setback*) is achieved by removing the bay $[2, 3) \times [1, 2)$ above story 2. On the full grid, this corresponds to the upper-right corner ($X \in [10, 15]$ m,

$Y \in [6, 12]\,\mathrm{m}$) where all columns, beams and slabs are suppressed for stories 3 and 4. The resulting structure has:

- 58 nodes,
- 46 columns (reduced from the full-grid count because of the cutout),
- 64 beams,
- 22 floor slabs (MITC4 Mindlin–Reissner shell elements),

for a total of 132 structural elements. The complete grid is generated by `make_building_domain(FramedBuildi` with the `cutout_x_start`, `cutout_y_start`, `cutout_x_end`, `cutout_y_end`, and `cutout_above_story` fields.

The floor slabs are essential for a realistic mass distribution. Without them, the building mass derives solely from the self-weight of beams and columns, yielding unrealistically short fundamental periods (on the order of $T_1 \approx 0.04\,\mathrm{s}$) and negligible seismic response. Including the 150 mm-thick reinforced-concrete slabs ($\rho = 2.4\,\mathrm{MN{\cdot}s^2/m^4}$) provides the dominant floor mass and shifts T_1 to approximately 0.5 s, consistent with the empirical estimates for four-story RC frames.

67.2 Material Properties

67.2.1 Columns

Each column has a $0.45\,\mathrm{m} \times 0.45\,\mathrm{m}$ fibered cross-section built with `make_rc_column_section(RCColumnSpec)`. The concrete fibres use the Kent–Park model with $f'_c = 30\,\mathrm{MPa}$. The longitudinal steel bars ($\phi 22\,\mathrm{mm}$) follow the Menegotto–Pinto model ($f_y = 420\,\mathrm{MPa}$, $E_s = 200\,000\,\mathrm{MPa}$, $b = 0.01$), with a clear cover of 35 mm and tie spacing of 100 mm. The yield strain is

$$\varepsilon_y = \frac{f_y}{E_s} = \frac{420}{200\,000} = 0.0021\,. \tag{67.1}$$

67.2.2 Beams

Beams are $0.30\,\mathrm{m} \times 0.50\,\mathrm{m}$ with $f'_c = 25\,\mathrm{MPa}$ and $\phi 19\,\mathrm{mm}$ bars ($f_y = 420\,\mathrm{MPa}$).

67.2.3 Slabs

Floor slabs are modelled as elastic Mindlin–Reissner shells with thickness $t = 0.15\,\mathrm{m}$, $E = 25\,000\,\mathrm{MPa}$, and $\nu = 0.20$. Their primary role is to provide realistic floor mass ($\rho = 2.4 \times 10^{-3}\,\mathrm{MN{\cdot}s^2/m^4}$) and in-plane diaphragm action.

67.3 Earthquake Input

The input ground motion is the 2011 Tōhoku earthquake as recorded at K-NET station MYG004 (Tsukidate, Miyagi). This near-source record from the M_w 9.0 event features very high accelerations in both horizontal components.

Both components are loaded from K-NET format files using `GroundMotionRecord::from_knet()`, trimmed to the [30, 50] s window of strongest shaking, and applied simultaneously via two calls to `bcs.add_ground_motion()`, scaled by a factor of 1.50 to push the fiber strains beyond the damage threshold.

Table 67.2: Ground-motion record parameters (MYG004, Tōhoku 2011).

Parameter	NS $\to X$	EW $\to Y$
PGA (full record)	2764 gal	1268 gal
PGA (window)	1325 gal	977 gal
Original sampling	0.01 s	0.01 s
Window	[30, 50] s	
Duration (trimmed)	20 s	20 s
Scale factor	1.50	

67.4 Dynamic Analysis Setup

The analysis uses `DynamicAnalysis<TimoshenkoBeam3D, SmallStrain, 6, SingleElementPolicy<Structu` with the following settings:

- **Time integrator:** Generalised-α (TSAlpha2) with spectral radius $\rho_\infty = 0.9$.
- **Fixed time step:** $\Delta t = 0.02\,\mathrm{s}$ (adaptive substep disabled; sub-stepping occurs only through SNES failure recovery).
- **Rayleigh damping:** 5 % critical at $\omega_1 = 2\pi/0.50$ and $\omega_3 = 2\pi/0.10$.
- **SNES:** 100 max iterations, $r_{\mathrm{tol}} = 10^{-3}$, $a_{\mathrm{tol}} = 10^{-6}$, unlimited failure recovery (`TSSetMaxSNESFailures(-` causes PETSc to halve Δt on each divergence and retry).

The unlimited SNES failure policy with adaptive sub-stepping ensures robust convergence through the strong nonlinear response but at the cost of many small time steps (typical effective $\Delta t \sim 5 \times 10^{-4}\,\mathrm{s}$) during the peak shaking interval.

67.5 Observers and Transition Criterion

Two observers are composed using `make_composite_observer`:

1. **DamageTracker:** evaluates the `MaxStrainDamageCriterion` at each step and maintains a running maximum of the damage index $d = \varepsilon_{\max}/\varepsilon_y$.
2. **NodeRecorder:** records displacement components u_x and u_y at four roof-level nodes:
   - Node $(0, 0, \mathrm{roof})$: lower-left corner,
   - Node $(3, 0, \mathrm{roof})$: lower-right corner,
   - Node $(0, 2, \mathrm{roof})$: upper-left corner,
   - Node $(2, 2, \mathrm{roof})$: near the setback.

The **transition director** is created via `make_damage_threshold_director(damage_crit, 0.80)`, which halts the global analysis when any element's damage index $d \geq 0.80$ (i.e. the peak fiber strain reaches 80 % of the steel yield strain). This pre-yield threshold enables the multiscale pipeline to activate before full plastic-hinge formation.



Figure 67.1: Peak damage index evolution during Phase 1 (global fiber model, blue circles) and Phase 2 (reinforced continuum sub-models, red squares). The dashed line marks the transition threshold $d_{\text{thr}} = 0.80$.

67.6 Phase 1 Results

The global analysis runs under bidirectional excitation until the damage-index threshold of 0.80 is reached. Figure 67.1 traces the peak damage index (d) and peak fiber strain ($\varepsilon_{\max}$) versus simulation time.

The response is initially linear-elastic for $t < 10\,\text{s}$ (the first $\sim$10 s within the window correspond to the P-wave coda of the Tōhoku event at 40 s absolute time). A rapid jump in damage occurs around $t = 11\,\text{s}$ when the strong S-wave phases arrive. This is the critical interval where the damage index escalates from approximately 0.04 to above the 0.80 threshold within a few seconds.

At the transition instant:

- **Transition time:** $t_y = 15.2475\,\text{s}$ within the trimmed window (approximately 45.25 s in the original record).
- **Critical element:** element 11, a first-story column at the re-entrant corner of the L-shape, consistent with earthquake reconnaissance findings that re-entrant corners concentrate torsional and translational damage.
- **Damage threshold reached:** $d = 0.8001$, corresponding to a peak fiber strain of approximately 1.68×10^{-3}.
- **Peak displacements:** the global model reaches $|u|_\infty \approx 9$–$15\,\text{mm}$ during the nonlinear burst that precedes the transition.

67.7 Phase 2: Reinforced Continuum Sub-Models

67.7.1 Sub-Model Construction

After the Phase 1 transition, the up-to-4 most damaged column elements (with $d > 0.30$) are identified and downscaled to reinforced 3D continuum sub-models. Each sub-model is built as follows:

1. `align_to_beam()` extracts the prismatic geometry (axis, cross-section, length) of the damaged beam element.

2. `make_reinforced_prismatic_domain()` generates a $4 \times 4 \times 8$ hex8 mesh (128 elements) plus embedded truss rebar elements.

3. Eight rebar bars are placed in the cross-section (4 corner + 4 mid-face) with area $A_{\text{bar}} = \pi\phi^2/4 = 3.80 \times 10^{-4}\,\text{m}^2$ each ($\phi = 22\,\text{mm}$).

4. The concrete uses the Ko–Bathe model (Chapter 64) with the same $f'_c = 30\,\text{MPa}$ as the global columns.

5. The rebar steel follows the Menegotto–Pinto model with $f_y = 420\,\text{MPa}$, providing the ductile energy-dissipation mechanism.

Each sub-model has $128 + 64 = 192$ elements (hexahedral + truss) with rebar elements spanning element indices 128–191.

67.7.2 Sub-Model Evolution

Boundary conditions for each sub-model are extracted from the global displacement field at the transition time. The `SubModelEvolver` (extended with `set_rebar()` for reinforced mode) then drives each sub-model through the remaining earthquake ground-motion time steps, continuously interpolating BCs from the global nodal displacements at the sub-model boundaries.

For the production run documented here, the evolution phase is capped to 50 global steps and the sub-model boundary conditions are refreshed every 10 global steps. This keeps the example computationally tractable on a desktop workstation while still exercising reinforced downscaling, incremental nonlinear solves, and VTK time-series export.

VTK snapshots of each sub-model are exported at regular intervals (every 50 evolution steps), showing the three-dimensional stress and damage fields in the concrete together with the axial-stress state of the embedded rebar bars.

67.8 Roof Displacement Time Histories

The `NodeRecorder` writes the displacement histories at the four roof nodes to `roof_displacement.csv`. Each record contains $(t,\ u_x^{(0,0)},\ u_y^{(0,0)},\ u_x^{(3,0)},\ u_y^{(3,0)},\ u_x^{(0,2)},\ u_y^{(0,2)},\ u_x^{(2,2)},\ u_y^{(2,2)})$.

For the corrected production run, the largest roof amplitudes are of order 1 cm in the X direction and 6–7 mm in the Y direction. In particular, the node at $(3, 0, \text{roof})$ reaches $\max|u_x| = 10.52\,\text{mm}$ and $\max|u_y| = 6.22\,\text{mm}$, while the node at $(0, 2, \text{roof})$ reaches $\max|u_x| = 9.82\,\text{mm}$ and $\max|u_y| = 6.83\,\text{mm}$. At the end of the truncated run ($t = 15.2631\,\text{s}$), the roof retains a residual translation of roughly $-10.3\,\text{mm}$ in X at the right-hand edge nodes, confirming that the transition criterion is reached during a genuinely nonlinear drift state.

Figure 67.2 shows the four roof-node time histories in both horizontal directions, and Figure 67.3 visualises the displacement orbit at node $(3, 0)$ on the u_x–u_y plane, clearly showing the residual drift towards the bottom-left corner of the orbit at the end of the analysis.

The time histories reveal several characteristic features of bidirectional seismic response in an irregular building:

- **Torsional coupling:** the asymmetric mass and stiffness distribution of the L-plan causes significant torsional amplification. Roof nodes at the re-entrant corner (node $(2, 2)$) show larger u_x amplitudes than the far corner (node $(0, 0)$).

- **Bidirectional interaction:** the u_y and u_x histories are not independent—peak u_x typically coincides with significant u_y motion, reflecting the coupled frequency content of the NS and EW components.

- **Permanent drift:** after the strong shaking subsides, the building retains a residual drift consistent with the inelastic damage accumulated during Phase 1.



Figure 67.2: Roof displacement time histories at the four monitored nodes. Top: u_x (NS direction); bottom: u_y (EW direction). The abrupt amplitude growth around $t = 10\,\mathrm{s}$ corresponds to the arrival of the S-wave phase in the Tōhoku MYG004 record.



Figure 67.3: Displacement orbit at the roof node $(3, 0)$ showing bidirectional coupling and the residual drift ($\approx -10\,\mathrm{mm}$ in u_x) at the end of the analysis.

67.9 Implementation Notes

67.9.1 CompositeObserver Pattern

The global solver requires a single observer. Because both the `DamageTracker` and `NodeRecorder` must observe each time step, we use `make_composite_observer<StructModel>(std::move(dt), std::move(rec))`. Individual observers are then accessed via `composite_obs.get<0>()` and `composite_obs.get<1>()`.

An earlier attempt using `std::ref()` wrappers failed because `std::reference_wrapper<T>` does not itself expose the observer interface (`on_step`, `on_analysis_start`, etc.). The solution is to *move* observers into the composite and keep references to the originals via `get<N>()`.

67.9.2 Manual-Stepping Observer Fix

During implementation, the roof-displacement recorder initially produced either no samples or non-physical floating-point garbage. Two issues caused this behaviour:

1. **Manual stepping via `TSStep()`:** the example advances the TS integrator through `step_to()` and `step_n()`, not only through a monolithic `TSSolve()` call. The solver was therefore updated so that `DynamicAnalysis::step()` executes the internal `post_step_()` pipeline explicitly after each converged step, with deduplication to avoid double notifications when PETSc monitors are active.

2. **Global-vs-local DOF indexing:** the original `NodeRecorder` read from the PETSc global displacement vector using node-local DOF indices. The corrected implementation reads from `model.state_vector()`, which is already localized and thus consistent with the structural domain numbering.

After these fixes, the recorder works without any ad hoc calls from the example driver, making this example a useful regression test for future dynamic multiscale studies.

67.9.3 Slab Mass Contribution

Early runs without floor slabs exhibited an unrealistically stiff response: the fundamental period was $T_1 \approx 0.04\,\mathrm{s}$ (instead of $\sim 0.5\,\mathrm{s}$), peak displacements were sub-millimetre even at scale factors of 5–10, and convergence was very poor due to the extreme stiffness contrast. Adding elastic Mindlin–Reissner slab elements resolved the issue by contributing the dominant floor mass from the slab self-weight.

67.9.4 Convergence and SNES Sub-Stepping

With `TSSetMaxSNESFailures(-1)`, PETSc automatically halves the time step upon each SNES divergence and retries. During the peak shaking interval ($t \in [10,\ 16]\,\mathrm{s}$), the effective time step is reduced to approximately $\Delta t_{\mathrm{eff}} \approx 5 \times 10^{-4}\,\mathrm{s}$ ($40\times$ smaller than the nominal $\Delta t = 0.02\,\mathrm{s}$). This causes the simulation to require on the order of 10^4–10^5 steps for the full time window, at a computational cost of about one hour for a single-threaded run with 132 structural elements.

67.9.5 Bypassing the MultiscaleCoordinator

The `MultiscaleCoordinator::build_sub_models()` method generates hex-only prismatic meshes. To include embedded rebar in the sub-models, the example bypasses the coordinator and directly calls `make_reinforced_prismatic_domain()` with a `RebarSpec` that places 8 bars (4 corner + 4 mid-face) in the column cross-section, using the same rebar properties as the global fiber model.

67.10 Summary

This chapter demonstrated the complete Phase 1 → Phase 2 multiscale pipeline on a realistic irregular building:

1. The L-shaped plan with vertical setback, including floor slabs for realistic mass, was generated automatically by the building domain builder with cutout parameters.
2. Bidirectional seismic input from the Tōhoku MYG004 record drove the structure into the nonlinear regime with maximum fiber strains approaching the steel yield point.
3. The damage-threshold director detected the transition and halted the global analysis at $d = 0.80$.
4. Up to 4 reinforced 3D sub-models were created from the most damaged columns and evolved through the remaining earthquake, producing detailed stress/damage fields in both concrete and rebar.
5. Roof displacement time histories captured the bidirectional response including torsional coupling effects from the plan irregularity.
6. The observer path for manual PETSc stepping was corrected and validated, eliminating corrupted roof-response records.

The example validates the interplay of all infrastructure developed in the preceding chapters and provides a template for more complex applications with additional sub-models and refined constitutive laws.

Chapter 68

Validation of the 3D Continuum Sub-Model with Imposed Rotation

The reinforced-concrete sub-model pipeline developed in Chapters 64–66 is designed to resolve the nonlinear material behaviour inside each beam cross-section of the global structural model. During a multiscale analysis, the `SubModelSolver` receives incremental boundary conditions derived from the global beam kinematics—primarily curvatures and axial strains that translate into imposed displacements on the faces of a prismatic finite-element domain.

This chapter validates the complete sub-model infrastructure by solving a standalone boundary-value problem: a doubly-clamped prismatic RC beam loaded by an incremental rotation imposed on one of its end faces. Two cases are compared:

Case A. **Plain concrete** (hex8 elements only), exercising the Ko–Bathe three-dimensional plastic-fracturing model in pure bending.

Case B. **Reinforced concrete** (hex8 + embedded truss rebar), testing the `MultiElementPolicy` assembly and the tension-stiffening effect of embedded steel bars.

The test reproduces—under controlled, quasi-static conditions—the exact loading pattern that the sub-model solver encounters during the global analysis: a linearly ramped displacement field on one face, with the opposite face fully clamped.

68.1 Geometry and Material Properties

The test specimen is a prismatic beam with dimensions $0.30 \times 0.40 \times 2.00$ m (width $\times$ height $\times$ span). The cross-section is discretised with a 4×4 grid, and 16 elements along the span, giving a total of $4 \times 4 \times 16 = 256$ hex8 elements.

Concrete. The Ko–Bathe three-dimensional plastic-fracturing model with $f'_c = 30$ MPa. All parameters are derived internally from f'_c as described in Chapter 64.

Reinforcement (Case B only). Eight longitudinal bars of ∅20 mm ($A_s = 3.14 \times 10^{-4}$ m^2 each) placed at the four corners and four mid-faces of the cross-section, one element inset from the edge to approximate concrete cover. Each bar is discretised into 16 truss segments—one per element along the span—producing 128 line elements. The steel follows the Menegotto–Pinto model with:

$$E_s = 200{,}000 \text{ MPa}, \quad f_y = 420 \text{ MPa}, \quad b = 0.01, \quad R_0 = 20, \quad cR_1 = 18.5, \quad cR_2 = 0.15.$$

The reinforced model contains $256 + 128 = 384$ elements assembled in a heterogeneous `FEM_Element` vector managed by `MultiElementPolicy`.

68.2 Boundary Conditions and Loading

The loading scheme reproduces the boundary-condition pattern that the sub-model solver applies when beam section kinematics change between global analysis steps:

- **MinZ face** (at $z = 0$): all three displacement components constrained to zero (clamped).
- **MaxZ face** (at $z = L$): a rotation θ_y about the local Y-axis is imposed through rigid-section kinematics:

$$u_x = 0, \qquad u_y = 0, \qquad u_z = -\theta_y\,(x - x_c), \tag{68.1}$$

  where x_c is the centroid of the MaxZ face. The displacement pattern is consistent with the plane-sections-remain-plane assumption used in beam theory.

The rotation ramps linearly from 0 to $\theta_{\max} = 5$ mrad (≈ 0.29ř) over 40 equal increments. The incremental solver uses Newton–Raphson iteration (PETSc SNES with LU preconditioner) with up to 8 levels of automatic bisection for non-convergent steps.

The `CustomControl` policy is used to implement the displacement control:

```
auto scheme = make_control(
    [&u_full](double p, Vec, Vec f_ext, auto* m) {
        VecSet(f_ext, 0.0);
        VecCopy(u_full, m->imposed_solution());
        VecScale(m->imposed_solution(), p);
    });
```

where `u_full` stores the target displacement field at $\theta_{\max}$ and the load parameter $p \in [0, 1]$ scales the boundary conditions linearly. This is exactly the same mechanism used by `SubModelSolver::solve_reinfo` in the multiscale pipeline.

68.3 Results

Both cases converge to the target rotation without bisection, confirming that the Newton–Raphson solver handles the progressive cracking and material softening robustly at this deformation level.

68.3.1 Moment–Rotation Response

Figure 68.1 shows the reaction moment M_y at the MaxZ face as a function of the imposed rotation θ_y. The reaction is computed from the assembled internal force vector at converged equilibrium:

$$M_y = \sum_{i \in \mathrm{MaxZ}} f_{x,i}\,(z_i - \bar{z}) - f_{z,i}\,(x_i - \bar{x}), \tag{68.2}$$

where $(\bar{x}, \bar{z})$ is the centroid of the loaded face.

Key observations:

- Both curves depart from the linear regime early as tensile cracking initiates in the extreme fibre, producing a gradual softening of the moment–rotation slope.
- The plain concrete beam reaches $M_y = 219.3$ kN·m at $\theta = 5$ mrad; the reinforced beam reaches $M_y = 239.2$ kN·m—a **9.1% increase** from the embedded rebar.
- The initial elastic stiffness $k_0 = M_y/\theta$ is 53.4 kN·m/mrad (plain) and 57.2 kN·m/mrad (reinforced), consistent with beam theory for a doubly-clamped beam ($k = 4EI_y/L$, $I_y = h\,b^3/12$).



Figure 68.1: Moment–rotation response for plain and reinforced concrete beams. Dashed lines show the initial elastic stiffness. Progressive cracking causes both curves to deviate from the elastic reference, with the reinforced beam maintaining consistently higher capacity.

68.3.2 Stiffness Degradation

Figure 68.2 plots the tangent stiffness $\mathrm{d}M/\mathrm{d}\theta$ at each step. Both curves exhibit monotonically decreasing stiffness as cracking progresses:

- The plain concrete beam loses approximately 43% of its initial stiffness by $\theta = 5$ mrad (k_t: 53.4 $\rightarrow$ 30.3 kN·m/mrad).
- The reinforced beam loses approximately 39% (57.2 $\rightarrow$ 34.7), confirming the tension-stiffening effect of the embedded rebar: the steel carries tensile forces across cracks, partially restraining the stiffness degradation.
- The degradation profile is smooth and monotonic, with no abrupt jumps or oscillations, indicating that the Ko–Bathe smeared-crack model transitions between intact and cracked states in a numerically stable fashion.

68.3.3 Moment Ratio

Figure 68.3 shows the ratio $M_y^{\text{reinf.}}/M_y^{\text{plain}}$ across the loading history. The rebar contribution grows monotonically from 7.2% to 9.1% as cracking progresses, because the steel carries an increasing share of the tensile resultant as the concrete loses stiffness.



Figure 68.2: Tangent stiffness degradation showing the effect of progressive concrete cracking. Dotted lines indicate the initial elastic stiffness. The reinforced beam retains a higher tangent stiffness throughout the loading history.



Figure 68.3: Ratio of the reinforced-to-plain moment capacity. The rebar contribution increases as cracking progresses.

68.4 Analytical Cross-Check

For a doubly-clamped beam with an imposed rotation θ at one end, Euler–Bernoulli beam theory gives the reaction moment at the rotating end as

$$M_y = \frac{4\,E\,I_y}{L}\,\theta, \qquad I_y = \frac{h\,b^3}{12} = \frac{0.40 \times 0.30^3}{12} = 9.0 \times 10^{-4}\ \mathrm{m}^4. \tag{68.3}$$

Using the initial tangent stiffness $k_0 = 53.4$ kN·m/mrad from the simulation, the back-calculated Young's modulus is

$$E_0 = \frac{k_0\,L}{4\,I_y} = \frac{53{,}400 \times 2.0}{4 \times 9.0 \times 10^{-4}} \approx 29{,}667\ \mathrm{MPa},$$

which is consistent with the Ko–Bathe model's initial elastic modulus for $f'_c = 30$ MPa (the ACI 318 formula gives $E_c = 4{,}700\sqrt{f'_c} \approx 25{,}743$ MPa; the Eurocode 2 formula gives $E_{cm} = 22{,}000\,(f_{cm}/10)^{0.3} \approx 32{,}837$ MPa for $f_{cm} = 38$ MPa). The back-calculated value falls between these standard estimates, confirming that the Ko–Bathe model uses a reasonable initial elastic modulus.

The smooth departure from the elastic reference in Figure 68.1 is the expected signature of the smeared-crack approach: the model does not exhibit a sharp cracking event but rather a gradual redistribution of stresses as Gauss points transition from intact to cracked states.

68.5 Implementation Notes

The validation driver (`main_rc_beam_validation.cpp`) is a standalone executable that exercises the same infrastructure used by the sub-model solver:

1. **Mesh generation.** `make_prismatic_domain()` for Case A; `make_reinforced_prismatic_domain()` for Case B. Both produce a `Domain<3>` + `PrismaticGrid` pair.

2. **Element assembly.** Case A uses a standard `Model` with homogeneous hex8 elements. Case B builds a `std::vector<FEM_Element>` with 256 hex8 and 128 truss elements, assembled via `MultiElementPolicy`.

3. **Boundary conditions.** The rotation BCs are computed from the rigid-section kinematics formula (68.1) and applied as Dirichlet constraints. The `CustomControl` scales the full displacement pattern by the load parameter p.

4. **Post-processing.** A step callback extracts the internal force vector at each converged increment, computes the resultant moment via Eq. (68.2), and records the data to CSV files.

5. **VTK export.** Final-step meshes and Gauss-point fields are exported via `VTKModelExporter` for visualization.

The entire pipeline runs in approximately 50 seconds per case on a single core (no MPI parallelism required for this validation test).

68.6 Conclusions

The validation confirms that:

1. The Ko–Bathe 3D constitutive model produces physically meaningful nonlinear responses under monotonic bending: gradual stiffness degradation from smeared cracking, consistent initial elastic modulus, and no spurious oscillations or loss of convergence.

2. The `MultiElementPolicy` infrastructure correctly assembles heterogeneous hex8 + truss element vectors, and the embedded rebar provides the expected tension-stiffening effect (7–9% additional capacity at $\theta = 5$ mrad).

3. The `CustomControl` displacement-control mechanism, which is the same mechanism used by `SubModelSolver`, reliably drives the incremental analysis through the full loading range without bisection.

4. The back-calculated initial stiffness is consistent with standardised Young's modulus estimates for 30 MPa concrete, validating the Ko–Bathe model's elastic regime.

These results provide confidence that the sub-model solver will produce correct results when called from the multiscale analysis pipeline under incrementally changing beam kinematics.

Chapter 69

Higher-Order Prismatic Domains and VTK Local Axes

Chapter 66 introduced the `PrismaticDomainBuilder` for generating structured hexahedral meshes (Hex8) automatically aligned to beam elements. The present chapter generalises the builder to support higher-order hexahedral elements—specifically the 20-node serendipity element (Hex20) and the 27-node triquadratic element (Hex27)—and adds a new VTK cell-data mechanism for exporting element local axes to ParaView.

69.1 Motivation

Linear hexahedral elements (Hex8) are the simplest three-dimensional continuum elements but suffer from well-known shear-locking artifacts in bending-dominated problems. When a prismatic sub-model is used to evaluate nonlinear concrete behaviour after kinematic reconstruction from a beam analysis, the accuracy of the strain field within the sub-model can be significantly improved by using quadratic elements.

Two quadratic hexahedral variants are available in `fall_n`:

Hex20 — Serendipity (`SerendipityElement<3,3,2>`) Uses 8 corner nodes plus 12 edge-midpoint nodes (no face or body-centre nodes). It yields a 20-DOF element that generally performs well in bending and avoids most Hex8 locking issues.

Hex27 — Triquadratic (`LagrangeElement3D<3,3,3>`) Uses all 27 nodes of a $3\times3\times3$ tensor-product grid. It offers full quadratic completeness at the cost of 7 additional internal nodes per element.

Both use $3\times3\times3$ Gauss–Legendre quadrature (27 integration points), which is the minimum complete rule for triquadratic shape functions.

69.2 The `HexOrder` Enumeration

The generalisation is controlled through the `HexOrder` enumeration:

```
enum class HexOrder {
    Linear,        // Hex8  -- 8-node trilinear
    Serendipity,   // Hex20 -- 20-node serendipity
    Quadratic      // Hex27 -- 27-node triquadratic
};
```

A new field `hex_order` was added to `PrismaticSpec` with a default value of `HexOrder::Linear`, so every existing call site remains unchanged:

```
struct PrismaticSpec {
    double width, height, length;
    int    nx, ny, nz;
    HexOrder hex_order = HexOrder::Linear;   // <-- new
    // ... origin, e_x, e_y, e_z, physical_group
};
```

69.3 Structured Grid Generalisation

The `PrismaticGrid` metadata struct was rewritten to support both linear and quadratic grids. Two key additions drive the change:

1. A **step** factor: `step = 1` for linear meshes, `step = 2` for quadratic meshes.
2. The number of nodes per direction becomes `step · n + 1` instead of `n + 1`.

For a quadratic mesh with $n_x \times n_y \times n_z$ elements the grid has $(2n_x + 1) \times (2n_y + 1) \times (2n_z + 1)$ node positions. Node IDs are assigned in lexicographic (column-major) order:

$$\text{node_id}(i_x, i_y, i_z) = i_z \cdot N_x \cdot N_y + i_y \cdot N_x + i_x, \qquad N_\alpha = \text{step} \cdot n_\alpha + 1. \tag{69.1}$$

For Hex20 (serendipity) meshes, all $(2n + 1)^3$ grid positions are created as nodes in the `Domain`, even though face-centre and body-centre positions are not referenced by any element connectivity. These orphan nodes are harmless and greatly simplify the code.

The node spacing in each direction is $\Delta x/\text{step}$ so that mid-edge nodes lie at exactly the half-way position between element corners:

```
const double sub_dx = dx / static_cast<double>(step);
// lx = x0 + ix * sub_dx
```

69.4 Element Connectivity Patterns

69.4.1 Hex8 — Linear

The original column-major pattern on a $\{0, 1\}^3$ sub-grid:

$$\texttt{conn}[i_0 + 2\,i_1 + 4\,i_2] = \text{node_id}(e_x + i_0,\ e_y + i_1,\ e_z + i_2), \qquad i_\alpha \in \{0, 1\}. \tag{69.2}$$

69.4.2 Hex20 — Serendipity

The 20-node connectivity follows the node ordering of `SerendipityCell<3,2>`:

- Nodes 0–7: corners at even grid offsets $\{0, 2\}^3$ from the base $(2e_x, 2e_y, 2e_z)$.
- Nodes 8–11: bottom-face edge midpoints (one odd x or y index, z at base).
- Nodes 12–15: top-face edge midpoints (one odd index, z at base+2).
- Nodes 16–19: vertical edge midpoints (both x, y even, z at base+1).

This ordering matches VTK's `VTK_QUADRATIC_HEXAHEDRON` exactly, so no permutation is needed (identity map in `VTKCellTraits`).

69.4.3 Hex27 — Triquadratic

A full 3^3 tensor product in column-major order:

$$\texttt{conn}[i_0 + 3\,i_1 + 9\,i_2] = \text{node_id}(2e_x + i_0,\ 2e_y + i_1,\ 2e_z + i_2), \qquad i_\alpha \in \{0, 1, 2\}. \tag{69.3}$$

69.5 Quadrature Selection

The quadrature rule is selected per element type:

Element	Template	Integrator	Gauss points
Hex8	`LagrangeElement3D<2,2,2>`	`GaussLegendreCellIntegrator<2,2,2>`	$2^3 = 8$
Hex20	`SerendipityElement<3,3,2>`	`GaussLegendreCellIntegrator<3,3,3>`	$3^3 = 27$
Hex27	`LagrangeElement3D<3,3,3>`	`GaussLegendreCellIntegrator<3,3,3>`	$3^3 = 27$

The $3 \times 3 \times 3$ rule is the minimum complete rule for a triquadratic integrand (order $2 \times 2 = 4$, requiring $\lceil 5/2 \rceil = 3$ points per direction).

69.6 Reinforced Domain with Higher-Order Elements

The `make_reinforced_prismatic_domain()` function was updated to dispatch on `hex_order` using the same logic as the unreinforced builder. The only change affecting rebar line elements is that corner nodes in a quadratic grid are located at even indices:

```
PetscInt conn[2] = {
    grid.node_id(step * bar.ix, step * bar.iy, step * iz),
    grid.node_id(step * bar.ix, step * bar.iy, step * (iz + 1)),
};
```

Since `step = 2` for quadratic meshes, the rebar bar at cross-section position `(ix, iy)` connects grid nodes `(2·ix, 2·iy, 2·iz)` and `(2·ix, 2·iy, 2·(iz+1))`, both of which are corner positions shared by the surrounding hex elements. The perfect-bond assumption is thus preserved exactly.

69.7 The `align_to_beam` Helper

The convenience function `align_to_beam()` now accepts an optional `HexOrder` parameter at the end of its argument list:

```
PrismaticSpec align_to_beam(
    A, B, up,
    width, height,
    nx, ny, nz,
    group = "Solid",
    hex_order = HexOrder::Linear     // <-- new, default = backward-
        compatible
);
```

The returned `PrismaticSpec` carries the requested `hex_order` alongside the computed origin and rotation matrix.

69.8 VTK Local-Axes Cell Data

69.8.1 Motivation

When interpreting material state fields (stress, strain, crack directions) on a prismatic sub-model, the analyst needs to know the element's local coordinate frame relative to the global axes. Without this information, a shear stress σ_{xz} in the results could refer to any direction, making visual inspection unreliable.

69.8.2 Implementation

The `VTKModelExporter` was extended with a general cell-data mechanism:

1. A new member `cell_fields_` (same `FieldBuffer` type used for nodal fields).
2. A new static method `attach_cell_field()` that calls `grid->GetCellData()->AddArray(...)`.
3. A `detach_mesh_cell_arrays()` housekeeping method.
4. Integration into `write_mesh()`: after attaching point-data arrays, cell-data arrays are also attached.
5. The `vtkCellData.h` header was added to the VTK include block.

A dedicated public method `set_local_axes(e_x, e_y, e_z)` creates three 3-component cell fields named `local_x`, `local_y` and `local_z`. Each field contains one 3D vector per cell, all set to the corresponding axis direction. Usage:

```
vtk_exporter.set_local_axes(spec.e_x, spec.e_y, spec.e_z);
vtk_exporter.write_mesh("submodel.vtu");
```

69.8.3 Visualisation in ParaView

To display local axes in ParaView:

1. Open the `.vtu` file.
2. Apply a **Cell Centers** filter to obtain a point per cell.
3. Apply a **Glyph** filter on the result:
   - Glyph type: Arrow.
   - Orientation array: `local_x` (or `local_y`, `local_z`).
   - Scale mode: Off (uniform arrow length).
4. Repeat for each axis, using different colours.

69.9 Example: Hex20 Prismatic Sub-Model

```
auto spec = fall_n::align_to_beam(
    A, B, up,
    0.40, 0.60,     // width, height
    4, 6, 8,        // nx, ny, nz
    "Concrete",
    fall_n::HexOrder::Serendipity    // Hex20
);
```

```

auto [domain, grid] = fall_n::make_prismatic_domain(spec);
// domain contains:
//   4 * 6 * 8 = 192  Hex20 elements  (27 GPs each)
//   (2*4+1)*(2*6+1)*(2*8+1) = 9 * 13 * 17 = 1989 nodes
```

69.10 Backward Compatibility

The default value `HexOrder::Linear` ensures that every existing call to `make_prismatic_domain()`, `make_reinforced_prismatic_domain()` and `align_to_beam()` continues to produce the same Hex8 meshes without modification. The grid's `step = 1` reproduces the original `(n+1)` indexing identically.

Chapter 70

Persistent Nonlinear Sub-Model Evolution and L-Shaped Building Multi-Scale Seismic Analysis

70.1 Introduction and Motivation

The multiscale seismic analysis framework developed in Chapter 63 provides the infrastructure for transitioning from a fibre-section beam model to three-dimensional continuum sub-models at critical elements. The single-shot solver `SubModelSolver` (Chapter 63, § Sub-model solve) and its reinforced variant (Chapter 66) construct a fresh `Model<>` at each call, which means every solve starts from a *virgin material state*: the internal variables—crack normals, plastic strains, damage indices—are discarded after each invocation.

For an earthquake time-history analysis spanning hundreds of time steps, this approach fails to capture the progressive degradation of the concrete. The Ko–Bathe plastic-fracturing model (Chapter 64) tracks up to three crack planes per integration point, storing:

- crack normals $\mathbf{n}_1, \mathbf{n}_2, \mathbf{n}_3$,
- crack opening strains $\varepsilon_{\mathrm{cr},1}, \varepsilon_{\mathrm{cr},2}, \varepsilon_{\mathrm{cr},3}$,
- open/closed status flags,
- a scalar damage index $d \in [0, 1]$.

Resetting these variables at each step would allow the same crack to form repeatedly without accumulating irrecoverable damage, yielding a fictitiously resilient response.

This chapter presents the `NonlinearSubModelEvolver`, a persistent nonlinear continuum sub-model driver that solves the sub-model boundary value problem *incrementally*, preserving material history across all earthquake time steps via direct PETSc `SNES` management. It is demonstrated through a 4-storey L-shaped reinforced-concrete building subjected to three-component earthquake excitation from the 2011 Tōhoku event (station MYG004) at full intensity (no scaling), with triquadratic Hex27 elements and detailed crack evolution tracking.

70.2 Mathematical Framework

70.2.1 Section Kinematics from Beam Elements

A Timoshenko beam element in three dimensions carries six degrees of freedom per node: translations (u_x, u_y, u_z) and rotations $(\theta_x, \theta_y, \theta_z)$ about the local axes. For a given element e with

nodal DOF vector $\mathbf{q}_e \in \mathbb{R}^{12}$ (two-node element) or $\mathbb{R}^{18}$ (three-node), the section kinematics at a parametric coordinate $\xi \in [-1, +1]$ along the beam axis are obtained by interpolation:

$$\mathbf{u}_0(\xi) = \mathbf{N}_u(\xi)\,\mathbf{q}_e, \tag{70.1}$$

$$\boldsymbol{\theta}(\xi) = \mathbf{N}_\theta(\xi)\,\mathbf{q}_e, \tag{70.2}$$

where $\mathbf{N}_u$ and $\mathbf{N}_\theta$ are the standard Lagrangian shape function matrices for translations and rotations, respectively. The section deformation measures are then:

$$\varepsilon_{zz} = \frac{\partial u_z}{\partial s}, \qquad \text{(axial strain)} \tag{70.3}$$

$$\kappa_x = \frac{\partial \theta_x}{\partial s}, \qquad \text{(curvature about local } x\text{)} \tag{70.4}$$

$$\kappa_y = \frac{\partial \theta_y}{\partial s}, \qquad \text{(curvature about local } y\text{)} \tag{70.5}$$

$$\gamma_{xz} = \frac{\partial u_x}{\partial s} - \theta_y, \qquad \text{(transverse shear } xz\text{)} \tag{70.6}$$

$$\gamma_{yz} = \frac{\partial u_y}{\partial s} + \theta_x, \qquad \text{(transverse shear } yz\text{)} \tag{70.7}$$

where s is the arc-length coordinate and the Jacobian $J = \partial s/\partial \xi$ converts parametric to physical derivatives.

The complete section state at each end ($\xi = -1$ for face A, $\xi = +1$ for face B) is collected in a `SectionKinematics` structure:

$$\mathcal{K} = \{\mathbf{u}_0,\ \boldsymbol{\theta},\ \varepsilon_{zz},\ \kappa_x,\ \kappa_y,\ \gamma_{xz},\ \gamma_{yz},\ E,\ G,\ \nu\}. \tag{70.8}$$

The elastic moduli (E, G, ν) are attached for computing the Poisson contraction contribution in the displacement reconstruction.

70.2.2 Kinematic Reconstruction: From Beam to 3D Continuum

The kinematic reconstruction maps the six-DOF section state $\mathcal{K}$ at a face (A or B) to three-component displacement boundary conditions on every node of the corresponding sub-model face. Let the local coordinate system of the cross-section be $(\hat{\mathbf{e}}_x, \hat{\mathbf{e}}_y, \hat{\mathbf{e}}_z)$, with $\hat{\mathbf{e}}_z$ along the beam axis. For a node at local position (x_ℓ, y_ℓ) relative to the section centroid, the reconstructed 3D displacement is:

$$\boxed{\mathbf{u}^{\mathrm{3D}}(x_\ell, y_\ell) = \underbrace{\mathbf{u}_0}_{\text{centroid}} + \underbrace{\boldsymbol{\theta} \times \mathbf{r}}_{\text{rotation}} \underbrace{- \nu\,\varepsilon_{zz}\,\mathbf{r}_\perp}_{\text{Poisson}}} \tag{70.9}$$

where:

$$\mathbf{r} = x_\ell\,\hat{\mathbf{e}}_x + y_\ell\,\hat{\mathbf{e}}_y, \tag{70.10}$$

$$\mathbf{r}_\perp = x_\ell\,\hat{\mathbf{e}}_x + y_\ell\,\hat{\mathbf{e}}_y. \tag{70.11}$$

Expanding the cross product $\boldsymbol{\theta} \times \mathbf{r}$ componentwise:

$$u_x(x_\ell, y_\ell) = u_{x,0} - \theta_z\,y_\ell - \nu\,\varepsilon_{zz}\,x_\ell, \tag{70.12}$$

$$u_y(x_\ell, y_\ell) = u_{y,0} + \theta_z\,x_\ell - \nu\,\varepsilon_{zz}\,y_\ell, \tag{70.13}$$

$$u_z(x_\ell, y_\ell) = u_{z,0} + \theta_x\,y_\ell - \theta_y\,x_\ell. \tag{70.14}$$

Equations (70.12)–(70.14) encode three physical mechanisms:

1. **Rigid-body translation $\mathbf{u}_0$**: bodily displacement of the entire section.

2. **Rotation-induced displacement $\boldsymbol{\theta} \times \mathbf{r}$**: the plane-sections hypothesis for bending (axial distribution linear in x_ℓ, y_ℓ) and torsion (θ_z produces in-plane displacements).

3. **Poisson contraction $-\nu\, \varepsilon_{zz}\, \mathbf{r}_\perp$**: lateral contraction (or expansion) of the cross-section due to axial strain, scaled by the effective Poisson ratio ν.

The reconstruction is evaluated at face A ($\xi = -1$, the MinZ face of the prismatic domain) and face B ($\xi = +1$, the MaxZ face), yielding Dirichlet boundary conditions for all nodes on those faces.

70.2.3 Incremental Application of Boundary Conditions

The evolver operates in two distinct modes, depending on whether the sub-model has been solved before.

First step: incremental loading from virgin state. At the transition instant (the first time the sub-model is activated), the material is virgin and the displacement field is zero. The target boundary displacements $\mathbf{u}_{\text{imp}}^{\text{target}}$ from (70.9) may be large relative to the elastic limit of the concrete. Applying them in a single step would produce a severe initial residual and likely cause Newton divergence.

Instead, the target is applied in N_{sub} increments (default $N_{\text{sub}} = 15$):

$$\mathbf{u}_{\text{imp}}^{(k)} = \frac{k}{N_{\text{sub}}}\, \mathbf{u}_{\text{imp}}^{\text{target}}, \qquad k = 1, 2, \ldots, N_{\text{sub}}. \tag{70.15}$$

At each sub-step, a Newton iteration is performed via `SNESSolve` from the current converged displacement. On convergence, the material state is committed (crack normals, plastic strains, damage are frozen); on divergence, the state is reverted to the previous converged snapshot and the analysis is flagged.

Subsequent steps: direct Newton from current state. For all following earthquake time steps, the boundary condition increment between consecutive steps is small (of order Δt times the ground velocity), so the previously converged displacement $\mathbf{U}^{(n)}$ is an excellent initial guess for $\mathbf{U}^{(n+1)}$. No sub-stepping is required:

$$\mathbf{U}^{(n+1)} = \text{SNESSolve}\big(\mathbf{U}^{(n)}\big) \quad \text{with updated } \mathbf{u}_{\text{imp}}^{(n+1)}. \tag{70.16}$$

This is the central design distinction from `NonlinearAnalysis::solve_incremental()`, which resets $\mathbf{U}$ *to zero before every solve.* By retaining the converged state, the evolver benefits from quadratic convergence from an excellent initial guess, and—crucially—the internal material variables evolve continuously.

70.2.4 Residual and Tangent Stiffness Formulation

The static equilibrium sub-problem at each step reads: find $\mathbf{U} \in \mathbb{R}^{n_{\text{free}}}$ such that

$$\mathbf{R}(\mathbf{U}) = \mathbf{f}_{\text{int}}(\mathbf{U}) - \mathbf{f}_{\text{ext}} = \mathbf{0}, \tag{70.17}$$

where the internal force vector is assembled element-by-element. The external force vector $\mathbf{f}_{\text{ext}}$ is identically zero for a sub-model driven purely by displacement boundary conditions (no applied tractions or body forces).

The total displacement at any node is:

$$\mathbf{u}_{\text{total}} = \underbrace{\mathbf{u}_{\text{free}}}_{\text{from SNES vector } \mathbf{U}} + \underbrace{\mathbf{u}_{\text{imp}}}_{\text{imposed_solution()}}. \tag{70.18}$$

The free DOFs $\mathbf{u}_{\text{free}}$ are determined by Newton iteration; the imposed DOFs $\mathbf{u}_{\text{imp}}$ are prescribed from the kinematic reconstruction. In the PETSc implementation, this decomposition is handled via `DMGlobalToLocal` (which maps the free-DOF global vector to the full local vector, placing zeros at constrained DOFs) and a subsequent `VecAXPY` to add the imposed solution.

Residual callback. At each Newton iterate with trial $\mathbf{U}^{(i)}$:

1. Compute the local total displacement: $\mathbf{u}_{\text{loc}} = \text{G2L}(\mathbf{U}^{(i)}) + \mathbf{u}_{\text{imp}}$.
2. Assemble element internal forces into a local vector: $\mathbf{f}_{\text{int,loc}} = \sum_e \mathbf{f}_{\text{int},e}(\mathbf{u}_{\text{loc}})$.
3. Map back to the global (free-DOF) space: $\mathbf{R} = \text{L2G}(\mathbf{f}_{\text{int,loc}}) - \mathbf{f}_{\text{ext}}$.

Tangent callback. The consistent tangent stiffness matrix is assembled analogously:

$$\mathbf{K}_T = \frac{\partial \mathbf{R}}{\partial \mathbf{U}} = \sum_e \mathbf{K}_{T,e}(\mathbf{u}_{\text{loc}}), \tag{70.19}$$

where each element tangent $\mathbf{K}_{T,e}$ is computed from the constitutive tangent operator at the current strain state, accounting for cracked/crushed zones in the Ko–Bathe model.

The Newton update is:

$$\mathbf{U}^{(i+1)} = \mathbf{U}^{(i)} - \mathbf{K}_T^{-1}\,\mathbf{R}(\mathbf{U}^{(i)}). \tag{70.20}$$

The PETSc SNES framework manages convergence monitoring, line-search strategies, and tolerance checks automatically. The solver is configured with:

- Direct LU factorisation (`-pc_type lu`),
- Maximum 50 iterations (`-snes_max_it 50`),
- Basic line search (`-snes_linesearch_type basic`).

70.2.5 Material State Management

After each converged Newton solve, the material state is *committed*:

$$\boldsymbol{\sigma}^{(n+1)}_{\text{committed}},\ \mathbf{q}^{(n+1)}_{\text{committed}} \leftarrow \boldsymbol{\sigma}^{(n+1)}_{\text{trial}},\ \mathbf{q}^{(n+1)}_{\text{trial}}, \tag{70.21}$$

where $\mathbf{q}$ contains all internal variables (crack normals, opening strains, plastic strains, damage, and loading/unloading flags). This is done by calling `elem.commit_material_state(u_local)` for every element, which evaluates the constitutive response at the converged displacement and freezes the internal state.

If Newton fails to converge, the material state is *reverted*:

$$\boldsymbol{\sigma}^{(n+1)}_{\text{trial}},\ \mathbf{q}^{(n+1)}_{\text{trial}} \leftarrow \boldsymbol{\sigma}^{(n)}_{\text{committed}},\ \mathbf{q}^{(n)}_{\text{committed}}, \tag{70.22}$$

which restores all Gauss-point states to the last converged snapshot. The displacement vector $\mathbf{U}$ retains the last converged values so that the next step can attempt to solve from that baseline.

70.2.6 Post-Setup Boundary Condition Update

The PETSc DMPlex framework applies Dirichlet constraints by eliminating constrained DOFs from the global vector during `model->setup()`. Thereafter, the method `constrain_node()` cannot be called again to modify constrained values.

The evolver bypasses this limitation by writing directly into the model's `imposed_solution()` local vector. For each constrained node i with new displacement target $\mathbf{u}_i^{\text{new}}$:

1. Retrieve the DMPlex point index: $p = \texttt{domain.node}(i).\texttt{sieve_id}$.
2. Query the PetscSection for the DOF offset: $\texttt{PetscSectionGetOffset}(section, p, \&offset)$.
3. Write the three displacement components at $\texttt{arr}[offset], \texttt{arr}[offset{+}1], \texttt{arr}[offset{+}2]$.

This low-level access is safe because the constraint topology (which nodes are constrained) does not change—only the *values* are updated. The DMPlex remains valid, and the `DMGlobalToLocal` / `DMLocalToGlobal` mappings continue to operate correctly.

70.3 Ko–Bathe Concrete in the Multi-Scale Context

The three-dimensional Ko–Bathe plastic-fracturing model (Chapter 64) governs the material response within the sub-model. In the multi-scale context, the model captures:

1. **Crack initiation and propagation.** When the maximum principal stress exceeds the tensile strength f_t (derived from f'_c via $f_t \approx 0.33\sqrt{f'_c}$ MPa), a crack plane is inserted normal to the major principal stress. Up to three orthogonal cracks can form at each Gauss point.
2. **Crack opening and closing.** Under cyclic earthquake loading, cracks may open, close, and partially reopen. The model tracks the open/closed status and applies a reduced shear retention factor β_{cr} for open cracks.
3. **Compressive plasticity.** Beyond the elastic limit in compression, the model uses a Drucker–Prager-type yield surface with hardening/softening.
4. **Damage accumulation.** A scalar damage index d monotonically increases as the material degrades, reducing the effective stiffness.

Because these internal variables persist across time steps in the `NonlinearSubModelEvolver`, the cyclic degradation during the earthquake is captured faithfully: a crack that opens at step n remains in the material memory at step $n{+}1$, affecting the local stiffness and stress redistribution.

Multi-scale RC treatment. The sub-model domain is meshed with homogeneous KoBathe concrete elements (no explicit rebar). This choice is justified within the multi-scale framework:

- The longitudinal and transverse reinforcement effects are captured at the *structural scale* through the fibre sections (Kent–Park confined concrete + Menegotto–Pinto steel) that govern the beam–column response.
- The 3D sub-model zooms into the *concrete matrix* to resolve crack patterns, stress redistribution around cracks, and damage localisation that the fibre model cannot capture.
- The boundary conditions imposed on the sub-model faces already encode the integrated effect of the reinforcement through the section kinematics extracted from the beam element.

This is consistent with the standard hierarchical multi-scale modelling approach where different resolution levels capture different physical phenomena.

70.4 Triquadratic Hex27 Elements

The sub-model domain used in this example employs triquadratic Lagrangian hexahedral elements (Hex27), constructed via `PrismaticDomainBuilder` with `HexOrder::Quadratic` (Chapter 69). Each element has 27 nodes (8 vertices + 12 edge midpoints + 6 face centres + 1 body centre) and is integrated with a $3 \times 3 \times 3$ Gauss quadrature rule (27 integration points per element).

Compared to the serendipity Hex20 elements (which lack face-centre and body-centre nodes), Hex27 elements provide:

- Complete triquadratic polynomial reproduction: all monomial terms up to $\xi^2\eta^2\zeta^2$ are represented exactly.
- Superior stress accuracy: the additional interior nodes eliminate spurious hourglass-like modes that can appear in Hex20 elements under bending-dominated deformations.
- Richer crack representation: with $4 \times 4 \times 8 = 128$ elements and $27 \times 128 = 3{,}456$ Gauss points, the sub-model can resolve fine spatial variations in the crack pattern.

The prismatic mesh with $n_x = 4$, $n_y = 4$, $n_z = 8$ divisions over a $0.40 \times 0.40 \times 3.20$ m column produces element aspect ratios of 1:1:4 (each element is $0.10 \times 0.10 \times 0.40$ m), which is acceptable for the primarily axial-plus-bending deformation mode of a column.

70.5 Crack Evolution Tracking

A key output of the persistent sub-model analysis is the temporal evolution of cracking: how many Gauss points have cracked, the total number of individual crack planes, the maximum damage, and the maximum crack opening—all as functions of the earthquake time.

70.5.1 CrackSummary Aggregation

After each solved step, the evolver collects `InternalFieldSnapshot` data from every integration point. A `CrackSummary` structure aggregates the statistics:

$$\texttt{CrackSummary} = \{n_{\text{GP,cracked}},\ n_{\text{cracks,total}},\ d_{\max},\ \varepsilon_{\text{cr,max}}\}, \tag{70.23}$$

where:

- $n_{\text{GP,cracked}}$ = number of Gauss points with at least one crack,
- $n_{\text{cracks,total}}$ = total crack planes across all cracked Gauss points (each GP can contribute 1–3),
- $d_{\max}$ = maximum scalar damage index among all GPs,
- $\varepsilon_{\text{cr,max}}$ = maximum crack opening strain.

70.5.2 CSV Output Format

At each evolution step, a row is written to `crack_evolution.csv`:

```
time,total_cracked_gps,total_cracks,max_damage,max_opening,
  sub0_cracked_gps,sub0_cracks,sub0_max_damage,
  sub1_cracked_gps,sub1_cracks,sub1_max_damage,...
```

This allows post-processing scripts to plot:

- Crack count vs. time: visualising the onset and progression of cracking with respect to ground motion intensity.
- Damage evolution: monitoring the growth of $d_{\max}$ and identifying the instant of peak damage.
- Per-sub-model comparison: comparing crack evolution across different column elements to identify the most vulnerable structural member.

70.5.3 Crack Plane Visualisation

In addition to the scalar statistics, for each integration point with $n_{\text{crack}} \geq 1$, a detailed `CrackRecord` is stored containing:

- Global coordinates $\mathbf{x}_{\text{GP}}$ of the Gauss point.
- Crack normals $\mathbf{n}_1, \mathbf{n}_2, \mathbf{n}_3 \in \mathbb{R}^3$.
- Crack opening strains $\varepsilon_{\text{cr},1}, \varepsilon_{\text{cr},2}, \varepsilon_{\text{cr},3}$.
- Open/closed status flags.
- Damage index d.

Each active crack is exported as a small `VTK_QUAD` cell centred at the Gauss point and oriented perpendicular to the crack normal. Two tangent vectors $\mathbf{t}_1, \mathbf{t}_2$ are computed as:

$$\mathbf{t}_1 = \frac{\mathbf{n}_k \times \mathbf{e}_{\text{ref}}}{\|\mathbf{n}_k \times \mathbf{e}_{\text{ref}}\|}, \qquad \mathbf{t}_2 = \mathbf{n}_k \times \mathbf{t}_1, \tag{70.24}$$

where $\mathbf{e}_{\text{ref}}$ is $\hat{\mathbf{e}}_x$ or $\hat{\mathbf{e}}_y$ (whichever is less parallel to $\mathbf{n}_k$). The quad corners are:

$$\mathbf{x}_j = \mathbf{x}_{\text{GP}} + \frac{h}{2}\big[(\pm 1)\,\mathbf{t}_1 + (\pm 1)\,\mathbf{t}_2\big], \qquad j = 1, \ldots, 4, \tag{70.25}$$

where $h = 0.4\,\min(\Delta x, \Delta y, \Delta z)/2$ is a sizing factor based on the element dimensions. Cell data arrays carry the opening strain, normal vector, and crack state (open = 1, closed = 0), enabling ParaView visualisation via Glyph or Threshold filters.

Three PVD time-series files are maintained per sub-model:

- `nlsub_<id>_mesh.pvd` — deformed mesh with displacement and material fields (stress, strain, damage).
- `nlsub_<id>_gauss.pvd` — Gauss-point cloud.
- `nlsub_<id>_cracks.pvd` — crack plane quads.

70.6 Implementation

70.6.1 Class Architecture

The `NonlinearSubModelEvolver` class manages:

1. A persistent `Model<ThreeDimensionalMaterial, SmallStrain, 3>` instance (`HomogModel`) with KoBathe concrete at every element.
2. PETSc SNES objects: `SNES snes_`, `Vec U_` (global free-DOF displacement), `Vec R_` (residual), `Vec f_ext_` (external forces, identically zero), and `Mat J_` (tangent stiffness).

3. A `Context` struct holding pointers to the model and external force vector, passed to the static SNES callbacks.
4. PVD writers for mesh, Gauss, and crack output.
5. A vector of `CrackRecord` containing the latest crack data.

The lifecycle proceeds as:

1. **Construction**: store reference to `MultiscaleSubModel`, f'_c, output paths.
2. **First `solve_step()` call**: create model, apply constraints, setup, create SNES, incremental load.
3. **Subsequent calls**: update `imposed_solution()` via PetscSection offsets, `SNESSolve` from current $\mathbf{U}$.
4. **After each solve**: collect crack data, write VTK.
5. **Finalisation**: write PVD files.

The class supports move semantics but prohibits copying, since the PETSc objects are non-copyable resources. The move constructor uses `std::exchange` for all PETSc handles and rebinds the `Context` pointer.

70.6.2 SNES Callbacks

Two static member functions serve as PETSc callbacks:

FormResidual.

1. Convert global $\mathbf{U}$ to local via `DMGlobalToLocal`.
2. Add `imposed_solution()` to obtain $\mathbf{u}_{\text{total}}$.
3. Loop over elements, calling `compute_internal_forces(u_local, f_local)`.
4. Map local $\mathbf{f}_{\text{int}}$ to global $\mathbf{R}$ via `DMLocalToGlobal(ADD_VALUES)`.
5. Subtract $\mathbf{f}_{\text{ext}}$ (zero for sub-models).

FormJacobian.

1. Zero the matrix $\mathbf{J}$.
2. Compute local total displacement (same as above).
3. Loop over elements, calling `inject_tangent_stiffness(u_local, J)`.
4. Assemble with `MatAssembly{Begin,End}`.

These callbacks are identical in structure to `NonlinearAnalysis::FormResidual/FormJacobian` (Chapter 62), but are owned by the evolver instance rather than the analysis wrapper, enabling the critical feature of persistent $\mathbf{U}$.

70.7 L-Shaped Building Example

70.7.1 Structural Configuration

A 4-storey reinforced-concrete moment frame with an L-shaped floor plan is modelled. The plan grid coordinates are:

Direction	Grid coordinates
x	0, 5, 10, 15 m
y	0, 4, 8 m

The L-shape is achieved by cutting out the bay at grid indices ($i_x \in [2, 3)$, $i_y \in [1, 2)$) above all storeys, removing the upper-right quadrant of the full rectangular plan. Each storey has a height of 3.2 m; the total building height is 12.8 m. The resulting structural model contains 55 nodes, 44 column elements, and 60 beam elements (104 structural elements total).

Section properties:

Member	b [m]	h [m]	f'_c [MPa]	Steel
Columns	0.40	0.40	28	$f_y = 420$ MPa
Beams	0.30	0.50	25	$f_y = 420$ MPa

Fibre sections use Kent–Park confined concrete (for columns with $s_t = 0.10$ m tie spacing) or unconfined concrete (for beams), and Menegotto–Pinto steel with hardening ratio $b = 0.01$.

Mass and damping. Lumped mass is computed with $\rho = 2.4 \times 10^{-3}$ MN·s^2/m^4. Rayleigh damping targets $\xi = 5\%$ at $T_1 \approx 0.60$ s and $T_3 \approx 0.15$ s.

70.7.2 Three-Component Ground Motion

The 2011 Tōhoku earthquake record from K-NET station MYG004 (Tsukidate, Miyagi Prefecture) is applied simultaneously in three components:

Component	DOF	PGA [m/s^2]	PGA [g]	t_{PGA} [s]
NS	x	26.79	2.731	70.60
EW	y	12.85	1.310	70.66
UD	z	18.87	1.923	70.31

The records are trimmed to $[25, 300]$ s (skipping the pre-event noise) and applied at **full intensity** (scale factor = 1.0, no amplification or reduction) to capture the realistic severity of this near-fault, high-intensity event. With PGA exceeding $2.7g$ in the NS direction, the structure is subjected to extreme demands that drive extensive cracking and damage in the sub-models.

Time integration uses the generalized-α method with spectral radius $\rho_\infty = 0.9$ and a fixed time step $\Delta t = 0.02$ s (matching the record sampling interval).

70.7.3 Phase 1: Global Dynamic Analysis with Transition Monitoring

A `DynamicAnalysis` solver is configured with a `CompositeObserver` containing:

1. `DamageTracker` — monitors the maximum fibre strain in every element and maintains a ranked list of the top-10 most-damaged elements.

2. `FiberHysteresisRecorder` — records (ε, σ) histories for the 5 most-stressed fibres per material class (concrete and steel), enabling post-processing of hysteretic loops.

3. `NodeRecorder` — records displacement time histories at all roof-level nodes (3 DOFs each).

A `TransitionDirector` with a `MaxStrainDamageCriterion` halts Phase 1 the instant any steel fibre anywhere in the structure exceeds its yield strain:

$$\varepsilon_{\max,e} > \varepsilon_y = \frac{f_y}{E_s} = \frac{420}{200{,}000} = 0.0021. \tag{70.26}$$

The transition report records the time of first yield, the critical element index, and the damage metric. Given the extreme ground motion intensity (PGA $> 2.7g$), first yield is expected well before the PGA arrival at $t \approx 45.6$ s (accounting for the 25 s trim offset from the original 70.6 s).

70.7.4 Phase 2: Multi-Scale Sub-Model Evolution

Critical element identification. After Phase 1 halts, the top-3 most-damaged beam elements (with damage index > 0.8) are identified from the `DamageTracker` ranking. If fewer than 3 elements exceed the threshold, the single critical element from the transition report is used.

Sub-model construction. For each critical column, a `MultiscaleCoordinator`:

1. Extracts section kinematics at both ends ($\xi = \pm 1$).
2. Builds a prismatic domain via `PrismaticDomainBuilder` with $n_x = 4,\ n_y = 4,\ n_z = 8$ Hex27 elements.
3. Computes displacement boundary conditions on the two end faces from (70.12)–(70.14).

Sub-model evolution loop. A `NonlinearSubModelEvolver` is instantiated per critical column with $f'_c = 28$ MPa. The global dynamic analysis then continues step-by-step. At each step:

1. The global solver advances one time step via `solver.step_n(1)`.
2. For each sub-model evolver:
   (a) Section kinematics are re-extracted from the (updated) beam element.
   (b) `update_kinematics(...)` recomputes face BCs via (70.9).
   (c) `solve_step(t)` performs Newton iteration from the previous converged state.
   (d) `crack_summary()` returns the aggregate statistics for the CSV log.
3. Crack evolution data is written to CSV.
4. Peak damage across the global model is updated.
5. VTK snapshots are written every 50 steps (1.0 s intervals).

This loop continues until the end of the 275 s analysis window (corresponding to $t = 300$ s in the original record).

Output files. The analysis produces:

- `yield_state.vtm` — global frame VTK at first yield.
- `evolution/frame_NNNNNN.vtm` + `frame.pvd` — global frame time series.
- `evolution/sub_models/nlsub_<id>_{mesh,gauss,cracks}.pvd` — per sub-model PVD series.
- `recorders/roof_displacement.csv` — nodal displacement histories at roof level.
- `recorders/fiber_hysteresis_{concrete,steel}.csv` — fibre stress–strain histories.
- `recorders/crack_evolution.csv` — crack count, damage, and opening vs. time for each sub-model.

70.8 Incremental Kinematics Coupling: Full Derivation

This section presents the complete mathematical chain from beam DOFs to sub-model Dirichlet boundary conditions.

Step 1: Element DOF extraction. For beam element e with element DOF vector $\mathbf{q}_e \in \mathbb{R}^{12}$ (2-node Timoshenko):

$$\mathbf{q}_e = \left[u_{x,A},\ u_{y,A},\ u_{z,A},\ \theta_{x,A},\ \theta_{y,A},\ \theta_{z,A},\ u_{x,B},\ u_{y,B},\ u_{z,B},\ \theta_{x,B},\ \theta_{y,B},\ \theta_{z,B}\right]^T. \tag{70.27}$$

Step 2: Interpolation at end sections. At $\xi = -1$ (face A), the linear shape functions give:

$$\mathbf{u}_0^A = (u_{x,A},\ u_{y,A},\ u_{z,A})^T, \tag{70.28}$$

$$\boldsymbol{\theta}^A = (\theta_{x,A},\ \theta_{y,A},\ \theta_{z,A})^T. \tag{70.29}$$

The section deformation measures at face A require derivative evaluation:

$$\varepsilon_{zz}^A = \frac{1}{L}(u_{z,B} - u_{z,A}), \tag{70.30}$$

$$\kappa_x^A = \frac{1}{L}(\theta_{x,B} - \theta_{x,A}), \tag{70.31}$$

$$\kappa_y^A = \frac{1}{L}(\theta_{y,B} - \theta_{y,A}), \tag{70.32}$$

where L is the element length. Analogous expressions hold for face B at $\xi = +1$.

Step 3: Displacement reconstruction on sub-model face. Let the sub-model face have n_f nodes at local coordinates $\{(x_{\ell,j}, y_{\ell,j})\}_{j=1}^{n_f}$ relative to the section centroid. The 3×1 displacement vector at node j is:

$$\mathbf{u}_j^{\text{face}} = \underbrace{\begin{pmatrix} u_{x,0} \\ u_{y,0} \\ u_{z,0} \end{pmatrix}}_{\text{centroid}} + \underbrace{\begin{pmatrix} -\theta_z\, y_{\ell,j} \\ \theta_z\, x_{\ell,j} \\ \theta_x\, y_{\ell,j} - \theta_y\, x_{\ell,j} \end{pmatrix}}_{\text{rotation}} + \underbrace{\begin{pmatrix} -\nu\, \varepsilon_{zz}\, x_{\ell,j} \\ -\nu\, \varepsilon_{zz}\, y_{\ell,j} \\ 0 \end{pmatrix}}_{\text{Poisson}}. \tag{70.33}$$

Step 4: Time stepping. At each earthquake step n, the beam element DOFs $\mathbf{q}_e^{(n)}$ are extracted from the global state vector. The section kinematics $\mathcal{K}_A^{(n)}, \mathcal{K}_B^{(n)}$ are computed, and the face displacements $\{\mathbf{u}_j^{\text{face}}\}_j$ are evaluated via (70.33). These become the Dirichlet BCs for the sub-model Newton solve at step n.

The *increment* in the boundary displacement between steps is:

$$\Delta\mathbf{u}_j^{(n)} = \mathbf{u}_j^{\text{face},(n)} - \mathbf{u}_j^{\text{face},(n-1)}, \tag{70.34}$$

which is typically small compared to the total displacement. This ensures that the Newton solver converges rapidly from the previous state, usually in 2–4 iterations.

Step 5: Equilibrium solve. The sub-model solves:

$$\mathbf{f}_{\text{int}}(\mathbf{u}_{\text{free}}^{(n)} + \mathbf{u}_{\text{imp}}^{(n)}) = \mathbf{0} \tag{70.35}$$

for $\mathbf{u}_{\text{free}}^{(n)}$, with initial guess $\mathbf{u}_{\text{free}}^{(n-1)}$. The constitutive response at each Gauss point accounts for the full crack/damage history from steps $1, \ldots, n-1$.

70.9 Discussion

Convergence behaviour. The first solve (incremental from virgin state with $N_{\text{sub}} = 15$ sub-steps) typically requires 5–10 Newton iterations per sub-step due to the nonlinearity of crack initiation. Subsequent solves converge in 2–4 iterations thanks to the small BC increments and the excellent initial guess from the previous converged state.

Computational cost. Each sub-model has $4 \times 4 \times 8 = 128$ Hex27 elements with $27 \times 128 = 3{,}456$ Gauss points and approximately $9 \times 9 \times 17 = 1{,}377$ nodes (accounting for the Hex27 lattice). With 3 DOFs per node, the free-DOF system (after constraining face nodes) has approximately 3,500–3,800 DOFs. A direct LU solve of this size is very fast: under 0.1 s per Newton iteration. For 3 sub-models with $\sim$5 iterations each per step, the sub-model overhead is approximately 1.5 s per global step—a modest cost relative to the global dynamic solve that includes mass matrix assembly, Rayleigh damping, and the generalized-α time integrator.

Persistent state vs. single-shot. The persistent evolver produces fundamentally different results from the single-shot `SubModelSolver`: once a crack forms at a Gauss point, it persists and affects all subsequent steps. Under cyclic earthquake loading, this leads to progressive stiffness degradation, stress redistribution to intact regions, and eventually crack localisation. The single-shot solver, by contrast, would produce the same crack pattern at every step for the same boundary displacements, regardless of prior loading history.

Full-scale earthquake effects. With the MYG004 record applied at full intensity (PGA $>$ $2.7g$ NS), the structure experiences extreme demands. The sub-models are expected to show:

- Early onset of cracking (during the build-up phase before PGA).
- Rapid increase in cracked Gauss points during the intense shaking phase ($t \approx 45$–95 s after the trim offset).
- Potential crack saturation (many GPs reaching the 3-crack maximum) at peak demands.
- Partial recovery during the coda phase as the ground motion subsides, with cracks closing but damage persisting.

Limitations and extensions.

- The current sub-models use homogeneous concrete without explicit rebar. For columns with high confinement or significant shear-reinforcement interaction, embedded truss elements (Chapter 65) could be added via `MixedModel`. This would require extending the evolver to handle both element types, with specialised crack data collection for the concrete elements.
- The kinematic coupling is one-way: the global beam model is not affected by the sub-model response. A two-way coupling (where the sub-model feeds back homogenised stiffness to the beam) would require modifications to the global dynamic solver.
- Geometric nonlinearity (large rotations) is not considered in the reconstruction (70.9). For columns with extreme inter-storey drifts, a co-rotational formulation would be more appropriate.

Chapter 71

Mixed-Model Reinforced Sub-Model with Discrete Rebars

71.1 Introduction and Motivation

The persistent nonlinear sub-model evolver introduced in Chapter 70 uses a homogeneous three-dimensional continuum model (all Hex27 elements with the Ko–Bathe concrete material) to track damage evolution at critical locations. While this captures concrete cracking and damage realistically, it neglects the contribution of reinforcing steel, which dominates the post-cracking response of reinforced-concrete (RC) members.

This chapter extends the sub-model framework to support *mixed models* that embed discrete one-dimensional rebar elements (two-node trusses) within the three-dimensional hexahedral mesh. The resulting model has two element types sharing nodes through the DMPlex sieve (perfect-bond assumption), a mixed finite-element configuration that cannot be handled by the single-type `SingleElementPolicy`. The type-erased `FEM_Element` wrapper and the `MultiElementPolicy` provide the mechanism to store and iterate over heterogeneous element types in a single `Model<>`.

71.2 Mathematical Formulation

71.2.1 Mixed Displacement Field and Perfect Bond

Let $\Omega_c \subset \mathbb{R}^3$ denote the concrete domain discretised by hexahedral elements, and let $\Gamma_s \subset \Omega_c$ denote the set of one-dimensional rebar segments embedded within the concrete mesh. Under the perfect-bond assumption, the rebar displacement at any point along the bar coincides with the continuum displacement interpolated at the shared nodes:

$$\mathbf{u}^s(\mathbf{x}) = \mathbf{u}^c(\mathbf{x}), \quad \forall\, \mathbf{x} \in \Gamma_s \cap \partial\Omega_c^{\text{nodes}}, \tag{71.1}$$

where the superscripts c and s refer to concrete and steel, respectively. Since truss nodes coincide with hexahedral nodes the shared DOFs enter both element stiffness contributions additively.

71.2.2 Continuum Element Contribution (Concrete)

Each hexahedral element e contributes the standard 3D solid tangent stiffness and internal-force vector:

$$\mathbf{K}_t^{(e)} = \int_{\Omega^{(e)}} \mathbf{B}_c^T\, \mathbf{D}_t^{(e)}\, \mathbf{B}_c \, \mathrm{d}\Omega, \qquad \mathbf{f}_{\text{int}}^{(e)} = \int_{\Omega^{(e)}} \mathbf{B}_c^T\, \boldsymbol{\sigma}^{(e)} \, \mathrm{d}\Omega, \tag{71.2}$$

where $\mathbf{B}_c$ is the standard strain–displacement matrix, $\mathbf{D}_t$ the consistent tangent modulus from the Ko–Bathe material, and $\boldsymbol{\sigma}$ the Cauchy stress vector. The integrals are evaluated via Gauss–Legendre quadrature at $3 \times 3 \times 3 = 27$ points for Hex27 elements.

71.2.3 Truss Element Contribution (Rebar)

Each rebar segment is modelled as a two-node bar element in 3D space with $2 \times 3 = 6$ DOFs. The element strain is purely axial:

$$\varepsilon = \mathbf{B}_s \, \mathbf{u}_e, \qquad \mathbf{B}_s = \frac{1}{L} \begin{bmatrix} -l & -m & -n & l & m & n \end{bmatrix}, \tag{71.3}$$

where (l, m, n) are the direction cosines of the bar axis and L is the element length. The tangent stiffness and internal force are:

$$\mathbf{K}_t^{(s)} = A_s \, L \, E_t(\varepsilon) \, \mathbf{B}_s^T \, \mathbf{B}_s, \qquad \mathbf{f}_{\text{int}}^{(s)} = A_s \, L \, \sigma(\varepsilon) \, \mathbf{B}_s^T, \tag{71.4}$$

where A_s is the bar cross-sectional area and $E_t = \partial\sigma/\partial\varepsilon$ is the uniaxial tangent modulus from the Menegotto–Pinto steel model.

One Gauss point suffices for exact integration over a 2-node linear element with constant $\mathbf{B}_s$.

71.2.4 Assembled Mixed System

The global stiffness matrix and internal-force vector are obtained by the standard direct-stiffness assembly:

$$\mathbf{K}_t = \sum_{e \in \mathcal{E}_c} \mathbf{A}_e^T \mathbf{K}_t^{(e)} \mathbf{A}_e + \sum_{s \in \mathcal{E}_s} \mathbf{A}_s^T \mathbf{K}_t^{(s)} \mathbf{A}_s, \tag{71.5}$$

where $\mathbf{A}_e$ and $\mathbf{A}_s$ are the Boolean scatter matrices that map element to global DOFs. Because rebar nodes are shared with hex nodes, the PETSc `MatSetValuesLocal` assembly with `ADD_VALUES` automatically couples both contributions at shared DOFs.

The equilibrium equation at each Newton iteration is therefore:

$$\mathbf{K}_t \, \delta\mathbf{u} = -\mathbf{R}, \qquad \mathbf{R} = \mathbf{f}_{\text{int}}^c + \mathbf{f}_{\text{int}}^s - \mathbf{f}_{\text{ext}}, \tag{71.6}$$

where $\mathbf{f}_{\text{int}}^c$ and $\mathbf{f}_{\text{int}}^s$ come from concrete and rebar elements respectively.

71.3 Type-Erased Element Access: `GaussPointSnapshot`

With `MultiElementPolicy`, the model stores elements as `std::vector<FEM_Element>`, where `FEM_Element` is a type-erased wrapper using the External Polymorphism pattern. The heterogeneous element list means we cannot call typed methods like `material_points()` directly.

A new virtual method `gauss_point_snapshots(Vec u_local)` was added to the `FEM_Element::Concept` base class. The `Model<T>` bridge template implements this method using `if constexpr`:

- For `ContinuumElement`: iterates `material_points()`, extracts position from geometry integration points, stress/strain from the material state, and crack data from `internal_field_snapshot()`.
- For `TrussElement`: returns an empty vector (steel has no crack model; its contribution is purely structural).

The returned `GaussPointSnapshot` struct aggregates:

$$\texttt{GaussPointSnapshot} = \{\mathbf{x},\ \boldsymbol{\sigma},\ \boldsymbol{\varepsilon},\ d,\ n_{\text{cracks}},\ \{\mathbf{n}_i\}_{i=1}^3,\ \{w_i\}_{i=1}^3,\ \{c_i\}_{i=1}^3\},$$

where d is the scalar damage, $\mathbf{n}_i$ are crack normals, w_i are crack openings, and c_i are open/-closed flags. This struct provides a uniform interface for both crack-data collection and volume-averaged stress/strain extraction.

71.4 Reinforced Prismatic Domain Construction

The function `make_reinforced_prismatic_domain()` generates a combined hex+line mesh:

1. All nodes are created on the structured prismatic grid (same as the homogeneous case).
2. Hexahedral element geometries are created with the specified element order (Hex8, Hex20, or Hex27), each assigned to the `"Solid"` physical group.
3. For each rebar bar specified by grid indices (i_x, i_y) and cross-sectional area A_s, the builder creates n_z 2-node line elements connecting consecutive z-level nodes at $(\texttt{step} \cdot i_x,\ \texttt{step} \cdot i_y,\ \texttt{step} \cdot k)$ for $k = 0, \ldots, n_z - 1$. These elements are assigned to the `"Rebar"` physical group.
4. A `RebarElementRange` is returned, providing the index range $[\texttt{first}, \texttt{last})$ of rebar element geometries within the domain's element list.

The coordinator maps physical rebar positions (y, z) from the `SubModelSpec` to grid indices via nearest-node snapping:

$$i_x = \text{round}\left(\frac{y + w/2}{\Delta x}\right), \qquad i_y = \text{round}\left(\frac{z + h/2}{\Delta y}\right), \tag{71.7}$$

where w and h are the section width and height, and $\Delta x = w/n_x$, $\Delta y = h/n_y$ are the element spacings. The indices are clamped to $[0, n_x]$ and $[0, n_y]$ respectively.

71.5 Model Construction in the Evolver

The `NonlinearSubModelEvolver` was refactored from a `HomogModel` (typed, `SingleElementPolicy`) to a `MixedModel` (`MultiElementPolicy`) which always stores elements as `FEM_Element`. The `first_solve()` method builds the element list explicitly:

1. **Concrete elements**: For each hex geometry (indices $[0, \texttt{rebar_first})$), create a `ContinuumElement` with the Ko–Bathe concrete material and wrap in `FEM_Element`.
2. **Rebar elements** (optional): For each line geometry (indices $[\texttt{rebar_first}, \texttt{rebar_last})$), create a `TrussElement<3>` with the Menegotto–Pinto steel material, the bar's cross-sectional area, and wrap in `FEM_Element`.
3. Pass the assembled `std::vector<FEM_Element>` to the Model constructor 2 (pre-built elements), then proceed with constraint application and PETSc SNES setup as before.

The SNES callbacks (`FormResidual`, `FormJacobian`) iterate `model_->elements()` and call `compute_internal_forces`, `inject_tangent_stiffness`, `commit_material_state`, and `revert_material_s` — all of which are forwarded through the `FEM_Element` type-erasure to the underlying concrete or truss element.

71.5.1 Post-Processing Adaptation

The `extract_results()` and `collect_crack_data()` methods were rewritten to use `gauss_point_snapshots(` instead of the typed `material_points()` access:

- `extract_results()`: Accumulates volume-averaged $\boldsymbol{\sigma}$ and $\boldsymbol{\varepsilon}$ from snapshots, computes effective E and G, and evaluates the von Mises peak.

- `collect_crack_data()`: Iterates snapshots with $n_{\text{cracks}} > 0$ to build `CrackRecord` entries for VTK crack-plane export.

Truss elements return empty snapshot vectors, so they contribute neither to crack statistics nor to the stress averaging (by design, rebar stress is a uniaxial contribution embedded in the continuum average).

71.6 Coordinator Integration

The `MultiscaleCoordinator::build_sub_models()` method was extended to detect `spec.has_rebar()` and dispatch accordingly:

- **Without rebar**: calls `make_prismatic_domain()` as before, producing a homogeneous hex mesh.
- **With rebar**: converts the physical rebar coordinates to grid indices via (71.7), builds a `RebarSpec`, and calls `make_reinforced_prismatic_domain()`.

The `MultiscaleSubModel` struct was extended with:

- `rebar_range`: the element index range for rebar geometries within the domain.
- `rebar_areas`: a vector of bar areas (one per bar, repeated for each z-level segment internally).
- `has_rebar()`: convenience query.

The evolver's `set_rebar_material(E, fy, b)` method allows specifying the Menegotto–Pinto parameters (elastic modulus, yield stress, hardening ratio) before the first solve.

71.7 Summary

The mixed-model extension enables realistic simulation of reinforced-concrete sub-models at the microscale:

1. Concrete (Hex27 + Ko–Bathe): captures cracking, softening, and damage accumulation.
2. Steel (TrussElement<3> + Menegotto–Pinto): captures yielding, Bauschinger effect, and cyclic hardening.
3. Perfect bond: shared nodes enforce displacement compatibility through the assembled stiffness.
4. Type erasure: `FEM_Element` and `MultiElementPolicy` allow both element types in a single `Model<>` with unified SNES callbacks.

The implementation preserves full backward compatibility: when `SubModelSpec` has no rebar bars, the evolver creates the same homogeneous concrete model as before.

Chapter 72

Arc-Length Control for Nonlinear Analysis

72.1 Introduction

Load-controlled and displacement-controlled Newton–Raphson methods fail at limit points (snap-through) and bifurcation points (snap-back) on the equilibrium path. At a limit point the tangent stiffness matrix becomes singular in the loading direction; at a snap-back the displacement path reverses, requiring negative load increments that standard monotonic schemes cannot produce.

The arc-length method—originally proposed by Riks (1979) and refined by Crisfield (1981, 1983)—augments the equilibrium system with a *constraint equation* that controls the step length along the equilibrium path in the combined load–displacement space. This chapter documents the mathematical formulation and its implementation in the `ArcLengthControl` and `ArcLengthSolver` classes.

72.2 Augmented System

We seek the equilibrium of a discretised structure under a proportional reference load $\hat{\mathbf{f}}$ scaled by a single load parameter λ:

$$\mathbf{R}(\mathbf{u}, \lambda) = \mathbf{f}_{\text{int}}(\mathbf{u}) - \lambda\,\hat{\mathbf{f}} = \mathbf{0}. \tag{72.1}$$

The unknowns are the displacement vector $\mathbf{u} \in \mathbb{R}^n$ and the scalar load parameter $\lambda \in \mathbb{R}$, totalling $n + 1$ equations for $n + 1$ unknowns once a constraint is appended.

72.2.1 Constraint Equations

Two variants are implemented:

Cylindrical. The cylindrical arc-length constraint (Crisfield, 1981) enforces a constant displacement-space step:

$$g(\Delta\mathbf{u}, \Delta\lambda) = \Delta\mathbf{u}^T\Delta\mathbf{u} + \psi^2\,\Delta\lambda^2\,\hat{\mathbf{f}}^T\hat{\mathbf{f}} - \Delta\ell^2 = 0, \tag{72.2}$$

where $\Delta\ell$ is the prescribed arc-length radius and ψ is a scaling factor that controls the relative weight of the load component ($\psi = 0$ reduces to a purely displacement-based norm, $\psi = 1$ gives the "spherical" version in the original coordinates).

Spherical. The spherical variant (Crisfield, 1981) uses the full $(n + 1)$-dimensional norm:

$$g = \Delta\mathbf{u}^T\Delta\mathbf{u} + \psi^2\,\Delta\lambda^2\,\hat{\mathbf{f}}^T\hat{\mathbf{f}} - \Delta\ell^2 = 0. \tag{72.3}$$

Both constraints share the same algebraic form but differ in the root-selection strategy of the corrector (see below).

72.3 Predictor Step (Tangent Predictor)

At the beginning of each new step k, the tangent stiffness at the last converged state $(\mathbf{u}_k, \lambda_k)$ is factored and the load-sensitivity vector is computed:

$$\mathbf{K}_t \, \delta\mathbf{u}_f = \hat{\mathbf{f}}. \tag{72.4}$$

The predictor increment satisfies the constraint exactly:

$$\Delta\lambda_{\text{pred}} = \pm \frac{\Delta\ell}{\sqrt{\delta\mathbf{u}_f^T \delta\mathbf{u}_f + \psi^2 \, \hat{\mathbf{f}}^T \hat{\mathbf{f}}}}. \tag{72.5}$$

The sign is chosen to maintain a consistent traversal direction:

$$\text{sign}(\Delta\lambda_{\text{pred}}) = \text{sign}(\Delta\lambda_{k-1}), \tag{72.6}$$

where $\Delta\lambda_{k-1}$ is the *converged* load increment from the previous step. At the very first step, a positive sign (loading) is assumed. After the predictor:

$$\Delta\mathbf{u}_{\text{pred}} = \Delta\lambda_{\text{pred}} \, \delta\mathbf{u}_f. \tag{72.7}$$

72.4 Corrector Iterations (Sherman–Morrison Decomposition)

At each Newton corrector iteration j within step k, the current state is $(\mathbf{u}_k^{(j)}, \lambda_k^{(j)})$ with accumulated increments $(\Delta\mathbf{u}^{(j)}, \Delta\lambda^{(j)})$. The residual is:

$$\mathbf{R}^{(j)} = \mathbf{f}_{\text{int}}(\mathbf{u}_k^{(j)}) - \lambda_k^{(j)} \, \hat{\mathbf{f}}. \tag{72.8}$$

Two right-hand-side solves are performed:

$$\mathbf{K}_t^{(j)} \, \delta\mathbf{u}_R = -\mathbf{R}^{(j)}, \qquad \mathbf{K}_t^{(j)} \, \delta\mathbf{u}_f = \hat{\mathbf{f}}. \tag{72.9}$$

The total correction is decomposed as:

$$\delta\mathbf{u} = \delta\mathbf{u}_R + \delta\lambda \, \delta\mathbf{u}_f, \tag{72.10}$$

where $\delta\lambda$ is determined from the constraint linearisation.

72.4.1 Cylindrical Corrector

Linearising (72.2) about $(\Delta\mathbf{u}^{(j)}, \Delta\lambda^{(j)})$ and substituting (72.10):

$$\delta\lambda = -\frac{\Delta\mathbf{u}^{(j)\,T} \delta\mathbf{u}_R}{\Delta\mathbf{u}^{(j)\,T} \delta\mathbf{u}_f + \psi^2 \, \Delta\lambda^{(j)} \, \hat{\mathbf{f}}^T \hat{\mathbf{f}}}. \tag{72.11}$$

This is the Sherman–Morrison formula for the bordered system.

72.4.2 Spherical Corrector

The full constraint (72.3) yields a quadratic in $\delta\lambda$:

$$a\,\delta\lambda^2 + b\,\delta\lambda + c = 0, \tag{72.12}$$

with:

$$a = \delta\mathbf{u}_f^T \delta\mathbf{u}_f + \psi^2\,\|\hat{\mathbf{f}}\|^2, \tag{72.13}$$

$$b = 2\big((\Delta\mathbf{u}^{(j)} + \delta\mathbf{u}_R)^T \delta\mathbf{u}_f + \psi^2\,\Delta\lambda^{(j)}\,\|\hat{\mathbf{f}}\|^2\big), \tag{72.14}$$

$$c = (\Delta\mathbf{u}^{(j)} + \delta\mathbf{u}_R)^T(\Delta\mathbf{u}^{(j)} + \delta\mathbf{u}_R) + \psi^2\,\Delta\lambda^{(j)\,2}\,\|\hat{\mathbf{f}}\|^2 - \Delta\ell^2. \tag{72.15}$$

The root with the smaller absolute value is chosen:

$$\delta\lambda = \frac{-b \pm \sqrt{b^2 - 4ac}}{2a}, \qquad \text{selecting } |\delta\lambda| \to \min. \tag{72.16}$$

When the discriminant is negative (the corrector cannot reach the arc-length sphere), the cylindrical formula (72.11) is used as a fallback.

72.5 Convergence Check and State Commit

At each corrector iteration:

$$\Delta\mathbf{u}^{(j+1)} = \Delta\mathbf{u}^{(j)} + \delta\mathbf{u}_R + \delta\lambda\,\delta\mathbf{u}_f, \qquad \Delta\lambda^{(j+1)} = \Delta\lambda^{(j)} + \delta\lambda. \tag{72.17}$$

Convergence is declared when the residual norm falls below the tolerance:

$$\frac{\|\mathbf{R}^{(j+1)}\|}{\|\hat{\mathbf{f}}\|} < \epsilon_r. \tag{72.18}$$

Upon convergence the material state is committed and the step result $(\lambda, \Delta\lambda, \Delta\ell)$ is stored. On divergence the material state is reverted and the step is reported as failed.

72.6 Implementation: `ArcLengthControl`

The `ArcLengthControl` struct in `IncrementalControl.hh` satisfies the existing `IncrementalControlPolicy` concept:

$$\texttt{scheme.apply}(p, \hat{\mathbf{f}}, \mathbf{f}_{\text{ext}}, \text{model}),$$

where $p \in [0, 1]$ is the load proportionality parameter. Internally, the control tracks:

- $\Delta\ell$: arc-length radius,
- ψ: scaling parameter,
- λ: current total load factor,
- $\Delta\mathbf{u}$: accumulated step displacement (PETSc Vec),
- $\Delta\lambda_{\text{prev}}$: last converged load increment (for sign determination),
- $\|\hat{\mathbf{f}}\|^2$: cached reference load norm.

The control manages a PETSc `Vec` for $\Delta\mathbf{u}$ with proper lifecycle (destructor, move semantics, deleted copy).

Variant enum. `ArcLengthVariant::Cylindrical` and `ArcLengthVariant::Spherical` select the constraint equation used in the corrector.

72.7 Implementation: `ArcLengthSolver`

The standalone `ArcLengthSolver` provides a complete SNES-free solver for tracing equilibrium paths. It manages its own PETSc vectors ($\mathbf{U}$, $\mathbf{R}$, $\hat{\mathbf{f}}$, $\mathbf{f}_{\text{ext}}$), matrix ($\mathbf{K}$), and KSP (direct LU via PCLU).

`solve_step()` implements the full algorithm:

1. Assemble tangent $\mathbf{K}_t$ at current state.
2. Solve $\mathbf{K}_t\,\delta\mathbf{u}_f = \hat{\mathbf{f}}$.
3. Tangent predictor: compute $\Delta\lambda_{\text{pred}}$ via (72.5), update $\Delta\mathbf{u}_{\text{pred}}$.
4. Corrector loop (up to 50 iterations):
   (a) Assemble residual $\mathbf{R}$ and tangent $\mathbf{K}_t$.
   (b) Solve (72.9) for $\delta\mathbf{u}_R$ and $\delta\mathbf{u}_f$.
   (c) Compute $\delta\lambda$ from constraint (cylindrical or spherical).
   (d) Update $\Delta\mathbf{u}$, $\Delta\lambda$, $\mathbf{U}$, λ.
   (e) Check convergence (72.18).
5. On convergence: commit material state.
6. On divergence: revert material state, report failure.

The result struct `ArcLengthResult` reports: convergence flag, λ, $\Delta\lambda$, $\Delta\ell$, iteration count, and final residual norm.

`solve_n_steps(int n)` provides a convenience wrapper that traces n steps sequentially with progress reporting.

72.8 Integration with the Sub-Model Evolver

For displacement-controlled sub-models driven by prescribed boundary conditions (the FE^2 context), the classical force-controlled arc-length formulation cannot be applied directly because the loading is not proportional force but imposed displacements. Instead, the `NonlinearSubModelEvolver` implements an *adaptive displacement sub-stepping* strategy triggered by the same auto-switch logic.

72.8.1 Auto-Switch Logic

Each sub-model tracks the number of consecutive SNES divergences. After $k \geq 3$ consecutive failures, the evolver switches to adaptive mode:

```
if (consecutive_divergences_ >= ARC_LENGTH_SWITCH_THRESHOLD) {
    use_arc_length_ = true;
}
```

Once active, the flag remains set for all subsequent steps. It can also be enabled manually via `enable_arc_length(true)`.

72.8.2 Adaptive Displacement Sub-Stepping

When `use_arc_length_` is active, the method `subsequent_solve_adaptive()` replaces the single full-step Newton call. The boundary condition increment is decomposed into sub-increments:

1. Save the previous imposed solution $\mathbf{u}^0_{\text{imp}}$.
2. Compute the full target $\mathbf{u}^1_{\text{imp}}$ from updated kinematics.
3. Set initial step fraction $\alpha = 0.5$, progress $p = 0$.
4. **While** $p < 1$:
   (a) Set target fraction $p^* = \min(p + \alpha,\ 1)$.
   (b) Interpolate: $\mathbf{u}_{\text{imp}} = (1 - p^*)\,\mathbf{u}^0_{\text{imp}} + p^*\,\mathbf{u}^1_{\text{imp}}$.
   (c) Run SNES from current $\mathbf{U}$.
   (d) **If converged**: commit state, $p \leftarrow p^*$, double step fraction $\alpha \leftarrow \min(2\alpha,\ 1 - p)$.
   (e) **If diverged**: revert state, halve step fraction $\alpha \leftarrow \alpha/2$. If $\alpha < 2^{-6}$ (minimum), report failure and exit.

This strategy captures the essential features of arc-length control (traversing through softening and limit points) in a displacement-controlled setting. The bisection limit of $2^{-6} = 1/64$ provides up to 64 sub-steps per increment, balancing robustness against computational cost. Step-size recovery (doubling α after convergence) avoids unnecessary sub-stepping in regions where the material response is smoother.

72.9 Summary

The arc-length implementation provides two complementary components:

1. `ArcLengthControl`: a lightweight constraint that plugs into the existing `IncrementalControlPolicy` framework for use within existing solvers.
2. `ArcLengthSolver`: a self-contained solver with its own PETSc infrastructure for standalone equilibrium-path tracing.

Both support cylindrical and spherical constraint variants, the Sherman–Morrison decomposition for the bordered system, and sign tracking for consistent traversal past limit and turning points. The implementation is general enough to work with any `Model<>` configuration, including the mixed concrete/rebar models introduced in Chapter 71.

Chapter 73

Two-Way FE^2 Coupling

Normative status. This chapter is retained as a historical design record. The current normative behaviour of the public multiscale API is documented in Chapter 82. Where terminology or behaviour differs, Chapter 82 prevails.

73.1 Introduction

The one-way downscaling framework (Chapters 63 –70) transfers kinematics from the global beam model to local continuum sub-models, but does not feed the sub-model response back into the beam analysis. This chapter develops the mathematical and computational framework for *two-way* FE^2 coupling, where the homogenised sub-model tangent modifies the beam section stiffness and the two scales are iterated until equilibrium is reached at both levels simultaneously.

73.2 FE^2 Framework

73.2.1 Scale Separation

Macro-scale. The global structural model consists of fibre-section beam elements with n_{gp} Gauss points along the axis. At each section Gauss point the generalised forces and deformations are:

$$\mathbf{s} = \{N,\, M_y,\, M_z,\, V_y,\, V_z,\, T\}^T, \qquad \mathbf{e} = \{\varepsilon_0,\, \kappa_y,\, \kappa_z,\, \gamma_y,\, \gamma_z,\, \theta'\}^T. \tag{73.1}$$

Micro-scale. Each critical section Gauss point is associated with a prismatic RVE (Representative Volume Element), modelled as a 3D continuum domain Ω_{RVE} with optional embedded rebar (Chapter 71). The RVE is driven by displacement boundary conditions derived from the macro-scale section kinematics via the Timoshenko kinematic field (Chapter **??**).

73.2.2 Homogenisation: Stress to Section Forces

The section forces are obtained by volume-averaging the RVE stress field and integrating over the cross-section:

$$N = \frac{1}{L_{\mathrm{RVE}}} \int_{\Omega_{\mathrm{RVE}}} \sigma_{zz}\, \mathrm{d}\Omega, \tag{73.2}$$

$$M_y = \frac{1}{L_{\mathrm{RVE}}} \int_{\Omega_{\mathrm{RVE}}} \sigma_{zz}\, x\, \mathrm{d}\Omega, \quad M_z = -\frac{1}{L_{\mathrm{RVE}}} \int_{\Omega_{\mathrm{RVE}}} \sigma_{zz}\, y\, \mathrm{d}\Omega, \tag{73.3}$$

$$V_y = \frac{1}{L_{\mathrm{RVE}}} \int_{\Omega_{\mathrm{RVE}}} \sigma_{yz}\, \mathrm{d}\Omega, \quad V_z = \frac{1}{L_{\mathrm{RVE}}} \int_{\Omega_{\mathrm{RVE}}} \sigma_{xz}\, \mathrm{d}\Omega, \tag{73.4}$$

where z is the beam axis direction and L_{RVE} is the RVE length. These integrals reduce to discrete summations over Gauss points with appropriate weights.

73.2.3 Section Forces from Boundary Reactions

An alternative—and more robust—approach extracts the section resultants directly from the assembled internal-force vector. After convergence of the RVE finite-element solve with displacement $\mathbf{u}$, the global internal-force vector is

$$\mathbf{f}_{\text{int}} = \bigcup_e \int_{\Omega_e} \mathbf{B}^T \boldsymbol{\sigma}(\mathbf{u}) \, \mathrm{d}\Omega. \tag{73.5}$$

At the constrained Face B boundary nodes, $\mathbf{f}_{\text{int}}$ gives the reaction forces. The section resultants follow from summation over all Face B nodes i:

$$\mathbf{F} = \sum_{i \in \text{Face B}} \mathbf{f}_i, \qquad \mathbf{M} = \sum_{i \in \text{Face B}} (\mathbf{x}_i - \mathbf{c}) \times \mathbf{f}_i, \tag{73.6}$$

where $\mathbf{c}$ is the section centroid. Rotating to the beam local frame via $\mathbf{R}$ gives N, V_y, V_z from $\mathbf{RF}$ and M_t, M_y, M_z from $\mathbf{RM}$.

This approach is preferred for the perturbation tangent loop because it evaluates the constitutive response from the displacement field at each perturbation step, avoiding reliance on stored material state which may be stale between non-committed SNES solves.

73.3 Homogenised Section Tangent

73.3.1 Perturbation-Based Tangent Computation

The 6×6 section tangent matrix $\mathbf{D}_{\text{hom}}$ relates infinitesimal increments of section deformations to section forces:

$$\delta \mathbf{s} = \mathbf{D}_{\text{hom}} \, \delta \mathbf{e}, \qquad D_{ij} = \frac{\partial s_i}{\partial e_j}. \tag{73.7}$$

Since the sub-model solver provides only the nonlinear response $\mathbf{s}(\mathbf{e})$, the tangent is computed by numerical (central) differentiation. For each section deformation component e_j, $j = 1, \ldots, 6$:

1. Perturb: $\mathbf{e}^+ = \mathbf{e} + h \, \mathbf{e}_j$, $\mathbf{e}^- = \mathbf{e} - h \, \mathbf{e}_j$.
2. Solve two nonlinear sub-models (or apply the kinematic field and re-homogenise without full Newton solve for small h).
3. Differentiate: $\mathbf{D}_{\text{hom}}(:, j) \approx (\mathbf{s}^+ - \mathbf{s}^-)/(2h)$.

The perturbation amplitude h should be chosen small enough for accuracy but large enough to avoid round-off:

$$h = \max(\epsilon_r \, |e_j|, \; h_{\min}), \tag{73.8}$$

where $\epsilon_r \approx 10^{-6}$ and $h_{\min} \approx 10^{-10}$.

For efficiency, the forward-difference approximation may be used when $\mathbf{s}(\mathbf{e})$ is already available at the current state:

$$\mathbf{D}_{\text{hom}}(:, j) \approx \frac{\mathbf{s}(\mathbf{e} + h \, \mathbf{e}_j) - \mathbf{s}(\mathbf{e})}{h}. \tag{73.9}$$

This halves the number of sub-model evaluations at the cost of first-order accuracy.

73.3.2 Structure of $\mathbf{D}_{\text{hom}}$

For a rectangular RC section under combined axial–flexural loading, the tangent has the block structure:

$$\mathbf{D}_{\text{hom}} = \begin{bmatrix} EA & ES_y & ES_z & 0 & 0 & 0 \\ ES_y & EI_y & EI_{yz} & 0 & 0 & 0 \\ ES_z & EI_{yz} & EI_z & 0 & 0 & 0 \\ 0 & 0 & 0 & GA_y & 0 & 0 \\ 0 & 0 & 0 & 0 & GA_z & 0 \\ 0 & 0 & 0 & 0 & 0 & GJ \end{bmatrix}, \tag{73.10}$$

where the axial–flexural block (3×3) is fully populated (coupling between N, M_y, M_z) and the shear–torsion block (3×3) is diagonal for symmetric sections. After cracking, the off-diagonal axial–flexural coupling terms grow as the neutral axis shifts.

73.4 Stiffness Injection into the Beam Element

The homogenised tangent $\mathbf{D}_{\text{hom}}$ replaces the fibre-based section tangent at the critical Gauss point. Two injection strategies are considered:

Strategy A: Section tangent override. The beam element's section stiffness at the critical Gauss point is replaced wholesale:

$$\mathbf{C}_t^{(k)} \leftarrow \mathbf{D}_{\text{hom}}^{(k)}, \qquad k \in \mathcal{G}_{\text{crit}}, \tag{73.11}$$

where $\mathcal{G}_{\text{crit}}$ is the set of critical Gauss points. The element stiffness is then re-integrated:

$$\mathbf{K}_e = \int_0^L \mathbf{B}^T \, \mathbf{C}_t(s) \, \mathbf{B} \, \mathrm{d}s, \tag{73.12}$$

where $\mathbf{C}_t(s)$ uses the fibre section tangent at non-critical Gauss points and $\mathbf{D}_{\text{hom}}$ at critical ones.

Strategy B: Homogenised material section adapter. A `HomogenizedMaterialSection` class that wraps the 6×6 tangent as a "virtual fibre section" and returns $\mathbf{D}_{\text{hom}}$ from `compute_section_tangent(` This approach integrates cleanly with the existing beam element template, which expects sections that satisfy the `BeamSectionConcept`.

73.5 Staggered Iteration Scheme

The FE^2 coupling is driven by a staggered iteration loop within each dynamic time step:

1. **Global solve**: Solve the macro-scale dynamic analysis for one time step, producing updated beam kinematics.
2. **Local solve**: For each critical element, update the RVE boundary conditions and solve the nonlinear sub-model.
3. **Homogenise**: Extract effective section forces and tangent from each sub-model via volume averaging and numerical differentiation.
4. **Inject**: Replace the beam section tangent at critical Gauss points with $\mathbf{D}_{\text{hom}}$.
5. **Convergence check**: Compare the sub-model section forces with the beam section forces at the critical Gauss points:
$$\frac{\|\mathbf{s}_{\text{beam}} - \mathbf{s}_{\text{sub}}\|}{\|\mathbf{s}_{\text{sub}}\| + \epsilon_0} < \epsilon_{\text{stag}}. \tag{73.13}$$
6. If not converged, return to step 1 with the updated section stiffness.

Convergence properties. The staggered scheme converges when the spectral radius of the coupling operator is less than unity. For quasi-static problems with moderate nonlinearity, 2–4 staggered iterations typically suffice. Under dynamic loading with explicit time integration at the macro-scale, a single staggered pass per step may be adequate if the time step is sufficiently small.

73.6 Planned Implementation Architecture

The two-way coupling builds on three new components and one modification to the existing codebase:

1. **`homogenize_tangent()`** in `HomogenizedSection.hh`: Performs 6 (or 12) perturbation solves on the sub-model to compute $\mathbf{D}_{\text{hom}}$ via central (or forward) differences. Returns a 6×6 Eigen matrix.

2. **`HomogenizedMaterialSection`**: An adapter class satisfying `BeamSectionConcept` that stores the 6×6 tangent and returns it from the section stiffness query. This allows seamless integration with `BeamElement`'s Gauss-point integration loop.

3. **Stiffness injection in `BeamElement`**: A method `override_section_tangent(gp_index, D_hom)` that replaces the fibre-based tangent at a specific Gauss point with the homogenised tangent. The beam element re-integrates using the overridden section for subsequent stiffness matrix and internal force computations.

4. **Staggered iteration loop**: Implemented in the main driver (e.g. `main_lshaped_multiscale.cpp`) as an outer loop wrapping the dynamic solver step and the sub-model updates. The loop tracks convergence via (73.13) and exits after a maximum number of staggered passes.

73.7 Summary

The two-way FE^2 coupling closes the multiscale loop:

- **Downward**: Beam kinematics → RVE boundary conditions → nonlinear sub-model solve.
- **Upward**: Sub-model stress → homogenised section forces and tangent → beam section stiffness override.
- **Iteration**: Staggered scheme iterates macro/micro solves until equilibrium at both scales.

Combined with the arc-length solver (Chapter 72) and mixedmodel reinforcement (Chapter 71), this framework enables full nonlinear multiscale analysis of reinforced-concrete structures through limit and softening regimes.

Chapter 74

Concurrent Multiscale Architecture: Diagnostic, Design, and Roadmap

Normative status. This chapter records the pre-publication architectural audit and roadmap. The current normative multiscale contracts and implemented semantics are given in Chapter 82.

74.1 Introduction

The previous chapters developed the building blocks of a concurrent multiscale framework for reinforced-concrete structures: a prismatic domain builder (Chapter **??**), a persistent nonlinear sub-model solver (Chapter 70), arc-length adaptive control (Chapter 72), and two-way coupling via homogenised tangent injection (Chapter 73). This chapter steps back to perform a comprehensive architectural audit of the current implementation, identifies rigidities and design debts, and lays out a detailed roadmap toward a flexible, SOLID-conformant, HPC-ready multiscale analysis framework suitable for publication and external use.

The discussion is organised as follows. Section 74.2 reviews the classical FE^2 method of Feyel and Chaboche and explains how our implementation adapts their ideas. Section 74.3 audits the current code against SOLID principles. Section 74.4 presents the target architecture. Section 74.5 catalogues reusable and hard-coded code. Section 74.6 addresses parallelism and HPC scalability. Section 74.7 provides a phased implementation plan.

74.2 The Classical FE^2 Method

74.2.1 Origin and Formulation

The FE^2 method was formalised by Feyel [1] and subsequently refined by Feyel and Chaboche [3] as a systematic framework for concurrent multiscale analysis. The fundamental idea is to replace the phenomenological constitutive law at each Gauss point of a macro-scale finite-element model by a boundary-value problem solved on a Representative Volume Element (RVE) at the micro-scale. The method proceeds as follows:

(i) **Localisation.** At a given macro-scale Gauss point with deformation gradient $\bar{\boldsymbol{F}}$ (or strain $\bar{\boldsymbol{\varepsilon}}$ in the small-strain case), the macro kinematic field is imposed as boundary conditions on the RVE domain Ω_μ:

$$\mathbf{u}(\mathbf{x}) = \bar{\boldsymbol{\varepsilon}} \cdot \mathbf{x} + \tilde{\mathbf{u}}(\mathbf{x}), \qquad \mathbf{x} \in \partial\Omega_\mu, \tag{74.1}$$

where $\tilde{\mathbf{u}}$ is a fluctuation field satisfying appropriate boundary conditions (linear displacement, periodic, or minimal kinematic).

(ii) **Micro-scale solve.** The RVE boundary-value problem is solved with the micro-scale material laws (plasticity, damage, cracking, etc.) to obtain the local stress field $\boldsymbol{\sigma}(\mathbf{x})$.

(iii) **Homogenisation.** The macro-scale stress is obtained by volume averaging over the RVE:

$$\bar{\boldsymbol{\sigma}} = \frac{1}{|\Omega_\mu|} \int_{\Omega_\mu} \boldsymbol{\sigma}(\mathbf{x}) \, \mathrm{d}\Omega. \tag{74.2}$$

(iv) **Consistent tangent.** The macro-scale algorithmic tangent $\bar{\mathbb{C}} = \partial\bar{\boldsymbol{\sigma}}/\partial\bar{\boldsymbol{\varepsilon}}$ is computed either by static condensation of the micro-scale tangent stiffness or by numerical perturbation. Feyel [1] derived the condensed tangent:

$$\bar{\mathbb{C}} = \frac{1}{|\Omega_\mu|} \left(\mathbf{K}_{bb} - \mathbf{K}_{bi} \, \mathbf{K}_{ii}^{-1} \, \mathbf{K}_{ib} \right), \tag{74.3}$$

where the subscripts b and i denote boundary and interior degrees of freedom, respectively.

The key contribution of Feyel and Chaboche was demonstrating that this concurrent scheme — nested FE solves — could be implemented within a single FE code, preserving the algorithmic tangent's consistency and thereby maintaining quadratic convergence of the macro-scale Newton iteration. They applied the method to metal–matrix composites with elasto-viscoplastic constituents, showing that the macro-scale response automatically captures complex nonlinear phenomena (damage localisation, strain gradients) that phenomenological models struggle to represent.

74.2.2 Extensions in the Literature

Since the original formulation, FE^2 has been extended in numerous directions:

- **Periodic boundary conditions** for textile composites (Miehe et al. [8]).
- **Computational homogenisation for shells and beams** using dimensional reduction at the micro-scale (Geers et al. [5]).
- **Second-order homogenisation** incorporating macro-scale strain gradients (Kouznetsova et al. [7]).
- **Adaptive FE^2** where the micro-scale solve is activated only at Gauss points exceeding a damage threshold (Ghosh et al. [6]).
- **HPC implementations** exploiting the embarrassingly parallel nature of the micro-scale solves (Feyel [2], Schröder [9]).

74.2.3 Adaptation in `fall_n`

Our implementation in `fall_n` adapts the original FE^2 framework with several domain-specific modifications tailored to structural engineering of RC frames under seismic loading:

(1) **Beam–continuum scale bridge.** Unlike the classical FE^2, where both scales operate in the same dimensionality (3D–3D or 2D–2D), our macro-scale is a one-dimensional beam element (Timoshenko 3D with fibre sections) and the micro-scale is a three-dimensional continuum RVE. The localisation step (74.1) is replaced by a *Timoshenko kinematic field* that maps section deformations $\mathbf{e} = \{\varepsilon_0, \kappa_y, \kappa_z, \gamma_y, \gamma_z, \theta'\}$ to displacement boundary conditions on the prismatic RVE faces (see Chapter **??**).

(2) **Boundary-reaction homogenisation.** Instead of volume-averaging the stress field (which requires access to the stored material state at all Gauss points), we extract section forces directly from the assembled internal-force vector at the RVE boundary face. This approach (Section 73.2.3) is more robust for the perturbation tangent loop, as it evaluates the constitutive response from the displacement field without relying on stored material state that may be stale between non-committed SNES solves.

(3) **Damage-triggered transition.** The micro-scale solve is activated only at beam elements exceeding a damage threshold (first steel fiber yield), implementing the adaptive FE^2 philosophy of Ghosh et al. [6]. A `TransitionDirector` monitors damage at every time step and triggers the transition seamlessly.

(4) **Persistent material state evolution.** Unlike one-shot homogenisation where the RVE is solved from scratch at each step, our `NonlinearSubModelEvolver` maintains the full material state (crack history, plastic strains, damage variables) across all time steps. This is essential for cyclic seismic loading, where unloading–reloading paths govern the hysteretic energy dissipation.

(5) **Mixed-model RVE.** The RVE employs a `MixedModel` combining `ContinuumElement` (KoBatheConcrete3D for the concrete matrix) and `TrussElement` (MenegottoPinto steel for embedded rebar), enabling a physically motivated representation of the reinforced cross-section.

(6) **Forward-difference perturbation tangent.** The consistent tangent (74.3) requires access to the condensed micro-scale stiffness matrix, which is not readily available when using PETSc's SNES (Newton) solver as a black box. Instead, we compute the 6×6 homogenised tangent $\mathbf{D}_{\text{hom}}$ by forward-difference perturbation of the section deformation components, using the boundary-reaction extraction at each perturbation step.

The principal contribution of our approach, relative to the classical FE^2, is the *beam–continuum dimensional bridge* with *boundary-reaction homogenisation*: by reducing the upscaling from a $6n_{\text{dof}}$-dimensional condensation to a six-component reaction summation, we achieve a computationally efficient coupling that avoids the full stiffness condensation and operates naturally within the PETSc solver framework.

74.3 Current Implementation Status

74.3.1 Component Inventory

Table 74.1 summarises the current multiscale components, their locations, and coupling directions.

74.3.2 Verification Test Results

The complete test suite (63 tests) passes after the boundary-reaction tangent implementation. The critical `evolver_advanced` test (21 sub-tests) reports:

$$\mathbf{D}_{\text{hom}} \text{ diagonal} = [1125.89,\ 6.51,\ 6.51,\ 72.09,\ 72.09,\ 3.52],$$
$$\mathbf{f}_{\text{hom}} = [0.114,\ 0,\ 0,\ \sim 0,\ \sim 0,\ 0],$$

confirming all six diagonal entries of the tangent are positive and the homogenised forces exhibit the expected axial-only response under pure tension.

Table 74.1: Multiscale component inventory.

Component	File	Role	Di
`MultiscaleCoordinator`	`MultiscaleCoordinator.hh`	Kinematic downscaling orchestrator	
`NonlinearSubModelEvolver`	`NonlinearSubModelEvolver.hh`	Persistent SNES-based RVE solver	
`section_forces_from_reactions()`	idem	Boundary-reaction homogenisation	
`compute_homogenized_tangent()`	idem	6×6 perturbation tangent	
`compute_homogenized_forces()`	idem	Section forces via `HomogenizedSection`	
`set_homogenized_tangent/forces`	`BeamElement.hh`	Injection into beam section	
Staggered iteration loop	`main_lshaped_multiscale.cpp`	Coupling iteration with relaxation	
`SubModelSolver`	`SubModelSolver.hh`	Stateless one-shot continuum solver	
`HomogenizedSection`	`HomogenizedSection.hh`	Stress-to-resultants projection	
`FieldTransfer / SubModelSpec`	`FieldTransfer.hh`	Kinematic field transfer	

74.3.3 SOLID Principles Audit

Despite passing all tests, the current implementation exhibits several design debts when evaluated against the SOLID principles of object-oriented design.

Single Responsibility Principle (SRP). `NonlinearSubModelEvolver` consolidates at least five distinct responsibilities in a single class:

- SNES-based nonlinear solving (residual/Jacobian callbacks, convergence control);
- Boundary condition transfer (writing imposed values from section kinematics);
- Material model construction (hard-coded `KoBatheConcrete3D` and `MenegottoPintoSteel`);
- VTK post-processing (mesh, Gauss cloud, crack plane export);
- Crack tracking and summary statistics.

Each of these is an independently evolving concern.

Open/Closed Principle (OCP). The material models used in the RVE are hard-coded:

Listing 74.1: Hard-coded material in `first_solve()`.

```
InelasticMaterial<KoBatheConcrete3D> mat_inst{fc_};
Material<Policy> mat{mat_inst, InelasticUpdate{}};
// ...
MenegottoPintoSteel steel_impl{rebar_E_, rebar_fy_, rebar_b_};
```

Extending the framework to alternative concrete models (e.g. CDPM2, Mazars damage) or steel models (Ramberg–Osgood, explicit cyclic) requires modifying the class internals.

Liskov Substitution Principle (LSP). `SubModelSolver` (stateless, per-step) and `NonlinearSubModelEvol` (stateful, persistent) do not share an interface, despite providing overlapping functionality: both solve a sub-model and extract results. Client code cannot substitute one for the other.

Interface Segregation Principle (ISP). The evolver exposes a monolithic interface that forces clients to depend on crack tracking, VTK export, and arc-length control even when they only require the solver or homogenisation functionality.

Dependency Inversion Principle (DIP). The staggered coupling loop in `main_lshaped_multiscale.cpp` (approximately 80 lines) depends directly on concrete types (`NonlinearSubModelEvolver`, `BeamElemT`, `COL_B`, `COL_H`). The coupling algorithm, convergence criterion, and relaxation strategy are all embedded in the application driver rather than abstracted behind stable interfaces.

74.4 Proposed Architecture: `MultiscaleAnalysis`

74.4.1 Design Overview

The target architecture decomposes the current monolith into a layered system of abstractions, as shown in Figure 74.1.



Figure 74.1: Proposed multiscale analysis architecture. Solid boxes are concrete classes; dashed boxes are interfaces (concepts or abstract classes).

74.4.2 Core Abstractions

`MultiscaleAnalysis`. The top-level orchestrator, analogous to `DynamicAnalysis` or `NonlinearAnalysis` in the existing codebase. It owns a `MultiscaleModel` and drives the staggered iteration loop. Its `step()` method encapsulates:

1. Global macro-scale solve (one time step or load increment).
2. Kinematics extraction at critical elements.
3. Parallel local-scale solves (sub-model updates).
4. Homogenisation and tangent injection.
5. Coupling convergence evaluation.

`MultiscaleModel`. An aggregation of model types: one `GlobalModel` (e.g. `Model<TimoshenkoBeam3D, ...>`) and a vector of `LocalModelAdapter` instances. The `MultiscaleModel` maintains the transition map (beam element → local model index) and provides the interface for kinematics transfer and result injection.

LocalModelAdapter. A type-erased or concept-constrained interface for local-scale solvers. Any class satisfying:

Listing 74.2: `LocalModelAdapter` concept (sketch).

```
template <typename T>
concept LocalModelAdapter = requires(T t,
    const SectionKinematics& kA,
    const SectionKinematics& kB,
    double time)
{
    { t.update_kinematics(kA, kB) };
    { t.solve_step(time) } -> SubModelSolverResult;
    { t.section_forces() } -> Eigen::Vector<double, 6>;
    { t.section_tangent(double) }
        -> Eigen::Matrix<double, 6, 6>;
    { t.revert_state() };
    { t.commit_state() };
};
```

can serve as a local model. This decouples the coupling framework from the specific solver implementation.

ScaleBridgePolicy. A strategy that controls the coupling direction:

- `OneWayCoupling`: downscaling only (kinematics → sub-model, no feedback).
- `TwoWayStaggered`: full staggered iteration with tangent injection.
- `TwoWayMonolithic`: assembles a combined system (future extension).

CouplingConvergence. An interface for convergence criteria:

Listing 74.3: Convergence criterion interface.

```
struct CouplingConvergence {
    virtual ~CouplingConvergence() = default;
    virtual bool converged(
        std::span<const Eigen::Matrix<double,6,6>> D_prev,
        std::span<const Eigen::Matrix<double,6,6>> D_curr
    ) const = 0;
};
```

Implementations include Frobenius-norm relative tolerance, energy-norm criteria, and force-equilibrium residuals.

RelaxationPolicy. Controls under-relaxation between staggered iterations:

- `ConstantRelaxation`: $\mathbf{D}^{(k+1)} = \omega\,\mathbf{D}_{\text{new}} + (1-\omega)\,\mathbf{D}^{(k)}$.
- `AitkenRelaxation`: adaptive ω from successive residual vectors.
- `AndersonAcceleration`: multi-secant acceleration using the last m iterates.

MaterialFactory. Decouples material construction from the solver:

Listing 74.4: Material factory concept.

```
struct ConcreteMaterialFactory {
    virtual Material<ThreeDimensionalMaterial>
```

```
        create_concrete() const = 0;
};
struct RebarMaterialFactory {
    virtual Material<UniaxialMaterial>
        create_rebar(double area) const = 0;
};
```

HomogenisationStrategy. Controls how micro-scale results are upscaled:

- `BoundaryReactionHomogenisation`: current approach (sum nodal reactions at Face B).
- `VolumeAveragingHomogenisation`: classical approach (74.2).
- `EnergyBasedHomogenisation`: Hill–Mandel energy equivalence.

74.5 Code Reusability Assessment

74.5.1 Directly Reusable Components

The following components have clean interfaces and correct implementations that can be adopted with minimal change:

1. **`section_forces_from_reactions()`** — Algorithm: assemble $\mathbf{f}_{\text{int}}$ from displacement, read Face B nodal forces, sum into section resultants. Generic and material-independent.
2. **Perturbation tangent loop** — The forward-difference scheme in `compute_homogenized_tangent()` is independent of the material model; it only requires a callable that maps kinematics to section forces.
3. **`SectionKinematics` + `compute_boundary_displacements()`** — The kinematic transfer from beam section deformations to 3D displacement BCs is well isolated in `FieldTransfer.hh`.
4. **`MultiscaleSubModel struct`** — A clean data container holding domain, grid, kinematics, and boundary conditions.
5. **Section override mechanism** — `BeamElement::set_homogenized_tangent/forces()` and the `tangent_override_` / `force_override_` in `MaterialSection` implement a clean Strategy/Decorator pattern for FE^2 injection.
6. **SNES callbacks** — `FormResidual()` and `FormJacobian()` are static functions parameterised by a `Context` struct; they can be reused in any PETSc-SNES-based solver.

74.5.2 Hard-Coded Dependencies Requiring Refactoring

1. **Material construction in `first_solve()`.** `KoBatheConcrete3D` and `MenegottoPintoSteel` are instantiated directly. Should be replaced by injected factories.
2. **Staggered loop in `main()`.** Approximately 80 lines of coupling algorithm embedded in the application driver, including convergence criterion, relaxation factor, and "lagged" coupling logic.
3. **`extract_beam_kinematics()` lambda.** Defined locally in `main_lshaped_multiscale.cpp`; should be a member of `MultiscaleModel` or a reusable free function.
4. **`SubModelSolver` vs. `NonlinearSubModelEvolver`.** Two classes with $> 60\%$ duplicated code (material setup, BCs, result extraction). Should be unified under a common interface.

5. **`homogenize()` in `HomogenizedSection.hh`.** Assumes uniform stress distribution across the section — not extensible to gradient-based or energy-based homogenisation. Should become a strategy.

6. **Geometry coupling to `PrismaticGrid`.** The evolver assumes a prismatic grid with `PrismFace::MinZ/MaxZ` faces. General RVE geometries (e.g. from Gmsh imports) would require a different boundary identification strategy.

74.6 Parallelism and HPC Scalability

74.6.1 Current Parallelism

The current implementation exploits parallelism at two levels:

- **BC computation:** `MultiscaleCoordinator::build_sub_models()` uses OpenMP for the embarrassingly parallel boundary displacement evaluation (Phase 2 of the coordinator).
- **Sub-model independence:** Each sub-model's SNES solver uses `PETSC_COMM_SELF` (sequential per sub-model), but multiple sub-models can be solved concurrently.

74.6.2 Scalability Bottlenecks

1. **Serial perturbation tangent.** The six perturbation solves in `compute_homogenized_tangent()` are executed sequentially. Since each perturbation is independent (all start from the same baseline state), they are trivially parallelisable.

2. **Serial sub-model evolution.** The sub-model loop in the staggered iteration executes sequentially. For N_s sub-models, this misses a factor-N_s speedup.

3. **Global–local communication.** Currently implemented via shared-memory access (kinematics extraction and tangent injection occur through direct pointer dereference). Distributed-memory parallelism would require explicit communication of kinematics and tangent data.

74.6.3 HPC Strategy

Level 1: Thread-level parallelism. Use `std::jthread` or OpenMP tasks for concurrent sub-model solves. Each sub-model owns its own PETSc objects (`PETSC_COMM_SELF`), so no synchronisation is needed during the SNES solve.

Level 2: MPI sub-communicators. For large-scale analyses with N_s sub-models, partition MPI ranks into sub-communicators:

$$\texttt{MPI_Comm_split}(\texttt{world},\ \text{rank mod } N_s,\ \text{rank},\ \&\text{sub_comm}). \tag{74.4}$$

Each sub-communicator drives one sub-model's PETSc solve in parallel. The global model runs on a dedicated communicator (or the full world communicator with the sub-model ranks idle during the global phase).

Level 3: Perturbation parallelism. The six perturbation directions can be distributed across MPI ranks or OpenMP tasks:

Listing 74.5: Parallelised perturbation tangent.

```
#pragma omp parallel for schedule(static)
for (int j = 0; j < 6; ++j) {
    // Each thread has its own copy of U, imposed_solution
```

```
    auto [sp, ok] = perturb_and_solve(j, h_pert);
    if (ok) D_hom.col(j) = (sp - s0) / h_pert;
}
```

This requires thread-local copies of the PETSc vectors and SNES objects, which can be pre-allocated in a pool.

Level 4: GPU offloading. For sub-models with $> 10{,}000$ degrees of freedom, PETSc's GPU backend (`MatSetType(MATAIJCUSPARSE)`) can accelerate the sparse linear algebra. This is transparent to the sub-model solver if the matrix and vector types are set via the options database.

Proposed architecture for HPC:

Listing 74.6: HPC-aware `MultiscaleAnalysis`.

```
class MultiscaleAnalysis {
    MPI_Comm global_comm_;          // all ranks
    MPI_Comm macro_comm_;           // global model ranks
    std::vector<MPI_Comm> micro_comms_; // per sub-model

    void step(double dt) {
        // 1. Global solve on macro_comm_
        // 2. Broadcast kinematics to micro_comms_
        // 3. Parallel local solves (each on micro_comm_)
        // 4. Gather homogenised responses
        // 5. Inject and check convergence
    }
};
```

74.7 Phased Implementation Plan

The refactoring is organised into eight phases, ordered by dependency and decreasing impact. Each phase is designed to maintain a green test suite throughout.

74.7.1 Phase 0: Build System Cleanup

- **P0.1:** Remove the 20 duplicate `fall_n_seismic_v2`–`v21` targets. Replace with a single parameterised executable. *Impact:* ∼35% build-time reduction.
- **P0.2:** Add precompiled headers (PCH) for Eigen, PETSc, VTK, and STL containers. *Impact:* ∼15−20% reduction.
- **P0.3:** Introduce explicit template instantiations for `Model<>`, `ContinuumElement<>`, `NonlinearAnalysis` in dedicated `.cpp` files, with `extern template` declarations in headers. *Impact:* ∼20−30% reduction.
- **P0.4:** Modularise `header_files.hh` into tier-specific headers (`fall_n/core.hh`, `fall_n/materials.hh`, etc.).

74.7.2 Phase 1: `LocalModelAdapter` Interface

- Define the `LocalModelAdapter` concept (or abstract base class).
- Refactor `NonlinearSubModelEvolver` to satisfy the concept.

- Deprecate `SubModelSolver` (stateless variant); provide a thin adapter if backward compatibility is required.
- All existing tests must pass without modification.

74.7.3 Phase 2: `MaterialFactory` Injection

- Extract material construction into factory interfaces (`ConcreteMaterialFactory`, `RebarMaterialFactor`
- Provide default implementations for KoBatheConcrete3D and MenegottoPinto.
- Inject the factory into the local model adapter via constructor parameter.
- Extend with at least one alternative material (e.g. linear-elastic concrete for testing) to validate OCP.

74.7.4 Phase 3: `MultiscaleModel` Aggregation

- Create a `MultiscaleModel` class that owns the global model and a vector of `LocalModelAdapter` instances.
- Implement the transition map (element ID $\rightarrow$ local model index).
- Move `extract_beam_kinematics()` from the main driver into `MultiscaleModel`.
- Provide `inject_homogenized_response()` as a member function.

74.7.5 Phase 4: `MultiscaleAnalysis` Orchestrator

- Create `MultiscaleAnalysis` class that owns a `MultiscaleModel` and orchestrates the staggered loop.
- Move the 80-line staggered iteration from `main_lshaped_multiscale.cpp` into `MultiscaleAnalysis::st`
- Accept `ScaleBridgePolicy`, `CouplingConvergence`, and `RelaxationPolicy` as constructor parameters.
- The main driver reduces to $\sim$20 lines of configuration plus `analysis.run()`.

74.7.6 Phase 5: Coupling Strategy Injection

- Implement `OneWayCoupling` and `TwoWayStaggeredCoupling` as `ScaleBridgePolicy` instances.
- Implement `FrobeniusConvergence`, `EnergyConvergence` as `CouplingConvergence` instances.
- Implement `ConstantRelaxation`, `AitkenRelaxation` as `RelaxationPolicy` instances.
- Verify that switching between strategies requires only configuration changes (no recompilation of the coupling core).

74.7.7 Phase 6: Inter-Sub-Model Parallelism

- Parallelise sub-model solves within `MultiscaleAnalysis::step()` using `std::jthread` (shared-memory) or `MPI_Comm_split` (distributed-memory).
- Parallelise the six perturbation directions in the tangent computation.
- Benchmark scaling: $N_s = 1, 2, 4, 8$ sub-models on 8 cores.

74.7.8 Phase 7: Homogenisation Strategy

- Refactor `homogenize()` into a `HomogenisationStrategy` interface.
- Implement boundary-reaction and volume-averaging variants.
- Verify consistency: both strategies must yield the same section forces for elastic material.

74.7.9 Phase 8: Header Modularisation and Compilation

- Decompose `header_files.hh` into module-specific aggregation headers.
- Create a CMake OBJECT library (`fall_n_core`) with explicit template instantiations.
- All executables link against the OBJECT library.
- Evaluate C++20 modules readiness (GCC 15 experimental support).

74.8 Summary

The `fall_n` multiscale framework successfully implements the core FE^2 coupling loop with verified two-way interaction between beam and continuum scales. The main contribution relative to the classical Feyel–Chaboche method is the *beam–continuum dimensional bridge with boundary-reaction homogenisation*, which provides a computationally efficient alternative to full stiffness condensation.

The architectural audit reveals that the current implementation, while functionally correct, concentrates too many responsibilities in `NonlinearSubModelEvolver` and hard-codes material choices and coupling parameters. The proposed refactoring into `MultiscaleAnalysis` → `MultiscaleModel` → `LocalModelAdapter` with injected strategies for coupling, convergence, relaxation, material, and homogenisation will yield a flexible, extensible, and HPC-ready framework aligned with SOLID principles and suitable for publication as a reusable library for the structural engineering community.

Chapter 75

Build System Diagnosis and Compilation Optimisation

75.1 Motivation

A full rebuild of `fall_n` with eight parallel jobs (`ninja -j8`) on a modern desktop (AMD Ryzen 7, 32 GB RAM) takes approximately 50 minutes to generate 115 Ninja targets (28 executables and 65 tests, plus object files). This severely limits the developer iteration cycle: a single-header edit that touches `header_files.hh` forces recompilation of every translation unit.

This chapter diagnoses the root causes of the excessive compilation time, quantifies the contribution of each factor, and proposes a concrete mitigation plan.

75.2 Build System Overview

The build system uses CMake with the Ninja generator. The main `CMakeLists.txt` defines:

- **28 executable targets**, including `fall_n_main`, `fall_n_seismic_main`, `fall_n_lshaped_multiscale`, and 20 variants `fall_n_seismic_v2` through `fall_n_seismic_v21`.
- **65 test targets** registered via the custom `fall_n_add_test()` macro, each compiling a separate test source file.
- **No static or shared library targets:** the codebase is entirely header-only, with all template definitions visible in every translation unit.

75.3 Root Cause Analysis

75.3.1 Monolithic Header: `header_files.hh`

The file `header_files.hh` includes approximately 100 project headers covering *every* module:

Listing 75.1: Excerpt from `header_files.hh`.

```
// Core
#include "src/geometry/entities/Node.hh"
#include "src/geometry/entities/Vertex.hh"
// ... 40+ geometry/element headers

// Materials
#include "src/materials/concrete/KoBatheConcrete3D.hh"
#include "src/materials/steel/MenegottoPintoSteel.hh"
// ... 15+ material headers
```

```

// Model, Analysis, VTK
#include "src/model/Model.hh"
#include "src/analysis/NonlinearAnalysis.hh"
#include "src/vtk/VtkWriter.hh"
// ... 20+ analysis/vtk headers

// Reconstruction
#include "src/reconstruction/SubModelSolver.hh"
#include "src/reconstruction/NonlinearSubModelEvolver.hh"
#include "src/reconstruction/HomogenizedSection.hh"
```

Every test and executable that includes `header_files.hh` must parse and instantiate templates from all 100+ headers. Since most tests depend on only a small subset of the library, the vast majority of this parsing is wasted.

Estimated impact. Header parsing and template instantiation account for approximately 70−80% of compilation time per translation unit. With 93 TUs (28 executables + 65 tests), the aggregate waste is substantial.

75.3.2 Duplicate Seismic Executables

Twenty targets (`fall_n_seismic_v2` through `fall_n_seismic_v21`) all compile the same source file, `main_multiscale_seismic.cpp`, with different preprocessor definitions:

Listing 75.2: CMakeLists.txt excerpt.

```
add_executable(fall_n_seismic_v2  main_multiscale_seismic.cpp)
target_compile_definitions(fall_n_seismic_v2  PRIVATE SEISMIC_V2)
add_executable(fall_n_seismic_v3  main_multiscale_seismic.cpp)
target_compile_definitions(fall_n_seismic_v3  PRIVATE SEISMIC_V3)
# ... v4 through v21
```

Each variant triggers a full compilation of a large translation unit (`main_multiscale_seismic.cpp`) that includes `header_files.hh`. Thus, the same 100+ headers are parsed and instantiated 20 times, producing nearly identical object files.

Estimated impact. These 20 targets represent ∼35% of the total build time. They can be consolidated into a single executable with a runtime parameter.

75.3.3 No Precompiled Headers (PCH)

CMake supports precompiled headers via `target_precompile_headers()`. The current project does not use this feature. Third-party headers (PETSc, Eigen, VTK, `<algorithm>`, `<vector>`, etc.) are re-parsed in every TU.

Estimated impact. PCH for stable third-party headers typically reduces per-TU compilation time by 15−25%.

75.3.4 No Explicit Template Instantiation

The library's template-heavy design (e.g. `Model<ElementT, MeshT>`, `ContinuumElement<Material, Kinematics, Quadrature>`) means that every translation unit that uses these templates instantiates them independently. Identical instantiations (e.g. `ContinuumElement<KoBathe, SmallStrain, GaussLegendre>`) occur in multiple TUs, leading to redundant compilation that is only discarded at link time.

Estimated impact. Explicit instantiation with `extern template` declarations can reduce compilation time by 20−30% for template-heavy codebases.

75.4 Mitigation Plan

Table 75.1 summarises the proposed optimisation steps in priority order, with estimated build-time reductions and implementation effort.

Table 75.1: Build optimisation steps, ordered by impact.

Step	Optimisation	Reduction	Effort	Risk
1	Consolidate seismic variants	∼35%	Low	None
2	Add PCH (Eigen, PETSc, VTK, STL)	∼15%	Low	None
3	Explicit template instantiation	∼25%	Med.	Moderate[a]
4	Modularise `header_files.hh`	∼15%	High	Low
5	CMake OBJECT library	∼10%	Med.	Low
6	C++20 modules (experimental)	TBD	High	High[b]

[a] Requires maintaining explicit instantiation lists in sync with the template usage across TUs. Missing an instantiation causes a linker error.
[b] GCC 15 offers partial C++20 module support; not yet production-ready.

75.4.1 Step 1: Consolidate Seismic Variants

Replace 20 separate executables with a single parameterised executable that selects the variant at runtime:

Listing 75.3: Proposed unified seismic driver.

```
int main(int argc, char* argv[]) {
    int variant = 2;   // default
    if (argc > 1) variant = std::atoi(argv[1]);

    switch (variant) {
        case 2:  run_seismic_v2();  break;
        case 3:  run_seismic_v3();  break;
        // ...
        default:
            std::cerr << "Unknown variant: "
                      << variant << "\n";
            return 1;
    }
}
```

If compile-time configuration is truly required, use `if constexpr` with a single `-DSEISMIC_VERSION=N` define, building only the needed variant. The CMake target reduces to one:

```
add_executable(fall_n_seismic main_multiscale_seismic.cpp)
target_compile_definitions(fall_n_seismic PRIVATE
    SEISMIC_VERSION=${SEISMIC_VERSION})
```

75.4.2 Step 2: Precompiled Headers

Add PCH for the heaviest third-party headers:

Listing 75.4: CMake PCH setup.

```cmake
# In CMakeLists.txt
set(PCH_HEADERS
    <Eigen/Dense>
    <Eigen/Sparse>
    <petsc.h>
    <petscsnes.h>
    <petscmat.h>
    <vtkSmartPointer.h>
    <vtkUnstructuredGrid.h>
    <algorithm>
    <vector>
    <array>
    <memory>
    <cmath>
)

# Apply to all fall_n targets
foreach(tgt ${FALL_N_ALL_TARGETS})
    target_precompile_headers(${tgt} PRIVATE ${PCH_HEADERS})
endforeach()
```

75.4.3 Step 3: Explicit Template Instantiation

Identify the most commonly instantiated template combinations and provide explicit instantiation definitions in dedicated `.cpp` files:

Listing 75.5: Explicit instantiation example.

```cpp
// file: src/model/Model_instantiations.cpp
#include "header_files.hh" // only this TU pays full cost

// Explicit instantiation definitions
template class Model<
    TimoshenkoBeam3D<GaussLobatto<3>>,
    DMPlexMesh>;

template class Model<
    ContinuumElement<
        Material<ThreeDimensionalMaterial>,
        SmallStrainKinematics,
        GaussLegendre<2,2,2>>,
    DMPlexMesh>;
```

In the headers, add `extern template` declarations to suppress implicit instantiation:

Listing 75.6: `extern template` in header.

```cpp
// In Model.hh, at the bottom:
#ifdef FALL_N_EXTERN_TEMPLATES
extern template class Model<
    TimoshenkoBeam3D<GaussLobatto<3>>,
    DMPlexMesh>;
// ... other common instantiations
#endif
```

A new CMake OBJECT library compiles the instantiation TUs once, and all executables link against it.

75.4.4 Step 4: Header Modularisation

Decompose `header_files.hh` into tiered headers:

Header	Contents
`fall_n/core.hh`	Node, Vertex, BasisFunctions, Quadrature
`fall_n/materials.hh`	Material, KoBathe, Menegotto, ...
`fall_n/elements.hh`	ContinuumElement, BeamElement, TrussElement
`fall_n/model.hh`	Model, DofHandler, BCs
`fall_n/analysis.hh`	NonlinearAnalysis, DynamicAnalysis
`fall_n/reconstruction.hh`	SubModel*, FieldTransfer, Evolver
`fall_n/vtk.hh`	VtkWriter, VtkPatch, ...
`fall_n/all.hh`	Includes all of the above (backward compat.)

Test files include only the tier they need:

```
// test_quadrature.cpp
#include "fall_n/core.hh"    // 10 headers instead of 100
```

This change requires updating all 65+ test files and 28+ main files, so it is best done incrementally.

75.4.5 Step 5: CMake OBJECT Library

Create a shared compilation target:

Listing 75.7: CMake OBJECT library.

```
add_library(fall_n_lib OBJECT
    src/model/Model_instantiations.cpp
    src/elements/Element_instantiations.cpp
    src/analysis/Analysis_instantiations.cpp
)
target_precompile_headers(fall_n_lib PRIVATE ${PCH_HEADERS})

# All executables link to the OBJECT library
foreach(tgt ${FALL_N_ALL_TARGETS})
    target_link_libraries(${tgt} PRIVATE fall_n_lib)
endforeach()
```

This ensures that common template instantiations are compiled exactly once.

75.4.6 Step 6: C++20 Modules (Exploratory)

GCC 15 provides experimental support for C++20 named modules. A future step could convert the most include-heavy components into modules:

```
// fall_n.core.cppm
export module fall_n.core;
export import :node;
export import :vertex;
export import :quadrature;
```

This is not recommended until the GCC/Clang module build system integration (via CMake 3.28+ `CXX_MODULES`) is stable.

75.5 Expected Cumulative Impact

Applying Steps 1–5 in sequence is expected to reduce the full build time as follows:

$$\underbrace{50\text{ min}}_{\text{current}} \xrightarrow[\text{Step 1}]{-35\%} 32\text{ min} \xrightarrow[\text{Step 2}]{-15\%} 27\text{ min} \xrightarrow[\text{Step 3}]{-25\%} 20\text{ min} \xrightarrow[\text{Step 4}]{-15\%} 17\text{ min} \xrightarrow[\text{Step 5}]{-10\%} 15\text{ min}$$

A ∼70% **overall reduction** is achievable with moderate engineering effort. Incremental builds (single-header changes) would benefit even more, as PCH and modularised headers eliminate the re-parsing of unrelated headers.

75.6 Summary

The current build system's excessive compilation time is attributable to four primary causes: a monolithic uber-header, 20 duplicate seismic targets, absence of precompiled headers, and redundant template instantiation across 93 translation units.

A five-step optimisation plan — consolidating seismic variants, adding PCH, introducing explicit template instantiations, modularising the header hierarchy, and creating a CMake OBJECT library — can reduce full build times from ∼50 minutes to ∼15 minutes.

These improvements require no changes to the library's public API or test expectations; they are purely internal build-system and compilation-model optimisations.

Chapter 76

Multiscale Architecture Refactoring: Implementation

Normative status. This chapter documents an earlier refactoring milestone. It remains useful as implementation provenance, but the authoritative description of the current public multiscale subsystem is Chapter 82.

76.1 Introduction

Chapter 74 identified six rigidities in the FE^2 coupling implementation and proposed a nine-phase refactoring plan to achieve a SOLID-conformant, extensible, and HPC-ready architecture. Chapter 75 diagnosed the root causes of the excessive compilation time and proposed a mitigation plan. This chapter documents the implementation of the first seven phases of that plan:

Phase 0: Build system cleanup: consolidation of 20 duplicate seismic targets.

Phase 1: `LocalModelAdapter` concept and type-erased handle.

Phase 2: `MaterialFactory` injection into the sub-model solver.

Phase 3: `MultiscaleModel` aggregation class.

Phase 4: `CouplingStrategy` interfaces and `MultiscaleAnalysis` orchestrator.

Phase 5: `HomogenisationStrategy` for switchable upscaling.

All code changes presented here compile under GCC 15.2 with `-Werror` enabled. The full test suite (63 CTest cases) continues to pass after each phase.

Section 76.2 covers the build system cleanup. Sections 76.3 through 76.8 present each architectural phase with design rationale, code listings, and SOLID analysis. Section 76.7 presents the `MultiscaleAnalysis` orchestrator that absorbs the staggered coupling loop. Section 76.9 provides a comprehensive discussion of design decisions and trade-offs.

76.2 Phase 0.1: Build System Cleanup

76.2.1 Problem: 20 Duplicate Seismic Targets

As diagnosed in Chapter 75, the CMake build system contained 20 near-identical executable targets (`fall_n_seismic_v2` through `fall_n_seismic_v21`), each compiling the same source file (`main_multiscale_seismic.cpp`) with a different preprocessor definition. Each target incurred the full parse cost of `header_files.hh` (∼100 project headers), resulting in ∼35% of the total build time spent on redundant compilation.

76.2.2 Solution: Target Consolidation

All 20 duplicate target blocks were removed from `CMakeLists.txt`. The single pre-existing target `fall_n_seismic` is retained; variant selection is performed at runtime via command-line arguments.

Impact.

- Ninja targets: 115 → 88 (−23%).
- Build time: estimated ∼35% reduction for full rebuilds.
- No test regressions: 63/63 CTest cases pass.

76.3 Phase 1: `LocalModelAdapter` Concept

76.3.1 Design Rationale

The `NonlinearSubModelEvolver` class (Chapter 70) is the sole concrete sub-model solver. However, the multiscale analysis framework should be open to alternative sub-model types (e.g. a future `LinearSubModel` for elastic columns, or a `ReducedOrderModel` for computational efficiency).

The design choice between a C++20 concept and a classical abstract base class (ABC) was guided by consistency with the existing codebase:

- `FiniteElement` (`src/elements/FiniteElementConcept.hh`) uses a concept.
- `SteppableSolver` (`src/analysis/SteppableSolverConcept.hh`) uses a concept.
- `IncrementalControlPolicy` (`src/analysis/IncrementalControl.hh`) uses a concept.
- `DamageCriterion` (`src/analysis/DamageCriterion.hh`) uses an ABC.

Concepts are preferred for interfaces where compile-time dispatch suffices. Since the inner staggered loop processes sub-models of homogeneous type (all are `NonlinearSubModelEvolver`), a concept avoids the overhead of virtual dispatch. For the heterogeneous case (mixing different solver types in one container), a type-erased handle is provided.

76.3.2 The `LocalModelAdapter` Concept

The concept is defined in `src/reconstruction/LocalModelAdapter.hh`:

Listing 76.1: C++20 concept for local sub-model solvers.

```
template <typename T>
concept LocalModelAdapter = requires(
    T& t,
    const SectionKinematics& kin,
    double width, double height, double h_pert, double time)
{
    { t.update_kinematics(kin, kin) };
    { t.solve_step(time) };
    { t.section_tangent(width, height, h_pert) }
        -> std::convertible_to<Eigen::Matrix<double, 6, 6>>;
    { t.section_forces(width, height) }
        -> std::convertible_to<Eigen::Vector<double, 6>>;
    { t.commit_state() };
    { t.revert_state() };
```

```
    { t.parent_element_id() }
        -> std::convertible_to<std::size_t>;
};
```

Each required expression maps to a well-defined responsibility:

update_kinematics Localisation: imposes macro-scale beam kinematics as Dirichlet BCs on the sub-model.

solve_step Solves the nonlinear boundary-value problem from the current converged state.

section_tangent Computational homogenisation: returns the 6×6 tangent $\mathbf{D}_{\text{hom}} = \partial \mathbf{s} / \partial \mathbf{e}$ via perturbation.

section_forces Returns the upscaled section forces $\mathbf{s} = [N, M_y, M_z, V_y, V_z, M_t]^\top$.

commit_state / revert_state Transaction semantics for irreversible constitutive state (damage, plasticity).

parent_element_id Identifies the owning beam element in the global model.

76.3.3 Type-Erased Handle: `LocalModelHandle`

For heterogeneous containers (`std::vector<LocalModelHandle>`), a type-erased wrapper follows the Concept/Model/Handle pattern established by `FEM_Element` (`src/elements/FEM_Element.hh`):

Listing 76.2: Type-erased handle (abridged).

```
class LocalModelHandle {
    struct Concept {  // pure virtual interface
        virtual ~Concept() = default;
        virtual void update_kinematics(...) = 0;
        virtual void solve_step(double) = 0;
        virtual Eigen::Matrix<double,6,6>
            section_tangent(double, double, double) = 0;
        virtual Eigen::Vector<double,6>
            section_forces(double, double) = 0;
        virtual void commit_state() = 0;
        virtual void revert_state() = 0;
        virtual std::size_t parent_element_id() const = 0;
    };

    template <LocalModelAdapter T>
    struct Model final : Concept {
        T adapter_;
        // ... delegates all calls to adapter_
    };

    std::unique_ptr<Concept> pimpl_;
public:
    template <LocalModelAdapter T>
    LocalModelHandle(T adapter);  // implicit conversion

    // Move-only (sub-models own PETSc resources)
    LocalModelHandle(LocalModelHandle&&) noexcept = default;
    LocalModelHandle(const LocalModelHandle&) = delete;

    // Forwarding interface mirrors the concept
    void update_kinematics(const SectionKinematics&,
```

```
                                const SectionKinematics&);
    void solve_step(double);
    auto section_tangent(double, double, double = 1e-6)
        -> Eigen::Matrix<double,6,6>;
    // ...
};
```

The handle is *move-only* because sub-model solvers own PETSc objects (DM, SNES, Vec) that cannot be trivially copied. The implicit converting constructor allows any `LocalModelAdapter`-satisfying type to be stored in a `std::vector<LocalModelHandle>` without explicit wrapping.

76.3.4 Adapting `NonlinearSubModelEvolver`

The evolver was modified to satisfy the concept:

1. **Public aliases:** New methods `section_tangent()` and `section_forces()` delegate to the existing private methods `compute_homogenized_tangent()` and `compute_homogenized_forces()`, preserving backward compatibility:

Listing 76.3: Public aliases on the evolver.

```
// LocalModelAdapter concept conformance
[[nodiscard]] Eigen::Matrix<double, 6, 6>
section_tangent(double width, double height,
                double h_pert = 1.0e-6) {
    return compute_homogenized_tangent(width, height, h_pert);
}

[[nodiscard]] Eigen::Vector<double, 6>
section_forces(double width, double height) {
    return compute_homogenized_forces(width, height);
}
```

2. **Public state management:** Methods `commit_state()` and `revert_state()` were moved from the private section to public. `commit_state()` traverses the DM mesh and calls `commit_material_state()` on each element. `revert_state()` calls `revert_material_state()` to discard the trial state after a perturbation solve.

3. **Static assertion:** A compile-time check at the end of the header ensures concept satisfaction is maintained as the class evolves:

Listing 76.4: Compile-time concept check.

```
static_assert(
    LocalModelAdapter<NonlinearSubModelEvolver>,
    "NonlinearSubModelEvolver must satisfy "
    "the LocalModelAdapter concept");
```

76.4 Phase 2: `MaterialFactory` Injection

76.4.1 Problem: Hardcoded Constitutive Models

The `first_solve()` method of `NonlinearSubModelEvolver` directly instantiated `KoBatheConcrete3D` and `MenegottoPintoSteel` material models:

Listing 76.5: Hardcoded material construction (before).

```
// In first_solve():
InelasticMaterial<KoBatheConcrete3D> mat_inst{fc_};
Material<ThreeDimensionalMaterial> mat{mat_inst, InelasticUpdate{}};
// ...
MenegottoPintoSteel steel_impl{200000.0, 420.0, 0.01};
InelasticMaterial<MenegottoPintoSteel> steel_inst{std::move(steel_impl)
    };
Material<UniaxialMaterial> steel_mat{std::move(steel_inst),
    InelasticUpdate{}};
```

This violated the Open–Closed Principle (OCP): using a different concrete model (e.g. `Mazars3D`) or rebar steel (e.g. `BilinearSteel`) required modifying the evolver source.

76.4.2 Solution: Abstract Factory Pattern

Two abstract factory interfaces are defined in `src/reconstruction/MaterialFactory.hh`, following the `DamageCriterion` ABC pattern from `src/analysis/DamageCriterion.hh`:

Listing 76.6: Material factory ABCs.

```
struct ConcreteMaterialFactory {
    virtual ~ConcreteMaterialFactory() = default;
    virtual Material<ThreeDimensionalMaterial> create() const = 0;
    virtual std::unique_ptr<ConcreteMaterialFactory> clone() const = 0;
};

struct RebarMaterialFactory {
    virtual ~RebarMaterialFactory() = default;
    virtual Material<UniaxialMaterial> create() const = 0;
    virtual std::unique_ptr<RebarMaterialFactory> clone() const = 0;
};
```

Default implementations encapsulate the previously hardcoded construction:

Listing 76.7: Default factory implementations.

```
class KoBatheConcreteMaterialFactory final
    : public ConcreteMaterialFactory
{
    double fc_;
public:
    explicit KoBatheConcreteMaterialFactory(double fc_MPa)
        : fc_{fc_MPa} {}

    Material<ThreeDimensionalMaterial> create() const override {
        InelasticMaterial<KoBatheConcrete3D> mat_inst{fc_};
        return Material<ThreeDimensionalMaterial>{
            mat_inst, InelasticUpdate{}};
    }

    std::unique_ptr<ConcreteMaterialFactory>
    clone() const override {
        return std::make_unique<
            KoBatheConcreteMaterialFactory>(*this);
    }
};
```

76.4.3 Injection into the Evolver

The evolver now holds two factory members:

Listing 76.8: Factory members in the evolver.

```
std::unique_ptr<ConcreteMaterialFactory> concrete_factory_;
std::unique_ptr<RebarMaterialFactory>    rebar_factory_;
```

Two constructors are provided:

1. **Original constructor** (backward-compatible): initialises default factories using `KoBatheConcreteMater` and `MenegottoPintoRebarFactory` with the same parameters as the previously hardcoded construction.

2. **Factory-injecting constructor**: accepts custom `std::unique_ptr<ConcreteMaterialFactory>` and `std::unique_ptr<RebarMaterialFactory>`, enabling user-defined materials without modifying the evolver.

In `first_solve()`, the hardcoded material lines are replaced by factory calls:

Listing 76.9: Factory-delegated material creation.

```
// Before: InelasticMaterial<KoBatheConcrete3D> mat_inst{fc_};
Material<Policy> mat = concrete_factory_->create();

// Before: MenegottoPintoSteel steel_impl{...};
Material<UniaxialMaterial> steel_mat = rebar_factory_->create();
```

OCP compliance. Adding a new constitutive model (e.g. `Mazars3D`) now requires only writing a new factory subclass; the evolver source is *closed for modification*.

76.5 Phase 3: `MultiscaleModel` Aggregation

76.5.1 Problem: Scattered Model–Sub-Model Coupling

In the original `main_lshaped_multiscale.cpp`, the relationship between the global beam model and the local sub-model solvers was managed through three separate variables:

Listing 76.10: Scattered state in original main.

```
std::vector<NonlinearSubModelEvolver> nl_evolvers;  // sub-models
std::vector<Eigen::Matrix<double,6,6>> D_prev;      // tangent history
// kinematics extraction: a lambda capturing model and material params
auto extract_beam_kinematics = [&](std::size_t e_idx) { ... };
```

The kinematics extraction lambda captured the global model, element type, and material constants (`EC_COL`, `GC_COL`, `NU_RC`) by reference. The injection of homogenised tangent and forces was performed inline via `beam->set_homogenized_tangent(D_hom)`. This scattered organisation made it impossible to reuse the coupling logic in another context (different building, different element type).

76.5.2 Design: Template on Local Model Type

The `MultiscaleModel` class aggregates the global–local relationship into a single reusable object, defined in `src/analysis/MultiscaleModel.hh`:

Listing 76.11: `MultiscaleModel` class template (abridged).

```
template <LocalModelAdapter LocalModel>
class MultiscaleModel {

```

```
    std::vector<LocalModel> local_models_;
    std::unordered_map<std::size_t, std::size_t> transition_map_;

    std::function<ElementKinematics(std::size_t)>
        kinematics_extractor_;

    using InjectorFn = std::function<void(
        std::size_t,
        const Eigen::Matrix<double,6,6>&,
        const Eigen::Vector<double,6>&)>;
    InjectorFn response_injector_;

public:
    void register_local_model(std::size_t parent_elem_id,
                              LocalModel model);

    LocalModel& local_model_for(std::size_t elem_id);

    ElementKinematics extract_kinematics(std::size_t elem_id) const;

    void inject_response(std::size_t elem_id,
                         const Eigen::Matrix<double,6,6>& D_hom,
                         const Eigen::Vector<double,6>& f_hom);

    std::size_t num_local_models() const;
    std::vector<std::size_t> parent_element_ids() const;
};
```

Key design decisions:

1. **Template on local model type.** The class is parametrised on a `LocalModelAdapter`-constrained type rather than using `LocalModelHandle` directly. This avoids virtual dispatch overhead in the inner staggered loop, while the concept constraint ensures type safety. If heterogeneous sub-models are needed, instantiate with `LocalModelHandle`.

2. **Callback-based scale bridging.** The kinematics extraction and response injection functions are stored as `std::function` callbacks, set via `set_kinematics_extractor()` and `set_response_injector()`. This decouples the model aggregation from the concrete element type (`TimoshenkoBeam3D`, `EulerBernoulliBeam`, etc.) and the specific model template parameters.

3. **Transition map.** An `unordered_map` maps global beam element IDs to sub-model indices, enabling $O(1)$ lookup. This replaces the implicit index-based correspondence in the original code.

76.6 Phase 4: Coupling Strategy Interfaces

76.6.1 Problem: Hardcoded Coupling Parameters

The staggered coupling loop in `main_lshaped_multiscale.cpp` used four hardcoded compile-time constants:

Listing 76.12: Hardcoded coupling parameters.

```
static constexpr int    MAX_STAGGERED_ITER  = 4;
static constexpr double STAGGERED_TOL       = 0.05;
static constexpr double STAGGERED_RELAX     = 0.7;
static constexpr int    COUPLING_START_STEP = 10;
```

The convergence criterion (relative Frobenius norm), relaxation policy (constant ω), and coupling mode (two-way staggered) were all embedded in the loop body. Switching to one-way coupling or Aitken adaptive relaxation required editing the main driver.

76.6.2 Strategy Interfaces

Three abstract base classes are defined in `src/analysis/CouplingStrategy.hh`, implementing the *Strategy pattern* [4]:

ScaleBridgePolicy. Controls whether the coupling is one-way (sub-models are *passive observers*) or two-way (sub-models feed back stiffness and forces to the global model):

Listing 76.13: Scale bridge policy ABC and concrete implementations.

```
struct ScaleBridgePolicy {
    virtual ~ScaleBridgePolicy() = default;
    virtual bool requires_feedback() const = 0;
    virtual int  max_staggered_iterations() const = 0;
};

class OneWayCoupling final : public ScaleBridgePolicy {
public:
    bool requires_feedback() const override { return false; }
    int  max_staggered_iterations() const override { return 1; }
};

class TwoWayStaggered final : public ScaleBridgePolicy {
    int max_iter_;
public:
    explicit TwoWayStaggered(int max_iter = 4)
        : max_iter_{max_iter} {}
    bool requires_feedback() const override { return true; }
    int  max_staggered_iterations() const override
        { return max_iter_; }
};
```

CouplingConvergence. Defines the convergence criterion for the staggered iteration. The current implementation uses the relative Frobenius norm:

Listing 76.14: Frobenius convergence criterion.

```
struct CouplingConvergence {
    virtual ~CouplingConvergence() = default;
    virtual bool converged(
        std::span<const Eigen::Matrix<double,6,6>> D_prev,
        std::span<const Eigen::Matrix<double,6,6>> D_curr) const = 0;
};

class FrobeniusConvergence final : public CouplingConvergence {
    double tol_;
public:
    explicit FrobeniusConvergence(double tol = 0.05)
        : tol_{tol} {}
    bool converged(
        std::span<const Eigen::Matrix<double,6,6>> D_prev,
        std::span<const Eigen::Matrix<double,6,6>> D_curr
    ) const override {
        for (std::size_t i = 0; i < D_prev.size(); ++i) {
```

```
            double d_norm = D_curr[i].norm();
            double delta  = (D_curr[i] - D_prev[i]).norm();
            if (d_norm > 1e-14 && delta / d_norm > tol_)
                return false;
        }
        return true;
    }
};
```

The convergence criterion checks whether the relative change in *every* sub-model's tangent matrix is below the tolerance τ:

$$\frac{\|\mathbf{D}^{(k)}_{\text{hom},i} - \mathbf{D}^{(k-1)}_{\text{hom},i}\|_F}{\|\mathbf{D}^{(k)}_{\text{hom},i}\|_F} < \tau, \qquad \forall i \in \{1, \ldots, N_s\} \tag{76.1}$$

where N_s is the number of sub-models and k is the staggered iteration counter.

RelaxationPolicy. Controls how the updated tangent is blended with the previous iteration's value:

Listing 76.15: Relaxation policy implementations.

```
struct RelaxationPolicy {
    virtual ~RelaxationPolicy() = default;
    virtual void relax(
        Eigen::Matrix<double,6,6>& D_new,
        const Eigen::Matrix<double,6,6>& D_prev,
        int iteration) = 0;
};

class ConstantRelaxation final : public RelaxationPolicy {
    double omega_;
public:
    explicit ConstantRelaxation(double omega = 0.7)
        : omega_{omega} {}
    void relax(
        Eigen::Matrix<double,6,6>& D_new,
        const Eigen::Matrix<double,6,6>& D_prev,
        [[maybe_unused]] int iteration) override
    {
        D_new = omega_ * D_new + (1.0 - omega_) * D_prev;
    }
};
```

The constant relaxation applies:

$$\mathbf{D}^{(k)}_{\text{hom}} \leftarrow \omega\, \mathbf{D}^{(k)}_{\text{hom}} + (1-\omega)\, \mathbf{D}^{(k-1)}_{\text{hom}} \tag{76.2}$$

with $\omega = 0.7$ as default. A `NoRelaxation` policy is also provided for cases where relaxation is unnecessary or destabilising.

76.7 Phase 4.3: `MultiscaleAnalysis` Orchestrator

76.7.1 Design

The `MultiscaleAnalysis` class, defined in `src/analysis/MultiscaleAnalysis.hh`, absorbs the staggered coupling loop into a reusable, strategy-controlled template:

Listing 76.16: `MultiscaleAnalysis` class (abridged).

```
template <LocalModelAdapter LocalModel>
class MultiscaleAnalysis {
    MultiscaleModel<LocalModel>              model_;
    std::unique_ptr<ScaleBridgePolicy>       bridge_;
    std::unique_ptr<CouplingConvergence>     convergence_;
    std::unique_ptr<RelaxationPolicy>        relaxation_;

    int    coupling_start_step_{0};
    double section_width_{0.30};
    double section_height_{0.30};
    double tangent_perturbation_{1.0e-6};

    std::vector<Eigen::Matrix<double,6,6>> D_prev_;

public:
    MultiscaleAnalysis(
        MultiscaleModel<LocalModel> model,
        std::unique_ptr<ScaleBridgePolicy> bridge,
        std::unique_ptr<CouplingConvergence> convergence,
        std::unique_ptr<RelaxationPolicy> relaxation);

    void set_coupling_start_step(int step);
    void set_section_dimensions(double w, double h);

    // One global time step + staggered loop
    bool step(double time, int global_step);
};
```

76.7.2 The `step()` Method

The `step()` method implements the full staggered coupling algorithm for one global time step. The pseudocode is:

1. Determine whether coupling is active: `bridge_->requires_feedback()` **and** `global_step` $\geq$ `coupling_start_step_`.
2. For each staggered iteration $k = 0, 1, \ldots$:
   (a) **Downscale.** For each local model: extract kinematics from the global model via `model_.extract_kinematics()`, update the sub-model BCs, and solve the nonlinear BVP.
   (b) **Upscale.** For each local model: compute the homogenised tangent $\mathbf{D}_{\text{hom}}^{(k)}$ via perturbation, apply relaxation (76.2), and check convergence (76.1).
   (c) **Inject.** Write $\mathbf{D}_{\text{hom}}^{(k)}$ and $\mathbf{f}_{\text{hom}}^{(k)}$ into the global beam elements via `model_.inject_response()`.
   (d) If $k > 0$ and converged, **break**.
3. Commit the converged constitutive state of all sub-models.

Intended usage in the main driver:

Listing 76.17: Proposed refactored main driver.

```
auto bridge = std::make_unique<TwoWayStaggered>(4);
auto conv   = std::make_unique<FrobeniusConvergence>(0.05);
auto relax  = std::make_unique<ConstantRelaxation>(0.7);

```

```
MultiscaleAnalysis<NonlinearSubModelEvolver> analysis(
    std::move(ms_model),
    std::move(bridge), std::move(conv), std::move(relax));
analysis.set_coupling_start_step(10);
analysis.set_section_dimensions(COL_B, COL_H);

for (int step = 0; step < n_steps; ++step)
    analysis.step(time[step], step);
```

This replaces the ~80 lines of staggered loop logic in the original `main_lshaped_multiscale.cpp` with a single `analysis.step()` call, while retaining full configurability via the injected strategy objects.

76.8 Phase 5: `HomogenisationStrategy`

76.8.1 Problem: Two Upscaling Methods

The sub-model solver implements two distinct methods for extracting section forces from the 3-D displacement field:

1. **Boundary reaction** (used by `section_forces_from_reactions()`): assembles the internal force vector $\mathbf{f}_{\text{int}}$, reads the nodal forces at Face B nodes, and computes the section resultants $\mathbf{s} = [N, M_y, M_z, V_y, V_z, M_t]^\top$ from the reaction force and moment sums. This method is consistent with the perturbation tangent computation and gives equilibrium-consistent forces.

2. **Volume averaging** (used by `compute_homogenized_forces()` via the `homogenize()` free function in `HomogenizedSection.hh`): integrates the Cauchy stress field over the cross-section using the uniform-stress approximation. This is the classical Hill–Mandel approach.

The choice between these methods was previously hardcoded: the tangent used boundary reactions while the forces used volume averaging.

76.8.2 Strategy Interface

The `HomogenisationStrategy` ABC in `src/reconstruction/HomogenisationStrategy.hh` provides a clean selection mechanism:

Listing 76.18: Homogenisation strategy interface.

```
struct HomogenisationStrategy {
    virtual ~HomogenisationStrategy() = default;

    virtual Eigen::Vector<double, 6> select_forces(
        const Eigen::Vector<double, 6>& boundary_reaction,
        const Eigen::Vector<double, 6>& volume_average
    ) const = 0;

    virtual std::string name() const = 0;
};
```

The interface is *deliberately independent* of the solver class to avoid circular header dependencies. The sub-model solver computes both force vectors and passes them to the strategy for selection.

Listing 76.19: Concrete homogenisation strategies.

Concrete implementations:

```
struct BoundaryReactionHomogenisation final
    : HomogenisationStrategy
{
    Eigen::Vector<double, 6> select_forces(
        const Eigen::Vector<double, 6>& boundary_reaction,
        const Eigen::Vector<double, 6>& /*volume_average*/
    ) const override { return boundary_reaction; }

    std::string name() const override
        { return "boundary-reaction"; }
};

struct VolumeAverageHomogenisation final
    : HomogenisationStrategy
{
    Eigen::Vector<double, 6> select_forces(
        const Eigen::Vector<double, 6>& /*boundary_reaction*/,
        const Eigen::Vector<double, 6>& volume_average
    ) const override { return volume_average; }

    std::string name() const override
        { return "volume-average"; }
};
```

The `BoundaryReactionHomogenisation` strategy is recommended as the default because it produces forces consistent with the perturbation-based tangent computation (both use assembled $\mathbf{f}_{\text{int}}$), whereas the volume-average approach may give stale results when the stored material state is behind the displacement field.

76.9 Discussion

76.9.1 SOLID Compliance

Table 76.1 summarises how each refactoring phase addresses specific SOLID principles.

Table 76.1: SOLID compliance of each refactoring phase.

Phase	Principle	Mechanism
1 – LocalModelAdapter	OCP, DIP	New sub-model types can be added without modifying the orchestrator; high-level modules depend on the concept abstraction.
2 – MaterialFactory	OCP, SRP	New materials via factory subclasses; material creation responsibility extracted from the solver.
3 – MultiscaleModel	SRP	Model–sub-model relationship encapsulated; main driver cleaned.
4 – CouplingStrategy	OCP, ISP, SRP	Convergence, relaxation, and coupling mode are independently switchable; each interface has a single, narrow contract.
5 – HomogenisationStrategy	OCP	Upscaling method switchable without modifying the solver.

76.9.2 Concept vs. ABC Trade-Offs

The choice between C++20 concepts and ABCs was made on a case-by-case basis:

- **Concept** (`LocalModelAdapter`): The local model type is known at compile time for a given analysis. A concept avoids virtual dispatch in the inner loop (perturbation tangent: 6 SNES solves per sub-model per staggered iteration) and enables the compiler to inline critical paths. The type-erased handle `LocalModelHandle` is available as an opt-in for the heterogeneous case.
- **ABC** (`ConcreteMaterialFactory`, `ScaleBridgePolicy`, `CouplingConvergence`, `RelaxationPolicy`, `HomogenisationStrategy`): These are called once per staggered iteration (not in a tight loop), so the virtual dispatch cost is negligible. ABCs provide runtime polymorphism, enabling strategy selection at configuration time rather than compilation time.

76.9.3 Circular Dependency Avoidance

The `HomogenisationStrategy` interface was redesigned to avoid a circular dependency between `HomogenisationStrategy.hh` and `NonlinearSubModelEvolver.hh`. The original design took a `NonlinearSubModelEvolver&` parameter. The final design takes pre-computed force vectors (boundary reaction and volume average), inverting the dependency: the solver computes both and passes them to the strategy. This also makes the strategies testable in isolation.

76.9.4 Type-Erasure Pattern Reuse

The `LocalModelHandle` follows the same Concept/Model/Handle triple used by `FEM_Element` (`src/elements/FEM_Element.hh`). This pattern is now a well-established idiom in the codebase:

Handle	Concept	Purpose
`FEM_Element`	`FiniteElement`	Heterogeneous element containers
`LocalModelHandle`	`LocalModelAdapter`	Heterogeneous sub-model containers

Both are move-only (owning PETSc/mesh resources) and use `std::unique_ptr<Concept>` for type erasure.

76.9.5 Build Verification

After all phases:

- **Compilation:** 88 Ninja targets (down from 115), all compile under GCC 15.2 with `-Werror -std=c++23`.
- **Tests:** 63/63 CTest cases pass (51 unit, 6 integration, 6 slow).
- **New headers:** 6 files added, listed in Table 76.2.
- **Modified headers:** 3 files modified, listed in Table 76.3.

76.9.6 Remaining Work

The following phases from the original roadmap (Chapter 74) are deferred to future chapters:

Phase 0.2 – PCH: Precompiled headers for third-party includes (Eigen, PETSc, VTK).

Table 76.2: New files introduced by the refactoring.

File	Purpose
`src/reconstruction/LocalModelAdapter.hh`	Concept + type-erased handle
`src/reconstruction/MaterialFactory.hh`	Material factory ABCs + defaults
`src/reconstruction/HomogenisationStrategy.hh`	Upscaling strategy ABC + implementations
`src/analysis/CouplingStrategy.hh`	Coupling strategy ABCs + implementations
`src/analysis/MultiscaleModel.hh`	Model aggregation template
`src/analysis/MultiscaleAnalysis.hh`	Staggered coupling orchestrator

Table 76.3: Modified files.

File	Changes
`CMakeLists.txt`	Removed 20 duplicate seismic targets (115 → 88).
`NonlinearSubModelEvolver.hh`	Public `section_tangent()`/`section_forces()` aliases; public `commit_state()`/`revert_state()`; factory injection; `static_assert` for concept.
`header_files.hh`	Added includes for all 6 new headers.

Phase 0.3 – Explicit instantiation: `extern template` for the most-used template combinations.

Phase 4.4 – Main driver refactoring: Replace the staggered loop in `main_lshaped_multiscale.cpp` with `MultiscaleAnalysis::step()`.

Phase 6 – Parallelism: OpenMP parallel sub-model solves and perturbation tangent.

Phase 7 – SRP cleanup: Extract VTK export and crack tracking from the evolver into separate classes.

Phase 8 – Header modularisation: Split `header_files.hh` into tiered includes.

Chapter 77

Main Driver Refactoring: MultiscaleAnalysis Integration

Normative status. This chapter describes the first migration of driver logic into a multiscale orchestrator. The current publication-oriented API and behaviour are specified normatively in Chapter 82.

77.1 Introduction

Chapter 76 implemented six architectural phases, culminating in the `MultiscaleAnalysis` orchestrator class that encapsulates the FE^2 staggered coupling loop. This chapter documents the integration of that orchestrator into the primary analysis driver (`main_lshaped_multiscale.cpp`), replacing ∼80 lines of hand-written staggered coupling logic with a single call to `analysis.step()`.

The refactoring achieves:

- **Line reduction**: 80 lines of staggered coupling → 15 lines of orchestrator invocation + post-step diagnostics.
- **Separation of concerns**: coupling logic (`MultiscaleAnalysis`), scale bridging (`MultiscaleModel`), and damage diagnostics (main driver) are cleanly separated.
- **Behavioral equivalence**: the refactored driver produces identical numerical results—the "lagged" staggered scheme, convergence tolerance, relaxation factor, and coupling start step are preserved unchanged.

77.2 Architecture Overview

Figure 77.1 shows the object graph after refactoring. The main driver creates the following objects and wires them together:

1. `MultiscaleModel<NonlinearSubModelEvolver>` — owns the sub-model evolvers (moved from a temporary vector), the kinematics extraction callback, and the response injection callback.
2. `MultiscaleAnalysis<NonlinearSubModelEvolver>` — owns the `MultiscaleModel` and three strategy objects: `TwoWayStaggered`, `FrobeniusConvergence`, `ConstantRelaxation`.
3. The main driver retains ownership of the global model, solver, observers, VTK exporters, and crack diagnostics.

```
main()
  |
  +-- model (StructModel)             [global FE model]
  +-- solver (DynSolver)              [Newmark time integrator]
  +-- analysis (MultiscaleAnalysis)
  |     |
  |     +-- model_ (MultiscaleModel)
  |     |     +-- local_models_       [NonlinearSubModelEvolver ...]
  |     |     +-- kinematics_extractor_
  |     |     +-- response_injector_
  |     |
  |     +-- bridge_  (TwoWayStaggered)
  |     +-- convergence_ (FrobeniusConvergence)
  |     +-- relaxation_  (ConstantRelaxation)
  |
  +-- crack_csv, pvd_global, ...      [diagnostics / I/O]
```

Figure 77.1: Object ownership graph after driver refactoring.

77.3 Evolver Transfer and Callback Wiring

Sub-model evolvers are created in a temporary vector, then moved into the `MultiscaleModel`:

Listing 77.1: Evolver transfer and callback wiring (section 12 of the driver).

```cpp
MultiscaleModel<NonlinearSubModelEvolver> ms_model;

// Kinematics extraction: delegates to existing lambda
ms_model.set_kinematics_extractor(extract_beam_kinematics);

// Response injection: sets D_hom and f_hom on beam elements
ms_model.set_response_injector(
    [&model](std::size_t eid,
             const Eigen::Matrix<double,6,6>& D_hom,
             const Eigen::Vector<double,6>&   f_hom)
    {
        if (auto* beam = model.elements()[eid].as<BeamElemT>()) {
            beam->set_homogenized_tangent(D_hom);
            beam->set_homogenized_forces(f_hom);
        }
    });

for (auto& ev : nl_evolvers) {
    const auto eid = ev.parent_element_id();
    ms_model.register_local_model(eid, std::move(ev));
}
```

Note the defensive sequencing in the move loop: the element id is captured *before* the move, avoiding undefined behaviour from unspecified function-argument evaluation order in C++.

77.4 Orchestrator Construction

The `MultiscaleAnalysis` is constructed with the same parameters that governed the original hand-written loop:

Listing 77.2: MultiscaleAnalysis construction with strategy injection.

```
MultiscaleAnalysis<NonlinearSubModelEvolver> analysis(
    std::move(ms_model),
    std::make_unique<TwoWayStaggered>(MAX_STAGGERED_ITER),
    std::make_unique<FrobeniusConvergence>(STAGGERED_TOL),
    std::make_unique<ConstantRelaxation>(STAGGERED_RELAX));

analysis.set_coupling_start_step(COUPLING_START_STEP);
analysis.set_section_dimensions(COL_B, COL_H);
```

The mapping between the original constants and the strategy objects is shown in Table 77.1.

Table 77.1: Mapping from original constants to strategy objects.

Original constant	Value	Strategy object
MAX_STAGGERED_ITER	4	TwoWayStaggered(4)
STAGGERED_TOL	0.05	FrobeniusConvergence(0.05)
STAGGERED_RELAX	0.7	ConstantRelaxation(0.7)
COUPLING_START_STEP	10	set_coupling_start_step(10)

77.5 Staggered Loop Replacement

The most significant change is the replacement of the hand-written staggered coupling loop. The original implementation spanned ∼80 lines and interleaved sub-model solving, tangent computation, relaxation, convergence checking, response injection, and crack diagnostics.

77.5.1 Before: Hand-Written Staggered Loop

The original loop structure is shown in Listing 77.3 (abbreviated).

Listing 77.3: Original staggered coupling loop (abbreviated, ∼80 lines).

```
std::vector<Eigen::Matrix<double,6,6>> D_prev(...);
int staggered_iters = 0;

for (int s_iter = 0; ; ++s_iter) {
    // (a) Extract kinematics, update BCs, solve sub-models
    for (auto& ev : nl_evolvers) {
        ev.update_kinematics(...);
        ev.solve_step(t);
        // ... accumulate crack summaries ...
    }

    if (!do_coupling || s_iter >= MAX_STAGGERED_ITER) break;

    // (c) Compute tangent, relax, check convergence, inject
    for (std::size_t i = 0; i < nl_evolvers.size(); ++i) {
        auto D_hom = nl_evolvers[i].compute_homogenized_tangent(...);
        // relax, check convergence, inject into beam ...
    }

    if (s_iter == 0) continue;  // at least 2 iterations
    if (all_converged) break;
    break;  // lagged coupling: exit after check
}
```

77.5.2 After: Orchestrator Delegation

The refactored code delegates entirely to the orchestrator:

Listing 77.4: Refactored staggered coupling (∼15 lines).

```
// FE^2 staggered coupling (delegated to MultiscaleAnalysis)
analysis.step(t, evol_step);
const int staggered_iters = analysis.last_staggered_iterations();

// Collect crack summaries (post-step)
int step_cracked_gps = 0, step_total_cracks = 0;
double step_max_crack_damage = 0.0, step_max_opening = 0.0;
std::vector<CrackSummary> step_summaries;
for (auto& ev : analysis.model().local_models()) {
    auto cs = ev.crack_summary();
    step_summaries.push_back(cs);
    step_cracked_gps  += cs.num_cracked_gps;
    step_total_cracks += cs.total_cracks;
    // ...
}
```

The crack diagnostics are collected *after* `analysis.step()` returns, querying each sub-model evolver via `analysis.model().local_models()`. This is equivalent to the original, which collected diagnostics after the final staggered iteration.

77.6 Behavioral Equivalence Analysis

Identical numerical behavior is ensured by the following design decisions:

1. **Lagged staggered scheme.** The `MultiscaleAnalysis::step()` method mirrors the original loop structure: iteration 0 always continues to iteration 1 (`s_iter == 0` ⇒ `continue`), and the convergence check occurs only at iteration 1 onwards. The effective behavior is a lagged coupling where the homogenized tangent computed at step n is used by the global solver at step $n+1$.

2. **No auto-commit.** The original driver does not call `commit_state()` on the sub-model evolvers after each global step. The orchestrator's `auto_commit_` flag defaults to `false`, preserving this behavior. The material state management follows the evolver's internal SNES convergence cycle.

3. **Same convergence metric.** The `FrobeniusConvergence` strategy implements the identical relative Frobenius norm criterion:

$$\frac{\|\mathbf{D}^{(i)}_{\text{curr}} - \mathbf{D}^{(i)}_{\text{prev}}\|_F}{\|\mathbf{D}^{(i)}_{\text{curr}}\|_F} < \tau \qquad \forall\, i \in \{1, \ldots, n_{\text{sub}}\} \tag{77.1}$$

   with $\tau = 0.05$ and per-sub-model enforcement.

4. **Same relaxation.** The `ConstantRelaxation` strategy applies $\omega = 0.7$ via:

$$\hat{\mathbf{D}}^{(i)} = \omega\, \mathbf{D}^{(i)}_{\text{hom}} + (1-\omega)\, \mathbf{D}^{(i)}_{\text{prev}} \tag{77.2}$$

   only when $s_{\text{iter}} > 0$, matching the original guard.

5. **Post-step crack diagnostics.** The original code accumulated crack summaries inside the staggered loop but cleared and re-accumulated on each iteration. Only the final iteration's data was written to CSV. The refactored code collects crack summaries once after `step()` returns, yielding identical output.

77.7 Diagnostic Accessors

Two accessors were added to `MultiscaleAnalysis` to support post-step reporting in the main driver:

Listing 77.5: Diagnostic accessors on MultiscaleAnalysis.

```
[[nodiscard]] int  last_staggered_iterations() const
    { return last_staggered_iters_; }

[[nodiscard]] bool last_converged() const
    { return last_converged_; }
```

These are populated by `step()` and consumed by the progress printing logic (every 500 steps) and the crack CSV writer. The `auto_commit_` flag is controlled via `set_auto_commit(bool)` and defaults to `false` to match the original driver semantics.

77.8 Line Count and Complexity Reduction

Table 77.2 summarises the quantitative impact of the refactoring on the driver file.

Table 77.2: Driver file metrics before and after refactoring.

Metric	Before	After
Lines in staggered loop block	∼80	∼15
Cyclomatic complexity (loop)	8	1
Direct `nl_evolvers` refs	12	0
Strategy parameters hard-coded	4	0
Build targets	88	88
CTest cases passing	63/63	63/63

All 12 direct references to the `nl_evolvers` vector in post- creation code (sections 13–16) were replaced with access through `analysis.model().local_models()` or `analysis.model().num_local_mod` The temporary vector is populated, moved into the model, and never referenced again.

77.9 Response Injector Design

A key design decision was encapsulating the response injection—which couples the orchestrator to concrete beam element types—in a `std::function` callback. The lambda captures the global `model` by reference and performs a safe `as<BeamElemT>` downcast:

$$\text{inject} : (\text{eid}, \mathbf{D}_{\text{hom}}, \mathbf{f}_{\text{hom}}) \;\mapsto\; \text{beam.set_homogenized_tangent}(\mathbf{D}_{\text{hom}}),\ \text{beam.set_homogenized_forces}(\mathbf{f}_{\text{hom}}) \tag{77.3}$$

This design preserves the Open/Closed Principle: new element types (shell, solid) can be supported by changing only the injector callback, without modifying `MultiscaleAnalysis` or `MultiscaleModel`.

77.10 Build and Test Verification

After all edits:

- **Build**: 88 Ninja targets compile under GCC 15.2 with `-std=c++23 -Werror -Wall -Wextra -Wpedantic`. No warnings.

- **Tests**: 63/63 CTest cases pass with `-output-on-failure`.
- **Files modified**: 2 (`main_lshaped_multiscale.cpp`, `MultiscaleAnalysis.hh`).

77.11 Discussion

77.11.1 Move Semantics and Evaluation Order

The evolver transfer loop demonstrates a subtle C++ pitfall: passing `ev.parent_element_id()` and `std::move(ev)` as arguments to the same function call invokes unspecified evaluation order (C++17 § 8.2.2). If the move is evaluated first, the subsequent `parent_element_id()` call operates on a moved-from object. The fix—capturing the id into a local variable before the function call—is a defensive pattern that should be applied whenever a move and a member access coexist in the same argument list.

77.11.2 Commit Semantics

The original driver does *not* call `commit_state()` on the sub-model evolvers after each global step. This is intentional: the evolver's internal SNES solve evaluates constitutive response during residual assembly, and the converged displacement field is retained in the PETSc `Vec`. The perturbation tangent computation saves and restores both the displacement vector and the material state, making an explicit commit unnecessary for the lagged coupling scheme.

The `auto_commit_` flag provides forward compatibility: a future multi-iteration staggered scheme that re-solves the global step within the coupling loop would require explicit commits between staggered iterations.

77.11.3 Crack Diagnostic Decoupling

Moving crack summary collection from inside the staggered loop to a post-step query is a clean application of the Single Responsibility Principle. The staggered loop is now purely concerned with coupling convergence; diagnostic collection is a separate concern handled by the driver after the coupling is complete.

77.12 Summary

This chapter documented the integration of the `MultiscaleAnalysis` orchestrator into the L-shaped multiscale driver. The refactoring replaced ∼80 lines of hand-written staggered coupling logic with a single `analysis.step()` call, reduced the cyclomatic complexity of the inner loop from 8 to 1, and decoupled crack diagnostics from coupling convergence. All 88 build targets compile cleanly and all 63 test cases continue to pass.

Chapter 78

Ejemplo avanzado: Edificio en L de 16 niveles con análisis multiescala FE^2

Normative status. Este capítulo se conserva como registro histórico del ejemplo de aplicación. La nomenclatura y la semántica normativas del módulo multiescala vigente se definen en el Chapter 82.

78.1 Introducción y motivación

Los edificios altos de concreto reforzado (CR) con irregularidades en altura presentan concentraciones de daño en las zonas de transición de sección, fenómeno que los modelos de fibra convencionales capturan solo parcialmente. En este capítulo se demuestra la capacidad completa del módulo multiescala FE^2 de `fall_n` para analizar un edificio en L de 16 niveles con tres zonas de sección diferente, sometido al sismo de Tohoku 2011 (estación MYG004) en las tres componentes (NS, EW, UD).

El objetivo es triple:

1. **Validar la transición automática** del análisis global con fibras a submodelos 3D No Lineales (Ko-Bathe Concrete 3D) cuando se alcanza la fluencia del acero.

2. **Demostrar el acoplamiento FE^2 doble** (two-way staggered) con convergencia de Frobenius y relajación constante, aplicado a múltiples submodelos con secciones distintas.

3. **Capturar la evolución de fisuras** en los submodelos y cuantificar su efecto en la respuesta global (desplazamientos de cubierta, curvas de histéresis, envolvente de derivas).

78.2 Hipótesis del modelo

Se plantean las siguientes hipótesis de trabajo:

H1 — Localización del daño: Debido a la reducción brusca de sección entre pisos 5–6 y 11–12, el daño se concentrará en las columnas de borde de la re-entrante del plano en L, entre los pisos 5 y 6 (transición de $0.50 \times 0.50\,\mathrm{m}$ a $0.40 \times 0.40\,\mathrm{m}$).

H2 — Acumulación progresiva de fisuras: Los submodelos 3D registrarán una apertura de fisura creciente con el número de ciclos de carga, alcanzando valores máximos durante los pulsos de mayor PGA ($t \approx 60$–$90\,\mathrm{s}$).

H3 — Efectividad del acoplamiento FE²: El esquema staggered de dos vías convergerá en menos de 6 iteraciones por paso, con norma de Frobenius relativa menor al 3 %.

H4 — Compatibilidad de irregularidad vertical: Las columnas del rango superior (0.30×0.30 m, $f'_c = 21$ MPa) experimentarán mayor deformación unitaria pero menor fuerza axial, resultando en un índice de daño menor al de las columnas de transición.

78.3 Descripción del modelo

78.3.1 Geometría

El edificio tiene planta en forma de L con 4 vanos en x (5 m cada uno = 20 m totales) y 3 vanos en y (4 m cada uno = 12 m totales), con una esquina recortada (2×1 vanos en la zona superior derecha). Se consideran 16 niveles con entrepiso uniforme $h_e = 3.2$ m, para una altura total de $H = 51.2$ m.

78.3.2 Irregularidad en altura — secciones por rango

Table 78.1: Secciones de columna por rango de pisos.

Rango	Pisos	$b \times h$ [m]	f'_c [MPa]	E_c [MPa]	Grupo
Inferior	1–5	0.50×0.50	35	27 806	`ColumnsLower`
Medio	6–11	0.40×0.40	28	24 870	`ColumnsMid`
Superior	12–16	0.30×0.30	21	21 538	`ColumnsUpper`

Las vigas son uniformes en todos los niveles: 0.30×0.60 m, $f'_c = 25$ MPa. Todas las barras longitudinales tienen $f_y = 420$ MPa y relación de endurecimiento $b = 0.01$.

78.3.3 Acción sísmica

Se emplea el registro del sismo de Tohoku 2011-03-11 (M_w 9.0), estación K-NET MYG004 (Tsukidate, Miyagi), cerca del campo cercano. Se aplican las tres componentes simultáneamente:

- **NS** → dirección x
- **EW** → dirección y
- **UD** → dirección z

con escala $\alpha = 1.0$ y ventana de análisis de 275 s (descartando los primeros 25 s de ruido previo al evento).

78.3.4 Parámetros de análisis dinámico

78.3.5 Parámetros del acoplamiento FE²

78.4 Implementación

78.4.1 Reasignación de grupos por rango

Dado que la función `make_building_domain` genera todas las columnas bajo un único grupo `"Columns"`, se realiza un postproceso inmediato sobre el dominio para reasignar los grupos según la coordenada z del nodo inferior de cada columna:

Table 78.2: Parámetros del análisis dinámico.

Parámetro	Valor	Unidad
Paso de tiempo Δt	0.02	s
Período fundamental T_1	1.60	s
Tercer modo T_3	0.40	s
Factor de amortiguamiento ξ	5	%
Densidad ρ	2.4×10^{-3}	$\mathrm{MN\,s^2/m^4}$
Integración temporal	Generalized-α ($\rho_\infty = 0.9$)	

Table 78.3: Configuración del acoplamiento multiescala.

Parámetro	Valor
Esquema de acoplamiento	IteratedTwoWayFE2 (doble)
Máx. iteraciones staggered	6
Tolerancia (Frobenius)	3 %
Factor de relajación	0.7
Paso de inicio de acoplamiento	10
Columnas críticas	5 (top-N por índice de daño)
Malla del submodelo	$4 \times 4 \times 8$ Hex27
Modelo constitutivo 3D	Ko-Bathe Concrete 3D

Listing 78.1: Reasignación de grupos de columnas por rango de piso.

```
std::size_t idx = 0;
for (auto& geom : domain.elements()) {
    if (geom.physical_group() == "Columns") {
        const double z_bot = geom.point_p(0).coord(2);
        const int r = story_range(z_bot);
        geom.set_physical_group(COL_GROUPS[r]);
        elem_to_range[idx] = r;
    }
    ++idx;
}
```

Esto permite registrar tres materiales distintos en el `StructuralModelBuilder`:

Listing 78.2: Asignación de material por grupo de piso.

```
for (int r = 0; r < NUM_RANGES; ++r)
    builder.set_frame_material(COL_GROUPS[r],
                               col_mats[r]);
builder.set_frame_material("Beams", bm_mat);
```

78.4.2 Coordinadores multiescala por rango

Los elementos críticos se agrupan por rango de piso, y se construye un `MultiscaleCoordinator` independiente para cada rango, utilizando las dimensiones de sección correspondientes:

Listing 78.3: Coordinadores por rango para submodelos con secciones distintas.

```
std::map<int, MultiscaleCoordinator> coordinators;
for (auto& [range, eids] : crit_by_range) {
    auto& coord = coordinators[range];
    for (auto eid : eids)
```

```
        coord.add_critical_element(
           extract_beam_kinematics(eid));
    coord.build_sub_models(SubModelSpec{
        .section_width  = COL_B[range],
        .section_height = COL_H[range],
        .nx=4, .ny=4, .nz=8,
        .hex_order = HexOrder::Quadratic});
}
```

78.4.3 Puente C++–Python para postproceso

Se implementó una clase utilitaria `PythonPlotter` en `src/utils/PythonPlotter.hh` que invoca scripts de Python directamente desde el ejecutable C++ al finalizar la simulación:

Listing 78.4: Invocación de Python desde C++ para generación de figuras.

```
fall_n::PythonPlotter plotter(
    BASE + "scripts/falln_postprocess.py");
plotter.plot(rec_dir,
    BASE + "doc/figures/lshaped_multiscale_16/");
```

La librería de postproceso `scripts/falln_postprocess.py` contiene funciones reutilizables: `plot_roof_displacement`, `plot_hysteresis`, `plot_crack_evolution`, `plot_interstory_drift`, y una interfaz CLI con `argparse`.

78.5 Resultados esperados

78.5.1 Desplazamientos de cubierta

Se registran los desplazamientos de todos los nodos activos del nivel 16 en las tres direcciones. La historia temporal permite identificar:

- El instante de máxima respuesta ($t^* \approx 60$–$90\,\mathrm{s}$).
- La amplificación debida al acoplamiento horizontal-vertical.
- El desfase del movimiento del suelo en las direcciones NS y EW.

La trayectoria orbital (u_x, u_y) del nodo de cubierta más cercano a la esquina re-entrante muestra la naturaleza bidireccional de la demanda sobre la estructura.

78.5.2 Curvas de histéresis a ambas escalas

Escala global (fibras) Las fibras de acero de las columnas críticas exhiben ciclos completos de fluencia cíclica con endurecimiento de Menegotto-Pinto. Las fibras de concreto muestran degradación progresiva de rigidez con el modelo de Kent-Park confinado.

Escala local (submodelos 3D) Los puntos de Gauss del submodelo siguen la envolvente de Ko-Bathe con formación de fisuras direccionales. Se espera degradación más pronunciada en los submodelos del rango inferior (columnas de $0.50\,\mathrm{m}$, más cargadas axialmente).

78.5.3 Evolución de fisuras en los submodelos

Cada submodelo exporta:

- Número de puntos de Gauss fisurados vs. tiempo.

- Apertura máxima de fisura vs. tiempo.
- Índice de daño máximo en la malla local.
- Glyphs VTK de planos de fisura para visualización en ParaView.

La comparación entre submodelos de distintos rangos permite cuantificar el efecto de la irregularidad en altura sobre la distribución de daño.

78.6 Discusión y análisis de validez

78.6.1 Localización del daño en transiciones de sección

La hipótesis H1 se verifica observando qué submodelos acumulan mayor número de fisuras. Se espera que los elementos en los pisos 5–6 (transición inferior–medio) sean los más afectados, seguidos por los pisos 11–12 (transición medio–superior).

78.6.2 Convergencia del acoplamiento FE^2

El número de iteraciones staggered por paso (≤ 6) y la reducción de la norma de Frobenius confirman la estabilidad del esquema two-way con relajación $\omega = 0.7$. Si en algún paso se alcanza el máximo de iteraciones sin convergencia, el algoritmo continúa con la mejor estimación disponible, registrando un aviso.

78.6.3 Efecto del amortiguamiento de Rayleigh

Con $\xi = 5\,\%$ entre $T_1 = 1.6\,\mathrm{s}$ y $T_3 = 0.4\,\mathrm{s}$, los modos intermedios están ligeramente sobreamortiguados. Se recomienda un estudio paramétrico variando ξ y verificando su impacto en la deriva inter-piso máxima.

78.7 Estrategia de validación

Se propone una estrategia de validación en tres niveles:

1. **Verificación numérica (code-to-code):** Comparar los desplazamientos de cubierta y derivas máximas con un modelo equivalente en OpenSees utilizando las mismas secciones, materiales y registro sísmico. El criterio de aceptación es una diferencia menor al 10 % en el pico de desplazamiento.
2. **Validación con resultados experimentales:** Cotejar las curvas de histéresis de fibra y las apariciones de fisura con los datos de ensayos de columnas RC cíclicas publicados por Saatcioglu & Ozcebe (1989) y Sheikh & Khoury (1993).
3. **Análisis de sensibilidad:** Evaluar la robustez del modelo variando:
   - Factor de escala del sismo ($\alpha \in \{0.5, 1.0, 1.5\}$).
   - Número de submodelos ($N_{\mathrm{crit}} \in \{3, 5, 7\}$).
   - Malla del submodelo ($4 \times 4 \times 8$ vs. $6 \times 6 \times 12$).
   - Factor de relajación ($\omega \in \{0.5, 0.7, 0.9\}$).

Table 78.4: KPIs para la validación del modelo multiescala.

KPI	Métrica	Criterio
Desplazamiento de cubierta	$u_{\max}$ relativo	$< 10\,\%$ vs. referencia
Deriva inter-piso máxima	$\theta_{\max}$	$< 2.5\,\%$ (LS)
Iteraciones FE^2	promedio por paso	≤ 4 (ideal)
Convergencia Frobenius	norma relativa final	$< 3\,\%$
Fisuras acumuladas	total en submodelos	monótonamente creciente

78.7.1 Indicadores clave de rendimiento (KPIs)

78.8 Conclusiones del ejemplo

Este ejemplo demuestra que el módulo multiescala de `fall_n` es capaz de:

- Manejar edificios de altura media (16 pisos) con irregularidades de sección en altura, sin modificar la API de `make_building_domain`.
- Ejecutar acoplamiento FE^2 doble con múltiples rangos de sección, cada uno con su propio `MultiscaleCoordinator` y propiedades de material.
- Generar resultados de postproceso (VTK, CSV, figuras) de forma integrada, incluyendo la invocación de scripts Python desde C++.
- Proporcionar una base sólida para estudios paramétricos y de validación que se desarrollarán en capítulos futuros.

Chapter 79

Acero embebido con acoplamiento por penalidad e interacción fibra-truss en sub-modelos FE^2

79.1 Motivación

En el esquema multiescala FE^2 descrito en capítulos anteriores (73, 78), las barras de refuerzo dentro de los sub-modelos continuos se discretizaban como elementos truss (línea) cuyos nodos coincidían con los nodos de esquina de la malla hexaédrica. Esto producía dos problemas:

1. **Posición no realista:** Para una malla gruesa ($N_x = N_y = 2$), la función `std::round` mapeaba la coordenada física de la barra al índice de nodo entero más cercano. Una barra diseñada a $y_0 = -0.200\,\mathrm{m}$ (*cover* + $\phi/2$) con $\Delta x = 0.250\,\mathrm{m}$ se redondeaba a $i_x = 0$, es decir, sobre la cara *exterior* del elemento. Esto es físicamente incorrecto porque ignora el recubrimiento de concreto y puede representar una condición de contorno diferente a la real.

2. **Acoplamiento artificial:** Al compartir nodos con el hexaedro, la barra heredaba la cinemática completa del concreto (3 grados de libertad compartidos), lo que impedía capturar el deslizamiento relativo barra–concreto y la contribución rigidizante correcta del acero.

La solución implementada consiste en:

- Crear *nodos independientes* para las barras en sus posiciones físicas exactas dentro de la sección transversal.
- Acoplar los nodos de la barra al continuo hexaédrico mediante *resortes de penalidad* que reproducen la interpolación Master-Slave.
- Incorporar el diámetro real de la barra en la exportación VTK para visualizar tubos con espesor físico en ParaView.

79.2 Posición física de las barras

Cada barra se especifica con sus coordenadas locales (l_y, l_z) relativas al centroide de la sección, su área A_b y su diámetro ϕ_b. La estructura `RebarBar` se define como:

```
struct RebarBar {
    double ly{0};          // coordenada local y [m]
    double lz{0};          // coordenada local z [m]
```

```
    double area{0};         // área [m²]
    double diameter{0};     // diámetro [m]
    std::string group = "Rebar";
};
```

Para una columna cuadrada de $b = h = 0.50\,\text{m}$ con recubrimiento $c = 40\,\text{mm}$ y barras de $\phi = 20\,\text{mm}$, las coordenadas extremas son:

$$y_0 = -\frac{b}{2} + c + \frac{\phi}{2} = -0.250 + 0.040 + 0.010 = -0.200\ \text{m} \tag{79.1}$$

lo que sitúa la barra a 50 mm del borde exterior, dentro del acero real de la sección. Las ocho barras (4 esquina + 4 central de cara) se posicionan según:

Barra	l_y [m]	l_z [m]
1–4 (esquinas)	± 0.200	± 0.200
5–6 (caras z)	0.000	± 0.200
7–8 (caras y)	± 0.200	0.000

79.3 Nodos independientes de barra y datos de imbricación

La función `make_reinforced_prismatic_domain()` genera la malla hexaédrica (idéntica a `make_prismatic_do` y luego crea nodos de barra adicionales a lo largo del eje z. Cada barra produce $n_z \cdot s + 1$ nodos ($s = 1$ para Hex8, $s = 2$ para Hex27), con identificadores que comienzan después de los nodos de la malla hex:

$$\text{nid}_{b,k} = N_{\text{hex}} + b \cdot (s \cdot n_z + 1) + k, \qquad k = 0, \ldots, s \cdot n_z, \tag{79.2}$$

donde N_{hex} es el número total de nodos hexaédricos.

Para el caso de la simulación del edificio ($n_z = 8$, Hex27, 8 barras), se crean $8 \times 17 = 136$ nodos de barra y $8 \times 8 = 64$ elementos línea (truss). El total de nodos del sub-modelo pasa de 850 (sólo hex) a 986.

79.3.1 Elemento huésped y coordenadas padres

Para cada nodo de barra, se identifica el hexaedro que lo contiene (*host element*) y se calculan las coordenadas padres $(\xi, \eta, \zeta) \in [-1, 1]^3$ mediante:

$$i_x^{\text{host}} = \text{floor}((l_y + w/2)/\Delta x), \qquad \xi = 2\,\frac{(l_y + w/2)/\Delta x - i_x^{\text{host}}}{1} - 1, \tag{79.3}$$

$$i_y^{\text{host}} = \text{floor}((l_z + h/2)/\Delta y), \qquad \eta = 2\,\frac{(l_z + h/2)/\Delta y - i_y^{\text{host}}}{1} - 1, \tag{79.4}$$

$$i_z^{\text{host}} = \text{floor}(k_z/s), \qquad \zeta = 2\,\frac{k_z - i_z^{\text{host}} \cdot s}{s} - 1, \tag{79.5}$$

donde k_z es el sub-nivel z del nodo de barra ($0 \le k_z \le s \cdot n_z$). Esta información se almacena en la estructura `RebarNodeEmbedding`:

```
struct RebarNodeEmbedding {
    PetscInt rebar_node_id;
    int host_elem_ix, host_elem_iy, host_elem_iz;
    double xi, eta, zeta;
};
```

79.4 Condiciones de contorno en los extremos de las barras

Los nodos de barra que caen en las caras $z_{\min}$ y $z_{\max}$ del sub-modelo reciben condiciones de Dirichlet computadas a partir de la cinemática seccional del elemento viga (Timoshenko) en las posiciones (l_y, l_z) exactas de la barra:

$$\mathbf{u}_{\text{bar,face}} = \mathbf{u}_c + \boldsymbol{\theta} \times (l_y\,\hat{e}_y + l_z\,\hat{e}_z), \tag{79.6}$$

donde $\mathbf{u}_c$ y $\boldsymbol{\theta}$ son el desplazamiento y la rotación del centroide de la sección, evaluados en el extremo A ($z_{\min}$) o B ($z_{\max}$).

Estos nodos se agregan a las listas `face_min_z_ids` y `face_max_z_ids` en la función `build_sub_models()` del `MultiscaleCoordinator`, inmediatamente después de `cache_face_nodes()`.

79.5 Acoplamiento por penalidad (Master-Slave)

Los nodos interiores de barra (todos excepto los de las caras z) no están conectados a la malla hexaédrica por el sieve de PETSc. Para acoplar su cinemática al continuo se emplea un esquema de *penalidad*, equivalente a Master-Slave con interpolación por funciones de forma.

79.5.1 Formulación

Sea r un nodo de barra interior con desplazamiento $\mathbf{u}_r$, y sea e el hexaedro huésped con nodos $\{i\}$ y funciones de forma $N_i(\xi, \eta, \zeta)$. El desplazamiento interpolado del hexaedro en la posición de la barra es:

$$\tilde{\mathbf{u}} = \sum_i N_i\,\mathbf{u}_i. \tag{79.7}$$

Se define un resorte de penalidad con rigidez α que impone:

$$\mathbf{f}_r^{\text{pen}} = \alpha\,(\mathbf{u}_r - \tilde{\mathbf{u}}), \qquad \mathbf{f}_i^{\text{pen}} = -\alpha\,N_i\,(\mathbf{u}_r - \tilde{\mathbf{u}}). \tag{79.8}$$

La contribución a la matriz tangente es:

$$\mathbf{K}^{\text{pen}} = \begin{bmatrix} \alpha\,\mathbf{I}_3 & -\alpha\,N_1\,\mathbf{I}_3 & \cdots & -\alpha\,N_n\,\mathbf{I}_3 \\ -\alpha\,N_1\,\mathbf{I}_3 & \alpha\,N_1 N_1\,\mathbf{I}_3 & \cdots & \alpha\,N_1 N_n\,\mathbf{I}_3 \\ \vdots & \vdots & \ddots & \vdots \\ -\alpha\,N_n\,\mathbf{I}_3 & \alpha\,N_n N_1\,\mathbf{I}_3 & \cdots & \alpha\,N_n N_n\,\mathbf{I}_3 \end{bmatrix}, \tag{79.9}$$

donde n es el número de nodos del hexaedro (8, 20 o 27) y donde sólo se incluyen los pares con $|N_i| > 10^{-15}$.

79.5.2 Selección de α

En la formulación de penalidad, el error relativo de acoplamiento es del orden de k_{elem}/α, donde k_{elem} es la rigidez diagonal dominante del grado de libertad. Para los parámetros del ejemplo:

$$k_{\text{truss}} = E_s\,A_b/L_e = 200\,000 \times 3.14 \times 10^{-4}/0.0625 \approx 1\,005\ \text{MPa}\,\text{m}, \tag{79.10}$$

$$k_{\text{hex}} \approx E_c \cdot \Delta x \cdot \Delta y \approx 30\,000 \times 0.25^2 = 1\,875\ \text{MPa}\,\text{m}. \tag{79.11}$$

Con $\alpha = 10^6$ (valor por defecto), el error relativo es $\sim 10^{-3}$, suficiente para la precisión de un modelo de sub-estructura.

79.5.3 Implementación en SNES

Las contribuciones de penalidad se inyectan directamente en los callbacks estáticos de PETSc:

- **FormResidual**: Los términos $\mathbf{f}^{\text{pen}}$ se suman al vector de fuerzas internas en espacio local (`f_int_local`) antes del scatter `DMLocalToGlobal`. Los grados de libertad de nodos con Dirichlet se eliminan automáticamente durante el scatter.
- **FormJacobian**: Los términos de $\mathbf{K}^{\text{pen}}$ se insertan en la matriz global $\mathbf{J}$ mediante `MatSetValues` con modo `ADD_VALUES`. Se utiliza la *global section* para obtener los offsets de cada nodo; los nodos restringidos (con 0 DOF en la sección global) se omiten. La opción `MAT_NEW_NONZERO_ALLOCATION_E = PETSC_FALSE` permite que PETSc asigne las nuevas entradas no-cero sin error.

Los datos de acoplamiento se pre-calculan una sola vez en `compute_penalty_couplings()`, invocado después de `model_->setup()` en `first_solve()`. Para cada nodo de barra interior:

1. Se identifica el hexaedro huésped (i_x, i_y, i_z) y las coordenadas padres (ξ, η, ζ) desde `RebarNodeEmbedding`.
2. Se evalúan las funciones de forma 1-D de Lagrange (lineales para Hex8, cuadráticas para Hex27) como producto tensorial:

$$N_{p,q,r}(\xi, \eta, \zeta) = L_p(\xi) \cdot L_q(\eta) \cdot L_r(\zeta),$$

   donde para el caso cuadrático:

$$L_0(t) = \frac{t(t-1)}{2}, \quad L_1(t) = 1 - t^2, \quad L_2(t) = \frac{t(t+1)}{2}.$$

3. Se almacenan los pares $(\text{sieve_point}_i, N_i)$ en un vector `hex_weights` dentro de `PenaltyCouplingEntry`.

79.6 Feedback Fibra-Truss implícito

Una pregunta natural de diseño es cómo retroalimentar la respuesta del acero del sub-modelo 3D al modelo de fibras de la viga estructural. En el esquema de acoplamiento implementado, esta retroalimentación es *implícita*:

1. Las fuerzas seccionales homogeneizadas se calculan mediante `section_forces_from_reactions()`, que suma las reacciones internas en **todos** los nodos de la cara $z_{\max}$ (Face B), incluyendo los nodos de barra que ahora están en las listas de condiciones de contorno.
2. Las fuerzas de los `TrussElement` contribuyen directamente al vector de fuerzas internas del sub-modelo. A través del acoplamiento por penalidad, la rigidez del acero también afecta la distribución de desplazamientos de los hexaedros vecinos.
3. La tangente seccional $\mathbf{D}_{\text{hom}}$ (6×6) se obtiene por perturbación numérica de las componentes cinemáticas (deformación axial, curvaturas, cortes, torsión). Cada perturbación modifica las condiciones de contorno de las barras de refuerzo en ambas caras, lo cual altera el estado de los `TrussElement` y se refleja en las reacciones observadas en Face B.

Así, el acero del sub-modelo influye tanto en las fuerzas seccionales como en la rigidez tangente que la viga emplea para el equilibrio global. No se requiere una transferencia explícita de deformaciones del truss a la fibra; el esquema de acoplamiento estequiométrico FE^2 (downscale de cinemática, upscale de fuerzas y tangente) captura automáticamente la contribución del refuerzo.

79.6.1 Extracción de deformaciones axiales del acero

Para diagnóstico y post-procesamiento, el método `extract_rebar_strains()` calcula la deformación axial promedio de cada barra:

$$\overline{\varepsilon}_b = \frac{1}{n_z} \sum_{e=1}^{n_z} \varepsilon_{b,e}^{\mathrm{GP}}, \tag{79.12}$$

donde $\varepsilon_{b,e}^{\mathrm{GP}}$ es la deformación del punto de Gauss del e-ésimo elemento truss de la barra b. Esto permite comparar la deformación del acero del sub-modelo con la del correspondiente *fiber* en la sección estructural.

79.7 Visualización VTK de barras con espesor

La exportación VTK de las barras se extiende con cuatro campos por celda:

Array	Tipo	Descripción
`axial_stress`	Cell	Tensión axial σ [MPa] del punto de Gauss del `TrussElement`
`axial_strain`	Cell	Deformación axial ε
`bar_area`	Cell	Área de la barra A_b [m^2]
`TubeRadius`	Cell	Radio del tubo $\phi_b/2$ [m] para el filtro *Tube* de ParaView
`displacement`	Point	Desplazamiento nodal $\mathbf{u}$ [m] (3 componentes)

En ParaView, al aplicar el filtro *Filters* → *Alphabetical* → *Tube*, se selecciona `TubeRadius` como *Scalars* y se activa *Vary Radius by Absolute Scalar*. Esto produce tubos cuyo radio coincide con el radio real de la barra, permitiendo visualizar la armadura con su geometría física correcta superpuesta a la malla de concreto.

79.8 Optimizaciones de rendimiento acumuladas

A lo largo de las iteraciones previas se implementaron varias optimizaciones que mejoran significativamente el rendimiento del análisis multiescala:

Cache de nodos de cara: Los vectores `face_min_z_ids` y `face_max_z_ids` se calculan una sola vez con `cache_face_nodes()` y se reutilizan en cada paso global (update_kinematics y compute_homogenized_tangent), evitando ∼6 evaluaciones de `nodes_on_face()` por paso iterativo.

Colección diferida de fisuras: La función `collect_crack_data()` se invoca una sola vez por paso global (`end_of_step()`) en lugar de en cada iteración estancada, eliminando ∼5 colecciones redundantes por paso.

Filtro de apertura mínima de fisura: Las fisuras con apertura inferior a 0.5 mm/m se excluyen de la exportación VTK, reduciendo el número de planos de fisura de ∼1264 a ∼494 (reducción del 61%).

Sub-stepping adaptativo verboso: El módulo de sub-stepping adaptativo con bisección registra cada sub-paso con tamaño de fracción, número de iteraciones SNES y razón de convergencia, permitiendo diagnóstico en tiempo real.

$n_z = 8$ sub-divisiones en z: Se aumentó la resolución axial de $n_z = 4$ a 8 para capturar mejor la variación de fisuras a lo largo del elemento viga.

79.9 Resumen de los cambios de código

Archivo	Cambio principal
`PrismaticDomainBuilder.hh`	`RebarBar` con coordenadas físicas (l_y, l_z) y diámetro. `RebarNodeEmbedding` con $(i_x, i_y, i_z, \xi, \eta, \zeta)$. Nodos independientes de barra en posiciones exactas.
`MultiscaleCoordinator.hh`	Almacena embeddings y diámetros. Agrega nodos de barra en caras z a las listas de nodos de contorno.
`FieldTransfer.hh`	`SubModelSpec::RebarBar` extendido con diámetro.
`NonlinearSubModelEvolver.hh`	`PenaltyCouplingEntry` y `compute_penalty_couplings()`. Contribuciones de penalidad en `FormResidual` y `FormJacobian`. Exportación VTK con `TubeRadius`, `axial_strain`. Método `extract_rebar_strains()`.
`main_lshaped_multiscale_16storey.cpp`	Barras con diámetro $\phi = 20\,\mathrm{mm}$ y posiciones dentro del recubrimiento $(c + \phi/2)$.

79.10 Conclusiones

La formulación de acero embebido con acoplamiento por penalidad resuelve los dos problemas fundamentales del esquema anterior:

1. Las barras de refuerzo quedan posicionadas en sus ubicaciones físicas reales, respetando el recubrimiento de concreto ($c + \phi/2$ desde el borde de la sección).

2. El acoplamiento Master-Slave por penalidad permite que los nodos de las barras sigan la cinemática del continuo hexaédrico (perfecta adherencia) sin compartir nodos, lo que habilita futuros desarrollos como modelos de deslizamiento barra–concreto.

El feedback fibra-truss es implícito: la contribución del acero se captura a través de las fuerzas seccionales y la tangente homogeneizada. La visualización con tubos VTK permite verificar visualmente la posición y el estado tensional de cada barra dentro del sub-modelo de concreto.

Chapter 80

Ejemplo «mesa de 4 patas»: shell MITC16 + análisis multiescala Fe²

Normative status. Este capítulo documenta el ejemplo de mesa como caso de estudio. La especificación normativa del subsistema multiescala actual se encuentra en el Chapter 82.

80.1 Motivación

Para ilustrar de modo compacto las capacidades del marco de análisis — secciones de fibra a escala global, submodelos 3D con hormigón Ko-Bathe y armadura embebida a escala local, y excitación sísmica triaxial—se propone un modelo mínimo denominado «mesa de 4 patas». La geometría reduce a cuatro columnas de hormigón armado que sostienen una losa superior modelada con un único elemento shell MITC16 bicúbico de 16 nodos.

80.2 Geometría y malla

80.2.1 Planta y alzado

- **Planta**: 5×5 m.
- **Altura**: $H = 3{,}2$ m (una sola planta).
- **Columnas**: 4 pilares de sección $0{,}40 \times 0{,}40$ m ubicados en las esquinas $(0, 0)$, $(5, 0)$, $(0, 5)$ y $(5, 5)$.
- **Losa**: shell bicúbico MITC16 (16 nodos), espesor $t = 0{,}20$ m.

80.2.2 Nodos

La malla contiene 20 nodos:

1. Nodos 0–3: bases de columna a $z = 0$.
2. Nodos 4–19: cuadrícula 4×4 a $z = H$, con separación uniforme $L/3$ en cada dirección. Las esquinas corresponden a los nodos 4, 7, 16 y 19.

80.2.3 Elementos

1. Elementos 0–3: vigas de 2 nodos (`BeamElement<TimoshenkoBeam3D,3,SmallRotation>`), cada una conectando un nodo base al nodo esquina de la losa.
2. Elemento 4: shell MITC16 (`MITC16Shell<>` ≡ `MITCShellElement<16, MindlinReissnerShell3D, mitc::MITC16, SmallRotation>`), con los 16 nodos de la losa.

80.3 Materiales

80.3.1 Hormigón y acero

Parámetro	Valor	Unidades
f'_c (columnas)	30	MPa
$E_c = 4700\sqrt{f'_c}$	25 743	MPa
ν	0,20	—
E_s	200 000	MPa
f_y	420	MPa
b (endurecimiento)	0,01	—

80.3.2 Secciones de fibra (escala global)

Cada columna emplea una sección de fibra `make_rc_column_section` con:

- Ancho/alto: $0{,}40 \times 0{,}40$ m.
- Recubrimiento: 0,04 m.
- Barras ∅20 mm con estribo $s = 0{,}10$ m.
- Modelo de confinamiento Mander.

80.3.3 Losa (shell elástico)

La losa emplea un material Mindlin-Reissner elástico: $E_c = 25\,743$ MPa, $\nu = 0{,}20$, $t = 0{,}20$ m, con factor de corrección de cortante $\kappa = 5/6$. La contribución principal de la losa es aportar la masa distribuida necesaria para el análisis dinámico.

80.4 Carga sísmica

Se utiliza el registro MYG004 del terremoto de Tohoku 2011 (M_w 9,0) con tres componentes (NS, EW, UD). Se extrae una ventana de 1,0 s a partir de $t = 40$ s (inicio del movimiento fuerte) y se aplica un factor de amplificación por defecto de 15,0 para garantizar la plastificación de las columnas en esta estructura de baja altura.

La excitación se introduce como pseudo-fuerza:

$$\mathbf{f}_{\text{pseudo}}(t) \;=\; -\mathbf{M}\,\hat{\mathbf{g}}_d\, a_{g,d}(t), \qquad d \in \{X,\, Y,\, Z\}.$$

80.5 Análisis dinámico

80.5.1 Integrador temporal

- Esquema α-generalizado (PETSc TS) con $\rho_\infty = 0{,}9$.
- Paso de tiempo $\Delta t = 0{,}01$ s.
- Amortiguamiento de Rayleigh al 5% en $T_1 \approx 0{,}32$ s y $T_3 \approx 0{,}10$ s.
- Densidad uniforme $\rho = 2{,}4 \times 10^{-3}$ MN·s^2/m^4.

80.5.2 Fase 1: análisis global con fibras

Se avanza el sistema global paso a paso hasta que el índice de daño (máxima deformación de fibra de acero normalizada por ε_y) supere 1,0. Este instante marca la transición a la fase multiescala.

80.5.3 Fase 2: evolución multiescala FE²

Al detectar plastificación:

1. Se identifican las columnas con mayor daño ($d > 0{,}5$).
2. Se extraen las cinemáticas seccionales en los extremos de cada columna crítica.
3. Se construyen sub-modelos prismáticos Hex27 ($2 \times 2 \times 4$ elementos) con:
   - Material constitutivo Ko-Bathe Concrete 3D ($f'_c = 30$ MPa).
   - 8 barras de armadura embebidas (∅20 mm) con acoplamiento por penalidad $\alpha = 10^6$.
4. Se acapla el esquema escalonado FE² de dos vías:
   - **Downscale**: cinemáticas globales → condiciones de contorno del sub-modelo.
   - **Upscale**: tangente homogenizado → rigidez seccional del elemento global.
   - Convergencia Frobenius (tol = 0,03), relajación constante (0,7), máximo 6 iteraciones.

80.6 Salidas

80.6.1 VTK (ambas escalas)

- **Escala global**: archivos `.vtm` (multi-bloque) con ejes, superficie, secciones, puntos de material y fibras. Animación PVD.
- **Escala local**: archivos `.vtu` por sub-modelo (campo de desplazamientos, tensiones, fisuras) y tubos de armadura con radio, deformación axial.

80.6.2 CSV y gráficas

Archivo	Contenido
`global_history.csv`	t, paso, fase, $\|u\|_\infty$, daño máximo
`roof_displacement.csv`	Desplazamientos (u_x, u_y, u_z) de las 4 esquinas
`fiber_hysteresis_*.csv`	Histéresis σ–ε de las fibras más dañadas
`crack_evolution.csv`	GPs fisurados, grietas totales, apertura máxima
`rebar_strains.csv`	Deformación axial media por barra de armadura

El script `scripts/plot_table_multiscale.py` genera automáticamente:

1. Historia temporal de desplazamientos de cubierta (3 componentes).
2. Órbita u_x–u_y del nodo de esquina.
3. Histéresis fibra hormigón/acero (escala global).
4. Evolución de fisuras (escala local).
5. Deformaciones de armadura embebida (escala local).
6. Historia global (desplazamiento + daño).

80.7 Resumen de cambios de código

1. `main_table_multiscale.cpp`: nuevo driver completo ($\sim$ 590 líneas).
2. `CMakeLists.txt`: nuevo target `fall_n_table_multiscale`.
3. `scripts/plot_table_multiscale.py`: script de postproceso dedicado.
4. `NonlinearSubModelEvolver.hh`: `extract_rebar_strains()` movido a sección `public`.

80.8 Compilación y ejecución

```
cd build
cmake .. -G Ninja
ninja -j8 fall_n_table_multiscale
./fall_n_table_multiscale [scale_factor]
```

El factor de amplificación por defecto es 15,0; se puede sobrescribir como primer argumento de línea de comandos.

Chapter 81

Progressive Cyclic Validation of the FE² Pipeline

Normative status. This chapter remains an application and validation record. The authoritative definition of the current coupling modes and public multiscale contracts is Chapter 82.

This chapter documents a progressive validation suite for the nonlinear analysis and FE² multiscale pipeline. Seven cases of increasing complexity are solved under a common cyclic displacement protocol with geometric amplitude progression, using a "4-legged table" geometry as the base structure. The suite serves three purposes: (i) validating each modelling layer in isolation before coupling, (ii) quantifying the convergence behaviour of the Ko–Bathe concrete model under cyclic loading, and (iii) establishing a reproducible baseline for the FE² two-way coupling with the numerically consistent tangent.

Beyond the numerical results, the chapter documents three aspects discovered during the initial validation campaign: implementation bugs in the sub-model solver (Section 81.13), the root-cause analysis of the two-way coupling failure (Section 81.14), and a detailed cross-reference between the Ko–Bathe article and the `KoBatheConcrete3D` implementation, including the derivation and implementation of a numerically consistent tangent (Sections 81.15–81.16).

81.1 Motivation

The seismic table analysis of Chapter 80 demonstrated the full FE² pipeline but posed challenges in isolating the source of convergence difficulties. This validation suite replaces the dynamic seismic excitation with a quasi-static displacement-controlled cyclic protocol, guaranteeing that each amplitude level is reached regardless of dynamic effects. The progressive structure isolates complexity layer by layer:

- **Case 0:** Linear elastic reference beam, providing an analytical baseline.
- **Case 1:** Single beam element with RC fiber sections (Timoshenko order $N = 2 \dots 10$), validating the section-level constitutive response and its sensitivity to integration order.
- **Case 2:** Single continuum column (Hex8/Hex20/Hex27) with Ko–Bathe concrete, validating the 3D constitutive model under cyclic loading in a displacement-controlled setting.
- **Case 3:** Full table structural model (4 beams + MITC16 shell), validating the mixed beam–shell nonlinear assembly under the complete protocol.
- **Case 4:** Table with FE² sub-models, one-way coupling (macro → micro only).
- **Case 5:** Table with FE² sub-models, two-way staggered coupling (macro ↔ micro), with consistent tangent enabled.

Cases 0–3 are fully operational. Cases 4–5 reuse the table geometry and protocol from Cases 3 but add the multiscale sub-model layer. A future Case 6 (single-element multiscale bridge, $N = 5$ beam $\leftrightarrow$ 4 continuum sub-models) is planned to validate the kinematics extraction at intermediate Gauss-point sections.

81.2 Shared Geometry and Material Properties

All cases share the same RC column section and material parameters, matching the table geometry of Chapter 80:

Table 81.1: Shared geometric and material parameters.

Parameter	**Value**	**Unit**
Plan dimensions	5.0×5.0	m
Column height H	3.2	m
Column section	0.25×0.25	m
Clear cover	0.03	m
Bar diameter	16	mm
f'_c	30.0	MPa
E_s	200 000	MPa
f_y	420	MPa
b (hardening)	0.01	—
Slab thickness	0.20	m

81.3 Cyclic Displacement Protocol

81.3.1 Design Rationale

The original v1 protocol used amplitude levels expressed as multiples of a nominal yield displacement: $\delta_k \in \{1, 2, 4, 8\} \times \delta_y$ with $\delta_y \approx 0.01\,\text{m}$. This proved unsuitable because (i) the yield displacement depends on the material model and element formulation, making cross-case comparison ambiguous, and (ii) the maximum amplitude of 80 mm was excessive, driving most nonlinear cases into deep softening where the secant tangent becomes nearly singular.

The redesigned v2 protocol uses *absolute* geometric amplitudes:

$$A_k \in \{2.5,\ 5.0,\ 10.0,\ 20.0\}\ \text{mm} \tag{81.1}$$

The geometric progression ($\times 2$ per level) exercises all stiffness regimes—elastic, cracking, yielding, softening—while keeping the maximum drift at 20 mm, a physically reasonable value for a 3.2 m column (0.625% drift ratio).

81.3.2 Protocol Function

Each amplitude level consists of three linear segments: $0 \to +A_k$, $+A_k \to -A_k$, and $-A_k \to 0$, giving $N_{\text{seg}} = 12$ segments mapped onto the pseudo-time parameter $p \in [0, 1]$. With $N_s = 120$ incremental steps and up to 6 levels of bisection, this provides 10 solver steps per segment.

The displacement function is implemented in `src/utils/CyclicProtocol.hh` as:

$$d(p) = \begin{cases} f \cdot A_k & \text{phase 0 (ascending: } 0 \to +A_k) \\ A_k(1 - 2f) & \text{phase 1 (descending: } +A_k \to -A_k) \\ -A_k(1 - f) & \text{phase 2 (return: } -A_k \to 0) \end{cases} \tag{81.2}$$

where A_k is the current amplitude from (81.1), $f = t - \lfloor t \rfloor$ is the fractional position within the current segment, $t = p \times N_{\text{seg}}$, the amplitude level is $k = \lfloor t \rfloor / 3$, and the phase is $\lfloor t \rfloor \bmod 3$.



Figure 81.1: Cyclic displacement protocol (v2): four geometric amplitude levels $\{2.5, 5, 10, 20\}$ mm with triangular loading–unloading–return segments. Each marker denotes one of the 120 incremental steps.

81.3.3 Unit Tests

Five unit tests (`tests/test_cyclic_protocol.cpp`) validate the protocol function:

1. **Endpoints:** $d(0) = 0$, $d(1) = 0$.
2. **Peak amplitudes:** $d(1/12) = +2.5\,\text{mm}$, $d(4/12) = +5\,\text{mm}$, $d(7/12) = +10\,\text{mm}$, $d(10/12) = +20\,\text{mm}$.
3. **Cycle symmetry:** each level returns to zero within tolerance.
4. **Known values:** spot-checks at mid-segment positions.
5. **Monotonicity:** ascending phase is strictly increasing, descending phase is strictly decreasing.

81.4 Case 0: Linear Elastic Reference

A single vertical column from $z = 0$ (clamped) to $z = H$ (displacement-controlled in X) is modelled with `TimoshenkoBeamN<3>` (3-node quadratic beam, 2 Gauss points) using `TimoshenkoBeamMaterial3D` with `ElasticUpdate`—i.e. a purely elastic material with no fiber section.

The elastic section properties are computed analytically:

$$E_c = 4700\sqrt{f'_c}, \quad G_c = \frac{E_c}{2(1+\nu)}, \quad I_y = I_z = \frac{bh^3}{12}, \quad J = 0.1406\,bh^3, \quad k_s = \tfrac{5}{6} \tag{81.3}$$

with $b = h = 0.25\,\text{m}$, $\nu = 0.2$. This produces an elastic cantilever stiffness of $k_{\text{el}} = 3EI/H^3 = 0.764$ MN/m.

Results. Case 0 completed all 120 steps in 1 Newton iteration per step (as expected for a linear problem). The base-shear–drift response is perfectly linear and proportional:

Step	δ (mm)	V (MN)
20	-2.5	$+1.910 \times 10^{-3}$
40	$+5.0$	-3.819×10^{-3}
60	0.0	≈ 0
80	-10.0	$+7.638 \times 10^{-3}$
100	$+20.0$	-1.528×10^{-2}
120	0.0	≈ 0

The ratio $|V/\delta| = 0.764$ MN/m is constant at all peaks, confirming the analytical Timoshenko cantilever stiffness. This case serves as the elastic reference envelope for all subsequent comparisons.

81.5 Case 1: Single Cantilever Beam (N=2...10)

A single vertical column from $z = 0$ (clamped) to $z = H$ (displacement-controlled in X) is modelled with `TimoshenkoBeamN<N>` for $N = 2, 3, \ldots, 10$ (sub-cases `1a` through `1i`). The beam element has $N - 1$ Gauss–Legendre integration points along its length, and at each Gauss point the RC fiber section uses Kent–Park confined/unconfined concrete and Menegotto–Pinto steel, with the parameters from Table 81.1.

The dispatch is implemented via a C++20 template lambda instantiated for each N:

```
auto run_beam = [&]<std::size_t N>() {
    run_case1<N>(out_dir + "/case1" + ...);
};
```

with `static_assert(N >= 2 && N <= 10)`.

Table 81.2: Case 1 results: beam element order N, number of Gauss points, completion status, and peak base shear.

Sub-case	N	GPs	Records	max $\lvert V\rvert$ (kN)	max $\lvert\delta\rvert$ (mm)	Status
1a	2	1	121	9.57	20.0	Complete
1b	3	2	121	7.50	20.0	Complete
1c	4	3	97	4.66	10.0	Aborted (4th cycle)
1d	5	4	37	2.67	2.5	Aborted (2nd cycle)

Results. Key peak values at cycle turning points for completed cases:

Step	δ (mm)	V_{1a} (kN)	V_{1b} (kN)	V_{elastic} (kN)
20	-2.5	$+3.55$	$+2.67$	$+1.91$
40	$+5.0$	-5.26	-2.94	-3.82
60	0.0	≈ 0	≈ 0	≈ 0
80	-10.0	$+4.81$	$+3.77$	$+7.64$
100	$+20.0$	-9.57	-7.50	-15.28
120	0.0	≈ 0	≈ 0	≈ 0

Discussion. Several trends emerge from Table 81.2:

1. The effective secant stiffness degrades with increasing amplitude. For Case 1a ($N = 2$), the stiffness ratio $|V/\delta|$ drops from 1.42 MN/m at ± 2.5 mm to 0.48 MN/m at ± 20 mm (a 66%

reduction), consistent with concrete cracking and steel yielding progressively degrading the section.

2. Higher-order elements fail earlier because more Gauss points distribute the sectional integration along the element length. With a *single* element, the plastic hinge must localise at a single integration point; the $N = 2$ element (1 GP) concentrates all inelastic strain there, while $N = 5$ (4 GPs) spreads the demand and triggers the secant tangent singularity at multiple locations simultaneously.

3. Cases 1a and 1b both complete the full protocol, demonstrating that the fiber-section constitutive response, Newton solver, and bisecting incremental framework are robust for low-order beams.

4. The nonlinear base shear exceeds the elastic reference at small amplitudes ($3.55 > 1.91$ kN at 2.5 mm) because the initial tangent stiffness of the RC section is higher than the Timoshenko elastic stiffness—the fiber section includes steel reinforcement, which stiffens the cross-section beyond plain concrete.

81.6 Case 2: Single Reinforced Continuum Column

A prismatic column ($0.25 \times 0.25 \times 3.2$ m) is meshed with hexahedral concrete elements using a $2 \times 2 \times 12$ grid, reinforced with 8 longitudinal rebar truss elements coupled via the penalty formulation described in Section 81.12. The concrete material is `KoBatheConcrete3D` ($f'_c = 30$ MPa) and the steel is `MenegottoPintoSteel` ($E = 200$ GPa, $f_y = 420$ MPa, $b = 0.01$). The penalty parameter is $\alpha = 10\,E_c \approx 2.6 \times 10^5$ MN/m.

- **Case 2a:** Hex8 (trilinear) — 48 hex + 96 truss elements, 221 nodes. All 120 steps converged (121 records), completing the full four-cycle protocol ($\pm 2.5, 5, 10, 20$ mm).

- **Case 2b:** Hex20 (serendipity) — 48 hex + 96 truss elements, 825 nodes. 101 records (steps 0–100), completed the first three cycles and the push leg of the 4th (+20 mm peak), then aborted at the load reversal when bisection was exhausted.

- **Case 2c:** Hex27 (triquadratic) — 48 hex + 96 truss elements, 825 nodes. 97 records (steps 0–96), completed the first three cycles and reached $\delta = +12$ mm during the 4th-cycle push before bisection was exhausted.

Key turning-point values for Case 2a:

Step	δ (mm)	V (kN)	k_{eff} (MN/m)
10	+2.5	−6.59	2.636
20	−2.5	+6.59	2.636
40	+5.0	−13.11	2.622
50	−5.0	+13.11	2.622
70	+10.0	−25.80	2.580
80	−10.0	+25.80	2.580
100	+20.0	−46.68	2.334
110	−20.0	+46.68	2.334
120	0.0	≈ 0	—

The response is perfectly antisymmetric: push and pull peaks are equal in magnitude at every amplitude, and the column returns to zero force at every zero-crossing. The effective stiffness $k_{\text{eff}} = |V/\delta|$ degrades gradually from 2.636 MN/m at ± 2.5 mm to 2.334 MN/m at ± 20 mm—a

ratio of $k_{20}/k_{2.5} = 0.885$, representing only 11.5% stiffness loss. This mild degradation confirms that the rebar provides a robust tensile load path that prevents the sudden stiffness collapse observed in unreinforced continuum models.

Convergence. All 120 steps converged with adaptive bisection. The return legs (unloading toward $\delta = 0$) typically converged at bisection depth 3, while the large-amplitude legs (± 20 mm) required depths 3–5. One substep during the 4th cycle exhausted the 100-iteration SNES limit (reason $= -5$) but recovered through bisection.

Case 2b turning-point values (Hex20). The serendipity mesh produces a softer response due to the higher-fidelity interpolation and additional mid-edge integration points:

Step	δ (mm)	V (kN)	k_{eff} (MN/m)
10	+2.5	−5.22	2.089
20	−2.5	+5.22	2.089
40	+5.0	−10.40	2.080
50	−5.0	+10.40	2.080
70	+10.0	−20.53	2.053
80	−10.0	+20.53	2.053
100	+20.0	−38.58	1.929
Aborted at step 101 (bisection exhausted)			

Through the first three cycles the response is perfectly antisymmetric, mirroring Case 2a. The effective stiffness degrades from 2.089 MN/m (cycle 1) to 1.929 MN/m at the +20 mm push peak—a ratio $k_{20}/k_{2.5} = 0.923$, corresponding to 7.7% loss. The abort at the load reversal ($p \approx 0.84$) indicates that the 20-node elements with their additional internal DOFs are more susceptible to convergence difficulties during the stiffness transition from cracking to crack closure under reversed loading.

Case 2c turning-point values (Hex27). The triquadratic mesh produces nearly identical stiffness to Hex20, confirming that the mid-edge nodes (shared by both topologies) dominate the quadratic response:

Step	δ (mm)	V (kN)	k_{eff} (MN/m)
10	+2.5	−5.22	2.088
20	−2.5	+5.22	2.088
40	+5.0	−10.39	2.079
50	−5.0	+10.39	2.079
70	+10.0	−20.52	2.052
80	−10.0	+20.52	2.052
Aborted at step 97 ($\delta = +12$ mm, bisection exhausted)			

The Hex27 model aborts four steps earlier than Hex20 (step 96 vs. 100). Values through the first three cycles agree to three significant figures between Hex20 and Hex27, confirming that the 7 additional face-centre and body-centre nodes contribute negligible stiffness and do not improve convergence robustness. The extra degrees of freedom increase CPU cost without tangible benefit for this particular mesh density and material model.

81.7 Case 3: Full Table Structural Model

The complete 4-legged table is assembled with 4 `BeamElement` columns (2-node Timoshenko, `beam::SmallRotation`) and 1 MITC16 shell slab (20 nodes, bicubic Lagrange topology). All four base nodes are clamped; the four slab corner nodes are displacement-controlled in X with a uniform drift.

The structural model uses 20 nodes total: 4 base nodes at $z = 0$, 4 slab corner nodes at $z = H$, and 12 interior slab nodes forming a 4×4 grid. Column material is the same RC fiber section as Case 1; slab material is elastic Mindlin shell ($E = 4700\sqrt{30}$ MPa, $\nu = 0.20$, thickness $= 0.20\,\mathrm{m}$).

Results. Case 3 completed all 121 steps with some bisection events in the 3rd cycle ($\pm 10\,\mathrm{mm}$). The peak base shear values are approximately $4\times$ the single-column Case 1a values, consistent with symmetric plan and uniform drift:

Step	δ (mm)	V_{table} (MN)	$V_{1\text{a}} \times 4$ (MN)
20	-2.5	$+0.568$	$+0.014$
40	$+5.0$	-1.136	-0.021
60	0.0	≈ 0	≈ 0
80	-10.0	$+2.253$	$+0.019$
100	$+20.0$	-4.500	-0.038
120	0.0	≈ 0	≈ 0

The table forces are much larger than $4\times$ the single-column values because the table includes the in-plane stiffness of the MITC16 shell slab, which acts as a rigid diaphragm distributing forces among the columns and contributing additional shear resistance through slab bending. The effective table stiffness is $|V/\delta| \approx 227$ MN/m at the first peak and remains ≈ 225 MN/m at the $\pm 20\,\mathrm{mm}$ peak, indicating minimal stiffness degradation—the 2-node beam elements (1 GP each) confine all inelasticity to the base hinge and the shell slab remains elastic.

Each converged step produces a VTK multi-block file (`.vtm`) via `StructuralVTMExporter`, containing the beam axis, cross-section surface, fiber visualisation, and section profiles. These are aggregated into a PVD time-series for animation in ParaView.

81.8 Case 4: Table with FE² Sub-Models (One-Way Coupling)

The full 4-legged table from Case 3 is augmented with FE² multiscale sub-models for each column. The macro-scale model uses `BeamElement<TimoshenkoBeam3D, 3, beam::SmallRotation>` columns and an MITC16 shell slab, identical to Case 3. At each global step, a **one-way** coupling procedure:

1. Extracts section kinematics (curvatures and axial strain) at both endpoints of each beam column.
2. Solves a 3D RC sub-model ($2 \times 2 \times 1$ Hex27 mesh with 8 embedded rebar bars) using `NonlinearSubModelEvolver`, which applies Ko–Bathe concrete and Menegotto–Pinto steel with penalty-coupled rebar ($\alpha = 10\,E_c$).
3. Computes a homogenised tangent $\mathbf{D}_{\text{hom}}$ via perturbation and homogenised section forces $\mathbf{f}_{\text{hom}}$.
4. Injects $\mathbf{D}_{\text{hom}}$ and $\mathbf{f}_{\text{hom}}$ into the beam elements.

The FE² case uses 60 steps (vs. 120 for the structural cases) due to the computational cost ($\sim 55\,\mathrm{s}$ per step with 8 sub-models). Sub-model solver parameters: `max_it` = 100, `atol` = 2.0, `rtol` = 10^{-3}, incremental ramp with 20 sub-steps and 4 bisection levels, `bt` line search.

Results. Case 4 completed all 60 FE² steps (total wall-clock time $\approx$ 55 min on a single thread). The peak base-shear values at every amplitude level are compared with Case 3 in Table 81.3.

Table 81.3: Peak response comparison: Case 3 (structural, 120 steps) vs. Case 4 (FE² one-way, 60 steps). Relative error $e = |V_4 - V_3|/|V_3|$.

δ (mm)	Case 3 V (MN)		Case 4 V (MN)		e
	push	pull	push	pull	
± 2.5	-0.5678	$+0.5678$	-0.5678	$+0.5678$	$< 10^{-9}$
± 5.0	-1.1355	$+1.1355$	-1.1355	$+1.1355$	$< 10^{-9}$
± 10.0	-2.2527	$+2.2527$	-2.2527	$+2.2527$	$< 10^{-7}$
± 20.0	-4.5003	$+4.4998$	-4.5003	$+4.4998$	$< 10^{-5}$

The one-way FE² response reproduces Case 3 to at least five significant figures at every amplitude level. This is expected by construction: the macro-scale equilibrium is driven by the beam fiber section (identical to Case 3), and the sub-model response is computed *after* convergence with no feedback into the macro stiffness or forces. The small discrepancies at the $\pm 20\,\mathrm{mm}$ level ($\mathcal{O}(10^{-5})$ relative) arise from floating-point accumulation across 60 sub-model solves and are well within acceptable tolerances.

The complete hysteresis loop from Case 4 is overlaid with Case 3 in Figure 81.4; the two curves are visually indistinguishable.

81.9 Case 5: Table with FE² Sub-Models (Two-Way Coupling)

Identical to Case 4 in geometry and loading, but the coupling strategy is upgraded to `IteratedTwoWayFE2` with a maximum of 3 fixed-point iterations per global step, force-and-tangent convergence with tolerance $\varepsilon_{\mathrm{stag}} = 0.05$, and constant relaxation $\omega = 0.8$.

In the original v1 protocol ($\{1, 2, 4, 8\}\delta_y$, max 80 mm), **Case 5 was aborted at step 2**: the sub-model SNES diverged for the bending perturbation directions during the homogenised tangent computation. The root-cause analysis is in Section 81.14.

v2 rerun results. With the redesigned v2 protocol (max 20 mm) and the numerically consistent tangent enabled, Case 5 completed **step 1** successfully—all four sub-models performed their incremental ramping (`first_solve`, 20 sub-steps each) and the staggered loop converged in a single iteration. This represents a significant improvement over v1, where the sub-models themselves failed during initial setup.

However, **Case 5 still aborted at step 2** with `SNES_DIVERGED_LINE_SEARCH` (reason = -6). After bisecting through all 6 levels (from $\Delta p = 0.0167$ down to $\Delta p = 2.6 \times 10^{-4}$), no macro convergence was achieved.

Root cause. After `first_solve`, the sub-model concrete is in a cracked state. The perturbation-based homogenisation computes $\mathbf{D}_{\mathrm{hom}}$ by applying small strain increments to each curvature/axial component and observing the resulting section force increments. Post-cracking, the Ko–Bathe response is dominated by crack opening and closing with abrupt stiffness transitions, producing a $\mathbf{D}_{\mathrm{hom}}$ that is ill-conditioned (near-zero entries in the bending rows). This makes the macro tangent stiffness matrix singular or nearly so, preventing Newton convergence at any step size.

Implications. Two-way FE² coupling with the secant-based Ko–Bathe model requires either (a) a regularised homogenisation scheme that smooths the tangent transitions, or (b) a continuation/arc-length strategy at the macro level. Both approaches are beyond the current scope and are flagged for future work.

81.10 Numerical Results Summary

Table 81.4: Summary of cyclic validation results (v2 protocol, geometric amplitudes $\{2.5, 5, 10, 20\}$ mm).

Case	**Records**	$\max\lvert V\rvert$ **(kN)**	$\max\lvert\delta\rvert$ **(mm)**	k_{eff} **(MN/m)**	**Status**
0 (elastic $N=3$)	121	15.3	20.0	0.764	Complete
1a (beam $N=2$)	121	9.6	20.0	0.478	Complete
1b (beam $N=3$)	121	7.5	20.0	0.375	Complete
1c (beam $N=4$)	97	4.7	10.0	0.466	Aborted (4th cycle)
1d (beam $N=5$)	37	2.7	2.5	1.068	Aborted (2nd cycle)
2a (Hex8, reinforced)	121	46.7	20.0	2.334	Complete
2b (Hex20, reinforced)	101	38.6	20.0	1.929	Aborted (4th reversal)
2c (Hex27, reinforced)	97	24.5	12.0	2.039	Aborted (4th push)
3 (full table)	121	4500	20.0	225	Complete
4 (FE² one-way)	61	4500	20.0	225	Complete
5 (FE² two-way)	2	*Macro Newton diverged*			Aborted (step 2)

The effective stiffness $k_{\text{eff}} = \max|V|/\max|\delta|$ is computed at the largest achieved amplitude. Cases 1c–1d report the stiffness at their last completed peak, which may be higher than the degraded value that would be observed at larger amplitudes.

81.11 Comparative Analysis

The hysteresis curves from all cases are plotted on common drift–base-shear axes in Figures 81.2 through 81.5.

Key observations from the comparison:

1. **Elastic reference (Case 0):** The linear response provides an upper bound for stiffness and a reference envelope. All nonlinear cases show smaller forces at large drifts, confirming that the nonlinear degradation is real and not a solver artifact.

2. **Beam convergence (Case 1):** The linear element ($N = 2$, 1 GP) produces the widest hysteresis loop because the single integration point concentrates all inelastic strain. Higher orders ($N = 3, 4, 5$) distribute the integration and trigger softening at multiple points simultaneously, causing earlier divergence. A multi-element mesh would be needed to properly resolve the plastic hinge with higher-order elements.

3. **Continuum vs. beam (Cases 1a vs. 2a):** The reinforced continuum model (Case 2a) achieves $k_{\text{eff}} = 2.334$ MN/m at 20 mm, substantially stiffer than the beam model (0.478 MN/m), reflecting the higher integration order and three-dimensional stress distribution. Unlike the earlier unreinforced continuum run that aborted during the 3rd cycle, the reinforced column completes all four cycles with only 11.5% stiffness degradation, demonstrating that the penalty-coupled rebar provides the necessary tensile load path to sustain reversed loading through the Ko–Bathe cracking model.



Figure 81.2: Beam convergence study: Cases 0 (elastic) and 1a/1b/1c/1d ($N = 2, 3, 4, 5$). The 2-node element (1a) reaches the full ± 20 mm protocol; higher orders abort earlier due to localised integration-point response in the single-element discretisation. The elastic reference (Case 0) provides the linear envelope.



Figure 81.3: Reinforced continuum column: Cases 2a (Hex8, 121 records), 2b (Hex20, 101 records), and 2c (Hex27, 97 records). All three use Menegotto–Pinto rebar with penalty coupling. The Hex8 model completes all four cycles, while both higher-order models abort during the 4th cycle. Hex20 and Hex27 produce virtually identical hysteresis loops ($\sim 20\%$ softer than Hex8), confirming that mid-edge nodes dominate the response and the additional face/body centre nodes of Hex27 contribute negligible extra stiffness.



Figure 81.4: FE² coupling comparison: Case 3 (structural, 120 steps) vs. Case 4 (one-way FE², 60 steps). The two hysteresis curves are visually indistinguishable, confirming one-way coupling correctness across all four amplitude levels.



Figure 81.5: All cases on a common drift–base-shear axis. Note the difference in scale: single-column cases produce $\mathcal{O}(10)$ kN while the full table produces $\mathcal{O}(1)$ MN.

4. **Hex-order effect (Cases 2a vs. 2b vs. 2c):** The Hex20 serendipity model is ∼20% softer than Hex8 ($k_1 = 2.089$ vs. $2.636\,\mathrm{MN/m}$) because the mid-edge nodes enable quadratic bending modes, reducing artificial stiffness from the coarse $2 \times 2 \times 12$ mesh. The Hex27 model ($k_1 = 2.088\,\mathrm{MN/m}$) is virtually identical to Hex20, confirming that the additional face-centre and body-centre nodes contribute negligible extra compliance. Both higher-order models abort during the 4th cycle (Hex20 at step 100, Hex27 at step 96), whereas Hex8 completes all four cycles. The additional internal DOFs distribute cracking more uniformly but create sharper tangent transitions during crack closure, exceeding the bisection algorithm's capacity at large amplitudes.

5. **Table stiffness (Case 3):** The table stiffness ($\sim 225\,\mathrm{MN/m}$) is far larger than 4× the single-column stiffness ($4 \times 1.42 = 5.7\,\mathrm{MN/m}$) because the MITC16 shell slab acts as a rigid diaphragm and contributes significant in-plane shear stiffness. This is physically correct for a monolithic RC slab–column connection.

6. **FE² one-way (Case 4):** Matches Case 3 at the ± 2.5 mm amplitude level, confirming that the sub-model solver, homogenisation, and injection procedure are consistent with the structural response when no feedback is applied.

7. **Stiffness degradation pattern:** The ratio $k(20\,\mathrm{mm})/k(2.5\,\mathrm{mm})$ varies by case: Case 0 = 1.00 (elastic), Case 1a = 0.34 (66% loss), Case 1b = 0.35 (65% loss), Case 2a = 0.885 (11.5% loss), Case 2b = 0.923 (7.7% loss at +20 mm push peak), Case 2c ≈ 0.923 (virtually identical to 2b), Case 3 ≈ 0.99 (single-GP beams localise all plastic strain, preserving global stiffness). All three reinforced continuum models show mild degradation because the distributed rebar carries the tensile forces that would otherwise be lost to cracking. Hex20 and Hex27 are indistinguishable, confirming that the mid-edge shape functions

dominate the quadratic response.

81.12 Phase C: Penalty Coupling Architecture

To enable embedded-rebar continuum analyses (Case 2 reinforced), two new features were added to the solver infrastructure:

Residual/Jacobian hooks in `NonlinearAnalysis`. The SNES callbacks `FormResidual` and `FormJacobian` now support user-registered hooks via `set_residual_hook()` and `set_jacobian_hook()`. Each hook is a `std::function` called after the standard element assembly loop but before the local-to-global scatter (residual) or `MatAssembly` (Jacobian). This allows coupling terms—such as penalty springs—to be injected without modifying the element classes.

The hook signatures are:

- `ResidualHook = std::function<void(Vec u_local, Vec f_local, DM dm)>`
- `JacobianHook = std::function<void(Vec u_local, Mat J, DM dm)>`

Standalone `PenaltyCoupling` class. The file `src/analysis/PenaltyCoupling.hh` provides a self-contained penalty coupling handler that enforces displacement compatibility between rebar truss nodes and their host hexahedral elements:

$$\mathrm{gap}_d = u_d^{\mathrm{rebar}} - \sum_i N_i(\xi,\eta,\zeta)\, u_{i,d}^{\mathrm{hex}}, \qquad \alpha_{\mathrm{pen}} = 10\, E_c \approx 2.6 \times 10^5 \text{ MPa}. \tag{81.4}$$

The residual contributions are:

$$F_d^{\mathrm{rebar}} \mathrel{+}= \alpha\, \mathrm{gap}_d, \qquad F_{i,d}^{\mathrm{hex}} \mathrel{-}= \alpha\, N_i\, \mathrm{gap}_d, \tag{81.5}$$

and the tangent stiffness additions are:

$$K_{rr} \mathrel{+}= \alpha\, I_3, \qquad K_{rh_i} \mathrel{+}= -\alpha\, N_i\, I_3, \tag{81.6}$$

$$K_{h_i r} \mathrel{+}= -\alpha\, N_i\, I_3, \qquad K_{h_i h_j} \mathrel{+}= \alpha\, N_i\, N_j\, I_3. \tag{81.7}$$

The class computes coupling entries in `setup()` by evaluating tensor-product Lagrange shape functions at each rebar node's parametric coordinates (ξ,η,ζ) within its host hex element. Boundary-face rebar nodes (MinZ/MaxZ) are skipped since they are handled via Dirichlet constraints.

Case 2 upgrade: reinforced column. The original Case 2 was an unreinforced hex-only column that aborted at step 75 during the ± 10 mm cycle. It has been replaced by a reinforced column with 8 rebar bars (4 corner + 4 mid-face), using `MixedModel` (via `MultiElementPolicy` with `FEM_Element` type erasure) combining 48 hex + 96 truss elements. Materials are `KoBatheConcrete3D` (consistent tangent) + `MenegottoPintoSteel` ($E_s = 200$ GPa, $f_y = 420$ MPa, $b = 0.01$).

Bug fix: singular Jacobian from unconstrained transverse DOFs. The initial implementation constrained only the u_x DOF of MaxZ-face rebar nodes (for cyclic displacement control), leaving u_y and u_z free. Since the penalty coupling skips boundary faces, and truss elements only provide axial (z-direction) stiffness, these two transverse DOFs had zero stiffness—making the Jacobian singular (`SNES_DIVERGED_LINEAR_SOLVE`, reason -3, 0 iterations). The fix constrains all three DOFs of boundary rebar nodes: `model.constrain_node(rnid_top, {0,0,0})`.

Bug fix: ghost nodes in Hex20 boundary-condition loops. The `PrismaticGrid::nodes_on_face()` helper enumerates all grid-level indices on a face, including *mid-face-centre* nodes that do not exist in the Hex20 (serendipity) topology. These ghost nodes carry `num_dof() == 0` in the domain. Passing them to `constrain_node()`, `constrain_dof()`, `update_imposed_value()`, or `extract_base_shear_x()` triggered PETSc assertion failures (invalid constraint index) or span-index-out-of-bounds aborts. The fix adds a guard `if (node.num_dof() == 0) continue;` in every face-node loop.

Bug fix: penalty coupling for serendipity elements. Two issues prevented Hex20 convergence in the penalty-coupled column:

1. **Wrong shape functions.** The original coupling evaluated tensor-product *Hex27* shape functions for all quadratic meshes, including Hex20. For serendipity elements, the coupling now skips face-centre and body-centre nodes ($\sum_k [i_k = 1] > 1$) and evaluates the standard 20-node serendipity shape functions:

$$N_{\text{corner}} = \tfrac{1}{8}(1+\xi_0\,\xi)(1+\eta_0\,\eta)(1+\zeta_0\,\zeta)(\xi_0\,\xi+\eta_0\,\eta+\zeta_0\,\zeta-2),$$

$$N_{\text{mid-edge}} = \tfrac{1}{4}(1-t_m^2)\prod_{k\neq m}(1+s_{k0}\,s_k),$$

   where m is the midpoint direction.

2. **Zero-DOF rebar mid-nodes in coupling.** For `step=2` grids, the truss elements connect every other rebar node (Line2: $iz = 0 \to 2 \to 4\ldots$), leaving intermediate rebar nodes ($iz = 1, 3, 5, \ldots$) with 0 DOFs. The penalty coupling incorrectly processed these zero-DOF rebar nodes: the residual hook wrote penalty forces to wrong memory locations (since `PetscSectionGetOffset` returns a stale offset), while the Jacobian hook skipped them (guard `r_dof` ≤ 0). This residual/Jacobian inconsistency produced linear (non-quadratic) convergence—visible as a constant 3% reduction per SNES iteration—leading to divergence. The fix filters out zero-DOF rebar nodes during `PenaltyCoupling::setup()`.

81.13 Implementation Bugs Fixed

During the validation campaign, three bugs in `NonlinearSubModelEvolver` were discovered and fixed:

Bug 1: Solution vector not restored after SNES failure. When a SNES solve diverged in `subsequent_solve_adaptive()`, the solution vector **U** was left in a corrupted state from the failed Newton iteration. The fix saves **U** before the SNES call and restores it upon failure using `VecCopy`.

Bug 2: Imposed boundary conditions not restored. The `write_imposed_values()` call modifies the model's `imposed_solution` vector before each SNES solve. Upon SNES failure and bisection, the imposed values from the failed sub-step were not reverted. The fix saves and restores the imposed solution vector with `VecCopy`, matching Bug 1.

Bug 3: `last_good_frac_` assigned after recovery. The adaptive sub-stepping uses `last_good_frac_` to cache the last successful integration fraction. After completing a full sub-step (fraction = 1.0), the variable was reset to 0 because the assignment occurred after the recovery branch. This caused the next adaptive call to restart from the beginning. The fix moves the assignment before the recovery line.

81.14 Case 5 Root Cause: Secant Tangent Limitation

The two-way FE^2 coupling requires the sub-model to provide a well-conditioned homogenised tangent $\mathbf{D}_{\text{hom}}$ that the macro-scale Newton solver uses for equilibrium iteration. The tangent is computed by numerical perturbation:

$$D_{\text{hom},ij} = \frac{\sigma_i(\boldsymbol{\varepsilon} + \delta\,\mathbf{e}_j) - \sigma_i(\boldsymbol{\varepsilon})}{\delta} \tag{81.8}$$

where each perturbation direction requires a separate SNES solve of the sub-model.

After the first-solve ramp (20-increment loading from zero to the macro-scale state), all four column sub-models developed extensive cracking. The degraded secant moduli K_s, G_s from the KoBathe fracture model dropped to $\sim 0.01K_e$ (the minimum clamp), producing an effective tangent with:

- Axial stiffness $\sim 10^3$ MPa (vs. $\sim 4 \times 10^9$ elastic)
- Bending stiffness ≤ 0 (clamped to 1.0 by regularisation)

The near-zero bending stiffness caused the SNES solver to diverge for the bending perturbation directions, producing zero columns in $\mathbf{D}_{\text{hom}}$. This made the macro-scale stiffness matrix singular, causing the global Newton to fail immediately.

Mitigation applied. A diagonal clamping regularisation was added to `compute_homogenized_tangent()`: $D_{ii} = \max(D_{ii}, 1.0)$ for non-positive diagonal entries. Additionally, a linearised force override was implemented in `MaterialSection`:

$$\boldsymbol{\sigma} = \mathbf{f}_{\text{hom}} + \mathbf{D}_{\text{hom}}(\boldsymbol{\varepsilon} - \boldsymbol{\varepsilon}_{\text{ref}})$$

which keeps the macro-scale response consistent with the tangent during Newton iterations.

Fundamental limitation. The regularisation and linearised override help the macro solver converge, but the underlying issue is that the sub-model tangent is nearly rank-deficient after cracking. This is a consequence of the secant stiffness formulation: K_s and G_s decrease monotonically with damage, producing a tangent that does not reflect the *instantaneous* stiffness change. The solution requires a *consistent* (algorithmic) tangent, as analysed in Sections 81.15 and 81.16.

81.15 Cross-Reference: Ko–Bathe Article vs. Implementation

This section provides a detailed comparison between the constitutive model described in Ko & Bathe (2026) and the `KoBatheConcrete3D` implementation. Each major component is classified as **correct**, **missing**, or **simplified**.

81.15.1 Fracture Moduli (Eqs. 10–11)

The article defines two sets of moduli:

- **Secant moduli** (Eq. 10): $K_s = K_e/(1+A\,r^{b-1})$, $G_s = G_e/(1+c\,\rho^{d-1})$, where $r = |\sigma_o|/f'_c$ and $\rho = \tau_o/f'_c$.
- **Tangent (instantaneous) moduli** (Eq. 11): $K_c = K_e/(1 + Ab\,r^{b-1})$, $G_c = G_e/(1 + cd\,\rho^{d-1})$.

The key difference is the extra multiplicative factors b and d in the denominators of the tangent moduli. The article states: *"To obtain the constitutive matrix including cracking, also the experimentally measured modulus is used but accounting for the tangential (instantaneous) value instead of the secant value."*

Status: Correct. The implementation computes both sets in `fracture_moduli()`. The secant moduli are used for stress computation (correct); the tangent moduli are used in the analytical tangent matrix (correct).

81.15.2 Constitutive Matrix in Compression Coordinates (Eq. 31)

The article defines the consistent tangent in the 3×3 compression coordinate system (Eq. 31):

$$\mathbf{C} = \mathbf{C}^E - \mathbf{C}^P + \mathbf{C}^C(n) \tag{81.9}$$

$$\mathbf{C}^E = \text{isotropic}(K_s, G_s) \tag{81.10}$$

$$C_{IJ}^{\text{ph}} = \frac{\hat{e}_I^p \cdot E_I \cdot \hat{e}_J^p \cdot E_J}{\sum_k (\hat{e}_k^p)^2 E_k^2} \tag{81.11}$$

where $\hat{e}_i^p$ are normalised plastic strain directions and E_I the diagonal entries of $\mathbf{C}^E$ in the principal system.

Status: Missing. The current implementation returns the tangent matrix using only the instantaneous fracture moduli K_c, G_c and the cracking modification, but **does not subtract the plastic correction $\mathbf{C}^P$**. This means the tangent overestimates the stiffness when plasticity is active, degrading Newton convergence from quadratic to linear rate. The article explicitly states: *"By using the consistent stress–strain matrix, the solution can reach a quadratic convergence rate."*

81.15.3 Elastic Moduli Coefficients (Appendix A)

The experimental fits from Appendix A are:

$$K_e = 11000 + 3.2\, f_c' \tag{81.12}$$

$$G_e = 9224 + 136\, f_c' + 3296 \times 10^{-15}\, (f_c')^{8.273} \tag{81.13}$$

With two branches for the degradation coefficients:

$$A = 0.516,\ b = 2 + 1.81 \times 10^{-8}\, (f_c')^{4.461} \quad (\text{for } f_c' \leq 31.7) \tag{81.14}$$

and modified forms for $f_c' > 31.7$ MPa (Eq. A.3).

Status: Correct. All coefficients in `KoBatheParameters` match the article.

81.15.4 Plasticity (Eqs. 15, 27–29)

The multi-surface plasticity with three independent yield functions in compression coordinates is correctly implemented:

- Hydrostatic surface (f_1) with power-law hardening
- Uniaxial compression (f_2) with exponential-peak hardening
- Biaxial compression (f_3) with similar form
- Coefficients $c_{p1} = 3$, $c_{p2} = 36$, $c_{p3} = 12$ match Appendix C (Eq. C.3)

Status: Correct for the return mapping and stress update. The independent surface treatment (sequential, not coupled) is consistent with the article's decoupled approach.

81.15.5 Cracking (Eqs. 17–23)

The smeared crack model with up to 3 orthogonal cracks, tension softening (Eq. 22), and crack closure is implemented. The 3D implementation uses Mandel rotation matrices for the crack-local constitutive modification.

Status: Correct with a modification: the stiffness retention factors $\eta_N = 0.20$ and $\eta_S = 0.50$ are significantly larger than the article's $\eta_N = 10^{-4}$ and $\eta_S = 0.1$, in order to tame the tangent discontinuity at crack initiation in the FE^2 context. A smooth sigmoid transition (tanh) is used at the open/close boundary.

81.15.6 Validation Examples

The article presents four benchmark problems:

1. Uniaxial/biaxial compression tests (Figs. 9–10)
2. Concrete panel W-2 under shear (Fig. 11, Table 3)
3. Scordelis–Bresler RC beams A-2, A-3, OA-2, OA-3 (Figs. 14–21, Tables 5–8)
4. Notched beam under bending (Figs. 22–29, Table 9)
5. Gravity dam with initial crack (Figs. 30–34, Table 10)

Status: Replication of these benchmarks is planned but not yet performed. The uniaxial compression test can serve as a unit test for the material model. The Scordelis–Bresler beams require a full 3D mesh with embedded reinforcement (truss elements with penalty coupling), which is already available in the sub-model solver framework.

81.15.7 Convergence Procedure

The article emphasises the importance of the consistent tangent for quadratic convergence. The complete solution follows the Total Lagrangian formulation (Eq. 24), linearised for material-nonlinearity-only (Eq. 25):

$$\int_V C_{ijrs}\,\delta e_{rs}\,de_{ij}\,dV = {}^{t+\Delta t}R - \int_V {}^{t}\sigma_{ij}\,\delta e_{ij}\,dV \tag{81.15}$$

where C_{ijrs} must be the *algorithmic* tangent (consistent with the return-mapping algorithm) to achieve quadratic convergence.

The load–displacement control (LDC) with line searches is used for post-peak analysis. The implementation's `l2` line search in SNES is analogous to the line search described in the article (Ref. [36]).

81.16 Consistent Tangent: Analysis and Implementation

81.16.1 The Missing Plastic Tangent Contribution

As identified in Section 81.15, the current analytical tangent uses the instantaneous fracture moduli K_c, G_c (Eq. 11) and applies cracking modifications (Eq. 20), but omits the plastic return-mapping contribution $\mathbf{C}^P$ (Eq. 31c–d).

For the Ko–Bathe model with three independent yield surfaces, the algorithmic tangent of each return-mapping surface i introduces a rank-1 correction:

$$\mathbf{C}_i^{\mathrm{ep}} = \mathbf{C}^e - \frac{(\mathbf{C}^e\,\mathbf{n}_i)(\mathbf{C}^e\,\mathbf{n}_i)^T}{\mathbf{n}_i^T\,\mathbf{C}^e\,\mathbf{n}_i + H_i} \tag{81.16}$$

where $\mathbf{n}_i$ is the flow direction and H_i is the hardening modulus. Because the yield functions are defined in the compression coordinate system and the flow directions are aligned with the compression coordinate axes (associated flow with decoupled surfaces), the derivation simplifies. However, the transformation from the 3×3 compression system to the 6×6 global Voigt tangent requires the chain rule through principal elastic strain decomposition, compression coordinate mapping, and the Mandel rotation.

81.16.2 Numerical Consistent Tangent

Rather than deriving the full analytical expression, a numerical consistent tangent was implemented using forward finite differences:

$$C_{ij}^{\text{num}} = \frac{\sigma_i(\boldsymbol{\varepsilon} + h\,\mathbf{e}_j) - \sigma_i(\boldsymbol{\varepsilon})}{h} \tag{81.17}$$

with adaptive perturbation $h = 10^{-7} \cdot \max(|\varepsilon_j|, 10^{-6})$, followed by symmetrisation $\mathbf{C} = \frac{1}{2}(\mathbf{C}^{\text{raw}} + (\mathbf{C}^{\text{raw}})^T)$.

This approach has several advantages:

1. It is **exactly consistent** with the algorithmic stress update, capturing all three nonlinearities (fracturing, plasticity, cracking) and their mutual interaction.
2. It requires no analytical derivation of the chain rule through the compression coordinate and principal strain transformations.
3. The cost (7 stress evaluations per Gauss point) is acceptable because the Ko–Bathe model is computationally inexpensive (no linear system solve in the constitutive update).
4. The symmetrisation produces a tangent suitable for symmetric solvers.

The implementation adds a `use_consistent_tangent_` flag (default: `false` for backward compatibility) and a `set_consistent_tangent(bool)` setter to `KoBatheConcrete3D`. When enabled, the `tangent()` methods call the numerical procedure instead of the analytical K_c/G_c tangent.

81.16.3 Expected Impact on Case 5

With the consistent tangent enabled, the sub-model SNES should exhibit improved Newton convergence even after extensive cracking, because:

- The tangent correctly reflects the *current* stiffness state, including the plastic return-mapping softening.
- The perturbation-based tangent (Eq. 81.17) naturally accounts for the crack opening/closing transitions, avoiding the discontinuity that causes the analytical tangent to oscillate.
- The improved tangent makes the numerical perturbation for $\mathbf{D}_{\text{hom}}$ (Eq. 81.8) more likely to converge, reducing the probability of zero columns.

A rerun of Case 5 with the consistent tangent is planned as future work.

81.17 FE² Allocation Audit and Optimisations

An audit of the PETSc vector allocations in the FE² pipeline (`NonlinearSubModelEvolver`) was performed. The key findings and subsequent optimisations:

81.17.1 Audit Findings

- `FormResidual`: 2 `DMGetLocalVector` per SNES iteration (plus corresponding restores).
- `FormJacobian`: 1 `DMGetLocalVector` per SNES iteration.
- `compute_homogenized_tangent`: previously 2 `VecDuplicate` per call (for saving/restoring the solution and imposed values).
- **No memory leak** was found in `section_forces_from_reactions()` — `DMRestoreLocalVector` is correctly called.

81.17.2 Pre-Allocated Working Vectors (Implemented)

The `VecDuplicate` calls in `compute_homogenized_tangent()` and `subsequent_solve()` have been replaced by persistent class-member vectors `U_work_` and `imp_work_`, allocated once during `setup_snes()` and destroyed in `destroy_petsc_objects()`. This eliminates ~ 80 allocation/deallocation cycles per global step per sub-model (2 allocs $\times$ 6 perturbation directions $\times$ $\sim$7 recovery calls per step).

81.17.3 RCM Reordering (Implemented)

Reverse Cuthill–McKee reordering is now applied to the direct factoriser within each sub-model:

```
PCFactorSetMatOrderingType(pc, MATORDERINGRCM);
PCFactorSetReuseOrdering(pc, PETSC_TRUE);
```

The reordering reduces fill-in during LU factorisation, and the reuse flag ensures that the symbolic factorisation (which includes the reordered sparsity pattern) is computed only once per sub-model lifetime, with subsequent factorisation steps reusing the same ordering. This benefits the sub-model solver because the sparsity pattern is constant (same mesh, same BCs) across all time steps.

81.18 Implementation Notes

The validation driver is implemented in `main_table_cyclic_validation.cpp` with a CLI dispatch:

```
./fall_n_table_cyclic_validation --case 0     # elastic reference
./fall_n_table_cyclic_validation --case 1a    # beam N=2
./fall_n_table_cyclic_validation --case 1i    # beam N=10
./fall_n_table_cyclic_validation --case 2a    # Hex8 continuum
./fall_n_table_cyclic_validation --case 3     # full table
./fall_n_table_cyclic_validation --case 4     # FE² one-way
./fall_n_table_cyclic_validation --case 5     # FE² two-way
./fall_n_table_cyclic_validation --case all   # all cases
```

Each case produces a `hysteresis.csv` file (columns: `step`, `p`, `drift_m`, `base_shear_MN`) and VTK output in the subdirectory `data/output/cyclic_validation/case{id}/`. Cases 2, 3, 4, 5 also produce PVD time-series VTK output in a `vtk/` subdirectory.

A Python plotting script (`scripts/plot_cyclic_validation.py`) reads all `hysteresis.csv` files and generates comparative PDF figures.

Protocol extraction. The cyclic displacement function is factored into a shared header `src/utils/CyclicProtocol.hh`, making it available for both the validation driver and unit tests. It is an `inline` free function in `namespace fall_n`, included transitively via `header_files.hh`.

Beam dispatch. Sub-cases `1a`–`1i` are instantiated from a single template function `run_case1<N>()` using a C++20 template lambda and compile-time dispatch, avoiding code duplication across nine element orders:

```
auto run_beam = [&]<std::size_t N>() {
    auto records = run_case1<N>(out + "/case1" + ...);
    all_records["1" + suffix] = std::move(records);
};
if (should_run("1a")) run_beam.template operator()<2>();
if (should_run("1b")) run_beam.template operator()<3>();
// ... through 1i → N=10
```

Key solver parameters.

- Global SNES: `bt` line search, `preonly/lu` KSP/PC, `max_it` = 100.
- Incremental solve: $N_s = 120$ steps (beam/continuum/table), $N_s = 60$ (FE^2), max bisection depth = 6.
- Sub-model SNES: `max_it` = 100, `atol` = 2.0, `rtol` = 10^{-3}, incremental ramp 20 sub-steps, 4 bisection levels.
- Sub-model: RCM reordering + reuse, penalty $\alpha = 10\,E_c$, $2 \times 2 \times 1$ Hex27 mesh.
- Staggered coupling (Case 5): max 3 iterations, tolerance = 0.05, relaxation $\omega = 0.8$.

Chapter 82

Normative Multiscale Publication Audit and Redesign

82.1 Purpose and Normative Scope

This chapter is the normative reference for the public multiscale API in `fall_n`. It supersedes the terminology and behavioural claims of Chapters 73 and 81 whenever those chapters describe an earlier or partially implemented coupling loop.

The goal of the redesign is not merely to rename components, but to align the software architecture with three simultaneous requirements:

1. **physical coherence:** the public semantics must reflect the actual multiscale algorithm implemented in code;
2. **architectural extensibility:** the hot path must remain zero-overhead while extension points stay explicit and SOLID at the API boundary;
3. **publication readiness:** code, examples, tests, and documentation must tell the same story.

82.2 Official Nomenclature

The multiscale subsystem now exposes three officially distinct coupling modes:

`OneWayDownscaling` macro solve followed by micro solve, with no feedback to the macro model;

`LaggedFeedbackCoupling` macro solve followed by micro solve and delayed feedback injection for subsequent macro steps;

`IteratedTwoWayFE2` fixed-point macro–micro iteration with checkpoint/restore and a single accepted commit at the end of the step.

This separation is implemented in `src/analysis/CouplingStrategy.hh` and reported explicitly through `CouplingMode` in `src/analysis/MultiscaleTypes.hh`. The previous labels `OneWayCoupling` and `TwoWayStaggered` are retained only as historical names in older documentation chapters.

82.3 Audit of Prior Claims

The redesign began by treating the existing code and documentation as hypotheses rather than ground truth. Table 82.1 records the main findings that motivated the current implementation.

Claim or behaviour	Status	Normative conclusion
The pre-redesign staggered driver was a full FE^2 loop	incorrect	It was a lagged outer-loop driver: the macro step was solved outside the coupling iteration and was not restored/re-solved inside each fixed-point pass.
Tangents and forces were homogenised by the same operator	incorrect	The tangent came from boundary reactions while forces could be injected via a separate approximate path; the public API now packages both in a single `SectionHomogenizedResponse`.
Homogenised injection was local to the critical macro site	approximate	Beam elements supported blanket overrides on all section points; the public path is now *site-based* through `CouplingSite`.
The driver owned no multiscale protocol details	incorrect	Older examples had to orchestrate `end_of_step()`, feedback injection, and convergence externally. The orchestrator now owns the full lifecycle.
Regularisation was a physical constitutive choice	incorrect	The previous diagonal clamp was an implicit numerical stabiliser; it is now surfaced as an explicit regularisation policy with diagnostics.
All documentation under Chapters 74–82 described the current code	historical	Those chapters remain useful as design records, but this chapter is the authoritative statement of the current implementation.

Table 82.1: Defect ledger for the multiscale redesign.

82.4 Underlying Mathematics and Physical Contract

82.4.1 Macro generalised variables

At the beam level, the section deformation vector is

$$\mathbf{e} = \{\varepsilon_0, \kappa_y, \kappa_z, \gamma_y, \gamma_z, \theta'\}^T, \tag{82.1}$$

and the section resultant vector is

$$\mathbf{s} = \{N, M_y, M_z, V_y, V_z, T\}^T. \tag{82.2}$$

The local continuum sub-model is driven by Timoshenko-consistent end kinematics extracted from the macro beam. The current implementation uses the kinematic transfer already established in Chapters 63 and 70, but the public contract is no longer "beam element to entire sub-model" in the abstract; it is *macro coupling site to local model* through `CouplingSite`.

82.4.2 Normative homogenised response

The public response object is `SectionHomogenizedResponse`, containing:

$$\mathbf{s}_0, \qquad \mathbf{D}_{\text{hom}} = \frac{\partial \mathbf{s}}{\partial \mathbf{e}}, \qquad \mathbf{e}_0. \tag{82.3}$$

The macro-scale injection contract is

$$\mathbf{s}(\mathbf{e}) = \mathbf{s}_0 + \mathbf{D}_{\text{hom}}(\mathbf{e} - \mathbf{e}_0), \tag{82.4}$$

with $\mathbf{e}_0$ stored as `strain_ref`. This eliminates the ambiguity of "tangent by one operator, forces by another" in the public API. The same response object also records the requested tangent mode (`TangentComputationMode`), the outcome of the condensed operator attempt (`CondensedTangentStatus`), and the residual of the sparse free solve whenever linearized condensation is attempted.

82.4.3 Boundary-reaction homogenisation

The default production path in `NonlinearSubModelEvolver` now computes section forces from assembled boundary reactions at the loaded end. In compact form,

$$\mathbf{s}_{\text{hom}} = \mathcal{H}_{\text{br}}(\mathbf{u}_\mu), \tag{82.5}$$

where $\mathcal{H}_{\text{br}}$ denotes the boundary-reaction operator and $\mathbf{u}_\mu$ is the converged micro displacement field. The publication-path tangent is obtained primarily from the linearised micro equilibrium equations. With the free/constrained partition $\{f, c\}$ and constrained increments $\delta\mathbf{u}_c = \mathbf{T}\,\delta\mathbf{q}$, the condensed section operator is

$$\mathbf{D}_{\text{hom}} = \mathbf{T}^{\mathsf{T}} \left(\mathbf{K}_{cc} - \mathbf{K}_{cf}\mathbf{K}_{ff}^{-1}\mathbf{K}_{fc}\right)\mathbf{T}. \tag{82.6}$$

The implementation evaluates this operator through a sparse solve of the six right-hand sides in $\mathbf{K}_{fc}\mathbf{T}$, not by materialising a full dense Schur complement.

Adaptive finite differences remain available as an explicit validation and fallback path:

$$\mathbf{D}_{\text{hom}}^{(:,j)} \approx \frac{\mathcal{H}_{\text{br}}(\mathbf{u}_\mu^{(j,+)}) - \mathcal{H}_{\text{br}}(\mathbf{u}_\mu^{(j,-)})}{2h_j}, \tag{82.7}$$

with one-sided fallback only when one perturbation fails. The public API can force this route through `TangentComputationMode::ForceAdaptiveFiniteDifference` for validation.

Volume averaging is retained only as a comparison/validation route and is reported through `HomogenizationOperator::VolumeAverage`; it is not the default FE^2 production operator.

82.4.4 Convergence criterion

The default coupling convergence is no longer defined solely through a tangent matrix norm. The implemented criterion monitors:

$$r_f^{(i)} = \frac{\|\mathbf{s}_{\text{macro}}^{(i)} - \mathbf{s}_{\text{micro}}^{(i)}\|}{\max\left(1, \|\mathbf{s}_{\text{macro}}^{(i)}\|, \|\mathbf{s}_{\text{micro}}^{(i)}\|\right)}, \tag{82.8}$$

for each coupled site i, together with an analogous relative tangent residual. The default policy in `src/analysis/CouplingStrategy.hh` is `ForceAndTangentConvergence`.

82.5 Implemented Architecture

82.5.1 Public data contracts

The redesign introduces explicit public types:

- `CouplingSite`: identifies the exact macro site (`macro_element_id`, section Gauss point, ξ, local frame);
- `MacroSectionState`: local macro strain/resultant snapshot;
- `SectionHomogenizedResponse`: homogenised forces, tangent, reference strain, operator provenance, regularisation diagnostics, linearisation provenance, condensed-attempt diagnostics, tangent-column validity, and perturbation sizes when the finite-difference fallback is actually used;
- `CouplingIterationReport`: mode, termination reason, iteration count, residuals, hard-failure sites, rollback state, regularisation presence, and macro/micro timing;

- `ModelCheckpoint` and solver-specific `checkpoint_type`: exact rollback state for FE^2 iteration.

The typed path through `MultiscaleModel<MacroBridgeT, LocalModelT>` is the normative public surface. The type-erased `LocalModelHandle` remains available only as an experimental utility until erased checkpoint/restore semantics are completed. Likewise, `src/reconstruction/Homogenisati` is retained as an internal validation utility rather than a recommended public extension point.

82.5.2 SOLID without sacrificing the hot path

The multiscale orchestration now follows the design principle "static in the kernel, explicit at the boundary":

- **Single Responsibility Principle.** `BeamMacroBridge` is responsible for macro extraction/injection; `MultiscaleModel` aggregates coupling sites and local models; `MultiscaleAnalysis` owns the protocol; the local solver owns local constitutive evolution. Internally, the nonlinear sub-model path now isolates boundary-condition application, persistent state lifecycle, and boundary-reaction homogenisation into dedicated header-only components.
- **Open/Closed Principle.** Coupling algorithms, convergence criteria, relaxation policies, and executors are all pluggable through small interfaces.
- **Liskov Substitution Principle.** Macro solvers participate through the `CheckpointableSteppableSolv` concept rather than through ad hoc assumptions about `DynamicAnalysis` or `NonlinearAnalysis`.
- **Interface Segregation Principle.** The local-model concept requires only what the multiscale loop actually needs: kinematics update, solve, homogenised response, commit/revert, and checkpoint control.
- **Dependency Inversion Principle.** `MultiscaleAnalysis` depends on abstract coupling policies and on concepts, not on concrete drivers.

These abstractions are intentionally placed at the orchestration layer. The inner loop remains template-based and avoids virtual dispatch in the hot path. This preserves the original performance philosophy of `fall_n` while making the multiscale subsystem externally reusable.

At the local-solver level, the same principle is now applied internally:

- `LocalBoundaryConditionApplicator` owns beam-to-continuum kinematic updates and writes the imposed boundary vector;
- `PersistentLocalStateOps` owns synchronisation, commit, and revert of the persistent continuum state;
- `BoundaryReactionHomogenizer` owns the section-force extraction, tangent diagnostics, linearized static condensation, finite-difference fallback, and response classification.

These components are value-type, header-only helpers with pointer-based composition; they add no virtual dispatch to the micro hot path while creating an explicit seam for future replacement of the current sparse condensation / validation-fallback pair by even more advanced local linearisation strategies.

This cycle also extended `FEM_Element` to mirror the explicit local linearisation API already present in `StructuralElement` (`extract_element_dofs`, `compute_internal_force_vector`, `compute_tangent_stiffness_matrix`, and `get_dof_indices`). That architectural change matters because the publication-ready local operator now depends on mixed-model assembly through type erasure without losing access to the element-level tangent information.

82.5.3 Local multiscale class diagram

Figure 82.1 summarises the current publication-path architecture for the local multiscale operator.



Figure 82.1: Current local multiscale architecture on the publication path.

82.5.4 Condensed operator implementation

The current primary local operator is no longer assembled as a dense micro-tangent followed by dense Schur complements. Instead, the implementation builds a sparse local tangent from the mixed element set, adds the embedded penalty coupling contributions, and solves only the six right-hand sides needed to evaluate

$$\mathbf{D}_{\text{hom}} = \mathbf{T}^{\mathsf{T}} \left(\mathbf{K}_{cc} - \mathbf{K}_{cf} \mathbf{K}_{ff}^{-1} \mathbf{K}_{fc} \right) \mathbf{T}. \tag{82.9}$$

Operationally, this is implemented as a sparse solve for $\mathbf{X} = \mathbf{K}_{ff}^{-1} \mathbf{K}_{fc} \mathbf{T}$, followed by the boundary contraction $\mathbf{T}^{\mathsf{T}}(\mathbf{K}_{cc}\mathbf{T} - \mathbf{K}_{cf}\mathbf{X})$. This keeps the physics of static condensation while reducing memory pressure and making the scalability story substantially more honest than the previous dense prototype.

82.5.5 Validation and fallback diagnostics

The current public contract does not hide whether the condensed operator was actually available. Instead, the response records:

- the requested tangent mode;
- the realised tangent scheme;
- the condensed operator status;
- the sparse solve residual when the condensed path is attempted.

The intended semantics are:

`PreferLinearizedCondensation` production mode; use the sparse condensed operator first and fall back only if it cannot be formed;

`ForceAdaptiveFiniteDifference` validation mode; skip condensation intentionally and compute the tangent through adaptive perturbations;

`CondensedTangentStatus` explicit reason code for the condensed attempt, including `Success`, `AssemblyFailed`, `FactorizationFailed`, `ResidualTooLarge`, and `ForcedAdaptiveFiniteDifference`.

This additional provenance is important for publication because it makes the scientific debt visible in the API instead of burying it inside solver logs.

82.5.6 Macro and local rollback

The FE^2 loop is only meaningful if the macro and micro states can both be restored exactly. The current implementation provides:

- model-level snapshots through `ModelCheckpoint`;
- solver-level snapshots in `DynamicAnalysis` and `NonlinearAnalysis`;
- local-model snapshots in `NonlinearSubModelEvolver`;
- explicit trial/commit control via `set_auto_commit(false)` during iteration and a single `commit_trial_state()` after acceptance.

82.6 Implemented Iterated Two-Way FE^2 Algorithm

Algorithm 3 summarises the implemented orchestrator semantics.

Input: macro solver S_M, multiscale model $\mathcal{M}$, predictor response $\mathbf{R}^{(0)}$
Output: accepted macro step and committed local states

```
capture macro checkpoint C_M
capture one checkpoint C_μ^(i) for each local model
disable automatic macro and local commit
for k = 0, 1, ..., k_max − 1 do
    restore C_M and all C_μ^(i)
    inject predictor response at each CouplingSite
    advance one macro step
    extract local beam kinematics for each site
    solve local models in parallel
    build SectionHomogenizedResponse for each site
    compute force and tangent residuals
    apply relaxation policy if configured
    if k ≥ 1 and all convergence criteria are satisfied then
        accept current iteration
        break
    end
    set predictor ← current response
end
inject accepted response at each site
commit macro trial state
commit local trial states and call end_of_step() once
```

Algorithm 3: Implemented `IteratedTwoWayFE2` protocol

Two implementation decisions are deliberate:

1. the first iteration is always treated as a predictor pass and is never accepted immediately;
2. `end_of_step()` is owned by the orchestrator, not by the driver.

82.7 HPC and Build Surface

The first publication-ready HPC layer focuses on robust shared-memory parallelism:

- `SerialExecutor` provides the reference path;
- `OpenMPExecutor` parallelises local-model solves over coupling sites;
- `CouplingCommunicators` makes the future MPI ownership explicit without pretending that a distributed FE^2 engine is already complete.

The build system now exposes a dedicated public CMake target:

`fall_n::multiscale_api`

and a slim public umbrella header:

`src/analysis/MultiscaleAPI.hh`

which gathers the multiscale-specific headers without routing users through the project-wide `header_files.hh` umbrella.

82.8 Verification and Test Matrix

The current redesign is supported by the following regression and contract tests:

- `tests/test_multiscale_analysis_api.cpp`: semantic separation of coupling modes, ownership of local lifecycle, analysis-local coupling start, accepted FE^2 commit, explicit rollback semantics, hard-failure classification, and parity between serial and OpenMP execution on the API harness;
- `tests/test_micro_solve_executor.cpp`: serial/OpenMP executor contract and communicator defaults;
- `tests/test_element_heterogeneity.cpp`: heterogeneous element-container contract, including the explicit local linearisation API now forwarded by `FEM_Element`;
- `tests/test_beam.cpp`: section-level beam behaviour, including the element path touched by local homogenised injection;
- `tests/test_steppable_solver.cpp` and `tests/test_steppable_dynamic.cpp`: solver contracts relied upon by the orchestrator;
- `tests/test_evolver_advanced.cpp`: persistent local-model evolution, condensed local tangent extraction with finite-difference fallback diagnostics, pure axial/flexural/shear/-torsional regression cases, linearised consistency, reaction-versus-volume operator comparison, and axial power consistency.

In addition, the heavy executable targets `fall_n_lshaped_multiscale`, `fall_n_lshaped_multiscale_16`, `fall_n_table_multiscale`, and `fall_n_table_cyclic_validation` serve as integration-level build checks of the public multiscale surface.

82.9 Known Limitations

The redesign closes the most serious semantic gaps, but several publication limitations remain explicit:

- the default section tangent is now obtained by linearized static condensation of the assembled local tangent operator $\mathbf{D}_{\text{hom}} = \mathbf{T}^{\mathsf{T}}\mathbf{K}_{\text{eff}}\mathbf{T}$, but the implementation is still a dense local condensation and falls back to adaptive finite differences when mixed-element local linearisation is unavailable or the free block becomes numerically singular;
- the accepted FE^2 step is a fixed-point iteration, not a monolithic multilevel Newton solve;
- MPI-distributed local-model execution is not yet implemented beyond the communicator contract;
- `NonlinearSubModelEvolver` still contains several responsibilities internally, but the boundary-condition, state-lifecycle, and homogenisation concerns have already been split from the main class body;
- the GitHub Actions workflow added for multiscale stability has been authored and documented, but only the local PowerShell gate has been executed in this audit cycle;
- historical chapters still contain earlier design narratives and should be read as provenance, not as the normative behavioural specification.

82.10 Future Work

The next publication-strength milestones are:

1. generalise the current condensed local tangent into a fully systematic algorithmic linearisation path that covers every local hook and minimises the need for the finite-difference fallback while retaining the same public response contract;
2. finish the internal split of `NonlinearSubModelEvolver` from the current state into a solver core, diagnostics service, and output service, reusing the already extracted boundary-condition, state, and homogenisation helpers;
3. add energy-consistency benchmarks and distributed MPI execution of local models;
4. package installable public headers for the multiscale target instead of exposing the source-tree include path;
5. extend the coupling-site abstraction beyond beam sections to shell or continuum macro sites.

82.11 Conclusion

The multiscale subsystem of `fall_n` is now documented and exposed as a library feature rather than as a driver convention. The redesign does not claim that every research-grade FE^2 feature is complete; it does claim, and the current code supports, that:

1. the coupling modes are semantically distinct and named honestly;
2. iterated two-way FE^2 performs real macro/micro checkpointed iteration;
3. forces, tangents, and reference strain are injected through one public response object;

4. the lifecycle no longer leaks into the examples;
5. the documentation now states these facts explicitly.

Chapter 83

Execution Record for Multiscale Stabilization v1

83.1 Intent and Verification Protocol

This chapter records the actual execution of the multiscale stabilization plan after the publication-oriented redesign documented in Chapter 82. The guiding rule for this stabilization cycle was strict: neither the previous code, nor the existing tests, nor the earlier documentation were accepted as ground truth without a fresh audit against the implemented path.

The execution protocol used in this cycle was:

1. audit the current normative path directly in code;
2. reproduce uncertainty or weakness with a dedicated test or diagnostic;
3. implement the correction or hardening;
4. rerun a focused regression gate;
5. document both the improvement and the residual debt in the same LaTeX document.

The main files audited and modified during this cycle were:

- `src/analysis/MultiscaleTypes.hh`;
- `src/analysis/MultiscaleAnalysis.hh`;
- `src/reconstruction/NonlinearSubModelEvolver.hh`;
- `src/reconstruction/LocalModelAdapter.hh`;
- `src/reconstruction/HomogenisationStrategy.hh`;
- `tests/test_multiscale_analysis_api.cpp`;
- `tests/test_evolver_advanced.cpp`;
- `scripts/ci_multiscale_stabilization.ps1`;
- `.github/workflows/multiscale-stability.yml`.

83.2 Phase 0: Truth Baseline

Table 83.1 summarises the baseline classification used before any code change was accepted.

Audited item	Status	Decision in this stabilization cycle
Typed multiscale orchestration path	verified	Kept as the normative public path.
Type-erased `LocalModelHandle` path	experimental	Left in code, but explicitly removed from the normative public narrative until exact erased checkpoint/restore semantics are implemented.
`HomogenisationStrategy` route	legacy/internal	Retained only as a comparison utility; no longer described as the production FE^2 extension mechanism.
Local tangent extraction in `NonlinearSubModelEvolver`	fragile	Replaced by sparse linearized condensation with explicit validation-mode fallback and explicit diagnostics.
Macro rollback on trial-step failure inside FE^2	incorrect	Explicit checkpoint restoration added to the failure path.
Physical regression matrix for pure load modes	missing	Added as dedicated solver-level regression tests.
Visible CI gate for the multiscale release surface	missing	Added as a documented local script and a repository workflow.

Table 83.1: Truth baseline for the stabilization cycle.

83.3 Phase 1: Numerical Hardening of the Local Response

83.3.1 Initial hypothesis

The main numerical fragility of the public multiscale path was the local tangent extraction: a one-sided perturbation with a fixed user-provided h_{pert}, silent zero columns on failed perturbations, and hidden post-processing by symmetry projection and diagonal clamping.

83.3.2 Observed evidence before the change

The audit of `NonlinearSubModelEvolver.hh` showed that the previous implementation:

- used only the + perturbation;
- used the same perturbation size for every generalized component;
- left the tangent column at zero if the perturbation solve diverged;
- restored displacement vectors but did not explicitly resynchronise the model state vector in the tangent loop;
- reported only the final tangent, thereby hiding which columns were valid and whether regularisation had actually modified the matrix.

83.3.3 Implemented change

The production operator remains the boundary-reaction operator, but the stabilization no longer treats finite differences as the primary tangent path. The current normative implementation first assembles the sparse local tangent operator at the converged micro state, including the embedded-rebar penalty terms, partitions it into free and constrained blocks, and condenses it against the boundary kinematics. With constrained increments $\delta\mathbf{u}_c = \mathbf{T}\,\delta\mathbf{q}$, the returned section tangent is

$$\mathbf{D}_{\text{hom}} = \mathbf{T}^{\mathsf{T}}\mathbf{K}_{\text{eff}}\mathbf{T}, \qquad \mathbf{K}_{\text{eff}} = \mathbf{K}_{cc} - \mathbf{K}_{cf}\mathbf{K}_{ff}^{-1}\mathbf{K}_{fc}. \tag{83.1}$$

This is the first version of the multiscale operator in the repository that is explicitly built from the linearised micro equilibrium equations rather than from perturb-and-observe solves. In the follow-up hardening pass, the implementation was further upgraded from a dense prototype to a sparse solve of the six required right-hand sides, which removed the need to materialise the full dense Schur complement.

Adaptive finite differences are retained only as a documented fallback. When the condensed operator cannot be formed—for example because a mixed element does not expose explicit local tangent data or because the free block is numerically singular—the implementation falls back to the adaptive scheme. For each generalized component e_j, the fallback uses

$$h_j = \frac{\max\big(h_{\mathrm{pert}}L,\ 10^{-3}\max(|q_j|, h_{\mathrm{pert}}L)\big)}{L}, \tag{83.2}$$

where L is the macro beam characteristic length and q_j is the corresponding relative end degree of freedom. The preferred tangent estimate is

$$\mathbf{D}_{\mathrm{hom}}^{(:,j)} \approx \frac{\mathbf{s}(\mathbf{e} + h_j\mathbf{e}_j) - \mathbf{s}(\mathbf{e} - h_j\mathbf{e}_j)}{2h_j}, \tag{83.3}$$

and the implementation falls back to one-sided differentiation only when one of the two perturbation solves fails.

The public response object now records:

- the tangent computation mode requested;
- the tangent scheme used;
- the status of the condensed operator attempt;
- the sparse condensed solve residual when that path is attempted;
- the perturbation size used for each column;
- whether each column is valid;
- whether each column used the central stencil;
- the number of failed perturbation solves;
- whether regularisation actually modified the returned tangent.

83.3.4 Resulting semantics

The stabilization deliberately stopped calling every non-perfect response "successful". The public status contract is now:

`Ok` the condensed operator was assembled successfully, all tangent columns are valid, and no actual regularisation was applied;

`Degraded` a usable response exists, but at least one fallback to finite differences or actual tangent regularisation occurred;

`SolveFailed` the response is not usable as a section operator;

`NotReady/InvalidOperator` explicit non-solution states.

83.3.5 Internal architectural hardening

The numerical hardening was paired with an internal architectural split of the local solver path. Instead of leaving boundary conditions, persistent state management, and boundary-reaction homogenisation interleaved inside `NonlinearSubModelEvolver`, the cycle extracted three dedicated components:

- `PersistentLocalStateOps`: synchronisation, commit, and revert of the persistent continuum state;
- `LocalBoundaryConditionApplicator`: update of section-end kinematics and writing of the imposed boundary vector;
- `BoundaryReactionHomogenizer`: section forces from reactions, condensed tangent extraction, finite-difference fallback, diagnostics, and response classification.

This split was intentionally implemented as lightweight header-only helpers composed through pointers and templates, so the hot path still avoids virtual dispatch and heap churn. Architecturally, this matters because it creates a single explicit seam where the current sparse condensation / validation fallback pair can later be upgraded again without changing the public `SectionHomogenizedResponse` contract or the typed local model API.

The same cycle also extended `FEM_Element` with the explicit local linearisation API already present in `StructuralElement`. This closes an architectural gap in the mixed-element path: the condensed local operator now sees the element DOF map and the element tangent even when the micro model is stored behind `MultiElementPolicy` type erasure.

The same cycle also hardened the semantics of operator validity. A local response is now classified as `InvalidOperator` if any tangent column is missing entirely. One-sided fallback with a complete operator remains `Degraded`; only a fully central, fully valid, non-regularised operator is reported as `Ok`. This change is small in code volume, but scientifically important because it prevents an incomplete section operator from being treated as merely "low quality" and then entering the FE^2 loop as if it were usable.

83.4 Phase 2: Protocol Hardening for Macro–Micro Iteration

83.4.1 Initial hypothesis

The checkpointed FE^2 loop added in the redesign was close to publication-ready, but the failure semantics were still too optimistic and too opaque for a release gate.

83.4.2 Errors confirmed during audit

Two issues were confirmed in the code:

1. on a macro trial-step failure inside `IteratedTwoWayFE2`, the macro checkpoint was not restored explicitly before returning;
2. `CouplingIterationReport` did not expose the termination reason, rollback execution, regularisation presence, or failed coupling sites.

83.4.3 Implemented change

The orchestrator now records:

- `CouplingTerminationReason`;
- whether rollback was performed;

- whether relaxation changed the current iterate;
- whether regularisation was detected among accepted local responses;
- the set of hard-failure sites;
- a count of regularised submodels.

Most importantly, the macro checkpoint is now restored explicitly on macro-step failure before the FE^2 step returns. This closes a real semantic gap that could otherwise leave a dirty trial state in memory after a reported failure.

83.5 Phase 3: Physical Regression Matrix

83.5.1 Added regression coverage

The stabilization cycle introduced a small deterministic matrix of physical reference cases using the real `NonlinearSubModelEvolver` path:

- pure axial loading;
- pure bending about y;
- pure bending about z;
- pure shear along y;
- pure shear along z;
- pure torsion.

The tests check:

- convergence of the local sub-model;
- availability of the homogenised response;
- positivity of the expected tangent diagonal;
- completion of the tangent diagnostics;
- use of `LinearizedCondensation` and the `forces_consistent_with_tangent` flag in the elastic cases;
- dominance or mode-consistent prominence of the expected resultant;
- linearised consistency in the elastic axial case;
- boundary-reaction versus volume-average agreement in the elastic axial case;
- axial macro–micro power consistency.

83.5.2 Observed numerical results

The focused axial consistency test produced the following values on the local execution used for this chapter:

$$\text{linearization_error} = 7.85096 \times 10^{-5}, \tag{83.4}$$

$$\text{operator_gap} = 2.84408 \times 10^{-5}, \tag{83.5}$$

$$\text{power_gap} = 2.84408 \times 10^{-9}. \tag{83.6}$$

These are sufficiently small for the intended stabilization gate and, more importantly, provide a reproducible numerical baseline for future refactors.

After the scientific-hardening follow-up, the local gate also compares the production condensed tangent with a deliberately forced adaptive finite-difference tangent on the same elastic mixed-mode state. The measured comparison on the audited execution was

$$\text{tangent_gap} = 4.60221 \times 10^{-2}, \tag{83.7}$$

$$\text{force_gap} = 0. \tag{83.8}$$

This result is intentionally not presented as exact equality. Its role in the stabilization gate is to show that the production condensed operator and the validation fallback remain close on a coupled elastic state while still making their non-zero discrepancy explicit.

83.5.3 Executed regression targets

The following focused executables were rebuilt and executed locally after the stabilization changes:

- `fall_n_multiscale_api_test.exe`: 39 passed, 0 failed;
- `fall_n_micro_solve_executor_test.exe`: 6 passed, 0 failed;
- `fall_n_evolver_advanced_test.exe`: 90 passed, 0 failed;
- `fall_n_heterogeneity_test.exe`: 26 passed, 0 failed;
- `fall_n_beam_test.exe`: 21 passed, 0 failed;
- `fall_n_steppable_solver_test.exe`: 48 passed, 0 failed;
- `fall_n_steppable_dynamic_test.exe`: 32 passed, 0 failed.

83.6 Phase 4: Release Hardening and CI Surface

83.6.1 Local reproducible gate

The repository now contains `scripts/ci_multiscale_stabilization.ps1`, which configures the build directory if needed, builds the multiscale release gate, executes the key regression tests, and compiles the PDF. In the current stabilized form, the script builds each target individually rather than issuing a single monolithic `ninja` invocation; that change was introduced specifically to expose which heavy target is consuming or blocking the local gate. The script covers:

- `fall_n_multiscale_api_test`;
- `fall_n_micro_solve_executor_test`;
- `fall_n_evolver_advanced_test`;

- `fall_n_beam_test`;
- `fall_n_steppable_solver_test`;
- `fall_n_steppable_dynamic_test`;
- `fall_n_lshaped_multiscale`;
- `fall_n_lshaped_multiscale_16`;
- `fall_n_table_multiscale`;
- `fall_n_table_cyclic_validation`;
- `latexmk -pdf`.

During this execution cycle, the script itself exposed two practical issues:

1. the initial `param()` placement was invalid for PowerShell and had to be corrected;
2. the document step required a defensive fallback to `pdflatex` on Windows when `latexmk` propagated a stale toolchain/runtime failure.

After those corrections, the equivalent gate commands were executed explicitly in the audit environment to verify the release surface.

For this follow-up execution cycle, the focused regression executables and the LaTeX document were revalidated again after the condensed tangent implementation. A fresh rebuild of the heavy example targets was also attempted, including separate launches for the main multiscale examples, and the target-by-target gate ultimately completed successfully. In the audited environment the full local stabilization script rebuilt `fall_n_lshaped_multiscale`, `fall_n_lshaped_multiscale_16`, `fall_n_table_multiscale`, and `fall_n_table_cyclic_validation`, reran the regression executables, and regenerated `main.pdf`. The wall-clock cost is still high, but the important point for release readiness is that the gate now finishes end-to-end instead of being left as an unverified partial build.

83.6.2 Repository workflow

The repository now also contains the workflow `.github/workflows/multiscale-stability.yml`. Its purpose is not to claim that hosted CI is already production-proven, but to freeze the intended release gate in repository form:

1. configure an MSYS2 UCRT64 environment on Windows;
2. install the numerical dependencies used by the project;
3. configure CMake with Ninja;
4. build the regression executables one by one;
5. build the heavy multiscale examples one by one;
6. run the focused regression executables;
7. compile the LaTeX document.

83.7 Post-Stabilization Merge Audit with `origin/master`

Once the stabilization gate was green locally, the branch was not merged blindly with `origin/master`. Instead, the integration was treated as another audit phase: every conflicting file was reviewed under the same rule used throughout this stabilization cycle, namely that older or semantically weaker code is not accepted just because it came from the remote default branch.

83.7.1 Audit hypothesis

The initial hypothesis was that the merge could reintroduce one of three classes of defects:

1. semantic regression, where the remote side reintroduced placeholder or legacy code that weakens the now-documented public API;
2. architectural regression, where a low-level header would be coupled again to non-normative concerns;
3. numerical regression, where a geometry or constitutive alias would silently change the behaviour of multiscale builds.

83.7.2 Conflict classification

Table 83.2 records the files that required explicit judgment during the merge.

83.7.3 Compatibility retained intentionally

Not every remote change was rejected. The merge kept small, safe compatibility improvements that do not weaken the stabilized architecture:

- `VoigtVector` now exposes a compatibility `set_vector(...)` alias that forwards to `set_components(...)` this preserves old call sites without making the legacy name normative again;
- the non-conflicting edits in `ReadGmsh.hh` and `DoF.hh` were audited and accepted because they do not alter the multiscale semantics or the release gate.

83.7.4 Merge-preserved dependency surface

The purpose of the merge was not to maximize line retention; it was to preserve the dependency surface that the stabilization cycle had already validated. The resulting local architecture around the merged headers is summarised in Figure 83.1.



Figure 83.1: Merged header surface intentionally preserved after the stabilization audit.

File	Resolution	Rationale
`src/analysis/Analysis.hh`	kept stabilized branch version	the remote side only carried a placeholder "analysis concept" comment, whereas the stabilized branch already exposed the complete analysis aggregator surface (`DynamicAnalysis`, `AnalysisDirector`, `TransitionDirector`, observers).
`src/elements/element_geometry/LagrangeElement.hh`	kept stabilized branch version	the remote side appended stale duplicated geometry/member code after the class definition. Accepting it would have reintroduced ambiguity and maintainability debt.
`src/geometry/Cell.hh`	kept stabilized branch version	the remote side tried to embed VTK-specific cell metadata directly in the core geometry descriptor. That coupling was rejected because VTK translation is already owned by the post-processing layer.
`src/materials/MaterialPolicy.hh`	kept stabilized branch version	the remote side only preserved historical comments and omitted the explicit constitutive-space aliases now required by the stabilized public API.
`src/materials/Strain.hh`	kept stabilized branch version	the stabilized branch already uses `set_components()`, which is the current normative vocabulary.
`src/materials/VoigtVector.hh`	merged with compatibility shim	the stabilized branch kept the stronger `components()` / `set_components()` semantics, but the legacy `set_vector()` entry point was reintroduced as a thin alias for backward compatibility.
`src/mesh/gmsh/GmshDomainBuilder.hh`	kept stabilized branch version	the remote side attempted to map HEX8 elements through a lower-order geometry and under-integrated rule, which would have been a genuine numerical regression.
`src/model/Model.hh`	kept stabilized branch version	the extra remote `friend class Analysis;` declaration was not required by the current architecture and would only preserve dead coupling.

Table 83.2: Conflict-by-conflict resolution during the merge with `origin/master`.

83.7.5 Decision

The merge decision was therefore conditional rather than automatic: the branch was considered mergeable with `origin/master` only after the stabilized surface survived conflict resolution *and* the regression gate was revalidated. In other words, the merge itself became part of the release readiness proof.

83.8 Phase 5: Residual Debt Ledger

The stabilization cycle deliberately left some debt explicit rather than masking it under a "green" release summary. Table 83.3 records the items that remain open after this execution.

Residual item	Severity	Current disposition
Sparse condensed tangent still depends on explicit element-level local linearisation support and keeps a finite-difference fallback	high	Documented explicitly; the primary path is now the condensed operator, but the fallback remains necessary for unsupported local elements or singular free blocks.
Validation against forced adaptive finite differences shows a non-zero but bounded tangent gap on mixed elastic states	medium/high	Documented explicitly through the new scientific regression; the current state is honest and useful, but it is not yet a proof of exact algebraic identity between the condensed operator and the perturbation fallback.
`NonlinearSubModelEvolver` still owns several responsibilities	medium	Improved in this cycle by extracting boundary-condition, state, and homogenisation helpers; solver-core, diagnostics, and output concerns still need separation.
MPI-distributed micro execution	medium	Communicator ownership is explicit, but the distributed execution engine is not yet implemented.
Type-erased local-model path	medium	Left available only as experimental code until erased checkpoint/restore is completed.
Legacy documentation warnings unrelated to this stabilization	low/medium	Inventoried below; not silently fixed in this cycle because they pre-existed and are broader than the multiscale module.

Table 83.3: Residual debt after the stabilization execution.

83.9 Documentation Warning Ledger

The PDF compilation succeeded during this cycle, but the log still reports pre-existing warnings outside the immediate stabilization work:

- undefined references;
- multiply-defined labels;
- several hyperref string warnings associated with older chapters.

These warnings were intentionally not hidden or silently normalised. The stabilization decision was to keep the document compiling, add the current chapter as an execution record, and leave the broader document cleanup as a separate documentation-quality task.

83.10 Closure of the Stabilization Cycle

The multiscale stabilization cycle v1 closed the most important gap between "public API redesign" and "release-worthy behaviour":

1. the local tangent path now exposes its own uncertainty instead of silently zeroing columns;
2. incomplete local section operators are now classified explicitly as invalid rather than being treated as weak-but-usable responses;
3. the FE^2 protocol reports why it terminated and whether it rolled back;
4. the physical path now has deterministic axial, flexural, shear, and torsional regression coverage;

5. the release gate exists both as a local script and as a repository workflow;
6. the debt that remains is explicit, bounded, and technically understandable.

Bibliography

[1] F. Feyel. Multiscale FE2 elastoviscoplastic analysis of composite structures. *Computational Materials Science*, 16(1–4):344–354, 1999.

[2] F. Feyel. A multilevel finite element method (FE2) to describe the response of highly non-linear structures using generalized continua. *Computer Methods in Applied Mechanics and Engineering*, 192(28–30):3233–3244, 2003.

[3] F. Feyel and J.-L. Chaboche. FE2 multiscale approach for modelling the elastoviscoplastic behaviour of long fibre SiC/Ti composite materials. *Computer Methods in Applied Mechanics and Engineering*, 183(3–4):309–330, 2000.

[4] E. Gamma, R. Helm, R. Johnson, and J. Vlissides. *Design Patterns: Elements of Reusable Object-Oriented Software*. Addison-Wesley, 1994.

[5] M. G. D. Geers, V. G. Kouznetsova, and W. A. M. Brekelmans. Multi-scale computational homogenization: Trends and challenges. *Journal of Computational and Applied Mathematics*, 234(7):2175–2182, 2010.

[6] S. Ghosh, K. Lee, and S. Moorthy. Multiple scale analysis of heterogeneous elastic structures using homogenization theory and Voronoi cell finite element method. *International Journal of Solids and Structures*, 32(1):27–62, 1995.

[7] V. G. Kouznetsova, M. G. D. Geers, and W. A. M. Brekelmans. Multi-scale second-order computational homogenization of multi-phase materials: a nested finite element solution strategy. *Computer Methods in Applied Mechanics and Engineering*, 193(48–51):5525–5550, 2004.

[8] C. Miehe, J. Schröder, and J. Schotte. Computational homogenization analysis in finite plasticity. Simulation of texture development in polycrystalline materials. *Computer Methods in Applied Mechanics and Engineering*, 171(3–4):387–418, 1999.

[9] J. Schröder. A numerical two-scale homogenization scheme: the FE2-method. In *Plasticity and Beyond*, volume 550 of *CISM International Centre for Mechanical Sciences*, pages 1–64. Springer, 2014.