Scan Report

October 5, 2026

Summary

This document reports on the results of an automatic security scan. All dates are displayed using the timezone "Coordinated Universal Time", which is abbreviated "UTC". The task was "Scan Découverte Réseau (suite)". The scan started at Mon Oct 5 16:52:52 2026 UTC and ended at Mon Oct 5 19:01:38 2026 UTC. The report first summarises the results found. Then, for each host, the report describes every issue found. Please consider the advice given in each description, in order to rectify the issue.

Contents

1 Result Overview **2**

2 Results per Host **2**

2.1 10.9.1.10 . . . 2
2.1.1 Low general/tcp . . . 2
2.1.2 Low general/icmp . . . 3
2.2 172.16.10.2 . . . 4
2.2.1 Low general/icmp . . . 4
2.3 172.16.30.1 . . . 5
2.3.1 Medium 23/tcp . . . 5
2.3.2 Low general/icmp . . . 5
2.4 172.16.30.2 . . . 6
2.4.1 Medium 23/tcp . . . 6
2.4.2 Low general/icmp . . . 7
2.5 172.16.31.2 . . . 8
2.5.1 Medium 23/tcp . . . 8
2.5.2 Low general/icmp . . . 8
2.6 172.16.31.10 . . . 9
2.6.1 Critical general/tcp . . . 9
2.6.2 High 445/tcp . . . 10
2.6.3 Medium 135/tcp . . . 11
2.6.4 Medium 3389/tcp . . . 12
2.6.5 Low general/tcp . . . 18
2.6.6 Low general/icmp . . . 19
2.7 172.16.254.1 . . . 20
2.7.1 Medium 23/tcp . . . 20
2.7.2 Low general/icmp . . . 20
2.8 172.16.255.1 . . . 21
2.8.1 Medium 23/tcp . . . 21
2.8.2 Low general/icmp . . . 22

1 Result Overview

Host	Critical	High	Medium	Low	Log	False P.
10.9.1.10 10.9.1.10	0	0	0	2	0	0
172.16.10.2 172.16.10.2	0	0	0	1	0	0
172.16.30.1 172.16.30.1	0	0	1	1	0	0
172.16.30.2 172.16.30.2	0	0	1	1	0	0
172.16.31.2 172.16.31.2	0	0	1	1	0	0
172.16.31.10 172.16.31.10	1	1	4	2	0	0
172.16.254.1 172.16.254.1	0	0	1	1	0	0
172.16.255.1 172.16.255.1	0	0	1	1	0	0
Total: 8	1	1	9	10	0	0

Vendor security updates are not trusted.
Overrides are off. Even when a result has an override, this report uses the actual threat of the result.
Information on overrides is included in the report.
Notes are included in the report.
This report might not show details of all issues that were found.
Issues with the threat level “Log” are not shown.
Issues with the threat level “Debug” are not shown.
Issues with the threat level “False Positive” are not shown.
Only results with a minimum QoD of 70 are shown.

This report contains all 21 results selected by the filtering described above. Before filtering there were 116 results.

2 Results per Host

2.1 10.9.1.10

Host scan start Mon Oct 5 16:55:48 2026 UTC
Host scan end Mon Oct 5 18:36:37 2026 UTC

Service (Port)	Threat Level
general/tcp	Low
general/icmp	Low

2.1.1 Low general/tcp

Low (CVSS: 2.6)

NVT: TCP Timestamps Information Disclosure

Summary
The remote host implements TCP timestamps and therefore allows to compute the uptime.

Quality of Detection (QoD): 80%

Vulnerability Detection Result
```
It was detected that the host implements RFC1323/RFC7323.
The following timestamps were retrieved with a delay of 1 seconds in-between:
```

... continues on next page ...

... continued from previous page ...

Packet 1: 3414248289
Packet 2: 3414249787

Impact
A side effect of this feature is that the uptime of the remote host can sometimes be computed.

Solution:
Solution type: Mitigation
To disable TCP timestamps on linux add the line 'net.ipv4.tcp_timestamps = 0' to /etc/sysctl.conf. Execute 'sysctl -p' to apply the settings at runtime.
To disable TCP timestamps on Windows execute 'netsh int tcp set global timestamps=disabled'
Starting with Windows Server 2008 and Vista, the timestamp can not be completely disabled.
The default behavior of the TCP/IP stack on this Systems is to not use the Timestamp options when initiating TCP connections, but use them if the TCP peer that is initiating communication includes them in their synchronize (SYN) segment.
See the references for more information.

Affected Software/OS
TCP implementations that implement RFC1323/RFC7323.

Vulnerability Insight
The remote host implements TCP timestamps, as defined by RFC1323/RFC7323.

Vulnerability Detection Method
Special IP packets are forged and sent with a little delay in between to the target IP. The responses are searched for a timestamps. If found, the timestamps are reported.
Details: TCP Timestamps Information Disclosure
OID:1.3.6.1.4.1.25623.1.0.80091
Version used: 2023-12-15T16:10:08Z

References
url: https://datatracker.ietf.org/doc/html/rfc1323
url: https://datatracker.ietf.org/doc/html/rfc7323
url: https://web.archive.org/web/20151213072445/http://www.microsoft.com/en-us/download/details.aspx?id=9152
url: https://www.fortiguard.com/psirt/FG-IR-16-090

[return to 10.9.1.10]

2.1.2 Low general/icmp

Low (CVSS: 2.1)

NVT: ICMP Timestamp Reply Information Disclosure

Summary
The remote host responded to an ICMP timestamp request.

Quality of Detection (QoD): 80%

Vulnerability Detection Result
The following response / ICMP packet has been received:
- ICMP Type: 14
- ICMP Code: 0

Impact
This information could theoretically be used to exploit weak time-based random number generators in other services.

Solution:
Solution type: Mitigation
Various mitigations are possible:
- Disable the support for ICMP timestamp on the remote host completely
- Protect the remote host by a firewall, and block ICMP packets passing through the firewall in either direction (either completely or only for untrusted networks)

... continues on next page ...

. . . continued from previous page . . .

Vulnerability Insight
The Timestamp Reply is an ICMP message which replies to a Timestamp message. It consists of the originating timestamp sent by the sender of the Timestamp as well as a receive timestamp and a transmit timestamp.

Vulnerability Detection Method
Sends an ICMP Timestamp (Type 13) request and checks if a Timestamp Reply (Type 14) is received.
Details: `ICMP Timestamp Reply Information Disclosure`
OID:1.3.6.1.4.1.25623.1.0.103190
Version used: `2025-01-21T05:37:33Z`

References
`cve: CVE-1999-0524`
`url: https://datatracker.ietf.org/doc/html/rfc792`
`url: https://datatracker.ietf.org/doc/html/rfc2780`
`cert-bund: CB-K15/1514`
`cert-bund: CB-K14/0632`
`dfn-cert: DFN-CERT-2014-0658`

[return to 10.9.1.10]

2.2 172.16.10.2

Host scan start Mon Oct 5 16:55:48 2026 UTC
Host scan end Mon Oct 5 17:42:19 2026 UTC

Service (Port)	Threat Level
general/icmp	Low

2.2.1 Low general/icmp

Low (CVSS: 2.1)
NVT: ICMP Timestamp Reply Information Disclosure

Summary
The remote host responded to an ICMP timestamp request.

Quality of Detection (QoD): 80%

Vulnerability Detection Result
`The following response / ICMP packet has been received:`
`- ICMP Type: 14`
`- ICMP Code: 0`

Impact
This information could theoretically be used to exploit weak time-based random number generators in other services.

Solution:
Solution type: Mitigation
Various mitigations are possible:
- Disable the support for ICMP timestamp on the remote host completely
- Protect the remote host by a firewall, and block ICMP packets passing through the firewall in either direction (either completely or only for untrusted networks)

Vulnerability Insight
The Timestamp Reply is an ICMP message which replies to a Timestamp message. It consists of the originating timestamp sent by the sender of the Timestamp as well as a receive timestamp and a transmit timestamp.

Vulnerability Detection Method
Sends an ICMP Timestamp (Type 13) request and checks if a Timestamp Reply (Type 14) is received.
Details: `ICMP Timestamp Reply Information Disclosure`

. . . continues on next page . . .

... continued from previous page ...

OID:1.3.6.1.4.1.25623.1.0.103190
Version used: 2025-01-21T05:37:33Z

References
cve: CVE-1999-0524
url: https://datatracker.ietf.org/doc/html/rfc792
url: https://datatracker.ietf.org/doc/html/rfc2780
cert-bund: CB-K15/1514
cert-bund: CB-K14/0632
dfn-cert: DFN-CERT-2014-0658

[return to 172.16.10.2]

2.3 172.16.30.1

Host scan start Mon Oct 5 16:55:48 2026 UTC
Host scan end Mon Oct 5 17:43:25 2026 UTC

Service (Port)	Threat Level
23/tcp	Medium
general/icmp	Low

2.3.1 Medium 23/tcp

Medium (CVSS: 4.8)

NVT: Telnet Unencrypted Cleartext Login

Summary
The remote host is running a Telnet service that allows cleartext logins over unencrypted connections.

Quality of Detection (QoD): 70%

Vulnerability Detection Result
Vulnerability was detected according to the Vulnerability Detection Method.

Impact
An attacker can uncover login names and passwords by sniffing traffic to the Telnet service.

Solution:
Solution type: Mitigation
Replace Telnet with a protocol like SSH which supports encrypted connections.

Vulnerability Detection Method
Details: Telnet Unencrypted Cleartext Login
OID:1.3.6.1.4.1.25623.1.0.108522
Version used: 2023-10-13T05:06:09Z

[return to 172.16.30.1]

2.3.2 Low general/icmp

Low (CVSS: 2.1)

NVT: ICMP Timestamp Reply Information Disclosure

Summary

... continues on next page ...

. . . continued from previous page . . .

The remote host responded to an ICMP timestamp request.

Quality of Detection (QoD): 80%

Vulnerability Detection Result
`The following response / ICMP packet has been received:`
`- ICMP Type: 14`
`- ICMP Code: 0`

Impact
This information could theoretically be used to exploit weak time-based random number generators in other services.

Solution:
Solution type: Mitigation
Various mitigations are possible:
- Disable the support for ICMP timestamp on the remote host completely
- Protect the remote host by a firewall, and block ICMP packets passing through the firewall in either direction (either completely or only for untrusted networks)

Vulnerability Insight
The Timestamp Reply is an ICMP message which replies to a Timestamp message. It consists of the originating timestamp sent by the sender of the Timestamp as well as a receive timestamp and a transmit timestamp.

Vulnerability Detection Method
Sends an ICMP Timestamp (Type 13) request and checks if a Timestamp Reply (Type 14) is received.
Details: `ICMP Timestamp Reply Information Disclosure`
OID:1.3.6.1.4.1.25623.1.0.103190
Version used: `2025-01-21T05:37:33Z`

References
`cve: CVE-1999-0524`
`url: https://datatracker.ietf.org/doc/html/rfc792`
`url: https://datatracker.ietf.org/doc/html/rfc2780`
`cert-bund: CB-K15/1514`
`cert-bund: CB-K14/0632`
`dfn-cert: DFN-CERT-2014-0658`

[return to 172.16.30.1]

2.4 172.16.30.2

Host scan start Mon Oct 5 16:55:48 2026 UTC
Host scan end Mon Oct 5 17:43:26 2026 UTC

Service (Port)	Threat Level
23/tcp	Medium
general/icmp	Low

2.4.1 Medium 23/tcp

Medium (CVSS: 4.8)

NVT: Telnet Unencrypted Cleartext Login

Summary
The remote host is running a Telnet service that allows cleartext logins over unencrypted connections.

Quality of Detection (QoD): 70%

Vulnerability Detection Result
Vulnerability was detected according to the Vulnerability Detection Method.

. . . continues on next page . . .

... continued from previous page ...

Impact
An attacker can uncover login names and passwords by sniffing traffic to the Telnet service.

Solution:
Solution type: Mitigation
Replace Telnet with a protocol like SSH which supports encrypted connections.

Vulnerability Detection Method
Details: `Telnet Unencrypted Cleartext Login`
OID:1.3.6.1.4.1.25623.1.0.108522
Version used: `2023-10-13T05:06:09Z`

[return to 172.16.30.2]

2.4.2 Low general/icmp

Low (CVSS: 2.1)

NVT: ICMP Timestamp Reply Information Disclosure

Summary
The remote host responded to an ICMP timestamp request.

Quality of Detection (QoD): 80%

Vulnerability Detection Result
```
The following response / ICMP packet has been received:
- ICMP Type: 14
- ICMP Code: 0
```

Impact
This information could theoretically be used to exploit weak time-based random number generators in other services.

Solution:
Solution type: Mitigation
Various mitigations are possible:
- Disable the support for ICMP timestamp on the remote host completely
- Protect the remote host by a firewall, and block ICMP packets passing through the firewall in either direction (either completely or only for untrusted networks)

Vulnerability Insight
The Timestamp Reply is an ICMP message which replies to a Timestamp message. It consists of the originating timestamp sent by the sender of the Timestamp as well as a receive timestamp and a transmit timestamp.

Vulnerability Detection Method
Sends an ICMP Timestamp (Type 13) request and checks if a Timestamp Reply (Type 14) is received.
Details: `ICMP Timestamp Reply Information Disclosure`
OID:1.3.6.1.4.1.25623.1.0.103190
Version used: `2025-01-21T05:37:33Z`

References
`cve: CVE-1999-0524`
`url: https://datatracker.ietf.org/doc/html/rfc792`
`url: https://datatracker.ietf.org/doc/html/rfc2780`
`cert-bund: CB-K15/1514`
`cert-bund: CB-K14/0632`
`dfn-cert: DFN-CERT-2014-0658`

[return to 172.16.30.2]

2.5 172.16.31.2

Host scan start Mon Oct 5 16:55:48 2026 UTC
Host scan end Mon Oct 5 17:43:47 2026 UTC

Service (Port)	Threat Level
23/tcp	Medium
general/icmp	Low

2.5.1 Medium 23/tcp

Medium (CVSS: 4.8)

NVT: Telnet Unencrypted Cleartext Login

Summary
The remote host is running a Telnet service that allows cleartext logins over unencrypted connections.

Quality of Detection (QoD): 70%

Vulnerability Detection Result
Vulnerability was detected according to the Vulnerability Detection Method.

Impact
An attacker can uncover login names and passwords by sniffing traffic to the Telnet service.

Solution:
Solution type: Mitigation
Replace Telnet with a protocol like SSH which supports encrypted connections.

Vulnerability Detection Method
Details: `Telnet Unencrypted Cleartext Login`
OID:1.3.6.1.4.1.25623.1.0.108522
Version used: `2023-10-13T05:06:09Z`

[return to 172.16.31.2]

2.5.2 Low general/icmp

Low (CVSS: 2.1)

NVT: ICMP Timestamp Reply Information Disclosure

Summary
The remote host responded to an ICMP timestamp request.

Quality of Detection (QoD): 80%

Vulnerability Detection Result
```
The following response / ICMP packet has been received:
- ICMP Type: 14
- ICMP Code: 0
```

Impact
This information could theoretically be used to exploit weak time-based random number generators in other services.

Solution:
Solution type: Mitigation
Various mitigations are possible:
- Disable the support for ICMP timestamp on the remote host completely

. . . continues on next page . . .

... continued from previous page ...

- Protect the remote host by a firewall, and block ICMP packets passing through the firewall in either direction (either completely or only for untrusted networks)

Vulnerability Insight
The Timestamp Reply is an ICMP message which replies to a Timestamp message. It consists of the originating timestamp sent by the sender of the Timestamp as well as a receive timestamp and a transmit timestamp.

Vulnerability Detection Method
Sends an ICMP Timestamp (Type 13) request and checks if a Timestamp Reply (Type 14) is received.
Details: ICMP Timestamp Reply Information Disclosure
OID:1.3.6.1.4.1.25623.1.0.103190
Version used: 2025-01-21T05:37:33Z

References
cve: CVE-1999-0524
url: https://datatracker.ietf.org/doc/html/rfc792
url: https://datatracker.ietf.org/doc/html/rfc2780
cert-bund: CB-K15/1514
cert-bund: CB-K14/0632
dfn-cert: DFN-CERT-2014-0658

[return to 172.16.31.2]

2.6 172.16.31.10

Host scan start Mon Oct 5 16:55:48 2026 UTC
Host scan end Mon Oct 5 19:01:35 2026 UTC

Service (Port)	Threat Level
general/tcp	Critical
445/tcp	High
135/tcp	Medium
3389/tcp	Medium
general/tcp	Low
general/icmp	Low

2.6.1 Critical general/tcp

Critical (CVSS: 10.0)

NVT: Operating System (OS) End of Life (EOL) Detection

Product detection result
cpe:/o:microsoft:windows_7:-:sp1
Detected by OS Detection Consolidation and Reporting (OID: 1.3.6.1.4.1.25623.1.0
↪.105937)

Summary
The Operating System (OS) on the remote host has reached the end of life (EOL) and should not be used anymore.

Quality of Detection (QoD): 80%

Vulnerability Detection Result
The "Windows 7" Operating System on the remote host has reached the end of life.
CPE: cpe:/o:microsoft:windows_7:-:sp1
Installed version,
build or SP: sp1
EOL date: 2020-01-14
EOL info: https://learn.microsoft.com/en-us/lifecycle/products/windows-
↪7

... continues on next page ...

... continued from previous page ...

Impact
An EOL version of an OS is not receiving any security updates from the vendor. Unfixed security vulnerabilities might be leveraged by an attacker to compromise the security of this host.

Solution:
Solution type: Mitigation
Update the OS on the remote host to a version which is still supported and receiving security updates by the vendor.
Note / Important: Please create an override for this result if the target host is a:
- Windows system with Extended Security Updates (ESU)
- System with additional 3rd-party / non-vendor security updates like e.g. from 'TuxCare', 'Freexian Extended LTS' or similar

Vulnerability Detection Method
Checks if an EOL version of an OS is present on the target host.
Details: `Operating System (OS) End of Life (EOL) Detection`
OID:1.3.6.1.4.1.25623.1.0.103674
Version used: `2025-05-21T05:40:19Z`

Product Detection Result
Product: `cpe:/o:microsoft:windows_7:-:sp1`
Method: `OS Detection Consolidation and Reporting`
OID: 1.3.6.1.4.1.25623.1.0.105937

[return to 172.16.31.10]

2.6.2 High 445/tcp

High (CVSS: 8.8)

NVT: Microsoft Windows SMB Server Multiple Vulnerabilities-Remote (4013389)

Summary
This host is missing a critical security update according to Microsoft Bulletin MS17-010.

Quality of Detection (QoD): 95%

Vulnerability Detection Result
Vulnerability was detected according to the Vulnerability Detection Method.

Impact
Successful exploitation will allow remote attackers to gain the ability to execute code on the target server, also could lead to information disclosure from the server.

Solution:
Solution type: VendorFix
The vendor has released updates. Please see the references for more information.

Affected Software/OS
- Microsoft Windows 10 x32/x64
- Microsoft Windows Server 2012
- Microsoft Windows Server 2016
- Microsoft Windows 8.1 x32/x64
- Microsoft Windows Server 2012 R2
- Microsoft Windows 7 x32/x64 Service Pack 1
- Microsoft Windows Vista x32/x64 Service Pack 2
- Microsoft Windows Server 2008 R2 x64 Service Pack 1
- Microsoft Windows Server 2008 x32/x64 Service Pack 2

Vulnerability Insight
Multiple flaws exist due to the way that the Microsoft Server Message Block 1.0 (SMBv1) server handles certain requests.

Vulnerability Detection Method
Send the crafted SMB transaction request with fid = 0 and check the response to confirm the vulnerability.

... continues on next page ...

... continued from previous page ...

Details: Microsoft Windows SMB Server Multiple Vulnerabilities-Remote (4013389)
OID:1.3.6.1.4.1.25623.1.0.810676
Version used: 2026-04-28T06:28:06Z

References
cve: CVE-2017-0143
cve: CVE-2017-0144
cve: CVE-2017-0145
cve: CVE-2017-0146
cve: CVE-2017-0147
cve: CVE-2017-0148
cisa: Known Exploited Vulnerability (KEV) catalog
url: https://www.cisa.gov/known-exploited-vulnerabilities-catalog
url: https://support.microsoft.com/en-us/kb/4013078
url: http://www.securityfocus.com/bid/96703
url: http://www.securityfocus.com/bid/96704
url: http://www.securityfocus.com/bid/96705
url: http://www.securityfocus.com/bid/96707
url: http://www.securityfocus.com/bid/96709
url: http://www.securityfocus.com/bid/96706
url: https://technet.microsoft.com/library/security/MS17-010
url: https://github.com/rapid7/metasploit-framework/pull/8167/files
cert-bund: CB-K17/0435
dfn-cert: DFN-CERT-2017-0448

[return to 172.16.31.10]

2.6.3 Medium 135/tcp

Medium (CVSS: 5.0)

NVT: DCE/RPC and MSRPC Services Enumeration Reporting

Summary
Distributed Computing Environment / Remote Procedure Calls (DCE/RPC) or MSRPC based service enumeration reporting.

Quality of Detection (QoD): 80%

Vulnerability Detection Result
```
Here is the list of DCE/RPC or MSRPC services running on this host via the TCP p
↪rotocol:
Port: 49152/tcp
      UUID: d95afe70-a6d5-4259-822e-2c84da1ddb0d, version 1
      Endpoint: ncacn_ip_tcp:172.16.31.10[49152]
Port: 49153/tcp
      UUID: 06bba54a-be05-49f9-b0a0-30f790261023, version 1
      Endpoint: ncacn_ip_tcp:172.16.31.10[49153]
      Annotation: Security Center
      UUID: 30adc50c-5cbc-46ce-9a0e-91914789e23c, version 1
      Endpoint: ncacn_ip_tcp:172.16.31.10[49153]
      Annotation: NRP server endpoint
      UUID: 3c4728c5-f0ab-448b-bda1-6ce01eb0a6d5, version 1
      Endpoint: ncacn_ip_tcp:172.16.31.10[49153]
      Annotation: DHCP Client LRPC Endpoint
      UUID: 3c4728c5-f0ab-448b-bda1-6ce01eb0a6d6, version 1
      Endpoint: ncacn_ip_tcp:172.16.31.10[49153]
      Annotation: DHCPv6 Client LRPC Endpoint
      UUID: f6beaff7-1e19-4fbb-9f8f-b89e2018337c, version 1
      Endpoint: ncacn_ip_tcp:172.16.31.10[49153]
      Annotation: Event log TCPIP
Port: 49154/tcp
      UUID: 30b044a5-a225-43f0-b3a4-e060df91f9c1, version 1
      Endpoint: ncacn_ip_tcp:172.16.31.10[49154]
      UUID: 552d076a-cb29-4e44-8b6a-d15e59e2c0af, version 1
      Endpoint: ncacn_ip_tcp:172.16.31.10[49154]
      Annotation: IP Transition Configuration endpoint
```

... continues on next page ...

... continued from previous page ...

```
      UUID: 86d35949-83c9-4044-b424-db363231fd0c, version 1
      Endpoint: ncacn_ip_tcp:172.16.31.10[49154]
      UUID: 98716d03-89ac-44c7-bb8c-285824e51c4a, version 1
      Endpoint: ncacn_ip_tcp:172.16.31.10[49154]
      Annotation: XactSrv service
      UUID: a398e520-d59a-4bdd-aa7a-3c1e0303a511, version 1
      Endpoint: ncacn_ip_tcp:172.16.31.10[49154]
      Annotation: IKE/Authip API
      UUID: c9ac6db5-82b7-4e55-ae8a-e464ed7b4277, version 1
      Endpoint: ncacn_ip_tcp:172.16.31.10[49154]
      Annotation: Impl friendly name
Port: 49155/tcp
      UUID: 12345778-1234-abcd-ef00-0123456789ac, version 1
      Endpoint: ncacn_ip_tcp:172.16.31.10[49155]
      Named pipe : lsass
      Win32 service or process : lsass.exe
      Description : SAM access
Port: 49156/tcp
      UUID: 367abb81-9844-35f1-ad32-98f038001003, version 2
      Endpoint: ncacn_ip_tcp:172.16.31.10[49156]
Port: 49158/tcp
      UUID: 12345678-1234-abcd-ef00-0123456789ab, version 1
      Endpoint: ncacn_ip_tcp:172.16.31.10[49158]
      Annotation: IPSec Policy agent endpoint
      Named pipe : spoolss
      Win32 service or process : spoolsv.exe
      Description : Spooler service
      UUID: 6b5bdd1e-528c-422c-af8c-a4079be4fe48, version 1
      Endpoint: ncacn_ip_tcp:172.16.31.10[49158]
      Annotation: Remote Fw APIs
Note: DCE/RPC or MSRPC services running on this host locally were identified. Re
↪porting this list is not enabled by default due to the possible large size of
↪this list. See the script preferences to enable this reporting.
```

Impact
An attacker may use this information to gain more knowledge about the remote host and to conduct further attacks based on it.

Solution:
Solution type: Mitigation
Filter incoming traffic to this ports.

Affected Software/OS
All systems exposing / disclosing information via DCE/RPC or MSRPC services.

Vulnerability Insight
DCE/RPC or MSRPC services running on the remote host can be enumerated by connecting on port 135 and doing the appropriate queries.

Vulnerability Detection Method
Reports previously collected (via 'DCE/RPC and MSRPC Services Enumeration' OID: 1.3.6.1.4.1.25623.1.0.108044) DCE/RPC or MSRPC services.
This VT is reporting a severity by default. If the scanned network is e.g. a private LAN / private WAN which contains systems not accessible to the public (access restricted) and it is accepted that the service is disclosing information to this network please set the 'Network type' configuration of the following VT to e.g. 'Private LAN' or 'Private WAN':
Global variable settings (OID: 1.3.6.1.4.1.25623.1.0.12288)
In this case a 'Log' level result is used instead.
Details: `DCE/RPC and MSRPC Services Enumeration Reporting`
OID:1.3.6.1.4.1.25623.1.0.10736
Version used: `2026-09-02T05:46:18Z`

[return to 172.16.31.10]

2.6.4 Medium 3389/tcp

Medium (CVSS: 5.9)

NVT: SSL/TLS: Report Weak Cipher Suites

Product detection result
cpe:/a:ietf:transport_layer_security
Detected by SSL/TLS: Report Supported Cipher Suites (OID: 1.3.6.1.4.1.25623.1.0.
↪802067)

Summary
This routine reports all weak SSL/TLS cipher suites accepted by a service.

Quality of Detection (QoD): 98%

Vulnerability Detection Result
'Weak' cipher suites accepted by this service via the TLSv1.0 protocol:
TLS_RSA_WITH_RC4_128_MD5
TLS_RSA_WITH_RC4_128_SHA

Impact
This could allow remote attackers to obtain sensitive information or have other, unspecified impacts.

Solution:
Solution type: Mitigation
The configuration of this services should be changed so that it does not accept the listed weak cipher suites anymore. Please see the references for more resources supporting you with this task.

Affected Software/OS
All services providing an encrypted communication using weak SSL/TLS cipher suites.

Vulnerability Insight
These rules are applied for the evaluation of the cryptographic strength:
- RC4 is considered to be weak (CVE-2013-2566, CVE-2015-2808)
- Ciphers using 64 bit or less are considered to be vulnerable to brute force methods and therefore considered as weak (CVE-2015-4000)
- 1024 bit RSA authentication is considered to be insecure and therefore as weak
- Any cipher considered to be secure for only the next 10 years is considered as medium
- Any other cipher is considered as strong

Vulnerability Detection Method
Checks previous collected cipher suites.
NOTE: No severity for SMTP services with 'Opportunistic TLS' and weak cipher suites on port 25/tcp is reported. If too strong cipher suites are configured for this service the alternative would be to fall back to an even more insecure cleartext communication.
Details: SSL/TLS: Report Weak Cipher Suites
OID:1.3.6.1.4.1.25623.1.0.103440
Version used: 2026-06-03T07:18:10Z

Product Detection Result
Product: cpe:/a:ietf:transport_layer_security
Method: SSL/TLS: Report Supported Cipher Suites
OID: 1.3.6.1.4.1.25623.1.0.802067

References
cve: CVE-2013-2566
cve: CVE-2015-2808
cve: CVE-2015-4000
url: https://configurator.tlsref.org/
url: https://www.bsi.bund.de/SharedDocs/Downloads/EN/BSI/Publications/TechGuidelines/TG02102/BSI-TR-02102-1.html
url: https://www.bsi.bund.de/EN/Themen/Oeffentliche-Verwaltung/Mindeststandards/TLS-Protokoll/TLS-Protokoll_node.html
url: https://www.bsi.bund.de/SharedDocs/Downloads/DE/BSI/Publikationen/TechnischeRichtlinien/TR03116/BSI-TR-03116-4.html
url: https://www.bsi.bund.de/SharedDocs/Downloads/DE/BSI/Mindeststandards/Mindeststandard_BSI_TLS_Version_2_4.html
url: https://web.archive.org/web/20240113175943/https://www.bettercrypto.org
url: https://www.enisa.europa.eu/publications/algorithms-key-size-and-parameters-report-2014
cert-bund: WID-SEC-2026-0180
cert-bund: CB-K21/0067
cert-bund: CB-K19/0812

... continues on next page ...

... continued from previous page ...

cert-bund: CB-K17/1750
cert-bund: CB-K16/1593
cert-bund: CB-K16/1552
cert-bund: CB-K16/1102
cert-bund: CB-K16/0617
cert-bund: CB-K16/0599
cert-bund: CB-K16/0168
cert-bund: CB-K16/0121
cert-bund: CB-K16/0090
cert-bund: CB-K16/0030
cert-bund: CB-K15/1751
cert-bund: CB-K15/1591
cert-bund: CB-K15/1550
cert-bund: CB-K15/1517
cert-bund: CB-K15/1514
cert-bund: CB-K15/1464
cert-bund: CB-K15/1442
cert-bund: CB-K15/1334
cert-bund: CB-K15/1269
cert-bund: CB-K15/1136
cert-bund: CB-K15/1090
cert-bund: CB-K15/1059
cert-bund: CB-K15/1022
cert-bund: CB-K15/1015
cert-bund: CB-K15/0986
cert-bund: CB-K15/0964
cert-bund: CB-K15/0962
cert-bund: CB-K15/0932
cert-bund: CB-K15/0927
cert-bund: CB-K15/0926
cert-bund: CB-K15/0907
cert-bund: CB-K15/0901
cert-bund: CB-K15/0896
cert-bund: CB-K15/0889
cert-bund: CB-K15/0877
cert-bund: CB-K15/0850
cert-bund: CB-K15/0849
cert-bund: CB-K15/0834
cert-bund: CB-K15/0827
cert-bund: CB-K15/0802
cert-bund: CB-K15/0764
cert-bund: CB-K15/0733
cert-bund: CB-K15/0667
cert-bund: CB-K14/0935
cert-bund: CB-K13/0942
dfn-cert: DFN-CERT-2023-2939
dfn-cert: DFN-CERT-2021-0775
dfn-cert: DFN-CERT-2020-1561
dfn-cert: DFN-CERT-2020-1276
dfn-cert: DFN-CERT-2017-1821
dfn-cert: DFN-CERT-2016-1692
dfn-cert: DFN-CERT-2016-1648
dfn-cert: DFN-CERT-2016-1168
dfn-cert: DFN-CERT-2016-0665
dfn-cert: DFN-CERT-2016-0642
dfn-cert: DFN-CERT-2016-0184
dfn-cert: DFN-CERT-2016-0135
dfn-cert: DFN-CERT-2016-0101
dfn-cert: DFN-CERT-2016-0035
dfn-cert: DFN-CERT-2015-1853
dfn-cert: DFN-CERT-2015-1679
dfn-cert: DFN-CERT-2015-1632
dfn-cert: DFN-CERT-2015-1608
dfn-cert: DFN-CERT-2015-1542
dfn-cert: DFN-CERT-2015-1518
dfn-cert: DFN-CERT-2015-1406
dfn-cert: DFN-CERT-2015-1341
dfn-cert: DFN-CERT-2015-1194
dfn-cert: DFN-CERT-2015-1144
dfn-cert: DFN-CERT-2015-1113
dfn-cert: DFN-CERT-2015-1078
dfn-cert: DFN-CERT-2015-1067

... continues on next page ...

...continued from previous page ...

dfn-cert: DFN-CERT-2015-1038
dfn-cert: DFN-CERT-2015-1016
dfn-cert: DFN-CERT-2015-1012
dfn-cert: DFN-CERT-2015-0980
dfn-cert: DFN-CERT-2015-0977
dfn-cert: DFN-CERT-2015-0976
dfn-cert: DFN-CERT-2015-0960
dfn-cert: DFN-CERT-2015-0956
dfn-cert: DFN-CERT-2015-0944
dfn-cert: DFN-CERT-2015-0937
dfn-cert: DFN-CERT-2015-0925
dfn-cert: DFN-CERT-2015-0884
dfn-cert: DFN-CERT-2015-0881
dfn-cert: DFN-CERT-2015-0879
dfn-cert: DFN-CERT-2015-0866
dfn-cert: DFN-CERT-2015-0844
dfn-cert: DFN-CERT-2015-0800
dfn-cert: DFN-CERT-2015-0737
dfn-cert: DFN-CERT-2015-0696
dfn-cert: DFN-CERT-2014-0977

Medium (CVSS: 4.3)

NVT: SSL/TLS: Deprecated TLSv1.0 and TLSv1.1 Protocol Detection

Product detection result
cpe:/a:ietf:transport_layer_security:1.0
Detected by SSL/TLS: Version Detection (OID: 1.3.6.1.4.1.25623.1.0.105782)

Summary
It was possible to detect the usage of the deprecated TLSv1.0 and/or TLSv1.1 protocol on this system.

Quality of Detection (QoD): 98%

Vulnerability Detection Result
The service is only providing the deprecated TLSv1.0 protocol and supports one o
↪r more ciphers. Those supported ciphers can be found in the 'SSL/TLS: Report S
↪upported Cipher Suites' (OID: 1.3.6.1.4.1.25623.1.0.802067) VT.

Impact
An attacker might be able to use the known cryptographic flaws to eavesdrop the connection between clients and the service to get access to sensitive data transferred within the secured connection.
Furthermore newly uncovered vulnerabilities in this protocols won't receive security updates anymore.

Solution:
Solution type: Mitigation
It is recommended to disable the deprecated TLSv1.0 and/or TLSv1.1 protocols in favor of the TLSv1.2+ protocols.
Please see the references for more resources supporting you with this task.

Affected Software/OS
- All services providing an encrypted communication using the TLSv1.0 and/or TLSv1.1 protocols
- CVE-2023-41928: Kiloview P1 4G and P2 4G Video Encoder
- CVE-2024-41270: Gorush v1.18.4
- CVE-2025-3200: Multiple products from Wiesemann & Theis

Vulnerability Insight
The TLSv1.0 and TLSv1.1 protocols contain known cryptographic flaws like:
- CVE-2011-3389: Browser Exploit Against SSL/TLS (BEAST)
- CVE-2015-0204: Factoring Attack on RSA-EXPORT Keys Padding Oracle On Downgraded Legacy Encryption (FREAK)

Vulnerability Detection Method
Checks the used TLS protocols of the services provided by this system.
Details: SSL/TLS: Deprecated TLSv1.0 and TLSv1.1 Protocol Detection
OID:1.3.6.1.4.1.25623.1.0.117274
Version used: 2026-06-03T07:18:10Z

...continues on next page ...

... continued from previous page ...

Product Detection Result
Product: cpe:/a:ietf:transport_layer_security:1.0
Method: SSL/TLS: Version Detection
OID: 1.3.6.1.4.1.25623.1.0.105782

References
cve: CVE-2011-3389
cve: CVE-2015-0204
cve: CVE-2023-41928
cve: CVE-2024-41270
cve: CVE-2025-3200
url: https://configurator.tlsref.org/
url: https://www.bsi.bund.de/SharedDocs/Downloads/EN/BSI/Publications/TechGuidelines/TG02102/BSI-TR-02102-1.html
url: https://www.bsi.bund.de/EN/Themen/Oeffentliche-Verwaltung/Mindeststandards/TLS-Protokoll/TLS-Protokoll_node.html
url: https://www.bsi.bund.de/SharedDocs/Downloads/DE/BSI/Publikationen/TechnischeRichtlinien/TR03116/BSI-TR-03116-4.html
url: https://www.bsi.bund.de/SharedDocs/Downloads/DE/BSI/Mindeststandards/Mindeststandard_BSI_TLS_Version_2_4.html
url: https://web.archive.org/web/20240113175943/https://www.bettercrypto.org
url: https://www.enisa.europa.eu/publications/algorithms-key-size-and-parameters-report-2014
url: https://datatracker.ietf.org/doc/rfc8996/
url: https://vnhacker.blogspot.com/2011/09/beast.html
url: https://web.archive.org/web/20201108095603/https://censys.io/blog/freak
url: https://certvde.com/en/advisories/VDE-2025-031/
url: https://gist.github.com/nyxfqq/cfae38fada582a0f576d154be1aeb1fc
url: https://advisories.ncsc.nl/advisory?id=NCSC-2024-0273
cert-bund: WID-SEC-2026-0180
cert-bund: WID-SEC-2023-1435
cert-bund: CB-K18/0799
cert-bund: CB-K16/1289
cert-bund: CB-K16/1096
cert-bund: CB-K15/1751
cert-bund: CB-K15/1266
cert-bund: CB-K15/0850
cert-bund: CB-K15/0764
cert-bund: CB-K15/0720
cert-bund: CB-K15/0548
cert-bund: CB-K15/0526
cert-bund: CB-K15/0509
cert-bund: CB-K15/0493
cert-bund: CB-K15/0384
cert-bund: CB-K15/0365
cert-bund: CB-K15/0364
cert-bund: CB-K15/0302
cert-bund: CB-K15/0192
cert-bund: CB-K15/0079
cert-bund: CB-K15/0016
cert-bund: CB-K14/1342
cert-bund: CB-K14/0231
cert-bund: CB-K13/0845
cert-bund: CB-K13/0796
cert-bund: CB-K13/0790
dfn-cert: DFN-CERT-2020-0177
dfn-cert: DFN-CERT-2020-0111
dfn-cert: DFN-CERT-2019-0068
dfn-cert: DFN-CERT-2018-1441
dfn-cert: DFN-CERT-2018-1408
dfn-cert: DFN-CERT-2016-1372
dfn-cert: DFN-CERT-2016-1164
dfn-cert: DFN-CERT-2016-0388
dfn-cert: DFN-CERT-2015-1853
dfn-cert: DFN-CERT-2015-1332
dfn-cert: DFN-CERT-2015-0884
dfn-cert: DFN-CERT-2015-0800
dfn-cert: DFN-CERT-2015-0758
dfn-cert: DFN-CERT-2015-0567
dfn-cert: DFN-CERT-2015-0544
dfn-cert: DFN-CERT-2015-0530
dfn-cert: DFN-CERT-2015-0396
dfn-cert: DFN-CERT-2015-0375
dfn-cert: DFN-CERT-2015-0374

... continues on next page ...

... continued from previous page ...

```
dfn-cert: DFN-CERT-2015-0305
dfn-cert: DFN-CERT-2015-0199
dfn-cert: DFN-CERT-2015-0079
dfn-cert: DFN-CERT-2015-0021
dfn-cert: DFN-CERT-2014-1414
dfn-cert: DFN-CERT-2013-1847
dfn-cert: DFN-CERT-2013-1792
dfn-cert: DFN-CERT-2012-1979
dfn-cert: DFN-CERT-2012-1829
dfn-cert: DFN-CERT-2012-1530
dfn-cert: DFN-CERT-2012-1380
dfn-cert: DFN-CERT-2012-1377
dfn-cert: DFN-CERT-2012-1292
dfn-cert: DFN-CERT-2012-1214
dfn-cert: DFN-CERT-2012-1213
dfn-cert: DFN-CERT-2012-1180
dfn-cert: DFN-CERT-2012-1156
dfn-cert: DFN-CERT-2012-1155
dfn-cert: DFN-CERT-2012-1039
dfn-cert: DFN-CERT-2012-0956
dfn-cert: DFN-CERT-2012-0908
dfn-cert: DFN-CERT-2012-0868
dfn-cert: DFN-CERT-2012-0867
dfn-cert: DFN-CERT-2012-0848
dfn-cert: DFN-CERT-2012-0838
dfn-cert: DFN-CERT-2012-0776
dfn-cert: DFN-CERT-2012-0722
dfn-cert: DFN-CERT-2012-0638
dfn-cert: DFN-CERT-2012-0627
dfn-cert: DFN-CERT-2012-0451
dfn-cert: DFN-CERT-2012-0418
dfn-cert: DFN-CERT-2012-0354
dfn-cert: DFN-CERT-2012-0234
dfn-cert: DFN-CERT-2012-0221
dfn-cert: DFN-CERT-2012-0177
dfn-cert: DFN-CERT-2012-0170
dfn-cert: DFN-CERT-2012-0146
dfn-cert: DFN-CERT-2012-0142
dfn-cert: DFN-CERT-2012-0126
dfn-cert: DFN-CERT-2012-0123
dfn-cert: DFN-CERT-2012-0095
dfn-cert: DFN-CERT-2012-0051
dfn-cert: DFN-CERT-2012-0047
dfn-cert: DFN-CERT-2012-0021
dfn-cert: DFN-CERT-2011-1953
dfn-cert: DFN-CERT-2011-1946
dfn-cert: DFN-CERT-2011-1844
dfn-cert: DFN-CERT-2011-1826
dfn-cert: DFN-CERT-2011-1774
dfn-cert: DFN-CERT-2011-1743
dfn-cert: DFN-CERT-2011-1738
dfn-cert: DFN-CERT-2011-1706
dfn-cert: DFN-CERT-2011-1628
dfn-cert: DFN-CERT-2011-1627
dfn-cert: DFN-CERT-2011-1619
dfn-cert: DFN-CERT-2011-1482
```

Medium (CVSS: 4.0)

NVT: SSL/TLS: Certificate Signed Using A Weak Signature Algorithm

Summary
The remote service is using a SSL/TLS certificate in the certificate chain that has been signed using a cryptographically weak hashing algorithm.

Quality of Detection (QoD): 80%

Vulnerability Detection Result
The following certificates are part of the certificate chain but using insecure

... continues on next page ...

... continued from previous page ...

```
↪signature algorithms:
Subject:              CN=user-PC
Signature Algorithm:  sha1WithRSAEncryption
```

Solution:
Solution type: Mitigation
Servers that use SSL/TLS certificates signed with a weak SHA-1, MD5, MD4 or MD2 hashing algorithm will need to obtain new SHA-2 signed SSL/TLS certificates to avoid web browser SSL/TLS certificate warnings.

Vulnerability Insight
The following hashing algorithms used for signing SSL/TLS certificates are considered cryptographically weak and not secure enough for ongoing use:
- Secure Hash Algorithm 1 (SHA-1)
- Message Digest 5 (MD5)
- Message Digest 4 (MD4)
- Message Digest 2 (MD2)
Beginning as late as January 2017 and as early as June 2016, browser developers such as Microsoft and Google will begin warning users when visiting web sites that use SHA-1 signed Secure Socket Layer (SSL) certificates.
NOTE: The script preference allows to set one or more custom SHA-1 fingerprints of CA certificates which are trusted by this routine. The fingerprints needs to be passed comma-separated and case-insensitive:
Fingerprint1
or
fingerprint1, Fingerprint2

Vulnerability Detection Method
Check which hashing algorithm was used to sign the remote SSL/TLS certificate.
Details: `SSL/TLS: Certificate Signed Using A Weak Signature Algorithm`
OID:1.3.6.1.4.1.25623.1.0.105880
Version used: `2021-10-15T11:13:32Z`

References
`url:` https://blog.mozilla.org/security/2014/09/23/phasing-out-certificates-with-sha-1-based-signature-algorithms/

[return to 172.16.31.10]

2.6.5 Low general/tcp

Low (CVSS: 2.6)

NVT: TCP Timestamps Information Disclosure

Summary
The remote host implements TCP timestamps and therefore allows to compute the uptime.

Quality of Detection (QoD): 80%

Vulnerability Detection Result
```
It was detected that the host implements RFC1323/RFC7323.
The following timestamps were retrieved with a delay of 1 seconds in-between:
Packet 1: 468641
Packet 2: 468749
```

Impact
A side effect of this feature is that the uptime of the remote host can sometimes be computed.

Solution:
Solution type: Mitigation
To disable TCP timestamps on linux add the line 'net.ipv4.tcp_timestamps = 0' to /etc/sysctl.conf. Execute 'sysctl -p' to apply the settings at runtime.
To disable TCP timestamps on Windows execute 'netsh int tcp set global timestamps=disabled'
Starting with Windows Server 2008 and Vista, the timestamp can not be completely disabled.
The default behavior of the TCP/IP stack on this Systems is to not use the Timestamp options when initiating TCP connections, but use them if the TCP peer that is initiating communication includes them in their synchronize (SYN) segment.
See the references for more information.

... continues on next page ...

... continued from previous page ...

Affected Software/OS
TCP implementations that implement RFC1323/RFC7323.

Vulnerability Insight
The remote host implements TCP timestamps, as defined by RFC1323/RFC7323.

Vulnerability Detection Method
Special IP packets are forged and sent with a little delay in between to the target IP. The responses are searched for a timestamps. If found, the timestamps are reported.
Details: `TCP Timestamps Information Disclosure`
OID:1.3.6.1.4.1.25623.1.0.80091
Version used: `2023-12-15T16:10:08Z`

References
`url:` https://datatracker.ietf.org/doc/html/rfc1323
`url:` https://datatracker.ietf.org/doc/html/rfc7323
`url:` https://web.archive.org/web/20151213072445/http://www.microsoft.com/en-us/download/details.aspx?id=9152
`url:` https://www.fortiguard.com/psirt/FG-IR-16-090

[return to 172.16.31.10]

2.6.6 Low general/icmp

Low (CVSS: 2.1)

NVT: ICMP Timestamp Reply Information Disclosure

Summary
The remote host responded to an ICMP timestamp request.

Quality of Detection (QoD): 80%

Vulnerability Detection Result
```
The following response / ICMP packet has been received:
- ICMP Type: 14
- ICMP Code: 0
```

Impact
This information could theoretically be used to exploit weak time-based random number generators in other services.

Solution:
Solution type: Mitigation
Various mitigations are possible:
- Disable the support for ICMP timestamp on the remote host completely
- Protect the remote host by a firewall, and block ICMP packets passing through the firewall in either direction (either completely or only for untrusted networks)

Vulnerability Insight
The Timestamp Reply is an ICMP message which replies to a Timestamp message. It consists of the originating timestamp sent by the sender of the Timestamp as well as a receive timestamp and a transmit timestamp.

Vulnerability Detection Method
Sends an ICMP Timestamp (Type 13) request and checks if a Timestamp Reply (Type 14) is received.
Details: `ICMP Timestamp Reply Information Disclosure`
OID:1.3.6.1.4.1.25623.1.0.103190
Version used: `2025-01-21T05:37:33Z`

References
`cve:` CVE-1999-0524
`url:` https://datatracker.ietf.org/doc/html/rfc792
`url:` https://datatracker.ietf.org/doc/html/rfc2780
`cert-bund:` CB-K15/1514
`cert-bund:` CB-K14/0632

... continues on next page ...

... continued from previous page ...

dfn-cert: DFN-CERT-2014-0658

[return to 172.16.31.10]

2.7 172.16.254.1

Host scan start Mon Oct 5 16:55:48 2026 UTC
Host scan end Mon Oct 5 17:41:19 2026 UTC

Service (Port)	Threat Level
23/tcp	Medium
general/icmp	Low

2.7.1 Medium 23/tcp

Medium (CVSS: 4.8)

NVT: Telnet Unencrypted Cleartext Login

Summary
The remote host is running a Telnet service that allows cleartext logins over unencrypted connections.

Quality of Detection (QoD): 70%

Vulnerability Detection Result
Vulnerability was detected according to the Vulnerability Detection Method.

Impact
An attacker can uncover login names and passwords by sniffing traffic to the Telnet service.

Solution:
Solution type: Mitigation
Replace Telnet with a protocol like SSH which supports encrypted connections.

Vulnerability Detection Method
Details: Telnet Unencrypted Cleartext Login
OID:1.3.6.1.4.1.25623.1.0.108522
Version used: 2023-10-13T05:06:09Z

[return to 172.16.254.1]

2.7.2 Low general/icmp

Low (CVSS: 2.1)

NVT: ICMP Timestamp Reply Information Disclosure

Summary
The remote host responded to an ICMP timestamp request.

Quality of Detection (QoD): 80%

Vulnerability Detection Result
The following response / ICMP packet has been received:
- ICMP Type: 14
- ICMP Code: 0

... continues on next page ...

. . . continued from previous page . . .

Impact
This information could theoretically be used to exploit weak time-based random number generators in other services.

Solution:
Solution type: Mitigation
Various mitigations are possible:
- Disable the support for ICMP timestamp on the remote host completely
- Protect the remote host by a firewall, and block ICMP packets passing through the firewall in either direction (either completely or only for untrusted networks)

Vulnerability Insight
The Timestamp Reply is an ICMP message which replies to a Timestamp message. It consists of the originating timestamp sent by the sender of the Timestamp as well as a receive timestamp and a transmit timestamp.

Vulnerability Detection Method
Sends an ICMP Timestamp (Type 13) request and checks if a Timestamp Reply (Type 14) is received.
Details: `ICMP Timestamp Reply Information Disclosure`
OID:1.3.6.1.4.1.25623.1.0.103190
Version used: `2025-01-21T05:37:33Z`

References
`cve: CVE-1999-0524`
`url: https://datatracker.ietf.org/doc/html/rfc792`
`url: https://datatracker.ietf.org/doc/html/rfc2780`
`cert-bund: CB-K15/1514`
`cert-bund: CB-K14/0632`
`dfn-cert: DFN-CERT-2014-0658`

[return to 172.16.254.1]

2.8 172.16.255.1

Host scan start Mon Oct 5 16:55:48 2026 UTC
Host scan end Mon Oct 5 17:41:09 2026 UTC

Service (Port)	Threat Level
23/tcp	Medium
general/icmp	Low

2.8.1 Medium 23/tcp

Medium (CVSS: 4.8)

NVT: Telnet Unencrypted Cleartext Login

Summary
The remote host is running a Telnet service that allows cleartext logins over unencrypted connections.

Quality of Detection (QoD): 70%

Vulnerability Detection Result
Vulnerability was detected according to the Vulnerability Detection Method.

Impact
An attacker can uncover login names and passwords by sniffing traffic to the Telnet service.

Solution:
Solution type: Mitigation
Replace Telnet with a protocol like SSH which supports encrypted connections.

. . . continues on next page . . .

. . . continued from previous page . . .

Vulnerability Detection Method
Details: Telnet Unencrypted Cleartext Login
OID:1.3.6.1.4.1.25623.1.0.108522
Version used: 2023-10-13T05:06:09Z

[return to 172.16.255.1]

2.8.2 Low general/icmp

Low (CVSS: 2.1)

NVT: ICMP Timestamp Reply Information Disclosure

Summary
The remote host responded to an ICMP timestamp request.

Quality of Detection (QoD): 80%

Vulnerability Detection Result
The following response / ICMP packet has been received:
- ICMP Type: 14
- ICMP Code: 0

Impact
This information could theoretically be used to exploit weak time-based random number generators in other services.

Solution:
Solution type: Mitigation
Various mitigations are possible:
- Disable the support for ICMP timestamp on the remote host completely
- Protect the remote host by a firewall, and block ICMP packets passing through the firewall in either direction (either completely or only for untrusted networks)

Vulnerability Insight
The Timestamp Reply is an ICMP message which replies to a Timestamp message. It consists of the originating timestamp sent by the sender of the Timestamp as well as a receive timestamp and a transmit timestamp.

Vulnerability Detection Method
Sends an ICMP Timestamp (Type 13) request and checks if a Timestamp Reply (Type 14) is received.
Details: ICMP Timestamp Reply Information Disclosure
OID:1.3.6.1.4.1.25623.1.0.103190
Version used: 2025-01-21T05:37:33Z

References
cve: CVE-1999-0524
url: https://datatracker.ietf.org/doc/html/rfc792
url: https://datatracker.ietf.org/doc/html/rfc2780
cert-bund: CB-K15/1514
cert-bund: CB-K14/0632
dfn-cert: DFN-CERT-2014-0658

[return to 172.16.255.1]