Scan Report

October 5, 2026

Summary

This document reports on the results of an automatic security scan. All dates are displayed using the timezone "Coordinated Universal Time", which is abbreviated "UTC". The task was "Scan Découverte Réseau". The scan started at Fri Oct 2 03:48:16 2026 UTC and ended at Fri Oct 2 08:15:42 2026 UTC. The report first summarises the results found. Then, for each host, the report describes every issue found. Please consider the advice given in each description, in order to rectify the issue.

Contents

1 Result Overview **2**

2 Results per Host **2**

2.1 172.16.30.10 . . . 2
2.1.1 Critical 445/tcp . . . 2
2.1.2 Medium 3389/tcp . . . 3
2.1.3 Low general/icmp . . . 5
2.2 172.16.30.11 . . . 6
2.2.1 Critical 22/tcp . . . 6
2.2.2 Medium 80/tcp . . . 8
2.2.3 Low general/icmp . . . 9
2.2.4 Low general/tcp . . . 9
2.2.5 Low 22/tcp . . . 10
2.3 172.16.30.60 . . . 11
2.4 172.16.255.1 . . . 11
2.4.1 Low general/icmp . . . 11

1 Result Overview

Host	Critical	High	Medium	Low	Log	False P.
172.16.30.10 172.16.30.10	1	0	1	1	0	0
172.16.30.11 172.16.30.11	1	0	1	3	0	0
172.16.30.60 172.16.30.60	0	0	0	0	0	0
172.16.255.1 172.16.255.1	0	0	0	1	0	0
Total: 4	2	0	2	5	0	0

Vendor security updates are not trusted.
Overrides are off. Even when a result has an override, this report uses the actual threat of the result.
Information on overrides is included in the report.
Notes are included in the report.
This report might not show details of all issues that were found.
Issues with the threat level "Log" are not shown.
Issues with the threat level "Debug" are not shown.
Issues with the threat level "False Positive" are not shown.
Only results with a minimum QoD of 70 are shown.

This report contains all 9 results selected by the filtering described above. Before filtering there were 103 results.

2 Results per Host

2.1 172.16.30.10

Host scan start Fri Oct 2 04:37:25 2026 UTC
Host scan end Fri Oct 2 08:15:33 2026 UTC

Service (Port)	Threat Level
445/tcp	Critical
3389/tcp	Medium
general/icmp	Low

2.1.1 Critical 445/tcp

Critical (CVSS: 10.0)

NVT: SMB Brute Force Logins With Default Credentials

Summary
A number of known default credentials are tried for the login via the SMB protocol.

Quality of Detection (QoD): 99%

Vulnerability Detection Result
```
It was possible to login with the following credentials via the SMB protocol to
↪the 'IPC$' share. <User>:<Password>
administrator:
```

Solution:
Solution type: Mitigation
Change the password as soon as possible.

...continues on next page ...

. . . continued from previous page . . .

Vulnerability Detection Method
Tries to login with a number of known default credentials via the SMB protocol.
Details: SMB Brute Force Logins With Default Credentials
OID:1.3.6.1.4.1.25623.1.0.804449
Version used: 2026-03-18T05:59:10Z

References
cve: CVE-1999-0503
cve: CVE-1999-0504
cve: CVE-1999-0505
cve: CVE-1999-0506
cve: CVE-1999-0585
cve: CVE-2000-0222
cve: CVE-2005-3595

[return to 172.16.30.10]

2.1.2 Medium 3389/tcp

Medium (CVSS: 4.3)
NVT: SSL/TLS: Deprecated TLSv1.0 and TLSv1.1 Protocol Detection

Product detection result
cpe:/a:ietf:transport_layer_security:1.0
Detected by SSL/TLS: Version Detection (OID: 1.3.6.1.4.1.25623.1.0.105782)

Summary
It was possible to detect the usage of the deprecated TLSv1.0 and/or TLSv1.1 protocol on this system.

Quality of Detection (QoD): 98%

Vulnerability Detection Result
In addition to TLSv1.2+ the service is also providing the deprecated TLSv1.0 and
↪ TLSv1.1 protocols and supports one or more ciphers. Those supported ciphers c
↪an be found in the 'SSL/TLS: Report Supported Cipher Suites' (OID: 1.3.6.1.4.1
↪.25623.1.0.802067) VT.

Impact
An attacker might be able to use the known cryptographic flaws to eavesdrop the connection between clients and the service to get access to sensitive data transferred within the secured connection.
Furthermore newly uncovered vulnerabilities in this protocols won't receive security updates anymore.

Solution:
Solution type: Mitigation
It is recommended to disable the deprecated TLSv1.0 and/or TLSv1.1 protocols in favor of the TLSv1.2+ protocols.
Please see the references for more resources supporting you with this task.

Affected Software/OS
- All services providing an encrypted communication using the TLSv1.0 and/or TLSv1.1 protocols
- CVE-2023-41928: Kiloview P1 4G and P2 4G Video Encoder
- CVE-2024-41270: Gorush v1.18.4
- CVE-2025-3200: Multiple products from Wiesemann & Theis

Vulnerability Insight
The TLSv1.0 and TLSv1.1 protocols contain known cryptographic flaws like:
- CVE-2011-3389: Browser Exploit Against SSL/TLS (BEAST)
- CVE-2015-0204: Factoring Attack on RSA-EXPORT Keys Padding Oracle On Downgraded Legacy Encryption (FREAK)

Vulnerability Detection Method
Checks the used TLS protocols of the services provided by this system.
Details: SSL/TLS: Deprecated TLSv1.0 and TLSv1.1 Protocol Detection

. . . continues on next page . . .

... continued from previous page ...

OID:1.3.6.1.4.1.25623.1.0.117274
Version used: 2026-06-03T07:18:10Z

Product Detection Result
Product: cpe:/a:ietf:transport_layer_security:1.0
Method: SSL/TLS: Version Detection
OID: 1.3.6.1.4.1.25623.1.0.105782

References
cve: CVE-2011-3389
cve: CVE-2015-0204
cve: CVE-2023-41928
cve: CVE-2024-41270
cve: CVE-2025-3200
url: https://configurator.tlsref.org/
url: https://www.bsi.bund.de/SharedDocs/Downloads/EN/BSI/Publications/TechGuidelines/TG02102/BSI-TR-02102-1.html
url: https://www.bsi.bund.de/EN/Themen/Oeffentliche-Verwaltung/Mindeststandards/TLS-Protokoll/TLS-Protokoll_node.html
url: https://www.bsi.bund.de/SharedDocs/Downloads/DE/BSI/Publikationen/TechnischeRichtlinien/TR03116/BSI-TR-03116-4.html
url: https://www.bsi.bund.de/SharedDocs/Downloads/DE/BSI/Mindeststandards/Mindeststandard_BSI_TLS_Version_2_4.html
url: https://web.archive.org/web/20240113175943/https://www.bettercrypto.org
url: https://www.enisa.europa.eu/publications/algorithms-key-size-and-parameters-report-2014
url: https://datatracker.ietf.org/doc/rfc8996/
url: https://vnhacker.blogspot.com/2011/09/beast.html
url: https://web.archive.org/web/20201108095603/https://censys.io/blog/freak
url: https://certvde.com/en/advisories/VDE-2025-031/
url: https://gist.github.com/nyxfqq/cfae38fada582a0f576d154be1aeb1fc
url: https://advisories.ncsc.nl/advisory?id=NCSC-2024-0273
cert-bund: WID-SEC-2026-0180
cert-bund: WID-SEC-2023-1435
cert-bund: CB-K18/0799
cert-bund: CB-K16/1289
cert-bund: CB-K16/1096
cert-bund: CB-K15/1751
cert-bund: CB-K15/1266
cert-bund: CB-K15/0850
cert-bund: CB-K15/0764
cert-bund: CB-K15/0720
cert-bund: CB-K15/0548
cert-bund: CB-K15/0526
cert-bund: CB-K15/0509
cert-bund: CB-K15/0493
cert-bund: CB-K15/0384
cert-bund: CB-K15/0365
cert-bund: CB-K15/0364
cert-bund: CB-K15/0302
cert-bund: CB-K15/0192
cert-bund: CB-K15/0079
cert-bund: CB-K15/0016
cert-bund: CB-K14/1342
cert-bund: CB-K14/0231
cert-bund: CB-K13/0845
cert-bund: CB-K13/0796
cert-bund: CB-K13/0790
dfn-cert: DFN-CERT-2020-0177
dfn-cert: DFN-CERT-2020-0111
dfn-cert: DFN-CERT-2019-0068
dfn-cert: DFN-CERT-2018-1441
dfn-cert: DFN-CERT-2018-1408
dfn-cert: DFN-CERT-2016-1372
dfn-cert: DFN-CERT-2016-1164
dfn-cert: DFN-CERT-2016-0388
dfn-cert: DFN-CERT-2015-1853
dfn-cert: DFN-CERT-2015-1332
dfn-cert: DFN-CERT-2015-0884
dfn-cert: DFN-CERT-2015-0800
dfn-cert: DFN-CERT-2015-0758
dfn-cert: DFN-CERT-2015-0567
dfn-cert: DFN-CERT-2015-0544
dfn-cert: DFN-CERT-2015-0530

... continues on next page ...

... continued from previous page ...

```
dfn-cert: DFN-CERT-2015-0396
dfn-cert: DFN-CERT-2015-0375
dfn-cert: DFN-CERT-2015-0374
dfn-cert: DFN-CERT-2015-0305
dfn-cert: DFN-CERT-2015-0199
dfn-cert: DFN-CERT-2015-0079
dfn-cert: DFN-CERT-2015-0021
dfn-cert: DFN-CERT-2014-1414
dfn-cert: DFN-CERT-2013-1847
dfn-cert: DFN-CERT-2013-1792
dfn-cert: DFN-CERT-2012-1979
dfn-cert: DFN-CERT-2012-1829
dfn-cert: DFN-CERT-2012-1530
dfn-cert: DFN-CERT-2012-1380
dfn-cert: DFN-CERT-2012-1377
dfn-cert: DFN-CERT-2012-1292
dfn-cert: DFN-CERT-2012-1214
dfn-cert: DFN-CERT-2012-1213
dfn-cert: DFN-CERT-2012-1180
dfn-cert: DFN-CERT-2012-1156
dfn-cert: DFN-CERT-2012-1155
dfn-cert: DFN-CERT-2012-1039
dfn-cert: DFN-CERT-2012-0956
dfn-cert: DFN-CERT-2012-0908
dfn-cert: DFN-CERT-2012-0868
dfn-cert: DFN-CERT-2012-0867
dfn-cert: DFN-CERT-2012-0848
dfn-cert: DFN-CERT-2012-0838
dfn-cert: DFN-CERT-2012-0776
dfn-cert: DFN-CERT-2012-0722
dfn-cert: DFN-CERT-2012-0638
dfn-cert: DFN-CERT-2012-0627
dfn-cert: DFN-CERT-2012-0451
dfn-cert: DFN-CERT-2012-0418
dfn-cert: DFN-CERT-2012-0354
dfn-cert: DFN-CERT-2012-0234
dfn-cert: DFN-CERT-2012-0221
dfn-cert: DFN-CERT-2012-0177
dfn-cert: DFN-CERT-2012-0170
dfn-cert: DFN-CERT-2012-0146
dfn-cert: DFN-CERT-2012-0142
dfn-cert: DFN-CERT-2012-0126
dfn-cert: DFN-CERT-2012-0123
dfn-cert: DFN-CERT-2012-0095
dfn-cert: DFN-CERT-2012-0051
dfn-cert: DFN-CERT-2012-0047
dfn-cert: DFN-CERT-2012-0021
dfn-cert: DFN-CERT-2011-1953
dfn-cert: DFN-CERT-2011-1946
dfn-cert: DFN-CERT-2011-1844
dfn-cert: DFN-CERT-2011-1826
dfn-cert: DFN-CERT-2011-1774
dfn-cert: DFN-CERT-2011-1743
dfn-cert: DFN-CERT-2011-1738
dfn-cert: DFN-CERT-2011-1706
dfn-cert: DFN-CERT-2011-1628
dfn-cert: DFN-CERT-2011-1627
dfn-cert: DFN-CERT-2011-1619
dfn-cert: DFN-CERT-2011-1482
```

[return to 172.16.30.10]

2.1.3 Low general/icmp

Low (CVSS: 2.1)

NVT: ICMP Timestamp Reply Information Disclosure

Summary
The remote host responded to an ICMP timestamp request.

Quality of Detection (QoD): 80%

Vulnerability Detection Result
`The following response / ICMP packet has been received:`
`- ICMP Type: 14`
`- ICMP Code: 0`

Impact
This information could theoretically be used to exploit weak time-based random number generators in other services.

Solution:
Solution type: Mitigation
Various mitigations are possible:
- Disable the support for ICMP timestamp on the remote host completely
- Protect the remote host by a firewall, and block ICMP packets passing through the firewall in either direction (either completely or only for untrusted networks)

Vulnerability Insight
The Timestamp Reply is an ICMP message which replies to a Timestamp message. It consists of the originating timestamp sent by the sender of the Timestamp as well as a receive timestamp and a transmit timestamp.

Vulnerability Detection Method
Sends an ICMP Timestamp (Type 13) request and checks if a Timestamp Reply (Type 14) is received.
Details: `ICMP Timestamp Reply Information Disclosure`
OID:1.3.6.1.4.1.25623.1.0.103190
Version used: `2025-01-21T05:37:33Z`

References
`cve: CVE-1999-0524`
`url: https://datatracker.ietf.org/doc/html/rfc792`
`url: https://datatracker.ietf.org/doc/html/rfc2780`
`cert-bund: CB-K15/1514`
`cert-bund: CB-K14/0632`
`dfn-cert: DFN-CERT-2014-0658`

[return to 172.16.30.10]

2.2 172.16.30.11

Host scan start Fri Oct 2 04:37:25 2026 UTC
Host scan end Fri Oct 2 07:38:39 2026 UTC

Service (Port)	Threat Level
22/tcp	Critical
80/tcp	Medium
general/icmp	Low
general/tcp	Low
22/tcp	Low

2.2.1 Critical 22/tcp

Critical (CVSS: 9.8)

NVT: SSH Brute Force Logins With Default Credentials Reporting

. . . continues on next page . . .

...continued from previous page ...

Summary
It was possible to login into the remote SSH server using default credentials.

Quality of Detection (QoD): 95%

Vulnerability Detection Result
`It was possible to login with the following credentials <User>:<Password>`
`admin:1234`

Impact
This issue may be exploited by a remote attacker to e.g. gain access to sensitive information or modify system configuration.

Solution:
Solution type: Mitigation
Change the password as soon as possible.

Affected Software/OS
The following products are known to use the default credentials checked by the VT 'SSH Brute Force Logins With Default Credentials' (OID: 1.3.6.1.4.1.25623.1.0.108013) used for this reporting:
- CVE-2017-16523: MitraStar GPT-2541GNAC (HGU) 1.00(VNJ0)b1 and DSL-100HN-T1 ES_113WJY0b16 devices
- CVE-2017-20214: FLIR Thermal Camera F/FC/PT/D
- CVE-2018-25138: FLIR AX8 Thermal Camera
- CVE-2018-25147: Microhard Systems IPn4G
- CVE-2019-25241: FaceSentry Access Control System
- CVE-2019-25291: INIM Electronics Smartliving SmartLAN/G/SI
- CVE-2020-29583: Zyxel Firewall / AP Controller
- CVE-2020-36915: Adtec Digital SignEdje Digital Signage Player
- CVE-2020-37092: Netis E1+ devices
- CVE-2020-9473: S. Siedle & Soehne SG 150-0 Smart Gateway before 1.2.4
- CVE-2021-27797: Brocade Fabric OS
- CVE-2021-47744: Cypress Solutions CTM-200/CTM-ONE
- CVE-2023-1944: minikube 1.29.0 and probably prior
- CVE-2023-53983: Anevia Flamingo XL/XS
- CVE-2024-22902: Vinchin Backup & Recovery
- CVE-2024-31970: AdTran SRG 834-5 HDC17600021F1 devices (with SmartOS 11.1.1.1) during a window of time when the device is being set up
- CVE-2024-46328: VONETS VAP11G-300 v3.3.23.6.9
- CVE-2025-12592: Legacy Vivotek devices
- CVE-2025-68718: KAYSUS KS-WR1200
- CVE-2026-36538: Netis AC1200 Router NC21 V4.0.1.4296
- CVE-2026-35905: T3 Technology CPE models T625Pro v1.0.07, T6825G v1.0.03 and T7281 v1.0.03
- Various additional products like e.g. Ubiquiti EdgeMax / EdgeRouter, Crestron AM-100 and similar for which no CVE was assigned (See 'default_credentials.inc' file on the file system for a full list)
Other products might be affected as well.

Vulnerability Insight
As the VT 'SSH Brute Force Logins With Default Credentials' (OID: 1.3.6.1.4.1.25623.1.0.108013) might run into a timeout the actual reporting of this vulnerability takes place in this VT instead.

Vulnerability Detection Method
Reports default credentials detected by the VT 'SSH Brute Force Logins With Default Credentials' (OID: 1.3.6.1.4.1.25623.1.0.108013).
Details: `SSH Brute Force Logins With Default Credentials Reporting`
OID:1.3.6.1.4.1.25623.1.0.103239
Version used: `2026-06-10T06:59:19Z`

References
`cve: CVE-1999-0501`
`cve: CVE-1999-0502`
`cve: CVE-1999-0507`
`cve: CVE-1999-0508`
`cve: CVE-2005-1379`
`cve: CVE-2006-5288`
`cve: CVE-2009-3710`
`cve: CVE-2012-4577`
`cve: CVE-2016-1000245`
`cve: CVE-2017-16523`
`cve: CVE-2017-20214`
`cve: CVE-2018-25138`

...continues on next page ...

... continued from previous page ...

cve: CVE-2018-25147
cve: CVE-2019-25241
cve: CVE-2019-25291
cve: CVE-2020-29583
cve: CVE-2020-36915
cve: CVE-2020-37092
cve: CVE-2020-9473
cve: CVE-2021-27797
cve: CVE-2021-47744
cve: CVE-2023-1944
cve: CVE-2023-53983
cve: CVE-2024-22902
cve: CVE-2024-31970
cve: CVE-2024-46328
cve: CVE-2025-12592
cve: CVE-2025-41696
cve: CVE-2025-68718
cve: CVE-2026-36538
cve: CVE-2026-35905
url: https://www.cisa.gov/known-exploited-vulnerabilities-catalog
cisa: Known Exploited Vulnerability (KEV) catalog
cert-bund: WID-SEC-2025-2760

[return to 172.16.30.11]

2.2.2 Medium 80/tcp

Medium (CVSS: 4.8)

NVT: Cleartext Transmission of Sensitive Information via HTTP

Summary
The host / application transmits sensitive information (username, passwords) in cleartext via HTTP.

Quality of Detection (QoD): 80%

Vulnerability Detection Result
The following input fields were identified (URL:input name):
http://172.16.30.11/:pass

Impact
An attacker could use this situation to compromise or eavesdrop on the HTTP communication between the client and the server using a man-in-the-middle attack to get access to sensitive data like usernames or passwords.

Solution:
Solution type: Workaround
Enforce the transmission of sensitive data via an encrypted SSL/TLS connection. Additionally make sure the host / application is redirecting all users to the secured SSL/TLS connection before allowing to input sensitive data into the mentioned functions.

Affected Software/OS
Hosts / applications which doesn't enforce the transmission of sensitive data via an encrypted SSL/TLS connection.

Vulnerability Detection Method
Evaluate previous collected information and check if the host / application is not enforcing the transmission of sensitive data via an encrypted SSL/TLS connection.
The script is currently checking the following:
- HTTP Basic Authentication (Basic Auth)
- HTTP Forms (e.g. Login) with input field of type 'password'
Details: Cleartext Transmission of Sensitive Information via HTTP
OID:1.3.6.1.4.1.25623.1.0.108440
Version used: 2023-09-07T05:05:21Z

References
url: https://www.owasp.org/index.php/Top_10_2013-A2-Broken_Authentication_and_Session_Management
url: https://www.owasp.org/index.php/Top_10_2013-A6-Sensitive_Data_Exposure

... continues on next page ...

. . . continued from previous page . . .

url: https://cwe.mitre.org/data/definitions/319.html

[return to 172.16.30.11]

2.2.3 Low general/icmp

Low (CVSS: 2.1)

NVT: ICMP Timestamp Reply Information Disclosure

Summary
The remote host responded to an ICMP timestamp request.

Quality of Detection (QoD): 80%

Vulnerability Detection Result
The following response / ICMP packet has been received:
- ICMP Type: 14
- ICMP Code: 0

Impact
This information could theoretically be used to exploit weak time-based random number generators in other services.

Solution:
Solution type: Mitigation
Various mitigations are possible:
- Disable the support for ICMP timestamp on the remote host completely
- Protect the remote host by a firewall, and block ICMP packets passing through the firewall in either direction (either completely or only for untrusted networks)

Vulnerability Insight
The Timestamp Reply is an ICMP message which replies to a Timestamp message. It consists of the originating timestamp sent by the sender of the Timestamp as well as a receive timestamp and a transmit timestamp.

Vulnerability Detection Method
Sends an ICMP Timestamp (Type 13) request and checks if a Timestamp Reply (Type 14) is received.
Details: ICMP Timestamp Reply Information Disclosure
OID:1.3.6.1.4.1.25623.1.0.103190
Version used: 2025-01-21T05:37:33Z

References
cve: CVE-1999-0524
url: https://datatracker.ietf.org/doc/html/rfc792
url: https://datatracker.ietf.org/doc/html/rfc2780
cert-bund: CB-K15/1514
cert-bund: CB-K14/0632
dfn-cert: DFN-CERT-2014-0658

[return to 172.16.30.11]

2.2.4 Low general/tcp

Low (CVSS: 2.6)

NVT: TCP Timestamps Information Disclosure

Summary
The remote host implements TCP timestamps and therefore allows to compute the uptime.

Quality of Detection (QoD): 80%

. . . continues on next page . . .

... continued from previous page ...

Vulnerability Detection Result
It was detected that the host implements RFC1323/RFC7323.
The following timestamps were retrieved with a delay of 1 seconds in-between:
Packet 1: 2282232
Packet 2: 2282518

Impact
A side effect of this feature is that the uptime of the remote host can sometimes be computed.

Solution:
Solution type: Mitigation
To disable TCP timestamps on linux add the line 'net.ipv4.tcp_timestamps = 0' to /etc/sysctl.conf. Execute 'sysctl -p' to apply the settings at runtime.
To disable TCP timestamps on Windows execute 'netsh int tcp set global timestamps=disabled'
Starting with Windows Server 2008 and Vista, the timestamp can not be completely disabled.
The default behavior of the TCP/IP stack on this Systems is to not use the Timestamp options when initiating TCP connections, but use them if the TCP peer that is initiating communication includes them in their synchronize (SYN) segment.
See the references for more information.

Affected Software/OS
TCP implementations that implement RFC1323/RFC7323.

Vulnerability Insight
The remote host implements TCP timestamps, as defined by RFC1323/RFC7323.

Vulnerability Detection Method
Special IP packets are forged and sent with a little delay in between to the target IP. The responses are searched for a timestamps. If found, the timestamps are reported.
Details: TCP Timestamps Information Disclosure
OID:1.3.6.1.4.1.25623.1.0.80091
Version used: 2023-12-15T16:10:08Z

References
url: https://datatracker.ietf.org/doc/html/rfc1323
url: https://datatracker.ietf.org/doc/html/rfc7323
url: https://web.archive.org/web/20151213072445/http://www.microsoft.com/en-us/download/details.aspx?id=9152
url: https://www.fortiguard.com/psirt/FG-IR-16-090

[return to 172.16.30.11]

2.2.5 Low 22/tcp

Low (CVSS: 2.6)
NVT: Weak MAC Algorithm(s) Supported (SSH)

Product detection result
cpe:/a:ietf:secure_shell_protocol
Detected by SSH Protocol Algorithms Supported (OID: 1.3.6.1.4.1.25623.1.0.105565
↪)

Summary
The remote SSH server is configured to allow / support weak MAC algorithm(s).

Quality of Detection (QoD): 80%

Vulnerability Detection Result
The remote SSH server supports the following weak client-to-server MAC algorithm
↪(s):
umac-64-etm@openssh.com
umac-64@openssh.com
The remote SSH server supports the following weak server-to-client MAC algorithm

... continues on next page ...

... continued from previous page ...

↪(s):
umac-64-etm@openssh.com
umac-64@openssh.com

Solution:
Solution type: Mitigation
Disable the reported weak MAC algorithm(s).

Vulnerability Detection Method
Checks the supported MAC algorithms (client-to-server and server-to-client) of the remote SSH server.
Currently weak MAC algorithms are defined as the following:
- MD5 based algorithms
- 96-bit based algorithms
- 64-bit based algorithms
- 'none' algorithm
Details: Weak MAC Algorithm(s) Supported (SSH)
OID:1.3.6.1.4.1.25623.1.0.105610
Version used: 2024-06-14T05:05:48Z

Product Detection Result
Product: cpe:/a:ietf:secure_shell_protocol
Method: SSH Protocol Algorithms Supported
OID: 1.3.6.1.4.1.25623.1.0.105565

References
url: https://www.rfc-editor.org/rfc/rfc6668
url: https://www.rfc-editor.org/rfc/rfc4253#section-6.4

[return to 172.16.30.11]

2.3 172.16.30.60

Host scan start Fri Oct 2 04:37:24 2026 UTC
Host scan end Fri Oct 2 06:09:36 2026 UTC

Service (Port)	Threat Level

2.4 172.16.255.1

Host scan start Fri Oct 2 04:37:27 2026 UTC
Host scan end Fri Oct 2 06:27:09 2026 UTC

Service (Port)	Threat Level
general/icmp	Low

2.4.1 Low general/icmp

Low (CVSS: 2.1)
NVT: ICMP Timestamp Reply Information Disclosure

Summary
The remote host responded to an ICMP timestamp request.

Quality of Detection (QoD): 80%

Vulnerability Detection Result
The following response / ICMP packet has been received:
- ICMP Type: 14

... continues on next page ...

. . . continued from previous page . . .

- ICMP Code: 0

Impact
This information could theoretically be used to exploit weak time-based random number generators in other services.

Solution:
Solution type: Mitigation
Various mitigations are possible:
- Disable the support for ICMP timestamp on the remote host completely
- Protect the remote host by a firewall, and block ICMP packets passing through the firewall in either direction (either completely or only for untrusted networks)

Vulnerability Insight
The Timestamp Reply is an ICMP message which replies to a Timestamp message. It consists of the originating timestamp sent by the sender of the Timestamp as well as a receive timestamp and a transmit timestamp.

Vulnerability Detection Method
Sends an ICMP Timestamp (Type 13) request and checks if a Timestamp Reply (Type 14) is received.
Details: ICMP Timestamp Reply Information Disclosure
OID:1.3.6.1.4.1.25623.1.0.103190
Version used: 2025-01-21T05:37:33Z

References
cve: CVE-1999-0524
url: https://datatracker.ietf.org/doc/html/rfc792
url: https://datatracker.ietf.org/doc/html/rfc2780
cert-bund: CB-K15/1514
cert-bund: CB-K14/0632
dfn-cert: DFN-CERT-2014-0658

[return to 172.16.255.1]