



Center for
Internet Security®

CIS Apache HTTP Server 2.4 Benchmark

v1.3.0 - 05-31-2016

This work is licensed under a Creative Commons Attribution-NonCommercial-ShareAlike 4.0 International Public License. The link to the license terms can be found at <https://creativecommons.org/licenses/by-nc-sa/4.0/legalcode>

To further clarify the Creative Commons license related to CIS Benchmark content, you are authorized to copy and redistribute the content for use by you, within your organization and outside your organization for non-commercial purposes only, provided that (i) appropriate credit is given to CIS, (ii) a link to the license is provided. Additionally, if you remix, transform or build upon the CIS Benchmark(s), you may only distribute the modified materials if they are subject to the same license terms as the original Benchmark license and your derivative will no longer be a CIS Benchmark. Commercial use of CIS Benchmarks is subject to the prior approval of the Center for Internet Security.

Table of Contents

Overview	7
Intended Audience	7
Consensus Guidance	7
Typographical Conventions	8
Scoring Information.....	8
Profile Definitions.....	9
Acknowledgements.....	10
Recommendations.....	11
1 Recommendations	11
1.1 Planning and Installation	12
1.1.1 Pre-Installation Planning Checklist (Not Scored)	12
1.1.2 Do Not Install a Multi-use System (Not Scored)	14
1.1.3 Installing Apache (Not Scored)	15
1.2 Minimize Apache Modules.....	17
1.2.1 Enable only necessary Authentication and Authorization Modules (Not Scored)	17
1.2.2 Enable the Log Config Module (Scored)	19
1.2.3 Disable WebDAV Modules (Scored).....	21
1.2.4 Disable Status Module (Scored).....	23
1.2.5 Disable Autoindex Module (Scored)	25
1.2.6 Disable Proxy Modules (Scored)	27
1.2.7 Disable User Directories Modules (Scored)	29
1.2.8 Disable Info Module (Scored)	31
1.3 Principles, Permissions, and Ownership	33
1.3.1 Run the Apache Web Server as a non-root user (Scored)	33
1.3.2 Give the Apache User Account an Invalid Shell (Scored)	35

1.3.3 Lock the Apache User Account (Scored).....	36
1.3.4 Set Ownership on Apache Directories and Files (Scored)	37
1.3.5 Set Group Id on Apache Directories and Files (Scored).....	38
1.3.6 Restrict Other Write Access on Apache Directories and Files (Scored).....	39
1.3.7 Secure Core Dump Directory (Scored)	40
1.3.8 Secure the Lock File (Scored)	42
1.3.9 Secure the Pid File (Scored)	44
1.3.10 Secure the ScoreBoard File (Scored).....	45
1.3.11 Restrict Group Write Access for the Apache Directories and Files (Scored) ..	47
1.3.12 Restrict Group Write Access for the Document Root Directories and Files (Scored).....	48
1.4 Apache Access Control	49
1.4.1 Deny Access to OS Root Directory (Scored)	49
1.4.2 Allow Appropriate Access to Web Content (Not Scored)	52
1.4.3 Restrict Override for the OS Root Directory (Scored)	55
1.4.4 Restrict Override for All Directories (Scored).....	57
1.5 Minimize Features, Content and Options.....	59
1.5.1 Restrict Options for the OS Root Directory (Scored)	59
1.5.2 Restrict Options for the Web Root Directory (Scored).....	61
1.5.3 Minimize Options for Other Directories (Scored)	63
1.5.4 Remove Default HTML Content (Scored)	65
1.5.5 Remove Default CGI Content printenv (Scored).....	68
1.5.6 Remove Default CGI Content test-cgi (Scored)	70
1.5.7 Limit HTTP Request Methods (Scored).....	72
1.5.8 Disable HTTP TRACE Method (Scored).....	74

1.5.9 Restrict HTTP Protocol Versions (Scored)	75
1.5.10 Restrict Access to .ht* files (Scored)	77
1.5.11 Restrict File Extensions (Scored)	79
1.5.12 Deny IP Address Based Requests (Scored)	81
1.5.13 Restrict Listen Directive (Scored)	83
1.5.14 Restrict Browser Frame Options (Scored)	85
1.6 Operations - Logging, Monitoring and Maintenance	87
1.6.1 Configure the Error Log (Scored)	87
1.6.2 Configure a Syslog Facility for Error Logging (Scored)	89
1.6.3 Configure the Access Log (Scored)	91
1.6.4 Log Storage and Rotation (Scored)	93
1.6.5 Apply Applicable Patches (Scored)	96
1.6.6 Install and Enable ModSecurity (Scored)	98
1.6.7 Install and Enable OWASP ModSecurity Core Rule Set (Scored)	100
1.7 SSL/TLS Configuration	103
1.7.1 Install mod_ssl and/or mod_nss (Scored)	103
1.7.2 Install a Valid Trusted Certificate (Scored)	105
1.7.3 Protect the Server's Private Key (Scored)	108
1.7.4 Disable the SSL v3.0 Protocol (Scored)	110
1.7.5 Restrict Weak SSL Ciphers (Scored)	112
1.7.6 Disable SSL Insecure Renegotiation (Scored)	114
1.7.7 Ensure SSL Compression is not Enabled (Scored)	116
1.7.8 Disable the TLS v1.0 Protocol (Scored)	117
1.7.9 Enable OCSP Stapling (Scored)	119
1.7.10 Enable HTTP Strict Transport Security (Scored)	121

1.8 Information Leakage.....	124
1.8.1 Set ServerToken to 'Prod' (Scored).....	124
1.8.2 Set ServerSignature to 'Off' (Scored).....	126
1.8.3 Information Leakage via Default Apache Content (Scored).....	127
1.9 Denial of Service Mitigations.....	129
1.9.1 Set Timeout to 10 or less (Scored)	129
1.9.2 Set the KeepAlive directive to On (Scored)	131
1.9.3 Set MaxKeepAliveRequests to 100 or greater (Scored).....	132
1.9.4 Set KeepAliveTimeout Low to Mitigate Denial of Service (Scored)	133
1.9.5 Set Timeout Limits for Request Headers (Scored).....	134
1.9.6 Set Timeout Limits for the Request Body (Scored).....	136
1.10 Request Limits	138
1.10.1 Set the LimitRequestLine directive to 512 or less (Scored)	138
1.10.2 Set the LimitRequestFields directive to 100 or less (Scored).....	140
1.10.3 Set the LimitRequestFieldSize directive to 1024 or less (Scored).....	141
1.10.4 Set the LimitRequestBody directive to 102400 or less (Scored)	143
1.11 Enable SELinux to Restrict Apache Processes	145
1.11.1 Enable SELinux in Enforcing Mode (Scored)	145
1.11.2 Run Apache Processes in the httpd_t Confined Context (Scored).....	147
1.11.3 Ensure the httpd_t Type is Not in Permissive Mode (Scored).....	150
1.11.4 Ensure Only the Necessary SELinux Booleans are Enabled (Not Scored).....	151
1.12 Enable AppArmor to Restrict Apache Processes	153
1.12.1 Enable the AppArmor Framework (Scored)	153
1.12.2 Customize the Apache AppArmor Profile (Not Scored)	155
1.12.3 Ensure Apache AppArmor Profile is in Enforce Mode (Scored)	158

Appendix: Change History	163
--------------------------------	-----

Overview

This document, CIS Apache 2.4 Benchmark, provides prescriptive guidance for establishing a secure configuration posture for Apache Web Server versions 2.4 running on Linux. This guide was tested against Apache Web Server 2.4.3 - 2.4.6 as built from source `httpd-2.4.x.tar.gz` from <http://httpd.apache.org/> on Linux. To obtain the latest version of this guide, please visit <http://benchmarks.cisecurity.org>. If you have questions, comments, or have identified ways to improve this guide, please write us at feedback@cisecurity.org.

Intended Audience

This document is intended for system and application administrators, security specialists, auditors, help desk, and platform deployment personnel who plan to develop, deploy, assess, or secure solutions that incorporate Apache HTTP Server 2.4 running on Linux.

Consensus Guidance

This benchmark was created using a consensus review process comprised of subject matter experts. Consensus participants provide perspective from a diverse set of backgrounds including consulting, software development, audit and compliance, security research, operations, government, and legal.

Each CIS benchmark undergoes two phases of consensus review. The first phase occurs during initial benchmark development. During this phase, subject matter experts convene to discuss, create, and test working drafts of the benchmark. This discussion occurs until consensus has been reached on benchmark recommendations. The second phase begins after the benchmark has been published. During this phase, all feedback provided by the Internet community is reviewed by the consensus team for incorporation in the benchmark. If you are interested in participating in the consensus process, please visit <https://community.cisecurity.org>.

Typographical Conventions

The following typographical conventions are used throughout this guide:

Convention	Meaning
<code>Stylized Monospace font</code>	Used for blocks of code, command, and script examples. Text should be interpreted exactly as presented.
Monospace font	Used for inline code, commands, or examples. Text should be interpreted exactly as presented.
< <i>italic font in brackets</i> >	Italic texts set in angle brackets denote a variable requiring substitution for a real value.
<i>Italic font</i>	Used to denote the title of a book, article, or other publication.
Note	Additional information or caveats

Scoring Information

A scoring status indicates whether compliance with the given recommendation impacts the assessed target's benchmark score. The following scoring statuses are used in this benchmark:

Scored

Failure to comply with "Scored" recommendations will decrease the final benchmark score. Compliance with "Scored" recommendations will increase the final benchmark score.

Not Scored

Failure to comply with "Not Scored" recommendations will not decrease the final benchmark score. Compliance with "Not Scored" recommendations will not increase the final benchmark score.

Profile Definitions

The following configuration profiles are defined by this Benchmark:

- **Level 1**

Items in this profile intend to:

- be practical and prudent;
- provide a clear security benefit; and
- not inhibit the utility of the technology beyond acceptable means.

- **Level 2**

This profile extends the "Level 1" profile. Items in this profile exhibit one or more of the following characteristics:

- are intended for environments or use cases where security is paramount
- acts as defense in depth measure
- may negatively inhibit the utility or performance of the technology.

Acknowledgements

This benchmark exemplifies the great things a community of users, vendors, and subject matter experts can accomplish through consensus collaboration. The CIS community thanks the entire consensus team with special recognition to the following individuals who contributed greatly to the creation of this guide:

Author

Ralph Durkee CISSP, GSEC, GCIH, GSNA, GPEN, C|EH, *Durkee Consulting, Inc.*

Contributor

Ahmed Adel GSEC, GCIH, GCFW, GWAN

Ryan Barnett

Quan Bui

Lawrence Grim

Adam Montville

Eduardo Petazze

Vytautas Vysniauskas PhD, *Consumer Direct*

Roger Kennedy Linux Systems Engineer

Adam Montville

Christian Folini

Recommendations

1 Recommendations

This benchmark is tested with a source code build of Apache on Linux and hence the default values reflect that configuration. Many of the paths to the Apache files and directories are prefixed with a `$APACHE_PREFIX` variable which is expected to be the Server Root directory value where all of the Apache directories are located. Although having all of the Apache2 directories under one parent isn't compliant with the Filesystem Hierarchy Standard (FHS), many distributions which are compliant, place symbolic links in the Server Root directory (such as `/etc/httpd`) to provide a logical root directory that works well. Likewise a `$DOCROOT` variable is used to reference the path to the Apache web document root which is defined by the Apache DocumentRoot directory value in the configuration. The `HTTPD_ROOT` directory may be obtained from the running the `httpd` command with the `-V` option as shown below. The `apachectl` or `apache2ctl` commands may also be used as well as they will pass the `-V` option to the `httpd`. Likewise, the Server Root directory and the Document Root can be obtained from the configuration file with the following commands:

```
httpd -V | grep HTTPD_ROOT
grep '^ServerRoot' conf/httpd.conf
grep '^DocumentRoot' conf/httpd.conf
```

Also a `find` command may be helpful in determining the correct Apache directory paths.

```
find / -type d -name apache2
```

1.1 Planning and Installation

This section contains recommendations for the planning and installation of an Apache HTTP Server.

1.1.1 Pre-Installation Planning Checklist (Not Scored)

Profile Applicability:

- Level 1

Description:

Review and implement the following items as appropriate:

- Reviewed and implemented company's security policies as they relate to web security.
- Implemented a secure network infrastructure by controlling access to/from your web server by using firewalls, routers and switches.
- Harden the underlying Operating System of the web server, by minimizing listening network services, applying proper patches and hardening the configurations as recommended in the appropriate Center for Internet Security benchmark for the platform.
- Implement central log monitoring processes.
- Implemented a disk space monitoring process and log rotation mechanism.
- Educate developers, architects and testers about developing secure applications, and integrate security into the software development lifecycle. <https://www.owasp.org/> <http://www.webappsec.org/>
- Ensure the WHOIS Domain information registered for our web presence does not reveal sensitive personnel information, which may be leveraged for Social Engineering (Individual POC Names), War Dialing (Phone Numbers) and Brute Force Attacks (Email addresses matching actual system usernames).
- Ensure your Domain Name Service (DNS) servers have been properly secured to prevent attacks, as recommended in the CIS BIND DNS Benchmark.
- Implemented a Network Intrusion Detection System to monitor attacks against the web server.

Rationale:

N/A

Audit:

N/A

Remediation:

N/A

References:

1. Open Web Application Security Project - <https://www.OWASP.org>
2. Web Application Security Consortium - <http://www.webappsec.org/>

1.1.2 Do Not Install a Multi-use System (Not Scored)

Profile Applicability:

- Level 1

Description:

Default server configurations often expose a wide variety of services unnecessarily increasing the risk to the system. Just because a server can perform many services doesn't mean it is wise to do so. The number of services and daemons executing on the Apache Web server should be limited to those necessary, with the Web server being the only primary function of the server.

Rationale:

Maintaining a server for a single purpose increases the security of your application and system. The more services which are exposed to an attacker, the more potential vectors an attacker has to exploit the system and therefore the higher the risk for the server. A Web server should function as only a web server and if possible should not be mixed with other primary functions such as mail, DNS, database or middleware.

Audit:

Leverage the package or services manager for your OS to list enabled services and review with documented business needs of the server. On Red Hat systems, the following will produce the list of current services enabled:

```
chkconfig --list | grep ':on'
```

Remediation:

Leverage the package or services manager for your OS to uninstall or disable unneeded services. On Red Hat systems, the following will disable a given service:

```
chkconfig <servicename> off
```

1.1.3 Installing Apache (Not Scored)

Profile Applicability:

- Level 1

Description:

The CIS Apache Benchmark recommends using the Apache binary provided by your vendor for most situations in order to reduce the effort and increase the effectiveness of maintenance and security patches. However to keep the benchmark as generic and applicable to all Unix/Linux platforms as possible, a default source build has been used for this benchmark.

Important Note: There is a major difference between source builds and most vendor packages that is very important to highlight. The default source build of Apache is fairly conservative and minimalist in the modules included and therefore starts off in a fairly strong security state, while most vendor binaries are typically very well loaded with most of the functionality that one may be looking for. ***Therefore it is important that you don't assume the default value shown in the benchmark will match default values in your installation.***

You should always test any new installation in your environment before putting it into production. Also keep in mind you can install and run a new version alongside the old one by using a different Apache prefix and a different IP address or port number in the `Listen` directive.

Rationale:

The benefits of using the vendor supplied binaries include:

- Ease of installation as it will just work, straight out of the box.
- It is customized for your OS environment.
- It will be tested and have gone through QA procedures.
- Everything you need is likely to be included, probably including some third party modules. For example, many OS vendors ship Apache with `mod_ssl` and OpenSSL, PHP, `mod_perl`, and `ModSecurity`.
- Your vendor will tell you about security issues so you have to look in fewer places.
- Updates to fix security issues will be easy to apply. The vendor will have already verified the problem, checked the signature on the Apache download, worked out the impact and so on.
- You may be able to get the updates automatically, reducing the window of risk.

Audit:

N/A

Remediation:

Installation depends on the operating system platform. For a source build, consult the Apache 2.4 documentation on compiling and installing <http://httpd.apache.org/docs/2.4/install.html> for a Red Hat Enterprise Linux 5 or 6, the following yum command could be used.

```
# yum install httpd
```

References:

1. Apache Compiling and Installation <http://httpd.apache.org/docs/2.4/install.html>

1.2 Minimize Apache Modules

It's crucial to have a minimal and compact Apache installation based on documented business requirements. This section covers specific modules that should be reviewed and disabled if not required for business purposes. However it's very important that the review and analysis of which modules are required for business purposes not be limited to the modules explicitly listed.

1.2.1 Enable only necessary Authentication and Authorization Modules (Not Scored)

Profile Applicability:

- Level 1

Description:

The Apache 2.4 modules for authentication and authorization are grouped and named to provide both granularity, and a consistent naming convention to simplify configuration. The `authn_*` modules provide authentication, while the `authz_*` modules provide authorization. Apache provides two types of authentication - basic and digest. Review the Apache Authentication and Authorization how-to documentation <http://httpd.apache.org/docs/2.4/howto/auth.html> and enable only the modules that are required.

Rationale:

Authentication and authorization are the front doors to the protected information in your web site. Most installations only need a small subset of the modules available. By minimizing the enabled modules to those that are actually used, we reduce the number of "doors" and have therefore reduce the attack surface of the web site. Likewise, having fewer modules means less software that could have vulnerabilities.

Audit:

1. Use the `httpd -M` option as root to check which `auth*` modules are loaded.

```
# httpd -M | egrep 'auth._'
```

2. Also use the `httpd -M` option as root to check for any LDAP modules which don't follow the same naming convention.

```
# httpd -M | egrep 'ldap'
```

The above commands should generate a list of modules installed to `stdout`.

Remediation:

Consult Apache module documentation for descriptions of each module in order to determine the necessary modules for the specific installation.

<http://httpd.apache.org/docs/2.4/mod/> The unnecessary static compiled modules are disabled through compile time configuration options as documented in <http://httpd.apache.org/docs/2.4/programs/configure.html>. The dynamically loaded modules are disabled by commenting out or removing the `LoadModule` directive from the Apache configuration files (typically `httpd.conf`). Some modules may be separate packages, and may be removed.

Default Value:

The following modules are loaded by a default source build:

```
authn_file_module (shared)
authn_core_module (shared)
authz_host_module (shared)
authz_groupfile_module (shared)
authz_user_module (shared)
authz_core_module (shared)
```

References:

1. Apache AAA how-to <http://httpd.apache.org/docs/2.4/howto/auth.html>
2. Apache Module Documentation <http://httpd.apache.org/docs/2.4/mod/>
3. Apache Source Configuration <http://httpd.apache.org/docs/2.4/programs/configure.html>

1.2.2 Enable the Log Config Module (Scored)

Profile Applicability:

- Level 1

Description:

The `log_config` module provides for flexible logging of client requests, and provides for the configuration of the information in each log.

Rationale:

Logging is critical for monitoring usage and potential abuse of your web server. This module is required to configure web server logging using the `log_format` directive.

Audit:

Perform the following to determine if the `log_config` has been loaded:

1. Use the `httpd -M` option as `root` to check that the module is loaded.

```
# httpd -M | grep log_config
```

Note: If the module is correctly enabled, the output will include the module name and whether it is loaded statically or as a shared module

Remediation:

Perform either one of the following:

- For source builds with static modules, run the Apache `./configure` script without including the `--disable-log-config` script options.

```
$ cd $DOWNLOAD_HTTPD
$ ./configure
```

- For dynamically loaded modules, add or modify the `LoadModule` directive so that it is present in the apache configuration as below and not commented out :

```
LoadModule log_config_module modules/mod_log_config.so
```

Default Value:

The `log_config` module is loaded by default.

References:

1. Mod Log Config http://httpd.apache.org/docs/2.4/mod/mod_log_config.html

1.2.3 Disable WebDAV Modules (Scored)

Profile Applicability:

- Level 1

Description:

The Apache `mod_dav` and `mod_dav_fs` modules support WebDAV ('Web-based Distributed Authoring and Versioning') functionality for Apache. WebDAV is an extension to the HTTP protocol which allows clients to create, move, and delete files and resources on the web server.

Rationale:

Disabling WebDAV modules will improve the security posture of the web server by reducing the amount of potentially vulnerable code paths exposed to the network and reducing potential for unauthorized access to files via misconfigured WebDAV access controls.

Audit:

Perform the following to determine if the WebDAV modules are enabled.

1. Run the `httpd` server with the `-M` option to list enabled modules:

```
# httpd -M | grep 'dav_[[:print:]]+module'
```

Note: If the WebDAV modules are correctly disabled, there will be no output when executing the above command.

Remediation:

Perform either one of the following to disable WebDAV module:

1. For source builds with static modules run the Apache `./configure` script without including the `mod_dav`, and `mod_dav_fs` in the `--enable-modules=configure` script options.

```
$ cd $DOWNLOAD_HTTPD
$ ./configure
```

2. For dynamically loaded modules comment out or remove the `LoadModule` directive for `mod_dav`, and `mod_dav_fs` modules the from the `httpd.conf` file.

```
##LoadModule dav_module modules/mod_dav.so  
##LoadModule dav_fs_module modules/mod_dav_fs.so
```

Default Value:

The WebDav modules are not enabled with a default source build.

References:

1. http://httpd.apache.org/docs/2.4/mod/mod_dav.html

1.2.4 Disable Status Module (Scored)

Profile Applicability:

- Level 1

Description:

The Apache `mod_status` module provides current server performance statistics.

Rationale:

When `mod_status` is loaded into the server, its handler capability is available in all configuration files, including per-directory files (e.g., `.htaccess`). The `mod_status` module may provide an adversary with information that can be used to refine exploits that depend on measuring server load.

Audit:

Perform the following to determine if the Status module is enabled.

1. Run the `httpd` server with the `-M` option to list enabled modules:

```
# httpd -M | egrep 'status_module'
```

Note: If the modules are correctly disabled, there will be no output when executing the above command.

Remediation:

Perform either one of the following to disable the `mod_status` module:

1. For source builds with static modules, run the Apache `./configure` script with the `--disable-status` `configure` script options.

```
$ cd $DOWNLOAD_HTTPD
$ ./configure --disable-status
```

2. For dynamically loaded modules, comment out or remove the `LoadModule` directive for the `mod_status` module from the `httpd.conf` file.

```
##LoadModule status_module modules/mod_status.so
```

Default Value:

The `mod_status` module IS enabled with a default source build.

References:

1. http://httpd.apache.org/docs/2.4/mod/mod_status.html

1.2.5 Disable Autoindex Module (Scored)

Profile Applicability:

- Level 1

Description:

The Apache `autoindex` module automatically generates web page listing the contents of directories on the server, typically used so that an `index.html` does not have to be generated.

Rationale:

Automated directory listings should not be enabled as it will also reveal information helpful to an attacker such as naming conventions and directory paths. Directory listings may also reveal files that were not intended to be revealed.

Audit:

Perform the following to determine if the module is enabled.

1. Run the `httpd` server with the `-M` option to list enabled modules:

```
# httpd -M | grep autoindex_module
```

Note: If the module is correctly disabled, there will be no output when executing the above command.

Remediation:

Perform either one of the following to disable the `mod_autoindex` module:

1. For source builds with static modules, run the Apache `./configure` script with the `-disable-autoindex` configure script options

```
$ cd $DOWNLOAD_HTTPD
$ ./configure --disable-autoindex
```

2. For dynamically loaded modules, comment out or remove the `LoadModule` directive for `mod_autoindex` from the `httpd.conf` file.

```
## LoadModule autoindex_module modules/mod_autoindex.so
```

Default Value:

The `mod_autoindex` module IS enabled with a default source build.

References:

1. http://httpd.apache.org/docs/2.4/mod/mod_autoindex.html

1.2.6 Disable Proxy Modules (Scored)

Profile Applicability:

- Level 1

Description:

The Apache proxy modules allow the server to act as a proxy (either forward or reverse proxy) of HTTP and other protocols with additional proxy modules loaded. If the Apache installation is not intended to proxy requests to or from another network then the proxy module should not be loaded.

Rationale:

Proxy servers can act as an important security control when properly configured, however a secure proxy server is not within the scope of this benchmark. A web server should be primarily a web server or a proxy server but not both, for the same reasons that other multi-use servers are not recommended. Scanning for web servers that will also proxy requests is a very common attack, as proxy servers are useful for anonymizing attacks on other servers, or possibly proxying requests into an otherwise protected network.

Audit:

Perform the following to determine if the modules are enabled.

1. Run the `httpd` server with the `-M` option to list enabled modules:

```
# httpd -M | grep proxy_
```

Note: If the modules are correctly disabled, there will be no output when executing the above command.

Remediation:

Perform either one of the following to disable the proxy module:

1. For source builds with static modules, run the Apache `./configure` script without including the `mod_proxy` in the `--enable-modules=configure` script options.

```
$ cd $DOWNLOAD_HTTPD
$ ./configure
```

2. For dynamically loaded modules, comment out or remove the `LoadModule` directive for `mod_proxy` module and all other proxy modules from the `httpd.conf` file.

```
##LoadModule proxy_module modules/mod_proxy.so
##LoadModule proxy_connect_module modules/mod_proxy_connect.so
##LoadModule proxy_ftp_module modules/mod_proxy_ftp.so
##LoadModule proxy_http_module modules/mod_proxy_http.so
##LoadModule proxy_fcgi_module modules/mod_proxy_fcgi.so
##LoadModule proxy_scgi_module modules/mod_proxy_scgi.so
##LoadModule proxy_ajp_module modules/mod_proxy_ajp.so
##LoadModule proxy_balancer_module modules/mod_proxy_balancer.so
##LoadModule proxy_express_module modules/mod_proxy_express.so
##LoadModule proxy_wstunnel_module modules/mod_proxy_wstunnel.so
##LoadModule proxy_fdpass_module modules/mod_proxy_fdpass.so
```

Default Value:

The `mod_proxy` module and other proxy modules are NOT enabled with a default source build.

References:

1. http://httpd.apache.org/docs/2.4/mod/mod_proxy.html

1.2.7 Disable User Directories Modules (Scored)

Profile Applicability:

- Level 1

Description:

The `UserDir` directive must be disabled so that user home directories are not accessed via the web site with a tilde (~) preceding the username. The directive also sets the path name of the directory that will be accessed. For example:

- <http://example.com/~ralph/> might access a `public_html` sub-directory of `ralph` user's home directory.
- The directive `UserDir . /` might map `~/root` to the root directory (`/`).

Rationale:

The user directories should not be globally enabled since it allows anonymous access to anything users may want to share with other users on the network. Also consider that every time a new account is created on the system, there is potentially new content available via the web site.

Audit:

Perform the following to determine if the modules are enabled.

1. Run the `httpd` server with the `-M` option to list enabled modules:

```
# httpd -M | grep userdir_
```

Note: If the modules are correctly disabled, there will be no output when executing the above command.

Remediation:

Perform either one of the following to disable the user directories module:

1. For source builds with static modules, run the Apache `./configure` script with the `-disable-userdir` `configure` script options.

```
$ cd $DOWNLOAD_HTTPD
$ ./configure --disable-userdir
```

2. For dynamically loaded modules, comment out or remove the `LoadModule` directive for `mod_userdir` module from the `httpd.conf` file.

```
##LoadModule userdir_module modules/mod_userdir.so
```

Default Value:

The `mod_userdir` module is not enabled with a default source build.

References:

1. http://httpd.apache.org/docs/2.4/mod/mod_userdir.html

1.2.8 Disable Info Module (Scored)

Profile Applicability:

- Level 1

Description:

The Apache `mod_info` module provides information on the server configuration via access to a `/server-info` URL location.

Rationale:

While having server configuration information available as a web page may be convenient it's recommended that this module NOT be enabled:

- Once `mod_info` is loaded into the server, its handler capability is available in per-directory `.htaccess` files and can leak sensitive information from the configuration directives of other Apache modules such as system paths, usernames/passwords, database names, etc.

Audit:

Perform the following to determine if the Info module is enabled.

1. Run the `httpd` server with the `-M` option to list enabled modules:

```
# httpd -M | egrep 'info_module'
```

Note: If the module is correctly disabled, there will be no output when executing the above command.

Remediation:

Perform either one of the following to disable the `mod_info` module:

1. For source builds with static modules, run the Apache `./configure` script without including the `mod_info` in the `--enable-modules=` `configure` script options.

```
$ cd $DOWNLOAD_HTTPD
$ ./configure
```

2. For dynamically loaded modules, comment out or remove the `LoadModule` directive for the `mod_info` module from the `httpd.conf` file.

```
##LoadModule info_module modules/mod_info.so
```


Default Value:

The `mod_info` module is not enabled with a default source build.

References:

1. http://httpd.apache.org/docs/2.4/mod/mod_info.html

1.3 Principles, Permissions, and Ownership

This section provides recommendations for configuring identities (users and groups) that Apache leverages, permissions on Apache-related filesystem resources, and ownership of Apache-related filesystem resources.

1.3.1 Run the Apache Web Server as a non-root user (Scored)

Profile Applicability:

- Level 1

Description:

Although Apache is typically started with `root` privileges in order to listen on port 80 and 443, it can and should run as another non-root user in order to perform the web services. The Apache `User` and `Group` directives are used to designate the user and group that the Apache worker processes will assume.

Rationale:

One of the best ways to reduce your exposure to attack when running a web server is to create a unique, unprivileged user and group for the server application. The "nobody" or "daemon" user and group that comes default on Unix variants should NOT be used to run the web server, since the account is commonly used for other separate daemon services. Instead, an account used only by the apache software so as to not give unnecessary access to other services. Also the identifier used for the apache user should be a unique system account. System user accounts UID numbers have lower values which are reserved for the special system accounts not used by regular users, such as discussed in User Accounts section of the CIS Red Hat benchmark. Typically system accounts numbers ranges from 1-999, or 1-499 and are defined in the `/etc/login.defs` file.

As an even more secure alternative, if the Apache web server can be run on high unprivileged ports, then it is not necessary to start Apache as `root`, and all of the Apache processes may be run as the Apache specific user as described below.

Audit:

Ensure the `apache` account is unique and has been created with a UID less than the minimum normal user account with the `apache` group and configured in the `httpd.conf` file.

1. Ensure the User and Group directives are present in the Apache configuration and not commented out:

```
# grep -i '^User' $APACHE_PREFIX/conf/httpd.conf
User apache
# grep -i '^Group' $APACHE_PREFIX/conf/httpd.conf
Group apache
```

1. Ensure the apache account UID is correct:

```
# grep '^UID_MIN' /etc/login.defs
# id apache
```

The uid must be less than the `UID_MIN` value in `/etc/login.defs`, and group of apache similar to the following entries:

```
UID_MIN          1000
uid=48(apache) gid=48(apache) groups=48(apache)
```

1. While the web server is running, check the user id for the `httpd` processes. The user name should match the configuration file.

```
# ps axu | grep httpd | grep -v '^root'
```

Remediation:

Perform the following:

1. If the `apacheuser` and group do not already exist, create the account and group as a unique system account:

```
# groupadd -r apache
# useradd apache -r -g apache -d /var/www -s /sbin/nologin
```

2. Configure the Apache user and group in the Apache configuration file `httpd.conf`:

```
User apache
Group apache
```

Default Value:

The default Apache User and Group is configured as `daemon`.

1.3.2 Give the Apache User Account an Invalid Shell (Scored)

Profile Applicability:

- Level 1

Description:

The `apache` account must not be used as a regular login account, and should be assigned an invalid or `nologin` shell to ensure that the account cannot be used to login.

Rationale:

Service accounts such as the `apache` account represent a risk if they can be used to get a login shell to the system.

Audit:

Check the `apache` login shell in the `/etc/passwd` file:

```
# grep apache /etc/passwd
```

The `apache` account shell must be `/sbin/nologin` or `/dev/null` similar to the following:
`/etc/passwd:apache:x:48:48:Apache:/var/www:/sbin/nologin`

Remediation:

Change the `apache` account to use the `nologin` shell or an invalid shell such as `/dev/null`:

```
# chsh -s /sbin/nologin apache
```

Default Value:

The default Apache user account is `daemon`. The `daemon` account may have a valid login shell or a shell of `/sbin/nologin` depending on the operating system distribution version.

1.3.3 Lock the Apache User Account (Scored)

Profile Applicability:

- Level 1

Description:

The user account under which Apache runs should not have a valid password, but should be locked.

Rationale:

As a defense-in-depth measure the Apache user account should be locked to prevent logins, and to prevent a user from `su`-ing to `apache` using the password. In general there shouldn't be a need for anyone to have to `su` as `apache`, and when there is a need, then `sudo` should be used instead, which would not require the `apache` account password.

Audit:

Ensure the `apache` account is locked using the following:

```
# passwd -S apache
```

The results will be similar to the following:

```
apache LK 2010-01-28 0 99999 7 -1 (Password locked.)  
- or -
```

```
apache L 07/02/2012 -1 -1 -1 -1
```

Remediation:

Use the `passwd` command to lock the `apache` account:

```
# passwd -l apache
```

Default Value:

The default user is `daemon` and the account is typically locked.

1.3.4 Set Ownership on Apache Directories and Files (Scored)

Profile Applicability:

- Level 1

Description:

The Apache directories and files should be owned by `root`. This applies to all of the Apache software directories and files installed.

Rationale:

Restricting ownership of the Apache files and directories will reduce the probability of unauthorized modifications to those resources.

Audit:

1. Identify files in the Apache directory that are not owned by `root`:

```
# find $APACHE_PREFIX \! -user root -ls
```

Remediation:

Perform the following:

- Set ownership on the `$APACHE_PREFIX` directories such as `/usr/local/apache2`:

```
$ chown -R root $APACHE_PREFIX
```

Default Value:

Default ownership and group is a mixture of the `user:group` that built the software and `root:root`.

1.3.5 Set Group Id on Apache Directories and Files (Scored)

Profile Applicability:

- Level 1

Description:

The Apache directories and files should be set to have a group Id of `root`, (or a root equivalent) group. This applies to all of the Apache software directories and files installed. The only expected exception is that the Apache web document root (`$APACHE_PREFIX/htdocs`) is likely to need a designated group to allow web content to be updated (such as `webupdate`) through a change management process.

Rationale:

Securing Apache files and directories will reduce the probability of unauthorized modifications to those resources.

Audit:

1. Identify files in the Apache directories other than `htdocs` with a group other than `root`:

```
# find $APACHE_PREFIX -path $APACHE_PREFIX/htdocs -prune -o \! -group root -ls
```

Remediation:

Perform the following:

- Set ownership on the `$APACHE_PREFIX` directories such as `/usr/local/apache2`:

```
$ chgrp -R root $APACHE_PREFIX
```

Default Value:

Default ownership and group is a mixture of the `user:group` that built the software and `root:root`.

1.3.6 Restrict Other Write Access on Apache Directories and Files (Scored)

Profile Applicability:

- Level 1

Description:

Permissions on Apache directories should generally be `rwxr-xr-x` (755) and file permissions should be similar except not executable if executable is not appropriate. This applies to all of the Apache software directories and files installed with the possible exception of the web document root `$APACHE_PREFIX/htdocs`. The directories and files in the web document root may have a designated group with write access to allow web content to be updated. In summary, the minimum recommendation is to not allow write access by `other`.

Rationale:

None of the Apache files and directories, including the Web document root must allow other write access. Other write access is likely to be very useful for unauthorized modification of web content, configuration files or software for malicious attacks.

Audit:

Identify files or directories in the Apache directory with other write access, excluding symbolic links:

```
# find -L $APACHE_PREFIX \! -type l -perm /o=w -ls
```

Remediation:

Perform the following to remove other write access on the `$APACHE_PREFIX` directories.

```
# chmod -R o-w $APACHE_PREFIX
```


1.3.7 Secure Core Dump Directory (Scored)

Profile Applicability:

- Level 1

Description:

The `CoreDumpDirectory` directive is used to specify the directory Apache attempts to switch to before creating the core dump. Core dumps will be disabled if the directory is not writable by the Apache user. Also, core dumps will be disabled if the server is started as `root` and switches to a non-root user, as is typical. It is recommended that the `CoreDumpDirectory` directive be set to a directory that is owned by the `root` user, owned by the group the Apache HTTPD process executes as, and be inaccessible to other users.

Rationale:

Core dumps are snapshots of memory and may contain sensitive information that should not be accessible by other accounts on the system.

Audit:

Verify that either the `CoreDumpDirectory` directive is not enabled in any of the Apache configuration files or that the configured directory meets the following requirements:

1. `CoreDumpDirectory` is not within the Apache web document root (`$APACHE_PREFIX/htdocs`)
2. Must be owned by root and have a group ownership of the Apache group (as defined via the `Group` directive)
3. Must have no read-write-search access permission for other users. (e.g. `o=rwx`)

Remediation:

Either remove the `CoreDumpDirectory` directive from the Apache configuration files or ensure that the configured directory meets the following requirements.

1. `CoreDumpDirectory` is not to be within the Apache web document root (`$APACHE_PREFIX/htdocs`)
2. Must be owned by root and have a group ownership of the Apache group (as defined via the `Group` directive)

```
# chown root:apache /var/log/httpd
```

3. Must have no read-write-search access permission for other users.

```
# chmod o-rwx /var/log/httpd
```

Default Value:

The default core dump directory is the `ServerRoot` directory.

References:

1. http://httpd.apache.org/docs/2.4/mod/mpm_common.html#coredumpdirectory

1.3.8 Secure the Lock File (Scored)

Profile Applicability:

- Level 1

Description:

The `Mutex` directive sets the locking mechanism used to serialize access to resources. It may be used to specify that a lock file is to be used as a mutex mechanism and may provide the path to the lock file to be used with the `fcntl(2)` or `flock(2)` system calls. Most Linux systems will default to using semaphores instead, so the directive may not apply. However in the event a lock file is used, it is important for the lock file to be in a local directory that is not writable by other users.

Rationale:

If the lock file to be used as a mutex is placed in a writable directory, other accounts could create a denial of service attack and prevent the server from starting by creating a lock file with the same name.

Audit:

Verify the configuration does NOT include a `Mutex` directive with the mechanism of `fcntl`, `flock` or `file`.

If one of the file locking mechanisms is configured, then find the directory in which the lock file would be created. The default value is the `ServerRoot/logs` directory.

1. Verify that the lock file directory is not a directory within the Apache `DocumentRoot`
2. Verify that the ownership and group of the directory is `root:root` (or the user under which Apache initially starts up if not root).
3. Verify the permissions on the directory are only writable by root (or the startup user if not root),
4. Check that the lock file directory is on a locally mounted hard drive rather than an NFS mounted file system

Remediation:

Find the directory path in which the lock file would be created. The default value is the `ServerRoot/logs` directory.

1. Modify the directory if the path is a directory within the Apache `DocumentRoot`
2. Change the ownership and group to be `root:root`, if not already.

3. Change the permissions so that the directory is only writable by root, or the user under which Apache initially starts up (default is root),
4. Check that the lock file directory is on a locally mounted hard drive rather than an NFS mounted file system.

Default Value:

The default mechanism for the `Mutex` directive is platform specific and may be determined by running `httpd -v`. The default path is the `ServerRoot/logs` directory.

References:

1. <http://httpd.apache.org/docs/2.4/mod/core.html#mutex>

1.3.9 Secure the Pid File (Scored)

Profile Applicability:

- Level 1

Description:

The `PidFile` directive sets the file path to the process ID file to which the server records the process id of the server, which is useful for sending a signal to the server process or for checking on the health of the process.

Rationale:

If the `PidFile` is placed in a writable directory, other accounts could create a denial of service attack and prevent the server from starting by creating a pid file with the same name.

Audit:

1. Find the directory in which the `PidFile` would be created. The default value is the `ServerRoot/logs` directory.
2. Verify that the process ID file directory is not a directory within the Apache `DocumentRoot`
3. Verify that the ownership and group of the directory is `root:root` (or the user under which Apache initially starts up if not root).
4. Verify the permissions on the directory are only writable by root (or the startup user if not root).

Remediation:

1. Find the directory in which the `PidFile` would be created. The default value is the `ServerRoot/logs` directory.
2. Modify the directory if the `PidFile` is in a directory within the Apache `DocumentRoot`
3. Change the ownership and group to be `root:root`, if not already.
4. Change the permissions so that the directory is only writable by root, or the user under which Apache initially starts up (default is root).

Default Value:

The default process ID file is `logs/httpd.pid`.

References:

1. http://httpd.apache.org/docs/2.4/mod/mpm_common.html#pidfile

1.3.10 Secure the ScoreBoard File (Scored)

Profile Applicability:

- Level 1

Description:

The `ScoreBoardFile` directive sets a file path which the server will use for inter-process communication (IPC) among the Apache processes. On most Linux platforms shared memory will be used instead of a file in the file system, so this directive is not generally needed and does not need to be specified. However, if the directive is specified, then Apache will use the configured file for the inter-process communication. Therefore if it is specified, it needs to be located in a secure directory.

Rationale:

If the `ScoreBoardFile` is placed in a writable directory, other accounts could create a denial of service attack and prevent the server from starting by creating a file with the same name, and or users could monitor and disrupt the communication between the processes by reading and writing to the file.

Audit:

1. Check to see if the `ScoreBoardFile` is specified in any of the Apache configuration files. If it is not present, the configuration is compliant.
2. Find the directory in which the `ScoreBoardFile` would be created. The default value is the `ServerRoot/logs` directory.
3. Verify that the scoreboard file directory is not a directory within the Apache `DocumentRoot`.
4. Verify that the ownership and group of the directory is `root:root` (or the user under which Apache initially starts up if not `root`).
5. Change the permissions so that the directory is only writable by `root` (or the startup user if not `root`).
6. Check that the scoreboard file directory is on a locally mounted hard drive rather than an NFS mounted file system.

Remediation:

1. Check to see if the `ScoreBoardFile` is specified in any of the Apache configuration files. If it is not present no changes are required.
2. If the directive is present, find the directory in which the `ScoreBoardFile` would be created. The default value is the `ServerRoot/logs` directory.

3. Modify the directory if the `ScoreBoardFile` is in a directory within the Apache `DocumentRoot`
4. Change the ownership and group to be `root:root`, if not already.
5. Change the permissions so that the directory is only writable by root, or the user under which apache initially starts up (default is root),
6. Check that the scoreboard file directory is on a locally mounted hard drive rather than an NFS mounted file system.

Default Value:

The default scoreboard file is `logs/apache_status`.

References:

1. http://httpd.apache.org/docs/2.4/mod/mpm_common.html#scoreboardfile

1.3.11 Restrict Group Write Access for the Apache Directories and Files (Scored)

Profile Applicability:

- Level 1

Description:

Group permissions on Apache directories should generally be `r-x` and file permissions should be similar except not executable if executable is not appropriate. This applies to all of the Apache software directories and files installed with the possible exception of the web document root `$DOCROOT` defined by Apache `DocumentRoot` and defaults to `$APACHE_PREFIX/htdocs`. The directories and files in the web document root may have a designated web development group with write access to allow web content to be updated.

Rationale:

Restricting write permissions on the Apache files and directories can help mitigate attacks that modify web content to provide unauthorized access, or to attack web clients.

Audit:

Identify files or directories in the Apache directory with group write access, excluding symbolic links:

```
# find -L $APACHE_PREFIX \! -type l -perm /g=w -ls
```

Remediation:

Perform the following to remove group write access on the `$APACHE_PREFIX` directories.

```
# chmod -R g-w $APACHE_PREFIX
```


1.3.12 Restrict Group Write Access for the Document Root Directories and Files (Scored)

Profile Applicability:

- Level 1

Description:

Group permissions on Apache Document Root directories \$DOCROOT may need to be writable by an authorized group such as development, support, or a production content management tool. However it is important that the Apache group used to run the server does not have write access to any directories or files in the document root.

Rationale:

Preventing Apache from writing to the web document root helps mitigate risk associated with web application vulnerabilities associated with file uploads or command execution. Typically, if an application hosted by Apache needs to write to directory, it is best practice to have that directory live outside the web root.

Audit:

Identify files or directories in the Apache Document Root directory with Apache group write access.

```
## Define $GRP to be the Apache group configured
# GRP=$(grep '^Group' $APACHE_PREFIX/conf/httpd.conf | cut -d' ' -f2)
find -L $DOCROOT -group $GRP -perm /g=w -ls
```

Remediation:

Perform the following to remove group write access on the \$DOCROOT directories and files with the apache group.

```
# find -L $DOCROOT -group $GRP -perm /g=w -print | xargs chmod g-w
```

1.4 Apache Access Control

Recommendations in this section pertain to configurable access control mechanisms that are available in Apache HTTP server.

1.4.1 Deny Access to OS Root Directory (Scored)

Profile Applicability:

- Level 1

Description:

The Apache `Directory` directive allows for directory specific configuration of access controls and many other features and options. One important usage is to create a default deny policy that does not allow access to Operating system directories and files, except for those specifically allowed. This is done, by denying access to the OS root directory.

Rationale:

One aspect of Apache, which is occasionally misunderstood, is the feature of default access. That is, unless you take steps to change it, if the server can find its way to a file through normal URL mapping rules, it can and will serve it to clients. Having a default deny is a predominate security principal, and then helps prevent the unintended access, and we do that in this case by denying access to the OS root directory using either of two methods but not both:

1. Using the Apache `Deny` directive along with an `Order` directive.
2. Using the Apache `Require` directive.

Either method is effective. The `Order/Deny/Allow` combination are now deprecated; they provide three passes where all the directives are processed in the specified order. In contrast, the `Require` directive works on the first match similar to firewall rules. The `Require` directive is the default for Apache 2.4 and is demonstrated in the remediation procedure as it may be less likely to be misunderstood.

Audit:

Perform the following to determine if the recommended state is implemented:

1. Search the Apache configuration files (`httpd.conf` and any included configuration files) to find a root `<Directory>` element.
2. Ensure that either one of the following two methods are configured:

Using the deprecated Order/Deny/Allow method:

1.
 1. Ensure there is a single `Order` directive with the value of `deny, allow`
 2. Ensure there is a `Deny` directive, and with the value of `from all`.
 3. Ensure there are no `Allow` or `Require` directives in the root `<Directory>` element.

Using the Require method:

1.
 1. Ensure there is a single `Require` directive with the value of `all denied`
 2. Ensure there are no `Allow` or `Deny` directives in the root `<Directory>` element.

The following may be useful in extracting root directory elements from the Apache configuration for auditing.

```
$ perl -ne 'print if /^ *<Directory *\\//i .. /<\\//Directory/i'
$APACHE_PREFIX/conf/httpd.conf
```

Remediation:

Perform the following to implement the recommended state:

1. Search the Apache configuration files (`httpd.conf` and any included configuration files) to find a root `<Directory>` element.
2. Add a single `Require` directive and set the value to `all denied`
3. Remove any `Deny` and `Allow` directives from the root `<Directory>` element.

```
<Directory>
. . .
    Require all denied
. . .
</Directory>
```

Default Value:

The following is the default root directory configuration:

```
<Directory>
. . .
    Require all denied
. . .
</Directory>
```

References:

1. <http://httpd.apache.org/docs/2.4/mod/core.html#directory>
2. http://httpd.apache.org/docs/2.4/mod/mod_authz_host.html

1.4.2 Allow Appropriate Access to Web Content (Not Scored)

Profile Applicability:

- Level 1

Description:

In order to serve Web content, either the Apache `Allow` directive or the `Require` directive will need to be used to allow for appropriate access to directories, locations and virtual hosts that contain web content.

Rationale:

Either the `Allow` or `Require` directives may be used within a directory, a location or other context to allow appropriate access. Access may be allowed to all, or to specific networks, or hosts, or users as appropriate. The `Allow/Deny/Order` directives are deprecated and should be replaced by the `Require` directive. It is also recommended that either the `Allow` directive or the `Require` directive be used, but not both in the same context.

Audit:

Perform the following to determine if the recommended state is implemented:

1. Search the Apache configuration files (`httpd.conf` and any included configuration files) to find all `<Directory>` elements.
2. Ensure that either one of the following two methods are configured:

Use the deprecated Order/Deny/Allow method:

1.
 1. Ensure there is a single `Order` directive with the value of `Deny,Allow` for each.
 2. Ensure the `Allow` and `Deny` directives, have values that are appropriate for the purposes of the directory.

Use the Require method:

1.
 1. Ensure that the `Order/Deny/Allow` directives are NOT used for the directory.
 2. Ensure the `Require` directives have values that are appropriate for the purposes of the directory.

The following command may be useful to extract <Directory> and <Location> elements and Allow directives from the Apache configuration files.

```
# perl -ne 'print if /^ *<Directory */i .. //<\Directory/i'
$APACHE_PREFIX/conf/httpd.conf $APACHE_PREFIX/conf.d/*.conf
# perl -ne 'print if /^ *<Location */i .. //<\Location/i'
$APACHE_PREFIX/conf/httpd.conf $APACHE_PREFIX/conf.d/*.conf
# grep -i -C 6 -i 'Allow[[:space:]]from' $APACHE_PREFIX/conf/httpd.conf
$APACHE_PREFIX/conf.d/*.conf
```

Remediation:

Perform the following to implement the recommended state:

1. Search the Apache configuration files (httpd.conf and any included configuration files) to find all <Directory> and <Location> elements. There should be one for the document root and any special purpose directories or locations. There are likely to be other access control directives in other contexts, such as virtual hosts or special elements like <Proxy>.
2. Include the appropriate Require directives, with values that are appropriate for the purposes of the directory.

The configurations below are just a few possible examples.

```
<Directory "/var/www/html/">
    Require ip 192.169.
</Directory>
```

```
<Directory "/var/www/html/">
    Require all granted
</Directory>
```

```
<Location /usage>
    Require local
</Location>
<Location /portal>
    Require valid-user
</Location>
```

Default Value:

The following is the default Web root directory configuration:

```
<Directory "/usr/local/apache2/htdocs">
    . . .
    Require all granted
```

```
. . .  
</Directory>
```

References:

1. <http://httpd.apache.org/docs/2.4/mod/core.html#directory>
2. http://httpd.apache.org/docs/2.4/mod/mod_authz_host.html
3. http://httpd.apache.org/docs/2.4/mod/mod_authz_core.html
4. http://httpd.apache.org/docs/2.4/mod/mod_access_compat.html

1.4.3 Restrict Override for the OS Root Directory (Scored)

Profile Applicability:

- Level 1

Description:

The Apache `AllowOverride` directive and the new `AllowOverrideList` directive allow for `.htaccess` files to be used to override much of the configuration, including authentication, handling of document types, auto generated indexes, access control, and options. When the server finds an `.htaccess` file (as specified by `AccessFileName`) it needs to know which directives declared in that file can override earlier access information. When this directive is set to `None`, then `.htaccess` files are completely ignored. In this case, the server will not even attempt to read `.htaccess` files in the filesystem. When this directive is set to `All`, then any directive which has the `.htaccess` Context is allowed in the `.htaccess` files.

Rationale:

While the functionality of `htaccess` files is sometimes convenient, usage decentralizes the access controls and increases the risk of configurations being changed or viewed inappropriately by an unintended or rogue `.htaccess` file. Consider also that some of the more common vulnerabilities in web servers and web applications allow the web files to be viewed or to be modified, then it is wise to keep the configuration out of the web server from being placed in `.htaccess` files.

Audit:

Perform the following to determine if the recommended state is implemented:

1. Search the Apache configuration files (`httpd.conf` and any included configuration files) to find a root element.
2. Ensure there is a single `AllowOverride` directive with the value of `None`.
3. Ensure there are no `AllowOverrideList` directives present.

The following may be useful for extracting root directory elements from the Apache configuration for auditing.

```
$ perl -ne 'print if /^ *<Directory *\\//i .. /<\\//Directory/i'
$APACHE_PREFIX/conf/httpd.conf
```

Remediation:

Perform the following to implement the recommended state:

1. Search the Apache configuration files (`httpd.conf` and any included configuration files) to find a root `<Directory>` element.
2. Remove any `AllowOverrideList` directives found.
3. Add a single `AllowOverride` directive if there is none.
4. Set the value for `AllowOverride` to `None`.

```
<Directory />
    . . .
    AllowOverride None
    . . .
</Directory>
```

Default Value:

The following is the default root directory configuration:

```
<Directory />
    . . .
    AllowOverride None
    . . .
</Directory>
```

References:

1. <http://httpd.apache.org/docs/2.4/mod/core.html#allowoverride>
2. <http://httpd.apache.org/docs/2.4/mod/core.html#allowoverridelist>

1.4.4 Restrict Override for All Directories (Scored)

Profile Applicability:

- Level 1

Description:

The Apache `AllowOverride` directive and the new `AllowOverrideList` directive allow for `.htaccess` files to be used to override much of the configuration, including authentication, handling of document types, auto generated indexes, access control, and options. When the server finds an `.htaccess` file (as specified by `AccessFileName`) it needs to know which directives declared in that file can override earlier access information. When this directive is set to `None`, then `.htaccess` files are completely ignored. In this case, the server will not even attempt to read `.htaccess` files in the filesystem. When this directive is set to `All`, then any directive which has the `.htaccess` context is allowed in `.htaccess` files.

Rationale:

`.htaccess` files decentralizes access control and increases the risk of server configuration being changed inappropriately.

Audit:

Perform the following to determine if the recommended state is implemented:

1. Search the Apache configuration files (`httpd.conf` and any included configuration files) to find any `AllowOverride` directives.
2. Ensure there the value for `AllowOverride` is `None`.

```
grep -i AllowOverride $APACHE_PREFIX/conf/httpd.conf
```

3. Ensure there are no `AllowOverrideList` directives present.

Remediation:

Perform the following to implement the recommended state:

1. Search the Apache configuration files (`httpd.conf` and any included configuration files) to find `AllowOverride` directives.
2. Set the value for all `AllowOverride` directives to `None`.

```
. . .  
AllowOverride None  
. . .
```

3. Remove any `AllowOverrideList` directives found.

References:

1. <http://httpd.apache.org/docs/2.4/mod/core.html#allowoverride>
2. <http://httpd.apache.org/docs/2.4/mod/core.html#allowoverridelist>

1.5 Minimize Features, Content and Options

Recommendations in this section intend to reduce the effective attack surface of Apache HTTP server.

1.5.1 Restrict Options for the OS Root Directory (Scored)

Profile Applicability:

- Level 1

Description:

The Apache `Options` directive allows for specific configuration of options, including execution of CGI, following symbolic links, server side includes, and content negotiation.

Rationale:

The `Options` directive for the root OS level is used to create a default minimal options policy that allows only the minimal options at the root directory level. Then for specific web sites or portions of the web site, options may be enabled as needed and appropriate. No options should be enabled and the value for the `Options` directive should be `None`.

Audit:

Perform the following to determine if the recommended state is implemented:

1. Search the Apache configuration files (`httpd.conf` and any included configuration files) to find a root `<Directory>` element.
2. Ensure there is a single `Options` directive with the value of `None`.

The following may be useful for extracting root directory elements from the Apache configuration for auditing.

```
perl -ne 'print if /^ *<Directory */i .. /\</Directory/i'
$APACHE_PREFIX/conf/httpd.conf
```

Remediation:

Perform the following to implement the recommended state:

1. Search the Apache configuration files (`httpd.conf` and any included configuration files) to find a root `<Directory>` element.
2. Add a single `Options` directive if there is none.
3. Set the value for `Options` to `None`.

```
<Directory>
    . . .
    Options None
    . . .
</Directory>
```

Default Value:

The default value for the root directory's `Options` directive is `Indexes FollowSymLinks`.

References:

1. <http://httpd.apache.org/docs/2.4/mod/core.html#options>

1.5.2 Restrict Options for the Web Root Directory (Scored)

Profile Applicability:

- Level 1

Description:

The Apache `Options` directive allows for specific configuration of options, including:

- Execution of CGI
- Following symbolic links
- Server side includes
- Content negotiation

Rationale:

The `Options` directive at the web root or document root level also needs to be restricted to the minimal options required. A setting of `None` is highly recommended, however it is recognized that this level content negotiation may be needed if multiple languages are supported. No other options should be enabled.

Audit:

Perform the following to determine if the recommended state is implemented:

1. Search the Apache configuration files (`httpd.conf` and any included configuration files) to find the document root `<Directory>` elements.
2. Ensure there is a single `Options` directive with the value of `None` or `Multiviews`.

The following may be useful in extracting directory elements from the Apache configuration for auditing.

```
perl -ne 'print if /^ *<Directory */i .. /\</Directory/i'
$APACHE_PREFIX/conf/httpd.conf
```

Remediation:

Perform the following to implement the recommended state:

1. Search the Apache configuration files (`httpd.conf` and any included configuration files) to find the document root `<Directory>` element.
2. Add or modify any existing `Options` directive to have a value of `None` or `Multiviews`, if multiviews are needed.

```
<Directory "/usr/local/apache2/htdocs">  
    . . .  
    Options None  
    . . .  
</Directory>
```

Default Value:

The default value for the web root directory's Option directive is FollowSymLinks.

References:

1. <http://httpd.apache.org/docs/2.4/mod/core.html#options>

1.5.3 Minimize Options for Other Directories (Scored)

Profile Applicability:

- Level 1

Description:

The Apache `Options` directive allows for specific configuration of options, including execution of CGI, following symbolic links, server side includes, and content negotiation.

Rationale:

Likewise the options for other directories and hosts needs to be restricted to the minimal options required. A setting of `None` is recommended, however it is recognized that other options may be needed in some cases:

- `Multiviews` - Is appropriate if content negotiation is required, such as when multiple language are supported.
- `ExecCGI` - Is only appropriate for special directories dedicated to executable content such as a `cgi-bin/` directory. That way you will know what is executed on the server. It is possible to enable CGI script execution based on file extension or permission settings, however this makes script control and management almost impossible as developers may install scripts without your knowledge. This may become a factor in a hosting environment.
- `FollowSymLinks` & `SymLinksIfOwnerMatch` - The following of symbolic links is not recommended and should be disabled if possible. The usage of symbolic links opens up additional risk for possible attacks that may use inappropriate symbolic links to access content outside of the document root of the web server. Also consider that it could be combined with a vulnerability that allowed an attacker or insider to create an inappropriate link. The option `SymLinksIfOwnerMatch` is much safer in that the ownership must match in order for the link to be used, however keep in mind there is additional overhead created by requiring Apache to check the ownership.
- `Includes` & `IncludesNOEXEC` - The `IncludesNOEXEC` option should only be needed when server side includes are required. The full `Includes` option should not be used as it also allows execution of arbitrary shell commands. See Apache Mod Include for details http://httpd.apache.org/docs/2.4/mod/mod_include.html
- `Indexes` - The `Indexes` option causes automatic generation of indexes, if the default index page is missing, and should be disabled unless required.

Audit:

Perform the following to determine if the recommended state is implemented:

1. Search the Apache configuration files (`httpd.conf` and any included configuration files) to find the all `Directory` elements.
2. Ensure that the `Options` directives do not enable `Includes`.

The following may be useful for extracting `Directory` elements from the Apache configuration for auditing.

```
perl -ne 'print if /^ *<Directory */i .. /\</Directory/i'
$APACHE_PREFIX/conf/httpd.conf
```

or

```
grep -i -A 12 '<Directory[[:space:]]' $APACHE_PREFIX/conf/httpd.conf
```

Remediation:

Perform the following to implement the recommended state:

1. Search the Apache configuration files (`httpd.conf` and any included configuration files) to find all `<Directory>` elements.
2. Add or modify any existing `Options` directive to NOT have a value of `Includes`. Other options may be set if necessary and appropriate as described above.

References:

1. <http://httpd.apache.org/docs/2.4/mod/core.html#options>

1.5.4 Remove Default HTML Content (Scored)

Profile Applicability:

- Level 1

Description:

Apache installations have default content that is not needed or appropriate for production use. The primary function for these sample content is to provide a default web site, provide user manuals or to demonstrate special features of the web server. All content that is not needed should be removed.

Rationale:

Historically these sample content and features have been remotely exploited and can provide different levels of access to the server. In the Microsoft arena, Code Red exploited a problem with the index service provided by the Internet Information Service. Usually these routines are not written for production use and consequently little thought was given to security in their development.

Audit:

Perform the following to determine if the recommended state is implemented:

1. Verify the document root directory and the configuration files do not provide for default index.html or welcome page,
2. Ensure the Apache User Manual content is not installed by checking the configuration files for manual location directives.
3. Verify the Apache configuration files do not have the Server Status handler configured.
4. Verify that the Server Information handler is not configured.
5. Verify that any other handler configurations such as `perl-status` is not enabled.

Remediation:

Review all pre-installed content and remove content which is not required. In particular look for the unnecessary content which may be found in the document root directory, a configuration directory such as `conf/extra` directory, or as a Unix/Linux package

1. Remove the default index.html or welcome page, if it is a separate package or comment out the configuration if it is part of main Apache `httpd` package such as it is on Red Hat Linux. Removing a file such as the `welcome.conf` shown below is not recommended as it may get replaced if the package is updated.

```
#
# This configuration file enables the default "Welcome"
# page if there is no default index page present for
# the root URL. To disable the Welcome page, comment
# out all the lines below.
#
##<LocationMatch "^/+$">
##     Options -Indexes
##     ErrorDocument 403 /error/noindex.html
##</LocationMatch>
```

2. Remove the Apache user manual content or comment out configurations referencing the manual

```
# yum erase httpd-manual
```

3. Remove or comment out any Server Status handler configuration.

```
#
# Allow server status reports generated by mod_status,
# with the URL of http://servername/server-status
# Change the ".example.com" to match your domain to enable.
#
##<Location /server-status>
##     SetHandler server-status
##     Order deny,allow
##     Deny from all
##     Allow from .example.com
##</Location>
```

4. Remove or comment out any Server Information handler configuration.

```
#
# Allow remote server configuration reports, with the URL of
# http://servername/server-info (requires that mod_info.c be loaded).
# Change the ".example.com" to match your domain to enable.
#
##<Location /server-info>
##     SetHandler server-info
##     Order deny,allow
##     Deny from all
##     Allow from .example.com
##</Location>
```

5. Remove or comment out any other handler configuration such as perl-status.

```
# This will allow remote server configuration reports, with the URL of
# http://servername/perl-status
# Change the ".example.com" to match your domain to enable.
#
##<Location /perl-status>
##     SetHandler perl-script
##     PerlResponseHandler Apache2::Status
##     Order deny,allow
##     Deny from all
##     Allow from .example.com
##</Location>
```

Default Value:

The default source build provides extra content available in the `/usr/local/apache2/conf/extra/` directory, but the configuration of most of the extra content is commented out by default. **In particular, the include of `conf/extra/proxy-html.conf` is not commented out in the `httpd.conf`.**

```
# Server-pool management (MPM specific)
#Include conf/extra/httpd-mpm.conf
# Multi-language error messages
#Include conf/extra/httpd-multilang-errordoc.conf
# Fancy directory listings
#Include conf/extra/httpd-autoindex.conf
# Language settings
#Include conf/extra/httpd-languages.conf
# User home directories
#Include conf/extra/httpd-userdir.conf
# Real-time info on requests and configuration
#Include conf/extra/httpd-info.conf
# Virtual hosts
#Include conf/extra/httpd-vhosts.conf
# Local access to the Apache HTTP Server Manual
#Include conf/extra/httpd-manual.conf
# Distributed authoring and versioning (WebDAV)
#Include conf/extra/httpd-dav.conf
# Various default settings
#Include conf/extra/httpd-default.conf
# Configure mod_proxy_html to understand HTML4/XHTML1
<IfModule proxy_html_module>
Include conf/extra/proxy-html.conf
</IfModule>
# Secure (SSL/TLS) connections
#Include conf/extra/httpd-ssl.conf
```

Also the only other default content is a minimal barebones `index.html` in the document root which contains.

```
<html><body><h1>It works!</h1></body></html>
```

1.5.5 Remove Default CGI Content printenv (Scored)

Profile Applicability:

- Level 1

Description:

Most Web Servers, including Apache installations have default CGI content which is not needed or appropriate for production use. The primary function for these sample programs is to demonstrate the capabilities of the web server. One common default CGI content for Apache installations is the script `printenv`. This script will print back to the requester all of the CGI environment variables which includes many server configuration details and system paths.

Rationale:

CGI programs have a long history of security bugs and problems associated with improperly accepting user-input. Since these programs are often targets of attackers, we need to make sure that there are no unnecessary CGI programs that could potentially be used for malicious purposes. Usually these programs are not written for production use and consequently little thought was given to security in their development. The `printenv` script in particular will disclose inappropriate information about the web server including directory paths and detailed version and configuration information.

Audit:

Perform the following to determine if the recommended state is implemented:

1. Locate cgi-bin files and directories enabled in the Apache configuration via `Script`, `ScriptAlias` or `ScriptAliasMatch` or `ScriptInterpreterSource` directives.
2. Ensure the `printenv` CGI is not installed in any configured cgi-bin directory.

Remediation:

Perform the following to implement the recommended state:

1. Locate cgi-bin files and directories enabled in the Apache configuration via `Script`, `ScriptAlias`, `ScriptAliasMatch`, or `ScriptInterpreterSource` directives.
2. Remove the `printenv` default CGI in cgi-bin directory if it is installed.

```
# rm $APACHE_PREFIX/cgi-bin/printenv
```

Default Value:

The default source installation includes the `printenv` script. However, this script is not executable by default.

1.5.6 Remove Default CGI Content test-cgi (Scored)

Profile Applicability:

- Level 1

Description:

Most Web Servers, including Apache installations have default CGI content which is not needed or appropriate for production use. The primary function for these sample programs is to demonstrate the capabilities of the web server. A common default CGI content for Apache installations is the script `test-cgi`. This script will print back to the requester CGI environment variables which includes many server configuration details.

Rationale:

CGI programs have a long history of security bugs and problems associated with improperly accepting user-input. Since these programs are often targets of attackers, we need to make sure that there are no unnecessary CGI programs that could potentially be used for malicious purposes. Usually these programs are not written for production use and consequently little thought was given to security in their development. The `test-cgi` script in particular will disclose inappropriate information about the web server including directory paths and detailed version and configuration information.

Audit:

Perform the following to determine if the recommended state is implemented:

1. Locate `cgi-bin` files and directories enabled in the Apache configuration via `Script`, `ScriptAlias` or `ScriptAliasMatch` other `ScriptInterpreterSource` directives.
2. Ensure the `test-cgi` script is not installed in any configured `cgi-bin` directory.

Remediation:

Perform the following to implement the recommended state:

1. Locate `cgi-bin` files and directories enabled in the Apache configuration via `Script`, `ScriptAlias`, `ScriptAliasMatch`, or `ScriptInterpreterSource` directives.
2. Remove the `test-cgi` default CGI in `cgi-bin` directory if it is installed.

```
# rm $APACHE_PREFIX/cgi-bin/test-cgi
```

Default Value:

The default source installation includes the test-cge script. However, this script is not executable by default.

1.5.7 Limit HTTP Request Methods (Scored)

Profile Applicability:

- Level 1

Description:

Use the Apache `<LimitExcept>` directive to restrict unnecessary HTTP request methods of the web server to only accept and process the `GET`, `HEAD`, `POST` and `OPTIONS` HTTP request methods.

Rationale:

The HTTP 1.1 protocol supports several request methods which are rarely used and potentially high risk. For example, methods such as `PUT` and `DELETE` are rarely used and should be disabled in keeping with the primary security principal of minimize features and options. Also since the usage of these methods is typically to modify resources on the web server, they should be explicitly disallowed. For normal web server operation, you will typically need to allow only the `GET`, `HEAD` and `POST` request methods. This will allow for downloading of web pages and submitting information to web forms. The `OPTIONS` request method will also be allowed as it used to request which HTTP request methods are allowed. Unfortunately the Apache `<LimitExcept>` directive does not deny the `TRACE` request method. The `TRACE` request method will be disallowed in another benchmark recommendation with the `TraceEnable` directive.

Audit:

Perform the following to determine if the recommended state is implemented:

1. Locate the Apache configuration files and included configuration files.
2. Search for all `<Directory>` directives other than the on the OS root directory.
3. Ensure that either one of the following two methods are configured:

Using the deprecated `Order/Deny/Allow` method:

1.
 1. Ensure that group contains a single `Order` directive within the `<Directory>` directive with a value of `deny, allow`
 2. Verify the `<LimitExcept>` directive does not include any HTTP methods other than `GET`, `POST`, and `OPTIONS`. (It may contain fewer methods.)

Using the `Require` method:

1.
 1. Ensure there is a single `Require` directive with the value of `all denied`
 2. Ensure there are no `Allow` or `Deny` directives in the root element.

Remediation:

Perform the following to implement the recommended state:

1. Locate the Apache configuration files and included configuration files.
2. Search for the directive on the document root directory such as:

```
<Directory "/usr/local/apache2/htdocs">
    . . .
</Directory>
```

3. Add a directive as shown below within the group of document root directives.

```
# Limit HTTP methods to standard methods. Note: Does not limit TRACE
<LimitExcept GET POST OPTIONS>
    Require all denied
</LimitExcept>
```

4. Search for other directives in the Apache configuration files other than the OS root directory, and add the same directives to each. It is very important to understand that the directives are based on the OS file system hierarchy as accessed by Apache and not the hierarchy of the locations within web site URLs.

```
<Directory "/usr/local/apache2/cgi-bin">
    . . .
    # Limit HTTP methods
    <LimitExcept GET POST OPTIONS>
        Require all denied
    </LimitExcept>
</Directory>
```

Default Value:

No Limits on HTTP methods.

References:

1. <http://httpd.apache.org/docs/2.4/mod/core.html#limitexcept>
2. <http://www.ietf.org/rfc/rfc2616.txt>

1.5.8 Disable HTTP TRACE Method (Scored)

Profile Applicability:

- Level 1

Description:

Use the Apache `TraceEnable` directive to disable the HTTP `TRACE` request method.

Rationale:

The HTTP 1.1 protocol requires support for the `TRACE` request method which reflects the request back as a response and was intended for diagnostics purposes. The `TRACE` method is not needed and is easily subjected to abuse and should be disabled.

Audit:

Perform the following to determine if the recommended state is implemented:

1. Locate the Apache configuration files and included configuration files.
2. Verify there is a single `TraceEnable` directive configured with a value of `off`.

Remediation:

Perform the following to implement the recommended state:

1. Locate the main Apache configuration file such as `httpd.conf`.
2. Add a `TraceEnable` directive to the server level configuration with a value of `off`.
Server level configuration is the top level configuration, not nested within any other directives like `<Directory>` or `<Location>`.

Default Value:

The `TRACE` method is enabled.

References:

1. <http://httpd.apache.org/docs/2.4/mod/core.html#traceenable>
2. <http://www.ietf.org/rfc/rfc2616.txt>

1.5.9 Restrict HTTP Protocol Versions (Scored)

Profile Applicability:

- Level 1

Description:

The Apache modules `mod_rewrite` or `mod_security` can be used to disallow old and invalid HTTP protocols versions. The HTTP version 1.1 RFC is dated June 1999, and has been supported by Apache since version 1.2. It should no longer be necessary to allow ancient versions of HTTP such as 1.0 and prior.

Rationale:

Many malicious automated programs, vulnerability scanners and fingerprinting tools will send abnormal HTTP protocol versions to see how the web server responds. These requests are usually part of the attacker's enumeration process and therefore it is important that we respond by denying these requests.

Audit:

Perform the following to determine if the recommended state is implemented:

1. Locate the Apache configuration files and included configuration files.
2. Verify there is a rewrite condition within the global server context that disallows requests that do not include the HTTP/1.1 header as shown below .

```
RewriteEngine On
RewriteCond %{THE_REQUEST} !HTTP/1\..1$
RewriteRule .* - [F]
```

3. Verify the following directives are included in each section so that the main server settings will be inherited.

```
RewriteEngine On
RewriteOptions Inherit
```

Remediation:

Perform the following to implement the recommended state:

1. Load the `mod_rewrite` module for Apache by doing either one of the following:
 1. Build Apache with `mod_rewrite` statically loaded during the build, by adding the `--enable-rewrite` option to the `./configure` script.

```
./configure --enable-rewrite
```

2. Or dynamically loading the module with the `LoadModule` directive in the `httpd.conf` configuration file.

```
LoadModule rewrite_module modules/mod_rewrite.so
```

2. Locate the main Apache configuration file such as `httpd.conf` and add the following rewrite condition to match HTTP/1.1 and the rewrite rule to the global server level configuration to disallow other protocol versions.

```
RewriteEngine On  
RewriteCond %{THE_REQUEST} !HTTP/1\.$  
RewriteRule .* - [F]
```

3. By default, `mod_rewrite` configuration settings from the main server context are not inherited by virtual hosts. Therefore it is also necessary to add the following directives in each section to inherit the main server settings.

```
RewriteEngine On  
RewriteOptions Inherit
```

Default Value:

The default value for the `RewriteEngine` directive is `off`.

References:

1. http://httpd.apache.org/docs/2.4/mod/mod_rewrite.html

1.5.10 Restrict Access to .ht* files (Scored)

Profile Applicability:

- Level 1

Description:

Restrict access to any files beginning with .ht using the `FilesMatch` directive.

Rationale:

The default name for access filename which allows files in web directories to override the Apache configuration is `.htaccess`. The usage of access files should not be allowed, but as a defense in depth a `FilesMatch` directive is recommended to prevent web clients from viewing those files in case they are created. Also a common name for web password and group files is `.htpasswd` and `.htgroup`. Neither of these files should be placed in the document root, but in the event they are, the `FilesMatch` directive can be used to prevent them from being viewed by web clients.

Audit:

Perform the following steps to determine if the recommended state is implemented:

1. Verify that a `FilesMatch` directive similar to the one below is present in the apache configuration and not commented out, The deprecated `Deny from All` directive may be used instead of the `Require` directive.

```
<FilesMatch "^\.ht">  
    Require all denied  
</FilesMatch>
```

Remediation:

Perform the following to implement the recommended state:

1. Add or modify the following lines in the apache configuration at the server configuration level.

```
<FilesMatch "^\.ht">  
    Require all denied  
</FilesMatch>
```

Default Value:

.ht* files are not accessible.

References:

1. <http://httpd.apache.org/docs/2.4/mod/core.html#filesmatch>

1.5.11 Restrict File Extensions (Scored)

Profile Applicability:

- Level 2

Description:

Restrict access to inappropriate file extensions that are not expected to be a legitimate part of web sites using the `FilesMatch` directive.

Rationale:

There are many files that are often left within the web server document root that could provide an attacker with sensitive information. Most often these files are mistakenly left behind after installation, trouble-shooting, or backing up files before editing. Regardless of the reason for their creation, these files can still be served by Apache even when there is no hyperlink pointing to them. The web administrators should use the `FilesMatch` directive to restrict access to only those file extensions that are appropriate for the web server. Rather than create a list of potentially inappropriate file extensions such as `.bak`, `.config`, `.old`, etc, it is recommended instead that a white list of the appropriate and expected file extensions for the web server be created, reviewed and restricted with a `FilesMatch` directive.

Audit:

Perform the following steps to determine if the recommended state is implemented:

1. Verify that the `FilesMatch` directive that denies access to all files is present as shown in step 3 of the remediation.
2. Verify that there is another `FilesMatch` directive similar to the one in step 4 of the remediation, with an expression that matches the approved file extensions.

Remediation:

Perform the following to implement the recommended state:

1. Compile a list of existing file extension on the web server. The following `find/awk` command may be useful, but is likely to need some customization according to the appropriate webroot directories for your web server. Please note that the `find` command skips over any files without a dot (.) in the file name, as these are not expected to be appropriate web content.

```
find */htdocs -type f -name '*..*' | awk -F. '{print $NF }' | sort -u
```


2. Review the list of existing file extensions, for appropriate content for the web server, remove those that are inappropriate and add any additional file extensions expected to be added to the web server in the near future.
3. Add the `FilesMatch` directive below which denies access to all files by default.

```
# Block all files by default, unless specifically allowed.
<FilesMatch "^.*$">
    Require all denied
</FilesMatch>
```

4. Add another a `FilesMatch` directive that allows access to those file extensions specifically allowed from the review process in step 2. An example `FilesMatch` directive is below. The file extensions in the regular expression should match your approved list, and not necessarily the expression below.

```
# Allow files with specifically approved file extensions
# Such as (css, htm; html; js; pdf; txt; xml; xsl; ...),
# images (gif; ico; jpeg; jpg; png; ...), multimedia
<FilesMatch "^.*\.(css|html?|js|pdf|txt|xml|xsl|gif|ico|jpe?g|png)$">
    Require all granted
</FilesMatch>
```

Default Value:

There are no restrictions on file extensions in the default configuration.

References:

1. <http://httpd.apache.org/docs/2.4/mod/core.html#filesmatch>

1.5.12 Deny IP Address Based Requests (Scored)

Profile Applicability:

- Level 2

Description:

The Apache module `mod_rewrite` can be used to disallow access for requests that use an IP address instead of a host name for the URL. Most normal access to the website from browsers and automated software will use a host name, and will therefore include the host name in the HTTP HOST header.

Rationale:

A common malware propagation and automated network scanning technique is to use IP addresses rather than host names for web requests, since it's much simpler to automate. By denying IP based web requests, these automated techniques will be denied access to the website. Of course malicious web scanning techniques continue to evolve, and many are now using hostnames, however denying access to the IP based requests is still a worthwhile defense.

Audit:

Perform the following steps to determine if the recommended state is implemented:

1. Locate the Apache configuration files and included configuration files.
2. Verify there is a rewrite condition within the global server context that disallows IP based requests by requiring a HTTP HOST header similar to the example shown below.

```
RewriteCond %{HTTP_HOST} !^www\.example\.com [NC]
RewriteCond %{REQUEST_URI} !^/error [NC]
RewriteRule ^.(*) - [L,F]
```

Remediation:

Perform the following to implement the recommended state:

1. Load the `mod_rewrite` module for Apache by doing either one of the following:
 1. Build Apache with `mod_rewrite` statically loaded during the build, by adding the `--enable-rewrite` option to the `./configure` script.

```
./configure --enable-rewrite
```

2. Or dynamically loading the module with the `LoadModule` directive in the `httpd.conf` configuration file.

```
LoadModule rewrite_module modules/mod_rewrite.so
```

2. Add the `RewriteEngine` directive to the configuration within the global server context with the value of `on` so that the rewrite engine is enabled.

```
RewriteEngine On
```

3. Locate the Apache configuration file such as `httpd.conf` and add the following rewrite condition to match the expected host name of the top server level configuration.

```
RewriteCond %{HTTP_HOST} !^www\.example\.com [NC]  
RewriteCond %{REQUEST_URI} !^/error [NC]  
RewriteRule ^.(.*) - [L,F]
```

Default Value:

```
RewriteEngine off
```

References:

1. http://httpd.apache.org/docs/2.4/mod/mod_rewrite.html

1.5.13 Restrict Listen Directive (Scored)

Profile Applicability:

- Level 2

Description:

The Apache `Listen` directive specifies the IP addresses and port numbers the Apache web server will listen for requests. Rather than be unrestricted to listen on all IP addresses available to the system, the specific IP address or addresses intended should be explicitly specified. Specifically a `Listen` directive with no IP address specified, or with an IP address of zeros should not be used.

Rationale:

Having multiple interfaces on web servers is fairly common, and without explicit `Listen` directives, the web server is likely to be listening on an inappropriate IP address / interface that was not intended for the web server. Single homed system with a single IP addressed are also required to have an explicit IP address in the `Listen` directive, in case additional interfaces are added to the system at a later date.

Audit:

Perform the following steps to determine if the recommended state is implemented:

1. Verify that no `Listen` directives are in the Apache configuration file with no IP address specified, or with an IP address of all zero's.

Remediation:

Perform the following to implement the recommended state:

1. Find any `Listen` directives in the Apache configuration file with no IP address specified, or with an IP address of all zeros similar to the examples below. Keep in mind there may be both IPv4 and IPv6 addresses on the system.

```
Listen 80
Listen 0.0.0.0:80
Listen [::ffff:0.0.0.0]:80
```

2. Modify the `Listen` directives in the Apache configuration file to have explicit IP addresses according to the intended usage. Multiple `Listen` directives may be specified for each IP address & Port.

```
Listen 10.1.2.3:80
Listen 192.168.4.5:80
Listen [2001:db8::a00:20ff:fea7:ccea]:80
```

Default Value:

Listen 80

References:

1. http://httpd.apache.org/docs/2.4/mod/mpm_common.html#listen

1.5.14 Restrict Browser Frame Options (Scored)

Profile Applicability:

- Level 2

Description:

The Header directive allows server HTTP response headers to be added, replaced or merged. We will use the directive to add an server HTTP response header to tell browsers to restrict all of the web pages from being framed by other web sites.

Rationale:

Using iframes and regular web frames to embed malicious content along with expected web content has been a favored attack vector for attacking web clients for a long time. This can happen when the attacker lures the victim to a malicious web site, which using frames to include the expected content from the legitimate site. The attack can also be performed via XSS (either reflected, DOM or stored XSS) to add the malicious content to the legitimate web site.

To combat this vector, an HTTP Response header, X-Frame-Options, has been introduced that allows a server to specify whether a web page may be loaded in any frame (`DENY`) or those frames that share the pages origin (`SAMEORIGIN`).

Audit:

Perform the following steps to determine if the recommended state is implemented:

1. Ensure a Header directive for X-Frame-Options is present in the Apache configuration and has the condition `always`, an action of `append` and a value of `SAMEORIGIN` or `DENY`, as shown below.:

```
# grep -i X-Frame-Options $APACHE_PREFIX/conf/httpd.conf
Header always append X-Frame-Options SAMEORIGIN
```

Remediation:

Perform the following to implement the recommended state:

1. Add or modify the Header directive for the X-Frames-Options header in the Apache configuration to have the condition `always`, an action of `append` and a value of `SAMEORIGIN` or `DENY`, as shown below.

```
Header always append X-Frame-Options SAMEORIGIN
```

Default Value:

The `X-Frame-Options` HTTP response header is not generated by default.

References:

1. http://httpd.apache.org/docs/2.4/mod/mod_headers.html#header
2. [https://developer.mozilla.org/en/The X-FRAME-OPTIONS response header/](https://developer.mozilla.org/en/The_X-FRAME-OPTIONS_response_header/)
3. <http://blogs.msdn.com/b/ie/archive/2009/01/27/ie8-security-part-vii-clickjacking-defenses.aspx>

1.6 Operations - Logging, Monitoring and Maintenance

Operational procedures of logging, monitoring and maintenance are vital to protecting your web servers as well as the rest of the infrastructure.

1.6.1 Configure the Error Log (Scored)

Profile Applicability:

- Level 1

Description:

The `LogLevel` directive is used to configure the severity level for the error logs. While the `ErrorLog` directive configures the error log file name. The log level values are the standard syslog levels of `emerg`, `alert`, `crit`, `error`, `warn`, `notice`, `info` and `debug`. The recommended level is `notice` for most modules, so that all errors from the `emerg` level through `notice` level will be logged. The recommend setting for the `core` module is `info` so that any "not found" requests will be included in the error logs.

Rationale:

The server error logs are invaluable because they can also be used to spot any potential problems before they become serious. Most importantly, they can be used to watch for anomalous behavior such as a lot of "not found" or "unauthorized" errors may be an indication that an attack is pending or has occurred. Starting with Apache 2.4 the error log does not include the "not found" errors except at the `info` logging level. Therefore, it is important that the log level be set to `info` for the `core` module. The "not found" requests need to be included in the error log for both forensics investigation and host intrusion detection purposes. Monitoring the access logs may not be practical for many web servers with high volume traffic.

Audit:

Perform the following steps to determine if the recommended state is implemented:

1. Verify the `LogLevel` in the Apache server configuration has a value of `info` or lower for the `core` module and `notice` or lower for other modules. Note that it is also compliant to have a value of `info` or `debug` if there is a need for a more verbose log and the storage and monitoring processes are capable of handling the extra load. The recommended value is `notice core:info`.
2. Verify the `ErrorLog` directive is configured to an appropriate log file or syslog facility.

3. Verify there is a similar `ErrorLog` directive for each virtual host configured if the virtual host will have different people responsible for the web site.

Remediation:

Perform the following to implement the recommended state:

1. Add or modify the `LogLevel` in the Apache configuration to have a value of `info` or lower for the core module, and `notice` or lower for all other modules. Note that it is compliant to have a value of `info` or `debug` if there is a need for a more verbose log and the storage and monitoring processes are capable of handling the extra load. The recommended value is `notice core:info`.

```
LogLevel notice core:info
```

2. Add an `ErrorLog` directive if not already configured. The file path may be relative or absolute, or the logs may be configured to be sent to a syslog server.

```
ErrorLog "logs/error_log"
```

3. Add a similar `ErrorLog` directive for each virtual host configured if the virtual host will have different people responsible for the web site. Each responsible individual or organization needs access to their own web logs, and needs the skills/training/tools for monitoring the logs.

Default Value:

The following is the default configuration:

```
LogLevel warn  
ErrorLog "logs/error_log"
```

References:

1. <http://httpd.apache.org/docs/2.4/logs.html>
2. <http://httpd.apache.org/docs/2.4/mod/core.html#loglevel>
3. <http://httpd.apache.org/docs/2.4/mod/core.html#errorlog>

1.6.2 Configure a Syslog Facility for Error Logging (Scored)

Profile Applicability:

- Level 2

Description:

The `ErrorLog` directive should be configured to send logs to a `syslog` facility so that the logs can be processed and monitored along with the system logs.

Rationale:

It is easy for the web server error logs to be overlooked in the log monitoring process, and yet the application level attacks have become the most common and are extremely important for detecting attacks early, as well as detecting non-malicious problems such as a broken link, or internal errors. By including the Apache error logs with the system logging facility, the application logs are more likely to be included in the established log monitoring process.

Audit:

Perform the following steps to determine if the recommended state is implemented:

1. Verify that the `ErrorLog` in the Apache server configuration has a value of `syslog:facility` where `facility` can be any of the `syslog` facility values such as `local1`.
2. Verify there is a similar `ErrorLog` directive is either configured or inherited for each virtual host.

Remediation:

Perform the following to implement the recommended state:

1. Add an `ErrorLog` directive if not already configured. Any appropriate `syslog` facility may be used in place of `local1`.

```
ErrorLog "syslog:local1"
```

1. Add a similar `ErrorLog` directive for each virtual host if necessary.

Default Value:

The following is the default configuration:

```
ErrorLog "logs/error_log"
```

References:

1. <http://httpd.apache.org/docs/2.4/logs.html>
2. <http://httpd.apache.org/docs/2.4/mod/core.html#loglevel>
3. <http://httpd.apache.org/docs/2.4/mod/core.html#errorlog>

1.6.3 Configure the Access Log (Scored)

Profile Applicability:

- Level 1

Description:

The `LogFormat` directive defines the format and information to be included in the access log entries. The `CustomLog` directive specifies the log file, syslog facility or piped logging utility.

Rationale:

The server access logs are also invaluable for a variety of reasons. They can be used to determine what resources are being used most. Most importantly, they can be used to investigate anomalous behavior that may be an indication that an attack is pending or has occurred. If the server only logs errors, and does not log successful access, then it is very difficult to investigate incidents. You may see that the errors stop, and wonder if the attacker gave up, or was the attack successful.

Audit:

Perform the following steps to determine if the recommended state is implemented:

1. Verify the `LogFormat` directive in the Apache server configuration has the recommended information parameters.
2. Verify the `CustomLog` directive is configured to an appropriate log file, syslog facility, or piped logging utility and uses the combined format.
3. Verify there is a similar `CustomLog` directives for each virtual host configured if the virtual host will have different people responsible for the web site.

Remediation:

Perform the following to implement the recommended state:

1. Add or modify the `LogFormat` directives in the Apache configuration to use the standard and recommended `combined` format show as shown below.

```
LogFormat "%h %l %u %t \"%r\" %>s %b \"%{Referer}i\" \"%{User-agent}i\""
combined
```

2. Add or modify the `CustomLog` directives in the Apache configuration to use the combined format with an appropriate log file, syslog facility or piped logging utility.

```
CustomLog log/access_log combined
```

3. Add a similar `CustomLog` directives for each virtual host configured if the virtual host will have different people responsible for the web site. Each responsible individual or organization needs access to their own web logs, and needs the skills/training/tools for monitor the logs.

The format string tokens provide the following information:

- `%h` = Remote hostname or IP address if `HostnameLookups` is set to `Off`, which is the default.
- `%l` = Remote logname / identity.
- `%u` = Remote user, if the request was authenticated.
- `%t` = Time the request was received,
- `%r` = First line of request.
- `%>s` = Final status.
- `%b` = Size of response in bytes.
- `%{Referer}i` = Variable value for Referer header.
- `%{User-agent}i` = Variable value for User Agent header.

Default Value:

The following are the default log configuration:

```
LogFormat "%h %l %u %t \"%r\" %>s %b \"%{Referer}i\" \"%{User-Agent}i\"" combined
LogFormat "%h %l %u %t \"%r\" %>s %b" common
CustomLog "logs/access_log" common
```

References:

1. http://httpd.apache.org/docs/2.4/mod/mod_log_config.html#customlog
2. http://httpd.apache.org/docs/2.4/mod/mod_log_config.html#formats

1.6.4 Log Storage and Rotation (Scored)

Profile Applicability:

- Level 1

Description:

It is important that there is adequate disk space on the partition that will hold all the log files, and that log rotation is configured to retain at least 3 months or 13 weeks if central logging is not used for storage.

Rationale:

Keep in mind that the generation of logs is under a potential attacker's control. So do not hold any Apache log files on the root partition of the OS. This could result in a denial of service against your web server host by filling up the root partition and causing the system to crash. For this reason it is recommended that the log files should be stored on a dedicated partition. Likewise consider that attackers sometimes put information into your logs which is intended to attack your log collection or log analysis processing software. So it is important that they are not vulnerable. Investigation of incidents often require access to several months or more of logs, which is why it is important to keep at least 3 months available. Two common log rotation utilities include `rotatelogs(8)` which is bundled with Apache, and `logrotate(8)` commonly bundled on Linux distributions are described in the remediation section.

Audit:

Perform the following steps to determine if the recommended state is implemented:

1. Verify the web log rotation configuration matches the Apache configured log files.
2. Verify the rotation period and number of logs to retain is at least 13 weeks or 3 months.
3. For each virtual host configured with its own log files ensure that those log files are also included in a similar log rotation.

Remediation:

To implement the recommended state do either option a) if using the Linux `logrotate` utility or option b) if using a piped logging utility such as the Apache `rotatelogs`:

1. File Logging with Logrotate:

1. Add or modify the web log rotation configuration to match your configured log files in `/etc/logrotate.d/httpd` to be similar to the following.

```
/var/log/httpd/*log {
    missingok
    notifempty
    sharedscripts
    postrotate
        /bin/kill -HUP `cat /var/run/httpd.pid 2>/dev/null` 2> /dev/null ||
    true
    endsript
}
```

2. Modify the rotation period and number of logs to keep so that at least 13 weeks or 3 months of logs are retained. This may be done as the default value for all logs in `/etc/logrotate.conf` or in the web specific log rotation configuration in `/etc/logrotate.d/httpd` to be similar to the following.

```
# rotate log files weekly
weekly
# keep 13 weeks of backlogs
rotate 13
```

3. For each virtual host configured with it's own log files ensure that those log files are also included in a similar log rotation.
2. Piped Logging:
 1. Configure the log rotation interval and log file names to a suitable interval such as daily.

```
CustomLog "|bin/rotatelogs -l /var/logs/logfile.%Y.%m.%d 86400" combined
```

2. Ensure the log file naming and any rotation scripts provide for retaining at least 3 months or 13 weeks of log files.
3. For each virtual host configured with its own log files ensure that those log files are also included in a similar log rotation.

Default Value:

The following is the default httpd log rotation configuration in `/etc/logrotate.d/httpd`:

```
/var/log/httpd/*log {
    missingok
    notifempty
    sharedscripts
    postrotate
        /bin/kill -HUP `cat /var/run/httpd.pid 2>/dev/null` 2> /dev/null || true
    endsript
}
```

The default log retention configured in `/etc/logrotate.conf`:

```
# rotate log files weekly
weekly
# keep 4 weeks worth of backlogs
rotate 4
```


1.6.5 Apply Applicable Patches (Scored)

Profile Applicability:

- Level 1

Description:

Apply available Apache patches within 1 month of availability.

Rationale:

Obviously knowing about newly discovered vulnerabilities is only part of the solution; there needs to be a process in place where patches are tested and installed. These patches fix diverse problems, including security issues. It is recommended to use the Apache packages and updates provide by the your Linux platform vendor rather than building from source when possible, in order to minimize the disruption and the work of keeping the software up-to-date.

Audit:

Perform the following steps to determine if the recommended state is implemented:

1. When Apache was built from source:
 1. Check the Apache web site for latest versions, date of releases and any security patches.
http://httpd.apache.org/security/vulnerabilities_24.html Apache patches are available <http://www.apache.org/dist/httpd/patches/>
 2. If newer versions with security patches more than 1 month old and are not installed, then the installation is not sufficiently up-to-date.
2. When using platform packages
3. Check for vendor supplied updates from the vendor web site.
4. If newer versions with security patches more than 1 month old are not installed, then the installation is not sufficiently up-to-date.

Remediation:

Update to the latest Apache release available according to either of the following:

1. When building from source:
 1. Read release notes and related security patch information
 2. Download latest source and any dependent modules such as `mod_security`.
 3. Build new Apache software according to your build process with the same configuration options.

4. Install and Test the new software according to your organizations testing process.
 5. Move to production according to your organizations deployment process.
2. When using platform packages
 1. Read release notes and related security patch information
 2. Download and install latest available Apache package and any dependent software.
 3. Test the new software according to your organizations testing process.
 4. Move to production according to your organizations deployment process.

References:

1. http://httpd.apache.org/security/vulnerabilities_24.html

1.6.6 Install and Enable ModSecurity (Scored)

Profile Applicability:

- Level 2

Description:

ModSecurity is a open source web application firewall (WAF) for real-time web application monitoring, logging, and access control. It enables but does not include a powerful customizable rule set, which may be used to detect and block common web application attacks. Installation of ModSecurity without a rule set does not provide additional security for the protected web applications. Refer to the benchmark recommendation "*Install and Enable OWASP ModSecurity Core Rule Set*" for details on a recommended rule set.

NOTE: Like other application security/application firewall systems, Mod_Security requires a significant commitment of staff resources for initial tuning of the rules and handling alerts. In some cases, this may require additional time working with application developers/maintainers to modify applications based on analysis of the results of tuning and monitoring logs. After setup, an ongoing commitment of staff is required for monitoring logs and ongoing tuning, especially after upgrades/patches. Without this commitment to tuning and monitoring, installing Mod_Security may NOT be effective and may provide a false sense of security.

Rationale:

Installation of the ModSecurity Apache module enables a customizable web application firewall rule set which may be configured to detect and block common attack patterns as well as block outbound data leakage.

Audit:

Perform the following to determine if the security2_module has been loaded:

1. Use the httpd -M option as root to check that the module is loaded.

```
# httpd -M | grep security2_module
```

Note: If the module is correctly enabled, the output will include the module name and whether it is loaded statically or as a shared module.

Remediation:

1. Install the ModSecurity module if it is not already installed in `modules/mod_security2.so`. It may be installed via OS package installation (such as `apt-get` or `yum`) or built from the source files. See <https://www.modsecurity.org/download.html> for details.
2. Add or modify the `LoadModule` directive if not already present in the Apache configuration as shown below. Typically the `LoadModule` directive is placed in file named `mod_security.conf` which is included in the Apache configuration:

```
LoadModule security2_module modules/mod_security2.so
```

Default Value:

The ModSecurity module is NOT loaded by default.

References:

1. <https://www.modsecurity.org/>

1.6.7 Install and Enable OWASP ModSecurity Core Rule Set (Scored)

Profile Applicability:

- Level 2

Description:

The OWASP ModSecurity Core Rules Set (CRS) is a set of open source web application defensive rules for the ModSecurity web application firewall (WAF). The OWASP ModSecurity CRS provides baseline protections in the following attack/threat categories:

- HTTP Protection - detecting violations of the HTTP protocol and a locally defined usage policy.
- Real-time Blacklist Lookups - utilizes 3rd Party IP Reputation
- HTTP Denial of Service Protections - defense against HTTP Flooding and Slow HTTP DoS Attacks.
- Common Web Attacks Protection - detecting common web application security attack.
- Automation Detection - Detecting bots, crawlers, scanners and other surface malicious activity.
- Integration with AV Scanning for File Uploads - detects malicious files uploaded through the web application.
- Tracking Sensitive Data - Tracks Credit Card usage and blocks leakages.
- Trojan Protection - Detecting access to Trojans horses.
- Identification of Application Defects - alerts on application misconfigurations.
- Error Detection and Hiding - Disguising error messages sent by the server.

NOTE: Like other application security/application firewall systems, Mod_Security requires a significant commitment of staff resources for initial tuning of the rules and handling alerts. In some cases, this may require additional time working with application developers/maintainers to modify applications based on analysis of the results of tuning and monitoring logs. After setup, an ongoing commitment of staff is required for monitoring logs and ongoing tuning, especially after upgrades/patches. Without this commitment to tuning and monitoring, installing Mod_Security may NOT be effective and may provide a false sense of security.

Rationale:

Installing, configuring and enabling of the OWASP ModSecurity Core Rule Set (CRS), provides additional baseline security defense, and provides a good starting point to customize the monitoring and blocking of common web application attacks.

Audit:

As of the 2.2.9 release, the OWASP ModSecurity CRS contains 15 base_rule configuration files, each with rule sets. The CRS also contains 14 optional rule sets, and 17 experimental rule sets. Since it is expected that customization and testing will be necessary to implement the CRS, it is not expected that any site will implement all CRS configuration files / rule sets. Therefore for the purpose of auditing, the OWASP ModSecurity CRS will be considered implemented if 200 or more of the security rules (SecRule) are active in the CRS configuration files.

Perform the following to determine if OWASP ModSecurity CRS is enabled:

- Use the following command to count the security rules in all of the active CRS configuration files.

```
find $APACHE_PREFIX/modsecurity.d/activated_rules/ -name 'modsecurity_crs_*.conf' |  
xargs grep '^SecRule ' | wc -l
```

- If the number of active files is 200 or greater than OWASP ModSecurity CRS is considered active for the purposes of the audit.

Remediation:

Install, configure and test the OWASP ModSecurity Core Rule Set:

1. Download the OWASP ModSecurity CRS from the project page https://www.owasp.org/index.php/Category:OWASP_ModSecurity_Core_Rule_Set_Project
2. Unbundled the archive and follow the instructions in the INSTALL file.
3. The modsecurity_crs_10_setup.conf file is required, and rules in the base_rules directory are intended as a baseline useful for most applications.
4. Test the application for correct functionality after installing the CRS. Check web server error logs and the modsec_audit.log file for blocked requests due to false positives.
5. It is also recommended to test the application response to malicious traffic such as an automated web application scanner to ensure the rules are active. The the web server error log and modsec_audit.log files should show logs of the attacks and the servers response codes.

Default Value:

The OWASP ModSecurity CRS is NOT installed or enabled by default.

References:

1. [https://www.owasp.org/index.php/Category:OWASP ModSecurity Core Rule Set Project](https://www.owasp.org/index.php/Category:OWASP_ModSecurity_Core_Rule_Set_Project)
2. <https://www.modsecurity.org/>

1.7 SSL/TLS Configuration

Recommendations in this section pertain to the configuration of SSL/TLS-related aspects of Apache HTTP server.

1.7.1 Install `mod_ssl` and/or `mod_nss` (Scored)

Profile Applicability:

- Level 1

Description:

Secure Sockets Layer (SSL) was developed by Netscape and turned into an open standard, and was renamed Transport Layer Security (TLS) as part of the process. TLS is important for protecting communication and can provide authentication of the server and even the client. However contrary to vendor claims, implementing SSL does NOT directly make your web server more secure! SSL is used to encrypt traffic and therefore does provide confidentiality of private information and users credentials. Keep in mind, however that just because you have encrypted the data in transit does not mean that the data provided by the client is secure while it is on the server. Also SSL does not protect the web server, as attackers will easily target SSL-Enabled web servers, and the attack will be hidden in the encrypted channel. The `mod_ssl` module is the standard, most used module that implements SSL/TLS for Apache. A newer module found on Red Hat systems can be a compliment or replacement for `mod_ssl`, and provides the same functionality plus additional security services. The `mod_nss` is an Apache module implementation of the Network Security Services (NSS) software from Mozilla, which implements a wide range of cryptographic functions in addition to TLS.

Rationale:

It is best to plan for SSL/TLS implementation from the beginning of any new web server. As most web servers have some need for SSL/TLS due to:

- Non-public information submitted that should be protected as it's transmitted to the web server.
- Non-public information that is downloaded from the web server.
- Users are going to be authenticated to some portion of the web server
- There is a need to authenticate the web server to ensure users that they have reached the real web server, and have not been phished or redirected to a bogus site.

Audit:

Perform the following steps to determine if the recommended state is implemented:

1. Ensure the `mod_ssl` and/or `mod_nss` is loaded in the Apache configuration:

```
# httpd -M | egrep 'ssl_module|nss_module'
```

Results should show either or both of the modules.

Remediation:

Perform either of the following to implement the recommended state:

1. For Apache installations built from the source, use the option `--with-ssl=` to specify the openssl path, and the `--enable-ssl` configure option to add the SSL modules to the build. The `--with-included-apr` configure option may be necessary if there are conflicts with the platform version. If a new version of Openssl is needed it may be downloaded from <http://www.openssl.org/> See the Apache documentation on building from source <http://httpd.apache.org/docs/2.4/install.html> for details.

```
# ./configure --with-included-apr --with-ssl=$OPENSSL_DIR --enable-ssl
```

2. For installations using OS packages, it is typically just a matter of ensuring the `mod_ssl` package is installed. The `mod_nss` package might also be installed. The following yum commands are suitable for Red Hat Linux.

```
# yum install mod_ssl
```

Default Value:

SSL is not enabled by default.

References:

1. http://httpd.apache.org/docs/2.4/mod/mod_ssl.html
2. http://directory.fedoraproject.org/wiki/Mod_nss

1.7.2 Install a Valid Trusted Certificate (Scored)

Profile Applicability:

- Level 1

Description:

The default SSL certificate is self-signed and is not trusted. Install a valid certificate signed by a commonly trusted certificate authority. To be valid, the certificate must be:

- Signed by a trusted certificate authority
- Not be expired, and
- Have a common name that matches the host name of the web server, such as `www.example.com`.

Rationale:

A digital certificate on your server automatically communicates your site's authenticity to visitors' web browsers. If a trusted authority signs your certificate, it confirms for the visitor they are actually communicating with you, and not with a fraudulent site stealing credit card numbers or personal information.

Audit:

Perform either or both of the following steps to determine if the recommended state is implemented:

1. OpenSSL can also be used to validate a certificate as a valid trusted certificate, using a trusted bundle of CA certificate. It is important that the CA bundle of certificates be an already validated and trusted file in order for the test to be valid.

```
$ openssl verify -CAfile /etc/pki/tls/certs/ca-bundle.crt -purpose sslserver  
/etc/pki/tls/certs/example.com.crt  
/etc/pki/tls/certs/example.com.crt: OK
```

A specific error message and code will be reported in addition to the OK if the certificate is not valid, For example:

```
error 10 at 0 depth lookup:certificate has expired  
OK
```

2. Testing can also be done by connecting to a running web server. This may be done with your favorite browser, a command line web client or with `openssl s_client`.

Of course it is important here as well to be sure of the integrity of the trusted certificate authorities used by the web client. Visit the OWASP testing SSL web page for additional suggestions:

https://www.owasp.org/index.php/Testing_for_SSL-TLS_%28OWASP-CM-001%29

Remediation:

Perform the following to implement the recommended state:

1. Decide on the host name to be used for the certificate. It is important to remember that the browser will compare the host name in the URL to the common name in the certificate, so that it is important that all https: URL's match the correct host name. Specifically the host name `www.example.com` is not the same as `example.com` nor the same as `ssl.example.com`.
2. Generate a private key using openssl. Although certificate key lengths of 1024 have been common in the past, a key length of 2048 is now recommended for strong authentication. The key must be kept confidential and will be encrypted with a passphrase by default. Follow the steps below and respond to the prompts for a passphrase. See the Apache or OpenSSL documentation for details:
http://httpd.apache.org/docs/2.4/ssl/ssl_faq.html#realcert
<http://www.openssl.org/docs/HOWTO/certificates.txt>

```
# cd /etc/pki/tls/certs
# umask 077
# openssl genrsa -aes128 2048 > example.com.key
Generating RSA private key, 2048 bit long modulus
...+++
.....+++
e is 65537 (0x10001)
Enter pass phrase:
Verifying - Enter pass phrase:
```

3. Generate the certificate signing request (CSR) to be signed by a certificate authority. It is important that common name exactly make the web host name.

```
# openssl req -utf8 -new -key www.example.com.key -out www.example.com.csr
Enter pass phrase for example.com.key:
You are about to be asked to enter information that will be incorporated
into your certificate request.
What you are about to enter is what is called a Distinguished Name or a DN.
There are quite a few fields but you can leave some blank
For some fields there will be a default value,
If you enter '.', the field will be left blank.
-----
Country Name (2 letter code) [GB]:US
State or Province Name (full name) [Berkshire]:New York
Locality Name (eg, city) [Newbury]:Lima
Organization Name (eg, company) [My Company Ltd]:Durkee Consulting
Organizational Unit Name (eg, section) []:
Common Name (eg, your name or your server's hostname) []:www.example.com
Email Address []:ralph@example.com
Please enter the following 'extra' attributes
to be sent with your certificate request
```

```
A challenge password []:  
An optional company name []:  
# mv www.example.com.key /etc/pki/tls/private/
```

4. Send the certificate signing request (CSR) to a certificate signing authority to be signed, and follow their instructions for submission and validation. The CSR and the final signed certificate are just encoded text, and need to be protected for integrity, but not confidentiality. This certificate will be given out for every SSL connection made.
5. The resulting signed certificate may be named `www.example.com.crt` and placed in `/etc/pki/tls/certs/` as readable by all (mode 0444). Please note that the certificate authority does not need the private key (`example.com.key`) and this file must be carefully protected. With a decrypted copy of the private key, it would be possible to decrypt all conversations with the server.
6. Do not forget the passphrase used to encrypt the private key. It will be required every time the server is started in https mode. If it is necessary to avoid requiring an administrator having to type the passphrase every time the `httpd` service is started, the private key may be stored in clear text. Storing the private key in clear text increases the convenience while increasing the risk of disclosure of the key, but may be appropriate for the sake of being able to restart, if the risks are well managed. Be sure that the key file is only readable by root. To decrypt the private key and store it in clear text file the following `openssl` command may be used. You can tell by the private key headers whether it is encrypted or clear text.

```
# cd /etc/pki/tls/private/  
# umask 077  
# openssl rsa -in www.example.com.key -out www.example.com.key.clear
```

7. Locate the Apache configuration file for `mod_ssl` and add or modify the `SSLCertificateFile` and `SSLCertificateKeyFile` directives to have the correct path for the private key and signed certificate files. If a clear text key is referenced then a passphrase will not be required. You can use the CA's certificate that signed your certificate instead of the CA bundle, to speed up the initial SSL connection as fewer certificates will need to be transmitted.

```
SSLCertificateFile /etc/pki/tls/certs/example.com.crt  
SSLCertificateKeyFile /etc/pki/tls/private/example.com.key  
# Default CA file, can be replaced with your CA's certificate.  
SSLCACertificateFile /etc/pki/tls/certs/ca-bundle.crt
```

8. Lastly, start or restart the `httpd` service and verify correct functioning with your favorite browser.

References:

1. https://www.owasp.org/index.php/Testing_for_SSL-TLS_%28OWASP-CM-001%29
2. http://httpd.apache.org/docs/2.4/ssl/ssl_faq.html#realcert
3. <http://www.openssl.org/docs/HOWTO/certificates.txt>

1.7.3 Protect the Server's Private Key (Scored)

Profile Applicability:

- Level 1

Description:

It is critical to protect the server's private key. The server's private key is encrypted by default as a means of protecting it. However, having it encrypted means that the passphrase is required each time the server is started up, and now it is necessary to protect the passphrase as well. The passphrase may be typed in when it is manually started up, or provided by an automated program.

To summarize, the options are:

1. Use `SSLPassPhraseDialog builtin`, - requires a passphrase to be manually entered.
2. Use `SSLPassPhraseDialog |/path/to/program` to provide the passphrase.
3. Use `SSLPassPhraseDialog exec:/path/to/program` to provide the passphrase,
4. Store the private key in clear text so that a passphrase is not required.

Any of the above options 1-4 are acceptable as long as the key and passphrase are protected as described below. Option 1 has the additional security benefit of not storing the passphrase, but is not generally acceptable for most production web servers, since it requires the web server to be manually started. Options 2 and 3 can provide additional security if the programs providing them are secure. Option 4 is the simplest, is widely used and is acceptable as long as the private key is appropriately protected.

Rationale:

If the private key were to be disclosed, it could be used to decrypt all of the SSL communications with the web server, and could also be used to impersonate the web server.

Audit:

Perform the following steps to determine if the recommended state is implemented:

1. For each certificate file referenced in the Apache configuration files with the `SSLCertificateFile` directive, examine the file for a private key, clearly identified by the string "PRIVATE KEY---"
2. For each file referenced in the Apache configuration files with the `SSLCertificateKeyFile` directive, verify the ownership is `root:root` and the permission `0400`.

Remediation:

Perform the following to implement the recommended state:

1. All private keys must be stored separately from the public certificates. Find all `SSLCertificateFile` directives in the Apache configuration files. For any `SSLCertificateFile` directives that do not have a corresponding separate `SSLCertificateKeyFile` directive, move the key to a separate file from the certificate, and add the `SSLCertificateKeyFile` directive for the key file.
2. For each of the `SSLCertificateKeyFile` directives, change the ownership and permissions on the server private key to be owned by `root:root` with permission `0400`.

References:

1. http://httpd.apache.org/docs/2.4/mod/mod_ssl.html
2. http://httpd.apache.org/docs/2.4/mod/mod_ssl.html#sslpassphrasedialog

1.7.4 Disable the SSL v3.0 Protocol (Scored)

Profile Applicability:

- Level 1

Description:

The Apache SSLProtocol directive specifies the SSL and TLS protocols allowed. The SSLv3 protocol should be disabled in this directive as it is out-dated and vulnerable to information disclosure. Only TLS protocols should be enabled.

Rationale:

The SSLv3 protocol was discovered to be vulnerable to the POODLE attack (Padding Oracle On Downgraded Legacy Encryption) in October 2014. The attack allows decryption and extraction of information from the server's memory. Due to this vulnerability disabling the SSLv3 protocol is highly recommended.

Audit:

Perform the following steps to determine if the recommended state is implemented:
Search the Apache configuration files for the SSLProtocol directive.

Verify that the directive exists and has either:

- a minus "-SSLv3" value included
- an explicit list of only TLS protocols without any plus (+) or minus (-) symbols

Remediation:

Perform the following to implement the recommended state:
Search the Apache configuration files for the SSLProtocol directive; add the directive if not present, or change the value to match one of the following values. The first setting "TLSv1.1 TLS1.2" is preferred when it is acceptable to also disable the TLSv1.0 protocol. See the level 2 recommendation "Disable the TLS v1.0 Protocol" for details.

```
SSLProtocol TLSv1.1 TLS1.2
SSLProtocol TLSv1
```

Default Value:

Default value is:

```
SSLProtocol all
```

References:

1. <https://www.us-cert.gov/ncas/alerts/TA14-290A>
2. <https://www.openssl.org/~bodo/ssl-poodle.pdf>

1.7.5 Restrict Weak SSL Ciphers (Scored)

Profile Applicability:

- Level 1

Description:

Disable weak SSL ciphers using the `SSLCipherSuite`, and `SSLHonorCipherOrder` directives. The `SSLCipherSuite` directive specifies which ciphers are allowed in the negotiation with the client. While the `SSLHonorCipherOrder` causes the servers preferred ciphers to be used instead of the clients specified preferences.

Rationale:

The SSL/TLS protocols support a large number of encryption ciphers including many weak ciphers that are subject to man-in-the middle attacks and information disclosure. Some implementations even support the NULL cipher which allows a TLS connection without any encryption! Therefore it is critical to ensure the configuration only allows strong ciphers greater than or equal to 128 bit to be negotiated with the client. Stronger 256-bit ciphers should be allowed and preferred. In addition enabling the `SSLHonorCipherOrder` further protects the client from man-in-the-middle downgrade attacks by ensuring the servers preferred ciphers will be used rather than the clients preferences.

Audit:

Perform the following steps to determine if the recommended state is implemented:

1. Verify the `SSLCipherSuite` directive disables weak ciphers in the Apache server level configuration and every virtual host that is SSL enabled.
2. Alternately the SSL protocols and ciphers supported can be easily tested by connecting to a running web server with `openssl s_client` such as shown in https://www.owasp.org/index.php/Testing_for_SSL-TLS_%28OWASP-CM-001%29

Remediation:

Perform the following to implement the recommended state:

Add or modify the following line in the Apache server level configuration and every virtual host that is SSL enabled:

```
SSLHonorCipherOrder On
SSLCipherSuite ALL:!EXP:!NULL:!ADH:!LOW:!SSLv2:!MD5:!RC4
```

FIPS Compliance: The above cipher suite specification may be used for servers that fall under FIPS 140-2 compliance requirements, SP800-52 provides guidelines for the TLS ciphers, because it eliminates the usage of the RC4 cipher and MD5 hash which are not deemed FIPS compliant.

Disable SSLv3 Ciphers: If the SSLv3 protocol has also been disabled, then the SSLv3 related ciphers will not be used, and could be removed from the cipher suite specification.

```
SSLCipherSuite ALL:!EXP:!NULL:!ADH:!LOW:!SSLv2:!SSLv3:!MD5:!RC4
```

Default Value:

The following are the default values:

```
SSLCipherSuite default depends on OpenSSL version.  
SSLHonorCipherOrder Off
```

References:

1. http://httpd.apache.org/docs/2.4/mod/mod_ssl.html#sslprotocol
2. http://httpd.apache.org/docs/2.4/mod/mod_ssl.html#ssliphersuite
3. <https://www.openssl.org/>
4. https://www.owasp.org/index.php/Testing_for_SSL-TLS_%28OWASP-CM-001%29
5. <https://community.qualys.com/blogs/securitylabs/2011/10/17/mitigating-the-beast-attack-on-tls>
6. <https://community.qualys.com/blogs/securitylabs/2013/03/19/rc4-in-tls-is-broken-now-what>
7. <http://blogs.msdn.com/b/kaushal/archive/2011/10/03/taming-the-beast-browser-exploit-against-ssl-tls.aspx>

1.7.6 Disable SSL Insecure Renegotiation (Scored)

Profile Applicability:

- Level 1

Description:

A man-in-the-middle renegotiation attack was discovered in SSLv3 and TLSv1 in November, 2009 ([CVE-2009-3555](https://cve.mitre.org/cve/2009/3555)). First, a work around and then a fix was approved as an Internet Standard as RFC 574, Feb 2010. The work around, which removes the renegotiation, is available from OpenSSL as of version 0.9.8l and newer versions. For details: http://www.openssl.org/news/secadv_20091111.txt

The `SSLInsecureRenegotiation` directive was added in Apache 2.2.15, for web servers linked with OpenSSL version 0.9.8m or later, to provide backward compatibility to clients with the older, unpatched SSL implementations.

Rationale:

Enabling the `SSLInsecureRenegotiation` directive leaves the server vulnerable to man-in-the-middle renegotiation attack. Therefore, the `SSLInsecureRenegotiation` directive should not be enabled.

Audit:

Perform the following steps to determine if the recommended state is implemented:

1. Search the Apache configuration files for the `SSLInsecureRenegotiation` directive and verify that the directive is either not present or has a value of `off`.

Remediation:

Perform the following to implement the recommended state:

1. Search the Apache configuration files for the `SSLInsecureRenegotiation` directive. If the directive is present modify the value to be `off`. If the directive is not present then no action is required.

```
SSLInsecureRenegotiation off
```

Default Value:

```
SSLInsecureRenegotiation off
```

References:

1. http://httpd.apache.org/docs/2.2/mod/mod_ssl.html#sslsecurerenegotiation
2. <http://cve.mitre.org/cgi-bin/cvename.cgi?name=CAN-2009-3555>
3. <http://www.phonefactor.com/sslgap/ssl-tls-authentication-patches>

1.7.7 Ensure SSL Compression is not Enabled (Scored)

Profile Applicability:

- Level 1

Description:

The `SSLCompression` directive controls whether SSL compression is used by Apache when serving content over HTTPS. It is recommended that the `SSLCompression` directive be set to `off`.

Rationale:

If SSL compression is enabled, HTTPS communication between the client and the server may be at increased risk to the CRIME attack. The CRIME attack increases a malicious actor's ability to derive the value of a session cookie, which commonly contains an authenticator. If the authenticator in a session cookie is derived, it can be used to impersonate the account associated with the authenticator.

Audit:

Perform the following steps to determine if the recommended state is implemented:

1. Search the Apache configuration files for the `SSLCompression` directive.
2. Verify that the directive either does not exist or exists and is set to `off`.

Remediation:

Perform the following to implement the recommended state:

1. Search the Apache configuration files for the `SSLCompression` directive.
2. If the directive is present, set it to `off`.

Default Value:

In Apache versions $\geq 2.4.3$, the `SSLCompression` directive is available and SSL compression is implicitly disabled. In Apache 2.4 - 2.4.2, the `SSLCompression` directive is not available and SSL compression is implicitly enabled.

References:

1. http://httpd.apache.org/docs/2.4/mod/mod_ssl.html#sslcompression
2. [http://en.wikipedia.org/wiki/CRIME_\(security_exploit\)](http://en.wikipedia.org/wiki/CRIME_(security_exploit))

1.7.8 Disable the TLS v1.0 Protocol (Scored)

Profile Applicability:

- Level 2

Description:

The TLSv1.0 protocol should be disabled via the SSLProtocol directive, if possible, as it has been shown to be vulnerable to information disclosure.

Rationale:

The TLSv1.0 protocol is vulnerable to the BEAST attack when used in CBC mode (October 2011). Unfortunately the TLSv1.0 uses CBC modes for all of the block mode ciphers, which only leaves the RC4 streaming cipher. The RC4 cipher is not vulnerable to the BEAST attack; however there is research that indicates it is also weak and is not recommended. Therefore it is recommended that the TLSv1.0 protocol be disabled if all TLS clients support the newer TLS protocols. All major up-to-date browsers support TLSv1.1 and TLSv1.2; however, some older IE browsers (8,9,10) may still have TLSv1.1 and TLSv1.2 disabled for some strange reason. While Safari 6 does not support the newer TLS protocols. Review the Wikipedia reference for browser support details. Ensuring that all user's browsers are configured to allow TLSv1.1 and TLSv1.2 is necessary before disabling TLSv1.0 on the Apache web server; therefore this recommendation is a level 2 rather than a level 1. Disabling TLSv1.0 on internal only websites is more easily accomplished when access is limited to clients with browsers controlled by the organization policies and procedures to allow and prefer TLSv1.1 and higher.

The NIST SP 800-52r1 guidelines for TLS configuration state that servers that support government-only applications shall not support TLSv1.0 or any of the SSL protocols. While Servers that support citizen or business-facing applications may be configured to support TLS version 1.0 in order to enable interaction with citizens and businesses.

Also it is important to note that Microsoft support for all older versions of IE ends January 12, 2016, and Apple ends support for Safari 6 with the fall release of OS X 10.11. So it is wise to plan for usage of TLSv1.0 to be eliminated in 2016.

Some organizations may find it helpful to implement a phased transitional plan where TLSv1.0 is not disabled, but the web server will detect browsers which do not have TLSv1.1 or newer enabled and redirect them to a web site that explains how to enable the newer

TLS protocols. The redirect can be implemented using the `mod_rewrite` which can detect the protocol used, and rewrite the URL to the helpful website.

Audit:

Perform the following steps to determine if the recommended state is implemented:
Search the Apache configuration files for the `SSLProtocol` directive and ensure it has the value of `"TLSv1.1 TLSv1.2"`.

Remediation:

Perform the following to implement the recommended state:
Search the Apache configuration files for the `SSLProtocol` directive; add the directive if not present, or change the value to `"TLSv1.1 TLSv1.2"`.

Default Value:

Default value is:

```
SSLProtocol all
```

References:

1. http://en.wikipedia.org/wiki/Transport_Layer_Security#Web_browsers- Browser support and defaults for SSL/TLS protocols
2. <https://community.qualys.com/blogs/securitylabs/2011/10/17/mitigating-the-beast-attack-on-tls>- Qualys - Ivan Ristic
3. <http://nvlpubs.nist.gov/nistpubs/SpecialPublications/NIST.SP.800-52r1.pdf>
4. <https://support.microsoft.com/en-us/gp/microsoft-internet-explorer>

1.7.9 Enable OCSP Stapling (Scored)

Profile Applicability:

- Level 2

Description:

The OCSP (Online Certificate Status Protocol) provides the current revocation status of an X.509 certificate and allows for a certificate authority to revoke the validity of a signed certificate before its expiration date. The URI for the OCSP server is included in the certificate and verified by the browser. The Apache `SSLUseStapling` directive along with the `SSLStaplingCache` directive are recommended to enable OCSP Stapling by the web server. If the client requests OCSP stapling, then the web server can include the OCSP server response along with the web server's X.509 certificate.

Rationale:

The OCSP protocol is a big improvement over CRLs (certificate revocation lists) for checking if a certificate has been revoked. There are however some minor privacy and efficiency concerns with OCSP. The fact that the browser has to check a third party CA discloses that the browser is configured for OCSP checking. Also the already high overhead of making an SSL connection is increased by the need for the OCSP requests and responses. The OCSP stapling improves the situation by having the SSL server "staple" an OCSP response, signed by the OCSP server, to the certificate it presents to the client. This obviates the need for the client to ask the OCSP server for status information on the server certificate. However, the client will still need to make OCSP requests on any intermediate CA certificates that are typically used to sign the server's certificate.

Audit:

Perform the following steps to determine if the recommended state is implemented. At the Apache server level configuration and for every virtual host that is SSL enabled:

- Verify the `SSLStaplingCache` directive is present and not commented out. There are three supported cache types, any of them are considered compliant.
- Verify the `SSLUseStapling` directive is enabled with a value of "on"

Remediation:

Perform the following to implement the recommended state:

Add or modify the `SSLUseStapling` directive to have a value of "on" in the Apache server

level configuration and every virtual host that is SSL enabled. Also ensure that `SSLStaplingCache` is set to one of the three cache types similar to the examples below.

```
SSLUseStapling On
SSLStaplingCache "shmcb:logs/ssl_staple_cache(512000) "
- or -
SSLStaplingCache "dbm:logs/ssl_staple_cache.db"
- or -
SSLStaplingCache  dc:UNIX:logs/ssl_staple_socket
```

Default Value:

Default values are:

`SSLUseStapling Off`

`SSLStaplingCache` *no default value*

References:

1. http://en.wikipedia.org/wiki/OCSP_stapling - OCSP Stapling
2. http://httpd.apache.org/docs/2.4/mod/mod_ssl.html - Apache SSL Directives

1.7.10 Enable HTTP Strict Transport Security (Scored)

Profile Applicability:

- Level 2

Description:

HTTP Strict Transport Security (HSTS) is an optional web server security policy mechanism specified by an HTTP Server header. The HSTS header allows a server declaration that only HTTPS communication should be used rather than clear text HTTP communication.

Rationale:

Usage of HTTP Strict Transport Security (HSTS) helps protect HSTS compliant browsers and other agents from HTTP downgrade attacks. Downgrade attacks include a variety of man-in-the-middle attacks which leave the web communication vulnerable to disclosure and modification by forcing the usage of HTTP rather than HTTPS communication. The sslstrip attack tool by Moxie Marlinspike released in 2009 is one such attack, which works when the server allows both HTTP and HTTPS communication. However a man-in-the-middle HTTP-to-HTTPS proxy would be effective in cases where the server required HTTPS, but did not publish an HSTS policy to the browser. This attack would also be effective on browsers which were not compliant with HSTS. All current up-to-date browsers support HSTS except Microsoft's Internet Explorer; Internet Explorer is expected to support HSTS in the next major release **after** IE 12.

The HSTS header specifies a length of time in seconds that the browser / user agent should access the server only using HTTPS. The header may also specify if all sub-domains should also be included in the same policy. Once a compliant browser receives the HSTS Header it will not allow access to the server via HTTP. Therefore it is important that you ensure that there is no portion of the web site or web application that requires HTTP prior to enabling the HSTS protocol.

If all sub-domains are to be included via the *includeSubDomains* option, then carefully consider all various host names, web applications and third party services used including any DNS CNAME values that may be impacted. An overly broad *includeSubDomains* policy will disable access to HTTP web sites for all websites with the same domain name. Also consider that the access will be disabled for the number of seconds given in the max-age value, so in the event a mistake is made, a large value, such as a year, could create significant support issues.

An optional flag of preload may be added if the web site name is to be submitted to be

preloaded in Chrome, Firefox and Safari browsers. See <https://hstspreload.appspot.com/> for details.

Audit:

Perform either of the following steps to determine if the recommended state is implemented.

At the Apache server level configuration and for every virtual host that is SSL enabled, verify there is a `Header` directive present that sets the `Strict-Transport-Security` header with a `max-age` value of at least 480 seconds or more (8 minutes or more). For example:

```
Header always set Strict-Transport-Security "max-age=600"
```

As an alternative the configuration may be validated by connecting to the HTTPS server and verifying the presence of the header. Such as the `openssl s_client` command shown below:

```
openssl s_client -connect www.example.com:443
GET / HTTP/1.1.
Host:www.example.com
HTTP/1.1 200 OK
Date: Mon, 08 Dec 2014 18:28:29 GMT
Server: Apache
X-Frame-Options: NONE
Strict-Transport-Security: max-age=600
Last-Modified: Mon, 19 Jun 2006 14:47:16 GMT
ETag: "152-41694d7a92500"
Accept-Ranges: bytes
Content-Length: 438
Connection: close
Content-Type: text/html
```

Remediation:

Perform the following to implement the recommended state:

Add a `Header` directive as shown below in the Apache server level configuration and every virtual host that is SSL enabled.

```
Header always set Strict-Transport-Security "max-age=600"
```

Default Value:

Default value is:

The Strict Transport Security header is not present by default.

References:

1. http://en.wikipedia.org/wiki/HTTP_Strict_Transport_Security
2. https://www.owasp.org/index.php/HTTP_Strict_Transport_Security
3. https://developer.mozilla.org/en-US/docs/Web/Security/HTTP_strict_transport_security

1.8 Information Leakage

Recommendations in this section intend to limit the disclosure of potentially sensitive information.

1.8.1 Set `ServerToken` to 'Prod' (Scored)

Profile Applicability:

- Level 1

Description:

Configure the Apache `ServerTokens` directive to provide minimal information. By setting the value to `Prod` or `ProductOnly`. The only version information given in the server HTTP response header will be "Apache" rather than providing detailed on modules and versions installed.

Rationale:

Information is power, and identifying web server details greatly increases the efficiency of any attack, as security vulnerabilities are extremely dependent upon specific software versions and configurations. Excessive probing and requests may cause too much "noise" being generated and may tip off an administrator. If an attacker can accurately target their exploits, the chances of successful compromise prior to detection increase dramatically. Script Kiddies are constantly scanning the Internet and documenting the version information openly provided by web servers. The purpose of this scanning is to accumulate a database of software installed on those hosts, which can then be used when new vulnerabilities are released.

Audit:

Perform the following steps to determine if the recommended state is implemented:

1. Verify the `ServerTokens` directive is present in the Apache configuration and has a value of `Prod` or `ProductOnly`.

Remediation:

Perform the following to implement the recommended state:

1. Add or modify the `ServerTokens` directive as shown below to have the value of `Prod` or `ProductOnly`:

ServerTokens Prod

Default Value:

The default value is `Full` which provides the most detailed information.

References:

1. <http://httpd.apache.org/docs/2.4/mod/core.html#servertokens>

1.8.2 Set ServerSignature to 'Off' (Scored)

Profile Applicability:

- Level 1

Description:

Disable the server signatures which generates a signature line as a trailing footer at the bottom of server generated documents such as error pages.

Rationale:

Server signatures are helpful when the server is acting as a proxy, since it helps the user distinguish errors from the proxy rather than the destination server, however in this context there is no need for the additional information and we want to limit leakage of unnecessary information.

Audit:

Verify the `ServerSignature` directive is either NOT present in the Apache configuration or has a value of `Off`.

Remediation:

Perform the following to implement the recommended state:

1. Add or modify the `ServerSignature` directive as shown below to have the value of `Off`:

```
ServerSignature Off
```

Default Value:

The default value is `Off` for `ServerSignature`.

References:

1. <http://httpd.apache.org/docs/2.4/mod/core.html#serversignature>

1.8.3 Information Leakage via Default Apache Content (Scored)

Profile Applicability:

- Level 2

Description:

In previous recommendations, we have removed default content such as the Apache manuals and default CGI programs. However, if you want to further restrict information leakage about the web server, it is important that default content such as icons are not left on the web server.

Rationale:

To identify the type of web servers and versions software installed it is common for attackers to scan for icons or special content specific to the server type and version. A simple request like http://example.com/icons/apache_pb2.png may tell the attacker that the server is Apache 2.2 as shown below. The many icons are used primarily for auto indexing, which is also recommended to be disabled.

Audit:

Perform the following step to determine if the recommended state is implemented:

1. Verify that there is no alias or directory access to the Apache icons directory in any of the Apache configuration files.

Remediation:

Perform either of the following to implement the recommended state:

1. The default source build places the auto-index and icon configurations in the `extra/httpd-autoindex.conf` file, so it can be disabled by leaving the include line commented out in the main `httpd.conf` file as shown below.

```
# Fancy directory listings
#Include conf/extra/httpd-autoindex.conf
```

2. Alternatively the `icon alias` directive and the directory access control configuration can be commented out as shown if present:

```
# We include the /icons/ alias for FancyIndexed directory listings. If
# you do not use FancyIndexing, you may comment this out.
#
#Alias /icons/ "/var/www/icons/"
```



```
#<Directory "/var/www/icons">
#   Options Indexes MultiViews FollowSymLinks
#   AllowOverride None
#   Order allow,deny
#   Allow from all
#</Directory>
```

Default Value:

The default source build does not enable access to the Apache icons

1.9 Denial of Service Mitigations

Denial of Service (DoS) attacks intend to degrade a service's ability to process and respond to service requests. Typically, DoS attacks attempt to exhaust the service's network-, CPU-, disk-, and/or memory- related resources. Configuration states in this section may increase a server's resiliency to DoS attacks.

1.9.1 Set Timeout to 10 or less (Scored)

Profile Applicability:

- Level 1

Description:

Denial of Service (DoS) is an attack technique with the intent of preventing a web site from serving normal user activity. DoS attacks, which are normally applied to the network layer, are also possible at the application layer. These malicious attacks can succeed by starving a system of critical resources, vulnerability exploit, or abuse of functionality. Although there is no 100% solution for preventing DoS attacks, the following recommendation uses the `Timeout` directive to mitigate some of the risk, by requiring more effort for a successful DoS attack. Of course DoS attacks can happen in rather unintentional ways as well as intentional and these directives will help in many of those situations as well.

Rationale:

One common technique for DoS is to initiate many connections to the server. By decreasing the timeout for old connections and we allow the server to free up resources more quickly and be more responsive. By making the server more efficient, it will be more resilient to DoS conditions. The `Timeout` directive affects several timeout values for Apache, so review the Apache document carefully.

<http://httpd.apache.org/docs/2.4/mod/core.html#timeout>

Audit:

Perform the following steps to determine if the recommended state is implemented:

Verify that the `Timeout` directive is specified in the Apache configuration files to have a value of 10 seconds or shorter.

Remediation:

Perform the following to implement the recommended state:

Add or modify the Timeout directive in the Apache configuration to have a value of 10 seconds or shorter.

```
Timeout 10
```

Default Value:

```
Timeout 60
```

References:

1. <http://httpd.apache.org/docs/2.4/mod/core.html#timeout>

1.9.2 Set the KeepAlive directive to On (Scored)

Profile Applicability:

- Level 1

Description:

The `KeepAlive` directive controls whether Apache will reuse the same TCP connection per client to process subsequent HTTP requests from that client. It is recommended that the `KeepAlive` directive be set to `On`.

Rationale:

Allowing per-client reuse of TCP sockets reduces the amount of system and network resources required to serve requests. This efficiency gain may improve a server's resiliency to DoS attacks.

Audit:

Perform the following steps to determine if the recommended state is implemented:

Verify that the `KeepAlive` directive in the Apache configuration to have a value of `On`, or is not present. If the directive is not present the default value is `On`.

Remediation:

Perform the following to implement the recommended state:

Add or modify the `KeepAlive` directive in the Apache configuration to have a value of `On`, so that Keepalive connections are enabled.

```
KeepAlive On
```

Default Value:

```
KeepAlive On
```

References:

1. <http://httpd.apache.org/docs/2.4/mod/core.html#keepalive>

1.9.3 Set MaxKeepAliveRequests to 100 or greater (Scored)

Profile Applicability:

- Level 1

Description:

The `MaxKeepAliveRequests` directive limits the number of requests allowed per connection when `KeepAlive` is on. If it is set to 0, unlimited requests will be allowed.

Rationale:

The `MaxKeepAliveRequests` directive is important to be used to mitigate the risk of Denial of Service (DoS) attack technique by reducing the overhead imposed on the server. The `KeepAlive` directive must be enabled before it is effective. Enabling `KeepAlives` allows for multiple HTTP requests to be sent while keeping the same TCP connection alive. This reduces the overhead of having to setup and tear down TCP connections for each request. By making the server more efficient, it will be more resilient to DoS conditions.

Audit:

Perform the following steps to determine if the recommended state is implemented:

Verify that the `MaxKeepAliveRequests` directive in the Apache configuration to have a value of 100 or more. If the directive is not present the default value is 100.

Remediation:

Perform the following to implement the recommended state:

Add or modify the `MaxKeepAliveRequests` directive in the Apache configuration to have a value of 100 or more.

```
MaxKeepAliveRequests 100
```

Default Value:

```
MaxKeepAliveRequests 100
```

References:

1. <http://httpd.apache.org/docs/2.4/mod/core.html#maxkeepaliverequests>

1.9.4 Set KeepAliveTimeout Low to Mitigate Denial of Service (Scored)

Profile Applicability:

- Level 1

Description:

The `KeepAliveTimeout` directive specifies the number of seconds Apache will wait for a subsequent request before closing a connection that is being kept alive.

Rationale:

The `KeepAliveTimeout` directive is used to mitigate some of the risk, by requiring more effort for a successful DoS attack. By enabling `KeepAlive` and keeping the timeout relatively low for old connections and we allow the server to free up resources more quickly and be more responsive.

Audit:

Perform the following steps to determine if the recommended state is implemented:

Verify that the `KeepAliveTimeout` directive in the Apache configuration to have a value of 15 or less. If the directive is not present the default value is 5 seconds.

Remediation:

Perform the following to implement the recommended state:

Add or modify the `KeepAliveTimeout` directive in the Apache configuration to have a value of 15 or less.

```
KeepAliveTimeout 15
```

Default Value:

```
KeepAliveTimeout 5
```

References:

1. <http://httpd.apache.org/docs/2.4/mod/core.html#keepalivetimeout>

1.9.5 Set Timeout Limits for Request Headers (Scored)

Profile Applicability:

- Level 1

Description:

The `RequestReadTimeout` directive allows configuration of timeout limits for client requests. The header portion of the directive provides for an initial timeout value, a maximum timeout and a minimum rate. The minimum rate specifies that after the initial timeout, the server will wait an additional 1 second for each N bytes received. The recommended setting is to have a maximum timeout of 40 seconds or less. Keep in mind that for SSL/TLS virtual hosts the time for the TLS handshake must fit within the timeout.

Rationale:

Setting a request header timeout is vital for mitigating Denial of Service attacks based on slow requests. The slow request attacks are particularly lethal and relative easy to perform, because they require very little bandwidth and can easily be done through anonymous proxies. Starting in June 2009 with the Slow Loris DoS attack, which used a slow GET request, was published by Robert Hansen (RSnake) on his blog <http://ha.ckers.org/slowloris/>. Later in November 2010 at the OWASP App Sec DC conference Wong Onn Chee demonstrated a slow POST request attack which was even more effective. See <http://code.google.com/p/owasp-dos-http-post/> for details.

Audit:

Perform the following to determine if the recommended state is implemented:

1. Locate the Apache configuration files and included configuration files.
2. Locate any `RequestReadTimeout` directives and verify that they have a maximum header request timeout of 40 seconds or less.
3. If the configuration does not contain any `RequestReadTimeout` directives, and the `mod_reqtimeout` module is being loaded, then the default value of 40 seconds is compliant with the benchmark recommendation.

```
RequestReadTimeout header=XXX-40,MinRate=XXX body=XXXXXXXXXX
```

Remediation:

Load the `mod_requesttimeout` module in the Apache configuration with the following configuration.

```
LoadModule reqtimeout_module modules/mod_reqtimeout.so
```

Add a `RequestReadTimeout` directive similar to the one below with the maximum request header timeout value of 40 seconds or less.

```
RequestReadTimeout header=20-40,MinRate=500 body=20,MinRate=500
```

Default Value:

```
header=20-40,MinRate=500
```

References:

1. <http://ha.ckers.org/slowloris/>
2. <http://code.google.com/p/owasp-dos-http-post/>
3. http://httpd.apache.org/docs/2.4/mod/mod_reqtimeout.html

1.9.6 Set Timeout Limits for the Request Body (Scored)

Profile Applicability:

- Level 1

Description:

The `RequestReadTimeout` directive also allows setting timeout values for the body portion of a request. The directive provides for an initial timeout value, and a maximum timeout and minimum rate. The minimum rate specifies that after the initial timeout, the server will wait an additional 1 second for each N bytes are received. The recommended setting is to have a maximum timeout of 20 seconds or less. The default value is `body=20,MinRate=500`.

Rationale:

It is not sufficient to timeout only on the header portion of the request, as the server will still be vulnerable to attacks like the OWASP Slow POST attack, which provide the body of the request very slowly. Therefore the body portion of the request must have a timeout as well. A timeout of 20 seconds or less is recommended.

Audit:

Perform the following to determine if the recommended state is implemented:

1. Locate the Apache configuration files and included configuration files.
2. Locate any `RequestReadTimeout` directives and verify the configuration has a maximum body request timeout of 20 seconds or less.
3. If the configuration does not contain any `RequestReadTimeout` directives, and the `mod_reqtimeout` module is being loaded, then the default value of 20 seconds is compliant with the benchmark recommendation.

```
RequestReadTimeout header=XXXXXX body=20,MinRate=XXXXXXXXXX
```

Remediation:

Load the `mod_reqtimeout` module in the Apache configuration with the following configuration.

```
LoadModule reqtimeout_module modules/mod_reqtimeout.so
```

Add a `RequestReadTimeout` directive similar to the one below with the maximum request body timeout value of 20 seconds or less.

```
RequestReadTimeout header=20-40,MinRate=500 body=20,MinRate=500
```

Default Value:

body=20,MinRate=500

References:

1. http://httpd.apache.org/docs/2.4/mod/mod_reqtimeout.html

1.10 Request Limits

Recommendations in this section reduce the maximum allowed size of request parameters. Doing so increases the likelihood of negatively impacting application and/or site functionality. It is highly recommended that the configuration states described in this section be tested on test servers prior deploying them to production servers.

1.10.1 Set the *LimitRequestLine* directive to 512 or less (Scored)

Profile Applicability:

- Level 2

Description:

Buffer Overflow attacks attempt to exploit an application by providing more data than the application buffer can contain. If the application allows copying data to the buffer to overflow the boundaries of the buffer, then the application is vulnerable to a buffer overflow. The results of Buffer overflow vulnerabilities varies, and may result in the application crashing, or may allow the attacker to execute instructions provided in the data. The Apache `LimitRequest*` directives allow the Apache web server to limit the sizes of requests and request fields and can be used to help protect programs and applications processing those requests.

Specifically the `LimitRequestLine` directive limits the allowed size of a client's HTTP request-line, which consists of the HTTP method, URI, and protocol version.

Rationale:

The limiting of the size of request line is helpful so that the web server can prevent an unexpectedly long or large requests from being passed to a potentially vulnerable CGI program, module or application that would have attempted to process the request. Of course the underlying dependency is that we need to set the limits high enough to not interfere with any one application on the server, while setting them low enough to be of value in protecting the applications. Since the configuration directive is available only at the server configuration level, it is not possible to tune the value for different portions of the same web server. Please read the Apache documentation carefully, as these requests may interfere with the expected functionality of some web applications.

Audit:

Perform the following steps to determine if the recommended state is implemented:

Verify that the `LimitRequestline` directive is in the Apache configuration and has a value of 512 or less.

Remediation:

Perform the following to implement the recommended state:

Add or modify the `LimitRequestline` directive in the Apache configuration to have a value of 512 or shorter.

```
LimitRequestline 512
```

Default Value:

```
LimitRequestline 8190
```

References:

1. <http://httpd.apache.org/docs/2.4/mod/core.html#limitrequestline>

1.10.2 Set the LimitRequestFields directive to 100 or less (Scored)

Profile Applicability:

- Level 2

Description:

The `LimitRequestFields` directive limits the number of fields allowed in an HTTP request.

Rationale:

The limiting of the number of fields is helpful so that the web server can prevent an unexpectedly high number of fields from being passed to a potentially vulnerable CGI program, module or application that would have attempted to process the request. Of course the underlying dependency is that we need to set the limits high enough to not interfere with any one application on the server, while setting them low enough to be of value in protecting the applications. Since the configuration directives are available only at the server configuration level, it is not possible to tune the value for different portions of the same web server. Please read the Apache documentation carefully, as these requests may interfere with the expected functionality of some web applications.

Audit:

Verify that the `LimitRequestFields` directive is in the Apache configuration and has a value of 100 or less.

Remediation:

Perform the following to implement the recommended state:

Add or modify the `LimitRequestFields` directive in the Apache configuration to have a value of 100 or less. If the directive is not present the default depends on a compile time configuration, but defaults to a value of 100.

```
LimitRequestFields 100
```

Default Value:

```
LimitRequestFields 100
```

References:

1. <http://httpd.apache.org/docs/2.4/mod/core.html#limitrequestfields>

1.10.3 Set the `LimitRequestFieldSize` directive to 1024 or less (Scored)

Profile Applicability:

- Level 2

Description:

The `LimitRequestFieldSize` limits the number of bytes that will be allowed in an HTTP request header. It is recommended that the `LimitRequestFieldSize` directive be set to 1024 or less.

Rationale:

By limiting of the size of request headers is helpful so that the web server can prevent an unexpectedly long or large values from being passed to exploit a potentially vulnerable program. Of course the underlying dependency is that we need to set the limits high enough to not interfere with any one application on the server, while setting them low enough to be of value in protecting the applications. Since the configuration directives are available only at the server configuration level, it is not possible to tune the value for different portions of the same web server. Please read the Apache documentation carefully, as these requests may interfere with the expected functionality of some web applications.

Audit:

Perform the following steps to determine if the recommended state is implemented:

Verify that the `LimitRequestFieldSize` directive is in the Apache configuration and has a value of 1024 or less.

Remediation:

Perform the following to implement the recommended state:

Add or modify the `LimitRequestFieldSize` directive in the Apache configuration to have a value of 1024 or less.

```
LimitRequestFieldSize 1024
```

Default Value:

```
LimitRequestFieldSize 8190
```

References:

1. <http://httpd.apache.org/docs/2.4/mod/core.html#limitrequestfieldsize>

1.10.4 Set the `LimitRequestBody` directive to 102400 or less (Scored)

Profile Applicability:

- Level 2

Description:

The `LimitRequestBody` directive limits the number of bytes that are allowed in a request body. Size of requests may vary greatly; for example during a file upload the size of the file must fit within this limit.

Rationale:

The limiting of the size of the request body is helpful so that the web server can prevent an unexpectedly long or large requests from being passed to a potentially vulnerable program. Of course the underlying dependency is that we need to set the limits high enough to not interfere with any one application on the server, while setting them low enough to be of value in protecting the applications. The `LimitRequestBody` may be configured on a per directory, or per location context.

Please read the Apache documentation carefully, as these requests may interfere with the expected functionality of some web applications.

Audit:

Verify that the `LimitRequestBody` directive in the Apache configuration to have a value of 102400 (100K) or less.

Remediation:

Perform the following to implement the recommended state:

Add or modify the `LimitRequestBody` directive in the Apache configuration to have a value of 102400 (100K) or less. Please read the Apache documentation so that it is understood that this directive will limit the size of file up-loads to the web server.

```
LimitRequestBody 102400
```

Default Value:

```
LimitRequestBody 0 (unlimited)
```

References:

1. <http://httpd.apache.org/docs/2.4/mod/core.html#limitrequestbody>

1.11 Enable SELinux to Restrict Apache Processes

Recommendations in this section provide mandatory access controls (MAC) using the SELinux kernel module in targeted mode. SELinux provides additional enforced security which will prevent access to resources, files and directories by the httpd processes even in cases where an application or server vulnerability might allow inappropriate access. The SELinux controls are advanced security controls that require significant effort to ensure they do not negatively impact the application and/or site functionality. It is highly recommended that the configuration states described in this section be tested thoroughly on test servers prior to deploying them to production servers.

SELinux and AppArmor provide similar controls, and it is not recommended to use both SELinux and AppArmor on the same system. Depending on which Linux distribution is in use either AppArmor or SELinux are likely to be already installed or readily available as packages. AppArmor differs from SELinux in that it binds the controls to programs rather than users and uses path names rather than labeled type enforcement.

1.11.1 Enable SELinux in Enforcing Mode (Scored)

Profile Applicability:

- Level 2

Description:

SELinux (Security-Enhanced Linux) is a Linux kernel security module that provides mandatory access control security policies with type enforcement that are checked after the traditional discretionary access controls. It was created by the US National Security Agency and can enforce rules on files and processes in a Linux system, and restrict actions, based on defined policies.

Rationale:

Web applications and services continue to be one of the leading attack vectors for black-hat criminals to gain access to information and servers. The threat is high because web servers are often externally accessible and typically have the greatest share of server-side vulnerabilities. The SELinux mandatory access controls provide a much stronger security model which can be used to implement a deny-by-default model which only allows what is explicitly permitted.

Audit:

Perform the following steps to determine if the recommended state is implemented:

Use the `sestatus` command to check that SELinux is enabled and that both the current mode and the configured mode are set to `enforcing`.

```
$ sestatus | grep -i mode
Current mode: enforcing
Mode from config file: enforcing
```

Remediation:

Perform the following to implement the recommended state:

If SELinux is not enabled in the configuration file, edit the file `/etc/selinux/config` and set the value of `SELINUX` as `enforcing` and reboot the system for the new configuration to be effective.

```
SELINUX=enforcing
```

If the current mode is not enforcing, and an immediate reboot is not possible, the current mode can be set to enforcing with the `setenforce` command shown below.

```
# setenforce 1
```

Default Value:

SELinux is not enabled by default.

References:

1. https://en.wikipedia.org/wiki/Security-Enhanced_Linux

1.11.2 Run Apache Processes in the httpd_t Confined Context (Scored)

Profile Applicability:

- Level 2

Description:

SELinux includes customizable targeted policies that may be used to confine the Apache httpd server to enforce least privileges so that the httpd server has only the minimal access to specified directories, files and network ports. Access is controlled by process types (domains) defined for the httpd process. There are over a hundred individual httpd related types defined in a default Apache SELinux policy which includes many of the common Apache add-ons and applications such as php, nagios, smokeping and many others. The default SELinux policies work well for a default Apache installation, but implementation of SELinux targeted policies on a complex or highly customized web server requires a rather significant development and testing effort which comprehends both the workings of SELinux and the detailed operations and requirements of the web application. All directories and files to be accessed by the web server process must have security labels with appropriate types.

The following types are a sample of the most commonly used:

- http_port_t - Network ports allowed for listening
- httpd_sys_content_t - Read access to directories and files with web content
- httpd_log_t - Directories and files to be used for writable log data
- httpd_sys_script_exec_t - Directories and files for executable content.

Rationale:

With the proper implementation of SELinux, vulnerabilities in the web application may be prevented from being exploited due to the additional restrictions. For example a vulnerability that allows an attacker to read to inappropriate system files may be prevented from execution by SELinux because the inappropriate files are not labeled as httpd_sys_content_t. Likewise writing to an unexpected directory or execution of unexpected content can be prevented by similar mandatory security labels enforced by SELinux.

Audit:

Check that all of the Apache httpd processes are confined to the httpd_t SELinux context. The type (the third colon separated field) for each process should be httpd_t. Note that on some platforms such as Ubuntu the Apache executable is named apache2 instead of httpd.

```
$ ps -eZ | grep httpd
unconfined_u:system_r:httpd_t:s0 1366 ? 00:00:00 httpd
unconfined_u:system_r:httpd_t:s0 1368 ? 00:00:00 httpd
. . .
```

Remediation:

If the running httpd processes are not confined to the httpd_t SELinux context. Then check the context for the httpd binary and the apachectl binary, and set the httpd binary to have a context of httpd_exec_t and the apachectl executable should have a context of initrc_exec_t as shown below. Also note that on some platforms such as Ubuntu, the Apache executable is named apache2 instead of httpd. Also note that on some platforms such as Ubuntu, the Apache executable is named apache2 instead of httpd.

```
# ls -alZ /usr/sbin/httpd /usr/sbin/httpd.* /usr/sbin/apachectl
-rwxr-xr-x. root root system_u:object_r:initrc_exec_t:s0 /usr/sbin/apachectl
-rwxr-xr-x. root root system_u:object_r:httpd_exec_t:s0 /usr/sbin/httpd
-rwxr-xr-x. root root system_u:object_r:httpd_exec_t:s0 /usr/sbin/httpd.worker
-rwxr-xr-x. root root system_u:object_r:httpd_exec_t:s0 /usr/sbin/httpd.event
```

If the executable files are not labeled correctly, they may be relabeled with the chcon command, as shown, however the file system labeling is based on the SELinux file context polices and the file systems will on some occasions be relabeled according to the policy.

```
# chcon -t initrc_exec_t /usr/sbin/apachectl
# chcon -t httpd_exec_t /usr/sbin/httpd /usr/sbin/httpd.*
```

Since the file system may be relabeled based on SELinux policy, it's best to check the SELinux policy with semanage fcontext "-l" option. If the policy is not present, then add the pattern to the policy using the "-a" option. The restorecon command shown below will restore the file context label according to the current policy, and is required if a pattern was added.

```
# ### Check the Policy
# semanage fcontext -l | fgrep 'apachectl'
/usr/sbin/apachectl regular file system_u:object_r:initrc_exec_t:s0
# semanage fcontext -l | fgrep '/usr/sbin/httpd'
/usr/sbin/httpd regular file system_u:object_r:httpd_exec_t:s0
/usr/sbin/httpd.worker regular file system_u:object_r:httpd_exec_t:s0
/usr/sbin/httpd.event regular file system_u:object_r:httpd_exec_t:s0
# ### Add to the policy, if not present
# semanage fcontext -f -- -a -t httpd_exec_t '/usr/sbin/httpd'
# semanage fcontext -f -- -a -t httpd_exec_t '/usr/sbin/httpd.worker'
# semanage fcontext -f -- -a -t httpd_exec_t '/usr/sbin/httpd.event'
# semanage fcontext -f -- -a -t initrc_exec_t /usr/sbin/apachectl
```

```
# ### Restore the file labeling accord to the SELinux policy
# restorecon -v /usr/sbin/httpd /usr/sbin/httpd.* /usr/sbin/apachectl
```

Default Value:

SELinux is not enabled by default.

References:

1. https://access.redhat.com/documentation/en-US/Red_Hat_Enterprise_Linux/6/html/Security-Enhanced_Linux/chap-Security-Enhanced_Linux-Targeted_Policy.html

1.11.3 Ensure the httpd_t Type is Not in Permissive Mode (Scored)

Profile Applicability:

- Level 2

Description:

In addition to setting the entire SELinux configuration in permissive mode, it is possible to set individual process types (domains) such as httpd_t into a permissive mode as well. The permissive mode will not prevent any access or actions, instead, any actions that would have been denied are simply logged.

Rationale:

Usage of the permissive mode is helpful for testing and ensuring that SELinux will not prevent access that is necessary for the proper function of a web application. However all access is allowed in permissive mode by SELinux.

Audit:

Check that the httpd_t process type (domain) is not in permissive mode with the `semodule` command. There should be no output if the type is not set to permissive.

```
# semodule -l | grep permissive_httpd_t
```

Remediation:

Perform the following to implement the recommended state:

If the httpd_t type is in permissive mode, the customized permissive mode should be deleted with the following `semanage` command.

```
# semanage permissive -d httpd_t
```

Default Value:

The httpd_t type is not in permissive mode by default.

References:

1. https://access.redhat.com/documentation/en-US/Red_Hat_Enterprise_Linux/6/html/Security-Enhanced_Linux/sect-Security-Enhanced_Linux-Fixing_Problems-Permissive_Domains.html

1.11.4 Ensure Only the Necessary SELinux Booleans are Enabled (Not Scored)

Profile Applicability:

- Level 2

Description:

SELinux booleans allow or disallow behavior specific to the Apache web server. Common examples include whether CGI execution is allowed, or if the httpd server is allowed to communicate with the current terminal (tty). Communication with the terminal, may be necessary for entering a passphrase during start up to decrypt a private key.

Rationale:

Enabling only the necessary httpd related booleans provides a defense in depth approach, that will deny actions that are not in use or expected.

Audit:

Review the SELinux httpd booleans that are enabled to ensure only the necessary booleans are enabled for the current and the configured state. Due to the variety and complexity of web server usages and organizational needs, a preset recommendation of enabled booleans is not practical. Run either of the two commands below to show only the enabled httpd related booleans. The `getsebool` command is installed with the core SELinux, while the `semanage` command is an optional package, however the `semanage` output includes descriptive text.

```
# getsebool -a | grep httpd_ | grep '> on'
httpd_builtin_scripting --> on
httpd_dbus_avahi --> on
httpd_tty_comm --> on
httpd_unified --> on
```

Alternative using the `semanage` command.

```
# semanage boolean -l | grep httpd_ | grep -v '(off , off)'
httpd_enable_cgi (on , on) Allow httpd cgi support
httpd_dbus_avahi (on , on) Allow Apache to communicate with avahi service via dbus
httpd_unified (on , on) Unify HTTPD handling of all content files.
httpd_builtin_scripting (on , on) Allow httpd to use built in scripting (usually php)
httpd_tty_comm (on , on) Unify HTTPD to communicate with the terminal...
```

Remediation:

To disable the SELinux httpd booleans that are determined to be unnecessary, use the `setsebool` command as shown below with the "-P" option to make the change persistent.

```
# setsebool -P httpd_enable_cgi off
# getsebool httpd_enable_cgi
httpd_enable_cgi --> off
```

Default Value:

SELinux is not enabled by default.

References:

1. https://access.redhat.com/documentation/en-US/Red_Hat_Enterprise_Linux/6/html/Security-Enhanced_Linux/sect-Security-Enhanced_Linux-Working_with_SELinux-Booleans.html

1.12 Enable AppArmor to Restrict Apache Processes

Recommendations in this section provide mandatory access controls (MAC) using the AppArmor kernel module. AppArmor provides additional enforced security which will prevent access to resources, files and directories by the apache2 processes even in cases where an application or server vulnerability might allow inappropriate access. The AppArmor controls are advanced security controls that require significant effort to ensure they do not negatively impact the application and/or site functionality. It is highly recommended that the configuration states described in this section be tested thoroughly on test servers prior to deploying them to production servers.

AppArmor and SELinux provide similar controls, and it is not recommended to use both SELinux and AppArmor on the same system. Depending on which Linux distribution is in use either AppArmor or SELinux are likely to be already installed or readily available as packages. AppArmor differs from SELinux in that it binds the controls to programs rather than users and uses path names rather than labeled type enforcement.

1.12.1 Enable the AppArmor Framework (Scored)

Profile Applicability:

- Level 2

Description:

AppArmor is a Linux kernel security module that provides a named based mandatory access control with security policies. AppArmor can enforce rules on programs for file access and network connections and restrict actions based on defined policies.

Rationale:

Web applications and web services continue to be one of the leading attack vectors for black-hat criminals to gain access to information and servers. The threat is high because web servers are often externally accessible and typically have the greatest share of server-side vulnerabilities. The AppArmor mandatory access controls provide a much stronger security model which can be used to implement a deny-by-default model which only allows what is explicitly permitted.

Audit:

Perform the following steps to determine if the recommended state is implemented:
Use the aa-status command with the `--enabled` option to check that AppArmor is enabled.

If AppArmor is enabled the command will return a zero (0) exit code for success. The '`&& echo Enabled`' is added to the command below to provide positive feedback. If no text is echoed, then AppArmor is not enabled.

```
# aa-status --enabled && echo Enabled
Enabled
```

Remediation:

Perform the following to implement the recommended state:

- If the `aa-status` command is not found, then the AppArmor package is not installed and needs to be installed using the appropriate the Linux distribution package management. For example:

```
# apt-get install apparmor
# apt-get install libapache2-mod-apparmor
```

- To enable the AppArmor framework run the `init.d` script as shown below.

```
# /etc/init.d/apparmor start
```

Default Value:

AppArmor is enabled by default.

References:

1. <https://help.ubuntu.com/community/AppArmor>

1.12.2 Customize the Apache AppArmor Profile (Not Scored)

Profile Applicability:

- Level 2

Description:

AppArmor includes customizable profiles that may be used to confine the Apache web server to enforce least privileges so that the server has only the minimal access to specified directories, files and network ports. Access is controlled by a profile defined for the `apache2` process. The default AppArmor profile is typically a very permissive profile that allows read-write access to all system files. Therefore it's important that the default profile be customized to enforce least privileges. The AppArmor utilities such as `aa-autodep`, `aa-complain`, and `aa-logprof` can be used to generate an initial profile based on actual usage. However thorough testing, review and customization will be necessary to ensure that the Apache profile restrictions allow necessary functionality while implementing least privilege.

Rationale:

With the proper implementation of AppArmor profile, vulnerabilities in the web application may be prevented from being exploited due to the additional restrictions. For example a vulnerability that allows an attacker to read an inappropriate system files may be prevented from execution by AppArmor because the inappropriate files are not allowed by the profile. Likewise writing to an unexpected directory or execution of unexpected content can be prevented by similar mandatory security controls enforced by AppArmor.

Audit:

Perform the following steps to determine if the recommended state is implemented:

- Find the Apache AppArmor profile typically found in `/etc/apparmor.d/usr.sbin.apache2` along with any files included by the profile such as `/etc/apparmor.d/apache2.d/*` and files in the `/etc/apparmor.d/abstractions/` directory.
- Review the capabilities and permissions granted to ensure that the profile implements least privileges for the web application. Wild-card paths such as `"/**"` which grant access to all files and directories starting with the root level directory, and should not be present in the profile. Instead read only access to specific necessary system files such `"/etc/group"` and to the web content files such as `/var/www/html/**` should be given. Refer to the `apparmor.d` man page for

additional details. Shown below are some possible example capabilities and path permissions.

```
capability dac_override,  
capability dac_read_search,  
capability net_bind_service,  
capability setgid,  
capability setuid,  
capability kill,  
capability sys_tty_config,  
. . .  
  
/usr/sbin/apache2 mr,  
/etc/gai.conf r,  
/etc/group r,  
/etc/apache2/** r,  
/var/www/html/** r,  
/run/apache2/** rw,  
/run/lock/apache2/** rw,  
/var/log/apache2/** rw,  
/etc/mime.types r,
```

Remediation:

Perform the following to implement the recommended state:

- Stop the Apache server

```
# service apache2 stop
```

- Create a mostly empty apache2 profile based on program dependencies.

```
# aa-autodep apache2  
Writing updated profile for /usr/sbin/apache2.
```

- Set the apache2 profile in complain mode so that access violations will be allowed, and will be logged.

```
# aa-complain apache2  
Setting /usr/sbin/apache2 to complain mode.
```

- Start the apache2 service

```
# service apache2 start
```

- Thoroughly test the web application attempting to exercise all intended functionality so that AppArmor will generate the necessary logs of all resources accessed. The logs are sent via the system syslog utility, and are typically found in either the

/var/log/syslog or /var/log/messages files. Also stop and restart the web server as part of the testing process.

- Use `aa-logprof` to update the profile based on logs generated during the testing. The tool will prompt for suggested modifications to the profile, based on the logs. The logs may also be reviewed manual in order to update the profile.

```
# aa-logprof
```

- Review and edit the profile, removing any inappropriate content, and adding appropriate access rules. Directories with multiple files accessed with the same permission can be simplified with the usage of wild-cards when appropriate. Reload the updated profile using the `apparmor_parser` command.

```
# apparmor_parser -r /etc/apparmor.d/usr.sbin.apache2
```

- Test the new updated profile again checking for any new apparmor denied logs generated. Update and reload the profile as necessary. Repeat the application tests, until no new apparmor deny logs are created, except for access which should be prohibited.

```
# tail -f /var/log/syslog
```

- Set the apache2 profile to enforce mode, reload apparmor, and then test the web site functionality again.

```
# aa-enforce /usr/sbin/apache2  
# /etc/init.d/apparmor reload
```

Default Value:

The default Apache profile is very permissive.

References:

1. <https://wiki.ubuntu.com/AppArmor>

1.12.3 Ensure Apache AppArmor Profile is in Enforce Mode (Scored)

Profile Applicability:

- Level 2

Description:

AppArmor profiles may be in one of three modes: disabled, complain or enforce. In the complain mode, any violations of the access controls are logged but the restrictions are not enforced. Also once a profile mode has been changed, it is recommended to restart the Apache server, otherwise the currently running process may not be confined by the policy.

Rationale:

The complain mode is useful for testing and debugging a profile, but is not appropriate for production. Only the confined process running in enforce mode will prevent attacks that violate the configured access controls.

Audit:

Perform the following steps to determine if the recommended state is implemented:

- Use the `aa-unconfined` command to check that the `apache2` policy is enforced, and that the currently running `apache2` processes are confined. The output should include both "confined by" and "(enforce)"

```
# aa-unconfined --paranoid | grep apache2
1899 /usr/sbin/apache2 confined by '/usr/sbin/apache2 (enforce) '
1902 /usr/sbin/apache2 confined by '/usr/sbin/apache2 (enforce) '
1903 /usr/sbin/apache2 confined by '/usr/sbin/apache2 (enforce) '
. . .
```

Note that non-compliant results may include "not confined" or "(complain)" such as the following:

```
3304 /usr/sbin/apache2 not confined
2502 /usr/sbin/apache2 confined by '/usr/sbin/apache2 (complain) '
4004 /usr/sbin/apache2 confined by '/usr/sbin/apache2//HANDLING_UNTRUSTED_INPUT
(complain) '
```

Remediation:

Perform the following to implement the recommended state:

- Set the profile state to enforce mode.

```
# aa-enforce apache2
Setting /usr/sbin/apache2 to enforce mode.
```

- Stop the Apache server, and confirm that it is not running. In some cases the AppArmor controls may prevent the web server from stopping properly, and it may be necessary to stop the process manually or even reboot the server.

```
# service apache2 stop
* Stopping web server apache2
# service apache2 status
* apache2 is not running
```

- Restart the Apache service.

```
# service apache2 start
* Starting web server apache2
```

Default Value:

The default mode is enforce

Control		Set Correctly	
		Yes	No
1	Recommendations		
1.1	Planning and Installation		
1.1.1	Pre-Installation Planning Checklist (Not Scored)	<input type="checkbox"/>	<input type="checkbox"/>
1.1.2	Do Not Install a Multi-use System (Not Scored)	<input type="checkbox"/>	<input type="checkbox"/>
1.1.3	Installing Apache (Not Scored)	<input type="checkbox"/>	<input type="checkbox"/>
1.2	Minimize Apache Modules		
1.2.1	Enable only necessary Authentication and Authorization Modules (Not Scored)	<input type="checkbox"/>	<input type="checkbox"/>
1.2.2	Enable the Log Config Module (Scored)	<input type="checkbox"/>	<input type="checkbox"/>
1.2.3	Disable WebDAV Modules (Scored)	<input type="checkbox"/>	<input type="checkbox"/>
1.2.4	Disable Status Module (Scored)	<input type="checkbox"/>	<input type="checkbox"/>
1.2.5	Disable Autoindex Module (Scored)	<input type="checkbox"/>	<input type="checkbox"/>
1.2.6	Disable Proxy Modules (Scored)	<input type="checkbox"/>	<input type="checkbox"/>
1.2.7	Disable User Directories Modules (Scored)	<input type="checkbox"/>	<input type="checkbox"/>
1.2.8	Disable Info Module (Scored)	<input type="checkbox"/>	<input type="checkbox"/>
1.3	Principles, Permissions, and Ownership		
1.3.1	Run the Apache Web Server as a non-root user (Scored)	<input type="checkbox"/>	<input type="checkbox"/>
1.3.2	Give the Apache User Account an Invalid Shell (Scored)	<input type="checkbox"/>	<input type="checkbox"/>
1.3.3	Lock the Apache User Account (Scored)	<input type="checkbox"/>	<input type="checkbox"/>
1.3.4	Set Ownership on Apache Directories and Files (Scored)	<input type="checkbox"/>	<input type="checkbox"/>
1.3.5	Set Group Id on Apache Directories and Files (Scored)	<input type="checkbox"/>	<input type="checkbox"/>
1.3.6	Restrict Other Write Access on Apache Directories and Files (Scored)	<input type="checkbox"/>	<input type="checkbox"/>
1.3.7	Secure Core Dump Directory (Scored)	<input type="checkbox"/>	<input type="checkbox"/>
1.3.8	Secure the Lock File (Scored)	<input type="checkbox"/>	<input type="checkbox"/>
1.3.9	Secure the Pid File (Scored)	<input type="checkbox"/>	<input type="checkbox"/>
1.3.10	Secure the ScoreBoard File (Scored)	<input type="checkbox"/>	<input type="checkbox"/>
1.3.11	Restrict Group Write Access for the Apache Directories and Files (Scored)	<input type="checkbox"/>	<input type="checkbox"/>
1.3.12	Restrict Group Write Access for the Document Root Directories and Files (Scored)	<input type="checkbox"/>	<input type="checkbox"/>
1.4	Apache Access Control		
1.4.1	Deny Access to OS Root Directory (Scored)	<input type="checkbox"/>	<input type="checkbox"/>
1.4.2	Allow Appropriate Access to Web Content (Not Scored)	<input type="checkbox"/>	<input type="checkbox"/>
1.4.3	Restrict Override for the OS Root Directory (Scored)	<input type="checkbox"/>	<input type="checkbox"/>
1.4.4	Restrict Override for All Directories (Scored)	<input type="checkbox"/>	<input type="checkbox"/>
1.5	Minimize Features, Content and Options		
1.5.1	Restrict Options for the OS Root Directory (Scored)	<input type="checkbox"/>	<input type="checkbox"/>
1.5.2	Restrict Options for the Web Root Directory (Scored)	<input type="checkbox"/>	<input type="checkbox"/>
1.5.3	Minimize Options for Other Directories (Scored)	<input type="checkbox"/>	<input type="checkbox"/>

1.5.4	Remove Default HTML Content (Scored)	<input type="checkbox"/>	<input type="checkbox"/>
1.5.5	Remove Default CGI Content printenv (Scored)	<input type="checkbox"/>	<input type="checkbox"/>
1.5.6	Remove Default CGI Content test-cgi (Scored)	<input type="checkbox"/>	<input type="checkbox"/>
1.5.7	Limit HTTP Request Methods (Scored)	<input type="checkbox"/>	<input type="checkbox"/>
1.5.8	Disable HTTP TRACE Method (Scored)	<input type="checkbox"/>	<input type="checkbox"/>
1.5.9	Restrict HTTP Protocol Versions (Scored)	<input type="checkbox"/>	<input type="checkbox"/>
1.5.10	Restrict Access to .ht* files (Scored)	<input type="checkbox"/>	<input type="checkbox"/>
1.5.11	Restrict File Extensions (Scored)	<input type="checkbox"/>	<input type="checkbox"/>
1.5.12	Deny IP Address Based Requests (Scored)	<input type="checkbox"/>	<input type="checkbox"/>
1.5.13	Restrict Listen Directive (Scored)	<input type="checkbox"/>	<input type="checkbox"/>
1.5.14	Restrict Browser Frame Options (Scored)	<input type="checkbox"/>	<input type="checkbox"/>
1.6	Operations - Logging, Monitoring and Maintenance		
1.6.1	Configure the Error Log (Scored)	<input type="checkbox"/>	<input type="checkbox"/>
1.6.2	Configure a Syslog Facility for Error Logging (Scored)	<input type="checkbox"/>	<input type="checkbox"/>
1.6.3	Configure the Access Log (Scored)	<input type="checkbox"/>	<input type="checkbox"/>
1.6.4	Log Storage and Rotation (Scored)	<input type="checkbox"/>	<input type="checkbox"/>
1.6.5	Apply Applicable Patches (Scored)	<input type="checkbox"/>	<input type="checkbox"/>
1.6.6	Install and Enable ModSecurity (Scored)	<input type="checkbox"/>	<input type="checkbox"/>
1.6.7	Install and Enable OWASP ModSecurity Core Rule Set (Scored)	<input type="checkbox"/>	<input type="checkbox"/>
1.7	SSL/TLS Configuration		
1.7.1	Install mod_ssl and/or mod_nss (Scored)	<input type="checkbox"/>	<input type="checkbox"/>
1.7.2	Install a Valid Trusted Certificate (Scored)	<input type="checkbox"/>	<input type="checkbox"/>
1.7.3	Protect the Server's Private Key (Scored)	<input type="checkbox"/>	<input type="checkbox"/>
1.7.4	Disable the SSL v3.0 Protocol (Scored)	<input type="checkbox"/>	<input type="checkbox"/>
1.7.5	Restrict Weak SSL Ciphers (Scored)	<input type="checkbox"/>	<input type="checkbox"/>
1.7.6	Disable SSL Insecure Renegotiation (Scored)	<input type="checkbox"/>	<input type="checkbox"/>
1.7.7	Ensure SSL Compression is not Enabled (Scored)	<input type="checkbox"/>	<input type="checkbox"/>
1.7.8	Disable the TLS v1.0 Protocol (Scored)	<input type="checkbox"/>	<input type="checkbox"/>
1.7.9	Enable OCSP Stapling (Scored)	<input type="checkbox"/>	<input type="checkbox"/>
1.7.10	Enable HTTP Strict Transport Security (Scored)	<input type="checkbox"/>	<input type="checkbox"/>
1.8	Information Leakage		
1.8.1	Set ServerToken to 'Prod' (Scored)	<input type="checkbox"/>	<input type="checkbox"/>
1.8.2	Set ServerSignature to 'Off' (Scored)	<input type="checkbox"/>	<input type="checkbox"/>
1.8.3	Information Leakage via Default Apache Content (Scored)	<input type="checkbox"/>	<input type="checkbox"/>
1.9	Denial of Service Mitigations		
1.9.1	Set Timeout to 10 or less (Scored)	<input type="checkbox"/>	<input type="checkbox"/>
1.9.2	Set the KeepAlive directive to On (Scored)	<input type="checkbox"/>	<input type="checkbox"/>
1.9.3	Set MaxKeepAliveRequests to 100 or greater (Scored)	<input type="checkbox"/>	<input type="checkbox"/>
1.9.4	Set KeepAliveTimeout Low to Mitigate Denial of Service (Scored)	<input type="checkbox"/>	<input type="checkbox"/>
1.9.5	Set Timeout Limits for Request Headers (Scored)	<input type="checkbox"/>	<input type="checkbox"/>
1.9.6	Set Timeout Limits for the Request Body (Scored)	<input type="checkbox"/>	<input type="checkbox"/>

1.10	Request Limits		
1.10.1	Set the LimitRequestLine directive to 512 or less (Scored)	<input type="checkbox"/>	<input type="checkbox"/>
1.10.2	Set the LimitRequestFields directive to 100 or less (Scored)	<input type="checkbox"/>	<input type="checkbox"/>
1.10.3	Set the LimitRequestFieldsize directive to 1024 or less (Scored)	<input type="checkbox"/>	<input type="checkbox"/>
1.10.4	Set the LimitRequestBody directive to 102400 or less (Scored)	<input type="checkbox"/>	<input type="checkbox"/>
1.11	Enable SELinux to Restrict Apache Processes		
1.11.1	Enable SELinux in Enforcing Mode (Scored)	<input type="checkbox"/>	<input type="checkbox"/>
1.11.2	Run Apache Processes in the httpd_t Confined Context (Scored)	<input type="checkbox"/>	<input type="checkbox"/>
1.11.3	Ensure the httpd_t Type is Not in Permissive Mode (Scored)	<input type="checkbox"/>	<input type="checkbox"/>
1.11.4	Ensure Only the Necessary SELinux Booleans are Enabled (Not Scored)	<input type="checkbox"/>	<input type="checkbox"/>
1.12	Enable AppArmor to Restrict Apache Processes		
1.12.1	Enable the AppArmor Framework (Scored)	<input type="checkbox"/>	<input type="checkbox"/>
1.12.2	Customize the Apache AppArmor Profile (Not Scored)	<input type="checkbox"/>	<input type="checkbox"/>
1.12.3	Ensure Apache AppArmor Profile is in Enforce Mode (Scored)	<input type="checkbox"/>	<input type="checkbox"/>

Appendix: Change History

Date	Version	Changes for this version
12-30-2012	1.0.0	Initial Release
12-03-2013	1.1.0	Updated to cover Apache 2.4.6
12-03-2013	1.1.0	Ticket #79: Correct Typos
12-03-2013	1.1.0	Ticket #78: 1.6.3 Establish Log Monitoring
12-03-2013	1.1.0	Ticket #77: 1.6.5 Monitor Vulnerability Lists
12-03-2013	1.1.0	Ticket #76: no recommendation to prevent apache from writing to web root
12-03-2013	1.1.0	Ticket #75: 1.3.4 Set Ownership on Apache Directories and Files
12-05-2014	1.2.0	Ticket #93: Update "Apache Directory and File Permissions" per discussion on unix domain socket file permissions.
12-05-2014	1.2.0	Ticket #87: Update SSL Cipher Recommendations not allow RC4 Apache 2.4
12-05-2014	1.2.0	Ticket #86: Update Protocol Recommendations to Mitigate both POODLE and BEAST Apache 2.4
12-09-2014	1.2.0	Ticket #91: Add recommendation for HTTP Strict Transport Security header BM 2.4

12-09-2014	1.2.0	Ticket #94: Consider adding recommendations for OCSP Stapling
12-10-2014	1.2.0	Ticket #97: Use code block format for UID output information in Recommendation 1.3.1.
12-10-2014	1.2.0	Ticket #96: Consider making Recommendation 1.7.2 "Install a Valid Trusted Certificate" scored.
12-10-2014	1.2.0	Ticket #95: Consider mentioning apachectl or apache2ctl to Overview of Section 1
04-23-2015	1.2.1	Informational update to 1.7.8 Disable the TLS v1.0 Protocol
04-23-2015	1.2.1	Informational update to 1.7.9 Enable HTTP Strict Transport Security
04-23-2015	1.2.1	Ticket #99: Typos in corrections needed in "Enable HTTP Strict Transport Security" 3.4 BM
05-31-2016	1.3.0	Ticket #108: Add recommendations for using AppArmor with Apache
05-31-2016	1.3.0	Ticket #107: Add recommendations for using SELinux in Targeted mode
05-31-2016	1.3.0	Ticket #106: Disable proxy modules
05-31-2016	1.3.0	Ticket #105: Adjust log level configuration to include Not Found Errors
05-31-2016	1.3.0	Ticket #104: Added recommendations for using ModSecurity and the OWASP Core Rule Set
05-31-2016	1.3.0	Ticket #99: Corrected typos in recommendation 3.4

05-31-2016	1.3.0	Ticket #112: Correct SSLStaplingCache in Recommendation 1.7.9
05-31-2016	1.3.0	Ticket #111: Correct TLS1.2 to TLSv1.2 in recommendation 1.7.8
05-31-2016	1.3.0	Ticket #109: Update restrict Weak SSL ciphers to reflect recent issues